According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



TESSAROL PRIMER FOR WOOD white

Version 2.0	Revision Date: 31.01.2024	SDS Number: MAT000477709 GB/EN	Date of last issue: 31.01.2022 Date of first issue: 16.03.2021
		GB/EN	

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Trade name	: TESSAROL PRIMER FOR WOOD white			
Product code	: 47770903			
2 Relevant identified uses of the substance or mixture and uses advised against				

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- stance/Mixture	:	Roller application or brushing, Non industrial spraying Coatings and paints, thinners, paint removers
Recommended restrictions	:	Professional and consumer use of coatings

on use

1.3 Details of the supplier of the safety data sheet

Company	: Helios TBLUS d.o.o. Količevo 65 1230 Domžale Slovenia
Telephone Company	: 386 (1) 722 4383
Telefax Company	: 386 (1) 722 4310
Responsible/issuing person	: 386 (1) 722 4383 productsafety@helios.si

1.4 Emergency telephone number

Call 999 (or 112) for emergency medical attention

professionals only: National Poison Information Service (NPIS) 24h national number 0844 892 0111

consumer: National Health Service (NHS) 24h national number, England & Scotland 111

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



TESSAROL PRIMER FOR WOOD white

Version 2.0 Revision Date: 31.01.2024

SDS Number: MAT000477709 GB/EN Date of last issue: 31.01.2022 Date of first issue: 16.03.2021

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Flammable liquids, Category 3H226: Flammable liquid and vapour.Specific target organ toxicity - single exposure, Category 3, Central nervousH336: May cause drowsiness or dizziness.systemH336: May cause drowsiness or dizziness.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Hazard pictograms Signal word	:	Warning	
Hazard statements	:	H226 H336	Flammable liquid and vapour. May cause drowsiness or dizziness.
Precautionary statements	:	P101 P102	If medical advice is needed, have product con- tainer or label at hand. Keep out of reach of children.
		Prevention	:
		P210 P271	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
			Use only outdoors or in a well-ventilated area.
		Response: P370 + P37	
		Storage: P405	Store locked up.
		Disposal: P501	Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label:

hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics 1-methoxy-2-propanol

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

SDS Number:

GB/EN

MAT000477709



TESSAROL PRIMER FOR WOOD white

Revision Date: 31.01.2024

Date of last issue: 31.01.2022 Date of first issue: 16.03.2021

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics	107-98-2 919-857-5 01-2119463258-33	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) Asp. Tox. 1; H304	>= 10 - < 20
1-methoxypropan-2-ol	203-539-1 603-064-00-3 01-2119457435-35	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system)	>= 1 - < 10
hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics	Not Assigned 918-481-9 01-2119457273-39	Asp. Tox. 1; H304	>= 1 - < 10
strontium bis(2-ethylhexanoate)	219-536-3	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318	>= 0,1 - < 0,3
Substances with a workplace exposure	e limit :		
titanium dioxide	236-675-5 01-2119489379-17		>= 1 - < 10
Limestone	215-279-6 EXEMPTED		>= 1 - < 10
talc	238-877-9 01-2120140278-58		>= 1 - < 10
dolomite	240-440-2		>= 1 - < 10
silicic acid, aluminum sodium salt	215-684-8 01-2119429887-22		>= 1 - < 10

For explanation of abbreviations see section 16.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



TESSAROL PRIMER FOR WOOD white

Version 2.0	Revision Date: 31.01.2024	SDS Number: MAT000477709 GB/EN	Date of last issue: 31.01.2022 Date of first issue: 16.03.2021
----------------	---------------------------	--------------------------------------	---

SECTION 4: First aid measures

4.1 Description of first aid meas	ure	S	
General advice	:	Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.	
If inhaled	:	Consult a physician after significant exposure. If unconscious, place in recovery position and seek medical advice.	
In case of skin contact	:	If on skin, rinse well with water. If on clothes, remove clothes.	
In case of eye contact	:	Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.	
If swallowed	:	Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.	
4.2 Most important symptoms a	nd e	effects, both acute and delayed	
Risks	:	May cause drowsiness or dizziness.	
4.3 Indication of any immediate	meo	dical attention and special treatment needed	
Treatment	:	Treat symptomatically.	
SECTION 5: Firefighting measures			
5.1 Extinguishing media			
Suitable extinguishing media	:	Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical	
Unsuitable extinguishing media	:	High volume water jet	

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-	:	Do not allow run-off from fire fighting to enter drains or water
fighting		courses.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



TESSAROL PRIMER FOR WOOD white

Version 2.0	Revision Date: 31.01.2024	SDS Number: MAT000477709 GB/EN	Date of last issue: 31.01.2022 Date of first issue: 16.03.2021

Hazardous combustion prod-	:	No hazardous combustion products are known
ucts		

5.3 Advice for firefighters

Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus.
Further information	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored sepa- rately in closed containments. Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	 Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions	:	Prevent product from entering drains.
		Prevent further leakage or spillage if safe to do so.
		If the product contaminates rivers and lakes or drains inform
		respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up	:	Contain spillage, and then collect with non-combustible ab-
		sorbent material, (e.g. sand, earth, diatomaceous earth, ver-
		miculite) and place in container for disposal according to local
		/ national regulations (see section 13).

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

: Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
For personal protection see section 8.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



TESSAROL PRIMER FOR WOOD white

Version 2.0	Revision Date: 31.01.2024		Number: 000477709 N	Date of last issue: 31.01.2022 Date of first issue: 16.03.2021
	ice on protection agai and explosion	nst :	plication area. Take precautionar Provide sufficient a Open drum carefu Dispose of rinse w regulations. Do not spray on a Take necessary ac (which might cause	nd drinking should be prohibited in the ap- y measures against static discharges. air exchange and/or exhaust in work rooms. Ily as content may be under pressure. ater in accordance with local and national naked flame or any incandescent material. ction to avoid static electricity discharge e ignition of organic vapours). Keep away hot surfaces and sources of ignition.
Hygiene measures :		Wash hands before breaks and at the end of workday.		
7.2 Con	ditions for safe stora	ge, inc	luding any incomp	atibilities
	uirements for storage as and containers	:	ventilated place. C fully resealed and label precautions.	container tightly closed in a dry and well- containers which are opened must be care- kept upright to prevent leakage. Observe Electrical installations / working materials the technological safety standards.
	her information on sto stability	or- :	No decomposition	if stored and applied as directed.
7.3 Spec	;ific end use(s)			
Spe	cific use(s)	:	For further informa sheet.	ation, refer to the product technical data
			Consult the technic stance/mixture.	cal guidelines for the use of this sub-

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
titanium dioxide	13463-67-7	TWA (inhalable dust)	10 mg/m3	GB EH40
		TWA (Respirable dust)	4 mg/m3	GB EH40
Limestone	1317-65-3	TWA (inhalable dust)	10 mg/m3	GB EH40
		TWA (Respirable dust)	4 mg/m3	GB EH40
Talc	14807-96-6	TWA (Respirable dust)	1 mg/m3	GB EH40
		TWA (Respirable	0,1 mg/m3	2004/37/EC

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



TESSAROL PRIMER FOR WOOD white

Version	Revision Date: 31.01.2024	SDS Number:	Date of last issue: 31.01.2022
2.0		MAT000477709	Date of first issue: 16.03.2021
		GB/EN	

		dust)				
	Further inform	nation: Carcinogens	or mutagens			
1-methoxy-2- propanol	107-98-2	TWA	100 ppm 375 mg/m3	GB EH40		
	Further inform	nation: Can be absor	bed through the skin. The as	signed sub-		
	stances are those for which there are concerns that dermal absorption will					
	lead to syster	lead to systemic toxicity.				
		STEL	150 ppm	GB EH40		
			560 mg/m3			
	Further information: Can be absorbed through the skin. The assigned sub-					
	stances are those for which there are concerns that dermal absorption will					
	lead to systemic toxicity.					
		TWA	100 ppm 375 mg/m3	2000/39/EC		
	Further information: Identifies the possibility of significant uptake through the skin, Indicative					
		STEL	150 ppm 568 mg/m3	2000/39/EC		
	Further information: Identifies the possibility of significant uptake through the skin, Indicative					

Derived No Effect Level (DNEL):

according to Regulation (EC) No. 1907/2006

Substance name	End Use	Exposure routes	Potential health ef- fects	Value
hydrocarbons, C9- C11, n-alkanes, isoal- kanes, cyclic, <2% aromatics	Workers	Inhalation	Long-term systemic effects	1500 mg/m3
	Consumers	Inhalation	Long-term systemic effects	900 mg/m3
	Workers	Dermal	Long-term systemic effects	300 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	300 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	300 mg/kg bw/day
titanium dioxide	Workers	Inhalation	Long-term local ef- fects	10 mg/m3
	Consumers	Oral	Long-term systemic effects	700 mg/kg bw/day
Talc	Workers	Inhalation	Acute systemic ef- fects	2,16 mg/m3
	Workers	Inhalation	Acute local effects	3,6 mg/m3
	Consumers	Inhalation	Acute systemic ef- fects	1,08 mg/m3
	Consumers	Inhalation	Acute local effects	1,8 mg/m3
	Consumers	Dermal	Long-term local ef- fects	2,27 mg/cm2

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



TESSAROL PRIMER FOR WOOD white

Version 2.0	Revision Date: 31.01.2024	SDS Number: MAT000477709 GB/EN	Date of last issue: 31.01.2022 Date of first issue: 16.03.2021
		OD/LIN	

	Workers	Dermal	Long-term local ef- fects	4,54 mg/cm2
	Consumers	Oral	Long-term systemic effects	160 mg/kg bw/day
	Consumers	Oral	Acute systemic ef- fects	160 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	43,2 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	21,6 mg/kg bw/day
silicic acid, aluminum sodium salt	Workers	Inhalation	Long-term local ef- fects	4 mg/m3
1-methoxy-2-propanol	Workers	Inhalation	Long-term systemic effects	369 mg/m3
	Workers	Inhalation	Acute systemic ef- fects	553,5 mg/m3
	Workers	Inhalation	Acute local effects	553,5 mg/m3
	Workers	Inhalation	Long-term systemic effects	43,9 mg/m3
	Workers	Dermal	Long-term systemic effects	183 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	78 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	33 mg/kg bw/day
strontium bis(2- ethylhexanoate)	Workers	Inhalation	Long-term systemic effects	0,730 mg/m3
	Workers	Dermal	Long-term systemic effects	0,410 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	0,180 mg/m3
	Consumers	Dermal	Long-term systemic effects	0,210 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	0,210 mg/kg bw/day

Predicted No Effect Concentration (PNEC):

according to Regulation (EC) No. 1907/2006

	301/2000	
Substance name	Environmental Compartment	Value
titanium dioxide	Soil	100 mg/kg dry weight (d.w.)
	Marine water	0,0184 mg/l
	Fresh water	0,184 mg/l
	Marine sediment	100 mg/kg dry weight (d.w.)
	Fresh water sediment	1000 mg/kg dry weight (d.w.)
	Sewage treatment plant	100 mg/l
	Intermittent use/release	0,193 mg/l

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



TESSAROL PRIMER FOR WOOD white

Talc	Marine water	141,26 mg/l
	Fresh water	597,97 mg/l
	Marine sediment	3,13 mg/kg dry
		weight (d.w.)
	Fresh water sediment	31,33 mg/kg dry
		weight (d.w.)
	Intermittent use/release	597,97 mg/l
1-methoxy-2-propanol	Soil	4,59 mg/kg dry
		weight (d.w.)
	Marine water	1 mg/l
	Fresh water	10 mg/l
	Marine sediment	5,2 mg/kg dry
		weight (d.w.)
	Fresh water sediment	52,3 mg/kg dry
		weight (d.w.)
	Sewage treatment plant	100 mg/l
	Intermittent use/release	100 mg/l
strontium bis(2-ethylhexanoate)	Fresh water	0,360 - 0,440
		mg/l
	Intermittent use/release	0,493 - 0,610
		mg/l
	Marine water	0,036 - 0,040
		mg/l
	Sewage treatment plant	71,7 - 88,52 mg/l
	Fresh water sediment	6,37 - 7,86 mg/kg
		dry weight (d.w.)
	Marine sediment	0,637 - 0,790
		mg/kg dry weight
		(d.w.)
	Soil	1,06 - 1,31 mg/kg
		dry weight (d.w.)

8.2 Exposure controls

Personal protective equipment Eye/face protection	t Equipment should conform to EN 166 Eye wash bottle with pure water Tightly fitting safety goggles
Gloves :	Nitrile rubber (> 0,1 mm; < 60 min); ISO EN374
Remarks :	The suitability for a specific workplace should be discussed with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



TESSAROL PRIMER FOR WOOD white

Version 2.0	Revision Date: 31.01.2024	SDS Number: MAT000477709 GB/EN	Date of last issue: 31.01.2022 Date of first issue: 16.03.2021
Respi	and body protection ratory protection ter type ctive measures	tions under which cuts, abrasion, ar Impervious clothi Choose body pro tration of the dan Use respiratory p tilation is provide exposures are wi Equipment shoul Combined particu Wash thoroughly Avoid contact wit	tection according to the amount and concen- gerous substance at the work place. rotection unless adequate local exhaust ven- d or exposure assessment demonstrates that thin recommended exposure guidelines. d conform to EN 14387 Jates and organic vapour type (A-P)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance Colour Odour Odour Threshold	: : :	liquid in accordance with the product description solvent-like No data available
рН	:	No data available
Flash point	:	43 °C Method: ISO 3679, closed cup
Flammability (solid, gas)	:	Static-accumulating flammable liquid., Combustible Solids
Relative vapour density	:	No data available
Relative density	:	No data available
Density	:	1,222 - 1,346 g/cm3
Solubility(ies) Water solubility Solubility in other solvents	:	insoluble Description: miscible with most organic solvents
Partition coefficient: n- octanol/water	:	No data available
Decomposition temperature	:	No decomposition if stored and applied as directed. Hazardous decomposition products formed under fire condi- tions.
Viscosity Viscosity, kinematic	:	> 20,5 mm2/s (40 °C)

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



TESSAROL PRIMER FOR WOOD white

Version 2.0	Revision Date: 31.01.2024	SDS Number: MAT000477709 GB/EN	Date of last issue: 31.01.2022 Date of first issue: 16.03.2021
----------------	------------------------------	--------------------------------------	---

Flow time	: > 60 s at 23 °C Cross section: 6 mm Method: ISO 2431
Explosive properties	: Not applicable
Oxidizing properties	: Sustains combustion
9.2 Other information No data available VOC	: (Directive 2004/42/EC) 300 g/l

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Incompatible with strong acids and bases.

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information. Not classified due to lack of data.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



TESSAROL PRIMER FOR WOOD white

Components:

components.			
1-methoxy-2-propanol:			
Acute oral toxicity :	LD50 Oral (Rabbit): > 2.000 mg/kg		
Acute dermal toxicity :	LD50 (Rabbit): > 2.000 mg/kg		
hydrocarbons, C10-C13 n-alka	nes, isoalkanes, cyclic, <2% aromatics:		
Acute oral toxicity :	LD50 Oral (Rat, male and female): > 5.000 mg/kg Method: OECD Test Guideline 401		
Acute inhalation toxicity :	LC50 (Rat): > 5.000 mg/l Test atmosphere: vapour Method: OECD Test Guideline 403		
Acute dermal toxicity :	LD50 Dermal (Rabbit, male and female): > 5.000 mg/kg Method: OECD Test Guideline 402		
strontium bis(2-ethylhexanoat	e):		
Acute oral toxicity :			
Limestone:			
Acute inhalation toxicity :	Assessment: The substance or mixture has no acute inhala- tion toxicity		
Skin corrosion/irritation			
Not classified based on available information. Not classified due to lack of data.			
Components:			
hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:			
Species :	Rabbit		
Method : Result :	OECD Test Guideline 404 No skin irritation		
GLP :	yes		
Result :	Repeated exposure may cause skin dryness or cracking.		
strontium bis(2-ethylhexanoate):			
Result :	irritating		
Serious eye damage/eye irritation			
Not classified based on available information.			

Not classified based on available information. Not classified due to lack of data.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



TESSAROL PRIMER FOR WOOD white

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Species	: Rabbit
Method	: OECD Test Guideline 405
Result	: No eye irritation

strontium bis(2-ethylhexanoate):

Result : Corrosive

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Skin sensitisation

Not classified due to lack of data.

Respiratory sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified due to lack of data.

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Exposure routes	: Skin contact
Species	: Guinea pig
Method	: OECD Test Guideline 406
Result	: Not a skin sensitizer.

Germ cell mutagenicity

Not classified based on available information. Not classified due to lack of data.

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Genotoxicity in vitro	:	Result: negative
-----------------------	---	------------------

Genotoxicity in vivo : Result: negative

Carcinogenicity

Not classified based on available information. Not classified due to lack of data.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



TESSAROL PRIMER FOR WOOD white

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics: Result : negative

Reproductive toxicity

Not classified based on available information. Not classified due to lack of data.

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Effects on foetal developmental toxicity tests did not reveal any effect on reproduction.

STOT - single exposure

May cause drowsiness or dizziness. May cause drowsiness or dizziness.

Components:

hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics:

Assessment : May cause drowsiness or dizziness.

1-methoxy-2-propanol:

Assessment : May cause drowsiness or dizziness.

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Remarks : Based on available data, the classification criteria are not met.

STOT - repeated exposure

Not classified based on available information. Not classified due to lack of data.

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics: Remarks : Based on available data, the classification criteria are not met.

Aspiration toxicity

Not classified based on available information. Not classified due to lack of data.

Components:

hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics: May be fatal if swallowed and enters airways.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



TESSAROL PRIMER FOR WOOD white

Version 2.0 Revision Date: 31.01.2024

SDS Number: MAT000477709 GB/EN Date of last issue: 31.01.2022 Date of first issue: 16.03.2021

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics: May be fatal if swallowed and enters airways.

Further information

Remarks

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.
 Concentrations substantially above the TLV value may cause narcotic effects.
 Solvents may degrease the skin.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Toxicity to fish

1-methoxy-2-propanol:

		Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	LC50 (Daphnia (water flea)): > 1.000 mg/l
Toxicity to algae/aquatic plants	:	LC50 (algae): > 1.000 mg/l

: LC50 (Fish): > 1.000 mg/l

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): > 1.000 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	:	EC50 : > 1.000 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	:	NOEC (Pseudokirchneriella subcapitata (microalgae)): 1.000 mg/l Exposure time: 72 h Method: OECD Test Guideline 201 EC50 (Pseudokirchneriella subcapitata (microalgae)): > 1.000 mg/l Exposure time: 72 h Method: OECD Test Guideline 201

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



TESSAROL PRIMER FOR WOOD white

Version	Revi
2.0	31.0

vision Date: 01.2024

SDS Number: MAT000477709 GB/EN Date of last issue: 31.01.2022 Date of first issue: 16.03.2021

12.2 Persistence and degradability

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:				
Biodegradability	:	Result: Readily biodegradable.		
		Biodegradation: 80 %		
		Exposure time: 28 d		
		Method: OECD Test Guideline 301F		

12.3 Bioaccumulative potential

Components:

1-methoxy-2-propanol:		
Partition coefficient: n- octanol/water	:	log Pow: -0,437

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

:

•	•			•			
Assessment	:	Substance	is not pers	sistent, b	bioaccumulative,	and toxic ((PBT).

12.6 Other adverse effects

Product:

Endocrine disrupting poten- tial	:	This substance/mixture does not contain components consid- ered to have endocrine disrupting properties for environment according to UK REACH Article 57(f).
Additional ecological infor- mation	:	No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemi-

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



TESSAROL PRIMER FOR WOOD white

Version 2.0	Revision Date: 31.01.2024	SDS Number MAT0004777 GB/EN	-	Date of last issue Date of first issue	
Conta	minated packaging	Empty Dispos Do no	remaining cor se of as unused t re-use empty	aste management ntents. d product.	

SECTION 14: Transport information

14.1	UN number			
	ADN	:	UN 1263	
	ADR	:	UN 1263	
	RID	:	UN 1263	
	IMDG	:	UN 1263	
	ΙΑΤΑ	:	UN 1263	
14.2	UN proper shipping name			
	ADN	:	PAINT	
	ADR	:	PAINT	
	RID	:	PAINT	
	IMDG	:	PAINT	
	ΙΑΤΑ	:	Paint	
14.3	Transport hazard class(es)			
	• • • • •			
			Class	Subsidiary risks
	ADN	:	Class 3	Subsidiary risks
		:		Subsidiary risks
	ADN		3	Subsidiary risks
	ADN ADR	:	3 3	Subsidiary risks
	ADN ADR RID	:	3 3 3	Subsidiary risks
	ADN ADR RID IMDG	::	3 3 3 3	Subsidiary risks
	ADN ADR RID IMDG IATA	::	3 3 3 3	Subsidiary risks

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



TESSAROL PRIMER FOR WOOD white

	Classification Code Hazard Identification Number Labels Tunnel restriction code	:	F1 30 3 (D/E)
	RID Packing group Classification Code Hazard Identification Number Labels	:	III F1 30 3
	IMDG Packing group Labels EmS Code	:	III 3 F-E, <u>S-E</u>
	IATA (Cargo) Packing instruction (cargo aircraft) Packing instruction (LQ) Packing group Labels	:	366 Y344 III Flammable Liquids
	IATA (Passenger) Packing instruction (passen- ger aircraft) Packing instruction (LQ) Packing group Labels	:	355 Y344 III Flammable Liquids
14.5	Environmental hazards		
	ADN Environmentally hazardous ADR	:	no
	Environmentally hazardous	:	no
	RID Environmentally hazardous	:	no
	IMDG Marine pollutant	:	no
14.6	Special precautions for use	r	
	Remarks	:	ADR: Packages smaller than or equal to 450 litres, not goods/merchandise ofClass 3 (exemption ADR 2.2.3.1.5) IMDG: Packages smaller than or equal to 450 litres, not goods/merchandise ofClass 3; "transport acc. IMDG-code 2.3.2.5"

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



TESSAROL PRIMER FOR WOOD white

Version	
2.0	

Revision Date: 31.01.2024

SDS Number: MAT000477709 GB/EN Date of last issue: 31.01.2022 Date of first issue: 16.03.2021

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17)	:	Conditions of restriction for the fol- lowing entries should be considered: Number on list 3
UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation	:	Not applicable
The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain)	:	Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	:	Not applicable
UK REACH List of substances subject to authorisation (Annex XIV)	:	Not applicable
GB Export and import of hazardous chemicals - Prior Informed Consent (PIC) Regulation	:	Not applicable
Control of Major Accident Hazards Regulations P5c 2015 (COMAH)	FL/	AMMABLE LIQUIDS

Volatile organic compounds : Directive 2004/42/EC

Volatile organic compounds (VOC) content: 300 g/l

Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

SECTION 16: Other information

Full text of H-Statements

H226	:	Flammable liquid and vapour.
H302	:	Harmful if swallowed.
H304	:	May be fatal if swallowed and enters airways.
H315	:	Causes skin irritation.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



TESSAROL PRIMER FOR WOOD white

H318	:	Causes serious eye damage.
H336	:	May cause drowsiness or dizziness.
Full text of other abbreviat	ions	
Acute Tox.	:	Acute toxicity
Asp. Tox.	:	Aspiration hazard
Eye Dam.	:	Serious eye damage
Flam. Liq.	:	Flammable liquids
Repr.	:	Reproductive toxicity
Skin Irrit.	:	Skin irritation
STOT SE	:	Specific target organ toxicity - single exposure
2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2004/37/EC	:	Europe. Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens or mutagens at work
GB EH40	:	UK. EH40 WEL - Workplace Exposure Limits
2000/39/EC / TWA	:	Limit Value - eight hours
2000/39/EC / STEL	:	Short term exposure limit
2004/37/EC / TWA	:	Long term exposure limit
GB EH40 / TWA	:	Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	:	Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA -European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance: PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet;

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



TESSAROL PRIMER FOR WOOD white

 Revision Date: 31.01.2024	SDS Number: MAT000477709 GB/EN	Date of last issue: 31.01.2022 Date of first issue: 16.03.2021
	00/211	

SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information	ı	
Classification of the	e mixture:	Classification procedure:
Flam. Liq. 3	H226	Based on product data or assessment
STOT SE 3	H336	Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.