according to Regulation (EC) No. 1907/2006

IDEAL tool cleaning agent DS



Version Revision Date: SDS Number: Date of last issue: -

1.0 16.04.2021 MAT000470599 Date of first issue: 16.04.2021

GB/EN

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product code : 47059902

Trade name : IDEAL tool cleaning agent DS

Unique Formula Identifier

(UFI)

: 1771-U0ND-A00P-6P6X

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Professional and consumer use of coatings

stance/Mixture PC9a Coatings and paints, thinners, paint removers

1.3 Details of the supplier of the safety data sheet

Company : Helios TBLUS d.o.o.

Količevo 65 1230 Domžale Slovenia

Telephone Company : 386 (1) 722 4383

Telefax Company : 386 (1) 722 4310

Responsible/issuing person : 386 (1) 722 4383

productsafety@helios.si

1.4 Emergency telephone number

Call 999 for emergency medical attention

professionals only: National Poison Information Service (NPIS) 24h national number 0844 892

0111

consumer: National Health Service (NHS) 24h national number, England & Scotland 111

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 Specific target organ toxicity - single ex-

posure, Category 3, Central nervous

system

H226: Flammable liquid and vapour. H336: May cause drowsiness or dizziness.

according to Regulation (EC) No. 1907/2006

IDEAL tool cleaning agent DS



Version Revision Date: SDS Number:

1.0 16.04.2021 MAT000470599 Date of first issue: 16.04.2021

GB / EN

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms

Signal word : Warning

Hazard statements : H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

Precautionary statements : P101 If medical advice is needed, have product container or

label at hand.

P102 Keep out of reach of children.

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open

Date of last issue: -

flames and other ignition sources. No smoking.

P271 Use only outdoors or in a well-ventilated area.

Response:

P370 + P378 In case of fire: Use dry sand, dry chemical or

alcohol-resistant foam to extinguish.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

Hazardous components which must be listed on the label:

2-methoxy-1-methylethyl acetate

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006

IDEAL tool cleaning agent DS



Version Revision Date: SDS Number: Date of last issue: -

1.0 16.04.2021 MAT000470599 Date of first issue: 16.04.2021

GB/EN

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Oomponents			1
Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Index-No.		
	Registration number		
2-methoxy-1-methylethyl acetate	108-65-6	Flam. Liq. 3; H226	>= 90 - <= 100
	203-603-9	STOT SE 3; H336	
	607-195-00-7	(Central nervous	
	01-2119475791-29	system)	
2-methoxypropyl acetate	70657-70-4	Flam. Liq. 3; H226	>= 0,1 - < 0,3
	274-724-2	Repr. 1B; H360D	
	607-251-00-0	STOT SE 3; H335	
	01-2119475791-29	(Respiratory system)	

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : Consult a physician after significant exposure.

If unconscious, place in recovery position and seek medical

advice.

In case of skin contact : If on skin, rinse well with water.

If on clothes, remove clothes.

In case of eye contact : Flush eyes with water as a precaution.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

Risks : May cause drowsiness or dizziness.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

according to Regulation (EC) No. 1907/2006

IDEAL tool cleaning agent DS



Version 1.0

Revision Date: 16.04.2021

SDS Number: MAT000470599

GB / EN

Date of last issue: -

Date of first issue: 16.04.2021

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media :

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion prod- : No hazardous combustion products are known

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

For safety reasons in case of fire, cans should be stored sepa-

rately in closed containments.

Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.2 Environmental precautions

6.3 Methods and material for containment and cleaning up

6.4 Reference to other sections

For disposal considerations see section 13., For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid formation of aerosol. Advice on safe handling

Do not breathe vapours/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes.

according to Regulation (EC) No. 1907/2006

IDEAL tool cleaning agent DS



Version Revision Date: SDS Number: Date of last issue: -

1.0 16.04.2021 MAT000470599 Date of first issue: 16.04.2021

GB / EN

For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national

regulations.

Advice on protection against

fire and explosion

Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : Consult the technical guidelines for the use of this sub-

stance/mixture.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
2-methoxy-1- methylethyl ace- tate	108-65-6	STEL	100 ppm 550 mg/m3	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	50 ppm 275 mg/m3	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	50 ppm 274 mg/m3	GB EH40
	stances are th	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will ead to systemic toxicity.		

according to Regulation (EC) No. 1907/2006

IDEAL tool cleaning agent DS



Version Revision Date: SDS Number: Date of last issue: -

1.0 16.04.2021 MAT000470599 Date of first issue: 16.04.2021

GB / EN

	STEL	100 ppm 548 mg/m3	GB EH40
Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
2-methoxy-1- methylethyl acetate	Workers	Inhalation	Long-term systemic effects	275 mg/m3
	Workers	Inhalation	Acute local effects	550 mg/m3
	Consumers	Inhalation	Long-term systemic effects	33 mg/m3
	Consumers	Inhalation	Long-term local ef- fects	33 mg/m3
	Workers	Dermal	Long-term systemic effects	796 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	320 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	36 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
2-methoxy-1-methylethyl acetate	Soil	0,29 mg/kg dry
		weight (d.w.)
	Marine water	0,0635 mg/l
	Fresh water	0,635 mg/l
	Marine sediment	0,329 mg/kg dry
		weight (d.w.)
	Fresh water sediment	3,29 mg/kg dry
		weight (d.w.)
	Sewage treatment plant	100 mg/l
	Intermittent use/release	0,00635 mg/l

8.2 Exposure controls

Personal protective equipment

Respiratory protection : Wear a full face respirator conforming to EN136 with Type

A/P2 filter or better.

Self-contained closed-circuit breathing apparatus com-

pressed (EN 145)

In the case of aerosol and mist formation use an approved

respirator filter (EN 141).

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid

Colour : in accordance with the product description

Odour : solvent-like

according to Regulation (EC) No. 1907/2006

IDEAL tool cleaning agent DS



Version 1.0

Revision Date:

16.04.2021

SDS Number:

GB / EN

MAT000470599

Date of last issue: -

Date of first issue: 16.04.2021

Odour Threshold

No data available

Melting point/freezing point

< 87 °C

(calculation method (principal components, lowest value))

Boiling point/boiling range

146 °C (calculation method (principal components, lowest

value))

Upper explosion limit / Upper

flammability limit

7 %(V) (calculation method (principal components, highest

Lower explosion limit / Lower

flammability limit

1,5 %(V) (calculation method (principal components, highest

value))

46 °C

Flash point

Ignition temperature

315 °C (calculation method (principal components, highest

value))

Decomposition temperature

Decomposition temperature

No decomposition if stored and applied as directed.

Hazardous decomposition products formed under fire condi-

tions.

рΗ No data available

Viscosity

Viscosity, kinematic < 20,5 mm2/s (40 °C)

Solubility(ies)

immiscible, partly soluble Water solubility

Solubility in other solvents Description: miscible with most organic solvents

Partition coefficient: n-

octanol/water

Relative density

log Pow: 1,2 (calculation method (principal components, high-

est value)) (20 °C)

pH: 6,8

Vapour pressure 4,9 hPa (calculation method (principal components, highest

> value)) (20 °C)

0,97 (calculation method (principal components, highest val-

ue))

0,964 g/cm3 Density

Relative vapour density 4,6 (calculation method (principal components, lowest value))

according to Regulation (EC) No. 1907/2006



IDEAL tool cleaning agent DS

Version Revision Date: SDS Number: Date of last issue: -

1.0 16.04.2021 MAT000470599 Date of first issue: 16.04.2021

GB / EN

(Air = 1.0)

9.2 Other information

Oxidizing properties : Sustains combustion

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Strong oxidizing agents

10.6 Hazardous decomposition products

Adequate ventilation is required.

Heating can release vapours which can be ignited.

Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Components:

2-methoxy-1-methylethyl acetate:

Acute oral toxicity : LD50 Oral (Rat): > > 2.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l

Test atmosphere: vapour

LC0 (Rat): 2000 ppm Exposure time: 3 h

according to Regulation (EC) No. 1907/2006



IDEAL tool cleaning agent DS

Version Revision Date: SDS Number: Date of last issue: -

1.0 16.04.2021 MAT000470599 Date of first issue: 16.04.2021

GB / EN

Acute dermal toxicity : LD50 (Rabbit): > > 2.000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

Components:

2-methoxypropyl acetate:

Reproductive toxicity - As- : Clear evidence of adverse effects on sexual function and fertil-

sessment ity, and/or on development, based on animal experiments

STOT - single exposure

May cause drowsiness or dizziness.

Components:

2-methoxy-1-methylethyl acetate:

Assessment : May cause drowsiness or dizziness.

2-methoxypropyl acetate:

Assessment : May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

according to Regulation (EC) No. 1907/2006

HELIOS

IDEAL tool cleaning agent DS

Version Revision Date: SDS Number: Date of last issue: -

1.0 16.04.2021 MAT000470599 Date of first issue: 16.04.2021

GB/EN

Assessment The substance/mixture does not contain components consid-

> ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

Further information

Product:

Remarks Symptoms of overexposure may be headache, dizziness,

tiredness, nausea and vomiting.

Concentrations substantially above the TLV value may cause

narcotic effects.

Solvents may degrease the skin.

SECTION 12: Ecological information

12.1 Toxicity

Components:

2-methoxy-1-methylethyl acetate:

Toxicity to fish LC50 (Oncorhynchus mykiss (rainbow trout)): 130 mg/l

Exposure time: 96 h

NOEC: 100 mg/l Exposure time: 96 h

Toxicity to daphnia and other : LC50: 408 mg/l

aquatic invertebrates

Exposure time: 48 h

Toxicity to fish (Chronic tox- : EC10: 47,5 mg/l

icity)

12.2 Persistence and degradability

Components:

2-methoxy-1-methylethyl acetate:

Biodegradability Readily biodegradable.

12.3 Bioaccumulative potential

Components:

2-methoxy-1-methylethyl acetate:

Partition coefficient: n-: log Pow: 1,2 (20 °C)

octanol/water pH: 6,8

12.4 Mobility in soil

No data available

according to Regulation (EC) No. 1907/2006

IDEAL tool cleaning agent DS



Version Revision Date: SDS Number: Date of last issue: -

1.0 16.04.2021 MAT000470599 Date of first issue: 16.04.2021

GB/EN

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological infor-

mation

: No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of as hazardous waste in compliance with local and

national regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

Waste Code : 08 01 11, waste paint and varnish containing organic solvents

or other hazardous substances

SECTION 14: Transport information

14.1 UN number or ID number

ADN : UN 1263
ADR : UN 1263
RID : UN 1263
IMDG : UN 1263
IATA : UN 1263

14.2 UN proper shipping name

according to Regulation (EC) No. 1907/2006



IDEAL tool cleaning agent DS

Version Revision Date: SDS Number: Date of last issue: -

1.0 16.04.2021 MAT000470599 Date of first issue: 16.04.2021

GB/EN

ADN PAINT RELATED MATERIAL **ADR** PAINT RELATED MATERIAL RID PAINT RELATED MATERIAL **IMDG** PAINT RELATED MATERIAL

IATA Paint related material

14.3 Transport hazard class(es)

ADN 3 **ADR** 3 RID 3 **IMDG** 3 IATA 3

14.4 Packing group

ADN

Ш Packing group Classification Code F1 Hazard Identification Number : 30 Labels 3

ADR

Ш Packing group Classification Code F1 Hazard Identification Number : 30 Labels 3 Tunnel restriction code (D/E)

RID

Packing group Ш Classification Code F1 Hazard Identification Number : 30 Labels 3

IMDG

Packing group Ш Labels

EmS Code F-E, <u>S-E</u>

IATA (Cargo)

Packing instruction (cargo 366

aircraft)

Packing instruction (LQ) Y344 Packing group Ш

Flammable Liquids Labels

IATA (Passenger)

Packing instruction (passen-355

ger aircraft)

Packing instruction (LQ) Y344 Packing group Ш

according to Regulation (EC) No. 1907/2006



IDEAL tool cleaning agent DS

Version **Revision Date:** SDS Number: Date of last issue: -

16.04.2021 MAT000470599 Date of first issue: 16.04.2021 1.0

GB / EN

Labels Flammable Liquids

14.5 Environmental hazards

ADN

Environmentally hazardous no

Environmentally hazardous no

Environmentally hazardous no

IMDG

Marine pollutant no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances. preparations and articles (Annex XVII)

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import

of dangerous chemicals

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

REACH - List of substances subject to authorisation

(Annex XIV)

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Conditions of restriction for the following entries should be considered:

Number on list 3 Not applicable

Not applicable

Not applicable

Not applicable

Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P5c FLAMMABLE LIQUIDS

Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

according to Regulation (EC) No. 1907/2006

IDEAL tool cleaning agent DS



Version Revision Date: SDS Number: Date of last issue: -

1.0 16.04.2021 MAT000470599 Date of first issue: 16.04.2021

GB / EN

15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

SECTION 16: Other information

Full text of H-Statements

H226 : Flammable liquid and vapour.
H335 : May cause respiratory irritation.
H336 : May cause drowsiness or dizziness.
H360D : May damage the unborn child.

Full text of other abbreviations

Flam. Liq. : Flammable liquids Repr. : Reproductive toxicity

STOT SE : Specific target organ toxicity - single exposure

2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first

list of indicative occupational exposure limit values

GB EH40 : UK. EH40 WEL - Workplace Exposure Limits

2000/39/EC / TWA : Limit Value - eight hours 2000/39/EC / STEL : Short term exposure limit

GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS -Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP -Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL -International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail: SADT - Self-Accelerating Decomposition Temperature: SDS - Safety Data Sheet: SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS -

according to Regulation (EC) No. 1907/2006

IDEAL tool cleaning agent DS



Version Revision Date: SDS Number: Date of last issue: -

1.0 16.04.2021 MAT000470599 Date of first issue: 16.04.2021

GB / EN

Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture: Classification procedure:

Flam. Liq. 3 H226 Based on product data or assessment

STOT SE 3 H336 Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.