according to Regulation (EC) No. 1907/2006



## TESSAROL ENAMEL FOR RADIATORS white

Version Revision Date: SDS Number: Date of last issue: -

1.0 18.01.2021 MAT000409301 Date of first issue: 18.01.2021

GB / EN

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product code : 40930113

Trade name : TESSAROL ENAMEL FOR RADIATORS white

Unique Formula Identifier

(UFI)

: AC61-S0RE-800R-K8D9

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : SU19 Building and construction work

stance/Mixture Professional and consumer use of coatings, Roller application

or brushing, Non industrial spraying

PC9a Coatings and paints, thinners, paint removers

1.3 Details of the supplier of the safety data sheet

Company : Helios TBLUS d.o.o.

Količevo 65 1230 Domžale Slovenia

Telephone Company : 386 (1) 722 4383

Telefax Company : 386 (1) 722 4310

Responsible/issuing person : 386 (1) 722 4383

productsafety@helios.si

1.4 Emergency telephone number

Call 999 for emergency medical attention

professionals only: National Poison Information Service (NPIS) 24h national number 0844 892

0111

consumer: National Health Service (NHS) 24h national number, England & Scotland 111

## **SECTION 2: Hazards identification**

## 2.1 Classification of the substance or mixture

### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 H226: Flammable liquid and vapour.

Specific target organ toxicity - single ex- H336: May cause drowsiness or dizziness.

posure, Category 3, Central nervous

according to Regulation (EC) No. 1907/2006



# **TESSAROL ENAMEL FOR RADIATORS white**

Version Revision Date: SDS Number: Date of last issue: -

1.0 18.01.2021 MAT000409301 Date of first issue: 18.01.2021

GB/EN

system

#### 2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :

Signal word : Warning

Hazard statements : H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

Precautionary statements : P101 If medical advice is needed, have product container or

label at hand.

P102 Keep out of reach of children.

**Prevention:** 

P210 Keep away from heat, hot surfaces, sparks, open

flames and other ignition sources. No smoking.

P271 Use only outdoors or in a well-ventilated area.

Response:

P370 + P378 In case of fire: Use dry sand, dry chemical or

alcohol-resistant foam to extinguish.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

Hazardous components which must be listed on the label:

hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics 1-methoxy-2-propanol

**Additional Labelling** 

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not

breathe spray or mist.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006



## **TESSAROL ENAMEL FOR RADIATORS white**

Version Revision Date: SDS Number: Date of last issue: -

1.0 18.01.2021 MAT000409301 Date of first issue: 18.01.2021

GB / EN

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## **SECTION 3: Composition/information on ingredients**

### 3.2 Mixtures

Components

Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Index-No.		
	Registration number		
hydrocarbons, C9-C11, n-alkanes,	64742-48-9	Flam. Liq. 3; H226	>= 30 - < 50
isoalkanes, cyclic, <2% aromatics	919-857-5	STOT SE 3; H336	
	01-2119463258-33	(Central nervous	
		system)	
		Asp. Tox. 1; H304	
titanium dioxide	13463-67-7	Carc. 2; H351	>= 20 - < 30
	236-675-5		
	01-2119489379-17		
1-methoxy-2-propanol	107-98-2	Flam. Liq. 3; H226	>= 1 - < 10
	203-539-1	STOT SE 3; H336	
	603-064-00-3	(Central nervous	
	01-2119457435-35	system)	
strontium bis(2-ethylhexanoate)	2457-02-5	Skin Irrit. 2; H315	>= 0,1 - < 1
	219-536-3	Eye Dam. 1; H318	
		Repr. 2; H361d	
		Asp. Tox. 1; H304	

### **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : Consult a physician after significant exposure.

If unconscious, place in recovery position and seek medical

advice.

In case of skin contact : If on skin, rinse well with water.

If on clothes, remove clothes.

In case of eye contact : Flush eyes with water as a precaution.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

according to Regulation (EC) No. 1907/2006



## TESSAROL ENAMEL FOR RADIATORS white

Version Revision Date: SDS Number: Date of last issue: -

1.0 18.01.2021 MAT000409301 Date of first issue: 18.01.2021

GB/EN

If swallowed Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

Risks May cause drowsiness or dizziness.

4.3 Indication of any immediate medical attention and special treatment needed

**Treatment** : Treat symptomatically.

**SECTION 5: Firefighting measures** 

5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

ucts

Hazardous combustion prod- : No hazardous combustion products are known

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

For safety reasons in case of fire, cans should be stored sepa-

rately in closed containments.

Use a water spray to cool fully closed containers.

**SECTION 6: Accidental release measures** 

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions Remove all sources of ignition.

Evacuate personnel to safe areas.

according to Regulation (EC) No. 1907/2006



## **TESSAROL ENAMEL FOR RADIATORS white**

Version Revision Date: SDS Number: Date of last issue: -

1.0 18.01.2021 MAT000409301 Date of first issue: 18.01.2021

GB / EN

Beware of vapours accumulating to form explosive concentra-

tions. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible ab-

sorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local

/ national regulations (see section 13).

6.4 Reference to other sections

For disposal considerations see section 13., For personal protection see section 8.

**SECTION 7: Handling and storage** 

7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol.

Do not breathe vapours/dust.

Avoid exposure - obtain special instructions before use.

For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national

regulations.

Advice on protection against

fire and explosion

Do not spray on a naked flame or any incandescent material.

Take necessary action to avoid static electricity discharge

(which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: No smoking. Keep container tightly closed in a dry and wellventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe

label precautions. Electrical installations / working materials must comply with the technological safety standards.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

7.3 Specific end use(s)

according to Regulation (EC) No. 1907/2006



# **TESSAROL ENAMEL FOR RADIATORS white**

Version Revision Date: SDS Number: Date of last issue: -

1.0 18.01.2021 MAT000409301 Date of first issue: 18.01.2021

GB / EN

Specific use(s) : For further information, refer to the product technical data

sheet.

## **SECTION 8: Exposure controls/personal protection**

## 8.1 Control parameters

## **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
titanium dioxide	13463-67-7	TWA (inhalable dust)	10 mg/m3	GB EH40
		TWA (Respirable dust)	4 mg/m3	GB EH40
barium sulphate, natural	7727-43-7	TWA (inhalable dust)	10 mg/m3	GB EH40
		TWA (Respirable dust)	4 mg/m3	GB EH40
1-methoxy-2- propanol	107-98-2	TWA	100 ppm 375 mg/m3	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	150 ppm 568 mg/m3	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	100 ppm 375 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	150 ppm 560 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			

## Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

	` '	•	` '	
Substance name	End Use	Exposure routes	Potential health effects	Value
titanium dioxide	Workers	Inhalation	Long-term local ef- fects	10 mg/m3
	Consumers	Oral	Long-term systemic effects	700 mg/kg bw/day
barium sulphate, nat- ural	Consumers	Inhalation	Long-term systemic effects	10 mg/m3
	Workers	Inhalation	Long-term systemic effects	10 mg/m3
	Consumers	Oral	Long-term systemic effects	13000 mg/kg bw/day

according to Regulation (EC) No. 1907/2006



# **TESSAROL ENAMEL FOR RADIATORS white**

Version Revision Date: SDS Number: Date of last issue: -

1.0 18.01.2021 MAT000409301 Date of first issue: 18.01.2021

GB / EN

1-methoxy-2-propanol	Workers	Inhalation	Long-term systemic effects	369 mg/m3
	Workers	Inhalation	Acute systemic ef- fects	553,5 mg/m3
	Workers	Inhalation	Acute local effects	553,5 mg/m3
	Workers	Inhalation	Long-term systemic effects	43,9 mg/m3
	Workers	Dermal	Long-term systemic effects	183 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	78 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	33 mg/kg bw/day
strontium bis(2- ethylhexanoate)	Workers	Inhalation	Long-term systemic effects	0,730 mg/m3
	Workers	Dermal	Long-term systemic effects	0,410 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	0,180 mg/m3
	Consumers	Dermal	Long-term systemic effects	0,210 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	0,210 mg/kg bw/day

# Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
titanium dioxide	Soil	100 mg/kg dry
		weight (d.w.)
	Marine water	0,0184 mg/l
	Fresh water	0,184 mg/l
	Marine sediment	100 mg/kg dry
		weight (d.w.)
	Fresh water sediment	1000 mg/kg dry
		weight (d.w.)
	Sewage treatment plant	100 mg/l
	Intermittent use/release	0,193 mg/l
barium sulphate, natural	Soil	207,7 mg/kg dry
·		weight (d.w.)
	Fresh water	0,115 mg/l
	Fresh water sediment	600,4 mg/kg dry
		weight (d.w.)
	Sewage treatment plant	62,2 mg/l
1-methoxy-2-propanol	Soil	4,59 mg/kg dry
		weight (d.w.)
	Marine water	1 mg/l
	Fresh water	10 mg/l
	Marine sediment	5,2 mg/kg dry
		weight (d.w.)
	Fresh water sediment	52,3 mg/kg dry
		weight (d.w.)
	Sewage treatment plant	100 mg/l
	Intermittent use/release	100 mg/l

according to Regulation (EC) No. 1907/2006



## TESSAROL ENAMEL FOR RADIATORS white

Version Revision Date: SDS Number: Date of last issue: -

1.0 18.01.2021 MAT000409301 Date of first issue: 18.01.2021

GB / EN

strontium bis(2-ethylhexanoate)	Fresh water	0,360 - 0,440 mg/l
	Intermittent use/release	0,493 - 0,610 mg/l
	Marine water	0,036 - 0,040 mg/l
	Sewage treatment plant	71,7 - 88,52 mg/l
	Fresh water sediment	6,37 - 7,86 mg/kg dry weight (d.w.)
	Marine sediment	0,637 - 0,790 mg/kg dry weight (d.w.)
	Soil	1,06 - 1,31 mg/kg dry weight (d.w.)

### 8.2 Exposure controls

#### Personal protective equipment

Eye protection

Hand protection

: Safety glasses with side-shields conforming to EN166

Directive : Equipment should conform to EN 374

Material : Viton®
Rate of permeability : > 480 min
Protective index : Class 6

Material : PVA
Rate of permeability : > 480 min
Protective index : Class 6

Glove thickness : > 0,5 mm

Remarks : The choice of an appropriate glove does not only depend on

its material but also on other quality features and is different

from one producer to the other.

The obtained break through times according to EN 374 Part III are not measured under normal operating conditions. Therefore a maximum usage time of 50% of the break through time is recommended. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Nitrile gloves are not suitable. Take note of the information given by the producer concerning permeability, degradation and break through times, and of

Skin and body protection : Long sleeved clothing

Safety shoes

special work

Respiratory protection : No personal respiratory protective equipment normally re-

quired.

Protective measures : Wash thoroughly after handling.

Avoid contact with skin, eyes and clothing.

Keep away from food, drink and animal feedingstuffs.

according to Regulation (EC) No. 1907/2006



## TESSAROL ENAMEL FOR RADIATORS white

Version Revision Date: SDS Number: Date of last issue: -

1.0 18.01.2021 MAT000409301 Date of first issue: 18.01.2021

GB / EN

## **SECTION 9: Physical and chemical properties**

9.1 Information on basic physical and chemical properties

Physical state : liquid

Colour : in accordance with the product description

Odour : solvent-like
Odour Threshold : No data available

Melting point/freezing point : 1.580,0 °C

(calculation method (principal components, lowest value))

Flammability : Static-accumulating flammable liquid., Combustible Solids

Upper explosion limit / Upper

flammability limit

6 %(V) (calculation method (principal components, highest

value))

Lower explosion limit / Lower

flammability limit

0,7 %(V) (calculation method (principal components, highest

value))

Flash point : 34 °C

Decomposition temperature

Decomposition temperature : No decomposition if stored and applied as directed.

Hazardous decomposition products formed under fire condi-

tions.

pH : No data available

Viscosity

Viscosity, kinematic : > 20,5 mm2/s (40 °C)

Flow time : > 60 s at 23 °C

Cross section: 6 mm Method: ISO 2431

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : Description: miscible with most organic solvents

Partition coefficient: n-

octanol/water

No data available

Density : 1,1 - 1,15 g/cm3

9.2 Other information

Explosives : Not applicable

Oxidizing properties : Sustains combustion

VOC : (Directive 2004/42/EC)

according to Regulation (EC) No. 1907/2006



## TESSAROL ENAMEL FOR RADIATORS white

Version Revision Date: SDS Number: Date of last issue: -

1.0 18.01.2021 MAT000409301 Date of first issue: 18.01.2021

GB / EN

500 g/l

## **SECTION 10: Stability and reactivity**

## 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

#### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

#### 10.5 Incompatible materials

Materials to avoid : Strong oxidizing agents

#### 10.6 Hazardous decomposition products

Adequate ventilation is required.

Heating can release vapours which can be ignited.

Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

## **SECTION 11: Toxicological information**

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

### **Acute toxicity**

Not classified based on available information.

## **Components:**

### hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics:

Acute oral toxicity : LD50 Oral (Rat): > 2.000 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg

1-methoxy-2-propanol:

Acute oral toxicity : LD50 Oral (Rabbit): > 2.000 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg

#### Skin corrosion/irritation

Not classified based on available information.

according to Regulation (EC) No. 1907/2006



## **TESSAROL ENAMEL FOR RADIATORS white**

Version Revision Date: SDS Number: Date of last issue: -

1.0 18.01.2021 MAT000409301 Date of first issue: 18.01.2021

GB/EN

#### **Components:**

#### strontium bis(2-ethylhexanoate):

Result : irritating

### Serious eye damage/eye irritation

Not classified based on available information.

### **Components:**

## strontium bis(2-ethylhexanoate):

Result : Corrosive

### Respiratory or skin sensitisation

#### Skin sensitisation

Not classified based on available information.

## Respiratory sensitisation

Not classified based on available information.

### Germ cell mutagenicity

Not classified based on available information.

## Carcinogenicity

Not classified based on available information.

#### Reproductive toxicity

Not classified based on available information.

### **Components:**

### strontium bis(2-ethylhexanoate):

Reproductive toxicity - As- : Some evidence of adverse effects on development, based on

sessment animal experiments.

#### STOT - single exposure

May cause drowsiness or dizziness.

#### **Components:**

#### hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics:

Assessment : May cause drowsiness or dizziness.

1-methoxy-2-propanol:

Assessment : May cause drowsiness or dizziness.

## STOT - repeated exposure

Not classified based on available information.

#### **Aspiration toxicity**

Not classified based on available information.

according to Regulation (EC) No. 1907/2006



# TESSAROL ENAMEL FOR RADIATORS white

Version Revision Date: SDS Number: Date of last issue: -

1.0 18.01.2021 MAT000409301 Date of first issue: 18.01.2021

GB/EN

#### **Components:**

#### hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics:

May be fatal if swallowed and enters airways.

### strontium bis(2-ethylhexanoate):

May be fatal if swallowed and enters airways.

#### 11.2 Information on other hazards

### **Endocrine disrupting properties**

**Product:** 

Assessment : The substance/mixture does not contain components consid-

> ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

**Further information** 

**Product:** 

Remarks Symptoms of overexposure may be headache, dizziness,

tiredness, nausea and vomiting.

Concentrations substantially above the TLV value may cause

narcotic effects.

Solvents may degrease the skin.

## **SECTION 12: Ecological information**

### 12.1 Toxicity

#### Components:

hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics:

Toxicity to fish LC50 (Fish): > 1.000 mg/l

Exposure time: 96 h

Toxicity to daphnia and other : LC50 (Daphnia (water flea)): > 1.000 mg/l

aquatic invertebrates

1-methoxy-2-propanol:

Toxicity to fish : LC50 (Fish): > 1.000 mg/l

Exposure time: 96 h

Toxicity to daphnia and other : LC50 (Daphnia (water flea)): > 1.000 mg/l

aquatic invertebrates

Toxicity to algae/aquatic

: LC50 (algae): > 1.000 mg/l

plants

according to Regulation (EC) No. 1907/2006



## TESSAROL ENAMEL FOR RADIATORS white

Version Revision Date: SDS Number: Date of last issue: -

1.0 18.01.2021 MAT000409301 Date of first issue: 18.01.2021

GB/EN

## 12.2 Persistence and degradability

No data available

#### 12.3 Bioaccumulative potential

#### **Components:**

### 1-methoxy-2-propanol:

Partition coefficient: n-

octanol/water

log Pow: -0,437

## 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### **Product:**

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

### 12.6 Endocrine disrupting properties

### **Product:**

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

### 12.7 Other adverse effects

#### **Product:**

Additional ecological infor-

: No data available

mation

## **SECTION 13: Disposal considerations**

### 13.1 Waste treatment methods

Product : Dispose of as hazardous waste in compliance with local and

national regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

Waste Code : 08 01 11, waste paint and varnish containing organic solvents

or other hazardous substances

according to Regulation (EC) No. 1907/2006



## **TESSAROL ENAMEL FOR RADIATORS white**

Version Revision Date: SDS Number: Date of last issue: -

1.0 18.01.2021 MAT000409301 Date of first issue: 18.01.2021

GB / EN

## **SECTION 14: Transport information**

#### 14.1 UN number or ID number

ADN : UN 1263
ADR : UN 1263
RID : UN 1263
IMDG : UN 1263
IATA : UN 1263

## 14.2 UN proper shipping name

ADN : PAINT
ADR : PAINT
RID : PAINT
IMDG : PAINT
IATA : Paint

## 14.3 Transport hazard class(es)

ADN : 3
ADR : 3
RID : 3
IMDG : 3
IATA : 3

## 14.4 Packing group

## ADN

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

### **ADR**

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3
Tunnel restriction code : (D/E)

### RID

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

#### **IMDG**

Packing group : III Labels : 3

according to Regulation (EC) No. 1907/2006



# **TESSAROL ENAMEL FOR RADIATORS white**

Version Revision Date: SDS Number: Date of last issue: -

1.0 18.01.2021 MAT000409301 Date of first issue: 18.01.2021

GB / EN

EmS Code : F-E, <u>S-E</u>

IATA (Cargo)

Packing instruction (cargo : 366

aircraft)

Packing instruction (LQ) : Y344
Packing group : III

Labels : Flammable Liquids

IATA (Passenger)

Packing instruction (passen- : 355

ger aircraft)

Packing instruction (LQ) : Y344
Packing group : III

Labels : Flammable Liquids

14.5 Environmental hazards

**ADN** 

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

**IMDG** 

Marine pollutant : no

14.6 Special precautions for user

Remarks : ADR: Packages smaller than or equal to 450 litres, not

goods/merchandise of Class 3 (exemption ADR 2.2.3.1.5) IMDG: Packages smaller than or equal to 450 litres, not

goods/merchandise of Class 3

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

**SECTION 15: Regulatory information** 

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

preparations and articles (Annex XVII)

Conditions of restriction for the following entries should be considered:

Number on list 3

Not applicable

benzene (Number on list 72, 5, 29,

28)

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

REACH - List of substances subject to authorisation : Not applicable

15 / 18

according to Regulation (EC) No. 1907/2006



## TESSAROL ENAMEL FOR RADIATORS white

Version Revision Date: SDS Number: Date of last issue: -

1.0 18.01.2021 MAT000409301 Date of first issue: 18.01.2021

GB/EN

(Annex XIV)

Regulation (EC) No 1005/2009 on substances that de- : Not applicable

plete the ozone layer

Regulation (EU) 2019/1021 on persistent organic pollu- : Not applicable

tants (recast)

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import

of dangerous chemicals

Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving

dangerous substances.

FLAMMABLE LIQUIDS

34 Petroleum products: (a) gasolines and naphthas, (b) kerosenes

(including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a)

to (d)

Volatile organic compounds : Directive 2004/42/EC

Volatile organic compounds (VOC) content: 500 g/l

#### Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

P5c

### 15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

### **SECTION 16: Other information**

#### **Full text of H-Statements**

H226 : Flammable liquid and vapour.

H304 : May be fatal if swallowed and enters airways.

H315 : Causes skin irritation.

H318 : Causes serious eye damage.
H336 : May cause drowsiness or dizziness.
H351 : Suspected of causing cancer if inhaled.
H361d : Suspected of damaging the unborn child.

#### Full text of other abbreviations

Asp. Tox. : Aspiration hazard Carc. : Carcinogenicity Eye Dam. : Serious eye damage

according to Regulation (EC) No. 1907/2006



## TESSAROL ENAMEL FOR RADIATORS white

Version Revision Date: SDS Number: Date of last issue: -

1.0 18.01.2021 MAT000409301 Date of first issue: 18.01.2021

GB / EN

Flam. Liq. : Flammable liquids Repr. : Reproductive toxicity

Skin Irrit. : Skin irritation

STOT SE : Specific target organ toxicity - single exposure

2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first

list of indicative occupational exposure limit values

GB EH40 : UK. EH40 WEL - Workplace Exposure Limits

2000/39/EC / TWA : Limit Value - eight hours 2000/39/EC / STEL : Short term exposure limit

GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS -Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP -Good Laboratory Practice: IARC - International Agency for Research on Cancer: IATA - International Air Transport Association: IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL -International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS -Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

#### **Further information**

### Classification of the mixture: Classification procedure:

Flam. Liq. 3 H226 Based on product data or assessment

STOT SE 3 H336 Calculation method

according to Regulation (EC) No. 1907/2006



# **TESSAROL ENAMEL FOR RADIATORS white**

Version Revision Date: SDS Number: Date of last issue: -

1.0 18.01.2021 MAT000409301 Date of first issue: 18.01.2021

GB/EN

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.