According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



IDEAL acrylic parquet lacquer (glossy / matt)

Version 2.0

Revision Date: 20.03.2024

SDS Number: MAT0GA00_052

Date of last issue: 08.09.2020 Date of first issue: 08.09.2020

GB/EN

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : IDEAL acrylic parquet lacquer (glossy / matt)

Product code : Please see section 16 for detailed data

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Building and construction work

stance/Mixture Professional and consumer use of coatings, Roller application

or brushing, Non industrial spraying

Coatings and paints, thinners, paint removers

1.3 Details of the supplier of the safety data sheet

Company : Helios TBLUS d.o.o.

Količevo 65 1230 Domžale Slovenia

Telephone Company : 386 (1) 722 4383

Telefax Company : 386 (1) 722 4310

Responsible/issuing person : 386 (1) 722 4383

productsafety@helios.si

1.4 Emergency telephone number

Call 999 (or 112) for emergency medical attention

professionals only: National Poison Information Service (NPIS) 24h national number 0844 892 0111

consumer: National Health Service (NHS) 24h national number, England & Scotland 111

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Not a hazardous substance or mixture.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



IDEAL acrylic parquet lacquer (glossy / matt)

Version Revision Date: 2.0 20.03.2024

SDS Number: MAT0GA00_052

Date of last issue: 08.09.2020 Date of first issue: 08.09.2020

GB/EN

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required

Precautionary statements : P101 If medical advice is needed, have product container or

label at hand.

P102 Keep out of reach of children.

Additional Labelling

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Waterborne paint

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)	
2-butoxyethanol	111-76-2 203-905-0 603-014-00-0 01-2119475108-36	Acute Tox. 4; H302 Acute Tox. 3; H331 Skin Irrit. 2; H315 Eye Irrit. 2; H319	>= 1 - < 10	
1,2-benzisothiazol-3(2H)-one	2634-33-5 220-120-9 613-088-00-6 01-2120761540-60	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 2; H411 ———— specific concentration limit Skin Sens. 1; H317 >= 0,05 %	>= 0,025 - < 0,05	
Substances with a workplace exposure limit :				

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



IDEAL acrylic parquet lacquer (glossy / matt)

Version Revision Date: SDS Number: Date of last issue: 08.09.2020 20.03.2024 MAT0GA00_052 Date of first issue: 08.09.2020

GB/EN

(2-methoxymethylethoxy)propanol	34590-94-8	>= 1 - < 10
	252-104-2	
	01-2119450011-60	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Do not leave the victim unattended.

If inhaled : Consult a physician after significant exposure.

If unconscious, place in recovery position and seek medical

advice.

In case of skin contact : If skin irritation persists, call a physician.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Flush eyes with water as a precaution.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : No symptoms known or expected.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Carbon dioxide (CO2)

Unsuitable extinguishing

media

High volume water jet

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



IDEAL acrylic parquet lacquer (glossy / matt)

Version 2.0

Revision Date: 20.03.2024

SDS Number: MAT0GA00_052 Date of last issue: 08.09.2020 Date of first issue: 08.09.2020

GB/EN

5.2 Special hazards arising from the substance or mixture

ucts

Hazardous combustion prod- : No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment:

for firefighters

Wear self-contained breathing apparatus for firefighting if nec-

essary.

Further information For safety reasons in case of fire, cans should be stored sepa-

rately in closed containments.

Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment.

Ensure adequate ventilation.

Do not flush into surface water or sanitary sewer system. Prevent further leakage or spillage if safe to do so.

6.2 Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Contain spillage, and then collect with non-combustible ab-Methods for cleaning up

> sorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local

/ national regulations (see section 13).

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling Avoid formation of aerosol.

> Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



IDEAL acrylic parquet lacquer (glossy / matt)

Version 2.0

Revision Date: 20.03.2024

SDS Number: MAT0GA00_052

Date of last issue: 08.09.2020 Date of first issue: 08.09.2020

GB/EN

Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national

regulations.

Advice on protection against

fire and explosion

Do not spray on a naked flame or any incandescent material. Keep away from open flames, hot surfaces and sources of

ignition.

Hygiene measures : When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: No smoking. Keep in a well-ventilated place. Observe label precautions. Electrical installations / working materials must

comply with the technological safety standards.

Advice on common storage :

No materials to be especially mentioned.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : For further information, refer to the product technical data

sheet.

For further information, refer to the product technical data

sheet.

Consult the technical guidelines for the use of this sub-

stance/mixture.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
2-butoxyethanol	111-76-2	TWA	25 ppm	GB EH40
-			123 mg/m3	
			bed through the skin. The as	
	stances are th	ose for which there	are concerns that dermal abs	sorption will
	lead to systemic toxicity.			
		STEL	50 ppm	GB EH40
			246 mg/m3	
	Further information: Can be absorbed through the skin. The assigned sub-			
	stances are those for which there are concerns that dermal absorption will			
	lead to systemic toxicity.			
		TWA	20 ppm	2000/39/EC
			98 mg/m3	

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



IDEAL acrylic parquet lacquer (glossy / matt)

VersionRevision Date:SDS Number:Date of last issue: 08.09.20202.020.03.2024MAT0GA00_052Date of first issue: 08.09.2020

GB/EN

	Further information: Identifies the possibility of significant uptake through the skin, Indicative				
		STEL	50 ppm 246 mg/m3	2000/39/EC	
		Further information: Identifies the possibility of significant uptake through the skin, Indicative			
(2-	34590-94-8	TWA	50 ppm	GB EH40	
Methoxymeth-			308 mg/m3		
ylethoxy)propanol					
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.				
		TWA	50 ppm 308 mg/m3	2000/39/EC	
	Further information: Identifies the possibility of significant uptake through the skin, Indicative				

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
2-butoxyethanol	111-76-2	butoxyacetic acid: 240 Millimoles per mole creatinine (Urine)	After shift	GB EH40 BAT

Derived No Effect Level (DNEL):

according to Regulation (EC) No. 1907/2006

Substance name	End Use	Exposure routes	Potential health effects	Value
2-butoxyethanol	Workers	Inhalation	Long-term systemic effects	98 mg/m3
	Workers	Inhalation	Acute systemic effects	1091 mg/m3
	Workers	Inhalation	Acute local effects	246 mg/m3
	Consumers	Inhalation	Long-term systemic effects	59 mg/m3
	Consumers	Inhalation	Acute systemic ef- fects	426 mg/m3
	Consumers	Inhalation	Acute local effects	147 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	125 mg/kg bw/day
	Workers	Dermal	Acute systemic effects	89 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	75 mg/kg bw/day
	Consumers	Dermal	Acute systemic effects	89 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	6,3 mg/kg bw/day

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



IDEAL acrylic parquet lacquer (glossy / matt)

VersionRevision Date:SDS Number:Date of last issue: 08.09.20202.020.03.2024MAT0GA00_052Date of first issue: 08.09.2020

GB/EN

	Consumers	Oral	Acute systemic effects	26,7 mg/kg bw/day
(2- Methoxymethyleth- oxy)propanol	Workers	Inhalation	Long-term systemic effects	308 mg/m3
	Consumers	Inhalation	Long-term systemic effects	37,2 mg/m3
	Workers	Dermal	Long-term systemic effects	283 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	121 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	36 mg/kg bw/day
1,2-benzisothiazol- 3(2H)-one	Workers	Inhalation	Long-term systemic effects	6,81 mg/m3
	Workers	Dermal	Long-term systemic effects	0,966 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	1,2 mg/m3
	Consumers	Dermal	Long-term systemic effects	0,345 mg/kg bw/day

Predicted No Effect Concentration (PNEC):

according to Regulation (EC) No. 1907/2006

Substance name	Environmental Compartment	Value
2-butoxyethanol	Soil	2,33 mg/kg dry
		weight (d.w.)
	Marine water	0,88 mg/l
	Fresh water	8,8 mg/l
	Fresh water sediment	34,6 mg/kg dry
		weight (d.w.)
	Sewage treatment plant	463 mg/l
	Intermittent use/release	9,1 mg/l
(2-	Soil	2,74 mg/kg dry
Methoxymethylethoxy)propanol		weight (d.w.)
	Marine water	1,9 mg/l
	Fresh water	19 mg/l
	Marine sediment	7,02 mg/kg dry
		weight (d.w.)
	Fresh water sediment	70,2 mg/kg dry
		weight (d.w.)
	Sewage treatment plant	4168 mg/l
	Intermittent use/release	190 mg/l
1,2-benzisothiazol-3(2H)-one	Fresh water	0,00403 mg/l
	Intermittent use/release	0,0011 mg/l
	Marine water	0,000403 mg/l
	Sewage treatment plant	1,03 mg/l
	Fresh water sediment	0,0499 mg/kg dry
		weight (d.w.)

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



IDEAL acrylic parquet lacquer (glossy / matt)

Version Revision Date: SDS Number: Date of last issue: 08.09.2020 20.03.2024 MAT0GA00_052 Date of first issue: 08.09.2020 2.0

GB/EN

Marine sediment	0,00499 mg/kg dry weight (d.w.)
Soil	3 mg/kg dry weight (d.w.)

8.2 Exposure controls

Personal protective equipment

Eye/face protection Equipment should conform to EN 166

> Eye wash bottle with pure water Tightly fitting safety goggles

Hand protection

Gloves Nitrile rubber (> 0,1 mm; < 60 min); ISO EN374

butyl-rubber (> 0,6 mm; < 240 min); ISO EN374 Viton® (> 0,6 mm; < 240 min); ISO EN374 PE laminate (> 0,1 mm; < 240 min); ISO EN374

Remarks The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of

cuts, abrasion, and the contact time.

Skin and body protection Impervious clothing

Choose body protection according to the amount and concen-

tration of the dangerous substance at the work place.

No personal respiratory protective equipment normally re-Respiratory protection

quired.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance liquid

Colour in accordance with the product description

Odour characteristic Odour Threshold No data available

pΗ No data available

Melting point/freezing point -70.0 °C

(calculation method (principal components, lowest value)) 100 °C (calculation method (principal components, lowest

Boiling point/boiling range

value))

Flash point 68 °C

Flammability (solid, gas) Not applicable

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



IDEAL acrylic parquet lacquer (glossy / matt)

Version

Revision Date:

SDS Number: MAT0GA00_052

Date of last issue: 08.09.2020

2.0

20.03.2024

GB/EN

Date of first issue: 08.09.2020

Upper explosion limit / Upper

flammability limit

10,6 %(V)

(calculation method (principal components, highest value))

Lower explosion limit / Lower

flammability limit

1,1 %(V)

(calculation method (principal components, highest value))

Vapour pressure 0,79 - 1,3 hPa (calculation method (principal components,

highest value))

(20 °C)

Density 1,01 - 1,02 g/cm3

Solubility(ies)

Water solubility completely miscible Solubility in other solvents No data available

Partition coefficient: n-

octanol/water

log Pow: 0,81 (calculation method (principal components,

highest value))

(20 °C)

Ignition temperature 230 °C (calculation method (principal components, highest

value))

Viscosity

Viscosity, kinematic $> 20,5 \text{ mm2/s} (40 \,^{\circ}\text{C})$

18 - 19 s at 23 °C Flow time

Method: DIN 53211 (CF4)

9.2 Other information

No data available

VOC (Directive 2004/42/EC)

140 g/l

Solids content in %: 30 - 33 %

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



IDEAL acrylic parquet lacquer (glossy / matt)

Version Revision Date: 2.0 20.03.2024

SDS Number: MAT0GA00_052

Date of last issue: 08.09.2020 Date of first issue: 08.09.2020

GB/EN

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Protect from frost, heat and sunlight.

Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Strong oxidizing agents

Not applicable

10.6 Hazardous decomposition products

Stable under recommended storage conditions. No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

Not classified due to lack of data.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2.000 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l

Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Components:

2-butoxyethanol:

Acute oral toxicity : Acute toxicity estimate: 1.200 mg/kg

Method: Acute toxicity estimate according to Regulation (EC)

No. 1272/2008

Acute inhalation toxicity : LC50 (Rat): 450 ppm

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



IDEAL acrylic parquet lacquer (glossy / matt)

Version 2.0

Revision Date: 20.03.2024

SDS Number: MAT0GA00_052

Date of last issue: 08.09.2020 Date of first issue: 08.09.2020

GB/EN

Exposure time: 4 h Test atmosphere: vapour

Assessment: The component/mixture is toxic after short term

inhalation.

Acute toxicity estimate: 3 mg/l Test atmosphere: vapour

1,2-benzisothiazol-3(2H)-one:

Acute oral toxicity Assessment: The component/mixture is moderately toxic after

single ingestion.

(2-Methoxymethylethoxy)propanol:

Acute oral toxicity Assessment: The substance or mixture has no acute oral tox-

icity

: Assessment: The substance or mixture has no acute inhala-Acute inhalation toxicity

tion toxicity

Acute dermal toxicity Assessment: The substance or mixture has no acute dermal

toxicity

Skin corrosion/irritation

Not classified based on available information.

Not classified due to lack of data.

Product:

Remarks May cause skin irritation and/or dermatitis.

Components:

2-butoxyethanol:

Result irritating

1,2-benzisothiazol-3(2H)-one:

Result irritating

Serious eye damage/eye irritation

Not classified based on available information.

Not classified due to lack of data.

Product:

Remarks Vapours may cause irritation to the eyes, respiratory system

and the skin.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



IDEAL acrylic parquet lacquer (glossy / matt)

Version Revision Date: SDS Number: Date of last issue: 08.09.2020 20.03.2024 MAT0GA00_052 Date of first issue: 08.09.2020

GB/EN

Components:

2-butoxyethanol:

Result : Eye irritation

1,2-benzisothiazol-3(2H)-one:

Result : Corrosive

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Skin sensitisation

Not classified due to lack of data.

Respiratory sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified due to lack of data.

Components:

1,2-benzisothiazol-3(2H)-one:

Result : Probability or evidence of skin sensitisation in humans

Germ cell mutagenicity

Not classified based on available information.

Not classified due to lack of data.

Carcinogenicity

Not classified based on available information.

Not classified due to lack of data.

Reproductive toxicity

Not classified based on available information.

Not classified due to lack of data.

STOT - single exposure

Not classified based on available information.

Not classified due to lack of data.

STOT - repeated exposure

Not classified based on available information.

Not classified due to lack of data.

Aspiration toxicity

Not classified based on available information.

Not classified due to lack of data.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



IDEAL acrylic parquet lacquer (glossy / matt)

Version 2.0

Revision Date: 20.03.2024

SDS Number: MAT0GA00_052

Date of last issue: 08.09.2020 Date of first issue: 08.09.2020

GB/EN

Further information

Product:

Remarks No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

2-butoxyethanol:

Toxicity to fish LC50 (Fish): >= 1.700 mg/l

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : LC50 (Daphnia (water flea)): > 1.000 mg/l

Exposure time: 48 h

Toxicity to microorganisms : EC50 (Bacteria): > 5.000 mg/l

1,2-benzisothiazol-3(2H)-one:

Ecotoxicology Assessment

Chronic aquatic toxicity Toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

Components:

2-butoxyethanol:

Biodegradability : Result: Biodegradable

Stability in water Hydrolyses slowly.

Photodegradation Decomposes slowly in contact with light.

12.3 Bioaccumulative potential

Components:

2-butoxyethanol:

Partition coefficient: nlog Pow: 0,81 (20 °C)

octanol/water

1,2-benzisothiazol-3(2H)-one:

Partition coefficient: n-

octanol/water

log Pow: 1,3

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



IDEAL acrylic parquet lacquer (glossy / matt)

Version 2.0

Revision Date: 20.03.2024

SDS Number: MAT0GA00_052

Date of last issue: 08.09.2020 Date of first issue: 08.09.2020

GB/EN

(2-Methoxymethylethoxy)propanol:

Partition coefficient: n-

octanol/water

: log Pow: -0,064

12.4 Mobility in soil

Components:

2-butoxyethanol:

Mobility : Medium: Air

Content: 1 %

: Medium: Water Content: 47 %

Medium: Soil Content: 52 %

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

Components:

2-butoxyethanol:

Assessment : Substance is not persistent, bioaccumulative, and toxic (PBT).

12.6 Other adverse effects

Product:

Endocrine disrupting poten-

-... ial This substance/mixture does not contain components considered to have endocrine disrupting properties for environment

according to UK REACH Article 57(f).

Additional ecological infor-

mation

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Send to a licensed waste management company.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



IDEAL acrylic parquet lacquer (glossy / matt)

Version 2.0

Revision Date: 20.03.2024

SDS Number: MAT0GA00_052

Date of fir

Date of last issue: 08.09.2020 Date of first issue: 08.09.2020

GB/EN

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

14.1 UN number

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.2 UN proper shipping name

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.4 Packing group

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA (Cargo) : Not regulated as a dangerous good
IATA (Passenger) : Not regulated as a dangerous good

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



IDEAL acrylic parquet lacquer (glossy / matt)

Version 2.0

Revision Date: 20.03.2024

SDS Number: MAT0GA00_052 Date of last issue: 08.09.2020 Date of first issue: 08.09.2020

GB/EN

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mix-

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17)

Not applicable

UK REACH Candidate list of substances of very high

Not applicable

concern (SVHC) for Authorisation

The Persistent Organic Pollutants Regulations (retained

Not applicable

Regulation (EU) 2019/1021 as amended for Great Brit-

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Not applicable

UK REACH List of substances subject to authorisation

(Annex XIV)

Not applicable

Not applicable

GB Export and import of hazardous chemicals - Prior

Informed Consent (PIC) Regulation

Control of Major Accident Hazards Regulations 2015 (COMAH)

Not applicable

Directive 2004/42/EC Volatile organic compounds

Volatile organic compounds (VOC) content: 140 g/l

Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

SECTION 16: Other information

Full text of H-Statements

H302 Harmful if swallowed.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



IDEAL acrylic parquet lacquer (glossy / matt)

Version Revision Date: SDS Number: Date of last issue: 08.09.2020 20.03.2024 MAT0GA00_052 Date of first issue: 08.09.2020

GB/EN

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.

H331 : Toxic if inhaled.

H400 : Very toxic to aquatic life.

H411 : Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Acute : Short-term (acute) aquatic hazard
Aquatic Chronic : Long-term (chronic) aquatic hazard

Eye Dam. : Serious eye damage

Eye Irrit. : Eye irritation
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation

2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first

list of indicative occupational exposure limit values

GB EH40 : UK. EH40 WEL - Workplace Exposure Limits
GB EH40 BAT : UK. Biological monitoring guidance values

2000/39/EC / TWA : Limit Value - eight hours 2000/39/EC / STEL : Short term exposure limit

GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways: ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA -European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals: OECD - Organization for Economic Co-operation and Development: OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Re-

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



IDEAL acrylic parquet lacquer (glossy / matt)

Version **Revision Date:** 2.0

SDS Number: 20.03.2024 MAT0GA00_052

GB/EN

Date of last issue: 08.09.2020 Date of first issue: 08.09.2020

striction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI -Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

Material codes (bulk) for which the SDS is valid

478630; 478631

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.