

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## TESSAROL acrylic putty for wood

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	17.03.2021	MAT0GA00_002	Date of first issue: 17.03.2021
		GB / EN	

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Product code : Please see section 16 for detailed data

Trade name : TESSAROL acrylic putty for wood

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-  
stance/Mixture : SU19 Building and construction work  
Professional and consumer use of coatings, Roller application  
or brushing, Non industrial spraying  
PC9a Coatings and paints, thinners, paint removers

#### 1.3 Details of the supplier of the safety data sheet

Company : Helios TBLUS d.o.o.  
Količevo 65  
1230 Domžale  
Slovenia

Telephone Company : 386 (1) 722 4383

Telefax Company : 386 (1) 722 4310

Responsible/issuing person : 386 (1) 722 4383  
productsafety@helios.si

#### 1.4 Emergency telephone number

Call 999 for emergency medical attention

professionals only: National Poison Information Service (NPIS) 24h national number 0844 892  
0111

consumer: National Health Service (NHS) 24h national number, England & Scotland 111

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Classification (REGULATION (EC) No 1272/2008)**

Not a hazardous substance or mixture.

#### 2.2 Label elements

**Labelling (REGULATION (EC) No 1272/2008)**

Not a hazardous substance or mixture.

Precautionary statements : P101 If medical advice is needed, have product container or

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## TESSAROL acrylic putty for wood

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	17.03.2021	MAT0GA00_002	Date of first issue: 17.03.2021
		GB / EN	

label at hand.  
P102 Keep out of reach of children.

### Additional Labelling

EUH208 Contains 1,2-benzisothiazol-3(2H)-one, reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one and 2-methyl-2H -isothiazol-3- one (3:1). May produce an allergic reaction.

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Chemical nature : Waterborne paint

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
1,2-benzisothiazol-3(2H)-one	2634-33-5 220-120-9 613-088-00-6 01-2120761540-60	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 2; H411  specific concentration limit Skin Sens. 1; H317 >= 0,05 %	>= 0,0025 - < 0,025
reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one and 2-methyl-2H -isothiazol-3- one (3:1)	55965-84-9  613-167-00-5 01-2120764691-48	Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 2; H310 Skin Corr. 1C; H314 Eye Dam. 1; H318	<= 0,0002

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## TESSAROL acrylic putty for wood

Version  
1.0

Revision Date:  
17.03.2021

SDS Number:  
MAT0GA00\_002  
GB / EN

Date of last issue: -  
Date of first issue: 17.03.2021

		<div>Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071</div> <div>M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100</div> <div>specific concentration limit Skin Corr. 1C; H314 ≥ 0,6 % Skin Irrit. 2; H315 0,06 - &lt; 0,6 % Eye Irrit. 2; H319 0,06 - &lt; 0,6 % Skin Sens. 1A; H317 ≥ 0,0015 % Eye Dam. 1; H318 ≥ 0,6 %</div>	
--	--	---	--

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : Do not leave the victim unattended.
- If inhaled : If breathed in, move person into fresh air.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes.
- In case of eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
If eye irritation persists: Get medical advice/ attention.
- If swallowed : Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.

#### 4.2 Most important symptoms and effects, both acute and delayed

None known.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## TESSAROL acrylic putty for wood

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	17.03.2021	MAT0GA00_002	Date of first issue: 17.03.2021
		GB / EN	

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

### 5.2 Special hazards arising from the substance or mixture

Hazardous combustion products : No hazardous combustion products are known

### 5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : The product itself does not burn.  
Standard procedure for chemical fires.  
Use a water spray to cool fully closed containers.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Avoid contact with skin and eyes.  
Do not flush into surface water or sanitary sewer system.  
Prevent further leakage or spillage if safe to do so.

### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.  
If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

### 6.4 Reference to other sections

For disposal considerations see section 13., For personal protection see section 8.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## TESSAROL acrylic putty for wood

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	17.03.2021	MAT0GA00_002	Date of first issue: 17.03.2021
		GB / EN	

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

- Advice on safe handling : No special technical protective measures required.  
For personal protection see section 8.
- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Hygiene measures : When using do not eat, drink or smoke. Wash thoroughly after handling.

#### 7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Containers which are opened must be carefully resealed and kept upright to prevent leakage. Perishable if frozen. To maintain product quality, do not store in heat or direct sunlight.
- Advice on common storage : No materials to be especially mentioned.
- Further information on storage stability : Protect from frost.

#### 7.3 Specific end use(s)

- Specific use(s) : Consult the technical guidelines for the use of this substance/mixture.

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

##### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
limestone	1317-65-3	TWA (inhalable dust)	10 mg/m <sup>3</sup>	GB EH40
		TWA (Respirable dust)	4 mg/m <sup>3</sup>	GB EH40
Calcium carbonate	471-34-1	TWA (inhalable dust)	10 mg/m <sup>3</sup>	GB EH40
		TWA (Respirable dust)	4 mg/m <sup>3</sup>	GB EH40
zinc distearate	557-05-1	TWA (inhalable dust)	10 mg/m <sup>3</sup>	GB EH40
		TWA (Respirable dust)	4 mg/m <sup>3</sup>	GB EH40
		STEL (inhalable dust)	20 mg/m <sup>3</sup>	GB EH40

##### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
----------------	---------	-----------------	--------------------------	-------

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## TESSAROL acrylic putty for wood

Version  
1.0

Revision Date:  
17.03.2021

SDS Number:  
MAT0GA00\_002  
GB / EN

Date of last issue: -  
Date of first issue: 17.03.2021

Calcium carbonate	Workers	Inhalation	Long-term local effects	4,26 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local effects	1,06 mg/m <sup>3</sup>
1,2-benzisothiazol-3(2H)-one	Workers	Inhalation	Long-term systemic effects	6,81 mg/m <sup>3</sup>
	Workers	Dermal	Long-term systemic effects	0,966 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	1,2 mg/m <sup>3</sup>
	Consumers	Dermal	Long-term systemic effects	0,345 mg/kg bw/day
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	Consumers	Inhalation	Acute local effects	0,04 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	0,02 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	0,04 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local effects	0,02 mg/m <sup>3</sup>
	Consumers	Oral	Long-term systemic effects	0,09 mg/kg bw/day
	Consumers	Oral	Acute systemic effects	0,11 mg/kg bw/day

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Calcium carbonate	Sewage treatment plant	100 mg/l
1,2-benzisothiazol-3(2H)-one	Fresh water	0,00403 mg/l
	Intermittent use/release	0,0011 mg/l
	Marine water	0,000403 mg/l
	Sewage treatment plant	1,03 mg/l
	Fresh water sediment	0,0499 mg/kg dry weight (d.w.)
	Marine sediment	0,00499 mg/kg dry weight (d.w.)
	Soil	3 mg/kg dry weight (d.w.)
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	Soil	0,01 mg/kg dry weight (d.w.)
	Marine water	0,00339 mg/l
	Fresh water	0,00339 mg/l
	Marine sediment	0,027 mg/kg dry weight (d.w.)
	Fresh water sediment	0,027 mg/kg dry weight (d.w.)
	Sewage treatment plant	0,23 mg/l
	Intermittent use/release	0,00339 mg/l

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## TESSAROL acrylic putty for wood

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	17.03.2021	MAT0GA00_002	Date of first issue: 17.03.2021
		GB / EN	

### 8.2 Exposure controls

#### Personal protective equipment

Eye protection	:	Goggles
Hand protection	:	
Material	:	Nitrile rubber
Glove thickness	:	0,2 mm
Protective index	:	Class 3
Remarks	:	Wear suitable gloves.
Skin and body protection	:	Long sleeved clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Respiratory protection	:	No personal respiratory protective equipment normally required.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state	:	liquid
Colour	:	in accordance with the product description
Odour	:	No information available.
Odour Threshold	:	No data available
Melting point/freezing point	:	0,0 °C (calculation method (principal components, lowest value))
Boiling point/boiling range	:	100 °C (calculation method (principal components, lowest value))
Flammability	:	Not applicable
Flash point	:	Not applicable
pH	:	No data available
Viscosity	:	
Viscosity, kinematic	:	> 20,5 mm <sup>2</sup> /s (40 °C)
Solubility(ies)	:	
Water solubility	:	completely miscible
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Density	:	1,65 - 1,75 g/cm <sup>3</sup>

### 9.2 Other information

VOC	:	(Directive 2004/42/EC) 30 g/l
-----	---	----------------------------------

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## TESSAROL acrylic putty for wood

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	17.03.2021	MAT0GA00_002	Date of first issue: 17.03.2021
		GB / EN	

---

---

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

No decomposition if stored and applied as directed.

#### 10.2 Chemical stability

Stable under recommended storage conditions.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : No data available

#### 10.4 Conditions to avoid

Conditions to avoid : Protect from frost, heat and sunlight.

#### 10.5 Incompatible materials

Materials to avoid : Incompatible with oxidizing agents.  
Incompatible with strong acids and bases.

#### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

---

### SECTION 11: Toxicological information

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

##### Acute toxicity

Not classified based on available information.

##### Components:

##### 1,2-benzisothiazol-3(2H)-one:

Acute oral toxicity : Assessment: The component/mixture is moderately toxic after single ingestion.

##### Skin corrosion/irritation

Not classified based on available information.

##### Components:

##### 1,2-benzisothiazol-3(2H)-one:

Result : irritating

##### Serious eye damage/eye irritation

Not classified based on available information.



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## TESSAROL acrylic putty for wood

Version  
1.0

Revision Date:  
17.03.2021

SDS Number:  
MAT0GA00\_002  
GB / EN

Date of last issue: -  
Date of first issue: 17.03.2021

### Components:

#### **1,2-benzisothiazol-3(2H)-one:**

Result : Corrosive

### **Respiratory or skin sensitisation**

#### **Skin sensitisation**

Not classified based on available information.

#### **Respiratory sensitisation**

Not classified based on available information.

### Components:

#### **1,2-benzisothiazol-3(2H)-one:**

Result : Probability or evidence of skin sensitisation in humans

### **Germ cell mutagenicity**

Not classified based on available information.

### **Carcinogenicity**

Not classified based on available information.

### **Reproductive toxicity**

Not classified based on available information.

### **STOT - single exposure**

Not classified based on available information.

### **STOT - repeated exposure**

Not classified based on available information.

### **Aspiration toxicity**

Not classified based on available information.

## **11.2 Information on other hazards**

### **Endocrine disrupting properties**

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## TESSAROL acrylic putty for wood

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	17.03.2021	MAT0GA00_002	Date of first issue: 17.03.2021
		GB / EN	

### SECTION 12: Ecological information

#### 12.1 Toxicity

##### Components:

##### **1,2-benzisothiazol-3(2H)-one:**

##### **Ecotoxicology Assessment**

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

##### **reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one and 2-methyl-2H -isothiazol-3-one (3:1):**

Toxicity to fish : LC50 (Salvelinus namaycush (lake trout)):  $\geq 10,85$  mg/l  
Exposure time: 96 h

Toxicity to algae/aquatic plants : LC50 (algae):  $\geq 0,82$  mg/l  
Exposure time: 48 h

LC50 (algae): 0,018 mg/l  
Exposure time: 72 h

M-Factor (Acute aquatic toxicity) : 100

M-Factor (Chronic aquatic toxicity) : 100

#### 12.2 Persistence and degradability

No data available

#### 12.3 Bioaccumulative potential

##### Components:

##### **1,2-benzisothiazol-3(2H)-one:**

Partition coefficient: n-octanol/water : log Pow: 1,3

#### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

##### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

#### 12.6 Endocrine disrupting properties

##### Product:

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## TESSAROL acrylic putty for wood

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	17.03.2021	MAT0GA00_002	Date of first issue: 17.03.2021
		GB / EN	

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

No data available

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : Do not release the product to the aquatic environment

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

Waste Code : 08 01 20, aqueous suspensions containing paint or varnish other than those mentioned in 08 01 19

## SECTION 14: Transport information

### 14.1 UN number or ID number

Not regulated as a dangerous good

### 14.2 UN proper shipping name

Not regulated as a dangerous good

### 14.3 Transport hazard class(es)

Not regulated as a dangerous good

### 14.4 Packing group

Not regulated as a dangerous good

### 14.5 Environmental hazards

Not regulated as a dangerous good

### 14.6 Special precautions for user

Not applicable

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Not applicable

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## TESSAROL acrylic putty for wood

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	17.03.2021	MAT0GA00_002	Date of first issue: 17.03.2021
		GB / EN	

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals	: Not applicable
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	: Not applicable
REACH - List of substances subject to authorisation (Annex XIV)	: Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	: Not applicable
Regulation (EU) 2019/1021 on persistent organic pollutants (recast)	: Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.	Not applicable
---	----------------

Volatile organic compounds	: Directive 2004/42/EC
Volatile organic compounds (VOC) content: 30 g/l	

### 15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

## SECTION 16: Other information

### Full text of H-Statements

H301	: Toxic if swallowed.
H302	: Harmful if swallowed.
H310	: Fatal in contact with skin.
H314	: Causes severe skin burns and eye damage.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H330	: Fatal if inhaled.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.
H411	: Toxic to aquatic life with long lasting effects.
EUH071	: Corrosive to the respiratory tract.

### Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Acute	: Short-term (acute) aquatic hazard
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Eye Dam.	: Serious eye damage
Skin Corr.	: Skin corrosion
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitisation
GB EH40	: UK. EH40 WEL - Workplace Exposure Limits
GB EH40 / TWA	: Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	: Short-term exposure limit (15-minute reference period)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## TESSAROL acrylic putty for wood

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	17.03.2021	MAT0GA00_002	Date of first issue: 17.03.2021
		GB / EN	

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

Material codes (bulk) for 473506; 473507; 473508; 473509;  
which the SDS is valid

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.