according to Regulation (EC) No. 1907/2006



SPEKTRA SILICONE IMPREGNATION

Version SDS Number: Date of last issue: -Revision Date:

1.0 19.05.2020 MAT000412397 Date of first issue: 19.05.2020

GB/EN

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product code : 41239704

Trade name : SPEKTRA SILICONE IMPREGNATION

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-SU19 Building and construction work

stance/Mixture Professional and consumer use of coatings, Roller application

or brushing, Non industrial spraying

PC9a Coatings and paints, thinners, paint removers

1.3 Details of the supplier of the safety data sheet

Company : Helios TBLUS d.o.o.

> Količevo 65 1230 Domžale Slovenia

Telephone Company : 386 (1) 722 4383

Telefax Company : 386 (1) 722 4310

Responsible/issuing person : 386 (1) 722 4383

productsafety@helios.si

1.4 Emergency telephone number

Call 999 (or 112) for emergency medical attention

professionals only: National Poison Information Service (NPIS) 24h national number 0844 892

0111

consumer: National Health Service (NHS) 24h national number, England & Scotland 111

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Long-term (chronic) aquatic hazard, Cat-H412: Harmful to aquatic life with long lasting effects.

egory 3

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

3, ,	-,	
	1 / 1 /	
	1 / 14	

according to Regulation (EC) No. 1907/2006



SPEKTRA SILICONE IMPREGNATION

Version Revision Date: SDS Number: Date of last issue: -

1.0 19.05.2020 MAT000412397 Date of first issue: 19.05.2020

GB / EN

Hazard statements : H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : P101 If medical advice is needed, have product container or

label at hand.

P102 Keep out of reach of children.

Prevention:

P273 Avoid release to the environment.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

Additional Labelling

EUH208 Contains 1,2-benzisothiazol-3(2H)-one, reaction mass of: 5-chloro-2- methyl-4-

isothiazolin-3-one and 2-methyl-2H -isothiazol-3- one (3:1). May produce an

allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Waterborne paint

Components

Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Index-No.		
	Registration number		
triethoxyoctylsilane	2943-75-1	Skin Irrit. 2; H315	>= 1 - < 2,5
	220-941-2	Aquatic Chronic 2;	
	01-2119972313-39	H411	
1,2-benzisothiazol-3(2H)-one	2634-33-5	Acute Tox. 4; H302	>= 0,0025 - <
	220-120-9	Skin Irrit. 2; H315	0,025
	613-088-00-6	Eye Dam. 1; H318	
	01-2120761540-60	Skin Sens. 1; H317	
		Aquatic Acute 1;	
		H400	
		Aquatic Chronic 2;	
		H411	
Zinc pyridinethione	13463-41-7	Acute Tox. 3; H301	>= 0,0025 - <
	236-671-3	Acute Tox. 3; H331	0,025
		Eye Dam. 1; H318	
		Aquatic Acute 1;	
		H400	
		Aquatic Chronic 1;	
		H410	

2 / 14

according to Regulation (EC) No. 1907/2006



>= 0.0002 - <

0.0015

SPEKTRA SILICONE IMPREGNATION

Version SDS Number: Date of last issue: -Revision Date:

1.0 19.05.2020 MAT000412397 Date of first issue: 19.05.2020

GB/EN

reaction mass of: 5-chloro-2- me-55965-84-9 thyl-4-isothiazolin-3-one and 2-

methyl-2H -isothiazol-3- one (3:1) 613-167-00-5

01-2120764691-48

Acute Tox. 2; H310 Skin Corr. 1C; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317

Aquatic Acute 1; H400

Aquatic Chronic 1; H410

Acute Tox. 3; H301

Acute Tox. 2; H330

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice Do not leave the victim unattended.

If inhaled If breathed in, move person into fresh air.

In case of contact, immediately flush skin with plenty of water. In case of skin contact

Remove contaminated clothing and shoes.

In case of eye contact IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue

rinsing.

If eye irritation persists: Get medical advice/ attention.

If swallowed Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

: Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Use water spray, alcohol-resistant foam, dry chemical or car-

bon dioxide.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion prod- : No hazardous combustion products are known

ucts

3 / 14		
3 / 14	0.1.1.1	
	3 / 14	
	37.11	1

according to Regulation (EC) No. 1907/2006



SPEKTRA SILICONE IMPREGNATION

Version Revision Date: SDS Number: Date of last issue: -

1.0 19.05.2020 MAT000412397 Date of first issue: 19.05.2020

GB/EN

5.3 Advice for firefighters

Special protective equipment:

for firefighters

Wear self-contained breathing apparatus for firefighting if nec-

essary.

Further information : The product itself does not burn.

Standard procedure for chemical fires.

Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Avoid contact with skin and eyes.

Do not flush into surface water or sanitary sewer system. Prevent further leakage or spillage if safe to do so.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For disposal considerations see section 13., For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : No special technical protective measures required.

For personal protection see section 8.

Advice on protection against :

fire and explosion

Normal measures for preventive fire protection.

Hygiene measures : When using do not eat, drink or smoke.

Wash thoroughly after handling.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Perishable if frozen.

To maintain product quality, do not store in heat or direct sun-

light.

Advice on common storage : No materials to be especially mentioned.

	i
4/14	1
7/17	

according to Regulation (EC) No. 1907/2006



SPEKTRA SILICONE IMPREGNATION

Version Revision Date: SDS Number: Date of last issue: -

1.0 19.05.2020 MAT000412397 Date of first issue: 19.05.2020

GB / EN

7.3 Specific end use(s)

Specific use(s) : Consult the technical guidelines for the use of this sub-

stance/mixture.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
triethoxyoctylsilane	Workers	Inhalation	Long-term systemic effects	16 mg/m3
	Workers	Inhalation	Acute systemic effects	16 mg/m3
	Workers	Dermal	Long-term systemic effects	9 mg/kg bw/day
	Workers	Dermal	Acute systemic effects	9 mg/kg bw/day
	Consumers	Inhalation	Acute systemic ef- fects	5,4 mg/m3
	Consumers	Inhalation	Long-term systemic effects	5,4 mg/m3
	Consumers	Dermal	Acute systemic ef- fects	6,2 mg/kg bw/day
	Consumer use	Dermal	Long-term systemic effects	6,2 mg/kg bw/day
	Consumer use	Oral	Acute systemic effects	6,2 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	6,2 mg/kg bw/day
1,2-benzisothiazol- 3(2H)-one	Workers	Inhalation	Long-term systemic effects	6,81 mg/m3
	Workers	Dermal	Long-term systemic effects	0,966 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	1,2 mg/m3
	Consumers	Dermal	Long-term systemic effects	0,345 mg/kg bw/day
reaction mass of: 5- chloro-2- methyl-4- isothiazolin-3-one and 2-methyl-2H - isothiazol-3- one (3:1)	Consumers	Inhalation	Acute local effects	0,04 mg/m3
	Workers	Inhalation	Long-term local ef- fects	0,02 mg/m3
	Workers	Inhalation	Acute local effects	0,04 mg/m3
	Consumers	Inhalation	Long-term local ef- fects	0,02 mg/m3

5 / 14	
--------	--

according to Regulation (EC) No. 1907/2006



SPEKTRA SILICONE IMPREGNATION

Version Revision Date: SDS Number: Date of last issue: -

1.0 19.05.2020 MAT000412397 Date of first issue: 19.05.2020

GB / EN

Consumers	Oral	Long-term systemic effects	0,09 mg/kg bw/day
Consumers	Oral	Acute systemic effects	0,11 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
triethoxyoctylsilane	Fresh water	0,0058 mg/l
	Marine water	0,00058 mg/l
	Sewage treatment plant	100 mg/l
	Fresh water sediment	2,34 mg/kg dry
		weight (d.w.)
	Marine sediment	0,230 mg/kg dry
		weight (d.w.)
	Soil	0,09 mg/kg dry
		weight (d.w.)
	Oral (Secondary Poisoning)	10 mg/kg food
1,2-benzisothiazol-3(2H)-one	Fresh water	0,00403 mg/l
	Intermittent use/release	0,0011 mg/l
	Marine water	0,000403 mg/l
	Sewage treatment plant	1,03 mg/l
	Fresh water sediment	0,0499 mg/kg dry
		weight (d.w.)
	Marine sediment	0,00499 mg/kg
		dry weight (d.w.)
	Soil	3 mg/kg dry
		weight (d.w.)
reaction mass of: 5-chloro-2-	Soil	0,01 mg/kg dry
methyl-4-isothiazolin-3-one and		weight (d.w.)
2-methyl-2H -isothiazol-3- one		
(3:1)		
	Marine water	0,00339 mg/l
	Fresh water	0,00339 mg/l
	Marine sediment	0,027 mg/kg dry
		weight (d.w.)
	Fresh water sediment	0,027 mg/kg dry
		weight (d.w.)
	Sewage treatment plant	0,23 mg/l
	Intermittent use/release	0,00339 mg/l

8.2 Exposure controls

Personal protective equipment

Eye protection : Goggles

Hand protection

Material : Nitrile rubber
Glove thickness : 0,2 mm
Protective index : Class 3

Remarks : Wear suitable gloves.
Skin and body protection : Long sleeved clothing

Choose body protection according to the amount and con-

7	0.1.4.4	
	6/14	
	0,	

according to Regulation (EC) No. 1907/2006



SPEKTRA SILICONE IMPREGNATION

Version Revision Date: SDS Number: Date of last issue: -

1.0 19.05.2020 MAT000412397 Date of first issue: 19.05.2020

GB / EN

centration of the dangerous substance at the work place.

Respiratory protection : No personal respiratory protective equipment normally re-

quired.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : in accordance with the product description

Odour : No information available.

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Boiling point/boiling range : No data available

Flash point : Not applicable

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Density : 1,0 - 1,1 g/cm3

Solubility(ies)

Water solubility : completely miscible Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

Viscosity

Viscosity, kinematic : > 20,5 mm2/s (40 °C)

Explosive properties : Not applicable

Oxidizing properties : Not applicable

9.2 Other information

No data available

VOC : (Directive 2004/42/EC)

1 g/l

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

7/11	
7 / 14	

according to Regulation (EC) No. 1907/2006



SPEKTRA SILICONE IMPREGNATION

Version Revision Date: SDS Number: Date of last issue: -

1.0 19.05.2020 MAT000412397 Date of first issue: 19.05.2020

GB / EN

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : No data available

10.4 Conditions to avoid

Conditions to avoid : Protect from frost, heat and sunlight.

10.5 Incompatible materials

Materials to avoid : Incompatible with oxidizing agents.

Incompatible with strong acids and bases.

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

Components:

1,2-benzisothiazol-3(2H)-one:

Acute oral toxicity : Assessment: The component/mixture is moderately toxic after

single ingestion.

Zinc pyridinethione:

Acute oral toxicity : Assessment: The component/mixture is toxic after single in-

gestion.

LD50 Oral (Rat): > 177 mg/kg

Acute inhalation toxicity : Test atmosphere: vapour

Assessment: The component/mixture is toxic after short term

inhalation.

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Components:

triethoxyoctylsilane:

Result : irritating

8 / 14	8 / 14	
--------	--------	--

according to Regulation (EC) No. 1907/2006



SPEKTRA SILICONE IMPREGNATION

Version Revision Date: SDS Number: Date of last issue: -

1.0 19.05.2020 MAT000412397 Date of first issue: 19.05.2020

GB/EN

1,2-benzisothiazol-3(2H)-one:

Result : irritating

Serious eye damage/eye irritation

Not classified based on available information.

Components:

1,2-benzisothiazol-3(2H)-one:

Result : Corrosive

Zinc pyridinethione:

Result : Corrosive

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

1,2-benzisothiazol-3(2H)-one:

Result : Probability or evidence of skin sensitisation in humans

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

according to Regulation (EC) No. 1907/2006



SPEKTRA SILICONE IMPREGNATION

Version Revision Date: SDS Number: Date of last issue: -

1.0 19.05.2020 MAT000412397 Date of first issue: 19.05.2020

GB/EN

SECTION 12: Ecological information

12.1 Toxicity

Components:

triethoxyoctylsilane:

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

1,2-benzisothiazol-3(2H)-one:

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Zinc pyridinethione:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): >= 0,0026

mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia (water flea)): >= 0,0028 mg/l

Exposure time: 48 h

Toxicity to algae : ErC50 (Desmodesmus subspicatus (green algae)): >= 0,028

mg/l

Exposure time: 120 h

M-Factor (Acute aquatic tox-

icity)

100

M-Factor (Chronic aquatic

toxicity)

10

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity:

Very toxic to aquatic life with long lasting effects.

reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one and 2-methyl-2H -isothiazol-3-

one (3:1):

Toxicity to fish : LC50 (Salvelinus namaycush (lake trout)): >= 10,85 mg/l

Exposure time: 96 h

Toxicity to algae : LC50 (algae): >= 0,82 mg/l

Exposure time: 48 h

10 / 14

according to Regulation (EC) No. 1907/2006



SPEKTRA SILICONE IMPREGNATION

Version Revision Date: SDS Number: Date of last issue: -

1.0 19.05.2020 MAT000412397 Date of first issue: 19.05.2020

GB/EN

LC50 (algae): 0,018 mg/l Exposure time: 72 h

M-Factor (Acute aquatic tox- : 100

icity)

M-Factor (Chronic aquatic : 100

toxicity)

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

Components:

1,2-benzisothiazol-3(2H)-one:

Partition coefficient: n-

octanol/water

log Pow: 1,3

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not release the product to the aquatic environment

Contaminated packaging : Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

Waste Code : 08 01 20, aqueous suspensions containing paint or varnish

other than those mentioned in 08 01 19

SECTION 14: Transport information

14.1 UN number

Not regulated as a dangerous good

11 / 14

according to Regulation (EC) No. 1907/2006

HELIOS

SPEKTRA SILICONE IMPREGNATION

Version Revision Date: SDS Number: Date of last issue: -

1.0 19.05.2020 MAT000412397 Date of first issue: 19.05.2020

GB / EN

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 649/2012 of the European Parlia-

ment and the Council concerning the export and import

of dangerous chemicals

REACH - Restrictions on the manufacture, placing on

the market and use of certain dangerous substances, preparations and articles (Annex XVII)

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of

major-accident hazards involving dangerous substances.

Not applicable

Volatile organic compounds : Directive 2004/42/EC

Volatile organic compounds (VOC) content: 1 g/l

Not applicable

Number on list 3

: Conditions of restriction for the fol-

lowing entries should be considered:

15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

SECTION 16: Other information

Full text of H-Statements

H301 : Toxic if swallowed.
H302 : Harmful if swallowed.
H310 : Fatal in contact with skin.

H314 : Causes severe skin burns and eye damage.

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.

H330 : Fatal if inhaled. H331 : Toxic if inhaled.

H400 : Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long lasting effects.

	12 / 14	
--	---------	--

according to Regulation (EC) No. 1907/2006



SPEKTRA SILICONE IMPREGNATION

Version Revision Date: SDS Number: Date of last issue: -

1.0 19.05.2020 MAT000412397 Date of first issue: 19.05.2020

GB / EN

H411 : Toxic to aguatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Acute : Short-term (acute) aquatic hazard
Aquatic Chronic : Long-term (chronic) aquatic hazard

Eye Dam. : Serious eye damage Skin Corr. : Skin corrosion Skin Irrit. : Skin irritation Skin Sens. : Skin sensitisation

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture: Classification procedure:

Aquatic Chronic 3 H412 Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not

according to Regulation (EC) No. 1907/2006



SPEKTRA SILICONE IMPREGNATION

Version Revision Date: SDS Number: Date of last issue: -

1.0 19.05.2020 MAT000412397 Date of first issue: 19.05.2020

GB/EN

to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.