

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



IDEAL parquet lacquer (gloss / semi-matt)

Version	Revision Date:	SDS Number:	Date of last issue: 11.07.2024
3.0	24.10.2025	MAT0GA00_034	Date of first issue: 11.06.2020
		GB/EN	

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : IDEAL parquet lacquer (gloss / semi-matt)

Product code : Please see section 16 for detailed data

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-
stance/Mixture : , PROC10: Professional and consumer use of coatings, Roller
application or brushing
PC9a: Coatings and paints, thinners, paint removers

1.3 Details of the supplier of the safety data sheet

Company : KANSAI HELIOS Slovenija d.o.o.
Količevo 65
1230 Domžale
Slovenia

Telephone Company : 386 (1) 722 4383

Telefax Company : 386 (1) 722 4310

Responsible/issuing person : 386 (1) 722 4383
productsafety@kansai-helios.si

1.4 Emergency telephone number

Call 999 (or 112) for emergency medical attention
professionals only: National Poison Information Service (NPIS) 24h national number 0844 892
0111
consumer: National Health Service (NHS) 24h national number, England & Scotland 111

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

**Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK
SI 2019/720, and UK SI 2020/1567)**

Flammable liquids, Category 3 H226: Flammable liquid and vapour.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



IDEAL parquet lacquer (gloss / semi-matt)

Version
3.0

Revision Date:
24.10.2025

SDS Number:
MAT0GA00_034
GB/EN



Date of last issue: 11.07.2024
Date of first issue: 11.06.2020

Specific target organ toxicity - single exposure, Category 3, Central nervous system

H336: May cause drowsiness or dizziness.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Hazard pictograms	:		
Signal word	:	Warning	
Hazard statements	:	H226 H336	Flammable liquid and vapour. May cause drowsiness or dizziness.
Precautionary statements	:	P101 P102	If medical advice is needed, have product container or label at hand. Keep out of reach of children.
		Prevention:	
		P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
		P271	Use only outdoors or in a well-ventilated area.
		Response:	
		P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
		Storage:	
		P405	Store locked up.
		Disposal:	
		P501	Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label:

hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics
1-methoxy-2-propanol

Additional Labelling

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



IDEAL parquet lacquer (gloss / semi-matt)

Version 3.0 Revision Date: 24.10.2025 SDS Number: MAT0GA00_034 GB/EN Date of last issue: 11.07.2024 Date of first issue: 11.06.2020

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics	64742-48-9 919-857-5 01-2119463258-33	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) Asp. Tox. 1; H304	>= 30 - < 50
1-methoxypropan-2-ol	107-98-2 203-539-1 603-064-00-3 01-2119457435-35	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system)	>= 1 - < 10
hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics	Not Assigned 918-481-9 01-2119457273-39	Asp. Tox. 1; H304	>= 1 - < 10
ethanol	64-17-5 200-578-6 603-002-00-5 01-2119457610-43	Flam. Liq. 2; H225 Eye Irrit. 2; H319	>= 1 - < 10
fatty acids, C18, unsatd., dimers, reaction products with N,N-dimethyl-1,3- propanediamine and 1,3-propanediamine	162627-17-0 01-2119970640-38	Skin Sens. 1; H317	>= 0,1 - < 1
Substances with a workplace exposure limit :			
Silica gel	112926-00-8 01-2119379499-16		>= 1 - < 10

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



IDEAL parquet lacquer (gloss / semi-matt)

Version	Revision Date:	SDS Number:	Date of last issue: 11.07.2024
3.0	24.10.2025	MAT0GA00_034 GB/EN	Date of first issue: 11.06.2020

- If inhaled : Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

- Risks : May cause drowsiness or dizziness.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.
-

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

- Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : No hazardous combustion products are known

5.3 Advice for firefighters

- Special protective equipment : In the event of fire, wear self-contained breathing apparatus.
-

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



IDEAL parquet lacquer (gloss / semi-matt)

Version	Revision Date:	SDS Number:	Date of last issue: 11.07.2024
3.0	24.10.2025	MAT0GA00_034 GB/EN	Date of first issue: 11.06.2020

for firefighters

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



IDEAL parquet lacquer (gloss / semi-matt)

Version 3.0 Revision Date: 24.10.2025 SDS Number: MAT0GA00_034 GB/EN Date of last issue: 11.07.2024 Date of first issue: 11.06.2020

Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations. Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : For further information, refer to the product technical data sheet.

Consult the technical guidelines for the use of this substance/mixture.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
1-methoxy-2-propanol	107-98-2	TWA	100 ppm 375 mg/m ³	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	150 ppm 560 mg/m ³	GB EH40
	Further information: Can be absorbed through the skin. The assigned sub-			

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



IDEAL parquet lacquer (gloss / semi-matt)

Version
3.0

Revision Date:
24.10.2025

SDS Number:
MAT0GA00_034
GB/EN

Date of last issue: 11.07.2024
Date of first issue: 11.06.2020

	stances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		TWA	100 ppm 375 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	150 ppm 568 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
silica gel	112926-00-8	TWA (inhalable dust)	6 mg/m ³ (Silica)	GB EH40
		TWA (Respirable dust)	2,4 mg/m ³ (Silica)	GB EH40
ethanol	64-17-5	TWA	1.000 ppm 1.920 mg/m ³	GB EH40

Derived No Effect Level (DNEL)

Substance name	End Use	Exposure routes	Potential health effects	Value
hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics	Workers	Inhalation	Long-term systemic effects	1500 mg/m ³
	Consumers	Inhalation	Long-term systemic effects	900 mg/m ³
	Workers	Dermal	Long-term systemic effects	300 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	300 mg/kg bw/day
1-methoxy-2-propanol	Consumers	Oral	Long-term systemic effects	300 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	369 mg/m ³
	Workers	Inhalation	Acute systemic effects	553,5 mg/m ³
	Workers	Inhalation	Acute local effects	553,5 mg/m ³
	Workers	Inhalation	Long-term systemic effects	43,9 mg/m ³
	Workers	Dermal	Long-term systemic effects	183 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	78 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	33 mg/kg bw/day
silica gel	Workers	Inhalation	Long-term systemic effects	4 mg/m ³

Predicted No Effect Concentration (PNEC)

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



IDEAL parquet lacquer (gloss / semi-matt)

Version
3.0

Revision Date:
24.10.2025

SDS Number:
MAT0GA00_034
GB/EN

Date of last issue: 11.07.2024
Date of first issue: 11.06.2020

Substance name	Environmental Compartment	Value
1-methoxy-2-propanol	Soil	4,59 mg/kg dry weight (d.w.)
	Marine water	1 mg/l
	Fresh water	10 mg/l
	Marine sediment	5,2 mg/kg dry weight (d.w.)
	Fresh water sediment	52,3 mg/kg dry weight (d.w.)
	Sewage treatment plant	100 mg/l
	Intermittent use/release	100 mg/l

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Equipment should conform to EN 166
Eye wash bottle with pure water
Tightly fitting safety goggles

Hand protection

Gloves : Nitrile rubber (> 0,1 mm; < 60 min); ISO EN374 |
butyl-rubber (> 0,6 mm; < 240 min); ISO EN374 |
Viton® (> 0,6 mm; < 240 min); ISO EN374 |
PE laminate (> 0,1 mm; < 240 min); ISO EN374 |

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Equipment should conform to EN 14387

Filter type : Organic vapour type (A)

Protective measures : Wash thoroughly after handling.
Avoid contact with skin, eyes and clothing.
Keep away from food, drink and animal feedingstuffs.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



IDEAL parquet lacquer (gloss / semi-matt)

Version	Revision Date:	SDS Number:	Date of last issue: 11.07.2024
3.0	24.10.2025	MAT0GA00_034 GB/EN	Date of first issue: 11.06.2020

Appearance	:	liquid
Colour	:	in accordance with the product description
Odour	:	solvent-like
Odour Threshold	:	No data available
pH	:	substance/mixture is non-polar/aprotic
Melting point/freezing point	:	< 0,0 °C (calculation method (principal components, lowest value))
Boiling point/boiling range	:	155 - 192 °C (calculation method (principal components, lowest value))
Flash point	:	40 °C (calculation method (principal components, lowest value)) 30 °C
Flammability	:	Static-accumulating flammable liquid., Combustible Solids
Upper explosion limit / Upper flammability limit	:	6,1 %(V) (calculation method (principal components, highest value))
Lower explosion limit / Lower flammability limit	:	0,6 %(V) (calculation method (principal components, highest value))
Vapour pressure	:	2 hPa (calculation method (principal components, highest value))
Relative vapour density	:	No data available
Relative density	:	0,94 (calculation method (principal components, highest value))
Density	:	0,87 - 0,90 g/cm ³
Solubility(ies)	:	
Water solubility	:	insoluble
Solubility in other solvents	:	Description: miscible with most organic solvents
Partition coefficient: n-octanol/water	:	No data available
Decomposition temperature	:	No decomposition if stored and applied as directed. Hazardous decomposition products formed under fire conditions

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



IDEAL parquet lacquer (gloss / semi-matt)

Version	Revision Date:	SDS Number:	Date of last issue: 11.07.2024
3.0	24.10.2025	MAT0GA00_034 GB/EN	Date of first issue: 11.06.2020

tions.

Viscosity
Viscosity, kinematic : > 21 mm²/s (40 °C)

Flow time : 65 - 80 s at 23 °C
Method: DIN 53211 (CF4)

Explosive properties : Not applicable

Oxidizing properties : Sustains combustion

9.2 Other information

No data available
VOC : (Directive 2004/42/EC)
500 g/l

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.
Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Incompatible with strong acids and bases.

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



IDEAL parquet lacquer (gloss / semi-matt)

Version	Revision Date:	SDS Number:	Date of last issue: 11.07.2024
3.0	24.10.2025	MAT0GA00_034	Date of first issue: 11.06.2020
		GB/EN	

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified due to lack of data.

Components:

hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics:

Acute oral toxicity : LD50 Oral: 5000 milligram per kilogram

Acute inhalation toxicity : LC50 (Rat): 5,61 mg/l
Test atmosphere: vapour

Acute dermal toxicity : LD50: 2000 milligram per kilogram

1-methoxy-2-propanol:

Acute oral toxicity : LD50 Oral (Rabbit): > 2.000 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Acute oral toxicity : LD50 Oral (Rat, male and female): > 5.000 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 5.000 mg/l
Test atmosphere: vapour
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 Dermal (Rabbit, male and female): > 5.000 mg/kg
Method: OECD Test Guideline 402

ethanol:

Acute oral toxicity : LD50 Oral (Rat): >= 7.060 mg/kg

Acute inhalation toxicity : LC50 (Rat): >= 39 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Skin corrosion/irritation

Not classified due to lack of data.

Product:

Remarks : May cause skin irritation and/or dermatitis.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



IDEAL parquet lacquer (gloss / semi-matt)

Version
3.0

Revision Date:
24.10.2025

SDS Number:
MAT0GA00_034
GB/EN

Date of last issue: 11.07.2024
Date of first issue: 11.06.2020

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation
GLP : yes

Result : Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Not classified due to lack of data.

Product:

Remarks : Vapours may cause irritation to the eyes, respiratory system and the skin.

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Species : Rabbit
Method : OECD Test Guideline 405
Result : No eye irritation

ethanol:

Result : Eye irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified due to lack of data.

Respiratory sensitisation

Not classified due to lack of data.

Product:

Remarks : Causes sensitisation.

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Exposure routes : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : Not a skin sensitizer.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



IDEAL parquet lacquer (gloss / semi-matt)

Version	Revision Date:	SDS Number:	Date of last issue: 11.07.2024
3.0	24.10.2025	MAT0GA00_034 GB/EN	Date of first issue: 11.06.2020

Fatty acids, C18-unsatd., dimers, reaction products with N,N-dimethyl-1,3-propanediamine and 1,3-propanediamine:

Result : Probability or evidence of skin sensitisation in humans

Germ cell mutagenicity

Not classified due to lack of data.

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Genotoxicity in vitro : Result: negative

Genotoxicity in vivo : Result: negative

Carcinogenicity

Not classified due to lack of data.

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Result : negative

Reproductive toxicity

Not classified due to lack of data.

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Effects on foetal development : Fertility and developmental toxicity tests did not reveal any effect on reproduction.

STOT - single exposure

May cause drowsiness or dizziness.

Components:

hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics:

Assessment : May cause drowsiness or dizziness.

1-methoxy-2-propanol:

Assessment : May cause drowsiness or dizziness.

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Remarks : Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



IDEAL parquet lacquer (gloss / semi-matt)

Version
3.0

Revision Date:
24.10.2025

SDS Number:
MAT0GA00_034
GB/EN

Date of last issue: 11.07.2024
Date of first issue: 11.06.2020

STOT - repeated exposure

Not classified due to lack of data.

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Remarks : Based on available data, the classification criteria are not met.

Aspiration toxicity

Not classified due to lack of data.

Components:

hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics:

May be fatal if swallowed and enters airways.

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.
Concentrations substantially above the TLV value may cause narcotic effects.
Solvents may degrease the skin.

SECTION 12: Ecological information

12.1 Toxicity

Components:

1-methoxy-2-propanol:

Toxicity to fish : LC50 (Fish): > 1.000 mg/l
Exposure time: 96 h

Toxicity to daphnia and other : LC50 (Daphnia (water flea)): > 1.000 mg/l
aquatic invertebrates

Toxicity to algae/aquatic : LC50 (algae): > 1.000 mg/l
plants

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 1.000 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



IDEAL parquet lacquer (gloss / semi-matt)

Version	Revision Date:	SDS Number:	Date of last issue: 11.07.2024
3.0	24.10.2025	MAT0GA00_034 GB/EN	Date of first issue: 11.06.2020

Toxicity to daphnia and other aquatic invertebrates : EC50 : > 1.000 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : NOEC (Pseudokirchneriella subcapitata (microalgae)): 1.000 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

EC50 (Pseudokirchneriella subcapitata (microalgae)): > 1.000 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

ethanol:

Toxicity to fish : LC50 (Fish): \geq 13.500 mg/l

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)): \geq 5.000 mg/l

12.2 Persistence and degradability

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 80 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

12.3 Bioaccumulative potential

Components:

1-methoxy-2-propanol:

Partition coefficient: n-octanol/water : log Pow: -0,437

ethanol:

Partition coefficient: n-octanol/water : log Pow: -0,32

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



IDEAL parquet lacquer (gloss / semi-matt)

Version
3.0

Revision Date:
24.10.2025

SDS Number:
MAT0GA00_034
GB/EN

Date of last issue: 11.07.2024
Date of first issue: 11.06.2020

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Assessment : Substance is not persistent, bioaccumulative, and toxic (PBT).

12.6 Other adverse effects

Product:

Endocrine disrupting potential : This substance/mixture does not contain components considered to have endocrine disrupting properties for environment according to UK REACH Article 57(f).

Additional ecological information : No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

14.1 UN number

ADN : UN 1263
ADR : UN 1263
RID : UN 1263
IMDG : UN 1263
IATA : UN 1263

14.2 UN proper shipping name

ADN : PAINT

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



IDEAL parquet lacquer (gloss / semi-matt)

Version	Revision Date:	SDS Number:	Date of last issue: 11.07.2024
3.0	24.10.2025	MAT0GA00_034	Date of first issue: 11.06.2020
		GB/EN	

ADR : PAINT
RID : PAINT
IMDG : PAINT
IATA : Paint

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADN	: 3	
ADR	: 3	
RID	: 3	
IMDG	: 3	
IATA	: 3	

14.4 Packing group

ADN
Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

ADR
Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3
Tunnel restriction code : (D/E)

RID
Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

IMDG
Packing group : III
Labels : 3
EmS Code : F-E, S-E

IATA (Cargo)
Packing instruction (cargo aircraft) : 366
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids

IATA (Passenger)

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



IDEAL parquet lacquer (gloss / semi-matt)

Version	Revision Date:	SDS Number:	Date of last issue: 11.07.2024
3.0	24.10.2025	MAT0GA00_034 GB/EN	Date of first issue: 11.06.2020

Packing instruction (passenger aircraft) : 355
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids

14.5 Environmental hazards

ADN
Environmentally hazardous : no

ADR
Environmentally hazardous : no

RID
Environmentally hazardous : no

IMDG
Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17)	:	Conditions of restriction for the following entries should be considered: Number on list 3
UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation	:	Not applicable
The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain)	:	Not applicable
Regulation (EU) No 2024/590 on substances that deplete the ozone layer	:	Not applicable
UK REACH List of substances subject to authorisation (Annex XIV)	:	Not applicable
GB Export and import of hazardous chemicals - Prior Informed Consent (PIC) Regulation	:	Not applicable
Control of Major Accident Hazards Regulations 2015 (COMAH)	P5c	FLAMMABLE LIQUIDS

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



IDEAL parquet lacquer (gloss / semi-matt)

Version	Revision Date:	SDS Number:	Date of last issue: 11.07.2024
3.0	24.10.2025	MAT0GA00_034	Date of first issue: 11.06.2020
		GB/EN	

Volatile organic compounds : Directive 2004/42/EC
Volatile organic compounds (VOC) content: 500 g/l

Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

SECTION 16: Other information

Full text of H-Statements

H225 : Highly flammable liquid and vapour.
H226 : Flammable liquid and vapour.
H304 : May be fatal if swallowed and enters airways.
H317 : May cause an allergic skin reaction.
H319 : Causes serious eye irritation.
H336 : May cause drowsiness or dizziness.

Full text of other abbreviations

Asp. Tox. : Aspiration hazard
Eye Irrit. : Eye irritation
Flam. Liq. : Flammable liquids
Skin Sens. : Skin sensitisation
STOT SE : Specific target organ toxicity - single exposure
2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
GB EH40 : UK. EH40 WEL - Workplace Exposure Limits
2000/39/EC / TWA : Limit Value - eight hours
2000/39/EC / STEL : Short term exposure limit
GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good La-

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



IDEAL parquet lacquer (gloss / semi-matt)

Version	Revision Date:	SDS Number:	Date of last issue: 11.07.2024
3.0	24.10.2025	MAT0GA00_034 GB/EN	Date of first issue: 11.06.2020

boratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Flam. Liq. 3	H226
STOT SE 3	H336

Classification procedure:

Based on product data or assessment
Calculation method

Material codes (bulk) for which the SDS is valid : 478628; 478629

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.