According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# COLOR ACRYLIC PRIMER FOR METAL

Version	Revision Date:	SDS Number:	Date of last issue: 18.05.2020
1.1	04.03.2022	MAT000401671	Date of first issue: 18.05.2020
		GB / EN	

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### **1.1 Product identifier**

Trade name	:	COLOR ACRYLIC PRIMER FOR METAL
Product code	:	40167102

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-	: Building and construction work
stance/Mixture	Professional and consumer use of coatings, Roller application
	or brushing, Non industrial spraying Coatings and paints, thinners, paint removers

#### **1.3** Details of the supplier of the safety data sheet

Company	:	Helios TBLUS d.o.o. Količevo 65 1230 Domžale Slovenia
Telephone Company	:	386 (1) 722 4383
Telefax Company	:	386 (1) 722 4310
Responsible/issuing person	:	386 (1) 722 4383 productsafety@helios.si

#### 1.4 Emergency telephone number

Call 999 (or 112) for emergency medical attention

professionals only: National Poison Information Service (NPIS) 24h national number 0844 892 0111

consumer: National Health Service (NHS) 24h national number, England & Scotland 111

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

# Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Long-term (chronic) aquatic hazard, Cat-	H412: Harmful to aquatic life with long lasting ef-
egory 3	fects.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# COLOR ACRYLIC PRIMER FOR METAL

Version	Revision Date:	SDS Number:	Date of last issue: 18.05.2020
1.1	04.03.2022	MAT000401671	Date of first issue: 18.05.2020
		GB / EN	

#### 2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI
2019/720, and UK SI 2020/1567)

Hazard statements		H412 Ha	armful to aquatic life with long lasting effects.
Precautionary statements :	:	label at ha	medical advice is needed, have product container or and. eep out of reach of children.
		Preventio	n:
		P273 Av	void release to the environment.
		Disposal:	
		P501 Dis disposal pl	ispose of contents/ container to an approved waste lant.
Hazard statements		H412 Ha	armful to aquatic life with long lasting effects.
Precautionary statements :	:	label at ha P102 Ke	medical advice is needed, have product container or and. eep out of reach of children. ead carefully and follow all instructions.
		P273 Av	void release to the environment.
			ispose of contents/ container to an approved sposal plant.

#### **Additional Labelling**

EUH208 Contains 1,2-benzisothiazol-3(2H)-one, reaction mass of: 5-chloro-2- methyl-4isothiazolin-3-one and 2-methyl-2H -isothiazol-3- one (3:1).

May produce an allergic reaction.

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

#### **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

Chemical nature : Waterborne paint

#### Components

Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

SDS Number:

GB / EN

MAT000401671



# COLOR ACRYLIC PRIMER FOR METAL

Version 1.1 Revision Date: 04.03.2022

Date of last issue: 18.05.2020 Date of first issue: 18.05.2020

	Index-No.		
	Registration number		
2-(2-butoxyethoxy)ethanol	112-34-5 203-961-6 603-096-00-8 01-2119475104-44	Eye Irrit. 2; H319	>= 1 - < 10
trizinc bis(orthophosphate)	7779-90-0 231-944-3 030-011-00-6 01-2119485044-40	Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 1 - < 2,5
zinc oxide	1314-13-2 215-222-5 030-013-00-7 01-2119463881-32	Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 0,25 - < 1
zinc 5-nitroisophthalate	60580-61-2	Aquatic Acute 1; H400 Aquatic Chronic 2; H411	>= 0,1 - < 0,25
1,2-benzisothiazol-3(2H)-one	2634-33-5 220-120-9 613-088-00-6 01-2120761540-60	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 2; H411 	>= 0,0025 - < 0,025
mixture of 5-chloro-2-methyl-2H- isothiazol-3-one and 2-methyl-2H- isothiazol-3-one (3:1)	55965-84-9 613-167-00-5 01-2120764691-48	Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 2; H310 Skin Corr. 1C; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071 M-Factor (Acute aquatic toxicity): 100100 M-Factor (Chronic aquatic toxicity):	>= 0,0002 - < 0,0015

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# COLOR ACRYLIC PRIMER FOR METAL

rsion	Revision Date: 04.03.2022	SDS Number: MAT000401671 GB / EN	Date of last issue: 18.05.2020 Date of first issue: 18.05.2020
			100100 specific concentra- tion limit Skin Corr. 1C; H314 >= 0,6 % Skin Irrit. 2; H315 0,06 - < 0,6 % Eye Irrit. 2; H319 0,06 - < 0,6 % Skin Sens. 1A; H317 >= 0,0015 % Eye Dam. 1; H318 >= 0,6 %
Subst	ances with a workp	ace exposure limit :	
talc		14807-96- 238-877-9 01-212014	)

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

General advice	:	Do not leave the victim unattended.
If inhaled	:	If breathed in, move person into fresh air.
In case of skin contact	:	In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes.
In case of eye contact	:	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/ attention.
If swallowed	:	Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.

# 4.2 Most important symptoms and effects, both acute and delayed

None known.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# COLOR ACRYLIC PRIMER FOR METAL

Version 1.1	Revision Date: 04.03.2022	SDS Number: MAT000401671 GB / EN	Date of last issue: 18.05.2020 Date of first issue: 18.05.2020
		GB / EN	

#### **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

Suitable extinguishing media	:	Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment. Use water spray, alcohol-resistant foam, dry chemical or car- bon dioxide.
5.2 Special hazards arising from	the	e substance or mixture
Hazardous combustion prod- ucts	:	No hazardous combustion products are known.
5.3 Advice for firefighters		
Special protective equipment for firefighters	:	Wear self-contained breathing apparatus for firefighting if nec- essary.
Further information	:	The product itself does not burn. Standard procedure for chemical fires. Use a water spray to cool fully closed containers.

#### **SECTION 6: Accidental release measures**

6.1 Personal precautions, protect	ctive	e equipment and emergency procedures
Personal precautions	:	Avoid contact with skin and eyes. Do not flush into surface water or sanitary sewer system. Prevent further leakage or spillage if safe to do so.
6.2 Environmental precautions		
Environmental precautions	:	Prevent product from entering drains. If the product contaminates rivers and lakes or drains inform respective authorities.
6.3 Methods and material for cor	ntai	nment and cleaning up
Methods for cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.
6.4 Reference to other sections		

For disposal considerations see section 13., For personal protection see section 8.

:

### **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Advice on safe handling

No special technical protective measures required. For personal protection see section 8.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# COLOR ACRYLIC PRIMER FOR METAL

Versio 1.1	n Revision Date: 04.03.2022		lumber: 00401671 EN	Date of last issue: 18.05.2020 Date of first issue: 18.05.2020
	dvice on protection agair re and explosion	ist :	Normal measures fo	or preventive fire protection.
Hygiene measures		:	When using do not e handling.	eat, drink or smoke. Wash thoroughly after
7.2 Conditions for safe storage, inc			uding any incompat	tibilities
	equirements for storage reas and containers	:	kept upright to preve	e opened must be carefully resealed and ent leakage. Perishable if frozen. To main- do not store in heat or direct sunlight.
А	dvice on common storag	e :	No materials to be e	especially mentioned.
-	urther information on sto ge stability	r- :	Protect from frost.	
7.3 Sp	ecific end use(s)			
S	pecific use(s)	:	Consult the technica stance/mixture.	al guidelines for the use of this sub-

### **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

#### Derived No Effect Level (DNEL):

Substance name	End Use	Exposure routes	Potential health ef- fects	Value
Talc	Workers	Inhalation	Acute systemic ef- fects	2,16 mg/m3
	Workers	Inhalation	Acute local effects	3,6 mg/m3
	Consumers	Inhalation	Acute systemic ef- fects	1,08 mg/m3
	Consumers	Inhalation	Acute local effects	1,8 mg/m3
	Consumers	Dermal	Long-term local ef- fects	2,27 mg/cm2
	Workers	Dermal	Long-term local ef- fects	4,54 mg/cm2
	Consumers	Oral	Long-term systemic effects	160 mg/kg bw/day
	Consumers	Oral	Acute systemic ef- fects	160 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	43,2 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	21,6 mg/kg bw/day
Calcium carbonate	Workers	Inhalation	Long-term local ef- fects	4,26 mg/m3
	Consumers	Inhalation	Long-term local ef- fects	1,06 mg/m3
diiron trioxide	Workers	Inhalation	Long-term local ef-	10 mg/m3

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# COLOR ACRYLIC PRIMER FOR METAL

Version	
1.1	

Revision Date: 04.03.2022

SDS Number: MAT000401671 GB / EN Date of last issue: 18.05.2020 Date of first issue: 18.05.2020

			fects	
2-(2- butoxyethoxy)ethanol	Workers	Inhalation	Long-term systemic effects	67,5 mg/m3
	Workers	Inhalation	Long-term local ef- fects	67,5 mg/m3
	Workers	Inhalation	Acute local effects	101,2 mg/m3
	Consumers	Inhalation	Long-term systemic effects	40,5 mg/m3
	Consumers	Inhalation	Long-term local ef- fects	40,5 mg/m3
	Consumers	Inhalation	Acute local effects	60,7 mg/m3
	Workers	Dermal	Long-term systemic effects	83 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	50 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	5 mg/kg bw/day
trizinc bis(orthophosphate)	Workers	Inhalation	Long-term systemic effects	5 mg/m3
	Consumers	Inhalation	Long-term systemic effects	2,5 mg/m3
	Workers	Dermal	Long-term systemic effects	83 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	83 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	0,83 mg/kg bw/day
zinc oxide	Workers	Inhalation	Long-term systemic effects	5 mg/m3
	Workers	Inhalation	Long-term local ef- fects	0,5 mg/m3
	Consumers	Inhalation	Long-term systemic effects	2,5 mg/m3
	Workers	Dermal	Long-term systemic effects	83 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	83 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	0,83 mg/kg bw/day
1,2-benzisothiazol- 3(2H)-one	Workers	Inhalation	Long-term systemic effects	6,81 mg/m3
	Workers	Dermal	Long-term systemic effects	0,966 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	1,2 mg/m3
	Consumers	Dermal	Long-term systemic effects	0,345 mg/kg bw/day
reaction mass of: 5- chloro-2- methyl-4- isothiazolin-3-one and 2-methyl-2H -	Consumers	Inhalation	Acute local effects	0,04 mg/m3

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

SDS Number:

GB / EN

MAT000401671



# COLOR ACRYLIC PRIMER FOR METAL

Re
04

evision Date: 4.03.2022 Date of last issue: 18.05.2020 Date of first issue: 18.05.2020

isothiazol-3- one (3:1)	1			
	Workers	Inhalation	Long-term local ef- fects	0,02 mg/m3
	Workers	Inhalation	Acute local effects	0,04 mg/m3
	Consumers	Inhalation	Long-term local ef- fects	0,02 mg/m3
	Consumers	Oral	Long-term systemic effects	0,09 mg/kg bw/day
	Consumers	Oral	Acute systemic ef- fects	0,11 mg/kg bw/day

#### Predicted No Effect Concentration (PNEC):

Substance name	Environmental Compartment	Value
Talc	Marine water	141,26 mg/l
	Fresh water	597,97 mg/l
	Marine sediment	3,13 mg/kg dry
		weight (d.w.)
	Fresh water sediment	31,33 mg/kg dry
		weight (d.w.)
	Intermittent use/release	597,97 mg/l
Calcium carbonate	Sewage treatment plant	100 mg/l
2-(2-butoxyethoxy)ethanol	Soil	0,32 mg/kg dry
		weight (d.w.)
	Marine water	0,11 mg/l
	Fresh water	1,1 mg/l
	Marine sediment	0,44 mg/kg dry
		weight (d.w.)
	Fresh water sediment	4,4 mg/kg dry
		weight (d.w.)
	Sewage treatment plant	200 mg/l
	Intermittent use/release	11 mg/l
trizinc bis(orthophosphate)	Soil	35,6 mg/kg dry
		weight (d.w.)
	Marine water	0,0061 mg/l
	Fresh water	0,0206 mg/l
	Marine sediment	56,5 mg/kg dry
		weight (d.w.)
	Fresh water sediment	117,8 mg/kg dry
		weight (d.w.)
	Sewage treatment plant	0,1 mg/l
zinc oxide	Soil	35,6 mg/kg dry
		weight (d.w.)
	Marine water	0,0061 mg/l
	Fresh water	0,0206 mg/l
	Marine sediment	56,5 mg/kg dry
		weight (d.w.)
	Fresh water sediment	117,8 mg/kg dry
		weight (d.w.)
	Sewage treatment plant	0,1 mg/l
zinc 5-nitroisophthalate	Fresh water	0,0206 - 0,0808
·		mg/l

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# COLOR ACRYLIC PRIMER FOR METAL

rsion	Revision Date: 04.03.2022	SDS Number: MAT000401671 GB / EN	Date of last issu Date of first issu	
		Marine water		0,0061 - 0,0239 mg/l
		Sewage treat	ment plant	0,100 - 0,3922 mg/l
		Fresh water s	ediment	117,8 - 462 mg/kg dry weight (d.w.)
		Marine sedim	ent	56,5 - 221 mg/kg dry weight (d.w.)
		Soil		56,5 - 221 mg/kg dry weight (d.w.)
1,2-be	enzisothiazol-3(2H)-c	ne Fresh water		0,00403 mg/l
		Intermittent us	se/release	0,0011 mg/l
		Marine water		0,000403 mg/l
		Sewage treat	ment plant	1,03 mg/l
		Fresh water s		0,0499 mg/kg dry weight (d.w.)
		Marine sedim	ent	0,00499 mg/kg dry weight (d.w.)
		Soil		3 mg/kg dry weight (d.w.)
methy	on mass of: 5-chloro /l-4-isothiazolin-3-on hyl-2H -isothiazol-3-	e and		0,01 mg/kg dry weight (d.w.)
		Marine water		0,00339 mg/l
		Fresh water		0,00339 mg/l
		Marine sedim	ent	0,027 mg/kg dry weight (d.w.)
		Fresh water s	ediment	0,027 mg/kg dry weight (d.w.)
		Sewage treat	ment plant	0,23 mg/l
		Intermittent us		0,00339 mg/l

#### 8.2 Exposure controls

#### Personal protective equipment

Eye protection Hand protection	:	Goggles
Material	:	Nitrile rubber
Glove thickness	:	0,2 mm
Protective index	:	Class 3
Remarks	:	Wear suitable gloves.
Skin and body protection	:	Long sleeved clothing Choose body protection according to the amount and concen- tration of the dangerous substance at the work place.
Respiratory protection	:	No personal respiratory protective equipment normally re- quired.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# COLOR ACRYLIC PRIMER FOR METAL

Version	Revision Date:	SDS Number:	Date of last issue: 18.05.2020
1.1	04.03.2022	MAT000401671 GB / EN	Date of first issue: 18.05.2020

#### **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Appearance Colour Odour Odour Threshold	:	liquid in accordance with the product description No information available. No data available
рН	:	No data available
Flash point	:	Not applicable
Flammability (solid, gas)	:	Not applicable
Density	:	1,3 - 1,4 g/cm3
Solubility(ies) Water solubility Solubility in other solvents	:	completely miscible No data available
Partition coefficient: n- octanol/water	:	No data available
Viscosity Viscosity, kinematic	:	> 20,5 mm2/s (40 °C)

#### 9.2 Other information

No data available

#### **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

No decomposition if stored and applied as directed.

#### 10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions				
Hazardous reactions	:	No data available		
10.4 Conditions to avoid				
Conditions to avoid	:	Protect from frost, heat and sunlight.		
10.5 Incompatible materials				
Materials to avoid	:	Incompatible with oxidizing agents. Incompatible with strong acids and bases.		

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# COLOR ACRYLIC PRIMER FOR METAL

Version	Revision Date:	SDS Number:	Date of last issue: 18.05.2020
1.1	04.03.2022	MAT000401671	Date of first issue: 18.05.2020
		GB / EN	

#### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

#### **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

#### Acute toxicity

Not classified based on available information.

#### Components:

#### 2-(2-butoxyethoxy)ethanol:

Acute oral toxicity	:	LD50 Oral (Rat): >= 6.560 mg/kg
Acute dermal toxicity	:	LD50 (Rabbit): >= 4.120 mg/kg

#### trizinc bis(orthophosphate):

Acute oral toxicity :	LD50 (Rat): 5.000 mg/kg
-----------------------	-------------------------

#### 1,2-benzisothiazol-3(2H)-one:

Acute oral toxicity : Assessment: The component/mixture is moderately toxic after single ingestion.

#### Skin corrosion/irritation

Not classified based on available information.

#### Components:

#### 1,2-benzisothiazol-3(2H)-one:

Result : irritating

#### Serious eye damage/eye irritation

Not classified based on available information.

#### Components:

2-(2-butoxyethoxy)ethanol:		
Result	:	Eye irritation

#### 1,2-benzisothiazol-3(2H)-one:

Result : Corrosive

#### Respiratory or skin sensitisation

#### Skin sensitisation

Not classified based on available information.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# COLOR ACRYLIC PRIMER FOR METAL

Version	Revision Date:	SDS Number:	Date of last issue: 18.05.2020
1.1	04.03.2022	MAT000401671	Date of first issue: 18.05.2020
		GB / EN	

#### **Respiratory sensitisation**

Not classified based on available information.

#### **Components:**

1,2-benzisothiazol-3(2H)-one:

Result

: Probability or evidence of skin sensitisation in humans

#### Germ cell mutagenicity

Not classified based on available information.

#### Carcinogenicity

Not classified based on available information.

# Reproductive toxicity

Not classified based on available information.

#### STOT - single exposure

Not classified based on available information.

#### STOT - repeated exposure

Not classified based on available information.

#### Aspiration toxicity

Not classified based on available information.

#### **SECTION 12: Ecological information**

#### 12.1 Toxicity

#### Components:

<b>2-(2-butoxyethoxy)ethanol:</b> Toxicity to fish	:	LC50 (Fish): >= 2.500 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	LC50 (Daphnia (water flea)): > 1.000 mg/l Exposure time: 48 h
Toxicity to microorganisms	:	EC50 (Bacteria): > 5.000 mg/l
trizinc bis(orthophosphate):		
trizinc bis(orthophosphate): Ecotoxicology Assessment Acute aquatic toxicity		Very toxic to aquatic life.

Chronic aquatic toxicity

Very toxic to aquatic life with long lasting effects.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# COLOR ACRYLIC PRIMER FOR METAL

ersion 1	Revision Date: 04.03.2022		Number: 000401671 EN	Date of last issue: 18.05.2020 Date of first issue: 18.05.2020		
zinc c	oxide:					
Toxici	ty to fish	:	LC50 (Danio reric Exposure time: 96	o (zebra fish)): >= 1,793 mg/l 6 h		
	ty to daphnia and oth ic invertebrates	ner :	EC50 (Daphnia (\ Exposure time: 48	water flea)): >= 2,6 mg/l 8 h		
	Toxicity to algae/aquatic : plants		mg/l	IC50 (Desmodesmus subspicatus (green algae)): >= 0,136 mg/l Exposure time: 72 h		
Ecoto	oxicology Assessme	ent				
	aquatic toxicity		Very toxic to aqua	atic life.		
Chron	ic aquatic toxicity	:				
			Very toxic to aqua	atic life with long lasting effects.		
zinc 5	-nitroisophthalate:					
	oxicology Assessme aquatic toxicity		Very toxic to aqua	atic life.		
Chron	ic aquatic toxicity	:				
			Toxic to aquatic li	ife with long lasting effects.		
1,2-be	enzisothiazol-3(2H)-	one:				
Ecoto	oxicology Assessme	ent				
Chron	ic aquatic toxicity	:	Toxic to aquatic li	ife with long lasting effects.		
reacti one (3		ro-2- n	nethyl-4-isothiazo	lin-3-one and 2-methyl-2H -isothiazol-3-		
Toxici	ty to fish	:	LC50 (Salvelinus Exposure time: 96	namaycush (lake trout)): >= 10,85 mg/l 6 h		
Toxici plants	ty to algae/aquatic	:	LC50 (algae): >= Exposure time: 48			
			LC50 (algae): 0,0 Exposure time: 72			
M-Fac icity)	ctor (Acute aquatic to	<b>x-</b> :	100			

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# COLOR ACRYLIC PRIMER FOR METAL

Version	Revision Date: 04.03.2022	SDS Number:	Date of last issue: 18.05.2020
1.1		MAT000401671	Date of first issue: 18.05.2020
		GB / EN	

M-Factor (Chronic aquatic : 100 toxicity)

#### 12.2 Persistence and degradability

#### Components:

#### zinc oxide:

Biodegradability		Result: Biodegradable
Diouogradability	•	Result. Diodegradable

#### 12.3 Bioaccumulative potential

#### **Components:**

#### 1,2-benzisothiazol-3(2H)-one:

Partition coefficient: n- : log Pow: 1,3 octanol/water

#### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

#### 12.6 Other adverse effects

Ρ	ro	dι	ıct	

Endocrine disrupting poten- tial	:	The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at layels of 0.1% or higher
		levels of 0.1% or higher.

#### **SECTION 13: Disposal considerations**

13.1 Waste treatment meth	ods
Product	: Do not release the product to the aquatic environment
Contaminated packagin	: Empty containers should be taken to an approved waste han- dling site for recycling or disposal.
Waste Code	: 08 01 20, aqueous suspensions containing paint or varnish other than those mentioned in 08 01 19

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# COLOR ACRYLIC PRIMER FOR METAL

Version 1.1

Revision Date: SDS Number: 04.03.2022 MAT000401671 GB / EN

Date of last issue: 18.05.2020 Date of first issue: 18.05.2020

#### **SECTION 14: Transport information**

#### 14.1 UN number

Not regulated as a dangerous good

#### 14.2 UN proper shipping name

Not regulated as a dangerous good

#### 14.3 Transport hazard class(es)

Not regulated as a dangerous good

#### 14.4 Packing group

Not regulated as a dangerous good

#### 14.5 Environmental hazards

Not regulated as a dangerous good

#### 14.6 Special precautions for user

Not applicable

#### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

#### **SECTION 15: Regulatory information**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII)	:	Conditions of restriction for the fol- lowing entries should be considered: Number on list 3 2-(2-butoxyethoxy)ethanol (Number on list 55)
REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII)	:	Conditions of restriction for the fol- lowing entries should be considered: Number on list 3 2-(2-butoxyethoxy)ethanol (Number on list 55)
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	:	Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	:	Not applicable
Regulation (EU) 2019/1021 on persistent organic pollu- tants (recast)	:	Not applicable
Seveso III: Directive 2012/18/EU of the Euro- pean Parliament and of the Council on the control of major-accident hazards involving	Not	applicable

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# COLOR ACRYLIC PRIMER FOR METAL

Version 1.1	Revision Date: 04.03.2022	SDS Number: MAT000401671 GB / EN	Date of last issue: 18.05.2020 Date of first issue: 18.05.2020
		GD / EN	

dangerous substances.

Seveso III Directive (2012/18/	Not applicable	
by Control of Major Accident H	lazards Regula-	
tions 2015 (COMAH)	-	
Volatile organic compounds	Directive 2004/42/EC	
	Volatile organic comp	ounds (VOC) content: 50 g/l

#### Other regulations:

#### 15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

#### **SECTION 16: Other information**

#### Full text of H-Statements

H301 :	Toxic if swallowed.
H302 :	Harmful if swallowed.
H310 :	Fatal in contact with skin.
H314 :	Causes severe skin burns and eye damage.
H315 :	Causes skin irritation.
H317 :	May cause an allergic skin reaction.
H318 :	Causes serious eye damage.
H319 :	Causes serious eye irritation.
H330 :	Fatal if inhaled.
H400 :	Very toxic to aquatic life.
H410 :	Very toxic to aquatic life with long lasting effects.
H411 :	Toxic to aquatic life with long lasting effects.

#### Full text of other abbreviations

Aquatic Acute:Aquatic Chronic:Eye Dam.:Eye Irrit.:Skin Corr.:Skin Irrit.:	Acute toxicity Short-term (acute) aquatic hazard Long-term (chronic) aquatic hazard Serious eye damage Eye irritation Skin corrosion Skin irritation Skin sensitisation
Skin Sens.	Skin sensitisation

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA -European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - Interna-

#### SAFETY DATA SHEET According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# COLOR ACRYLIC PRIMER FOR METAL

Version 1.1	Revision Date: 04.03.2022	SDS Number: MAT000401671 GB / EN	Date of last issue: 18.05.2020 Date of first issue: 18.05.2020

tional Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI -Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

#### **Classification of the mixture:**

Aquatic Chronic 3 H412

Classification procedure: Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN