

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## COLOR ACRYLIC PRIMER FOR METAL

Version	Revision Date:	SDS Number:	Date of last issue: 18.05.2020
1.1	04.03.2022	MAT000401671 GB / EN	Date of first issue: 18.05.2020

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : COLOR ACRYLIC PRIMER FOR METAL  
Product code : 40167102

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-  
stance/Mixture : Building and construction work  
Professional and consumer use of coatings, Roller application  
or brushing, Non industrial spraying  
Coatings and paints, thinners, paint removers

#### 1.3 Details of the supplier of the safety data sheet

Company : KANSAI HELIOS Slovenija d.o.o.  
Količevo 65  
1230 Domžale  
Slovenia  
Telephone Company : 386 (1) 722 4383  
Telefax Company : 386 (1) 722 4310  
Responsible/issuing person : 386 (1) 722 4383  
productsafety@kansai-helios.si

#### 1.4 Emergency telephone number

Call 999 (or 112) for emergency medical attention  
professionals only: National Poison Information Service (NPIS) 24h national number 0844 892  
0111  
consumer: National Health Service (NHS) 24h national number, England & Scotland 111

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK  
SI 2019/720, and UK SI 2020/1567)**

Long-term (chronic) aquatic hazard, Cat-  
egory 3 H412: Harmful to aquatic life with long lasting ef-  
fects.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## COLOR ACRYLIC PRIMER FOR METAL

Version 1.1      Revision Date: 04.03.2022      SDS Number: MAT000401671 GB / EN      Date of last issue: 18.05.2020      Date of first issue: 18.05.2020

### 2.2 Label elements

**Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)**

Hazard statements : H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.

**Prevention:**  
P273 Avoid release to the environment.

**Disposal:**  
P501 Dispose of contents/ container to an approved waste disposal plant.

Hazard statements : H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.  
P103 Read carefully and follow all instructions.

**P273 Avoid release to the environment.**

**P501 Dispose of contents/ container to an approved waste disposal plant.**

### Additional Labelling

EUH208 Contains 1,2-benzisothiazol-3(2H)-one, reaction mass of: 5-chloro-2- methyl-4- isothiazolin-3-one and 2-methyl-2H -isothiazol-3- one (3:1).

May produce an allergic reaction.

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Chemical nature : Waterborne paint

#### Components

Chemical name	CAS-No. EC-No.	Classification	Concentration (% w/w)
---------------	-------------------	----------------	--------------------------

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## COLOR ACRYLIC PRIMER FOR METAL

Version  
1.1

Revision Date:  
04.03.2022

SDS Number:  
MAT000401671  
GB / EN

Date of last issue: 18.05.2020  
Date of first issue: 18.05.2020

	Index-No. Registration number		
2-(2-butoxyethoxy)ethanol	112-34-5 203-961-6 603-096-00-8 01-2119475104-44	Eye Irrit. 2; H319	$\geq 1 - < 10$
trizinc bis(orthophosphate)	7779-90-0 231-944-3 030-011-00-6 01-2119485044-40	Aquatic Acute 1; H400 Aquatic Chronic 1; H410	$\geq 1 - < 2,5$
zinc oxide	1314-13-2 215-222-5 030-013-00-7 01-2119463881-32	Aquatic Acute 1; H400 Aquatic Chronic 1; H410	$\geq 0,25 - < 1$
zinc 5-nitroisophthalate	60580-61-2	Aquatic Acute 1; H400 Aquatic Chronic 2; H411	$\geq 0,1 - < 0,25$
1,2-benzisothiazol-3(2H)-one	2634-33-5 220-120-9 613-088-00-6 01-2120761540-60	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 2; H411  specific concentra- tion limit Skin Sens. 1; H317 $\geq 0,05 \%$	$\geq 0,0025 - < 0,025$
mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	55965-84-9  613-167-00-5 01-2120764691-48	Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 2; H310 Skin Corr. 1C; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071  M-Factor (Acute aquatic toxicity): 100100 M-Factor (Chronic aquatic toxicity):	$\geq 0,0002 - < 0,0015$

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## COLOR ACRYLIC PRIMER FOR METAL

Version  
1.1

Revision Date:  
04.03.2022

SDS Number:  
MAT000401671  
GB / EN

Date of last issue: 18.05.2020  
Date of first issue: 18.05.2020

		100100	
		specific concentra- tion limit Skin Corr. 1C; H314 >= 0,6 % Skin Irrit. 2; H315 0,06 - < 0,6 % Eye Irrit. 2; H319 0,06 - < 0,6 % Skin Sens. 1A; H317 >= 0,0015 % Eye Dam. 1; H318 >= 0,6 %	
Substances with a workplace exposure limit :			
talc	14807-96-6 238-877-9 01-2120140278-58		>= 1 - < 10

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : Do not leave the victim unattended.
- If inhaled : If breathed in, move person into fresh air.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water.  
Remove contaminated clothing and shoes.
- In case of eye contact : IF IN EYES: Rinse cautiously with water for several minutes.  
Remove contact lenses, if present and easy to do. Continue rinsing.  
If eye irritation persists: Get medical advice/ attention.
- If swallowed : Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.

#### 4.2 Most important symptoms and effects, both acute and delayed

None known.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## COLOR ACRYLIC PRIMER FOR METAL

Version	Revision Date:	SDS Number:	Date of last issue: 18.05.2020
1.1	04.03.2022	MAT000401671 GB / EN	Date of first issue: 18.05.2020

---

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

#### 5.2 Special hazards arising from the substance or mixture

Hazardous combustion products : No hazardous combustion products are known.

#### 5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : The product itself does not burn.  
Standard procedure for chemical fires.  
Use a water spray to cool fully closed containers.

---

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Avoid contact with skin and eyes.  
Do not flush into surface water or sanitary sewer system.  
Prevent further leakage or spillage if safe to do so.

#### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.  
If the product contaminates rivers and lakes or drains inform respective authorities.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

#### 6.4 Reference to other sections

For disposal considerations see section 13., For personal protection see section 8.

---

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Advice on safe handling : No special technical protective measures required.  
For personal protection see section 8.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## COLOR ACRYLIC PRIMER FOR METAL

Version 1.1      Revision Date: 04.03.2022      SDS Number: MAT000401671 GB / EN      Date of last issue: 18.05.2020  
Date of first issue: 18.05.2020

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : When using do not eat, drink or smoke. Wash thoroughly after handling.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Containers which are opened must be carefully resealed and kept upright to prevent leakage. Perishable if frozen. To maintain product quality, do not store in heat or direct sunlight.

Advice on common storage : No materials to be especially mentioned.

Further information on storage stability : Protect from frost.

### 7.3 Specific end use(s)

Specific use(s) : Consult the technical guidelines for the use of this substance/mixture.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Derived No Effect Level (DNEL):

Substance name	End Use	Exposure routes	Potential health effects	Value
Talc	Workers	Inhalation	Acute systemic effects	2,16 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	3,6 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute systemic effects	1,08 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute local effects	1,8 mg/m <sup>3</sup>
	Consumers	Dermal	Long-term local effects	2,27 mg/cm <sup>2</sup>
	Workers	Dermal	Long-term local effects	4,54 mg/cm <sup>2</sup>
	Consumers	Oral	Long-term systemic effects	160 mg/kg bw/day
	Consumers	Oral	Acute systemic effects	160 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	43,2 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	21,6 mg/kg bw/day
Calcium carbonate	Workers	Inhalation	Long-term local effects	4,26 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local effects	1,06 mg/m <sup>3</sup>
diiron trioxide	Workers	Inhalation	Long-term local ef-	10 mg/m <sup>3</sup>

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## COLOR ACRYLIC PRIMER FOR METAL

Version  
1.1

Revision Date:  
04.03.2022

SDS Number:  
MAT000401671  
GB / EN

Date of last issue: 18.05.2020  
Date of first issue: 18.05.2020

			fects	
2-(2-butoxyethoxy)ethanol	Workers	Inhalation	Long-term systemic effects	67,5 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	67,5 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	101,2 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term systemic effects	40,5 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local effects	40,5 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute local effects	60,7 mg/m <sup>3</sup>
	Workers	Dermal	Long-term systemic effects	83 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	50 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	5 mg/kg bw/day
trizinc bis(orthophosphate)	Workers	Inhalation	Long-term systemic effects	5 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term systemic effects	2,5 mg/m <sup>3</sup>
	Workers	Dermal	Long-term systemic effects	83 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	83 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	0,83 mg/kg bw/day
zinc oxide	Workers	Inhalation	Long-term systemic effects	5 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	0,5 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term systemic effects	2,5 mg/m <sup>3</sup>
	Workers	Dermal	Long-term systemic effects	83 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	83 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	0,83 mg/kg bw/day
1,2-benzisothiazol-3(2H)-one	Workers	Inhalation	Long-term systemic effects	6,81 mg/m <sup>3</sup>
	Workers	Dermal	Long-term systemic effects	0,966 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	1,2 mg/m <sup>3</sup>
	Consumers	Dermal	Long-term systemic effects	0,345 mg/kg bw/day
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H -	Consumers	Inhalation	Acute local effects	0,04 mg/m <sup>3</sup>

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## COLOR ACRYLIC PRIMER FOR METAL

Version  
1.1

Revision Date:  
04.03.2022

SDS Number:  
MAT000401671  
GB / EN

Date of last issue: 18.05.2020  
Date of first issue: 18.05.2020

isothiazol-3- one (3:1)				
	Workers	Inhalation	Long-term local effects	0,02 mg/m3
	Workers	Inhalation	Acute local effects	0,04 mg/m3
	Consumers	Inhalation	Long-term local effects	0,02 mg/m3
	Consumers	Oral	Long-term systemic effects	0,09 mg/kg bw/day
	Consumers	Oral	Acute systemic effects	0,11 mg/kg bw/day

### Predicted No Effect Concentration (PNEC):

Substance name	Environmental Compartment	Value
Talc	Marine water	141,26 mg/l
	Fresh water	597,97 mg/l
	Marine sediment	3,13 mg/kg dry weight (d.w.)
	Fresh water sediment	31,33 mg/kg dry weight (d.w.)
	Intermittent use/release	597,97 mg/l
Calcium carbonate	Sewage treatment plant	100 mg/l
2-(2-butoxyethoxy)ethanol	Soil	0,32 mg/kg dry weight (d.w.)
	Marine water	0,11 mg/l
	Fresh water	1,1 mg/l
	Marine sediment	0,44 mg/kg dry weight (d.w.)
	Fresh water sediment	4,4 mg/kg dry weight (d.w.)
	Sewage treatment plant	200 mg/l
trizinc bis(orthophosphate)	Intermittent use/release	11 mg/l
	Soil	35,6 mg/kg dry weight (d.w.)
	Marine water	0,0061 mg/l
	Fresh water	0,0206 mg/l
	Marine sediment	56,5 mg/kg dry weight (d.w.)
	Fresh water sediment	117,8 mg/kg dry weight (d.w.)
zinc oxide	Sewage treatment plant	0,1 mg/l
	Soil	35,6 mg/kg dry weight (d.w.)
	Marine water	0,0061 mg/l
	Fresh water	0,0206 mg/l
	Marine sediment	56,5 mg/kg dry weight (d.w.)
	Fresh water sediment	117,8 mg/kg dry weight (d.w.)
zinc 5-nitroisophthalate	Sewage treatment plant	0,1 mg/l
	Fresh water	0,0206 - 0,0808 mg/l

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## COLOR ACRYLIC PRIMER FOR METAL

Version 1.1      Revision Date: 04.03.2022      SDS Number: MAT000401671      Date of last issue: 18.05.2020  
GB / EN      Date of first issue: 18.05.2020

	Marine water	0,0061 - 0,0239 mg/l
	Sewage treatment plant	0,100 - 0,3922 mg/l
	Fresh water sediment	117,8 - 462 mg/kg dry weight (d.w.)
	Marine sediment	56,5 - 221 mg/kg dry weight (d.w.)
	Soil	56,5 - 221 mg/kg dry weight (d.w.)
1,2-benzisothiazol-3(2H)-one	Fresh water	0,00403 mg/l
	Intermittent use/release	0,0011 mg/l
	Marine water	0,000403 mg/l
	Sewage treatment plant	1,03 mg/l
	Fresh water sediment	0,0499 mg/kg dry weight (d.w.)
	Marine sediment	0,00499 mg/kg dry weight (d.w.)
	Soil	3 mg/kg dry weight (d.w.)
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H -isothiazol-3- one (3:1)	Soil	0,01 mg/kg dry weight (d.w.)
	Marine water	0,00339 mg/l
	Fresh water	0,00339 mg/l
	Marine sediment	0,027 mg/kg dry weight (d.w.)
	Fresh water sediment	0,027 mg/kg dry weight (d.w.)
	Sewage treatment plant	0,23 mg/l
	Intermittent use/release	0,00339 mg/l

### 8.2 Exposure controls

#### Personal protective equipment

Eye protection : Goggles

Hand protection

Material : Nitrile rubber

Glove thickness : 0,2 mm

Protective index : Class 3

Remarks : Wear suitable gloves.

Skin and body protection : Long sleeved clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : No personal respiratory protective equipment normally required.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## COLOR ACRYLIC PRIMER FOR METAL

Version	Revision Date:	SDS Number:	Date of last issue: 18.05.2020
1.1	04.03.2022	MAT000401671	Date of first issue: 18.05.2020
		GB / EN	

---

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Appearance	:	liquid
Colour	:	in accordance with the product description
Odour	:	No information available.
Odour Threshold	:	No data available
pH	:	No data available
Flash point	:	Not applicable
Flammability (solid, gas)	:	Not applicable
Density	:	1,3 - 1,4 g/cm <sup>3</sup>
Solubility(ies)		
Water solubility	:	completely miscible
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Viscosity		
Viscosity, kinematic	:	> 20,5 mm <sup>2</sup> /s (40 °C)

#### 9.2 Other information

No data available

---

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

No decomposition if stored and applied as directed.

#### 10.2 Chemical stability

Stable under recommended storage conditions.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions	:	No data available
---------------------	---	-------------------

#### 10.4 Conditions to avoid

Conditions to avoid	:	Protect from frost, heat and sunlight.
---------------------	---	--

#### 10.5 Incompatible materials

Materials to avoid	:	Incompatible with oxidizing agents. Incompatible with strong acids and bases.
--------------------	---	--

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## COLOR ACRYLIC PRIMER FOR METAL

Version	Revision Date:	SDS Number:	Date of last issue: 18.05.2020
1.1	04.03.2022	MAT000401671 GB / EN	Date of first issue: 18.05.2020

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

Not classified based on available information.

#### Components:

##### 2-(2-butoxyethoxy)ethanol:

Acute oral toxicity : LD50 Oral (Rat):  $\geq 6.560$  mg/kg

Acute dermal toxicity : LD50 (Rabbit):  $\geq 4.120$  mg/kg

##### trizinc bis(orthophosphate):

Acute oral toxicity : LD50 (Rat): 5.000 mg/kg

##### 1,2-benzisothiazol-3(2H)-one:

Acute oral toxicity : Assessment: The component/mixture is moderately toxic after single ingestion.

#### Skin corrosion/irritation

Not classified based on available information.

#### Components:

##### 1,2-benzisothiazol-3(2H)-one:

Result : irritating

#### Serious eye damage/eye irritation

Not classified based on available information.

#### Components:

##### 2-(2-butoxyethoxy)ethanol:

Result : Eye irritation

##### 1,2-benzisothiazol-3(2H)-one:

Result : Corrosive

#### Respiratory or skin sensitisation

##### Skin sensitisation

Not classified based on available information.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## COLOR ACRYLIC PRIMER FOR METAL

Version	Revision Date:	SDS Number:	Date of last issue: 18.05.2020
1.1	04.03.2022	MAT000401671	Date of first issue: 18.05.2020
		GB / EN	

### Respiratory sensitisation

Not classified based on available information.

### Components:

#### 1,2-benzisothiazol-3(2H)-one:

Result : Probability or evidence of skin sensitisation in humans

### Germ cell mutagenicity

Not classified based on available information.

### Carcinogenicity

Not classified based on available information.

### Reproductive toxicity

Not classified based on available information.

### STOT - single exposure

Not classified based on available information.

### STOT - repeated exposure

Not classified based on available information.

### Aspiration toxicity

Not classified based on available information.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

#### 2-(2-butoxyethoxy)ethanol:

Toxicity to fish : LC50 (Fish):  $\geq 2.500$  mg/l  
Exposure time: 96 h

Toxicity to daphnia and other : LC50 (Daphnia (water flea)):  $> 1.000$  mg/l  
aquatic invertebrates Exposure time: 48 h

Toxicity to microorganisms : EC50 (Bacteria):  $> 5.000$  mg/l

#### trizinc bis(orthophosphate):

#### Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity :

Very toxic to aquatic life with long lasting effects.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## COLOR ACRYLIC PRIMER FOR METAL

Version	Revision Date:	SDS Number:	Date of last issue: 18.05.2020
1.1	04.03.2022	MAT000401671	Date of first issue: 18.05.2020
		GB / EN	

### **zinc oxide:**

Toxicity to fish : LC50 (Danio rerio (zebra fish)):  $\geq 1,793$  mg/l  
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia (water flea)):  $\geq 2,6$  mg/l  
aquatic invertebrates Exposure time: 48 h

Toxicity to algae/aquatic : IC50 (Desmodesmus subspicatus (green algae)):  $\geq 0,136$   
plants mg/l  
Exposure time: 72 h

### **Ecotoxicology Assessment**

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity :  
Very toxic to aquatic life with long lasting effects.

### **zinc 5-nitroisophthalate:**

#### **Ecotoxicology Assessment**

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity :  
Toxic to aquatic life with long lasting effects.

### **1,2-benzisothiazol-3(2H)-one:**

#### **Ecotoxicology Assessment**

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

### **reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one and 2-methyl-2H -isothiazol-3-one (3:1):**

Toxicity to fish : LC50 (Salvelinus namaycush (lake trout)):  $\geq 10,85$  mg/l  
Exposure time: 96 h

Toxicity to algae/aquatic : LC50 (algae):  $\geq 0,82$  mg/l  
plants Exposure time: 48 h

LC50 (algae): 0,018 mg/l  
Exposure time: 72 h

M-Factor (Acute aquatic tox- : 100  
icity)

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## COLOR ACRYLIC PRIMER FOR METAL

Version	Revision Date:	SDS Number:	Date of last issue: 18.05.2020
1.1	04.03.2022	MAT000401671 GB / EN	Date of first issue: 18.05.2020

---

M-Factor (Chronic aquatic toxicity) : 100

### 12.2 Persistence and degradability

#### Components:

##### **zinc oxide:**

Biodegradability : Result: Biodegradable

### 12.3 Bioaccumulative potential

#### Components:

##### **1,2-benzisothiazol-3(2H)-one:**

Partition coefficient: n-octanol/water : log Pow: 1,3

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Other adverse effects

#### Product:

Endocrine disrupting potential : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : Do not release the product to the aquatic environment

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

Waste Code : 08 01 20, aqueous suspensions containing paint or varnish other than those mentioned in 08 01 19

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## COLOR ACRYLIC PRIMER FOR METAL

Version	Revision Date:	SDS Number:	Date of last issue: 18.05.2020
1.1	04.03.2022	MAT000401671 GB / EN	Date of first issue: 18.05.2020

---

### SECTION 14: Transport information

#### 14.1 UN number

Not regulated as a dangerous good

#### 14.2 UN proper shipping name

Not regulated as a dangerous good

#### 14.3 Transport hazard class(es)

Not regulated as a dangerous good

#### 14.4 Packing group

Not regulated as a dangerous good

#### 14.5 Environmental hazards

Not regulated as a dangerous good

#### 14.6 Special precautions for user

Not applicable

#### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

---

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:  
Number on list 3  
2-(2-butoxyethoxy)ethanol (Number on list 55)

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:  
Number on list 3  
2-(2-butoxyethoxy)ethanol (Number on list 55)

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving : Not applicable

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## COLOR ACRYLIC PRIMER FOR METAL

Version	Revision Date:	SDS Number:	Date of last issue: 18.05.2020
1.1	04.03.2022	MAT000401671	Date of first issue: 18.05.2020
		GB / EN	

dangerous substances.

Seveso III Directive (2012/18/EU) implemented by Control of Major Accident Hazards Regulations 2015 (COMAH) : Not applicable

Volatile organic compounds : Directive 2004/42/EC  
Volatile organic compounds (VOC) content: 50 g/l

### Other regulations:

### 15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

## SECTION 16: Other information

### Full text of H-Statements

H301 : Toxic if swallowed.  
H302 : Harmful if swallowed.  
H310 : Fatal in contact with skin.  
H314 : Causes severe skin burns and eye damage.  
H315 : Causes skin irritation.  
H317 : May cause an allergic skin reaction.  
H318 : Causes serious eye damage.  
H319 : Causes serious eye irritation.  
H330 : Fatal if inhaled.  
H400 : Very toxic to aquatic life.  
H410 : Very toxic to aquatic life with long lasting effects.  
H411 : Toxic to aquatic life with long lasting effects.

### Full text of other abbreviations

Acute Tox. : Acute toxicity  
Aquatic Acute : Short-term (acute) aquatic hazard  
Aquatic Chronic : Long-term (chronic) aquatic hazard  
Eye Dam. : Serious eye damage  
Eye Irrit. : Eye irritation  
Skin Corr. : Skin corrosion  
Skin Irrit. : Skin irritation  
Skin Sens. : Skin sensitisation

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - Interna-

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## COLOR ACRYLIC PRIMER FOR METAL

Version	Revision Date:	SDS Number:	Date of last issue: 18.05.2020
1.1	04.03.2022	MAT000401671	Date of first issue: 18.05.2020
		GB / EN	

tional Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

### Classification of the mixture:

Aquatic Chronic 3                      H412

### Classification procedure:

Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN