

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## AVTOCOL PUTTY SOFT

Version	Revision Date:	SDS Number:	Date of last issue: 27.01.2023
1.4	13.02.2023	MAT000453447 GB/EN	Date of first issue: 16.03.2021

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : AVTOCOL PUTTY SOFT

Product code : 45344711

Unique Formula Identifier (UFI) : K0UA-H1WM-X006-5RTK

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Professional and consumer use of coatings  
Putty/filler

#### 1.3 Details of the supplier of the safety data sheet

Company : KANSAI HELIOS Slovenija d.o.o.  
Količevo 65  
1230 Domžale  
Slovenia

Telephone Company : 386 (1) 722 4383

Telefax Company : 386 (1) 722 4310

Responsible/issuing person : 386 (1) 722 4383  
productsafety@kansai-helios.si

#### 1.4 Emergency telephone number

Call 999 (or 112) for emergency medical attention

professionals only: National Poison Information Service (NPIS) 24h national number 0844 892  
0111

consumer: National Health Service (NHS) 24h national number, England & Scotland 111

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK  
SI 2019/720, and UK SI 2020/1567)**

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758




## AVTOCOL PUTTY SOFT

Version	Revision Date:	SDS Number:	Date of last issue: 27.01.2023
1.4	13.02.2023	MAT000453447 GB/EN	Date of first issue: 16.03.2021

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Reproductive toxicity, Category 2	H361d: Suspected of damaging the unborn child.
Specific target organ toxicity - repeated exposure, Category 1	H372: Causes damage to organs through prolonged or repeated exposure.

### 2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Hazard pictograms : 

Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H361d Suspected of damaging the unborn child.  
H372 Causes damage to organs through prolonged or repeated exposure.

Precautionary statements : P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.

**Prevention:**  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P260 Do not breathe mist or vapours.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

**Response:**  
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

**Storage:**  
P405 Store locked up.

**Disposal:**  
P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label:  
styrene

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## AVTOCOL PUTTY SOFT

Version 1.4      Revision Date: 13.02.2023      SDS Number: MAT000453447 GB/EN      Date of last issue: 27.01.2023  
Date of first issue: 16.03.2021

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
styrene	100-42-5  202-851-5 601-026-00-0 01-2119457861-32	Flam. Liq. 3; H226 Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Repr. 2; H361d STOT SE 3; H335 (Respiratory system) STOT RE 1; H372 (hearing organs) Asp. Tox. 1; H304 Aquatic Chronic 3; H412	>= 10 - < 20
Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-ethanol	-  911-490-9 01-2119979579-10	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Chronic 3; H412	>= 0,25 - < 1
Substances with a workplace exposure limit :			
talc	14807-96-6  238-877-9 01-2120140278-58		>= 20 - < 30

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## AVTOCOL PUTTY SOFT

Version	Revision Date:	SDS Number:	Date of last issue: 27.01.2023
1.4	13.02.2023	MAT000453447 GB/EN	Date of first issue: 16.03.2021

---

- In case of skin contact : If skin irritation persists, call a physician.  
If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.

### 4.2 Most important symptoms and effects, both acute and delayed

- Risks : Causes skin irritation.  
Causes serious eye irritation.  
Suspected of damaging the unborn child.  
Causes damage to organs through prolonged or repeated exposure.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.
- 

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

- Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

- Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : No hazardous combustion products are known

### 5.3 Advice for firefighters

- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## AVTOCOL PUTTY SOFT

Version	Revision Date:	SDS Number:	Date of last issue: 27.01.2023
1.4	13.02.2023	MAT000453447 GB/EN	Date of first issue: 16.03.2021

---

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.

---

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

#### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

#### 6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

---

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol.  
Do not breathe vapours/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Open drum carefully as content may be under pressure.  
Dispose of rinse water in accordance with local and national

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## AVTOCOL PUTTY SOFT

Version 1.4      Revision Date: 13.02.2023      SDS Number: MAT000453447 GB/EN      Date of last issue: 27.01.2023  
Date of first issue: 16.03.2021

- regulations.  
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.
- Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage stability : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

- Specific use(s) : For further information, refer to the product technical data sheet.
- Consult the technical guidelines for the use of this substance/mixture.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Derived No Effect Level (DNEL):

Substance name	End Use	Exposure routes	Potential health effects	Value
Talc	Workers	Inhalation	Acute systemic effects	2,16 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	3,6 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute systemic effects	1,08 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute local effects	1,8 mg/m <sup>3</sup>
	Consumers	Dermal	Long-term local effects	2,27 mg/cm <sup>2</sup>
	Workers	Dermal	Long-term local effects	4,54 mg/cm <sup>2</sup>
	Consumers	Oral	Long-term systemic effects	160 mg/kg bw/day
	Consumers	Oral	Acute systemic effects	160 mg/kg bw/day

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## AVTOCOL PUTTY SOFT

Version  
1.4

Revision Date:  
13.02.2023

SDS Number:  
MAT000453447  
GB/EN

Date of last issue: 27.01.2023  
Date of first issue: 16.03.2021

	Workers	Dermal	Long-term systemic effects	43,2 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	21,6 mg/kg bw/day
styrene	Workers	Inhalation	Acute systemic effects	100 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	100 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term systemic effects	85 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute systemic effects	10 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute local effects	10 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term systemic effects	1 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	100 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	1 mg/m <sup>3</sup>
	Workers	Dermal	Long-term systemic effects	406 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	343 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	0,0077 mg/kg bw/day
barium sulfate	Consumers	Inhalation	Long-term systemic effects	10 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term systemic effects	10 mg/m <sup>3</sup>
	Consumers	Oral	Long-term systemic effects	13000 mg/kg bw/day
titanium dioxide	Workers	Inhalation	Long-term local effects	10 mg/m <sup>3</sup>
	Consumers	Oral	Long-term systemic effects	700 mg/kg bw/day

### Predicted No Effect Concentration (PNEC):

Substance name	Environmental Compartment	Value
Talc	Marine water	141,26 mg/l
	Fresh water	597,97 mg/l
	Marine sediment	3,13 mg/kg dry weight (d.w.)
	Fresh water sediment	31,33 mg/kg dry weight (d.w.)
	Intermittent use/release	597,97 mg/l
styrene	Soil	0,146 - 0,200 mg/kg dry weight (d.w.)
	Marine water	0,014 - 0,040 mg/l
	Fresh water	0,028 - 0,040 mg/l

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## AVTOCOL PUTTY SOFT

Version  
1.4

Revision Date:  
13.02.2023

SDS Number:  
MAT000453447  
GB/EN

Date of last issue: 27.01.2023  
Date of first issue: 16.03.2021

	Marine sediment	0,307 - 0,418 mg/kg dry weight (d.w.)
	Fresh water sediment	0,418 - 0,614 mg/kg dry weight (d.w.)
	Sewage treatment plant	5 mg/l
barium sulfate	Soil	207,7 mg/kg dry weight (d.w.)
	Fresh water	0,115 mg/l
	Fresh water sediment	600,4 mg/kg dry weight (d.w.)
	Sewage treatment plant	62,2 mg/l
titanium dioxide	Soil	100 mg/kg dry weight (d.w.)
	Marine water	0,0184 mg/l
	Fresh water	0,184 mg/l
	Marine sediment	100 mg/kg dry weight (d.w.)
	Fresh water sediment	1000 mg/kg dry weight (d.w.)
	Sewage treatment plant	100 mg/l
	Intermittent use/release	0,193 mg/l

### 8.2 Exposure controls

#### Personal protective equipment

Eye/face protection : Equipment should conform to EN 166  
Eye wash bottle with pure water  
Tightly fitting safety goggles  
Wear face-shield and protective suit for abnormal processing  
problems.

Hand protection

Remarks : The suitability for a specific workplace should be discussed  
with the producers of the protective gloves.  
Please observe the instructions regarding permeability and  
breakthrough time which are provided by the supplier of the  
gloves. Also take into consideration the specific local condi-  
tions under which the product is used, such as the danger of  
cuts, abrasion, and the contact time.

Skin and body protection : Impervious clothing  
Choose body protection according to the amount and concen-  
tration of the dangerous substance at the work place.

Respiratory protection : Use respiratory protection unless adequate local exhaust ven-  
tilation is provided or exposure assessment demonstrates that  
exposures are within recommended exposure guidelines.  
Equipment should conform to EN 143

Filter type : Particulates type (P)  
Protective measures : Wash thoroughly after handling.  
Avoid contact with skin, eyes and clothing.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## AVTOCOL PUTTY SOFT

Version	Revision Date:	SDS Number:	Date of last issue: 27.01.2023
1.4	13.02.2023	MAT000453447 GB/EN	Date of first issue: 16.03.2021

Keep away from food, drink and animal feedingstuffs.

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Appearance	:	liquid
Colour	:	in accordance with the product description
Odour	:	solvent-like
Odour Threshold	:	No data available
pH	:	No data available
Melting point/freezing point	:	-31,0 °C (calculation method (principal components, lowest value))
Boiling point/boiling range	:	145 °C (calculation method (principal components, lowest value))
Flash point	:	31 °C (calculation method (principal components, lowest value))
Flammability (solid, gas)	:	Static-accumulating flammable liquid., Combustible Solids
Upper explosion limit / Upper flammability limit	:	8 %(V) (calculation method (principal components, highest value))
Lower explosion limit / Lower flammability limit	:	1,1 %(V) (calculation method (principal components, highest value))
Relative vapour density	:	3,6 (calculation method (principal components, highest value)) (Air = 1.0)
Density	:	1,71 - 1,86 g/cm <sup>3</sup>
Solubility(ies)	:	
Water solubility	:	insoluble
Solubility in other solvents	:	Description: miscible with most organic solvents
Partition coefficient: n-octanol/water	:	log Pow: 2,95 (calculation method (principal components, highest value))
Auto-ignition temperature	:	490 °C (calculation method (principal components, highest value))
Decomposition temperature	:	No decomposition if stored and applied as directed.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## AVTOCOL PUTTY SOFT

Version	Revision Date:	SDS Number:	Date of last issue: 27.01.2023
1.4	13.02.2023	MAT000453447 GB/EN	Date of first issue: 16.03.2021

Hazardous decomposition products formed under fire conditions.

Viscosity  
Viscosity, kinematic : > 20,5 mm<sup>2</sup>/s (40 °C)

Explosive properties : Not applicable

Oxidizing properties : Sustains combustion

### 9.2 Other information

No data available  
VOC : (Directive 2004/42/EC)  
250 g/l

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

### 10.5 Incompatible materials

Materials to avoid : Not applicable

### 10.6 Hazardous decomposition products

Adequate ventilation is required.

Heating can release vapours which can be ignited.

Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

Not classified based on available information.

#### Product:

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## AVTOCOL PUTTY SOFT

Version	Revision Date:	SDS Number:	Date of last issue: 27.01.2023
1.4	13.02.2023	MAT000453447 GB/EN	Date of first issue: 16.03.2021

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method

### Components:

#### **styrene:**

Acute oral toxicity : LD50 Oral (Rat): >= 5.000 mg/kg  
Acute inhalation toxicity : LC50 (Rat): >= 24 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Acute dermal toxicity : LD50 (Rabbit): > 2.650 mg/kg

#### **Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-ethanol:**

Acute oral toxicity : Assessment: The component/mixture is moderately toxic after single ingestion.

#### **Skin corrosion/irritation**

Causes skin irritation.

#### Product:

Remarks : May cause skin irritation and/or dermatitis.

### Components:

#### **styrene:**

Result : irritating

#### **Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-ethanol:**

Result : Irritating to skin.

#### **Serious eye damage/eye irritation**

Causes serious eye irritation.

#### Product:

Remarks : May cause irreversible eye damage.

### Components:

#### **styrene:**

Result : Eye irritation

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## AVTOCOL PUTTY SOFT

Version	Revision Date:	SDS Number:	Date of last issue: 27.01.2023
1.4	13.02.2023	MAT000453447 GB/EN	Date of first issue: 16.03.2021

### Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-ethanol:

Result : Irreversible effects on the eye

### Respiratory or skin sensitisation

#### Skin sensitisation

Not classified based on available information.

#### Respiratory sensitisation

Not classified based on available information.

#### Product:

Remarks : Causes sensitisation.

#### Components:

### Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-ethanol:

Result : Probability or evidence of skin sensitisation in humans

### Germ cell mutagenicity

Not classified based on available information.

### Carcinogenicity

Not classified based on available information.

### Reproductive toxicity

Suspected of damaging the unborn child.

#### Components:

##### styrene:

Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments.

### STOT - single exposure

Not classified based on available information.

#### Components:

##### styrene:

Assessment : May cause respiratory irritation.

### STOT - repeated exposure

Causes damage to organs through prolonged or repeated exposure.

#### Components:

##### styrene:

Assessment : Causes damage to organs through prolonged or repeated

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## AVTOCOL PUTTY SOFT

Version	Revision Date:	SDS Number:	Date of last issue: 27.01.2023
1.4	13.02.2023	MAT000453447 GB/EN	Date of first issue: 16.03.2021

exposure.

### Aspiration toxicity

Not classified based on available information.

### Components:

#### styrene:

May be fatal if swallowed and enters airways.

### Further information

#### Product:

Remarks : Solvents may degrease the skin.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

#### styrene:

Toxicity to fish : LC50 (Fish):  $\geq 10 - 12$  mg/l

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)):  $\geq 4,7$  mg/l

#### Ecotoxicology Assessment

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

#### Reaction mass of 2,2'-[[4-methylphenyl]imino]bisethanol and 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-ethanol:

#### Ecotoxicology Assessment

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

### 12.2 Persistence and degradability

#### Components:

#### styrene:

Biodegradability : Test Type: aerobic  
Remarks: Readily biodegradable.

Test Type: anaerobic  
Remarks: According to the results of tests of biodegradability this product is not readily biodegradable.

Physico-chemical removabil- : Remarks: The product evaporates readily.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## AVTOCOL PUTTY SOFT

Version	Revision Date:	SDS Number:	Date of last issue: 27.01.2023
1.4	13.02.2023	MAT000453447 GB/EN	Date of first issue: 16.03.2021

---

ity	Readily biodegradable.
Stability in water	: Remarks: Hydrolyses slowly.
Photodegradation	: Remarks: Decomposes rapidly in contact with light.

### 12.3 Bioaccumulative potential

#### Components:

##### **styrene:**

Bioaccumulation	: Remarks: Bioaccumulation is unlikely.
Partition coefficient: n-octanol/water	: log Pow: 2,95

### 12.4 Mobility in soil

#### Components:

##### **styrene:**

Mobility	: Medium: Air Content: 98,6 %
	: Medium: Water Content: 1,21 %
	: Medium: Sediment Content: 0,09 %
	: Medium: Soil Content: 0,09 %

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment	: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.
------------	--

### 12.6 Other adverse effects

#### Product:

Endocrine disrupting potential	: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
Additional ecological information	: No data available

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## AVTOCOL PUTTY SOFT

Version	Revision Date:	SDS Number:	Date of last issue: 27.01.2023
1.4	13.02.2023	MAT000453447 GB/EN	Date of first issue: 16.03.2021

---

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

Product	:	Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.
Contaminated packaging	:	Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.
Waste Code	:	08 01 11, waste paint and varnish containing organic solvents or other hazardous substances

---

### SECTION 14: Transport information

#### 14.1 UN number

ADN	:	UN 3269
ADR	:	UN 3269
RID	:	UN 3269
IMDG	:	UN 3269
IATA	:	UN 3269

#### 14.2 UN proper shipping name

ADN	:	POLYESTER RESIN KIT
ADR	:	POLYESTER RESIN KIT
RID	:	POLYESTER RESIN KIT
IMDG	:	POLYESTER RESIN KIT
IATA	:	Polyester resin kit

#### 14.3 Transport hazard class(es)

ADN	:	3
ADR	:	3
RID	:	3
IMDG	:	3
IATA	:	3

#### 14.4 Packing group

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## AVTOCOL PUTTY SOFT

Version	Revision Date:	SDS Number:	Date of last issue: 27.01.2023
1.4	13.02.2023	MAT000453447 GB/EN	Date of first issue: 16.03.2021

---

### ADN

Packing group : III  
Classification Code : F3  
Labels : 3

### ADR

Packing group : III  
Classification Code : F3  
Labels : 3  
Tunnel restriction code : (E)

### RID

Packing group : III  
Classification Code : F3  
Hazard Identification Number : 30  
Labels : 3

### IMDG

Packing group : III  
Labels : 3  
EmS Code : F-E, S-D

### IATA (Cargo)

Packing instruction (cargo aircraft) : 370  
Packing instruction (LQ) : Y370  
Packing group : III  
Labels : Flammable Liquids

### IATA (Passenger)

Packing instruction (passenger aircraft) : 370  
Packing instruction (LQ) : Y370  
Packing group : III  
Labels : Flammable Liquids

## 14.5 Environmental hazards

### ADN

Environmentally hazardous : no

### ADR

Environmentally hazardous : no

### RID

Environmentally hazardous : no

### IMDG

Marine pollutant : no

## 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## AVTOCOL PUTTY SOFT

Version	Revision Date:	SDS Number:	Date of last issue: 27.01.2023
1.4	13.02.2023	MAT000453447 GB/EN	Date of first issue: 16.03.2021

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17) : Conditions of restriction for the following entries should be considered: Solvent naphtha (petroleum), light arom.; Low boiling point naphtha - unspecified (Number on list 29, 28)

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 75, 3

If you intend to use this product as tattoo ink, please contact your vendor.

UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation : Not applicable

The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

UK REACH List of substances subject to authorisation (Annex XIV) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P5c FLAMMABLE LIQUIDS

Control of Major Accident Hazards Regulations 2015 (COMAH) P5c FLAMMABLE LIQUIDS

Volatile organic compounds : Directive 2004/42/EC  
Volatile organic compounds (VOC) content: 250 g/l

#### Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## AVTOCOL PUTTY SOFT

Version	Revision Date:	SDS Number:	Date of last issue: 27.01.2023
1.4	13.02.2023	MAT000453447	Date of first issue: 16.03.2021
		GB/EN	

### 15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

### SECTION 16: Other information

#### Full text of H-Statements

H226	: Flammable liquid and vapour.
H302	: Harmful if swallowed.
H304	: May be fatal if swallowed and enters airways.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H335	: May cause respiratory irritation.
H361d	: Suspected of damaging the unborn child.
H372	: Causes damage to organs through prolonged or repeated exposure.
H412	: Harmful to aquatic life with long lasting effects.

#### Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Eye Dam.	: Serious eye damage
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Repr.	: Reproductive toxicity
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitisation
STOT RE	: Specific target organ toxicity - repeated exposure
STOT SE	: Specific target organ toxicity - single exposure

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified;

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## AVTOCOL PUTTY SOFT

Version	Revision Date:	SDS Number:	Date of last issue: 27.01.2023
1.4	13.02.2023	MAT000453447 GB/EN	Date of first issue: 16.03.2021

NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECl - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

### Further information

#### Classification of the mixture:

Flam. Liq. 3	H226
Skin Irrit. 2	H315
Eye Irrit. 2	H319
Repr. 2	H361d
STOT RE 1	H372

#### Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN