

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

{ error: graphic file not  
found:  
C:\WWI\graphics\01\_H  
ELIOS TBLUS.JPG }

## COLOR NITRO THINNER

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09.11.2020	MAT000478623	Date of first issue: 09.11.2020
		GB / EN	

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Product code : 47862302

Trade name : COLOR NITRO THINNER

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-  
stance/Mixture : Professional and consumer use of coatings  
PC9a Coatings and paints, thinners, paint removers

#### 1.3 Details of the supplier of the safety data sheet

Company : Helios TBLUS d.o.o.  
Količevo 65  
1230 Domžale  
Slovenia

Telephone Company : 00386 1 722 4383

Telefax Company : 1 722 4310

Responsible/issuing person : 00386 1 722 4383  
productsafety@helios.si

#### 1.4 Emergency telephone number

Call 999 for emergency medical attention

professionals only: National Poison Information Service (NPIS) 24h national number 0844 892 0111

consumer: National Health Service (NHS) 24h national number, England & Scotland 111

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2	H225: Highly flammable liquid and vapour.
Skin irritation, Category 2	H315: Causes skin irritation.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Reproductive toxicity, Category 2	H361d: Suspected of damaging the unborn child.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

{ error: graphic file not  
found:  
C:\WWI\graphics\01\_H  
ELIOS TBLUS.JPG }

## COLOR NITRO THINNER

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09.11.2020	MAT000478623	Date of first issue: 09.11.2020
		GB / EN	

Specific target organ toxicity - single exposure, Category 3, Central nervous system

H336: May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure, Category 2

H373: May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard, Category 1

H304: May be fatal if swallowed and enters airways.

Long-term (chronic) aquatic hazard, Category 3

H412: Harmful to aquatic life with long lasting effects.

### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements :

- H225 Highly flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H336 May cause drowsiness or dizziness.
- H361d Suspected of damaging the unborn child.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H412 Harmful to aquatic life with long lasting effects.

Precautionary statements :

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.

#### Prevention:

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

#### Response:

- P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
- P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

{ error: graphic file not  
found:  
C:\WWI\graphics\01\_H  
ELIOS TBLUS.JPG }

## COLOR NITRO THINNER

Version  
1.0

Revision Date:  
09.11.2020

SDS Number:  
MAT000478623  
GB / EN

Date of last issue: -  
Date of first issue: 09.11.2020

P331 Do NOT induce vomiting.  
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

### Storage:

P405 Store locked up.

### Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label:

acetone  
toluene  
hydrocarbons, C6-C7, isoalkanes, cyclic, <5% n-hexane  
butan-1-ol

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Chemical nature : Paint related material

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
acetone	67-64-1 200-662-2 606-001-00-8 01-2119471330-49	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	>= 30 - < 50
toluene	108-88-3 203-625-9 601-021-00-3 01-2119471310-51	Flam. Liq. 2; H225 Skin Irrit. 2; H315 Repr. 2; H361d STOT SE 3; H336 STOT RE 2; H373 Asp. Tox. 1; H304 Aquatic Chronic 3; H412	>= 30 - < 50
hydrocarbons, C6-C7, isoalkanes, cyclic, <5% n-hexane	- 01-2119486291-36	Flam. Liq. 2; H225 STOT SE 3; H336 Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>= 10 - < 20
n-butyl acetate	123-86-4 204-658-1	Flam. Liq. 3; H226 STOT SE 3; H336	>= 1 - < 10

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

{ error: graphic file not  
found:

C:\WWI\graphics\01\_H  
ELIOS TBLUS.JPG }

## COLOR NITRO THINNER

Version  
1.0

Revision Date:  
09.11.2020

SDS Number:  
MAT000478623  
GB / EN

Date of last issue: -  
Date of first issue: 09.11.2020

	607-025-00-1 01-2119485493-29		
butan-1-ol	71-36-3 200-751-6 603-004-00-6 01-2119484630-38	Flam. Liq. 3; H226 Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H336 STOT SE 3; H335	>= 3 - < 10
n-hexane	110-54-3 203-777-6 601-037-00-0 01-2119480412-44	Flam. Liq. 2; H225 Skin Irrit. 2; H315 Repr. 2; H361f STOT SE 3; H336 STOT RE 2; H373 Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>= 0,25 - < 1

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.  
Symptoms of poisoning may appear several hours later.  
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.  
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If skin irritation persists, call a physician.  
If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.  
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
Continue rinsing eyes during transport to hospital.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do NOT induce vomiting.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

{ error: graphic file not  
found:  
C:\WWI\graphics\01\_H  
ELIOS TBLUS.JPG }

## COLOR NITRO THINNER

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09.11.2020	MAT000478623	Date of first issue: 09.11.2020
		GB / EN	

### 4.2 Most important symptoms and effects, both acute and delayed

Risks	: May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye damage. May cause drowsiness or dizziness. Suspected of damaging the unborn child. May cause damage to organs through prolonged or repeated exposure.
	May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye damage. May cause drowsiness or dizziness. Suspected of damaging the unborn child. May cause damage to organs through prolonged or repeated exposure.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment	: Treat symptomatically.
-----------	--------------------------

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media	: Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical
Unsuitable extinguishing media	: High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting	: Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	: No hazardous combustion products are known

### 5.3 Advice for firefighters

Special protective equipment for firefighters	: In the event of fire, wear self-contained breathing apparatus.
Further information	: Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, non-combustible vessels with product should be stored separately in closed containments. Use a water spray to cool fully closed containers.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

{ error: graphic file not  
found:  
C:\WWI\graphics\01\_H  
ELIOS TBLUS.JPG }

## COLOR NITRO THINNER

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09.11.2020	MAT000478623	Date of first issue: 09.11.2020
		GB / EN	

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Ensure adequate ventilation.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

#### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

#### 6.4 Reference to other sections

For disposal considerations see section 13., For personal protection see section 8.

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol.  
Do not breathe vapours/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Container may be opened only under exhaust ventilation hood.  
Open drum carefully as content may be under pressure.  
To avoid spills during handling keep bottle on a metal tray.  
Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

{ error: graphic file not  
found:  
C:\WWI\graphics\01\_H  
ELIOS TBLUS.JPG }

## COLOR NITRO THINNER

Version  
1.0

Revision Date:  
09.11.2020

SDS Number:  
MAT000478623  
GB / EN

Date of last issue: -  
Date of first issue: 09.11.2020

Use only explosion-proof equipment.  
Keep away from open flames, hot surfaces and sources of  
ignition.

Hygiene measures : When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : No smoking.  
Keep container tightly closed in a dry and well-ventilated  
place.  
Containers which are opened must be carefully resealed and  
kept upright to prevent leakage.  
Observe label precautions.  
Electrical installations / working materials must comply with  
the technological safety standards.

Further information on stor- : No decomposition if stored and applied as directed.  
age stability

### 7.3 Specific end use(s)

Specific use(s) : Consult the technical guidelines for the use of this sub-  
stance/mixture.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
acetone	67-64-1	TWA	500 ppm 1.210 mg/m3	2000/39/EC
Further information	Indicative			
		TWA	500 ppm 1.210 mg/m3	GB EH40
		STEL	1.500 ppm 3.620 mg/m3	GB EH40
toluene	108-88-3	TWA	50 ppm 192 mg/m3	2006/15/EC
Further information	Indicative, Identifies the possibility of significant uptake through the skin			
		STEL	100 ppm 384 mg/m3	2006/15/EC
Further information	Indicative, Identifies the possibility of significant uptake through the skin			
		TWA	50 ppm 191 mg/m3	GB EH40
Further information	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

{ error: graphic file not

found:

C:\WWI\graphics\01\_H  
ELIOS TBLUS.JPG }

## COLOR NITRO THINNER

Version  
1.0

Revision Date:  
09.11.2020

SDS Number:  
MAT000478623  
GB / EN

Date of last issue: -  
Date of first issue: 09.11.2020

		STEL	100 ppm 384 mg/m3	GB EH40
Further information	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
n-butyl acetate	123-86-4	TWA	150 ppm 724 mg/m3	GB EH40
		STEL	200 ppm 966 mg/m3	GB EH40
butan-1-ol	71-36-3	STEL	50 ppm 154 mg/m3	GB EH40
Further information	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
n-hexane	110-54-3	TWA	20 ppm 72 mg/m3	2006/15/EC
Further information	Indicative			
		TWA	20 ppm 72 mg/m3	GB EH40
Further information	Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.			

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
toluene	Workers	Inhalation	Long-term systemic effects	192 mg/m3
	Workers	Inhalation	Long-term local effects	192 mg/m3
	Consumers	Inhalation	Acute systemic effects	226 mg/m3
	Consumers	Inhalation	Acute local effects	226 mg/m3
n-butyl acetate	Workers	Inhalation	Acute systemic effects	600 mg/m3
	Workers	Inhalation	Acute local effects	600 mg/m3
	Workers	Inhalation	Long-term systemic effects	48 mg/m3
	Workers	Inhalation	Long-term local effects	300 mg/m3
	Consumers	Inhalation	Acute systemic effects	300 mg/m3
	Consumers	Inhalation	Acute local effects	300 mg/m3
	Consumers	Inhalation	Long-term systemic effects	12 mg/m3
	Consumers	Inhalation	Long-term local effects	35,7 mg/m3
	Consumers	Dermal	Long-term systemic effects	3,4 mg/kg bw/day
	Consumers	Dermal	Acute systemic effects	6 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	2 mg/kg bw/day
	Consumers	Oral	Acute systemic effects	2 mg/kg



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

{ error: graphic file not

found:

C:\WWW\graphics\01\_H

ELIOS TBLUS.JPG }

## COLOR NITRO THINNER

Version  
1.0

Revision Date:  
09.11.2020

SDS Number:  
MAT000478623  
GB / EN

Date of last issue: -  
Date of first issue: 09.11.2020

			fects	bw/day
	Workers	Dermal	Long-term systemic effects	7 mg/kg bw/day
	Workers	Dermal	Acute systemic effects	11 mg/kg bw/day
acetone	Consumers	Inhalation	Long-term systemic effects	200 mg/m3
	Workers	Inhalation	Acute local effects	2420 mg/m3
	Workers	Inhalation	Long-term systemic effects	1210 mg/m3
	Consumers	Oral	Long-term systemic effects	62 mg/kg
	Consumers	Dermal	Long-term systemic effects	62 mg/kg
	Workers	Dermal	Long-term systemic effects	186 mg/kg
butan-1-ol	Workers	Inhalation	Long-term local effects	310 mg/m3
	Consumers	Inhalation	Long-term systemic effects	55,357 mg/m3
	Consumers	Inhalation	Long-term local effects	155 mg/m3
	Consumers	Dermal	Long-term systemic effects	3,125 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	1,562 mg/kg bw/day
hydrocarbons, C6-C7, isoalkanes, cyclic, <5% n-hexane	Workers	Inhalation	Long-term systemic effects	5306 mg/m3
	Consumers	Inhalation	Long-term systemic effects	1131 mg/m3
	Consumers	Oral	Long-term systemic effects	1301 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	13964 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	1377 mg/kg bw/day

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
toluene	Soil	2,89 mg/kg dry weight (d.w.)
	Marine water	0,68 mg/l
	Fresh water	0,68 mg/l
	Marine sediment	16,39 mg/kg dry weight (d.w.)
	Fresh water sediment	16,39 mg/kg dry weight (d.w.)
	Sewage treatment plant	13,61 mg/l
	Intermittent use/release	0,68 mg/l
n-butyl acetate	Soil	0,0903 mg/kg dry weight (d.w.)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

{ error: graphic file not  
found:  
C:\WWI\graphics\01\_H  
ELIOS TBLUS.JPG }

## COLOR NITRO THINNER

Version  
1.0

Revision Date:  
09.11.2020

SDS Number:  
MAT000478623  
GB / EN

Date of last issue: -  
Date of first issue: 09.11.2020

	Marine water	0,018 mg/l
	Fresh water	0,18 mg/l
	Marine sediment	0,0981 mg/kg dry weight (d.w.)
	Fresh water sediment	0,981 mg/kg dry weight (d.w.)
	Sewage treatment plant	35,6 mg/l
	Intermittent use/release	0,36 mg/l
acetone	Soil	29,5 mg/kg
	Marine water	1,06 mg/l
	Fresh water	10,6 mg/l
	Marine sediment	3,04 mg/l
	Fresh water sediment	30,4 mg/l
	Sewage treatment plant	100 mg/l
butan-1-ol	Soil	0,0166 mg/kg dry weight (d.w.)
	Marine water	0,0082 mg/l
	Fresh water	0,082 mg/l
	Marine sediment	0,0324 mg/kg dry weight (d.w.)
	Fresh water sediment	0,324 mg/kg dry weight (d.w.)
	Sewage treatment plant	2476 mg/l
	Intermittent use/release	2,25 mg/l

### 8.2 Exposure controls

#### Personal protective equipment

Eye protection : Eye wash bottle with pure water

Safety glasses with side-shields conforming to EN166

Hand protection

Directive : Equipment should conform to EN 374

Material : Gloves composed of the following material are recommended:

Material : butyl-rubber

Material : PVA

Remarks : The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other.  
The obtained break through times according to EN 374 Part III are not measured under normal operating conditions.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

{ error: graphic file not  
found:  
C:\WWI\graphics\01\_H  
ELIOS TBLUS.JPG }

## COLOR NITRO THINNER

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09.11.2020	MAT000478623	Date of first issue: 09.11.2020
		GB / EN	

Therefore a maximum usage time of 50% of the break through time is recommended.  
Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.  
Nitrile gloves are not suitable.  
Take note of the information given by the producer concerning permeability, degradation and break through times, and of special work

Skin and body protection : Long sleeved clothing

Safety shoes

Respiratory protection : In case of inadequate ventilation wear respiratory protection.

EN-143; EN-149; EN-529

Filter type : A/P2

No personal respiratory protective equipment normally required.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : in accordance with the product description

Odour : solvent-like

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : Not applicable

Flash point : 5 °C

Method: ISO 3679, closed cup

Upper explosion limit / Upper flammability limit : 13 %(V)(calculation method (principal components, highest value))

Lower explosion limit / Lower flammability limit : 1,2 %(V)(calculation method (principal components, lowest value))

Vapour pressure : 233 hPa(calculation method (principal components, highest value))  
(20 °C)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

{ error: graphic file not  
found:  
C:\WWI\graphics\01\_H  
ELIOS TBLUS.JPG }

## COLOR NITRO THINNER

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09.11.2020	MAT000478623	Date of first issue: 09.11.2020
		GB / EN	

Density	:	0,85 g/cm3
Solubility(ies)	:	
Water solubility	:	immiscible, partly soluble
Solubility in other solvents	:	Description: miscible with most organic solvents
Partition coefficient: n-octanol/water	:	log Pow: 2,65 (calculation method (principal components, highest value))
Ignition temperature	:	425 °C (calculation method (principal components, lowest value))
Decomposition temperature	:	No decomposition if stored and applied as directed. Hazardous decomposition products formed under fire conditions.
Viscosity	:	
Viscosity, kinematic	:	< 20,5 mm2/s (40 °C)
Oxidizing properties	:	Sustains combustion

### 9.2 Other information

No data available

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

### 10.5 Incompatible materials

Materials to avoid : Strong oxidizing agents

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

{ error: graphic file not  
found:  
C:\WWW\graphics\01\_H  
ELIOS TBLUS.JPG }

## COLOR NITRO THINNER

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09.11.2020	MAT000478623	Date of first issue: 09.11.2020
		GB / EN	

### 10.6 Hazardous decomposition products

Adequate ventilation is required.  
Heating can release vapours which can be ignited.  
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

Not classified based on available information.

#### Product:

Acute oral toxicity : Acute toxicity estimate: > 2.000 mg/kg  
Method: Calculation method

#### Components:

##### acetone:

Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg  
Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg

##### toluene:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg  
Acute inhalation toxicity : LC50 (Rat): > 28 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

##### n-butyl acetate:

Acute oral toxicity : LD50 Oral (Rat): >= 10.760 mg/kg  
Acute dermal toxicity : LD50 (Rabbit): >= 5.000 mg/kg

##### butan-1-ol:

Acute oral toxicity : Assessment: The component/mixture is moderately toxic after  
single ingestion.  
LD50 Oral (Rat): > 2.000 mg/kg  
Acute inhalation toxicity : LC50 (Rat): > 5 mg/l  
Test atmosphere: vapour  
Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

{ error: graphic file not  
found:  
C:\WWI\graphics\01\_H  
ELIOS TBLUS.JPG }

## COLOR NITRO THINNER

Version  
1.0

Revision Date:  
09.11.2020

SDS Number:  
MAT000478623  
GB / EN

Date of last issue: -  
Date of first issue: 09.11.2020

### Skin corrosion/irritation

Causes skin irritation.

#### Product:

: Extremely corrosive and destructive to tissue.

#### Components:

##### toluene:

Result : irritating

##### butan-1-ol:

Result : irritating

##### n-hexane:

Result : irritating

### Serious eye damage/eye irritation

Causes serious eye damage.

#### Product:

: May cause irreversible eye damage.

#### Components:

##### acetone:

Result : Eye irritation

##### butan-1-ol:

Result : Corrosive

### Respiratory or skin sensitisation

#### Skin sensitisation

Not classified based on available information.

#### Respiratory sensitisation

Not classified based on available information.

#### Germ cell mutagenicity

Not classified based on available information.

#### Carcinogenicity

Not classified based on available information.

#### Reproductive toxicity

Suspected of damaging the unborn child.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

{ error: graphic file not  
found:

C:\WWI\graphics\01\_H  
ELIOS TBLUS.JPG }

## COLOR NITRO THINNER

Version  
1.0

Revision Date:  
09.11.2020

SDS Number:  
MAT000478623  
GB / EN

Date of last issue: -  
Date of first issue: 09.11.2020

### Components:

#### **toluene:**

Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments.

#### **n-hexane:**

Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments.

#### **STOT - single exposure**

May cause drowsiness or dizziness.

### Components:

#### **acetone:**

Assessment : May cause drowsiness or dizziness.

#### **toluene:**

Assessment : May cause drowsiness or dizziness.

#### **hydrocarbons, C6-C7, isoalkanes, cyclic, <5% n-hexane:**

Assessment : May cause drowsiness or dizziness.

#### **n-butyl acetate:**

Assessment : May cause drowsiness or dizziness.

#### **butan-1-ol:**

Assessment : May cause drowsiness or dizziness.

Assessment : May cause respiratory irritation.

#### **n-hexane:**

Assessment : May cause drowsiness or dizziness.

#### **STOT - repeated exposure**

May cause damage to organs through prolonged or repeated exposure.

### Components:

#### **toluene:**

Assessment : May cause damage to organs through prolonged or repeated exposure.

#### **n-hexane:**

Assessment : May cause damage to organs through prolonged or repeated

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

{ error: graphic file not  
found:  
C:\WWI\graphics\01\_H  
ELIOS TBLUS.JPG }

## COLOR NITRO THINNER

Version  
1.0

Revision Date:  
09.11.2020

SDS Number:  
MAT000478623  
GB / EN

Date of last issue: -  
Date of first issue: 09.11.2020

exposure.

### Aspiration toxicity

May be fatal if swallowed and enters airways.

### Components:

#### toluene:

May be fatal if swallowed and enters airways.

#### hydrocarbons, C6-C7, isoalkanes, cyclic, <5% n-hexane:

May be fatal if swallowed and enters airways.

#### n-hexane:

May be fatal if swallowed and enters airways.

### Further information

#### Product:

: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.  
Concentrations substantially above the TLV value may cause narcotic effects.  
Solvents may degrease the skin.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

##### acetone:

Toxicity to fish : LC50 (Fish): > 1.000 mg/l

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)): > 1.000 mg/l

Toxicity to microorganisms : EC50 (Bacteria): > 1.000 mg/l

##### toluene:

#### Ecotoxicology Assessment

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

#### hydrocarbons, C6-C7, isoalkanes, cyclic, <5% n-hexane:

#### Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

{ error: graphic file not  
found:  
C:\WWI\graphics\01\_H  
ELIOS TBLUS.JPG }

## COLOR NITRO THINNER

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09.11.2020	MAT000478623	Date of first issue: 09.11.2020
		GB / EN	

### **n-butyl acetate:**

Toxicity to algae : NOEC (Desmodesmus subspicatus (green algae)): > 200 mg/l  
EC50 (Desmodesmus subspicatus (green algae)): >= 647,7 mg/l  
Exposure time: 72 h

Toxicity to microorganisms : IC50 (Tetrahymena pyriformis): 356 mg/l  
Exposure time: 40 h

### **butan-1-ol:**

Toxicity to fish : LC50 (Fish): > 1.000 mg/l

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)): > 1.000 mg/l

Toxicity to microorganisms : EC50 (Bacteria): > 1.000 mg/l

### **n-hexane:**

#### **Ecotoxicology Assessment**

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

## 12.2 Persistence and degradability

### Components:

#### **n-butyl acetate:**

Biodegradability : Result: Biodegradable  
Biodegradation: 83 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301D

Stability in water : Degradation half life: 78 d  
pH: 8  
Hydrolyses slowly.

Photodegradation : Decomposes rapidly in contact with light.

## 12.3 Bioaccumulative potential

### Components:

#### **acetone:**

Partition coefficient: n-octanol/water : log Pow: -0,24

#### **toluene:**

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

{ error: graphic file not

found:

C:\WWI\graphics\01\_H  
ELIOS TBLUS.JPG }

## COLOR NITRO THINNER

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09.11.2020	MAT000478623	Date of first issue: 09.11.2020
		GB / EN	

Partition coefficient: n-octanol/water : log Pow: 2,65

### **n-butyl acetate:**

Bioaccumulation : Bioconcentration factor (BCF): 15  
Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water : log Pow: 1,81

### **butan-1-ol:**

Partition coefficient: n-octanol/water : log Pow: 0,785

## 12.4 Mobility in soil

No data available

## 12.5 Results of PBT and vPvB assessment

### **Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

## 12.6 Other adverse effects

### **Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Harmful to aquatic life with long lasting effects.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

Waste Code : 08 01 11, waste paint and varnish containing organic solvents or other hazardous substances

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

{ error: graphic file not  
found:  
C:\WWI\graphics\01\_H  
ELIOS TBLUS.JPG }

## COLOR NITRO THINNER

Version 1.0      Revision Date: 09.11.2020      SDS Number: MAT000478623  
GB / EN

Date of last issue: -  
Date of first issue: 09.11.2020

### SECTION 14: Transport information

#### 14.1 UN number

ADN : UN 1263  
ADR : UN 1263  
RID : UN 1263  
IMDG : UN 1263  
IATA : UN 1263

#### 14.2 UN proper shipping name

ADN : PAINT RELATED MATERIAL  
ADR : PAINT RELATED MATERIAL  
RID : PAINT RELATED MATERIAL  
IMDG : PAINT RELATED MATERIAL  
IATA : Paint related material

#### 14.3 Transport hazard class(es)

ADN : 3  
ADR : 3  
RID : 3  
IMDG : 3  
IATA : 3

#### 14.4 Packing group

**ADN**  
Packing group : II  
Classification Code : F1  
Hazard Identification Number : 33  
Labels : 3

**ADR**  
Packing group : II  
Classification Code : F1  
Hazard Identification Number : 33  
Labels : 3  
Tunnel restriction code : (D/E)

**RID**  
Packing group : II  
Classification Code : F1  
Hazard Identification Number : 33  
Labels : 3

**IMDG**

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

{ error: graphic file not  
found:  
C:\WWI\graphics\01\_H  
ELIOS TBLUS.JPG }

## COLOR NITRO THINNER

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09.11.2020	MAT000478623	Date of first issue: 09.11.2020
		GB / EN	

Packing group : II  
Labels : 3  
EmS Code : F-E, S-E

### IATA (Cargo)

Packing instruction (cargo aircraft) : 364  
Packing instruction (LQ) : Y341  
Packing group : II  
Labels : Class 3 - Flammable liquids

### IATA (Passenger)

Packing instruction (passenger aircraft) : 353  
Packing instruction (LQ) : Y341  
Packing group : II  
Labels : Class 3 - Flammable liquids

## 14.5 Environmental hazards

### ADN

Environmentally hazardous : no

### ADR

Environmentally hazardous : no

### RID

Environmentally hazardous : no

### IMDG

Marine pollutant : no

## 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

{ error: graphic file not  
found:  
C:\WWI\graphics\01\_H  
ELIOS TBLUS.JPG }

## COLOR NITRO THINNER

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09.11.2020	MAT000478623	Date of first issue: 09.11.2020
		GB / EN	

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:  
Number on list 3  
toluene (Number on list 48)  
benzene (Number on list 72, 5, 29, 28)

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.  
P5c FLAMMABLE LIQUIDS

### Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

### 15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

## SECTION 16: Other information

### Full text of H-Statements

H225	: Highly flammable liquid and vapour.
H226	: Flammable liquid and vapour.
H302	: Harmful if swallowed.
H304	: May be fatal if swallowed and enters airways.
H315	: Causes skin irritation.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H361d	: Suspected of damaging the unborn child.
H361f	: Suspected of damaging fertility.
H373	: May cause damage to organs through prolonged or repeated exposure.
H411	: Toxic to aquatic life with long lasting effects.
H412	: Harmful to aquatic life with long lasting effects.

### Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

{ error: graphic file not

found:

C:\WWW\graphics\01\_H

ELIOS TBLUS.JPG }

## COLOR NITRO THINNER

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09.11.2020	MAT000478623	Date of first issue: 09.11.2020
		GB / EN	

Eye Dam.	: Serious eye damage
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Repr.	: Reproductive toxicity
Skin Irrit.	: Skin irritation
STOT RE	: Specific target organ toxicity - repeated exposure
STOT SE	: Specific target organ toxicity - single exposure
2000/39/EC	: Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2006/15/EC	: Europe. Indicative occupational exposure limit values
GB EH40	: UK. EH40 WEL - Workplace Exposure Limits
2000/39/EC / TWA	: Limit Value - eight hours
2006/15/EC / TWA	: Limit Value - eight hours
2006/15/EC / STEL	: Short term exposure limit
GB EH40 / TWA	: Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	: Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

Classification of the mixture:

Classification procedure:

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

{ error: graphic file not  
found:  
C:\WWI\graphics\01\_H  
ELIOS TBLUS.JPG }

## COLOR NITRO THINNER

Version 1.0	Revision Date: 09.11.2020	SDS Number: MAT000478623 GB / EN	Date of last issue: - Date of first issue: 09.11.2020
Flam. Liq. 2	H225	Based on product data or assessment	
Skin Irrit. 2	H315	Calculation method	
Eye Dam. 1	H318	Calculation method	
Repr. 2	H361d	Calculation method	
STOT SE 3	H336	Calculation method	
STOT RE 2	H373	Calculation method	
Asp. Tox. 1	H304	Calculation method	
Aquatic Chronic 3	H412	Calculation method	

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.