

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



COLOR FAST DRYING VARNISH PRIMER

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	17.03.2021	MAT000478624	Date of first issue: 17.03.2021
		GB / EN	

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product code : 47862402

Trade name : COLOR FAST DRYING VARNISH PRIMER

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-
stance/Mixture : SU19 Building and construction work
Professional and consumer use of coatings, Roller application
or brushing, Non industrial spraying
PC9a Coatings and paints, thinners, paint removers

1.3 Details of the supplier of the safety data sheet

Company : Helios TBLUS d.o.o.
Količevo 65
1230 Domžale
Slovenia

Telephone Company : 00386 1 722 4383

Telefax Company : 1 722 4310

Responsible/issuing person : 00386 1 722 4383
productsafety@helios.si

1.4 Emergency telephone number

Call 999 for emergency medical attention

professionals only: National Poison Information Service (NPIS) 24h national number 0844 892 0111

consumer: National Health Service (NHS) 24h national number, England & Scotland 111

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



COLOR FAST DRYING VARNISH PRIMER

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	17.03.2021	MAT000478624	Date of first issue: 17.03.2021
		GB / EN	

Precautionary statements : P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Waterborne paint

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
2-butoxyethanol	111-76-2 203-905-0 603-014-00-0 01-2119475108-36	Acute Tox. 4; H302 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319	$\geq 1 - < 10$
Substances with a workplace exposure limit :			
(2-Methoxymethylethoxy)propanol	34590-94-8 252-104-2 01-2119450011-60		$\geq 1 - < 10$

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Do not leave the victim unattended.

If inhaled : If breathed in, move person into fresh air.

In case of skin contact : In case of contact, immediately flush skin with plenty of water.
Remove contaminated clothing and shoes.

In case of eye contact : IF IN EYES: Rinse cautiously with water for several minutes.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



COLOR FAST DRYING VARNISH PRIMER

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	17.03.2021	MAT000478624	Date of first issue: 17.03.2021
GB / EN			

Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice/ attention.

If swallowed : Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products : No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : The product itself does not burn.
Standard procedure for chemical fires.
Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Avoid contact with skin and eyes.
Do not flush into surface water or sanitary sewer system.
Prevent further leakage or spillage if safe to do so.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



COLOR FAST DRYING VARNISH PRIMER

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	17.03.2021	MAT000478624	Date of first issue: 17.03.2021
		GB / EN	

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For disposal considerations see section 13., For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : No special technical protective measures required.
For personal protection see section 8.
- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Hygiene measures : When using do not eat, drink or smoke. Wash thoroughly after handling.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Containers which are opened must be carefully resealed and kept upright to prevent leakage. Perishable if frozen. To maintain product quality, do not store in heat or direct sunlight.
- Advice on common storage : No materials to be especially mentioned.
- Further information on storage stability : Protect from frost.

7.3 Specific end use(s)

- Specific use(s) : Consult the technical guidelines for the use of this substance/mixture.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
2-butoxyethanol	111-76-2	TWA	20 ppm 98 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	50 ppm 246 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	25 ppm 123 mg/m ³	GB EH40

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



COLOR FAST DRYING VARNISH PRIMER

Version
1.0

Revision Date:
17.03.2021

SDS Number:
MAT000478624
GB / EN

Date of last issue: -
Date of first issue: 17.03.2021

	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	50 ppm 246 mg/m ³	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
(2-Methoxymethylethoxy)propanol	34590-94-8	TWA	50 ppm 308 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	50 ppm 308 mg/m ³	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
2-butoxyethanol	111-76-2	butoxyacetic acid: 240 Millimoles per mole Creatinine (Urine)	After shift	GB EH40 BAT

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
2-butoxyethanol	Workers	Inhalation	Long-term systemic effects	98 mg/m ³
	Workers	Inhalation	Acute systemic effects	1091 mg/m ³
	Workers	Inhalation	Acute local effects	246 mg/m ³
	Consumers	Inhalation	Long-term systemic effects	59 mg/m ³
	Consumers	Inhalation	Acute systemic effects	426 mg/m ³
	Consumers	Inhalation	Acute local effects	147 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	125 mg/kg bw/day
	Workers	Dermal	Acute systemic effects	89 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	75 mg/kg bw/day
	Consumers	Dermal	Acute systemic effects	89 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	6,3 mg/kg bw/day
	Consumers	Oral	Acute systemic effects	26,7 mg/kg bw/day

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



COLOR FAST DRYING VARNISH PRIMER

Version
1.0

Revision Date:
17.03.2021

SDS Number:
MAT000478624
GB / EN

Date of last issue: -
Date of first issue: 17.03.2021

(2-Methoxymethylethoxy)propanol	Workers	Inhalation	Long-term systemic effects	308 mg/m3
	Consumers	Inhalation	Long-term systemic effects	37,2 mg/m3
	Workers	Dermal	Long-term systemic effects	283 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	121 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	36 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
2-butoxyethanol	Soil	2,33 mg/kg dry weight (d.w.)
	Marine water	0,88 mg/l
	Fresh water	8,8 mg/l
	Fresh water sediment	34,6 mg/kg dry weight (d.w.)
	Sewage treatment plant	463 mg/l
	Intermittent use/release	9,1 mg/l
(2-Methoxymethylethoxy)propanol	Soil	2,74 mg/kg dry weight (d.w.)
	Marine water	1,9 mg/l
	Fresh water	19 mg/l
	Marine sediment	7,02 mg/kg dry weight (d.w.)
	Fresh water sediment	70,2 mg/kg dry weight (d.w.)
	Sewage treatment plant	4168 mg/l
	Intermittent use/release	190 mg/l

8.2 Exposure controls

Personal protective equipment

Eye protection : Goggles

Hand protection

Material : Nitrile rubber
Glove thickness : 0,2 mm
Protective index : Class 3

Remarks : Wear suitable gloves.

Skin and body protection : Long sleeved clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : No personal respiratory protective equipment normally required.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



COLOR FAST DRYING VARNISH PRIMER

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	17.03.2021	MAT000478624	Date of first issue: 17.03.2021
		GB / EN	

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	: liquid
Colour	: in accordance with the product description
Odour Threshold	: No data available
Melting point/freezing point	: 0,0 °C (calculation method (principal components, lowest value))
Boiling point/boiling range	: 100 °C (calculation method (principal components, lowest value))
Flammability	: Not applicable
Flash point	: Not applicable
pH	: 7 - 9
Viscosity	
Viscosity, kinematic	: > 20,5 mm ² /s (40 °C)
Solubility(ies)	
Water solubility	: completely miscible
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Density	: 1,0 - 1,1 g/cm ³

9.2 Other information

VOC	: (Directive 2004/42/EC) 130 g/l
-----	-------------------------------------

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions	: No data available
---------------------	---------------------

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



COLOR FAST DRYING VARNISH PRIMER

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	17.03.2021	MAT000478624	Date of first issue: 17.03.2021
		GB / EN	

10.4 Conditions to avoid

Conditions to avoid : Protect from frost, heat and sunlight.

10.5 Incompatible materials

Materials to avoid : Incompatible with oxidizing agents.
Incompatible with strong acids and bases.

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

Components:

2-butoxyethanol:

Acute oral toxicity : Assessment: The component/mixture is moderately toxic after single ingestion.

LD50 Oral (Rat): ≥ 1.480 mg/kg

Acute inhalation toxicity : Test atmosphere: vapour
Assessment: The component/mixture is moderately toxic after short term inhalation.

LC50 (Rat): 450 ppm
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : Assessment: The component/mixture is moderately toxic after single contact with skin.

LD50 (Rabbit): ≥ 1.500 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



COLOR FAST DRYING VARNISH PRIMER

Version
1.0

Revision Date:
17.03.2021

SDS Number:
MAT000478624
GB / EN

Date of last issue: -
Date of first issue: 17.03.2021

Skin corrosion/irritation

Not classified based on available information.

Components:

2-butoxyethanol:

Result : irritating

Serious eye damage/eye irritation

Not classified based on available information.

Components:

2-butoxyethanol:

Result : Eye irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



COLOR FAST DRYING VARNISH PRIMER

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	17.03.2021	MAT000478624	Date of first issue: 17.03.2021
		GB / EN	

SECTION 12: Ecological information

12.1 Toxicity

Components:

2-butoxyethanol:

Toxicity to fish	:	LC50 (Fish): ≥ 1.700 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	LC50 (Daphnia (water flea)): > 1.000 mg/l Exposure time: 48 h
Toxicity to microorganisms	:	EC50 (Bacteria): > 5.000 mg/l

12.2 Persistence and degradability

Components:

2-butoxyethanol:

Biodegradability	:	Result: Biodegradable
Stability in water	:	Hydrolyses slowly.
Photodegradation	:	Decomposes slowly in contact with light.

12.3 Bioaccumulative potential

Components:

2-butoxyethanol:

Partition coefficient: n-octanol/water	:	log Pow: 0,81 (20 °C)
--	---	-----------------------

(2-Methoxymethylethoxy)propanol:

Partition coefficient: n-octanol/water	:	log Pow: -0,064
--	---	-----------------

12.4 Mobility in soil

Components:

2-butoxyethanol:

Mobility	:	Medium: Air Content: 1 %
	:	Medium: Water Content: 47 %
	:	Medium: Soil

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



COLOR FAST DRYING VARNISH PRIMER

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	17.03.2021	MAT000478624	Date of first issue: 17.03.2021
		GB / EN	

Content: 52 %

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

Components:

2-butoxyethanol:

Assessment : This substance is not considered to be persistent, bioaccumulating and toxic (PBT)..

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	: Do not release the product to the aquatic environment
Contaminated packaging	: Empty containers should be taken to an approved waste handling site for recycling or disposal.
Waste Code	: 08 01 20, aqueous suspensions containing paint or varnish other than those mentioned in 08 01 19

SECTION 14: Transport information

14.1 UN number or ID number

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



COLOR FAST DRYING VARNISH PRIMER

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	17.03.2021	MAT000478624	Date of first issue: 17.03.2021
		GB / EN	

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: formaldehyde (Number on list 72, 28)

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. : Not applicable

Volatile organic compounds : Directive 2004/42/EC
Volatile organic compounds (VOC) content: 130 g/l

Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



COLOR FAST DRYING VARNISH PRIMER

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	17.03.2021	MAT000478624	Date of first issue: 17.03.2021
		GB / EN	

15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

SECTION 16: Other information

Full text of H-Statements

H302	: Harmful if swallowed.
H312	: Harmful in contact with skin.
H315	: Causes skin irritation.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Eye Irrit.	: Eye irritation
Skin Irrit.	: Skin irritation
2000/39/EC	: Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
GB EH40	: UK. EH40 WEL - Workplace Exposure Limits
GB EH40 BAT	: UK. Biological monitoring guidance values
2000/39/EC / TWA	: Limit Value - eight hours
2000/39/EC / STEL	: Short term exposure limit
GB EH40 / TWA	: Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	: Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



COLOR FAST DRYING VARNISH PRIMER

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	17.03.2021	MAT000478624	Date of first issue: 17.03.2021
		GB / EN	

Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.