

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

{ error: graphic file not  
found:  
C:\WWI\graphics\01\_H  
ELIOS TBLUS.JPG }

## MOBIHEL 2K acrylic enamel MIX

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	04.10.2019	MAT0GA05_004Country / Language SI / EN	Date of first issue: 04.10.2019

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : MOBIHEL 2K acrylic enamel MIX

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-  
stance/Mixture : PC9a Coatings and paints, thinners, paint removers

Recommended restrictions  
on use : Reserved for industrial and professional use.

#### 1.3 Details of the supplier of the safety data sheet

Company : Helios TBLUS d.o.o.  
Količevo 65  
1230 Domžale  
Slovenia

Telephone Company : 00386 1 722 4383

Telefax Company : 1 722 4310

Responsible/issuing person : 00386 1 722 4383  
productsafety@helios.si

#### 1.4 Emergency telephone number

- V nujnih primerih poklicati - 112

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 H226: Flammable liquid and vapour.

Skin irritation, Category 2 H315: Causes skin irritation.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Specific target organ toxicity - single exposure, Category 3, Central nervous system H336: May cause drowsiness or dizziness.

Specific target organ toxicity - single exposure, Category 3, Respiratory system H335: May cause respiratory irritation.

Specific target organ toxicity - repeated H373: May cause damage to organs through pro-

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

{ error: graphic file not  
found:

C:\WWI\graphics\01\_H  
ELIOS TBLUS.JPG }

## MOBIHEL 2K acrylic enamel MIX

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	04.10.2019	MAT0GA05_004Country / Language SI / EN	Date of first issue: 04.10.2019

exposure, Category 2

longed or repeated exposure.

Long-term (chronic) aquatic hazard, Category 3

H412: Harmful to aquatic life with long lasting effects.

### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Warning

Hazard statements :

- H226 Flammable liquid and vapour.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H412 Harmful to aquatic life with long lasting effects.

Precautionary statements :

#### Prevention:

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
- P264 Wash skin thoroughly after handling.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

#### Response:

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

n-butyl acetate  
reaction mixture of ethylbenzene, m-xylene and p-xylene  
hydrocarbons, C9 aromatics

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

{ error: graphic file not

found:

C:\WWI\graphics\01\_H  
ELIOS TBLUS.JPG }

## MOBIHEL 2K acrylic enamel MIX

Version 1.0      Revision Date: 04.10.2019      SDS Number: MAT0GA05\_004Country / Language SI / EN      Date of last issue: -      Date of first issue: 04.10.2019

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

##### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
n-butyl acetate	123-86-4 204-658-1 607-025-00-1 01-2119485493-29	Flam. Liq. 3; H226 STOT SE 3; H336	>= 20 - < 30
reaction mixture of ethylbenzene, m-xylene and p-xylene	Not Assigned  01-2119555267-33	Flam. Liq. 3; H226 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 STOT RE 2; H373 Asp. Tox. 1; H304	>= 10 - < 20
hydrocarbons, C9 aromatics	Not Assigned  01-2119455851-35	Flam. Liq. 3; H226 STOT SE 3; H336 STOT SE 3; H335 Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>= 10 - < 20

For explanation of abbreviations see section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.  
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If skin irritation persists, call a physician.  
If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

{ error: graphic file not  
found:  
C:\WWI\graphics\01\_H  
ELIOS TBLUS.JPG }

## MOBIHEL 2K acrylic enamel MIX

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	04.10.2019	MAT0GA05_004Country / Language SI / EN	Date of first issue: 04.10.2019

Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.

### 4.2 Most important symptoms and effects, both acute and delayed

None known.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No information available.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

{ error: graphic file not  
found:  
C:\WWI\graphics\01\_H  
ELIOS TBLUS.JPG }

## MOBIHEL 2K acrylic enamel MIX

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	04.10.2019	MAT0GA05_004Country / Language SI / EN	Date of first issue: 04.10.2019

Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform  
respective authorities.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

### 6.4 Reference to other sections

For disposal considerations see section 13., For personal protection see section 8.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol.  
Do not breathe vapours/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Open drum carefully as content may be under pressure.  
Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).  
Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : No smoking.  
Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
Electrical installations / working materials must comply with the technological safety standards.

Further information on storage : No decomposition if stored and applied as directed.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

{ error: graphic file not  
found:

C:\WWI\graphics\01\_H  
ELIOS TBLUS.JPG }

## MOBIHEL 2K acrylic enamel MIX

Version  
1.0

Revision Date:  
04.10.2019

SDS Number:  
MAT0GA05\_004Country /  
Language SI / EN

Date of last issue: -  
Date of first issue: 04.10.2019

age stability

### 7.3 Specific end use(s)

Specific use(s) : For further information, refer to the product technical data sheet.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
n-butyl acetate	123-86-4	MV	100 ppm 480 mg/m <sup>3</sup>	SI OEL
Further information	Substances without teratogenic effects when respecting limit values and bat values.			
C.I.Pigment Blue 15:2	12239-87-1	MV (Inhalable fraction)	1 mg/m <sup>3</sup> (Copper)	SI OEL
Further information	Inhalable fraction - the part of the total suspended material that is inhaled by the employees			

#### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
n-butyl acetate	Workers	Inhalation	Acute systemic effects	600 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	600 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term systemic effects	48 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	300 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute systemic effects	300 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute local effects	300 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term systemic effects	12 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local effects	35,7 mg/m <sup>3</sup>
	Consumers	Dermal	Long-term systemic effects	3,4 mg/kg bw/day
	Consumers	Dermal	Acute systemic effects	6 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	2 mg/kg bw/day
	Consumers	Oral	Acute systemic effects	2 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	7 mg/kg bw/day
	Workers	Dermal	Acute systemic ef-	11 mg/kg

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

{ error: graphic file not  
found:  
C:\WWI\graphics\01\_H  
ELIOS TBLUS.JPG }

## MOBIHEL 2K acrylic enamel MIX

Version 1.0      Revision Date: 04.10.2019      SDS Number: MAT0GA05\_004Country / Language SI / EN      Date of last issue: -      Date of first issue: 04.10.2019

			fects	bw/day
reaction mixture of ethylbenzene, m-xylene and p-xylene	Workers	Inhalation	Long-term exposure	221 mg/m3
	Workers	Inhalation	Short-term exposure	442 mg/m3
	Consumers	Inhalation	Long-term exposure	65,3 mg/m3
	Consumers	Inhalation	Short-term exposure	260 mg/m3
	Workers	Dermal	Long-term exposure	3182 mg/kg bw/day
	Consumers	Dermal	Long-term exposure	1872 mg/kg bw/day
	Consumers	Oral	Long-term exposure	12,5 mg/kg bw/day
hydrocarbons, C9 aromatics	Workers	Inhalation	Long-term systemic effects	150 mg/m3
	Workers	Oral	Long-term systemic effects	150 mg/m3
	Consumers	Inhalation	Long-term exposure	32 mg/m3
	Workers	Dermal	Long-term systemic effects	25 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	11 mg/kg bw/day

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
n-butyl acetate	Soil	0,0903 mg/kg dry weight (d.w.)
	Marine water	0,018 mg/l
	Fresh water	0,18 mg/l
	Marine sediment	0,0981 mg/kg dry weight (d.w.)
	Fresh water sediment	0,981 mg/kg dry weight (d.w.)
	Sewage treatment plant	35,6 mg/l
	Intermittent use/release	0,36 mg/l
reaction mixture of ethylbenzene, m-xylene and p-xylene	Soil	2,41 mg/kg
	Marine water	0,25 mg/l
	Fresh water sediment	14,33 mg/kg

## 8.2 Exposure controls

### Personal protective equipment

Eye protection : Eye wash bottle with pure water  
Tightly fitting safety goggles  
Wear face-shield and protective suit for abnormal processing problems.

Hand protection  
Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Impervious clothing

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

{ error: graphic file not  
found:  
C:\WWI\graphics\01\_H  
ELIOS TBLUS.JPG }

## MOBIHEL 2K acrylic enamel MIX

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	04.10.2019	MAT0GA05_004Country / Language SI / EN	Date of first issue: 04.10.2019

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : <\*\* Phrase language not available: [ EN ] CUST - Z\_OWNO000000005 \*\*>  
Wear a full face respirator conforming to EN136 with Type A/P2 filter or better.  
Self-contained closed-circuit breathing apparatus compressed (EN 145)

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Appearance	: liquid
Colour	: in accordance with the product description
Odour	: solvent-like
pH	: Not applicable
Flash point	: 26 °C

Method: ISO 3679, closed cup

Density	: 0,976 - 1,415 g/cm <sup>3</sup>
Viscosity	
Viscosity, kinematic	: > 21 mm <sup>2</sup> /s (40 °C)
Flow time	: 90 - 100 s at 20 °C
	Cross section: 4 mm
	Method: DIN 53211

### 9.2 Other information

No data available

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

{ error: graphic file not  
found:  
C:\WWI\graphics\01\_H  
ELIOS TBLUS.JPG }

## MOBIHEL 2K acrylic enamel MIX

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	04.10.2019	MAT0GA05_004Country / Language SI / EN	Date of first issue: 04.10.2019

---

### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

### 10.5 Incompatible materials

Materials to avoid : Strong acids and oxidizing agents  
Strong reducing agents

### 10.6 Hazardous decomposition products

Adequate ventilation is required.  
Heating can release vapours which can be ignited.  
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

---

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

#### Components:

##### **n-butyl acetate:**

Acute oral toxicity : LD50 Oral (Rat):  $\geq 10.760$  mg/kg

Acute dermal toxicity : LD50 (Rabbit):  $\geq 5.000$  mg/kg

##### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Acute oral toxicity : LD50 Oral (Rat): 3.523 mg/kg

Acute inhalation toxicity : LC50 (Rat): 6350 ppm  
Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): 12.126 mg/kg

##### **hydrocarbons, C9 aromatics:**

Acute dermal toxicity : LD50 (Rabbit):  $> 3.160$  mg/kg

#### **Skin corrosion/irritation**

#### Product:

: May cause skin irritation in susceptible persons.

#### Components:

##### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Result : irritating

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

{ error: graphic file not  
found:  
C:\WWI\graphics\01\_H  
ELIOS TBLUS.JPG }

## MOBIHEL 2K acrylic enamel MIX

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	04.10.2019	MAT0GA05_004Country / Language SI / EN	Date of first issue: 04.10.2019

---

### Serious eye damage/eye irritation

#### Product:

: May cause irreversible eye damage.

#### Components:

##### reaction mixture of ethylbenzene, m-xylene and p-xylene:

Result : Eye irritation

### STOT - single exposure

#### Components:

##### n-butyl acetate:

Assessment : May cause drowsiness or dizziness.

##### reaction mixture of ethylbenzene, m-xylene and p-xylene:

Assessment : May cause respiratory irritation.

##### hydrocarbons, C9 aromatics:

Assessment : May cause drowsiness or dizziness.

Assessment : May cause respiratory irritation.

### STOT - repeated exposure

#### Components:

##### reaction mixture of ethylbenzene, m-xylene and p-xylene:

Assessment : May cause damage to organs through prolonged or repeated exposure.

### Aspiration toxicity

#### Components:

##### reaction mixture of ethylbenzene, m-xylene and p-xylene:

May be fatal if swallowed and enters airways.

##### hydrocarbons, C9 aromatics:

May be fatal if swallowed and enters airways.

### Further information

#### Product:

: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.  
Concentrations substantially above the TLV value may cause

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

{ error: graphic file not  
found:  
C:\WWI\graphics\01\_H  
ELIOS TBLUS.JPG }

## MOBIHEL 2K acrylic enamel MIX

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	04.10.2019	MAT0GA05_004Country / Language SI / EN	Date of first issue: 04.10.2019

narcotic effects.  
Solvents may degrease the skin.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

##### **n-butyl acetate:**

Toxicity to algae : NOEC (Desmodesmus subspicatus (green algae)): > 200 mg/l  
EC50 (Desmodesmus subspicatus (green algae)): >= 647,7 mg/l  
Exposure time: 72 h

Toxicity to microorganisms : IC50 (Tetrahymena pyriformis): 356 mg/l  
Exposure time: 40 h

##### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 3300 - 4093 µg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): 2930 - 4400 µg/l  
Exposure time: 48 h  
LC50 (Daphnia magna (Water flea)): >=8500 µg/l  
Exposure time: 48 h

##### **hydrocarbons, C9 aromatics:**

Toxicity to fish : LC50 (Fish): >= 9,2 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): >= 3,2 mg/l  
Exposure time: 48 h

#### **Ecotoxicology Assessment**

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

#### Components:

##### **n-butyl acetate:**

Partition coefficient: n- : log Pow: 1,81

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

{ error: graphic file not  
found:  
C:\WWI\graphics\01\_H  
ELIOS TBLUS.JPG }

## MOBIHEL 2K acrylic enamel MIX

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	04.10.2019	MAT0GA05_004Country / Language SI / EN	Date of first issue: 04.10.2019

octanol/water

### reaction mixture of ethylbenzene, m-xylene and p-xylene:

Partition coefficient: n-  
octanol/water : log Pow: 3,12 (20 °C)  
pH: 7

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

### 12.6 Other adverse effects

#### Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Harmful to aquatic life with long lasting effects.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

Waste Code : 08 01 11, waste paint and varnish containing organic solvents or other hazardous substances

## SECTION 14: Transport information

### 14.1 UN number

ADN : UN 1263  
ADR : UN 1263

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

{ error: graphic file not  
found:  
C:\WWI\graphics\01\_H  
ELIOS TBLUS.JPG }

## MOBIHEL 2K acrylic enamel MIX

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	04.10.2019	MAT0GA05_004Country / Language SI / EN	Date of first issue: 04.10.2019

---

**RID** : UN 1263

**IMDG** : UN 1263

**IATA** : UN 1263

### 14.2 UN proper shipping name

**ADN** : PAINT

**ADR** : PAINT

**RID** : PAINT

**IMDG** : PAINT

**IATA** : Paint

### 14.3 Transport hazard class(es)

**ADN** : 3

**ADR** : 3

**RID** : 3

**IMDG** : 3

**IATA** : 3

### 14.4 Packing group

#### **ADN**

Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3

#### **ADR**

Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3  
Tunnel restriction code : (D/E)

#### **RID**

Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3

#### **IMDG**

Packing group : III  
Labels : 3  
EmS Code : F-E, S-E

#### **IATA (Cargo)**

Packing instruction (cargo aircraft) : 366  
Packing instruction (LQ) : Y344  
Packing group : III

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

{ error: graphic file not  
found:  
C:\WWI\graphics\01\_H  
ELIOS TBLUS.JPG }

## MOBIHEL 2K acrylic enamel MIX

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	04.10.2019	MAT0GA05_004Country / Language SI / EN	Date of first issue: 04.10.2019

Labels : Class 3 - Flammable liquids

### IATA (Passenger)

Packing instruction (passenger aircraft) : 355

Packing instruction (LQ) : Y344

Packing group : III

Labels : Class 3 - Flammable liquids

### 14.5 Environmental hazards

#### ADN

Environmentally hazardous : no

#### ADR

Environmentally hazardous : no

#### RID

Environmentally hazardous : no

#### IMDG

Marine pollutant : no

### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P5c FLAMMABLE LIQUIDS

### 15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

## SECTION 16: Other information

### Full text of H-Statements

H226	: Flammable liquid and vapour.
H304	: May be fatal if swallowed and enters airways.
H315	: Causes skin irritation.
H319	: Causes serious eye irritation.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H373	: May cause damage to organs through prolonged or repeated exposure.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

{ error: graphic file not  
found:  
C:\WWW\graphics\01\_H  
ELIOS TBLUS.JPG }

## MOBIHEL 2K acrylic enamel MIX

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	04.10.2019	MAT0GA05_004Country /	Date of first issue: 04.10.2019
		Language SI / EN	

H411 : Toxic to aquatic life with long lasting effects.

### Full text of other abbreviations

Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Skin Irrit.	: Skin irritation
STOT RE	: Specific target organ toxicity - repeated exposure
STOT SE	: Specific target organ toxicity - single exposure
SI OEL	: Slovenia. Chemical agents at work - Appendix 1: Occupational exposure limits
SI OEL / MV	: Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

#### Classification of the mixture:

Flam. Liq. 3	H226
Skin Irrit. 2	H315

#### Classification procedure:

Based on product data or assessment  
Calculation method

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

{ error: graphic file not  
found:  
C:\WWI\graphics\01\_H  
ELIOS TBLUS.JPG }

## MOBIHEL 2K acrylic enamel MIX

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	04.10.2019	MAT0GA05_004Country / Language SI / EN	Date of first issue: 04.10.2019

Eye Irrit. 2	H319	Calculation method
STOT SE 3	H336	Calculation method
STOT SE 3	H335	Calculation method
STOT RE 2	H373	Calculation method
Aquatic Chronic 3	H412	Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.