

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



COLOR PAINT REMOVER

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	23.03.2021	MAT000478649	Date of first issue: 23.03.2021
		GB / EN	

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product code : 47864902

Trade name : COLOR PAINT REMOVER

Unique Formula Identifier (UFI) : 1M3F-K7SN-H10C-YE2A

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Professional and consumer use of coatings
PC9a Coatings and paints, thinners, paint removers

1.3 Details of the supplier of the safety data sheet

Company : Helios TBLUS d.o.o.
Količevo 65
1230 Domžale
Slovenia

Telephone Company : 00386 1 722 4383

Telefax Company : 1 722 4310

Responsible/issuing person : 00386 1 722 4383
productsafety@helios.si

1.4 Emergency telephone number

Call 999 for emergency medical attention

professionals only: National Poison Information Service (NPIS) 24h national number 0844 892 0111

consumer: National Health Service (NHS) 24h national number, England & Scotland 111

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2 H225: Highly flammable liquid and vapour.

Eye irritation, Category 2 H319: Causes serious eye irritation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



COLOR PAINT REMOVER

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	23.03.2021	MAT000478649	Date of first issue: 23.03.2021
		GB / EN	

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.

Precautionary statements : P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.

Response:

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Paint related material

Components

Chemical name	CAS-No.	Classification	Concentration
---------------	---------	----------------	---------------

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



COLOR PAINT REMOVER

Version
1.0

Revision Date:
23.03.2021

SDS Number:
MAT000478649
GB / EN

Date of last issue: -
Date of first issue: 23.03.2021

	EC-No. Index-No. Registration number		(% w/w)
1,3-dioxolane	646-06-0 211-463-5 605-017-00-2 01-2119490744-29	Flam. Liq. 2; H225 Eye Irrit. 2; H319	$\geq 50 - < 70$
hydrocarbons, C10-C13 n- alkanes, isoalkanes, cyclic, <2% aromatics	- 01-2119457273-39	Asp. Tox. 1; H304	$\geq 1 - < 10$
ethanol	64-17-5 200-578-6 603-002-00-5 01-2119457610-43	Flam. Liq. 2; H225 Eye Irrit. 2; H319	$\geq 1 - < 10$
White mineral oil (petroleum)	8042-47-5 232-455-8 01-2119487078-27	Asp. Tox. 1; H304	$\geq 1 - < 10$
methanol	67-56-1 200-659-6 603-001-00-X 01-2119433307-44	Flam. Liq. 2; H225 Acute Tox. 3; H301 Acute Tox. 3; H331 Acute Tox. 3; H311 <u>STOT SE 1; H370</u> specific concentration limit STOT SE 1; H370 $\geq 10 \%$ STOT SE 2; H371 $3 - < 10 \%$	$\geq 1 - < 3$
2-dimethylaminoethanol	108-01-0 203-542-8 603-047-00-0 01-2119492298-24	Flam. Liq. 3; H226 Acute Tox. 4; H302 Acute Tox. 3; H331 Acute Tox. 4; H312 Skin Corr. 1B; H314 Eye Dam. 1; H318 STOT SE 3; H335 <u>(Respiratory system)</u> specific concentration limit STOT SE 3; H335 $\geq 5 \%$	$\geq 0,1 - < 1$

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



COLOR PAINT REMOVER

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	23.03.2021	MAT000478649	Date of first issue: 23.03.2021
		GB / EN	

- Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Cool closed containers exposed to fire with water spray.

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



COLOR PAINT REMOVER

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	23.03.2021	MAT000478649	Date of first issue: 23.03.2021
		GB / EN	

For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For disposal considerations see section 13., For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



COLOR PAINT REMOVER

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	23.03.2021	MAT000478649	Date of first issue: 23.03.2021
		GB / EN	

explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : Consult the technical guidelines for the use of this substance/mixture.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Dimethoxymethane	109-87-5	TWA	1.000 ppm 3.160 mg/m ³	GB EH40
		STEL	1.250 ppm 3.950 mg/m ³	GB EH40
ethanol	64-17-5	TWA	1.000 ppm 1.920 mg/m ³	GB EH40
methanol	67-56-1	TWA	200 ppm 260 mg/m ³	2006/15/EC
	Further information: Indicative, Identifies the possibility of significant uptake through the skin			
		TWA	200 ppm 266 mg/m ³	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	250 ppm 333 mg/m ³	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
2-dimethylaminoeth-	108-01-0	TWA	2 ppm 7,4 mg/m ³	GB EH40

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



COLOR PAINT REMOVER

Version
1.0

Revision Date:
23.03.2021

SDS Number:
MAT000478649
GB / EN

Date of last issue: -
Date of first issue: 23.03.2021

anol				
		STEL	6 ppm 22 mg/m3	GB EH40

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
1,3-dioxolane	Workers	Inhalation	Long-term systemic effects	18,09 mg/m3
	Consumers	Dermal	Long-term systemic effects	4,36 mg/m3
Dimethoxymethane	Workers	Inhalation	Long-term systemic effects	126,6 mg/m3
	Consumers	Inhalation	Long-term systemic effects	31,5 mg/m3
	Consumers	Dermal	Long-term systemic effects	18,1 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	18,1 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	17,9 mg/kg bw/day
ethanol	Workers	Inhalation	Long-term systemic effects	950 mg/m3
	Consumers	Inhalation	Acute local effects	950 mg/m3
	Workers	Inhalation	Acute local effects	1900 mg/m3
	Consumers	Inhalation	Long-term systemic effects	114 mg/m3
	Consumers	Oral	Long-term systemic effects	87 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	343 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	206 mg/kg bw/day
methanol	Workers	Inhalation	Acute systemic effects	260 mg/m3
	Workers	Inhalation	Acute local effects	260 mg/m3
	Workers	Inhalation	Long-term systemic effects	260 mg/m3
	Workers	Inhalation	Long-term local effects	260 mg/m3
	Consumers	Inhalation	Acute systemic effects	50 mg/m3
	Consumers	Inhalation	Long-term local effects	50 mg/m3
	Consumers	Inhalation	Long-term systemic effects	50 mg/m3
	Consumers	Inhalation	Acute local effects	50 mg/m3
	Workers	Dermal	Acute systemic effects	40 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	40 mg/kg bw/day
	Consumers	Dermal	Acute systemic effects	8 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



COLOR PAINT REMOVER

Version
1.0

Revision Date:
23.03.2021

SDS Number:
MAT000478649
GB / EN

Date of last issue: -
Date of first issue: 23.03.2021

			fects	bw/day
	Consumers	Oral	Acute systemic effects	8 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	8 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	8 mg/kg bw/day
2-dimethylaminoethanol	Workers	Inhalation	Long-term systemic effects	7,4 mg/m3
	Workers	Inhalation	Acute local effects	22 mg/m3
	Workers	Dermal	Acute local effects	0,08 mg/cm2
	Workers	Dermal	Long-term systemic effects	1,04 mg/kg bw/day
	Workers	Dermal	Acute systemic effects	5 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
1,3-dioxolane	Soil	2,62 mg/kg dry weight (d.w.)
	Marine water	1,97 mg/l
	Fresh water	19,7 mg/l
	Marine sediment	7,77 mg/kg dry weight (d.w.)
	Fresh water sediment	77,7 mg/kg dry weight (d.w.)
	Sewage treatment plant	1 mg/l
	Intermittent use/release	0,95 mg/l
Dimethoxymethane	Soil	4,654 mg/kg dry weight (d.w.)
	Marine water	1,477 mg/l
	Fresh water	14,577 mg/l
	Fresh water sediment	13,135 mg/kg dry weight (d.w.)
	Sewage treatment plant	10000 mg/l
ethanol	Soil	0,63 mg/kg dry weight (d.w.)
	Marine water	0,79 mg/l
	Fresh water	0,96 mg/l
	Marine sediment	2,9 mg/kg dry weight (d.w.)
	Fresh water sediment	3,6 mg/kg dry weight (d.w.)
	Sewage treatment plant	580 mg/l
methanol	Soil	23,5 mg/kg
	Marine water	15,4 mg/l
	Fresh water	154 mg/l
	Marine sediment	570,4 mg/kg dry weight (d.w.)
	Sewage treatment plant	100 mg/l
	Intermittent use/release	1540 mg/l
2-dimethylaminoethanol	Soil	0,0177 mg/kg dry

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



COLOR PAINT REMOVER

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	23.03.2021	MAT000478649	Date of first issue: 23.03.2021
		GB / EN	

		weight (d.w.)
	Marine water	0,00661 mg/l
	Fresh water	0,0661 mg/l
	Fresh water sediment	0,0529 mg/kg dry weight (d.w.)
	Sewage treatment plant	10 mg/l
	Intermittent use/release	0,0661 mg/l

8.2 Exposure controls

Personal protective equipment

Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : Wear a full face respirator conforming to EN136 with Type A/P2 filter or better.
Self-contained closed-circuit breathing apparatus compressed (EN 145)
In the case of aerosol and mist formation use an approved respirator filter (EN 141).

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	: liquid
Colour	: in accordance with the product description
Odour	: characteristic
Odour Threshold	: No data available
Melting point/freezing point	: Not applicable
Boiling point/boiling range	: No data available
Upper explosion limit / Upper flammability limit	: 6,1 %(V) (calculation method (principal components, highest value))
Lower explosion limit / Lower	: 0,6 %(V) (calculation method (principal components, highest

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



COLOR PAINT REMOVER

Version 1.0	Revision Date: 23.03.2021	SDS Number: MAT000478649 GB / EN	Date of last issue: - Date of first issue: 23.03.2021
----------------	------------------------------	--	--

flammability limit	value))
Flash point	: 2 °C
Ignition temperature	: 237 °C (calculation method (principal components, highest value))
Decomposition temperature Decomposition temperature	: No decomposition if stored and applied as directed. Hazardous decomposition products formed under fire conditions.
pH	: 7 - 10 Not applicable
Viscosity Viscosity, dynamic	: 6.000 - 8.000 mPa.s (23 °C)
Viscosity, kinematic	: > 21 mm ² /s (40 °C)
Solubility(ies) Water solubility	: immiscible, partly soluble
Solubility in other solvents	: Description: miscible with most organic solvents
Partition coefficient: n-octanol/water	: log Pow: -0,37 (calculation method (principal components, highest value))
Density	: 0,92 - 1,02 g/cm ³

9.2 Other information

Oxidizing properties	: Sustains combustion
----------------------	-----------------------

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions	: No decomposition if stored and applied as directed.
---------------------	---

Vapours may form explosive mixture with air.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



COLOR PAINT REMOVER

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	23.03.2021	MAT000478649	Date of first issue: 23.03.2021
		GB / EN	

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Strong oxidizing agents

10.6 Hazardous decomposition products

Adequate ventilation is required.

Heating can release vapours which can be ignited.

Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Acute oral toxicity : LD50 Oral (Rat, male and female): > 5.000 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 5.000 mg/l
Test atmosphere: vapour
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 Dermal (Rabbit, male and female): > 5.000 mg/kg
Method: OECD Test Guideline 402

ethanol:

Acute oral toxicity : LD50 Oral (Rat): >= 7.060 mg/kg

Acute inhalation toxicity : LC50 (Rat): >= 39 mg/l
Exposure time: 4 h
Test atmosphere: vapour

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



COLOR PAINT REMOVER

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	23.03.2021	MAT000478649	Date of first issue: 23.03.2021
		GB / EN	

methanol:

Acute oral toxicity	:	Assessment: The component/mixture is toxic after single ingestion.
Acute inhalation toxicity	:	Test atmosphere: vapour Assessment: The component/mixture is toxic after short term inhalation.
Acute dermal toxicity	:	Assessment: The component/mixture is toxic after single contact with skin.

2-dimethylaminoethanol:

Acute inhalation toxicity	:	Assessment: The component/mixture is toxic after short term inhalation.
---------------------------	---	---

Skin corrosion/irritation

Product:

Remarks	:	May cause skin irritation in susceptible persons.
---------	---	---

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Species	:	Rabbit
Method	:	OECD Test Guideline 404
Result	:	No skin irritation
GLP	:	yes
Result	:	Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Product:

Remarks	:	May cause irreversible eye damage.
---------	---	------------------------------------

Components:

1,3-dioxolane:

Result	:	Eye irritation
--------	---	----------------

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Species	:	Rabbit
Method	:	OECD Test Guideline 405
Result	:	No eye irritation

ethanol:

Result	:	Eye irritation
--------	---	----------------

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



COLOR PAINT REMOVER

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	23.03.2021	MAT000478649	Date of first issue: 23.03.2021
		GB / EN	

Respiratory or skin sensitisation

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Exposure routes	:	Skin contact
Species	:	Guinea pig
Method	:	OECD Test Guideline 406
Result	:	Not a skin sensitizer.

Germ cell mutagenicity

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Genotoxicity in vitro	:	Result: negative
Genotoxicity in vivo	:	Result: negative

Carcinogenicity

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Result	:	negative
--------	---	----------

Reproductive toxicity

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Effects on foetal development	:	Fertility and developmental toxicity tests did not reveal any effect on reproduction.
-------------------------------	---	---

STOT - single exposure

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Remarks	:	Based on available data, the classification criteria are not met.
---------	---	---

methanol:

Assessment	:	Causes damage to organs.
------------	---	--------------------------

2-dimethylaminoethanol:

Assessment	:	May cause respiratory irritation.
------------	---	-----------------------------------

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



COLOR PAINT REMOVER

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	23.03.2021	MAT000478649	Date of first issue: 23.03.2021
		GB / EN	

STOT - repeated exposure

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Remarks : Based on available data, the classification criteria are not met.

Aspiration toxicity

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

May be fatal if swallowed and enters airways.

White mineral oil (petroleum):

May be fatal if swallowed and enters airways.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Further information

Product:

Remarks : Solvents may degrease the skin.

SECTION 12: Ecological information

12.1 Toxicity

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 1.000 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other : EC50 : > 1.000 mg/l
aquatic invertebrates
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic : NOEC (Pseudokirchneriella subcapitata (microalgae)): 1.000
plants mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



COLOR PAINT REMOVER

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	23.03.2021	MAT000478649	Date of first issue: 23.03.2021
		GB / EN	

Exposure time: 72 h
Method: OECD Test Guideline 201

EC50 (Pseudokirchneriella subcapitata (microalgae)): > 1.000 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOELR: 0,10 mg/l
Exposure time: 28 d
Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR: 0,18 mg/l
Exposure time: 21 d
Species: Daphnia (water flea)

ethanol:

Toxicity to fish : LC50 (Fish): >= 13.500 mg/l

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)): >= 5.000 mg/l

12.2 Persistence and degradability

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 80 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

White mineral oil (petroleum):

Biodegradability : Result: Biodegradable

12.3 Bioaccumulative potential

Components:

1,3-dioxolane:

Partition coefficient: n-octanol/water : log Pow: -0,37

ethanol:

Partition coefficient: n-octanol/water : log Pow: -0,32

White mineral oil (petroleum):

Partition coefficient: n- : log Pow: > 6

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



COLOR PAINT REMOVER

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	23.03.2021	MAT000478649	Date of first issue: 23.03.2021
GB / EN			

octanol/water

methanol:

Partition coefficient: n-octanol/water : log Pow: -0,77

2-dimethylaminoethanol:

Partition coefficient: n-octanol/water : log Pow: -0,55

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Assessment : This substance is not considered to be persistent, bioaccumulating and toxic (PBT)..

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



COLOR PAINT REMOVER

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	23.03.2021	MAT000478649	Date of first issue: 23.03.2021
		GB / EN	

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

Waste Code : 08 01 11, waste paint and varnish containing organic solvents
or other hazardous substances

SECTION 14: Transport information

14.1 UN number or ID number

ADN	: UN 1263
ADR	: UN 1263
RID	: UN 1263
IMDG	: UN 1263
IATA	: UN 1263

14.2 UN proper shipping name

ADN	: PAINT RELATED MATERIAL
ADR	: PAINT RELATED MATERIAL
RID	: PAINT RELATED MATERIAL
IMDG	: PAINT RELATED MATERIAL
IATA	: Paint related material

14.3 Transport hazard class(es)

ADN	: 3
ADR	: 3
RID	: 3
IMDG	: 3
IATA	: 3

14.4 Packing group

ADN	
Packing group	: II
Classification Code	: F1
Hazard Identification Number	: 33
Labels	: 3
Remarks	: Special Provision 640C

ADR	
Packing group	: II

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



COLOR PAINT REMOVER

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	23.03.2021	MAT000478649	Date of first issue: 23.03.2021
		GB / EN	

Classification Code : F1
Hazard Identification Number : 33
Labels : 3
Tunnel restriction code : (D/E)
Remarks : Special Provision 640C

RID

Packing group : II
Classification Code : F1
Hazard Identification Number : 33
Labels : 3
Remarks : Special Provision 640C

IMDG

Packing group : II
Labels : 3
EmS Code : F-E, S-E

IATA (Cargo)

Packing instruction (cargo aircraft) : 364
Packing instruction (LQ) : Y341
Packing group : II
Labels : Flammable Liquids

IATA (Passenger)

Packing instruction (passenger aircraft) : 353
Packing instruction (LQ) : Y341
Packing group : II
Labels : Flammable Liquids

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



COLOR PAINT REMOVER

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	23.03.2021	MAT000478649	Date of first issue: 23.03.2021
		GB / EN	

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P5c FLAMMABLE LIQUIDS

15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

SECTION 16: Other information

Full text of H-Statements

H225	: Highly flammable liquid and vapour.
H226	: Flammable liquid and vapour.
H301	: Toxic if swallowed.
H302	: Harmful if swallowed.
H304	: May be fatal if swallowed and enters airways.
H311	: Toxic in contact with skin.
H312	: Harmful in contact with skin.
H314	: Causes severe skin burns and eye damage.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H331	: Toxic if inhaled.
H335	: May cause respiratory irritation.
H370	: Causes damage to organs.

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Asp. Tox.	: Aspiration hazard
Eye Dam.	: Serious eye damage
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Skin Corr.	: Skin corrosion
STOT SE	: Specific target organ toxicity - single exposure
2006/15/EC	: Europe. Indicative occupational exposure limit values
GB EH40	: UK. EH40 WEL - Workplace Exposure Limits
2006/15/EC / TWA	: Limit Value - eight hours
GB EH40 / TWA	: Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	: Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada);

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



COLOR PAINT REMOVER

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	23.03.2021	MAT000478649	Date of first issue: 23.03.2021
		GB / EN	

ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Flam. Liq. 2	H225
Eye Irrit. 2	H319

Classification procedure:

Based on product data or assessment
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.