according to Regulation (EC) No. 1907/2006

# **MOBIHEL 2K thinner 2100**



Version Revision Date: SDS Number: Date of last issue: -

1.0 07.07.2021 MAT000416721 Date of first issue: 07.07.2021

GB / EN

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product code : 41672151

Trade name : MOBIHEL 2K thinner 2100

Unique Formula Identifier

(UFI)

: Y9K0-E0H9-800V-RG0Y

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : PC9a Coatings and paints, thinners, paint removers

stance/Mixture

Recommended restrictions

on use

: Reserved for industrial and professional use.

1.3 Details of the supplier of the safety data sheet

Company : Helios TBLUS d.o.o.

Količevo 65 1230 Domžale Slovenia

Telephone Company : 386 (1) 722 4383

Telefax Company : 386 (1) 722 4310

Responsible/issuing person : 386 (1) 722 4383

productsafety@helios.si

1.4 Emergency telephone number

Call 999 for emergency medical attention

professionals only: National Poison Information Service (NPIS) 24h national number 0844 892

0111

consumer: National Health Service (NHS) 24h national number, England & Scotland 111

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

#### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 H226: Flammable liquid and vapour.

Specific target organ toxicity - single exH336: May cause drowsiness or dizziness.

according to Regulation (EC) No. 1907/2006

# **MOBIHEL 2K thinner 2100**



Version Revision Date: SDS Number: Date of last issue: -

1.0 07.07.2021 MAT000416721 Date of first issue: 07.07.2021

GB / EN

posure, Category 3, Central nervous system

#### 2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :

Signal word : Warning

Hazard statements : H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

Supplemental Hazard

Statements

EUH066

Repeated exposure may cause skin

dryness or cracking.

Precautionary statements : Prevention:

P210 Keep away from heat, hot surfaces, sparks, open

flames and other ignition sources. No smoking.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immedi-

ately all contaminated clothing. Rinse skin with water.

P304 + P340 + P312 IF INHALED: Remove person to fresh

air and keep comfortable for breathing. Call a POISON

CENTER/ doctor if you feel unwell.

P370 + P378 In case of fire: Use dry sand, dry chemical or

alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container

tightly closed.

## Hazardous components which must be listed on the label:

2-methoxy-1-methylethyl acetate n-butyl acetate

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006

# **MOBIHEL 2K thinner 2100**



Version Revision Date: SDS Number: Date of last issue: -

1.0 07.07.2021 MAT000416721 Date of first issue: 07.07.2021

GB / EN

## **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

Chemical nature : Solvent mixture

Components

Chamical name	CACNO	Classification	Concentration
Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Index-No.		
	Registration number		
2-methoxy-1-methylethyl acetate	108-65-6	Flam. Liq. 3; H226	>= 50 - < 70
	203-603-9	STOT SE 3; H336	
	607-195-00-7	(Central nervous	
	01-2119475791-29	system)	
n-butyl acetate	123-86-4	Flam. Liq. 3; H226	>= 30 - < 50
	204-658-1	STOT SE 3; H336	
	607-025-00-1	(Central nervous	
	01-2119485493-29	system)	
		EUH066	
		2011000	
2-methoxypropyl acetate	70657-70-4	Flam. Liq. 3; H226	>= 0,1 - < 0,3
	274-724-2	Repr. 1B; H360D	
	607-251-00-0	STOT SE 3; H335	
	01-2119475791-29	(Respiratory system)	

#### **SECTION 4: First aid measures**

## 4.1 Description of first aid measures

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : Consult a physician after significant exposure.

If unconscious, place in recovery position and seek medical

advice.

In case of skin contact : If on skin, rinse well with water.

If on clothes, remove clothes.

In case of eye contact : Flush eyes with water as a precaution.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

according to Regulation (EC) No. 1907/2006

## **MOBIHEL 2K thinner 2100**



Version Revision Date: SDS Number:

07.07.2021 MAT000416721 1.0

GB / EN

Date of last issue: -

Date of first issue: 07.07.2021

If symptoms persist, call a physician. Take victim immediately to hospital.

#### 4.2 Most important symptoms and effects, both acute and delayed

Risks May cause drowsiness or dizziness.

Repeated exposure may cause skin dryness or cracking.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

## **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

High volume water jet

#### 5.2 Special hazards arising from the substance or mixture

fighting

Specific hazards during fire- : Cool closed containers exposed to fire with water spray.

## 5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

For safety reasons in case of fire, cans should be stored sepa-

rately in closed containments.

Use a water spray to cool fully closed containers.

#### **SECTION 6: Accidental release measures**

## 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment.

> Remove all sources of ignition. Evacuate personnel to safe areas.

Beware of vapours accumulating to form explosive concentra-

tions. Vapours can accumulate in low areas.

according to Regulation (EC) No. 1907/2006

## **MOBIHEL 2K thinner 2100**



Version Revision Date: SDS Number: Date of last issue: -

1.0 07.07.2021 MAT000416721 Date of first issue: 07.07.2021

GB / EN

#### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible ab-

sorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local

/ national regulations (see section 13).

#### 6.4 Reference to other sections

For disposal considerations see section 13., For personal protection see section 8.

### **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol.

Do not breathe vapours/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Take precautionary measures against static discharges.

Provide sufficient air exchange and/or exhaust in work rooms.

Open drum carefully as content may be under pressure.

Dispose of rinse water in accordance with local and national

regulations.

Advice on protection against

fire and explosion

Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away

from open flames, hot surfaces and sources of ignition.

Hygiene measures : When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

#### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials

must comply with the technological safety standards.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

#### 7.3 Specific end use(s)

Specific use(s) : For further information, refer to the product technical data

sheet.

according to Regulation (EC) No. 1907/2006

# **MOBIHEL 2K thinner 2100**



Version Revision Date: SDS Number:

1.0 07.07.2021 MAT000416721

GB/EN

Date of last issue: -

Date of first issue: 07.07.2021

Consult the technical guidelines for the use of this substance/mixture.

# **SECTION 8: Exposure controls/personal protection**

## 8.1 Control parameters

## **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis	
2-methoxy-1- methylethyl ace- tate	108-65-6	STEL	100 ppm 550 mg/m3	2000/39/EC	
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			ce through the	
		TWA	50 ppm 275 mg/m3	2000/39/EC	
		Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	50 ppm 274 mg/m3	GB EH40	
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.				
		STEL	100 ppm 548 mg/m3	GB EH40	
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.				
n-butyl acetate	123-86-4	TWA	150 ppm 724 mg/m3	GB EH40	
		STEL	200 ppm 966 mg/m3	GB EH40	
		STEL	150 ppm 723 mg/m3	2019/1831/E U	
	Further information: Indicative				
		TWA	50 ppm 241 mg/m3	2019/1831/E U	
	Further information: Indicative				

## Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
2-methoxy-1- methylethyl acetate	Workers	Inhalation	Long-term systemic effects	275 mg/m3
	Workers	Inhalation	Acute local effects	550 mg/m3
	Consumers	Inhalation	Long-term systemic effects	33 mg/m3
	Consumers	Inhalation	Long-term local ef-	33 mg/m3

according to Regulation (EC) No. 1907/2006

# HELIOS

# **MOBIHEL 2K thinner 2100**

Version Revision Date: SDS Number: Date of last issue: -

1.0 07.07.2021 MAT000416721 Date of first issue: 07.07.2021

GB/EN

		1	fects	1
	Workers	Dermal	Long-term systemic effects	796 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	320 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	36 mg/kg bw/day
n-butyl acetate	Workers	Inhalation	Acute systemic ef- fects	600 mg/m3
	Workers	Inhalation	Acute local effects	600 mg/m3
	Workers	Inhalation	Long-term systemic effects	48 mg/m3
	Workers	Inhalation	Long-term local ef- fects	300 mg/m3
	Consumers	Inhalation	Acute systemic effects	300 mg/m3
	Consumers	Inhalation	Acute local effects	300 mg/m3
	Consumers	Inhalation	Long-term systemic effects	12 mg/m3
	Consumers	Inhalation	Long-term local ef- fects	35,7 mg/m3
	Consumers	Dermal	Long-term systemic effects	3,4 mg/kg bw/day
	Consumers	Dermal	Acute systemic ef- fects	6 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	2 mg/kg bw/day
	Consumers	Oral	Acute systemic ef- fects	2 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	7 mg/kg bw/day
	Workers	Dermal	Acute systemic effects	11 mg/kg bw/day

# Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
2-methoxy-1-methylethyl acetate	Soil	0,29 mg/kg dry
		weight (d.w.)
	Marine water	0,0635 mg/l
	Fresh water	0,635 mg/l
	Marine sediment	0,329 mg/kg dry weight (d.w.)
	Fresh water sediment	3,29 mg/kg dry weight (d.w.)
	Sewage treatment plant	100 mg/l
	Intermittent use/release	0,00635 mg/l
n-butyl acetate	Soil	0,0903 mg/kg dry weight (d.w.)
	Marine water	0,018 mg/l
	Fresh water	0,18 mg/l
	Marine sediment	0,0981 mg/kg dry weight (d.w.)

according to Regulation (EC) No. 1907/2006

## **MOBIHEL 2K thinner 2100**



Version Revision Date: SDS Number: Date of last issue: -

1.0 07.07.2021 MAT000416721 Date of first issue: 07.07.2021

GB / EN

Fresh water sediment	0,981 mg/kg dry weight (d.w.)
Sewage treatment plant	35,6 mg/l
Intermittent use/release	0,36 mg/l

#### 8.2 Exposure controls

Personal protective equipment

Eye protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Hand protection

Remarks : Please observe the instructions regarding permeability and

breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of

cuts, abrasion, and the contact time.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : Wear a full face respirator conforming to EN136 with Type

A/P2 filter or better.

Self-contained closed-circuit breathing apparatus com-

pressed (EN 145)

In the case of aerosol and mist formation use an approved

respirator filter (EN 141).

### **SECTION 9: Physical and chemical properties**

## 9.1 Information on basic physical and chemical properties

Physical state : liquid
Colour : colourless
Odour : solvent-like
Odour Threshold : No data available

Melting point/freezing point : -78,0 °C

(calculation method (principal components, lowest value))

Boiling point/boiling range : 126 °C (calculation method (principal components, lowest

value))

Flammability : Static-accumulating flammable liquid., Combustible Solids

Upper explosion limit / Upper

flammability limit

7 %(V) (calculation method (principal components, highest

value)

Lower explosion limit / Lower

flammability limit

: 1,5 %(V) (calculation method (principal components, highest

value))

Flash point : 29 °C

Ignition temperature : 315 °C (calculation method (principal components, highest

according to Regulation (EC) No. 1907/2006

## **MOBIHEL 2K thinner 2100**



Version 1.0

Revision Date: 07.07.2021

SDS Number: MAT000416721

GB / EN

Date of last issue: -

Date of first issue: 07.07.2021

value))

Decomposition temperature

Decomposition temperature No decomposition if used as directed.

Hazardous decomposition products formed under fire condi-

tions.

рΗ Not applicable

Viscosity

Viscosity, kinematic < 20,5 mm2/s (40 °C)

Solubility(ies)

Water solubility partly miscible Solubility in other solvents No data available

Partition coefficient: n-

octanol/water

log Pow: 1,81 (calculation method (principal components,

highest value))

13 hPa (calculation method (principal components, highest Vapour pressure

value))

Relative density No data available

Density : 0,923 g/cm3

Relative vapour density 4,6 (calculation method (principal components, lowest value))

(Air = 1.0)

9.2 Other information

**Explosives** Not applicable

Oxidizing properties Sustains combustion

Evaporation rate No data available

#### **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

No decomposition if stored and applied as directed.

#### 10.2 Chemical stability

No decomposition if stored and applied as directed.

## 10.3 Possibility of hazardous reactions

according to Regulation (EC) No. 1907/2006

# HELIOS

## **MOBIHEL 2K thinner 2100**

Version Revision Date: SDS Number: Date of last issue: -

1.0 07.07.2021 MAT000416721 Date of first issue: 07.07.2021

GB / EN

Hazardous reactions : No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Strong acids and oxidizing agents

Strong reducing agents

#### 10.6 Hazardous decomposition products

Adequate ventilation is required.

Heating can release vapours which can be ignited.

Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

## **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### **Acute toxicity**

Not classified based on available information.

#### Components:

## 2-methoxy-1-methylethyl acetate:

Acute oral toxicity : LD50 Oral (Rat): > > 2.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l

Test atmosphere: vapour

LC0 (Rat): 2000 ppm Exposure time: 3 h

Acute dermal toxicity : LD50 (Rabbit): > > 2.000 mg/kg

n-butyl acetate:

Acute oral toxicity : LD50 Oral (Rat): >= 10.760 mg/kg

Acute dermal toxicity : LD50 (Rabbit): >= 5.000 mg/kg

#### Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

## Serious eye damage/eye irritation

Not classified based on available information.

according to Regulation (EC) No. 1907/2006

# **MOBIHEL 2K thinner 2100**



Version Revision Date: SDS Number: Date of last issue: -

1.0 07.07.2021 MAT000416721 Date of first issue: 07.07.2021

GB/EN

#### Respiratory or skin sensitisation

#### Skin sensitisation

Not classified based on available information.

#### Respiratory sensitisation

Not classified based on available information.

## Germ cell mutagenicity

Not classified based on available information.

#### Carcinogenicity

Not classified based on available information.

#### Reproductive toxicity

Not classified based on available information.

#### **Components:**

## 2-methoxypropyl acetate:

Reproductive toxicity - As-

sessment

Clear evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments

## STOT - single exposure

May cause drowsiness or dizziness.

#### **Components:**

#### 2-methoxy-1-methylethyl acetate:

Assessment : May cause drowsiness or dizziness.

n-butyl acetate:

Assessment : May cause drowsiness or dizziness.

2-methoxypropyl acetate:

Assessment : May cause respiratory irritation.

#### STOT - repeated exposure

Not classified based on available information.

#### **Aspiration toxicity**

Not classified based on available information.

#### 11.2 Information on other hazards

#### **Endocrine disrupting properties**

#### **Product:**

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

according to Regulation (EC) No. 1907/2006

## **MOBIHEL 2K thinner 2100**



Version Revision Date: 1.0

07.07.2021

SDS Number: MAT000416721 Date of last issue: -

Date of first issue: 07.07.2021

GB / EN

levels of 0.1% or higher.

**Further information** 

**Product:** 

Remarks Symptoms of overexposure may be headache, dizziness,

tiredness, nausea and vomiting.

Concentrations substantially above the TLV value may cause

narcotic effects.

Solvents may degrease the skin.

## **SECTION 12: Ecological information**

#### 12.1 Toxicity

#### Components:

#### 2-methoxy-1-methylethyl acetate:

Toxicity to fish LC50 (Oncorhynchus mykiss (rainbow trout)): 130 mg/l

Exposure time: 96 h

NOEC: 100 mg/l Exposure time: 96 h

Toxicity to daphnia and other : LC50: 408 mg/l

aquatic invertebrates

Exposure time: 48 h

Toxicity to fish (Chronic tox- : EC10: 47,5 mg/l

icity)

n-butyl acetate:

Toxicity to algae/aquatic

plants

NOEC (Desmodesmus subspicatus (green algae)): > 200 mg/l

EC50 (Desmodesmus subspicatus (green algae)): >= 647,7

mg/l

Exposure time: 72 h

IC50 (Tetrahymena pyriformis): 356 mg/l Toxicity to microorganisms

Exposure time: 40 h

## 12.2 Persistence and degradability

#### **Components:**

## 2-methoxy-1-methylethyl acetate:

Biodegradability Readily biodegradable.

n-butyl acetate:

Result: Biodegradable Biodegradability

Biodegradation: 83 %

according to Regulation (EC) No. 1907/2006

# **MOBIHEL 2K thinner 2100**



Version Revision Date: SDS Number: Date of last issue: -

1.0 07.07.2021 MAT000416721 Date of first issue: 07.07.2021

GB / EN

Exposure time: 28 d

Method: OECD Test Guideline 301D

Stability in water : Degradation half life: 78 d

pH: 8

Hydrolyses slowly.

Photodegradation : Decomposes rapidly in contact with light.

#### 12.3 Bioaccumulative potential

#### **Components:**

## 2-methoxy-1-methylethyl acetate:

Partition coefficient: n- : log Pow: 1,2 (20 °C)

octanol/water pH: 6,8

n-butyl acetate:

Bioaccumulation : Bioconcentration factor (BCF): 15

Bioaccumulation is unlikely.

Partition coefficient: n-

octanol/water

log Pow: 1,81

#### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

#### **Product:**

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

#### 12.6 Endocrine disrupting properties

## **Product:**

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

## 12.7 Other adverse effects

**Product:** 

Additional ecological infor-

mation

: No data available

according to Regulation (EC) No. 1907/2006

# HELIOS

## **MOBIHEL 2K thinner 2100**

Version Revision Date: SDS Number: Date of last issue: -

1.0 07.07.2021 MAT000416721 Date of first issue: 07.07.2021

GB/EN

## **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

Waste Code : 08 01 11\*, waste paint and varnish containing organic sol-

vents or other hazardous substances

## **SECTION 14: Transport information**

## 14.1 UN number or ID number

ADN : UN 1263
ADR : UN 1263
RID : UN 1263
IMDG : UN 1263
IATA : UN 1263

## 14.2 UN proper shipping name

ADN : PAINT RELATED MATERIAL
ADR : PAINT RELATED MATERIAL
RID : PAINT RELATED MATERIAL
IMDG : PAINT RELATED MATERIAL

IATA : Paint related material

## 14.3 Transport hazard class(es)

ADN : 3
ADR : 3
RID : 3
IMDG : 3
IATA : 3

#### 14.4 Packing group

ADN

Packing group : III

according to Regulation (EC) No. 1907/2006

# HELIOS

## **MOBIHEL 2K thinner 2100**

Version Revision Date: SDS Number: Date of last issue: -

1.0 07.07.2021 MAT000416721 Date of first issue: 07.07.2021

GB/EN

Classification Code : F1 Hazard Identification Number : 30 Labels : 3

ADR

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3
Tunnel restriction code : (D/E)

**RID** 

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

**IMDG** 

Packing group : III Labels : 3

EmS Code : F-E, <u>S-E</u>

IATA (Cargo)

Packing instruction (cargo : 366

aircraft)

Packing instruction (LQ) : Y344
Packing group : III

Labels : Flammable Liquids

IATA (Passenger)

Packing instruction (passen: 355

ger aircraft)

Packing instruction (LQ) : Y344
Packing group : III

Labels : Flammable Liquids

14.5 Environmental hazards

ADN

Environmentally hazardous : no

**ADR** 

Environmentally hazardous : no

RID

Environmentally hazardous : no

**IMDG** 

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

according to Regulation (EC) No. 1907/2006

## **MOBIHEL 2K thinner 2100**



Version Revision Date: SDS Number: Date of last issue: -

07.07.2021 MAT000416721 Date of first issue: 07.07.2021 1.0

GB/EN

## **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mix-

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances.

preparations and articles (Annex XVII)

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

REACH - List of substances subject to authorisation

(Annex XIV)

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import

of dangerous chemicals

Conditions of restriction for the following entries should be considered:

Number on list 3

Not applicable

Not applicable

Not applicable

: Not applicable

Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P5c FLAMMABLE LIQUIDS

## Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

#### 15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

## **SECTION 16: Other information**

#### **Full text of H-Statements**

H226 Flammable liquid and vapour. May cause respiratory irritation. H335 May cause drowsiness or dizziness. H336 May damage the unborn child. H360D

EUH066 Repeated exposure may cause skin dryness or cracking.

## Full text of other abbreviations

Flam. Liq. Flammable liquids Repr. Reproductive toxicity

STOT SE Specific target organ toxicity - single exposure

2000/39/EC Europe. Commission Directive 2000/39/EC establishing a first

list of indicative occupational exposure limit values

Europe. Commission Directive 2019/1831/EU establishing a 2019/1831/EU

fifth list of indicative occupational exposure limit values

GB EH40 UK. EH40 WEL - Workplace Exposure Limits

2000/39/EC / TWA Limit Value - eight hours 2000/39/EC / STEL Short term exposure limit

according to Regulation (EC) No. 1907/2006

## **MOBIHEL 2K thinner 2100**



Version Revision Date: SDS Number: Date of last issue: -

1.0 07.07.2021 MAT000416721 Date of first issue: 07.07.2021

GB / EN

2019/1831/EU / TWA : Limit Value - eight hours 2019/1831/EU / STEL : Short term exposure limit

GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS -Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP -Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population: LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose): MARPOL -International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS -Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

#### **Further information**

#### Classification of the mixture: Classification procedure:

Flam. Liq. 3 H226 Based on product data or assessment

STOT SE 3 H336 Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

according to Regulation (EC) No. 1907/2006



# **MOBIHEL 2K thinner 2100**

Version Revision Date: 1.0

07.07.2021

SDS Number: MAT000416721

GB / EN

Date of last issue: -

Date of first issue: 07.07.2021