

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL QDry THINNER

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 13.07.2021 | MAT000480788 | Date of first issue: 13.07.2021 |
| | | GB / EN | |

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product code : 48078802

Trade name : MOBIHEL QDry THINNER

Unique Formula Identifier (UFI) : E1X0-P0SW-J00R-E4V1

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : PC9a Coatings and paints, thinners, paint removers

Recommended restrictions on use : Reserved for industrial and professional use.

1.3 Details of the supplier of the safety data sheet

Company : Helios TBLUS d.o.o.
Količevo 65
1230 Domžale
Slovenia

Telephone Company : 386 (1) 722 4383

Telefax Company : 386 (1) 722 4310

Responsible/issuing person : 386 (1) 722 4383
productsafety@helios.si

1.4 Emergency telephone number

Call 999 for emergency medical attention

professionals only: National Poison Information Service (NPIS) 24h national number 0844 892 0111

consumer: National Health Service (NHS) 24h national number, England & Scotland 111

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

| | |
|-------------------------------|---|
| Flammable liquids, Category 2 | H225: Highly flammable liquid and vapour. |
| Skin irritation, Category 2 | H315: Causes skin irritation. |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL QDry THINNER

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 13.07.2021 | MAT000480788 | Date of first issue: 13.07.2021 |
| | | GB / EN | |

Serious eye damage, Category 1
Reproductive toxicity, Category 2
Specific target organ toxicity - single exposure, Category 3, Central nervous system
Specific target organ toxicity - repeated exposure, Category 2
Aspiration hazard, Category 1

Long-term (chronic) aquatic hazard, Category 3

H318: Causes serious eye damage.
H361d: Suspected of damaging the unborn child.
H336: May cause drowsiness or dizziness.

H373: May cause damage to organs through prolonged or repeated exposure.
H304: May be fatal if swallowed and enters airways.
H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements :

- H225 Highly flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H336 May cause drowsiness or dizziness.
- H361d Suspected of damaging the unborn child.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
- P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.
P331 Do NOT induce vomiting.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

acetone
toluene

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL QDry THINNER

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 13.07.2021 | MAT000480788 | Date of first issue: 13.07.2021 |
| | | GB / EN | |

hydrocarbons, C6-C7, isoalkanes, cyclic, <5% n-hexane
butan-1-ol

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

| Chemical name | CAS-No. EC-No. Index-No. Registration number | Classification | Concentration (% w/w) |
|---|---|---|--------------------------|
| acetone | 67-64-1 200-662-2 606-001-00-8 01-2119471330-49 | Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system) EUH066 | >= 30 - < 50 |
| toluene | 108-88-3 203-625-9 601-021-00-3 01-2119471310-51 | Flam. Liq. 2; H225 Skin Irrit. 2; H315 Repr. 2; H361d STOT SE 3; H336 (Central nervous system) STOT RE 2; H373 Asp. Tox. 1; H304 Aquatic Chronic 3; H412 | >= 30 - < 50 |
| hydrocarbons, C6-C7, isoalkanes, cyclic, <5% n-hexane | - 01-2119486291-36 | Flam. Liq. 2; H225 STOT SE 3; H336 (Central nervous system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411 | >= 10 - < 20 |
| n-butyl acetate | 123-86-4 204-658-1 607-025-00-1 | Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous | >= 1 - < 10 |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL QDry THINNER

Version
1.0

Revision Date:
13.07.2021

SDS Number:
MAT000480788
GB / EN

Date of last issue: -
Date of first issue: 13.07.2021

| | | | |
|------------|---|---|-------------------|
| | 01-2119485493-29 | system) EUH066 | |
| butan-1-ol | 71-36-3 200-751-6 603-004-00-6 01-2119484630-38 | Flam. Liq. 3; H226 Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system) | $\geq 3 - < 10$ |
| n-hexane | 110-54-3 203-777-6 601-037-00-0 01-2119480412-44 | Flam. Liq. 2; H225 Skin Irrit. 2; H315 Repr. 2; H361f STOT SE 3; H336 (Central nervous system) STOT RE 2; H373 Asp. Tox. 1; H304 Aquatic Chronic 2; H411 specific concentration limit STOT RE 2; H373 $\geq 5 \%$ | $\geq 0,25 - < 1$ |

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
Symptoms of poisoning may appear several hours later.
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL QDry THINNER

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 13.07.2021 | MAT000480788 | Date of first issue: 13.07.2021 |
| | | GB / EN | |

Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

Risks : May be fatal if swallowed and enters airways.
Causes skin irritation.
Causes serious eye damage.
May cause drowsiness or dizziness.
Suspected of damaging the unborn child.
May cause damage to organs through prolonged or repeated exposure.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Cool closed containers exposed to fire with water spray.

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL QDry THINNER

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 13.07.2021 | MAT000480788 | Date of first issue: 13.07.2021 |
| | | GB / EN | |

Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For disposal considerations see section 13., For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
To avoid spills during handling keep bottle on a metal tray.
Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL QDry THINNER

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 13.07.2021 | MAT000480788 | Date of first issue: 13.07.2021 |
| | | GB / EN | |

Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : For further information, refer to the product technical data sheet.

Consult the technical guidelines for the use of this substance/mixture.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

| Components | CAS-No. | Value type (Form of exposure) | Control parameters | Basis |
|------------|--|-------------------------------|--------------------------------------|------------|
| acetone | 67-64-1 | TWA | 500 ppm 1.210 mg/m ³ | 2000/39/EC |
| | Further information: Indicative | | | |
| | | TWA | 500 ppm 1.210 mg/m ³ | GB EH40 |
| | | STEL | 1.500 ppm 3.620 mg/m ³ | GB EH40 |
| toluene | 108-88-3 | TWA | 50 ppm 192 mg/m ³ | 2006/15/EC |
| | Further information: Indicative, Identifies the possibility of significant uptake through the skin | | | |
| | | STEL | 100 ppm 384 mg/m ³ | 2006/15/EC |
| | Further information: Indicative, Identifies the possibility of significant uptake through the skin | | | |
| | | TWA | 50 ppm 191 mg/m ³ | GB EH40 |
| | Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity. | | | |
| | | STEL | 100 ppm 384 mg/m ³ | GB EH40 |
| | Further information: Can be absorbed through the skin. The assigned sub- | | | |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL QDry THINNER

Version
1.0

Revision Date:
13.07.2021

SDS Number:
MAT000480788
GB / EN

Date of last issue: -
Date of first issue: 13.07.2021

| | | | | |
|-----------------|--|------|----------------------------------|------------------|
| | stances are those for which there are concerns that dermal absorption will lead to systemic toxicity. | | | |
| n-butyl acetate | 123-86-4 | TWA | 150 ppm 724 mg/m ³ | GB EH40 |
| | | STEL | 200 ppm 966 mg/m ³ | GB EH40 |
| | | STEL | 150 ppm 723 mg/m ³ | 2019/1831/E U |
| | Further information: Indicative | | | |
| | | TWA | 50 ppm 241 mg/m ³ | 2019/1831/E U |
| | Further information: Indicative | | | |
| butan-1-ol | 71-36-3 | STEL | 50 ppm 154 mg/m ³ | GB EH40 |
| | Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity. | | | |
| n-hexane | 110-54-3 | TWA | 20 ppm 72 mg/m ³ | 2006/15/EC |
| | Further information: Indicative | | | |
| | | TWA | 20 ppm 72 mg/m ³ | GB EH40 |

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

| Substance name | End Use | Exposure routes | Potential health effects | Value |
|---|-----------|-----------------|----------------------------|------------------------|
| acetone | Consumers | Inhalation | Long-term systemic effects | 200 mg/m ³ |
| | Workers | Inhalation | Acute local effects | 2420 mg/m ³ |
| | Workers | Inhalation | Long-term systemic effects | 1210 mg/m ³ |
| | Consumers | Oral | Long-term systemic effects | 62 mg/kg |
| | Consumers | Dermal | Long-term systemic effects | 62 mg/kg |
| toluene | Workers | Dermal | Long-term systemic effects | 186 mg/kg |
| | Workers | Inhalation | Long-term systemic effects | 192 mg/m ³ |
| | Workers | Inhalation | Long-term local effects | 192 mg/m ³ |
| | Consumers | Inhalation | Acute systemic effects | 226 mg/m ³ |
| | Consumers | Inhalation | Acute local effects | 226 mg/m ³ |
| hydrocarbons, C6-C7, isoalkanes, cyclic, <5% n-hexane | Workers | Inhalation | Long-term systemic effects | 5306 mg/m ³ |
| | Consumers | Inhalation | Long-term systemic effects | 1131 mg/m ³ |
| | Consumers | Oral | Long-term systemic effects | 1301 mg/kg bw/day |
| | Workers | Dermal | Long-term systemic | 13964 mg/kg |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL QDry THINNER

Version
1.0

Revision Date:
13.07.2021

SDS Number:
MAT000480788
GB / EN

Date of last issue: -
Date of first issue: 13.07.2021

| | | | effects | bw/day |
|-----------------|-----------|------------|----------------------------|--------------------|
| | Consumers | Dermal | Long-term systemic effects | 1377 mg/kg bw/day |
| n-butyl acetate | Workers | Inhalation | Acute systemic effects | 600 mg/m3 |
| | Workers | Inhalation | Acute local effects | 600 mg/m3 |
| | Workers | Inhalation | Long-term systemic effects | 48 mg/m3 |
| | Workers | Inhalation | Long-term local effects | 300 mg/m3 |
| | Consumers | Inhalation | Acute systemic effects | 300 mg/m3 |
| | Consumers | Inhalation | Acute local effects | 300 mg/m3 |
| | Consumers | Inhalation | Long-term systemic effects | 12 mg/m3 |
| | Consumers | Inhalation | Long-term local effects | 35,7 mg/m3 |
| | Consumers | Dermal | Long-term systemic effects | 3,4 mg/kg bw/day |
| | Consumers | Dermal | Acute systemic effects | 6 mg/kg bw/day |
| | Consumers | Oral | Long-term systemic effects | 2 mg/kg bw/day |
| | Consumers | Oral | Acute systemic effects | 2 mg/kg bw/day |
| | Workers | Dermal | Long-term systemic effects | 7 mg/kg bw/day |
| | Workers | Dermal | Acute systemic effects | 11 mg/kg bw/day |
| butan-1-ol | Workers | Inhalation | Long-term local effects | 310 mg/m3 |
| | Consumers | Inhalation | Long-term systemic effects | 55,357 mg/m3 |
| | Consumers | Inhalation | Long-term local effects | 155 mg/m3 |
| | Consumers | Dermal | Long-term systemic effects | 3,125 mg/kg bw/day |
| | Consumers | Oral | Long-term systemic effects | 1,562 mg/kg bw/day |

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

| Substance name | Environmental Compartment | Value |
|----------------|---------------------------|------------------------------|
| acetone | Soil | 29,5 mg/kg |
| | Marine water | 1,06 mg/l |
| | Fresh water | 10,6 mg/l |
| | Marine sediment | 3,04 mg/l |
| | Fresh water sediment | 30,4 mg/l |
| | Sewage treatment plant | 100 mg/l |
| toluene | Soil | 2,89 mg/kg dry weight (d.w.) |
| | Marine water | 0,68 mg/l |
| | Fresh water | 0,68 mg/l |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL QDry THINNER

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 13.07.2021 | MAT000480788 | Date of first issue: 13.07.2021 |
| | | GB / EN | |

| | | |
|-----------------|--------------------------|--------------------------------|
| | Marine sediment | 16,39 mg/kg dry weight (d.w.) |
| | Fresh water sediment | 16,39 mg/kg dry weight (d.w.) |
| | Sewage treatment plant | 13,61 mg/l |
| | Intermittent use/release | 0,68 mg/l |
| n-butyl acetate | Soil | 0,0903 mg/kg dry weight (d.w.) |
| | Marine water | 0,018 mg/l |
| | Fresh water | 0,18 mg/l |
| | Marine sediment | 0,0981 mg/kg dry weight (d.w.) |
| | Fresh water sediment | 0,981 mg/kg dry weight (d.w.) |
| | Sewage treatment plant | 35,6 mg/l |
| | Intermittent use/release | 0,36 mg/l |
| butan-1-ol | Soil | 0,0166 mg/kg dry weight (d.w.) |
| | Marine water | 0,0082 mg/l |
| | Fresh water | 0,082 mg/l |
| | Marine sediment | 0,0324 mg/kg dry weight (d.w.) |
| | Fresh water sediment | 0,324 mg/kg dry weight (d.w.) |
| | Sewage treatment plant | 2476 mg/l |
| | Intermittent use/release | 2,25 mg/l |

8.2 Exposure controls

Personal protective equipment

Eye protection : Equipment should conform to EN 166
Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Hand protection

Remarks : Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : Wear a full face respirator conforming to EN136 with Type A/P2 filter or better.
Self-contained closed-circuit breathing apparatus compressed (EN 145)
In the case of aerosol and mist formation use an approved respirator filter (EN 141).

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL QDry THINNER

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 13.07.2021 | MAT000480788 | Date of first issue: 13.07.2021 |
| | | GB / EN | |

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

| | |
|--|---|
| Physical state | : liquid |
| Colour | : in accordance with the product description |
| Odour | : solvent-like |
| Odour Threshold | : No data available |
| Melting point/freezing point | : -95,0 °C (calculation method (principal components, lowest value)) |
| Boiling point/boiling range | : 56 °C (calculation method (principal components, lowest value)) |
| Flammability | : Static-accumulating flammable liquid., Combustible Solids |
| Upper explosion limit / Upper flammability limit | : 13 %(V) (calculation method (principal components, highest value)) |
| Lower explosion limit / Lower flammability limit | : 1,2 %(V) (calculation method (principal components, highest value)) |
| Flash point | : -18 °C (calculation method (principal components, lowest value)) |
| Ignition temperature | : 425 °C (calculation method (principal components, highest value)) |
| Decomposition temperature | |
| Decomposition temperature | : No decomposition if used as directed. Hazardous decomposition products formed under fire conditions. |
| pH | : Not applicable |
| Viscosity | |
| Viscosity, kinematic | : < 20,5 mm ² /s (40 °C) |
| Solubility(ies) | |
| Water solubility | : immiscible, partly soluble |
| Solubility in other solvents | : No data available |
| Partition coefficient: n-octanol/water | : log Pow: 2,65 (calculation method (principal components, highest value)) |
| Vapour pressure | : < 1.100 hPa (calculation method (principal components, highest value)) (50 °C) |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL QDry THINNER

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 13.07.2021 | MAT000480788 | Date of first issue: 13.07.2021 |
| | | GB / EN | |

Relative density : 0,79 (calculation method (principal components, highest value))

Density : 0,804 g/cm³

Relative vapour density : 4 (calculation method (principal components, lowest value))

9.2 Other information

Explosives : Not applicable

Oxidizing properties : Sustains combustion

Evaporation rate : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Strong acids and oxidizing agents
Strong reducing agents

10.6 Hazardous decomposition products

Adequate ventilation is required.

Heating can release vapours which can be ignited.

Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL QDry THINNER

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 13.07.2021 | MAT000480788 | Date of first issue: 13.07.2021 |
| | | GB / EN | |

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

Components:

acetone:

Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg
Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg

toluene:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg
Acute inhalation toxicity : LC50 (Rat): > 28 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

n-butyl acetate:

Acute oral toxicity : LD50 Oral (Rat): >= 10.760 mg/kg
Acute dermal toxicity : LD50 (Rabbit): >= 5.000 mg/kg

butan-1-ol:

Acute oral toxicity : Assessment: The component/mixture is moderately toxic after single ingestion.
LD50 Oral (Rat): > 2.000 mg/kg
Acute inhalation toxicity : LC50 (Rat): > 5 mg/l
Test atmosphere: vapour
Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks : Extremely corrosive and destructive to tissue.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL QDry THINNER

Version
1.0

Revision Date:
13.07.2021

SDS Number:
MAT000480788
GB / EN

Date of last issue: -
Date of first issue: 13.07.2021

Components:

toluene:

Result : irritating

butan-1-ol:

Result : irritating

n-hexane:

Result : irritating

Serious eye damage/eye irritation

Causes serious eye damage.

Product:

Remarks : May cause irreversible eye damage.

Components:

acetone:

Result : Eye irritation

butan-1-ol:

Result : Corrosive

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Suspected of damaging the unborn child.

Components:

toluene:

Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments.

n-hexane:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL QDry THINNER

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 13.07.2021 | MAT000480788 | Date of first issue: 13.07.2021 |
| | | GB / EN | |

Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments.

STOT - single exposure

May cause drowsiness or dizziness.

Components:

acetone:

Assessment : May cause drowsiness or dizziness.

toluene:

Assessment : May cause drowsiness or dizziness.

hydrocarbons, C6-C7, isoalkanes, cyclic, <5% n-hexane:

Assessment : May cause drowsiness or dizziness.

n-butyl acetate:

Assessment : May cause drowsiness or dizziness.

butan-1-ol:

Assessment : May cause drowsiness or dizziness.

Assessment : May cause respiratory irritation.

n-hexane:

Assessment : May cause drowsiness or dizziness.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Components:

toluene:

Assessment : May cause damage to organs through prolonged or repeated exposure.

n-hexane:

Assessment : May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

May be fatal if swallowed and enters airways.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL QDry THINNER

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 13.07.2021 | MAT000480788 | Date of first issue: 13.07.2021 |
| | | GB / EN | |

Components:

toluene:

May be fatal if swallowed and enters airways.

hydrocarbons, C6-C7, isoalkanes, cyclic, <5% n-hexane:

May be fatal if swallowed and enters airways.

n-hexane:

May be fatal if swallowed and enters airways.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Further information

Product:

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.
Concentrations substantially above the TLV value may cause narcotic effects.
Solvents may degrease the skin.

SECTION 12: Ecological information

12.1 Toxicity

Components:

acetone:

Toxicity to fish : LC50 (Fish): > 1.000 mg/l

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)): > 1.000 mg/l

Toxicity to microorganisms : EC50 (Bacteria): > 1.000 mg/l

toluene:

Ecotoxicology Assessment

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL QDry THINNER

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 13.07.2021 | MAT000480788 | Date of first issue: 13.07.2021 |
| | | GB / EN | |

hydrocarbons, C6-C7, isoalkanes, cyclic, <5% n-hexane:

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

n-butyl acetate:

Toxicity to algae/aquatic plants : NOEC (Desmodesmus subspicatus (green algae)): > 200 mg/l
EC50 (Desmodesmus subspicatus (green algae)): >= 647,7 mg/l
Exposure time: 72 h

Toxicity to microorganisms : IC50 (Tetrahymena pyriformis): 356 mg/l
Exposure time: 40 h

butan-1-ol:

Toxicity to fish : LC50 (Fish): > 1.000 mg/l

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)): > 1.000 mg/l

Toxicity to microorganisms : EC50 (Bacteria): > 1.000 mg/l

n-hexane:

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

Components:

n-butyl acetate:

Biodegradability : Result: Biodegradable
Biodegradation: 83 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

Stability in water : Degradation half life: 78 d
pH: 8
Hydrolyses slowly.

Photodegradation : Decomposes rapidly in contact with light.

12.3 Bioaccumulative potential

Components:

acetone:

Partition coefficient: n-octanol/water : log Pow: -0,24

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL QDry THINNER

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 13.07.2021 | MAT000480788 | Date of first issue: 13.07.2021 |
| | | GB / EN | |

toluene:

Partition coefficient: n-octanol/water : log Pow: 2,65

n-butyl acetate:

Bioaccumulation : Bioconcentration factor (BCF): 15
Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water : log Pow: 1,81

butan-1-ol:

Partition coefficient: n-octanol/water : log Pow: 0,785

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL QDry THINNER

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 13.07.2021 | MAT000480788 | Date of first issue: 13.07.2021 |
| | | GB / EN | |

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

Waste Code : 08 01 11*, waste paint and varnish containing organic solvents or other hazardous substances

SECTION 14: Transport information

14.1 UN number or ID number

ADN : UN 1263
ADR : UN 1263
RID : UN 1263
IMDG : UN 1263
IATA : UN 1263

14.2 UN proper shipping name

ADN : PAINT RELATED MATERIAL
ADR : PAINT RELATED MATERIAL
RID : PAINT RELATED MATERIAL
IMDG : PAINT RELATED MATERIAL
IATA : Paint related material

14.3 Transport hazard class(es)

ADN : 3
ADR : 3
RID : 3
IMDG : 3
IATA : 3

14.4 Packing group

ADN
Packing group : II
Classification Code : F1
Hazard Identification Number : 33
Labels : 3
Remarks : Special Provision 640D

ADR
Packing group : II
Classification Code : F1
Hazard Identification Number : 33
Labels : 3

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL QDry THINNER

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 13.07.2021 | MAT000480788 | Date of first issue: 13.07.2021 |
| | | GB / EN | |

Tunnel restriction code : (D/E)
Remarks : Special Provision 640D

RID

Packing group : II
Classification Code : F1
Hazard Identification Number : 33
Labels : 3
Remarks : Special Provision 640D

IMDG

Packing group : II
Labels : 3
EmS Code : F-E, S-E

IATA (Cargo)

Packing instruction (cargo aircraft) : 364
Packing instruction (LQ) : Y341
Packing group : II
Labels : Flammable Liquids

IATA (Passenger)

Packing instruction (passenger aircraft) : 353
Packing instruction (LQ) : Y341
Packing group : II
Labels : Flammable Liquids

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on : Conditions of restriction for the fol-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL QDry THINNER

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 13.07.2021 | MAT000480788 | Date of first issue: 13.07.2021 |
| | | GB / EN | |

the market and use of certain dangerous substances, preparations and articles (Annex XVII)

lowing entries should be considered:
Number on list 3
toluene (Number on list 48)

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).

: Not applicable

REACH - List of substances subject to authorisation (Annex XIV)

: Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals

: Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer

: Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast)

: Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P5c

FLAMMABLE LIQUIDS

Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

SECTION 16: Other information

Full text of H-Statements

| | |
|--------|--|
| H225 | : Highly flammable liquid and vapour. |
| H226 | : Flammable liquid and vapour. |
| H302 | : Harmful if swallowed. |
| H304 | : May be fatal if swallowed and enters airways. |
| H315 | : Causes skin irritation. |
| H318 | : Causes serious eye damage. |
| H319 | : Causes serious eye irritation. |
| H335 | : May cause respiratory irritation. |
| H336 | : May cause drowsiness or dizziness. |
| H361d | : Suspected of damaging the unborn child. |
| H361f | : Suspected of damaging fertility. |
| H373 | : May cause damage to organs through prolonged or repeated exposure. |
| H411 | : Toxic to aquatic life with long lasting effects. |
| H412 | : Harmful to aquatic life with long lasting effects. |
| EUH066 | : Repeated exposure may cause skin dryness or cracking. |

Full text of other abbreviations

Acute Tox. : Acute toxicity

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL QDry THINNER

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 13.07.2021 | MAT000480788 | Date of first issue: 13.07.2021 |
| GB / EN | | | |

| | |
|---------------------|--|
| Aquatic Chronic | : Long-term (chronic) aquatic hazard |
| Asp. Tox. | : Aspiration hazard |
| Eye Dam. | : Serious eye damage |
| Eye Irrit. | : Eye irritation |
| Flam. Liq. | : Flammable liquids |
| Repr. | : Reproductive toxicity |
| Skin Irrit. | : Skin irritation |
| STOT RE | : Specific target organ toxicity - repeated exposure |
| STOT SE | : Specific target organ toxicity - single exposure |
| 2000/39/EC | : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values |
| 2006/15/EC | : Europe. Indicative occupational exposure limit values |
| 2019/1831/EU | : Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values |
| GB EH40 | : UK. EH40 WEL - Workplace Exposure Limits |
| 2000/39/EC / TWA | : Limit Value - eight hours |
| 2006/15/EC / TWA | : Limit Value - eight hours |
| 2006/15/EC / STEL | : Short term exposure limit |
| 2019/1831/EU / TWA | : Limit Value - eight hours |
| 2019/1831/EU / STEL | : Short term exposure limit |
| GB EH40 / TWA | : Long-term exposure limit (8-hour TWA reference period) |
| GB EH40 / STEL | : Short-term exposure limit (15-minute reference period) |

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS -

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL QDry THINNER

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 13.07.2021 | MAT000480788 | Date of first issue: 13.07.2021 |
| | | GB / EN | |

Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States);
UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

| | |
|-------------------|-------|
| Flam. Liq. 2 | H225 |
| Skin Irrit. 2 | H315 |
| Eye Dam. 1 | H318 |
| Repr. 2 | H361d |
| STOT SE 3 | H336 |
| STOT RE 2 | H373 |
| Asp. Tox. 1 | H304 |
| Aquatic Chronic 3 | H412 |

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.