

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TESSAROL primer for iron

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2021
1.1	15.07.2021	MAT0GA00_006 GB / EN	Date of first issue: 09.03.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product code : Please see section 16 for detailed data

Trade name : TESSAROL primer for iron

Unique Formula Identifier (UFI) : 0391-Y0U4-200K-R61C

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : SU19 Building and construction work
Professional and consumer use of coatings, Roller application or brushing, Non industrial spraying
PC9a Coatings and paints, thinners, paint removers

1.3 Details of the supplier of the safety data sheet

Company : Helios TBLUS d.o.o.
Količevo 65
1230 Domžale
Slovenia

Telephone Company : 386 (1) 722 4383

Telefax Company : 386 (1) 722 4310

Responsible/issuing person : 386 (1) 722 4383
productsafety@helios.si

1.4 Emergency telephone number

Call 999 for emergency medical attention

professionals only: National Poison Information Service (NPIS) 24h national number 0844 892 0111

consumer: National Health Service (NHS) 24h national number, England & Scotland 111

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 : H226: Flammable liquid and vapour.

Specific target organ toxicity - single exposure, Category 3, Central nervous : H336: May cause drowsiness or dizziness.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TESSAROL primer for iron

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2021
1.1	15.07.2021	MAT0GA00_006 GB / EN	Date of first issue: 09.03.2021

system

Long-term (chronic) aquatic hazard, Category 3

H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Warning

Hazard statements : H226 Flammable liquid and vapour.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P271 Use only outdoors or in a well-ventilated area.

Response:

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label:

hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics

Additional Labelling

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

EUH208 Contains rosin, cobalt bis(2-ethylhexanoate). May produce an allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TESSAROL primer for iron

Version 1.1 Revision Date: 15.07.2021 SDS Number: MAT0GA00_006 GB / EN Date of last issue: 09.03.2021 Date of first issue: 09.03.2021

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics	64742-48-9 919-857-5 01-2119463258-33	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) Asp. Tox. 1; H304	>= 20 - < 30
titanium dioxide	13463-67-7 236-675-5 01-2119489379-17	Carc. 2; H351	>= 1 - < 10
trizinc bis(orthophosphate)	7779-90-0 231-944-3 030-011-00-6	Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 1 - < 2,5
reaction mixture of ethylbenzene, m-xylene and p-xylene	- 905-562-9 01-2119555267-33	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 Asp. Tox. 1; H304	>= 1 - < 10
hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics	- 01-2119457273-39	Asp. Tox. 1; H304	>= 1 - < 10
strontium bis(2-ethylhexanoate)	2457-02-5 219-536-3	Skin Irrit. 2; H315 Eye Dam. 1; H318 Repr. 2; H361d Asp. Tox. 1; H304	>= 0,1 - < 1
zinc oxide	1314-13-2 215-222-5 030-013-00-7 01-2119463881-32	Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 0,1 - < 0,25
rosin	8050-09-7	Skin Sens. 1; H317	>= 0,1 - < 1

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TESSAROL primer for iron

Version
1.1

Revision Date:
15.07.2021

SDS Number:
MAT0GA00_006
GB / EN

Date of last issue: 09.03.2021
Date of first issue: 09.03.2021

	232-475-7 650-015-00-7 01-2119480418-32		
zinc 5-nitroisophthalate	60580-61-2	Aquatic Acute 1; H400 Aquatic Chronic 2; H411	$\geq 0,1 - < 0,25$
cobalt bis(2-ethylhexanoate)	136-52-7 205-250-6 01-2119524678-29	Eye Irrit. 2; H319 Skin Sens. 1A; H317 Repr. 1B; H360 Aquatic Acute 1; H400 Aquatic Chronic 3; H412	$\geq 0,025 - < 0,1$
Substances with a workplace exposure limit :			
Talc	14807-96-6 238-877-9 01-2120140278-58		$\geq 10 - < 20$
Kaolin	1332-58-7 310-194-1		$\geq 10 - < 20$

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TESSAROL primer for iron

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2021
1.1	15.07.2021	MAT0GA00_006 GB / EN	Date of first issue: 09.03.2021

4.2 Most important symptoms and effects, both acute and delayed

Risks : May cause drowsiness or dizziness.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : No hazardous combustion products are known.

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TESSAROL primer for iron

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2021
1.1	15.07.2021	MAT0GA00_006 GB / EN	Date of first issue: 09.03.2021

Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform
respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For disposal considerations see section 13., For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national regulations.
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : When using do not eat or drink. When using do not smoke.
Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage stability : No decomposition if stored and applied as directed.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TESSAROL primer for iron

Version
1.1

Revision Date:
15.07.2021

SDS Number:
MAT0GA00_006
GB / EN

Date of last issue: 09.03.2021
Date of first issue: 09.03.2021

7.3 Specific end use(s)

Specific use(s) : For further information, refer to the product technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Calcium carbonate	471-34-1	TWA (inhalable dust)	10 mg/m ³	GB EH40
		TWA (Respirable dust)	4 mg/m ³	GB EH40
Talc	14807-96-6	TWA (Respirable dust)	1 mg/m ³	GB EH40
		TWA (Respirable dust)	0,1 mg/m ³	2004/37/EC
	Further information: Carcinogens or mutagens			
Kaolin	1332-58-7	TWA (Respirable dust)	2 mg/m ³	GB EH40
		TWA (Respirable dust)	0,1 mg/m ³	2004/37/EC
	Further information: Carcinogens or mutagens			
titanium dioxide	13463-67-7	TWA (inhalable dust)	10 mg/m ³	GB EH40
		TWA (Respirable dust)	4 mg/m ³	GB EH40
reaction mixture of ethylbenzene, m-xylene and p-xylene	1330-20-7	TWA	50 ppm 221 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	100 ppm 442 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	50 ppm 220 mg/m ³	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	100 ppm 441 mg/m ³	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will			

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TESSAROL primer for iron

Version
1.1

Revision Date:
15.07.2021

SDS Number:
MAT0GA00_006
GB / EN

Date of last issue: 09.03.2021
Date of first issue: 09.03.2021

	lead to systemic toxicity.			
rosin	8050-09-7	TWA (Fumes)	0,05 mg/m3	GB EH40
	Further information: Capable of causing occupational asthma.			
		STEL (Fumes)	0,15 mg/m3	GB EH40
	Further information: Capable of causing occupational asthma.			
cobalt bis(2-ethylhexanoate)	136-52-7	TWA	0,1 mg/m3 (Cobalt)	GB EH40
	Further information: Capable of causing occupational asthma., Capable of causing cancer and/or heritable genetic damage.			

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
reaction mixture of ethylbenzene, m-xylene and p-xylene	1330-20-7	methyl hippuric acid: 650 Millimoles per mole Creatinine (Urine)	After shift	GB EH40 BAT

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Calcium carbonate	Workers	Inhalation	Long-term local effects	4,26 mg/m3
	Consumers	Inhalation	Long-term local effects	1,06 mg/m3
Talc	Workers	Inhalation	Acute systemic effects	2,16 mg/m3
	Workers	Inhalation	Acute local effects	3,6 mg/m3
	Consumers	Inhalation	Acute systemic effects	1,08 mg/m3
	Consumers	Inhalation	Acute local effects	1,8 mg/m3
	Consumers	Dermal	Long-term local effects	2,27 mg/cm2
	Workers	Dermal	Long-term local effects	4,54 mg/cm2
	Consumers	Oral	Long-term systemic effects	160 mg/kg bw/day
	Consumers	Oral	Acute systemic effects	160 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	43,2 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	21,6 mg/kg bw/day
titanium dioxide	Workers	Inhalation	Long-term local effects	10 mg/m3
	Consumers	Oral	Long-term systemic effects	700 mg/kg bw/day
trizinc bis(orthophosphate)	Workers	Inhalation	Long-term systemic effects	5 mg/m3
	Consumers	Inhalation	Long-term systemic effects	2,5 mg/m3
	Workers	Dermal	Long-term systemic	83 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TESSAROL primer for iron

Version
1.1

Revision Date:
15.07.2021

SDS Number:
MAT0GA00_006
GB / EN

Date of last issue: 09.03.2021
Date of first issue: 09.03.2021

			effects	bw/day
	Consumers	Dermal	Long-term systemic effects	83 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	0,83 mg/kg bw/day
reaction mixture of ethylbenzene, m-xylene and p-xylene	Workers	Inhalation	Long-term systemic effects	77 mg/m3
	Consumers	Inhalation	Long-term local effects	65,3 mg/m3
	Workers	Inhalation	Acute systemic effects	442 mg/m3
	Workers	Inhalation	Acute local effects	289 mg/m3
	Consumers	Inhalation	Acute systemic effects	260 mg/m3
	Workers	Inhalation	Long-term local effects	221 mg/m3
	Consumers	Inhalation	Long-term systemic effects	14,8 mg/m3
	Consumers	Inhalation	Acute local effects	260 mg/m3
	Consumers	Dermal	Long-term systemic effects	108 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	16 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	180 mg/kg bw/day
strontium bis(2-ethylhexanoate)	Workers	Inhalation	Long-term systemic effects	0,730 mg/m3
	Workers	Dermal	Long-term systemic effects	0,410 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	0,180 mg/m3
	Consumers	Dermal	Long-term systemic effects	0,210 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	0,210 mg/kg bw/day
zinc oxide	Workers	Inhalation	Long-term systemic effects	5 mg/m3
	Workers	Inhalation	Long-term local effects	0,5 mg/m3
	Consumers	Inhalation	Long-term systemic effects	2,5 mg/m3
	Workers	Dermal	Long-term systemic effects	83 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	83 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	0,83 mg/kg bw/day
rosin	Workers	Inhalation	Long-term systemic effects	117 mg/m3
	Consumers	Inhalation	Long-term systemic effects	35 mg/m3

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TESSAROL primer for iron

Version
1.1

Revision Date:
15.07.2021

SDS Number:
MAT0GA00_006
GB / EN

Date of last issue: 09.03.2021
Date of first issue: 09.03.2021

	Workers	Dermal	Long-term systemic effects	17 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	10 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	10 mg/kg bw/day
cobalt bis(2-ethylhexanoate)	Workers	Inhalation	Long-term systemic effects	0,2351 mg/m ³
	Consumers	Inhalation	Long-term local effects	0,037 mg/m ³
	Consumers	Oral	Long-term systemic effects	0,0276 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Calcium carbonate	Sewage treatment plant	100 mg/l
Talc	Marine water	141,26 mg/l
	Fresh water	597,97 mg/l
	Marine sediment	3,13 mg/kg dry weight (d.w.)
	Fresh water sediment	31,33 mg/kg dry weight (d.w.)
	Intermittent use/release	597,97 mg/l
titanium dioxide	Soil	100 mg/kg dry weight (d.w.)
	Marine water	0,0184 mg/l
	Fresh water	0,184 mg/l
	Marine sediment	100 mg/kg dry weight (d.w.)
	Fresh water sediment	1000 mg/kg dry weight (d.w.)
trizinc bis(orthophosphate)	Sewage treatment plant	100 mg/l
	Intermittent use/release	0,193 mg/l
	Soil	35,6 mg/kg dry weight (d.w.)
	Marine water	0,0061 mg/l
	Fresh water	0,0206 mg/l
reaction mixture of ethylbenzene, m-xylene and p-xylene	Marine sediment	56,5 mg/kg dry weight (d.w.)
	Fresh water sediment	117,8 mg/kg dry weight (d.w.)
	Sewage treatment plant	0,1 mg/l
	Soil	2,31 mg/kg dry weight (d.w.)
	Marine water	0,327 mg/l
	Fresh water	0,327 mg/l
	Marine sediment	12,46 mg/kg dry weight (d.w.)
	Fresh water sediment	12,46 mg/kg dry weight (d.w.)
	Sewage treatment plant	6,58 mg/l
	Intermittent use/release	0,327 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TESSAROL primer for iron

Version
1.1

Revision Date:
15.07.2021

SDS Number:
MAT0GA00_006
GB / EN

Date of last issue: 09.03.2021

Date of first issue: 09.03.2021

strontium bis(2-ethylhexanoate)	Fresh water	0,360 - 0,440 mg/l
	Intermittent use/release	0,493 - 0,610 mg/l
	Marine water	0,036 - 0,040 mg/l
	Sewage treatment plant	71,7 - 88,52 mg/l
	Fresh water sediment	6,37 - 7,86 mg/kg dry weight (d.w.)
	Marine sediment	0,637 - 0,790 mg/kg dry weight (d.w.)
	Soil	1,06 - 1,31 mg/kg dry weight (d.w.)
zinc oxide	Soil	35,6 mg/kg dry weight (d.w.)
	Marine water	0,0061 mg/l
	Fresh water	0,0206 mg/l
	Marine sediment	56,5 mg/kg dry weight (d.w.)
	Fresh water sediment	117,8 mg/kg dry weight (d.w.)
	Sewage treatment plant	0,1 mg/l
rosin	Soil	0,00045 mg/kg dry weight (d.w.)
	Marine water	0,00016 mg/l
	Fresh water	0,0016 mg/l
	Marine sediment	0,0007 mg/kg dry weight (d.w.)
	Fresh water sediment	0,007 mg/kg dry weight (d.w.)
	Sewage treatment plant	1 mg/l
	Intermittent use/release	0,016 mg/l
zinc 5-nitroisophthalate	Fresh water	0,0206 - 0,0808 mg/l
	Marine water	0,0061 - 0,0239 mg/l
	Sewage treatment plant	0,100 - 0,3922 mg/l
	Fresh water sediment	117,8 - 462 mg/kg dry weight (d.w.)
	Marine sediment	56,5 - 221 mg/kg dry weight (d.w.)
cobalt bis(2-ethylhexanoate)	Soil	56,5 - 221 mg/kg dry weight (d.w.)
	Soil	10,9 mg/kg dry weight (d.w.)
	Marine water	0,00236 mg/l
	Fresh water	0,0006 mg/l
	Marine sediment	9,5 mg/kg dry weight (d.w.)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TESSAROL primer for iron

Version 1.1 Revision Date: 15.07.2021 SDS Number: MAT0GA00_006
GB / EN Date of last issue: 09.03.2021 Date of first issue: 09.03.2021

	Fresh water sediment	9,5 mg/kg dry weight (d.w.)
	Sewage treatment plant	0,37 mg/l

8.2 Exposure controls

Personal protective equipment

Eye protection : Safety glasses with side-shields conforming to EN166

Hand protection

Directive : Equipment should conform to EN 374

Material : Viton®
Rate of permeability : > 480 min
Protective index : Class 6

Material : PVA
Rate of permeability : > 480 min
Protective index : Class 6

Glove thickness : > 0,5 mm

Remarks : The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other.
The obtained break through times according to EN 374 Part III are not measured under normal operating conditions. Therefore a maximum usage time of 50% of the break through time is recommended. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Nitrile gloves are not suitable. Take note of the information given by the producer concerning permeability, degradation and break through times, and of special work

Skin and body protection : Long sleeved clothing
Safety shoes

Respiratory protection : In case of inadequate ventilation wear respiratory protection.

EN-143; EN-149; EN-529

Filter type : A/P2

Protective measures : Wash thoroughly after handling.
Avoid contact with skin, eyes and clothing.
Keep away from food, drink and animal feedingstuffs.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TESSAROL primer for iron

Version 1.1	Revision Date: 15.07.2021	SDS Number: MAT0GA00_006 GB / EN	Date of last issue: 09.03.2021 Date of first issue: 09.03.2021
----------------	------------------------------	--	---

Physical state	: liquid
Colour	: in accordance with the product description
Odour	: solvent-like
Odour Threshold	: No data available
Melting point/freezing point	: 825,0 °C (calculation method (principal components, lowest value))
Flammability	: Static-accumulating flammable liquid., Combustible Solids
Upper explosion limit / Upper flammability limit	: 6 %(V) (calculation method (principal components, highest value))
Lower explosion limit / Lower flammability limit	: 0,7 %(V) (calculation method (principal components, highest value))
Flash point	: 40 °C
Decomposition temperature Decomposition temperature	: No decomposition if stored and applied as directed. Hazardous decomposition products formed under fire conditions.
pH	: No data available
Viscosity Viscosity, kinematic	: > 20,5 mm ² /s (40 °C)
Flow time	: > 60 s at 23 °C Cross section: 6 mm Method: ISO 2431
Solubility(ies) Water solubility	: insoluble
Solubility in other solvents	: Description: miscible with most organic solvents
Partition coefficient: n-octanol/water	: No data available
Density	: 1,25 - 1,40 g/cm ³

9.2 Other information

Explosives	: Not applicable
Oxidizing properties	: Sustains combustion

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TESSAROL primer for iron

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2021
1.1	15.07.2021	MAT0GA00_006 GB / EN	Date of first issue: 09.03.2021

VOC : (Directive 1999/13/EC)
500 g/l

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.
Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Strong oxidizing agents

10.6 Hazardous decomposition products

Adequate ventilation is required.
Heating can release vapours which can be ignited.
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Product:

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

Components:

hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics:

Acute oral toxicity : LD50 Oral (Rat): > 2.000 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TESSAROL primer for iron

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2021
1.1	15.07.2021	MAT0GA00_006 GB / EN	Date of first issue: 09.03.2021

Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg

trizinc bis(orthophosphate):

Acute oral toxicity : LD50 (Rat): 5.000 mg/kg

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Acute oral toxicity : LD50 Oral (Rat): >= 8.700 mg/kg

Acute inhalation toxicity : Test atmosphere: vapour
Assessment: The component/mixture is moderately toxic after short term inhalation.

Acute dermal toxicity : Assessment: The component/mixture is moderately toxic after single contact with skin.

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Acute oral toxicity : LD50 Oral (Rat, male and female): > 5.000 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 5.000 mg/l
Test atmosphere: vapour
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 Dermal (Rabbit, male and female): > 5.000 mg/kg
Method: OECD Test Guideline 402

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks : May cause skin irritation and/or dermatitis.

Components:

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Result : irritating

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation
GLP : yes

Result : Repeated exposure may cause skin dryness or cracking.

strontium bis(2-ethylhexanoate):

Result : irritating

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TESSAROL primer for iron

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2021
1.1	15.07.2021	MAT0GA00_006 GB / EN	Date of first issue: 09.03.2021

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks : Vapours may cause irritation to the eyes, respiratory system and the skin.

Components:

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Result : Eye irritation

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Species : Rabbit
Method : OECD Test Guideline 405
Result : No eye irritation

strontium bis(2-ethylhexanoate):

Result : Corrosive

cobalt bis(2-ethylhexanoate):

Result : Eye irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Product:

Remarks : Causes sensitisation.

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Exposure routes : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : Not a skin sensitizer.

rosin:

Result : Probability or evidence of skin sensitisation in humans

cobalt bis(2-ethylhexanoate):

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TESSAROL primer for iron

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2021
1.1	15.07.2021	MAT0GA00_006 GB / EN	Date of first issue: 09.03.2021

Result : The product is a skin sensitiser, sub-category 1A.

Germ cell mutagenicity

Not classified based on available information.

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Genotoxicity in vitro : Result: negative

Genotoxicity in vivo : Result: negative

Carcinogenicity

Not classified based on available information.

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Result : negative

Reproductive toxicity

Not classified based on available information.

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Effects on foetal development : Fertility and developmental toxicity tests did not reveal any effect on reproduction.

strontium bis(2-ethylhexanoate):

Reproductive toxicity - Assessment : Some evidence of adverse effects on development, based on animal experiments.

cobalt bis(2-ethylhexanoate):

Reproductive toxicity - Assessment : Some evidence of adverse effects on development, based on animal experiments., Presumed human reproductive toxicant

STOT - single exposure

May cause drowsiness or dizziness.

Components:

hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics:

Assessment : May cause drowsiness or dizziness.

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Assessment : May cause respiratory irritation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TESSAROL primer for iron

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2021
1.1	15.07.2021	MAT0GA00_006 GB / EN	Date of first issue: 09.03.2021

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Remarks : Based on available data, the classification criteria are not met.

STOT - repeated exposure

Not classified based on available information.

Components:

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Assessment : May cause damage to organs through prolonged or repeated exposure.

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Remarks : Based on available data, the classification criteria are not met.

Aspiration toxicity

Not classified based on available information.

Components:

hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics:

May be fatal if swallowed and enters airways.

reaction mixture of ethylbenzene, m-xylene and p-xylene:

May be fatal if swallowed and enters airways.

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

May be fatal if swallowed and enters airways.

strontium bis(2-ethylhexanoate):

May be fatal if swallowed and enters airways.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Further information

Product:

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TESSAROL primer for iron

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2021
1.1	15.07.2021	MAT0GA00_006 GB / EN	Date of first issue: 09.03.2021

Concentrations substantially above the TLV value may cause narcotic effects.
Solvents may degrease the skin.

SECTION 12: Ecological information

12.1 Toxicity

Components:

hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics:

Toxicity to fish : LC50 (Fish): > 1.000 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)): > 1.000 mg/l

trizinc bis(orthophosphate):

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Toxicity to fish : LC50 (Fish): >= 1 - 10 mg/l

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)): >= 1 - 10 mg/l

Toxicity to microorganisms : EC50 (Bacteria): >= 1 - 100 mg/l

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 1.000 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 : > 1.000 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : NOEC (Pseudokirchneriella subcapitata (microalgae)): 1.000 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

EC50 (Pseudokirchneriella subcapitata (microalgae)): > 1.000 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TESSAROL primer for iron

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2021
1.1	15.07.2021	MAT0GA00_006 GB / EN	Date of first issue: 09.03.2021

Toxicity to fish (Chronic toxicity) : NOELR: 0,10 mg/l
Exposure time: 28 d
Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR: 0,18 mg/l
Exposure time: 21 d
Species: Daphnia (water flea)

zinc oxide:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): >= 1,793 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): >= 2,6 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : IC50 (Desmodesmus subspicatus (green algae)): >= 0,136 mg/l
Exposure time: 72 h

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

zinc 5-nitroisophthalate:

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

cobalt bis(2-ethylhexanoate):

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

12.2 Persistence and degradability

Components:

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Biodegradability : Readily biodegradable.

Photodegradation : Decomposes rapidly in contact with light.

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TESSAROL primer for iron

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2021
1.1	15.07.2021	MAT0GA00_006 GB / EN	Date of first issue: 09.03.2021

Biodegradability : Result: Readily biodegradable.
Biodegradation: 80 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

zinc oxide:

Biodegradability : Result: Biodegradable

12.3 Bioaccumulative potential

Components:

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Bioaccumulation : Bioconcentration factor (BCF): 25,9
Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water : log Pow: 2,77 - 3,15

12.4 Mobility in soil

Components:

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Distribution among environmental compartments : Koc: 537, log Koc: 2,73
Moderately mobile in soils
The product evaporates from soil.

Stability in soil : Dissipation time: 23 d
Percentage dissipation: 50 % (DT50)

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Assessment : This substance is not considered to be persistent, bioaccumulating and toxic (PBT)..

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TESSAROL primer for iron

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2021
1.1	15.07.2021	MAT0GA00_006 GB / EN	Date of first issue: 09.03.2021

REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life.
Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

Waste Code : 08 01 11*, waste paint and varnish containing organic solvents or other hazardous substances

SECTION 14: Transport information

14.1 UN number or ID number

ADN : UN 1263
ADR : UN 1263
RID : UN 1263
IMDG : UN 1263
IATA : UN 1263

14.2 UN proper shipping name

ADN : PAINT
ADR : PAINT
RID : PAINT
IMDG : PAINT
IATA : Paint

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TESSAROL primer for iron

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2021
1.1	15.07.2021	MAT0GA00_006 GB / EN	Date of first issue: 09.03.2021

14.3 Transport hazard class(es)

ADN	:	3
ADR	:	3
RID	:	3
IMDG	:	3
IATA	:	3

14.4 Packing group

ADN	
Packing group	: III
Classification Code	: F1
Hazard Identification Number	: 30
Labels	: 3
ADR	
Packing group	: III
Classification Code	: F1
Hazard Identification Number	: 30
Labels	: 3
Tunnel restriction code	: (D/E)
RID	
Packing group	: III
Classification Code	: F1
Hazard Identification Number	: 30
Labels	: 3
IMDG	
Packing group	: III
Labels	: 3
EmS Code	: F-E, <u>S-E</u>
IATA (Cargo)	
Packing instruction (cargo aircraft)	: 366
Packing instruction (LQ)	: Y344
Packing group	: III
Labels	: Flammable Liquids
IATA (Passenger)	
Packing instruction (passenger aircraft)	: 355
Packing instruction (LQ)	: Y344
Packing group	: III
Labels	: Flammable Liquids

14.5 Environmental hazards

ADN	
Environmentally hazardous	: no
ADR	
Environmentally hazardous	: no

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TESSAROL primer for iron

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2021
1.1	15.07.2021	MAT0GA00_006 GB / EN	Date of first issue: 09.03.2021

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

Remarks : ADR: Packages smaller than or equal to 450 litres, not goods/merchandise of Class 3 (exemption ADR 2.2.3.1.5)
IMDG: Packages smaller than or equal to 450 litres, not goods/merchandise of Class 3; "transport acc. IMDG-code 2.3.2.5"

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:
Number on list 3

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P5c FLAMMABLE LIQUIDS

34 Petroleum products: (a) gasolines and naphthas, (b) kerosenes

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TESSAROL primer for iron

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2021
1.1	15.07.2021	MAT0GA00_006 GB / EN	Date of first issue: 09.03.2021

(including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams), (d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)

Volatile organic compounds : Directive 1999/13/EC
Volatile organic compounds (VOC) content: 500 g/l

Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

SECTION 16: Other information

Full text of H-Statements

H226	: Flammable liquid and vapour.
H304	: May be fatal if swallowed and enters airways.
H312	: Harmful in contact with skin.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H351	: Suspected of causing cancer if inhaled.
H360	: May damage fertility or the unborn child.
H361d	: Suspected of damaging the unborn child.
H373	: May cause damage to organs through prolonged or repeated exposure.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.
H411	: Toxic to aquatic life with long lasting effects.
H412	: Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Acute	: Short-term (acute) aquatic hazard
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Carc.	: Carcinogenicity

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TESSAROL primer for iron

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2021
1.1	15.07.2021	MAT0GA00_006	Date of first issue: 09.03.2021
GB / EN			

Eye Dam.	:	Serious eye damage
Eye Irrit.	:	Eye irritation
Flam. Liq.	:	Flammable liquids
Repr.	:	Reproductive toxicity
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitisation
STOT RE	:	Specific target organ toxicity - repeated exposure
STOT SE	:	Specific target organ toxicity - single exposure
2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2004/37/EC	:	Europe. Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens or mutagens at work
GB EH40	:	UK. EH40 WEL - Workplace Exposure Limits
GB EH40 BAT	:	UK. Biological monitoring guidance values
2000/39/EC / TWA	:	Limit Value - eight hours
2000/39/EC / STEL	:	Short term exposure limit
2004/37/EC / TWA	:	Long term exposure limit
GB EH40 / TWA	:	Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	:	Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TESSAROL primer for iron

Version	Revision Date:	SDS Number:	Date of last issue: 09.03.2021
1.1	15.07.2021	MAT0GA00_006 GB / EN	Date of first issue: 09.03.2021

Further information

Classification of the mixture:

Flam. Liq. 3	H226
STOT SE 3	H336
Aquatic Chronic 3	H412

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method

Material codes (bulk) for which the SDS is valid 402540; 409381; 418668;

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.