according to Regulation (EC) No. 1907/2006

HELIOS

TESSAROL Antik 3in1 silver

Version Revision Date: SDS Number: Date of last issue: 15.03.2021 1.1 22.07.2021 MAT000401637 Date of first issue: 15.03.2021

GB / EN

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product code : 40163702

Trade name : TESSAROL Antik 3in1 silver

Unique Formula Identifier

(UFI)

: 1XC0-Y0EW-M008-S6W6

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : SU19 Building and construction work

stance/Mixture Professional and consumer use of coatings, Roller application

or brushing, Non industrial spraying

PC9a Coatings and paints, thinners, paint removers

1.3 Details of the supplier of the safety data sheet

Company : Helios TBLUS d.o.o.

Količevo 65 1230 Domžale Slovenia

Telephone Company : 386 (1) 722 4383

Telefax Company : 386 (1) 722 4310

Responsible/issuing person : 386 (1) 722 4383

productsafety@helios.si

1.4 Emergency telephone number

Call 999 for emergency medical attention

professionals only: National Poison Information Service (NPIS) 24h national number 0844 892

0111

consumer: National Health Service (NHS) 24h national number, England & Scotland 111

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 H226: Flammable liquid and vapour.

according to Regulation (EC) No. 1907/2006

TESSAROL Antik 3in1 silver



Version 1.1

Revision Date: 22.07.2021

SDS Number: MAT000401637 GB / EN Date of last issue: 15.03.2021 Date of first issue: 15.03.2021

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms

Signal word

: Warning

Hazard statements

H226 Flammable liquid and vapour.

Precautionary statements

P101 If medical advice is needed, have product container or

label at hand.

P102 Keep out of reach of children.

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open

flames and other ignition sources. No smoking.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immedi-

ately all contaminated clothing. Rinse skin with water.

P370 + P378 In case of fire: Use dry sand, dry chemical or

alcohol-resistant foam to extinguish.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

Additional Labelling

EUH208

Contains Fatty acids, C18-unsatd., dimers, reaction products with N,N-dimethyl-1,3-propanediamine and 1,3-propanediamine. May produce an allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

according to Regulation (EC) No. 1907/2006

Pind allows

TESSAROL Antik 3in1 silver

Version Revision Date: SDS Number: Date of last issue: 15.03.2021
1.1 22.07.2021 MAT000401637 Date of first issue: 15.03.2021

GB / EN

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)	
hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics	64742-48-9 919-857-5 01-2119463258-33	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) Asp. Tox. 1; H304	>= 10 - < 20	
hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics	01-2119457273-39	Asp. Tox. 1; H304	>= 1 - < 10	
1-methoxy-2-propanol	107-98-2 203-539-1 603-064-00-3 01-2119457435-35	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system)	>= 1 - < 10	
2-ethylhexanoic acid, zirconium salt	22464-99-9 245-018-1 01-2119979088-21	Repr. 2; H361d	>= 0,1 - < 1	
fatty acids, C18, unsatd., dimers, reaction products with N,N-dimethyl-1,3- propanediamine and 1,3-propanediamine	162627-17-0 01-2119970640-38	Skin Sens. 1; H317	>= 0,1 - < 1	
Substances with a workplace exposure limit :				
Silicon dioxide	7631-86-9 231-545-4 01-2119379499-16 (covered by CAS 7631-86-9)		>= 1 - < 10	

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : If on skin, rinse well with water.

If on clothes, remove clothes.

In case of eye contact : Flush eyes with water as a precaution.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

according to Regulation (EC) No. 1907/2006

TESSAROL Antik 3in1 silver



Version Revision Date: SDS Number: Date of last issue: 15.03.2021 1.1 22.07.2021 MAT000401637 Date of first issue: 15.03.2021

GB/EN

If swallowed Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

ucts

Hazardous combustion prod- : No hazardous combustion products are known.

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

For safety reasons in case of fire, cans should be stored sepa-

rately in closed containments.

Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment.

Remove all sources of ignition. Evacuate personnel to safe areas.

according to Regulation (EC) No. 1907/2006

TESSAROL Antik 3in1 silver



Version 1.1

Revision Date: 22.07.2021

SDS Number: MAT000401637 GB / EN Date of last issue: 15.03.2021 Date of first issue: 15.03.2021

Beware of vapours accumulating to form explosive concentra-

tions. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions

Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible ab-

sorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local

/ national regulations (see section 13).

6.4 Reference to other sections

For disposal considerations see section 13., For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Avoid formation of aerosol.

Do not breathe vapours/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national

regulations.

Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Advice on protection against

fire and explosion

Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

according to Regulation (EC) No. 1907/2006

HELIOS

TESSAROL Antik 3in1 silver

Version Revision Date: SDS Number: Date of last issue: 15.03.2021 1.1 22.07.2021 MAT000401637 Date of first issue: 15.03.2021

GB / EN

age stability

Further information on stor- : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : For further information, refer to the product technical data

sheet.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
barium sulphate, natural	7727-43-7	TWA (inhalable dust)	10 mg/m3	GB EH40
		TWA (Respirable dust)	4 mg/m3	GB EH40
aluminium powder (stabilised)	7429-90-5	TWA (inhalable dust)	10 mg/m3	GB EH40
		TWA (Respirable dust)	4 mg/m3	GB EH40
1-methoxy-2- propanol	107-98-2	TWA	100 ppm 375 mg/m3	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			ke through the
		STEL	150 ppm 568 mg/m3	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			ke through the
		TWA	100 ppm 375 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	150 ppm 560 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assignances are those for which there are concerns that dermal absorption lead to systemic toxicity.			
Silicon dioxide	7631-86-9	TWA (Respirable dust)	0,1 mg/m3	2004/37/EC
	Further information: Carcinogens or mutagens			
		TWA (inhalable dust)	6 mg/m3 (Silica)	GB EH40
		TWA (Respirable dust)	2,4 mg/m3 (Silica)	GB EH40
2-ethylhexanoic acid, zirconium salt	22464-99-9	TWA	5 mg/m3 (Zirconium)	GB EH40

according to Regulation (EC) No. 1907/2006



TESSAROL Antik 3in1 silver

Version Revision Date: SDS Number: Date of last issue: 15.03.2021 Date of first issue: 15.03.2021 1.1 22.07.2021 MAT000401637

GB / EN

STEL 10 mg/m3 GB EH40 (Zirconium)

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
barium sulphate, nat- ural	Consumers	Inhalation	Long-term systemic effects	10 mg/m3
	Workers	Inhalation	Long-term systemic effects	10 mg/m3
	Consumers	Oral	Long-term systemic effects	13000 mg/kg bw/day
aluminium powder (stabilised)	Workers	Inhalation	Long-term exposure	3,72 mg/m3
	Workers	Inhalation	Long-term local effects	3,72 mg/m3
		Oral	Long-term systemic effects	3,95 mg/kg bw/day
1-methoxy-2-propanol	Workers	Inhalation	Long-term systemic effects	369 mg/m3
	Workers	Inhalation	Acute systemic effects	553,5 mg/m3
	Workers	Inhalation	Acute local effects	553,5 mg/m3
	Workers	Inhalation	Long-term systemic effects	43,9 mg/m3
	Workers	Dermal	Long-term systemic effects	183 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	78 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	33 mg/kg bw/day
Silicon dioxide	Workers	Inhalation	Long-term systemic effects	4 mg/m3
2-ethylhexanoic acid, zirconium salt	Workers	Inhalation	Long-term systemic effects	32 mg/m3
	Consumers	Inhalation	Long-term systemic effects	8 mg/m3
	Consumers	Oral	Long-term systemic effects	2,5 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	6,49 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	3,25 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

		,
Substance name	Environmental Compartment	Value
barium sulphate, natural	Soil	207,7 mg/kg dry weight (d.w.)
	Fresh water	0,115 mg/l
	Fresh water sediment	600,4 mg/kg dry weight (d.w.)
	Sewage treatment plant	62,2 mg/l

according to Regulation (EC) No. 1907/2006

TESSAROL Antik 3in1 silver



Version Revision Date: SDS Number: Date of last issue: 15.03.2021 1.1 22.07.2021 MAT000401637 Date of first issue: 15.03.2021

GB / EN

aluminium powder (stabilised)	Sewage treatment plant	20 mg/l
1-methoxy-2-propanol	Soil	4,59 mg/kg dry weight (d.w.)
	Marine water	1 mg/l
	Fresh water	10 mg/l
	Marine sediment	5,2 mg/kg dry weight (d.w.)
	Fresh water sediment	52,3 mg/kg dry weight (d.w.)
	Sewage treatment plant	100 mg/l
	Intermittent use/release	100 mg/l
2-ethylhexanoic acid, zirconium salt	Soil	1,06 mg/kg dry weight (d.w.)
	Marine water	0,036 mg/l
	Fresh water	0,36 mg/l
	Marine sediment	0,637 mg/kg dry weight (d.w.)
	Fresh water sediment	6,37 mg/kg dry weight (d.w.)
	Sewage treatment plant	71,7 mg/l
	Intermittent use/release	0,493 mg/l

8.2 Exposure controls

Personal protective equipment

Eye protection

Safety glasses with side-shields conforming to EN166

Hand protection

Directive : Equipment should conform to EN 374

Material : Viton®
Rate of permeability : > 480 min
Protective index : Class 6

Material : PVA
Rate of permeability : > 480 min
Protective index : Class 6

Glove thickness : > 0,5 mm

Remarks : The choice of an appropriate glove does not only depend on

its material but also on other quality features and is different

from one producer to the other.

The obtained break through times according to EN 374 Part III are not measured under normal operating conditions. Therefore a maximum usage time of 50% of the break through time is recommended. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Nitrile gloves are not suitable. Take note of the information given by the producer concerning permeability, degradation and break through times, and of

special work

Skin and body protection : Long sleeved clothing

according to Regulation (EC) No. 1907/2006

TESSAROL Antik 3in1 silver



Version Revision Date: 22.07.2021

SDS Number: MAT000401637

Date of last issue: 15.03.2021 Date of first issue: 15.03.2021

GB / EN

Safety shoes

Respiratory protection : In case of inadequate ventilation wear respiratory protection.

EN-143; EN-149; EN-529

Filter type : A/P2

Protective measures : Wash thoroughly after handling.

Avoid contact with skin, eyes and clothing.

Keep away from food, drink and animal feedingstuffs.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid

Colour : in accordance with the product description

Odour : solvent-like
Odour Threshold : No data available

Melting point/freezing point : 1.580,0 °C

(calculation method (principal components, lowest value))

Flammability : Static-accumulating flammable liquid., Combustible Solids

Upper explosion limit / Upper

flammability limit

6 %(V) (calculation method (principal components, highest

value))

Lower explosion limit / Lower

flammability limit

0,7 %(V) (calculation method (principal components, highest

value)

Flash point : 43 °C (calculation method (principal components, lowest val-

ue))

Decomposition temperature

Decomposition temperature : No decomposition if stored and applied as directed.

Hazardous decomposition products formed under fire condi-

tions.

pH : No data available

Viscosity

Viscosity, kinematic : > 20,5 mm2/s (40 °C)

Flow time : > 60 s at 23 °C

Cross section: 6 mm Method: ISO 2431

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : Description: miscible with most organic solvents

Partition coefficient: n- : No data available

according to Regulation (EC) No. 1907/2006

TESSAROL Antik 3in1 silver



Version 1.1

Revision Date: 22.07.2021

SDS Number: MAT000401637

Date of last issue: 15.03.2021 Date of first issue: 15.03.2021

GB / EN

octanol/water

Density : 1,628 g/cm3

9.2 Other information

Explosives : Not applicable

Oxidizing properties : Sustains combustion

VOC : (Directive 2004/42/EC)

500 g/l

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Strong oxidizing agents

10.6 Hazardous decomposition products

Adequate ventilation is required.

Heating can release vapours which can be ignited.

Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Components:

hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics:

Acute oral toxicity : LD50 Oral (Rat): > 2.000 mg/kg

according to Regulation (EC) No. 1907/2006



TESSAROL Antik 3in1 silver

Version Revision Date: SDS Number: Date of last issue: 15.03.2021 1.1 22.07.2021 MAT000401637 Date of first issue: 15.03.2021

GB/EN

Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Acute oral toxicity : LD50 Oral (Rat, male and female): > 5.000 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 5.000 mg/l

Test atmosphere: vapour

Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 Dermal (Rabbit, male and female): > 5.000 mg/kg

Method: OECD Test Guideline 402

1-methoxy-2-propanol:

Acute oral toxicity : LD50 Oral (Rabbit): > 2.000 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks : May cause skin irritation and/or dermatitis.

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

GLP : yes

Result : Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks : Vapours may cause irritation to the eyes, respiratory system

and the skin.

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Species : Rabbit

Method : OECD Test Guideline 405

Result : No eye irritation

according to Regulation (EC) No. 1907/2006

HELIOS

TESSAROL Antik 3in1 silver

Version Revision Date: SDS Number: Date of last issue: 15.03.2021 1.1 22.07.2021 MAT000401637 Date of first issue: 15.03.2021

GB/EN

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Product:

Remarks : Causes sensitisation.

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Exposure routes : Skin contact Species : Guinea pig

Method : OECD Test Guideline 406 Result : Not a skin sensitizer.

Fatty acids, C18-unsatd., dimers, reaction products with N,N-dimethyl-1,3-propanediamine and 1,3-propanediamine:

Result : Probability or evidence of skin sensitisation in humans

Germ cell mutagenicity

Not classified based on available information.

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Genotoxicity in vitro : Result: negative

Genotoxicity in vivo : Result: negative

Carcinogenicity

Not classified based on available information.

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Result : negative

Reproductive toxicity

Not classified based on available information.

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Effects on foetal develop: : Fertility and developmental toxicity tests did not reveal any

ment effect on reproduction.

according to Regulation (EC) No. 1907/2006

TESSAROL Antik 3in1 silver



Version Revision Date: SDS Number: Date of last issue: 15.03.2021 1.1 22.07.2021 MAT000401637 Date of first issue: 15.03.2021

GB / EN

2-ethylhexanoic acid, zirconium salt:

Reproductive toxicity - As-

sessment

Some evidence of adverse effects on development, based on

animal experiments.

STOT - single exposure

Not classified based on available information.

Components:

hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics:

Assessment : May cause drowsiness or dizziness.

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Remarks : Based on available data, the classification criteria are not met.

1-methoxy-2-propanol:

Assessment : May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Remarks : Based on available data, the classification criteria are not met.

Aspiration toxicity

Not classified based on available information.

Components:

hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics:

May be fatal if swallowed and enters airways.

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

May be fatal if swallowed and enters airways.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006

TESSAROL Antik 3in1 silver



Version Revision Date: SDS Number: Date of last issue: 15.03.2021 1.1 22.07.2021 MAT000401637 Date of first issue: 15.03.2021

GB / EN

Further information

Product:

Remarks Solvents may degrease the skin.

SECTION 12: Ecological information

12.1 Toxicity

Components:

hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics:

Toxicity to fish : LC50 (Fish): > 1.000 mg/l

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : LC50 (Daphnia (water flea)): > 1.000 mg/l

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Toxicity to fish LC50 (Oncorhynchus mykiss (rainbow trout)): > 1.000 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50: > 1.000 mg/l Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

NOEC (Pseudokirchneriella subcapitata (microalgae)): 1.000

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

EC50 (Pseudokirchneriella subcapitata (microalgae)): > 1.000

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to fish (Chronic tox-

icity)

NOELR: 0,10 mg/l Exposure time: 28 d

Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

NOELR: 0,18 mg/l Exposure time: 21 d

ic toxicity)

Species: Daphnia (water flea)

1-methoxy-2-propanol:

Toxicity to fish LC50 (Fish): > 1.000 mg/l

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : LC50 (Daphnia (water flea)): > 1.000 mg/l

according to Regulation (EC) No. 1907/2006

TESSAROL Antik 3in1 silver



Version 1.1

Revision Date: 22.07.2021

SDS Number: MAT000401637

Date of last issue: 15.03.2021 Date of first issue: 15.03.2021

GB / EN

Toxicity to algae/aquatic

plants

: LC50 (algae): > 1.000 mg/l

12.2 Persistence and degradability

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 80 % Exposure time: 28 d

Method: OECD Test Guideline 301F

12.3 Bioaccumulative potential

Components:

1-methoxy-2-propanol:

Partition coefficient: n-

octanol/water

log Pow: -0,437

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Assessment : This substance is not considered to be persistent, bioaccumu-

lating and toxic (PBT)..

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological infor-

mation

: No data available

according to Regulation (EC) No. 1907/2006

TESSAROL Antik 3in1 silver



Version 1.1

Revision Date: 22.07.2021

SDS Number: MAT000401637 GB / EN Date of last issue: 15.03.2021 Date of first issue: 15.03.2021

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

Waste Code : 08 00 00, WASTES FROM THE MANUFACTURE,

FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS

(PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS

08 01 00, wastes from MFSU and removal of paint and var-

nish

08 01 11*, waste paint and varnish containing organic sol-

vents or other hazardous substances

15 00 00, WASTE PACKAGING; ABSORBENTS, WIPING

CLOTHS, FILTER MATERIALS AND PROTECTIVE

CLOTHING NOT OTHERWISE SPECIFIED

15 01 00, packaging (including separately collected municipal

packaging waste)

15 01 10*, packaging containing residues of or contaminated

by hazardous substances

HP3, Flammable

SECTION 14: Transport information

14.1 UN number or ID number

ADN : UN 1263
ADR : UN 1263
RID : UN 1263
IMDG : UN 1263
IATA : UN 1263

14.2 UN proper shipping name

ADN : PAINT
ADR : PAINT
RID : PAINT
IMDG : PAINT
IATA : Paint

according to Regulation (EC) No. 1907/2006



TESSAROL Antik 3in1 silver

Version Revision Date: SDS Number: Date of last issue: 15.03.2021
1.1 22.07.2021 MAT000401637 Date of first issue: 15.03.2021

GB/EN

14.3 Transport hazard class(es)

ADN : 3
ADR : 3
RID : 3
IMDG : 3
IATA : 3

14.4 Packing group

ADN

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

ADR

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3
Tunnel restriction code : (D/E)

RID

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

IMDG

Packing group : III
Labels : 3
EmS Code : F-E, <u>S-E</u>

IATA (Cargo)

Packing instruction (cargo : 366

aircraft)

Packing instruction (LQ) : Y344
Packing group : III

Labels : Flammable Liquids

IATA (Passenger)

Packing instruction (passen: 355

ger aircraft)

Packing instruction (LQ) : Y344
Packing group : III

Labels : Flammable Liquids

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

according to Regulation (EC) No. 1907/2006

TESSAROL Antik 3in1 silver



Version 1.1

Revision Date: 22.07.2021

SDS Number: MAT000401637 Date of last issue: 15.03.2021 Date of first issue: 15.03.2021

GB / EN

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

Remarks : ADR: Packages smaller than or equal to 450 litres, not

goods/merchandise of Class 3 (exemption ADR 2.2.3.1.5) IMDG: Packages smaller than or equal to 450 litres, not goods/merchandise of Class 3; "transport acc. IMDG-code

2.3.2.5"

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mix-

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII)

lowing entries should be considered: Number on list 3

Conditions of restriction for the fol-

REACH - Candidate List of Substances of Very High

Not applicable

Concern for Authorisation (Article 59).

: Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import

of dangerous chemicals

: Not applicable

REACH - List of substances subject to authorisation

(Annex XIV)
Regulation (EC) No 1005/2009 on substances that de-

: Not applicable

plete the ozone layer

: Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

FLAMMABLE LIQUIDS

Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and

P5c

34

according to Regulation (EC) No. 1907/2006

TESSAROL Antik 3in1 silver



Version Revision Date: SDS Number: Date of last issue: 15.03.2021 1.1 22.07.2021 MAT000401637 Date of first issue: 15.03.2021

GB/EN

environmental hazards as the products referred to in points (a)

to (d)

Volatile organic compounds : Directive 2004/42/EC

Volatile organic compounds (VOC) content: 500 g/l

Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

SECTION 16: Other information

Full text of H-Statements

H226 : Flammable liquid and vapour.

H304 : May be fatal if swallowed and enters airways.

H317 : May cause an allergic skin reaction.
H336 : May cause drowsiness or dizziness.
H361d : Suspected of damaging the unborn child.

Full text of other abbreviations

Asp. Tox. : Aspiration hazard Flam. Liq. : Flammable liquids Repr. : Reproductive toxicity Skin Sens. : Skin sensitisation

STOT SE : Specific target organ toxicity - single exposure

2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first

list of indicative occupational exposure limit values

2004/37/EC : Europe. Directive 2004/37/EC on the protection of workers

from the risks related to exposure to carcinogens or mutagens

at work

GB EH40 : UK. EH40 WEL - Workplace Exposure Limits

2000/39/EC / TWA : Limit Value - eight hours 2000/39/EC / STEL : Short term exposure limit 2004/37/EC / TWA : Long term exposure limit

GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP -

according to Regulation (EC) No. 1907/2006

TESSAROL Antik 3in1 silver



Version Revision Date: SDS Number: Date of last issue: 15.03.2021 1.1 22.07.2021 MAT000401637 Date of first issue: 15.03.2021

GB/EN

Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL -International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance: PICCS - Philippines Inventory of Chemicals and Chemical Substances: (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS -Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Classification procedure:

Flam. Liq. 3 H226

Based on product data or assessment

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.