

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL 1K primer filler QDry

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	28.09.2021	MAT000400269	Date of first issue: 28.09.2021
		GB / EN	

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Product code : 400269

Trade name : MOBIHEL 1K primer filler QDry

Unique Formula Identifier (UFI) : X8F0-N02M-V00M-NEMX

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : PC9a Coatings and paints, thinners, paint removers

Recommended restrictions on use : Reserved for industrial and professional use.

#### 1.3 Details of the supplier of the safety data sheet

Company : Helios TBLUS d.o.o.  
Količevo 65  
1230 Domžale  
Slovenia

Telephone Company : 386 (1) 722 4383

Telefax Company : 386 (1) 722 4310

Responsible/issuing person : 386 (1) 722 4383  
productsafety@helios.si

#### 1.4 Emergency telephone number

Call 999 for emergency medical attention

professionals only: National Poison Information Service (NPIS) 24h national number 0844 892 0111

consumer: National Health Service (NHS) 24h national number, England & Scotland 111

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2	H225: Highly flammable liquid and vapour.
Eye irritation, Category 2	H319: Causes serious eye irritation.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL 1K primer filler QDry

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	28.09.2021	MAT000400269	Date of first issue: 28.09.2021
		GB / EN	

Specific target organ toxicity - single exposure, Category 3, Central nervous system

H336: May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure, Category 2

H373: May cause damage to organs through prolonged or repeated exposure.

### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements :  
H225 Highly flammable liquid and vapour.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
H373 May cause damage to organs through prolonged or repeated exposure.

Supplemental Hazard Statements : EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements : **Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 Keep container tightly closed.  
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.  
**Response:**  
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.  
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

#### Hazardous components which must be listed on the label:

n-butyl acetate  
ethyl acetate  
propan-2-ol  
hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclic, aromatic content (2-25%)

#### Additional Labelling

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL 1K primer filler QDry

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	28.09.2021	MAT000400269	Date of first issue: 28.09.2021
		GB / EN	

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
n-butyl acetate	123-86-4 204-658-1 607-025-00-1 01-2119485493-29	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) EUH066	>= 20 - < 30
reaction mixture of ethylbenzene, m-xylene and p-xylene	- 905-562-9 01-2119555267-33	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 Asp. Tox. 1; H304	>= 1 - < 10
ethyl acetate	141-78-6 205-500-4 607-022-00-5 01-2119475103-46	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system) EUH066	>= 1 - < 10
propan-2-ol	67-63-0 200-661-7 603-117-00-0 01-2119457558-25	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system)	>= 1 - < 10
titanium dioxide	13463-67-7 236-675-5 01-2119489379-17	Carc. 2; H351	>= 1 - < 10

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL 1K primer filler QDry

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	28.09.2021	MAT000400269	Date of first issue: 28.09.2021
		GB / EN	

hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclic, aromatic content (2-25%)	- 919-446-0 649-330-00-2 01-2119458049-33	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) STOT RE 1; H372 Asp. Tox. 1; H304 Aquatic Chronic 2; H411	$\geq 1 - < 2,5$
Substances with a workplace exposure limit :			
Talc	14807-96-6 238-877-9 01-2120140278-58		$\geq 1 - < 10$

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.  
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If skin irritation persists, call a physician.  
If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.

#### 4.2 Most important symptoms and effects, both acute and delayed

- Risks : Causes serious eye irritation.  
May cause drowsiness or dizziness.  
May cause damage to organs through prolonged or repeated exposure.  
Repeated exposure may cause skin dryness or cracking.

#### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL 1K primer filler QDry

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	28.09.2021	MAT000400269	Date of first issue: 28.09.2021
		GB / EN	

---

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : High volume water jet

#### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Cool closed containers exposed to fire with water spray.

#### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.

---

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Ensure adequate ventilation.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

#### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL 1K primer filler QDry

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	28.09.2021	MAT000400269	Date of first issue: 28.09.2021
		GB / EN	

---

### 6.4 Reference to other sections

For disposal considerations see section 13., For personal protection see section 8.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

- Advice on safe handling : Avoid formation of aerosol.  
Do not breathe vapours/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Open drum carefully as content may be under pressure.  
Dispose of rinse water in accordance with local and national regulations.
- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.
- Hygiene measures : When using do not eat or drink. When using do not smoke.  
Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage stability : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

- Specific use(s) : For further information, refer to the product technical data sheet.
- Consult the technical guidelines for the use of this substance/mixture.

---

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL 1K primer filler QDry

Version  
1.0

Revision Date:  
28.09.2021

SDS Number:  
MAT000400269  
GB / EN

Date of last issue: -  
Date of first issue: 28.09.2021

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
n-butyl acetate	123-86-4	TWA	150 ppm 724 mg/m <sup>3</sup>	GB EH40
		STEL	200 ppm 966 mg/m <sup>3</sup>	GB EH40
		STEL	150 ppm 723 mg/m <sup>3</sup>	2019/1831/EU
	Further information: Indicative			
		TWA	50 ppm 241 mg/m <sup>3</sup>	2019/1831/EU
	Further information: Indicative			
Calcium carbonate	471-34-1	TWA (inhalable dust)	10 mg/m <sup>3</sup>	GB EH40
		TWA (Respirable dust)	4 mg/m <sup>3</sup>	GB EH40
reaction mixture of ethylbenzene, m-xylene and p-xylene	1330-20-7	TWA	50 ppm 221 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	100 ppm 442 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	50 ppm 220 mg/m <sup>3</sup>	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	100 ppm 441 mg/m <sup>3</sup>	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
ethyl acetate	141-78-6	STEL	400 ppm 1.468 mg/m <sup>3</sup>	2017/164/EU
	Further information: Indicative			
		TWA	200 ppm 734 mg/m <sup>3</sup>	2017/164/EU
	Further information: Indicative			
		TWA	200 ppm 734 mg/m <sup>3</sup>	GB EH40
		STEL	400 ppm 1.468 mg/m <sup>3</sup>	GB EH40
propan-2-ol	67-63-0	TWA	400 ppm 999 mg/m <sup>3</sup>	GB EH40
		STEL	500 ppm 1.250 mg/m <sup>3</sup>	GB EH40
Talc	14807-96-6	TWA (Respirable)	1 mg/m <sup>3</sup>	GB EH40

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL 1K primer filler QDry

Version  
1.0

Revision Date:  
28.09.2021

SDS Number:  
MAT000400269  
GB / EN

Date of last issue: -  
Date of first issue: 28.09.2021

		dust)		
		TWA (Respirable dust)	0,1 mg/m <sup>3</sup>	2004/37/EC
Further information: Carcinogens or mutagens				
titanium dioxide	13463-67-7	TWA (inhalable dust)	10 mg/m <sup>3</sup>	GB EH40
		TWA (Respirable dust)	4 mg/m <sup>3</sup>	GB EH40

### Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
reaction mixture of ethylbenzene, m-xylene and p-xylene	1330-20-7	methyl hippuric acid: 650 Millimoles per mole Creatinine (Urine)	After shift	GB EH40 BAT

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
n-butyl acetate	Workers	Inhalation	Acute systemic effects	600 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	600 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term systemic effects	48 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	300 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute systemic effects	300 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute local effects	300 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term systemic effects	12 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local effects	35,7 mg/m <sup>3</sup>
	Consumers	Dermal	Long-term systemic effects	3,4 mg/kg bw/day
	Consumers	Dermal	Acute systemic effects	6 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	2 mg/kg bw/day
	Consumers	Oral	Acute systemic effects	2 mg/kg bw/day
Calcium carbonate	Workers	Dermal	Long-term systemic effects	7 mg/kg bw/day
	Workers	Dermal	Acute systemic effects	11 mg/kg bw/day
	Workers	Inhalation	Long-term local effects	4,26 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local effects	1,06 mg/m <sup>3</sup>
reaction mixture of ethylbenzene, m-	Workers	Inhalation	Long-term systemic effects	77 mg/m <sup>3</sup>



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL 1K primer filler QDry

Version  
1.0

Revision Date:  
28.09.2021

SDS Number:  
MAT000400269  
GB / EN

Date of last issue: -  
Date of first issue: 28.09.2021

xylene and p-xylene				
	Consumers	Inhalation	Long-term local effects	65,3 mg/m3
	Workers	Inhalation	Acute systemic effects	442 mg/m3
	Workers	Inhalation	Acute local effects	289 mg/m3
	Consumers	Inhalation	Acute systemic effects	260 mg/m3
	Workers	Inhalation	Long-term local effects	221 mg/m3
	Consumers	Inhalation	Long-term systemic effects	14,8 mg/m3
	Consumers	Inhalation	Acute local effects	260 mg/m3
	Consumers	Dermal	Long-term systemic effects	108 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	16 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	180 mg/kg bw/day
ethyl acetate	Workers	Inhalation	Acute systemic effects	1468 mg/m3
	Workers	Inhalation	Long-term local effects	1468 mg/m3
	Workers	Inhalation	Long-term systemic effects	734 mg/m3
	Workers	Inhalation	Long-term local effects	734 mg/m3
	Consumers	Inhalation	Acute systemic effects	734 mg/m3
	Consumers	Inhalation	Acute local effects	734 mg/m3
	Consumers	Inhalation	Long-term systemic effects	367 mg/m3
	Consumers	Inhalation	Long-term local effects	367 mg/m3
	Workers	Dermal	Long-term systemic effects	63 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	37 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	4,5 mg/kg bw/day
propan-2-ol	Workers	Inhalation	Long-term systemic effects	500 mg/m3
	Consumers	Inhalation	Long-term systemic effects	89 mg/m3
	Workers	Dermal	Long-term systemic effects	888 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	319 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	26 mg/kg bw/day
Talc	Workers	Inhalation	Acute systemic effects	2,16 mg/m3

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL 1K primer filler QDry

Version  
1.0

Revision Date:  
28.09.2021

SDS Number:  
MAT000400269  
GB / EN

Date of last issue: -  
Date of first issue: 28.09.2021

	Workers	Inhalation	Acute local effects	3,6 mg/m3
	Consumers	Inhalation	Acute systemic effects	1,08 mg/m3
	Consumers	Inhalation	Acute local effects	1,8 mg/m3
	Consumers	Dermal	Long-term local effects	2,27 mg/cm2
	Workers	Dermal	Long-term local effects	4,54 mg/cm2
	Consumers	Oral	Long-term systemic effects	160 mg/kg bw/day
	Consumers	Oral	Acute systemic effects	160 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	43,2 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	21,6 mg/kg bw/day
titanium dioxide	Workers	Inhalation	Long-term local effects	10 mg/m3
	Consumers	Oral	Long-term systemic effects	700 mg/kg bw/day
hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclic, aromatic content (2-25%)	Workers	Inhalation	Long-term systemic effects	330 mg/m3
	Consumers	Inhalation	Long-term systemic effects	71 mg/m3
	Workers	Dermal	Long-term systemic effects	44 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	26 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	26 mg/kg bw/day

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
n-butyl acetate	Soil	0,0903 mg/kg dry weight (d.w.)
	Marine water	0,018 mg/l
	Fresh water	0,18 mg/l
	Marine sediment	0,0981 mg/kg dry weight (d.w.)
	Fresh water sediment	0,981 mg/kg dry weight (d.w.)
	Sewage treatment plant	35,6 mg/l
	Intermittent use/release	0,36 mg/l
Calcium carbonate	Sewage treatment plant	100 mg/l
reaction mixture of ethylbenzene, m-xylene and p-xylene	Soil	2,31 mg/kg dry weight (d.w.)
	Marine water	0,327 mg/l
	Fresh water	0,327 mg/l
	Marine sediment	12,46 mg/kg dry weight (d.w.)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL 1K primer filler QDry

Version  
1.0

Revision Date:  
28.09.2021

SDS Number:  
MAT000400269  
GB / EN

Date of last issue: -  
Date of first issue: 28.09.2021

	Fresh water sediment	12,46 mg/kg dry weight (d.w.)
	Sewage treatment plant	6,58 mg/l
	Intermittent use/release	0,327 mg/l
ethyl acetate	Soil	0,24 mg/kg dry weight (d.w.)
	Marine water	0,026 mg/l
	Fresh water	0,26 mg/l
	Marine sediment	0,125 mg/kg dry weight (d.w.)
	Fresh water sediment	1,25 mg/kg dry weight (d.w.)
	Sewage treatment plant	650 mg/l
	Intermittent use/release	1,65 mg/l
propan-2-ol	Soil	28 mg/kg
	Marine water	140,9 mg/l
	Fresh water	140,9 mg/l
	Fresh water sediment	552 mg/kg dry weight (d.w.)
	Sewage treatment plant	2251 mg/l
	Intermittent use/release	140,9 mg/l
Talc	Marine water	141,26 mg/l
	Fresh water	597,97 mg/l
	Marine sediment	3,13 mg/kg dry weight (d.w.)
	Fresh water sediment	31,33 mg/kg dry weight (d.w.)
	Intermittent use/release	597,97 mg/l
titanium dioxide	Soil	100 mg/kg dry weight (d.w.)
	Marine water	0,0184 mg/l
	Fresh water	0,184 mg/l
	Marine sediment	100 mg/kg dry weight (d.w.)
	Fresh water sediment	1000 mg/kg dry weight (d.w.)
	Sewage treatment plant	100 mg/l
	Intermittent use/release	0,193 mg/l

### 8.2 Exposure controls

#### Personal protective equipment

Eye protection : Eye wash bottle with pure water  
Tightly fitting safety goggles  
Wear face-shield and protective suit for abnormal processing problems.

Hand protection

Remarks : Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL 1K primer filler QDry

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	28.09.2021	MAT000400269	Date of first issue: 28.09.2021
		GB / EN	

Skin and body protection	:	cuts, abrasion, and the contact time. Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Respiratory protection	:	Wear a full face respirator conforming to EN136 with Type A/P2 filter or better. Self-contained closed-circuit breathing apparatus compressed (EN 145) In the case of aerosol and mist formation use an approved respirator filter (EN 141).

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state	:	liquid
Colour	:	in accordance with the product description
Odour	:	solvent-like
Odour Threshold	:	No data available
Melting point/freezing point	:	-83,6 °C (calculation method (principal components, lowest value))
Boiling point/boiling range	:	36 °C (calculation method (principal components, lowest value))
Flammability	:	Static-accumulating flammable liquid., Combustible Solids
Upper explosion limit / Upper flammability limit	:	11 %(V) (calculation method (principal components, highest value))
Lower explosion limit / Lower flammability limit	:	1,1 %(V) (calculation method (principal components, highest value))
Flash point	:	20 °C  Method: ISO 3679, closed cup
Ignition temperature	:	170 °C (calculation method (principal components, highest value))
Decomposition temperature	:	No decomposition if stored and applied as directed. Hazardous decomposition products formed under fire conditions.
pH	:	Not applicable
Viscosity	:	
Viscosity, kinematic	:	> 20,5 mm <sup>2</sup> /s (40 °C)
Flow time	:	> 60 s at 23 °C

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL 1K primer filler QDry

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	28.09.2021	MAT000400269	Date of first issue: 28.09.2021
		GB / EN	

Cross section: 6 mm

Method: ISO 2431

### Solubility(ies)

Water solubility

: immiscible, partly soluble

Solubility in other solvents

: Description: miscible with most organic solvents

Partition coefficient: n-octanol/water

: log Pow: 2,77 - 3,15 (calculation method (principal components, highest value))

Vapour pressure

: < 1.100 hPa (calculation method (principal components, highest value))  
(50 °C)

Relative density

: No data available

Density

: 1,160 g/cm<sup>3</sup>

Relative vapour density

: 4 (calculation method (principal components, lowest value))

### 9.2 Other information

Explosives

: Not applicable

Oxidizing properties

: Sustains combustion

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions

: No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

### 10.4 Conditions to avoid

Conditions to avoid

: Heat, flames and sparks.

### 10.5 Incompatible materials

Materials to avoid

: Strong acids and oxidizing agents  
Strong reducing agents

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL 1K primer filler QDry

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	28.09.2021	MAT000400269	Date of first issue: 28.09.2021
		GB / EN	

### 10.6 Hazardous decomposition products

Adequate ventilation is required.

Heating can release vapours which can be ignited.

Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Not classified based on available information.

#### Product:

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg  
Method: Calculation method

#### Components:

##### **n-butyl acetate:**

Acute oral toxicity : LD50 Oral (Rat): >= 10.760 mg/kg

Acute dermal toxicity : LD50 (Rabbit): >= 5.000 mg/kg

##### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Acute oral toxicity : LD50 Oral (Rat): >= 8.700 mg/kg

Acute inhalation toxicity : Test atmosphere: vapour  
Assessment: The component/mixture is moderately toxic after short term inhalation.

Acute dermal toxicity : Assessment: The component/mixture is moderately toxic after single contact with skin.

##### **ethyl acetate:**

Acute oral toxicity : LD50 Oral (Rat): >= 5.620 mg/kg

Acute inhalation toxicity : LC50 (Rat): 1600 ppm  
Exposure time: 8 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): >= 20.000 mg/kg

##### **propan-2-ol:**

Acute oral toxicity : LD50 Oral (Rat): >= 5.840 mg/kg

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL 1K primer filler QDry

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	28.09.2021	MAT000400269	Date of first issue: 28.09.2021
		GB / EN	

Acute inhalation toxicity : LC50 (Rat): > 25 mg/l  
Exposure time: 6 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): >= 13.900 mg/kg

### Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

#### Product:

Remarks : May cause skin irritation and/or dermatitis.

#### Components:

##### reaction mixture of ethylbenzene, m-xylene and p-xylene:

Result : irritating

### Serious eye damage/eye irritation

Causes serious eye irritation.

#### Product:

Remarks : May cause irreversible eye damage.

#### Components:

##### reaction mixture of ethylbenzene, m-xylene and p-xylene:

Result : Eye irritation

##### ethyl acetate:

Result : Eye irritation

##### propan-2-ol:

Result : Eye irritation

### Respiratory or skin sensitisation

#### Skin sensitisation

Not classified based on available information.

#### Respiratory sensitisation

Not classified based on available information.

#### Germ cell mutagenicity

Not classified based on available information.

#### Carcinogenicity

Not classified based on available information.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL 1K primer filler QDry

Version  
1.0

Revision Date:  
28.09.2021

SDS Number:  
MAT000400269  
GB / EN

Date of last issue: -  
Date of first issue: 28.09.2021

---

### **Reproductive toxicity**

Not classified based on available information.

### **STOT - single exposure**

May cause drowsiness or dizziness.

### **Components:**

#### **n-butyl acetate:**

Assessment : May cause drowsiness or dizziness.

#### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Assessment : May cause respiratory irritation.

#### **ethyl acetate:**

Assessment : May cause drowsiness or dizziness.

#### **propan-2-ol:**

Assessment : May cause drowsiness or dizziness.

#### **hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclic, aromatic content (2-25%):**

Assessment : May cause drowsiness or dizziness.

### **STOT - repeated exposure**

May cause damage to organs through prolonged or repeated exposure.

### **Components:**

#### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Assessment : May cause damage to organs through prolonged or repeated exposure.

#### **hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclic, aromatic content (2-25%):**

Assessment : Causes damage to organs through prolonged or repeated exposure.

### **Aspiration toxicity**

Not classified based on available information.

### **Components:**

#### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

May be fatal if swallowed and enters airways.

#### **hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclic, aromatic content (2-25%):**

May be fatal if swallowed and enters airways.



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL 1K primer filler QDry

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	28.09.2021	MAT000400269	Date of first issue: 28.09.2021
		GB / EN	

### 11.2 Information on other hazards

#### Endocrine disrupting properties

##### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

#### Further information

##### Product:

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.  
Concentrations substantially above the TLV value may cause narcotic effects.  
Solvents may degrease the skin.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

##### **n-butyl acetate:**

Toxicity to algae/aquatic plants : NOEC (Desmodesmus subspicatus (green algae)): > 200 mg/l  
EC50 (Desmodesmus subspicatus (green algae)): >= 647,7 mg/l  
Exposure time: 72 h

Toxicity to microorganisms : IC50 (Tetrahymena pyriformis): 356 mg/l  
Exposure time: 40 h

##### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Toxicity to fish : LC50 (Fish): >= 1 - 10 mg/l

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)): >= 1 - 10 mg/l

Toxicity to microorganisms : EC50 (Bacteria): >= 1 - 100 mg/l

##### **propan-2-ol:**

Toxicity to fish : LC50 (Fish): > 100 mg/l  
Exposure time: 48 h

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)): > 100 mg/l  
Exposure time: 48 h

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL 1K primer filler QDry

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	28.09.2021	MAT000400269	Date of first issue: 28.09.2021
		GB / EN	

Toxicity to microorganisms : EC50 (Bacteria): > 1.000 mg/l

**hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclic, aromatic content (2-25%):**

### Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

## 12.2 Persistence and degradability

### Components:

#### **n-butyl acetate:**

Biodegradability : Result: Biodegradable  
Biodegradation: 83 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301D

Stability in water : Degradation half life: 78 d  
pH: 8  
Hydrolyses slowly.

Photodegradation : Decomposes rapidly in contact with light.

#### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Biodegradability : Readily biodegradable.

Photodegradation : Decomposes rapidly in contact with light.

## 12.3 Bioaccumulative potential

### Components:

#### **n-butyl acetate:**

Bioaccumulation : Bioconcentration factor (BCF): 15  
Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water : log Pow: 1,81

#### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Bioaccumulation : Bioconcentration factor (BCF): 25,9  
Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water : log Pow: 2,77 - 3,15

#### **ethyl acetate:**

Partition coefficient: n-octanol/water : log Pow: 0,6

#### **propan-2-ol:**

Partition coefficient: n-octanol/water : log Pow: 0,05

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL 1K primer filler QDry

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	28.09.2021	MAT000400269	Date of first issue: 28.09.2021
		GB / EN	

---

octanol/water

### 12.4 Mobility in soil

#### Components:

##### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Distribution among environmental compartments : Koc: 537, log Koc: 2,73  
Moderately mobile in soils  
The product evaporates from soil.

Stability in soil : Dissipation time: 23 d  
Percentage dissipation: 50 % (DT50)

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

### 12.6 Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

#### Product:

Additional ecological information : No data available

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product	: Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.
Contaminated packaging	: Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.
Waste Code	: 08 01 11*, waste paint and varnish containing organic solvents or other hazardous substances

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL 1K primer filler QDry

Version  
1.0

Revision Date:  
28.09.2021

SDS Number:  
MAT000400269  
GB / EN

Date of last issue: -  
Date of first issue: 28.09.2021

---

### SECTION 14: Transport information

#### 14.1 UN number or ID number

ADN	:	UN 1263
ADR	:	UN 1263
RID	:	UN 1263
IMDG	:	UN 1263
IATA	:	UN 1263

#### 14.2 UN proper shipping name

ADN	:	PAINT
ADR	:	PAINT
RID	:	PAINT
IMDG	:	PAINT
IATA	:	Paint

#### 14.3 Transport hazard class(es)

ADN	:	3
ADR	:	3
RID	:	3
IMDG	:	3
IATA	:	3

#### 14.4 Packing group

<b>ADN</b>	
Packing group	: III
Classification Code	: F1
Labels	: 3
<b>ADR</b>	
Packing group	: III
Classification Code	: F1
Labels	: 3
Tunnel restriction code	: (E)
Remarks	: ADR 2.2.3.1.4 (> 450 L --> PG = II)
<b>RID</b>	
Packing group	: III
Classification Code	: F1
Hazard Identification Number	: 33
Labels	: 3
Remarks	: RID 2.2.3.1.4 (> 450 L --> PG = II)
<b>IMDG</b>	

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL 1K primer filler QDry

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	28.09.2021	MAT000400269	Date of first issue: 28.09.2021
		GB / EN	

Packing group : III  
Labels : 3  
EmS Code : F-E, S-E  
Remarks : IMDG 2.2.3.2 (> 450 L --> PG = II)

### IATA (Cargo)

Packing instruction (cargo aircraft) : 364  
Packing instruction (LQ) : Y341  
Packing group : II  
Labels : Flammable Liquids  
Remarks : IATA\_C 3.3.3.1.1 (< 100 L --> PG = III)

### IATA (Passenger)

Packing instruction (passenger aircraft) : 353  
Packing instruction (LQ) : Y341  
Packing group : II  
Labels : Flammable Liquids  
Remarks : IATA\_P 3.3.3.1.1 (< 30 L --> PG = III)

## 14.5 Environmental hazards

### ADN

Environmentally hazardous : no

### ADR

Environmentally hazardous : no

### RID

Environmentally hazardous : no

### IMDG

Marine pollutant : no

## 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII)	: Conditions of restriction for the following entries should be considered: Number on list 3
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	: Not applicable
REACH - List of substances subject to authorisation (Annex XIV)	: Not applicable
Regulation (EC) No 1005/2009 on substances that de-	: Not applicable

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL 1K primer filler QDry

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	28.09.2021	MAT000400269	Date of first issue: 28.09.2021
		GB / EN	

plete the ozone layer

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

P5c

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P5c FLAMMABLE LIQUIDS

### Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

### 15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

## SECTION 16: Other information

### Full text of H-Statements

H225	: Highly flammable liquid and vapour.
H226	: Flammable liquid and vapour.
H304	: May be fatal if swallowed and enters airways.
H312	: Harmful in contact with skin.
H315	: Causes skin irritation.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H351	: Suspected of causing cancer if inhaled.
H372	: Causes damage to organs through prolonged or repeated exposure.
H373	: May cause damage to organs through prolonged or repeated exposure.
H411	: Toxic to aquatic life with long lasting effects.
EUH066	: Repeated exposure may cause skin dryness or cracking.

### Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Carc.	: Carcinogenicity
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Skin Irrit.	: Skin irritation

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL 1K primer filler QDry

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	28.09.2021	MAT000400269	Date of first issue: 28.09.2021
		GB / EN	

STOT RE	: Specific target organ toxicity - repeated exposure
STOT SE	: Specific target organ toxicity - single exposure
2000/39/EC	: Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2004/37/EC	: Europe. Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens or mutagens at work
2017/164/EU	: Europe. Commission Directive 2017/164/EU establishing a fourth list of indicative occupational exposure limit values
2019/1831/EU	: Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values
GB EH40	: UK. EH40 WEL - Workplace Exposure Limits
GB EH40 BAT	: UK. Biological monitoring guidance values
2000/39/EC / TWA	: Limit Value - eight hours
2000/39/EC / STEL	: Short term exposure limit
2004/37/EC / TWA	: Long term exposure limit
2017/164/EU / STEL	: Short term exposure limit
2017/164/EU / TWA	: Limit Value - eight hours
2019/1831/EU / TWA	: Limit Value - eight hours
2019/1831/EU / STEL	: Short term exposure limit
GB EH40 / TWA	: Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	: Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS -

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL 1K primer filler QDry

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	28.09.2021	MAT000400269	Date of first issue: 28.09.2021
		GB / EN	

Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States);  
UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

#### Classification of the mixture:

Flam. Liq. 2	H225
Eye Irrit. 2	H319
STOT SE 3	H336
STOT RE 2	H373

#### Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.