

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL Clear base

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 12.11.2021 | MAT000418258 | Date of first issue: 12.11.2021 |
| | | GB / EN | |

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product code : 418258

Trade name : MOBIHEL Clear base

Unique Formula Identifier (UFI) : Y2M0-Y0QV-100A-PJ8J

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : PC9a Coatings and paints, thinners, paint removers

Recommended restrictions on use : Reserved for industrial and professional use.

1.3 Details of the supplier of the safety data sheet

Company : Helios TBLUS d.o.o.
Količevo 65
1230 Domžale
Slovenia

Telephone Company : 386 (1) 722 4383

Telefax Company : 386 (1) 722 4310

Responsible/issuing person : 386 (1) 722 4383
productsafety@helios.si

1.4 Emergency telephone number

Call 999 for emergency medical attention

professionals only: National Poison Information Service (NPIS) 24h national number 0844 892 0111

consumer: National Health Service (NHS) 24h national number, England & Scotland 111

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

| | |
|-------------------------------|------------------------------------|
| Flammable liquids, Category 3 | H226: Flammable liquid and vapour. |
| Skin irritation, Category 2 | H315: Causes skin irritation. |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006




MOBIHEL Clear base

| | | | |
|---------|----------------|-------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 12.11.2021 | MAT000418258 GB / EN | Date of first issue: 12.11.2021 |

| | |
|--|--|
| Serious eye damage, Category 1 Reproductive toxicity, Category 2 | H318: Causes serious eye damage. H361: Suspected of damaging fertility or the unborn child. |
| Specific target organ toxicity - single exposure, Category 3, Central nervous system | H336: May cause drowsiness or dizziness. |

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms : 

Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H336 May cause drowsiness or dizziness.
H361 Suspected of damaging fertility or the unborn child.

Precautionary statements : **Prevention:**
P201 Obtain special instructions before use.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

n-butyl acetate
hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclic, <2% aromatics
butan-1-ol
butyl glycolate

Additional Labelling

EUH208 Contains formaldehyde. May produce an allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL Clear base

Version
1.0

Revision Date:
12.11.2021

SDS Number:
MAT000418258
GB / EN

Date of last issue: -
Date of first issue: 12.11.2021

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

| Chemical name | CAS-No. EC-No. Index-No. Registration number | Classification | Concentration (% w/w) |
|--|--|---|--------------------------|
| n-butyl acetate | 123-86-4 204-658-1 607-025-00-1 01-2119485493-29 | Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) EUH066 | >= 30 - < 50 |
| hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclic, <2% aromatics | - 01-2119471843-32 | Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) Asp. Tox. 1; H304 Aquatic Chronic 3; H412 | >= 20 - < 25 |
| 1-ethoxypropan-2-ol | 1569-02-4 216-374-5 603-177-00-8 01-2119462792-32 | Flam. Liq. 3; H226 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system) | >= 10 - < 20 |
| butan-1-ol | 71-36-3 200-751-6 603-004-00-6 01-2119484630-38 | Flam. Liq. 3; H226 Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system) | >= 10 - < 20 |
| reaction mixture of ethylbenzene, m-xylene and p-xylene | - 905-562-9 01-2119555267-33 | Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) | >= 1 - < 10 |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL Clear base

Version 1.0 Revision Date: 12.11.2021 SDS Number: MAT000418258 GB / EN Date of last issue: - Date of first issue: 12.11.2021

| | | | |
|------------------|--|--|-----------------|
| | | STOT RE 2; H373 Asp. Tox. 1; H304 | |
| butyl glycollate | 7397-62-8 230-991-7 01-2119514685-36 | Eye Dam. 1; H318 Repr. 2; H361 | $\geq 3 - < 10$ |
| formaldehyde | 50-00-0 200-001-8 605-001-00-5 01-2119488953-20 | Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 3; H311 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1; H317 Muta. 2; H341 Carc. 1B; H350 STOT SE 3; H335 (Respiratory system) specific concentration limit Skin Corr. 1B; H314 $\geq 25\%$ Skin Irrit. 2; H315 5 - $< 25\%$ Eye Irrit. 2; H319 5 - $< 25\%$ STOT SE 3; H335 $\geq 5\%$ Skin Sens. 1; H317 $\geq 0,2\%$ | $< 0,1$ |

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL Clear base

| | | | |
|---------|----------------|-------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 12.11.2021 | MAT000418258 GB / EN | Date of first issue: 12.11.2021 |

Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

Risks : Causes skin irritation.
Causes serious eye damage.
May cause drowsiness or dizziness.
Suspected of damaging fertility or the unborn child.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : No hazardous combustion products are known.

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL Clear base

| | | | |
|---------|----------------|-------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 12.11.2021 | MAT000418258 GB / EN | Date of first issue: 12.11.2021 |

Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
To avoid spills during handling keep bottle on a metal tray.
Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : When using do not eat or drink. When using do not smoke.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL Clear base

Version 1.0 Revision Date: 12.11.2021 SDS Number: MAT000418258 GB / EN Date of last issue: - Date of first issue: 12.11.2021

Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : For further information, refer to the product technical data sheet.

Consult the technical guidelines for the use of this substance/mixture.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

| Components | CAS-No. | Value type (Form of exposure) | Control parameters | Basis |
|---|--|-------------------------------|----------------------------------|------------------|
| n-butyl acetate | 123-86-4 | TWA | 150 ppm 724 mg/m ³ | GB EH40 |
| | | STEL | 200 ppm 966 mg/m ³ | GB EH40 |
| | | STEL | 150 ppm 723 mg/m ³ | 2019/1831/E U |
| | Further information: Indicative | | | |
| | | TWA | 50 ppm 241 mg/m ³ | 2019/1831/E U |
| | Further information: Indicative | | | |
| butan-1-ol | 71-36-3 | STEL | 50 ppm 154 mg/m ³ | GB EH40 |
| | Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity. | | | |
| reaction mixture of ethylbenzene, m-xylene and p-xylene | 1330-20-7 | TWA | 50 ppm 221 mg/m ³ | 2000/39/EC |
| | Further information: Identifies the possibility of significant uptake through the skin, Indicative | | | |
| | | STEL | 100 ppm 442 mg/m ³ | 2000/39/EC |
| | Further information: Identifies the possibility of significant uptake through the skin, Indicative | | | |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL Clear base

Version
1.0

Revision Date:
12.11.2021

SDS Number:
MAT000418258
GB / EN

Date of last issue: -
Date of first issue: 12.11.2021

| | | | | |
|--------------|--|------|-----------------------------------|------------|
| | | TWA | 50 ppm 220 mg/m ³ | GB EH40 |
| | Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity. | | | |
| | | STEL | 100 ppm 441 mg/m ³ | GB EH40 |
| | Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity. | | | |
| formaldehyde | 50-00-0 | TWA | 2 ppm 2,5 mg/m ³ | GB EH40 |
| | Further information: Capable of causing cancer and/or heritable genetic damage. | | | |
| | | STEL | 2 ppm 2,5 mg/m ³ | GB EH40 |
| | Further information: Capable of causing cancer and/or heritable genetic damage. | | | |
| | | TWA | 0,3 ppm 0,37 mg/m ³ | 2004/37/EC |
| | Further information: Dermal sensitisation, Carcinogens or mutagens | | | |
| | | STEL | 0,6 ppm 0,74 mg/m ³ | 2004/37/EC |
| | Further information: Dermal sensitisation, Carcinogens or mutagens | | | |

Biological occupational exposure limits

| Substance name | CAS-No. | Control parameters | Sampling time | Basis |
|---|-----------|--|---------------|----------------|
| reaction mixture of ethylbenzene, m-xylene and p-xylene | 1330-20-7 | methyl hippuric acid: 650 Millimoles per mole Creatinine (Urine) | After shift | GB EH40 BAT |

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

| Substance name | End Use | Exposure routes | Potential health effects | Value |
|-----------------|-----------|-----------------|----------------------------|------------------------|
| n-butyl acetate | Workers | Inhalation | Acute systemic effects | 600 mg/m ³ |
| | Workers | Inhalation | Acute local effects | 600 mg/m ³ |
| | Workers | Inhalation | Long-term systemic effects | 48 mg/m ³ |
| | Workers | Inhalation | Long-term local effects | 300 mg/m ³ |
| | Consumers | Inhalation | Acute systemic effects | 300 mg/m ³ |
| | Consumers | Inhalation | Acute local effects | 300 mg/m ³ |
| | Consumers | Inhalation | Long-term systemic effects | 12 mg/m ³ |
| | Consumers | Inhalation | Long-term local effects | 35,7 mg/m ³ |
| | Consumers | Dermal | Long-term systemic effects | 3,4 mg/kg bw/day |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL Clear base

Version
1.0

Revision Date:
12.11.2021

SDS Number:
MAT000418258
GB / EN

Date of last issue: -
Date of first issue: 12.11.2021

| | | | | |
|--|-----------|------------|----------------------------|--------------------|
| | Consumers | Dermal | Acute systemic effects | 6 mg/kg bw/day |
| | Consumers | Oral | Long-term systemic effects | 2 mg/kg bw/day |
| | Consumers | Oral | Acute systemic effects | 2 mg/kg bw/day |
| | Workers | Dermal | Long-term systemic effects | 7 mg/kg bw/day |
| | Workers | Dermal | Acute systemic effects | 11 mg/kg bw/day |
| hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclic, <2% aromatics | Workers | Inhalation | Long-term systemic effects | 871 mg/m3 |
| | Consumers | Inhalation | Long-term systemic effects | 185 mg/m3 |
| | Workers | Dermal | Long-term systemic effects | 208 mg/kg bw/day |
| | Consumers | Dermal | Long-term systemic effects | 125 mg/kg bw/day |
| | Consumers | Oral | Long-term systemic effects | 125 mg/kg bw/day |
| butan-1-ol | Workers | Inhalation | Long-term local effects | 310 mg/m3 |
| | Consumers | Inhalation | Long-term systemic effects | 55,357 mg/m3 |
| | Consumers | Inhalation | Long-term local effects | 155 mg/m3 |
| | Consumers | Dermal | Long-term systemic effects | 3,125 mg/kg bw/day |
| | Consumers | Oral | Long-term systemic effects | 1,562 mg/kg bw/day |
| reaction mixture of ethylbenzene, m-xylene and p-xylene | Workers | Inhalation | Long-term systemic effects | 77 mg/m3 |
| | Consumers | Inhalation | Long-term local effects | 65,3 mg/m3 |
| | Workers | Inhalation | Acute systemic effects | 442 mg/m3 |
| | Workers | Inhalation | Acute local effects | 289 mg/m3 |
| | Consumers | Inhalation | Acute systemic effects | 260 mg/m3 |
| | Workers | Inhalation | Long-term local effects | 221 mg/m3 |
| | Consumers | Inhalation | Long-term systemic effects | 14,8 mg/m3 |
| | Consumers | Inhalation | Acute local effects | 260 mg/m3 |
| | Consumers | Dermal | Long-term systemic effects | 108 mg/kg bw/day |
| | Consumers | Oral | Long-term systemic effects | 16 mg/kg bw/day |
| | Workers | Dermal | Long-term systemic | 180 mg/kg |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL Clear base

Version
1.0

Revision Date:
12.11.2021

SDS Number:
MAT000418258
GB / EN

Date of last issue: -
Date of first issue: 12.11.2021

| | | | effects | bw/day |
|------------------|-----------|------------|----------------------------|-------------------------|
| butyl glycollate | Workers | Inhalation | Long-term systemic effects | 58,8 mg/m ³ |
| | Consumers | Inhalation | Long-term systemic effects | 17,4 mg/m ³ |
| | Consumers | Inhalation | Long-term local effects | 17,4 mg/m ³ |
| | Consumers | Dermal | Long-term local effects | 0,11 mg/cm ² |
| | Consumers | Oral | Long-term systemic effects | 4,2 mg/kg bw/day |
| | Workers | Dermal | Long-term systemic effects | 41,7 mg/kg bw/day |
| | Consumers | Dermal | Long-term systemic effects | 25 mg/kg bw/day |
| formaldehyde | Workers | Inhalation | Long-term systemic effects | 9 mg/m ³ |
| | Consumers | Inhalation | Long-term systemic effects | 3,2 mg/m ³ |
| | Workers | Dermal | Long-term systemic effects | 240 mg/kg bw/day |
| | Consumers | Dermal | Long-term systemic effects | 102 mg/kg bw/day |
| | Consumers | Oral | Long-term systemic effects | 4,1 mg/kg bw/day |

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

| Substance name | Environmental Compartment | Value |
|---|---------------------------|--------------------------------|
| n-butyl acetate | Soil | 0,0903 mg/kg dry weight (d.w.) |
| | Marine water | 0,018 mg/l |
| | Fresh water | 0,18 mg/l |
| | Marine sediment | 0,0981 mg/kg dry weight (d.w.) |
| | Fresh water sediment | 0,981 mg/kg dry weight (d.w.) |
| | Sewage treatment plant | 35,6 mg/l |
| | Intermittent use/release | 0,36 mg/l |
| butan-1-ol | Soil | 0,0166 mg/kg dry weight (d.w.) |
| | Marine water | 0,0082 mg/l |
| | Fresh water | 0,082 mg/l |
| | Marine sediment | 0,0324 mg/kg dry weight (d.w.) |
| | Fresh water sediment | 0,324 mg/kg dry weight (d.w.) |
| | Sewage treatment plant | 2476 mg/l |
| | Intermittent use/release | 2,25 mg/l |
| reaction mixture of ethylbenzene, m-xylene and p-xylene | Soil | 2,31 mg/kg dry weight (d.w.) |
| | Marine water | 0,327 mg/l |
| | Fresh water | 0,327 mg/l |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL Clear base

Version
1.0

Revision Date:
12.11.2021

SDS Number:
MAT000418258
GB / EN

Date of last issue: -
Date of first issue: 12.11.2021

| | | |
|------------------|--------------------------|--------------------------------|
| | Marine sediment | 12,46 mg/kg dry weight (d.w.) |
| | Fresh water sediment | 12,46 mg/kg dry weight (d.w.) |
| | Sewage treatment plant | 6,58 mg/l |
| | Intermittent use/release | 0,327 mg/l |
| butyl glycollate | Soil | 0,0112 mg/kg dry weight (d.w.) |
| | Marine water | 0,005 mg/l |
| | Fresh water | 0,05 mg/l |
| | Marine sediment | 0,0203 mg/kg dry weight (d.w.) |
| | Fresh water sediment | 0,203 mg/kg dry weight (d.w.) |
| | Sewage treatment plant | 232 mg/l |
| | Intermittent use/release | 0,5 mg/l |
| formaldehyde | Marine water | 0,44 mg/l |
| | Fresh water | 0,44 mg/l |
| | Marine sediment | 2,3 mg/kg dry weight (d.w.) |
| | Fresh water sediment | 2,3 mg/kg dry weight (d.w.) |
| | Sewage treatment plant | 0,19 mg/l |
| | Intermittent use/release | 4,44 mg/l |

8.2 Exposure controls

Personal protective equipment

Eye protection : Equipment should conform to EN 166
Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Hand protection

Gloves : | Viton® (> 0,6 mm; < 240 min); DIN EN374 | | PE laminate (> 0,1 mm; < 240 min); DIN EN374 |

Remarks : Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Equipment should conform to EN 14387

Filter type : Organic vapour type (A)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL Clear base

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 12.11.2021 | MAT000418258 | Date of first issue: 12.11.2021 |
| | | GB / EN | |

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

| | |
|--|---|
| Physical state | : liquid |
| Colour | : colourless |
| Odour | : solvent-like |
| Odour Threshold | : No data available |
| Melting point/freezing point | : -78,0 °C (calculation method (principal components, lowest value)) |
| Boiling point/boiling range | : 80 - 110 °C (calculation method (principal components, lowest value)) |
| Flammability | : Static-accumulating flammable liquid., Combustible Solids |
| Upper explosion limit / Upper flammability limit | : 12 %(V) (calculation method (principal components, highest value)) |
| Lower explosion limit / Lower flammability limit | : 1,2 %(V) (calculation method (principal components, highest value)) |
| Flash point | : 23 °C Method: ISO 3679, closed cup |
| Ignition temperature | : 343 °C (calculation method (principal components, highest value)) |
| Decomposition temperature | |
| Decomposition temperature | : No decomposition if stored and applied as directed. Hazardous decomposition products formed under fire conditions. |
| pH | : Not applicable |
| Viscosity | |
| Viscosity, kinematic | : > 20,5 mm ² /s (40 °C) |
| Flow time | : 20 - 22 s at 20 °C Cross section: 4 mm Method: DIN 53211 |
| Solubility(ies) | |
| Water solubility | : immiscible, partly soluble |
| Solubility in other solvents | : Description: miscible with most organic solvents |
| Partition coefficient: n-octanol/water | : log Pow: 1,81 (calculation method (principal components, highest value)) |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL Clear base

| | | | |
|---------|----------------|-------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 12.11.2021 | MAT000418258 GB / EN | Date of first issue: 12.11.2021 |

| | | |
|-------------------------|---|---|
| Vapour pressure | : | < 1.100 hPa (calculation method (principal components, highest value)) (50 °C) |
| Relative density | : | No data available |
| Density | : | 0,881 g/cm ³ |
| Relative vapour density | : | No data available |

9.2 Other information

| | | |
|----------------------|---|---------------------|
| Explosives | : | Not applicable |
| Oxidizing properties | : | Sustains combustion |

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

| | | |
|---------------------|---|---|
| Hazardous reactions | : | No decomposition if stored and applied as directed. |
|---------------------|---|---|

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

| | | |
|---------------------|---|--------------------------|
| Conditions to avoid | : | Heat, flames and sparks. |
|---------------------|---|--------------------------|

10.5 Incompatible materials

| | | |
|--------------------|---|---|
| Materials to avoid | : | Incompatible with strong acids and bases. |
|--------------------|---|---|

10.6 Hazardous decomposition products

Adequate ventilation is required.
Heating can release vapours which can be ignited.
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL Clear base

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 12.11.2021 | MAT000418258 | Date of first issue: 12.11.2021 |
| | | GB / EN | |

Product:

Acute oral toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

Components:

n-butyl acetate:

Acute oral toxicity : LD50 Oral (Rat): \geq 10.760 mg/kg

Acute dermal toxicity : LD50 (Rabbit): \geq 5.000 mg/kg

butan-1-ol:

Acute oral toxicity : Assessment: The component/mixture is moderately toxic after single ingestion.

LD50 Oral (Rat): > 2.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Acute oral toxicity : LD50 Oral (Rat): \geq 8.700 mg/kg

Acute inhalation toxicity : Test atmosphere: vapour
Assessment: The component/mixture is moderately toxic after short term inhalation.

Acute dermal toxicity : Assessment: The component/mixture is moderately toxic after single contact with skin.

formaldehyde:

Acute oral toxicity : Assessment: The component/mixture is toxic after single ingestion.

Acute inhalation toxicity : Test atmosphere: vapour
Assessment: The component/mixture is highly toxic after short term inhalation.

Acute dermal toxicity : Assessment: The component/mixture is toxic after single contact with skin.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL Clear base

Version
1.0

Revision Date:
12.11.2021

SDS Number:
MAT000418258
GB / EN

Date of last issue: -
Date of first issue: 12.11.2021

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks : Extremely corrosive and destructive to tissue.

Components:

butan-1-ol:

Result : irritating

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Result : irritating

formaldehyde:

Result : Corrosive after 3 minutes to 1 hour of exposure

Serious eye damage/eye irritation

Causes serious eye damage.

Product:

Remarks : May cause irreversible eye damage.

Components:

1-ethoxypropan-2-ol:

Result : Eye irritation

butan-1-ol:

Result : Corrosive

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Result : Eye irritation

butyl glycollate:

Result : Corrosive

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL Clear base

| | | | |
|---------|----------------|-------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 12.11.2021 | MAT000418258 GB / EN | Date of first issue: 12.11.2021 |

Components:

formaldehyde:

Result : Probability or evidence of skin sensitisation in humans

Germ cell mutagenicity

Not classified based on available information.

Components:

formaldehyde:

Germ cell mutagenicity- Assessment : In vitro tests showed mutagenic effects

Carcinogenicity

Not classified based on available information.

Components:

formaldehyde:

Carcinogenicity - Assessment : Possible human carcinogen

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

Components:

butyl glycollate:

Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments.

STOT - single exposure

May cause drowsiness or dizziness.

Components:

n-butyl acetate:

Assessment : May cause drowsiness or dizziness.

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclic, <2% aromatics:

Assessment : May cause drowsiness or dizziness.

1-ethoxypropan-2-ol:

Assessment : May cause drowsiness or dizziness.

butan-1-ol:

Assessment : May cause drowsiness or dizziness.

Assessment : May cause respiratory irritation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL Clear base

| | | | |
|---------|----------------|-------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 12.11.2021 | MAT000418258 GB / EN | Date of first issue: 12.11.2021 |

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Assessment : May cause respiratory irritation.

formaldehyde:

Assessment : May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Components:

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Assessment : May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

Components:

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclic, <2% aromatics:

May be fatal if swallowed and enters airways.

reaction mixture of ethylbenzene, m-xylene and p-xylene:

May be fatal if swallowed and enters airways.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Further information

Product:

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.
Concentrations substantially above the TLV value may cause narcotic effects.
Solvents may degrease the skin.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL Clear base

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 12.11.2021 | MAT000418258 | Date of first issue: 12.11.2021 |
| | | GB / EN | |

SECTION 12: Ecological information

12.1 Toxicity

Components:

n-butyl acetate:

Toxicity to algae/aquatic plants : NOEC (Desmodesmus subspicatus (green algae)): > 200 mg/l
EC50 (Desmodesmus subspicatus (green algae)): >= 647,7 mg/l
Exposure time: 72 h

Toxicity to microorganisms : IC50 (Tetrahymena pyriformis): 356 mg/l
Exposure time: 40 h

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclic, <2% aromatics:

Ecotoxicology Assessment

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

butan-1-ol:

Toxicity to fish : LC50 (Fish): > 1.000 mg/l

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)): > 1.000 mg/l

Toxicity to microorganisms : EC50 (Bacteria): > 1.000 mg/l

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Toxicity to fish : LC50 (Fish): >= 1 - 10 mg/l

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)): >= 1 - 10 mg/l

Toxicity to microorganisms : EC50 (Bacteria): >= 1 - 100 mg/l

12.2 Persistence and degradability

Components:

n-butyl acetate:

Biodegradability : Result: Biodegradable
Biodegradation: 83 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

Stability in water : Degradation half life: 78 d
pH: 8
Hydrolyses slowly.

Photodegradation : Decomposes rapidly in contact with light.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL Clear base

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 12.11.2021 | MAT000418258 | Date of first issue: 12.11.2021 |
| | | GB / EN | |

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Biodegradability : Readily biodegradable.

Photodegradation : Decomposes rapidly in contact with light.

12.3 Bioaccumulative potential

Components:

n-butyl acetate:

Bioaccumulation : Bioconcentration factor (BCF): 15
Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water : log Pow: 1,81

butan-1-ol:

Partition coefficient: n-octanol/water : log Pow: 0,785

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Bioaccumulation : Bioconcentration factor (BCF): 25,9
Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water : log Pow: 2,77 - 3,15

formaldehyde:

Partition coefficient: n-octanol/water : log Pow: 0,35

12.4 Mobility in soil

Components:

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Distribution among environmental compartments : Koc: 537, log Koc: 2,73
Moderately mobile in soils
The product evaporates from soil.

Stability in soil : Dissipation time: 23 d
Percentage dissipation: 50 % (DT50)

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL Clear base

| | | | |
|---------|----------------|-------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 12.11.2021 | MAT000418258 GB / EN | Date of first issue: 12.11.2021 |

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

Waste Code : 08 00 00, WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01 00, wastes from MFSU and removal of paint and varnish
08 01 11*, waste paint and varnish containing organic solvents or other hazardous substances
15 00 00, WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED
15 01 00, packaging (including separately collected municipal packaging waste)
15 01 10*, packaging containing residues of or contaminated by hazardous substances
HP3, Flammable
HP4, Irritant - skin irritation and eye damage
HP10, Toxic for reproduction

SECTION 14: Transport information

14.1 UN number or ID number

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL Clear base

Version 1.0
Revision Date: 12.11.2021
SDS Number: MAT000418258
GB / EN

Date of last issue: -
Date of first issue: 12.11.2021

ADN : UN 1263
ADR : UN 1263
RID : UN 1263
IMDG : UN 1263
IATA : UN 1263

14.2 UN proper shipping name

ADN : PAINT
ADR : PAINT
RID : PAINT
IMDG : PAINT
IATA : Paint

14.3 Transport hazard class(es)

ADN : 3
ADR : 3
RID : 3
IMDG : 3
IATA : 3

14.4 Packing group

ADN
Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

ADR
Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3
Tunnel restriction code : (D/E)

RID
Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

IMDG
Packing group : III
Labels : 3
EmS Code : F-E, S-E

IATA (Cargo)
Packing instruction (cargo) : 366

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL Clear base

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 12.11.2021 | MAT000418258 | Date of first issue: 12.11.2021 |
| | | GB / EN | |

aircraft)
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids

IATA (Passenger)

Packing instruction (passenger aircraft) : 355
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

| | |
|--|---|
| REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) | : Conditions of restriction for the following entries should be considered: Number on list 3 formaldehyde (Number on list 72, 28) |
| Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals | : Not applicable |
| REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). | : Not applicable |
| REACH - List of substances subject to authorisation (Annex XIV) | : Not applicable |
| Regulation (EC) No 1005/2009 on substances that deplete the ozone layer | : Not applicable |
| Regulation (EU) 2019/1021 on persistent organic pollutants | : Not applicable |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL Clear base

| | | | |
|---------|----------------|-------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 12.11.2021 | MAT000418258 GB / EN | Date of first issue: 12.11.2021 |

tants (recast)

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P5c FLAMMABLE LIQUIDS

Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

SECTION 16: Other information

Full text of H-Statements

| | |
|--------|--|
| H226 | : Flammable liquid and vapour. |
| H301 | : Toxic if swallowed. |
| H302 | : Harmful if swallowed. |
| H304 | : May be fatal if swallowed and enters airways. |
| H311 | : Toxic in contact with skin. |
| H312 | : Harmful in contact with skin. |
| H314 | : Causes severe skin burns and eye damage. |
| H315 | : Causes skin irritation. |
| H317 | : May cause an allergic skin reaction. |
| H318 | : Causes serious eye damage. |
| H319 | : Causes serious eye irritation. |
| H330 | : Fatal if inhaled. |
| H332 | : Harmful if inhaled. |
| H335 | : May cause respiratory irritation. |
| H336 | : May cause drowsiness or dizziness. |
| H341 | : Suspected of causing genetic defects. |
| H350 | : May cause cancer. |
| H361 | : Suspected of damaging fertility or the unborn child. |
| H373 | : May cause damage to organs through prolonged or repeated exposure. |
| H412 | : Harmful to aquatic life with long lasting effects. |
| EUH066 | : Repeated exposure may cause skin dryness or cracking. |

Full text of other abbreviations

| | |
|-----------------|--------------------------------------|
| Acute Tox. | : Acute toxicity |
| Aquatic Chronic | : Long-term (chronic) aquatic hazard |
| Asp. Tox. | : Aspiration hazard |
| Carc. | : Carcinogenicity |
| Eye Dam. | : Serious eye damage |
| Eye Irrit. | : Eye irritation |
| Flam. Liq. | : Flammable liquids |
| Muta. | : Germ cell mutagenicity |
| Repr. | : Reproductive toxicity |
| Skin Corr. | : Skin corrosion |
| Skin Irrit. | : Skin irritation |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL Clear base

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 12.11.2021 | MAT000418258 | Date of first issue: 12.11.2021 |
| GB / EN | | | |

Skin Sens. : Skin sensitisation
STOT RE : Specific target organ toxicity - repeated exposure
STOT SE : Specific target organ toxicity - single exposure
2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2004/37/EC : Europe. Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens or mutagens at work
2019/1831/EU : Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values
GB EH40 : UK. EH40 WEL - Workplace Exposure Limits
GB EH40 BAT : UK. Biological monitoring guidance values
2000/39/EC / TWA : Limit Value - eight hours
2000/39/EC / STEL : Short term exposure limit
2004/37/EC / STEL : Short term exposure limit
2004/37/EC / TWA : Long term exposure limit
2019/1831/EU / TWA : Limit Value - eight hours
2019/1831/EU / STEL : Short term exposure limit
GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL Clear base

Version
1.0

Revision Date:
12.11.2021

SDS Number:
MAT000418258
GB / EN

Date of last issue: -
Date of first issue: 12.11.2021

Further information

Classification of the mixture:

| | |
|---------------|------|
| Flam. Liq. 3 | H226 |
| Skin Irrit. 2 | H315 |
| Eye Dam. 1 | H318 |
| Repr. 2 | H361 |
| STOT SE 3 | H336 |

Classification procedure:

| |
|-------------------------------------|
| Based on product data or assessment |
| Calculation method |
| Calculation method |
| Calculation method |
| Calculation method |

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.