

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



COLOR FACADE PAINT

Version	Revision Date:	SDS Number:	Date of last issue: 02.04.2021
1.2	03.05.2022	MAT000476446	Date of first issue: 18.05.2020
		GB / EN	

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name	:	COLOR FACADE PAINT
Product code	:	47644605
Unique Formula Identifier (UFI)	:	8CJ1-K037-G002-8XYJ

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture	:	Building and construction work Professional and consumer use of coatings, Roller application or brushing, Non industrial spraying Coatings and paints, thinners, paint removers
-------------------------------	---	---

1.3 Details of the supplier of the safety data sheet

Company	:	Helios TBLUS d.o.o. Količevo 65 1230 Domžale Slovenia
Telephone Company	:	386 (1) 722 4383
Telefax Company	:	386 (1) 722 4310
Responsible/issuing person	:	386 (1) 722 4383 productsafety@helios.si

1.4 Emergency telephone number

Call 999 (or 112) for emergency medical attention
professionals only: National Poison Information Service (NPIS) 24h national number 0844 892 0111
consumer: National Health Service (NHS) 24h national number, England & Scotland 111

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
--------------------------------	--

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



COLOR FACADE PAINT

Version	Revision Date:	SDS Number:	Date of last issue: 02.04.2021
1.2	03.05.2022	MAT000476446	Date of first issue: 18.05.2020
		GB / EN	

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Hazard pictograms :



Signal word : Warning

Hazard statements : H317 May cause an allergic skin reaction.

Precautionary statements : P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.

Prevention:

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P280 Wear protective gloves.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label:

1,2-benzisothiazol-3(2H)-one

2-methylisothiazol-3(2H)-one

reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one and 2-methyl-2H -isothiazol-3- one (3:1)

Additional Labelling

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Waterborne paint

Components

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



COLOR FACADE PAINT

Version
1.2

Revision Date:
03.05.2022

SDS Number:
MAT000476446
GB / EN

Date of last issue: 02.04.2021
Date of first issue: 18.05.2020

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
1,2-benzisothiazol-3(2H)-one	2634-33-5 220-120-9 613-088-00-6 01-2120761540-60	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 2; H411 specific concentra- tion limit Skin Sens. 1; H317 >= 0,05 %	>= 0,0025 - < 0,025
2-methyl-2H-isothiazol-3-one	2682-20-4 220-239-6 613-326-00-9 01-2120764690-50	Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 3; H311 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071 M-Factor (Acute aquatic toxicity): 1010 M-Factor (Chronic aquatic toxicity): 11 specific concentra- tion limit Skin Sens. 1A; H317 >= 0,0015 %	>= 0,0025 - < 0,025
mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	55965-84-9 613-167-00-5 01-2120764691-48	Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 2; H310 Skin Corr. 1C; H314 Eye Dam. 1; H318 Skin Sens. 1A;	<= 0,0002

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



COLOR FACADE PAINT

Version
1.2

Revision Date:
03.05.2022

SDS Number:
MAT000476446
GB / EN

Date of last issue: 02.04.2021
Date of first issue: 18.05.2020

		<p>H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071</p> <hr/> <p>M-Factor (Acute aquatic toxicity): 100100 M-Factor (Chronic aquatic toxicity): 100100</p> <hr/> <p>specific concentra- tion limit Skin Corr. 1C; H314 ≥ 0,6 % Skin Irrit. 2; H315 0,06 - < 0,6 % Eye Irrit. 2; H319 0,06 - < 0,6 % Skin Sens. 1A; H317 ≥ 0,0015 % Eye Dam. 1; H318 ≥ 0,6 %</p>	
Substances with a workplace exposure limit :			
talc	14807-96-6 238-877-9 01-2120140278-58		≥ 1 - < 10

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Do not leave the victim unattended.
- If inhaled : If breathed in, move person into fresh air.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water.
Remove contaminated clothing and shoes.
- In case of eye contact : IF IN EYES: Rinse cautiously with water for several minutes.
Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice/ attention.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



COLOR FACADE PAINT

Version	Revision Date:	SDS Number:	Date of last issue: 02.04.2021
1.2	03.05.2022	MAT000476446	Date of first issue: 18.05.2020
		GB / EN	

If swallowed : Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

Risks : May cause an allergic skin reaction.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products : No hazardous combustion products are known.

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : The product itself does not burn.
Standard procedure for chemical fires.
Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Avoid contact with skin and eyes.
Do not flush into surface water or sanitary sewer system.
Prevent further leakage or spillage if safe to do so.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel,

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



COLOR FACADE PAINT

Version	Revision Date:	SDS Number:	Date of last issue: 02.04.2021
1.2	03.05.2022	MAT000476446	Date of first issue: 18.05.2020
		GB / EN	

acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For disposal considerations see section 13., For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : No special technical protective measures required.
For personal protection see section 8.

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : When using do not eat, drink or smoke. Wash thoroughly after handling.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Containers which are opened must be carefully resealed and kept upright to prevent leakage. Perishable if frozen. To maintain product quality, do not store in heat or direct sunlight.

Advice on common storage : No materials to be especially mentioned.

Further information on storage stability : Protect from frost.

7.3 Specific end use(s)

Specific use(s) : Consult the technical guidelines for the use of this substance/mixture.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Derived No Effect Level (DNEL):

Substance name	End Use	Exposure routes	Potential health effects	Value
Calcium carbonate	Workers	Inhalation	Long-term local effects	4,26 mg/m3
	Consumers	Inhalation	Long-term local effects	1,06 mg/m3
titanium dioxide	Workers	Inhalation	Long-term local effects	10 mg/m3
	Consumers	Oral	Long-term systemic effects	700 mg/kg bw/day
Talc	Workers	Inhalation	Acute systemic effects	2,16 mg/m3
	Workers	Inhalation	Acute local effects	3,6 mg/m3

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



COLOR FACADE PAINT

Version
1.2

Revision Date:
03.05.2022

SDS Number:
MAT000476446
GB / EN

Date of last issue: 02.04.2021
Date of first issue: 18.05.2020

	Consumers	Inhalation	Acute systemic effects	1,08 mg/m3
	Consumers	Inhalation	Acute local effects	1,8 mg/m3
	Consumers	Dermal	Long-term local effects	2,27 mg/cm2
	Workers	Dermal	Long-term local effects	4,54 mg/cm2
	Consumers	Oral	Long-term systemic effects	160 mg/kg bw/day
	Consumers	Oral	Acute systemic effects	160 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	43,2 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	21,6 mg/kg bw/day
1,2-benzisothiazol-3(2H)-one	Workers	Inhalation	Long-term systemic effects	6,81 mg/m3
	Workers	Dermal	Long-term systemic effects	0,966 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	1,2 mg/m3
	Consumers	Dermal	Long-term systemic effects	0,345 mg/kg bw/day
reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one and 2-methyl-2H - isothiazol-3- one (3:1)	Consumers	Inhalation	Acute local effects	0,04 mg/m3
	Workers	Inhalation	Long-term local effects	0,02 mg/m3
	Workers	Inhalation	Acute local effects	0,04 mg/m3
	Consumers	Inhalation	Long-term local effects	0,02 mg/m3
	Consumers	Oral	Long-term systemic effects	0,09 mg/kg bw/day
	Consumers	Oral	Acute systemic effects	0,11 mg/kg bw/day

Predicted No Effect Concentration (PNEC):

Substance name	Environmental Compartment	Value
Calcium carbonate	Sewage treatment plant	100 mg/l
titanium dioxide	Soil	100 mg/kg dry weight (d.w.)
	Marine water	0,0184 mg/l
	Fresh water	0,184 mg/l
	Marine sediment	100 mg/kg dry weight (d.w.)
	Fresh water sediment	1000 mg/kg dry weight (d.w.)
	Sewage treatment plant	100 mg/l
	Intermittent use/release	0,193 mg/l

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



COLOR FACADE PAINT

Version
1.2

Revision Date:
03.05.2022

SDS Number:
MAT000476446
GB / EN

Date of last issue: 02.04.2021
Date of first issue: 18.05.2020

Talc	Marine water	141,26 mg/l
	Fresh water	597,97 mg/l
	Marine sediment	3,13 mg/kg dry weight (d.w.)
	Fresh water sediment	31,33 mg/kg dry weight (d.w.)
	Intermittent use/release	597,97 mg/l
1,2-benzisothiazol-3(2H)-one	Fresh water	0,00403 mg/l
	Intermittent use/release	0,0011 mg/l
	Marine water	0,000403 mg/l
	Sewage treatment plant	1,03 mg/l
	Fresh water sediment	0,0499 mg/kg dry weight (d.w.)
	Marine sediment	0,00499 mg/kg dry weight (d.w.)
	Soil	3 mg/kg dry weight (d.w.)
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H -isothiazol-3- one (3:1)	Soil	0,01 mg/kg dry weight (d.w.)
	Marine water	0,00339 mg/l
	Fresh water	0,00339 mg/l
	Marine sediment	0,027 mg/kg dry weight (d.w.)
	Fresh water sediment	0,027 mg/kg dry weight (d.w.)
	Sewage treatment plant	0,23 mg/l
	Intermittent use/release	0,00339 mg/l

8.2 Exposure controls

Personal protective equipment

Eye protection : Goggles

Hand protection

Material : Nitrile rubber

Glove thickness : 0,2 mm

Protective index : Class 3

Remarks : Wear suitable gloves.

Skin and body protection : Long sleeved clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : No personal respiratory protective equipment normally required.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : in accordance with the product description

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



COLOR FACADE PAINT

Version	Revision Date:	SDS Number:	Date of last issue: 02.04.2021
1.2	03.05.2022	MAT000476446	Date of first issue: 18.05.2020
		GB / EN	

Odour	:	No information available.
Odour Threshold	:	No data available
pH	:	9 - 10 Concentration: 10 %
Flash point	:	Not applicable
Flammability (solid, gas)	:	Not applicable
Density	:	1,53 - 1,58 g/cm ³
Solubility(ies)		
Water solubility	:	completely miscible
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Viscosity		
Viscosity, kinematic	:	> 20,5 mm ² /s (40 °C)

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : No data available

10.4 Conditions to avoid

Conditions to avoid : Protect from frost, heat and sunlight.

10.5 Incompatible materials

Materials to avoid : Incompatible with oxidizing agents.
Incompatible with strong acids and bases.

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



COLOR FACADE PAINT

Version
1.2

Revision Date:
03.05.2022

SDS Number:
MAT000476446
GB / EN

Date of last issue: 02.04.2021
Date of first issue: 18.05.2020

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

Components:

1,2-benzisothiazol-3(2H)-one:

Acute oral toxicity : Assessment: The component/mixture is moderately toxic after single ingestion.

2-methylisothiazol-3(2H)-one:

Acute oral toxicity : Assessment: The component/mixture is toxic after single ingestion.

Acute inhalation toxicity : Test atmosphere: vapour
Assessment: The component/mixture is highly toxic after short term inhalation.

Acute dermal toxicity : Assessment: The component/mixture is toxic after single contact with skin.

Skin corrosion/irritation

Not classified based on available information.

Components:

1,2-benzisothiazol-3(2H)-one:

Result : irritating

2-methylisothiazol-3(2H)-one:

Result : Corrosive after 3 minutes to 1 hour of exposure

Serious eye damage/eye irritation

Not classified based on available information.

Components:

1,2-benzisothiazol-3(2H)-one:

Result : Corrosive

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



COLOR FACADE PAINT

Version
1.2

Revision Date:
03.05.2022

SDS Number:
MAT000476446
GB / EN

Date of last issue: 02.04.2021
Date of first issue: 18.05.2020

Respiratory sensitisation

Not classified based on available information.

Components:

1,2-benzisothiazol-3(2H)-one:

Result : Probability or evidence of skin sensitisation in humans

2-methylisothiazol-3(2H)-one:

Result : Probability or evidence of skin sensitisation in humans

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

SECTION 12: Ecological information

12.1 Toxicity

Components:

1,2-benzisothiazol-3(2H)-one:

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

2-methylisothiazol-3(2H)-one:

M-Factor (Acute aquatic toxicity) : 10

M-Factor (Chronic aquatic toxicity) : 1

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



COLOR FACADE PAINT

Version	Revision Date:	SDS Number:	Date of last issue: 02.04.2021
1.2	03.05.2022	MAT000476446	Date of first issue: 18.05.2020
		GB / EN	

reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one and 2-methyl-2H -isothiazol-3-one (3:1):

Toxicity to fish : LC50 (Salvelinus namaycush (lake trout)): >= 10,85 mg/l
Exposure time: 96 h

Toxicity to algae/aquatic plants : LC50 (algae): >= 0,82 mg/l
Exposure time: 48 h

LC50 (algae): 0,018 mg/l
Exposure time: 72 h

M-Factor (Acute aquatic toxicity) : 100

M-Factor (Chronic aquatic toxicity) : 100

12.2 Persistence and degradability

Components:

2-methylisothiazol-3(2H)-one:

Biodegradability : Result: Biodegradable

12.3 Bioaccumulative potential

Components:

1,2-benzisothiazol-3(2H)-one:

Partition coefficient: n-octanol/water : log Pow: 1,3

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Product:

Endocrine disrupting potential : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



COLOR FACADE PAINT

Version	Revision Date:	SDS Number:	Date of last issue: 02.04.2021
1.2	03.05.2022	MAT000476446	Date of first issue: 18.05.2020
		GB / EN	

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	:	Do not release the product to the aquatic environment
Contaminated packaging	:	Empty containers should be taken to an approved waste handling site for recycling or disposal.
Waste Code	:	08 01 20, aqueous suspensions containing paint or varnish other than those mentioned in 08 01 19

SECTION 14: Transport information

14.1 UN number

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII)	:	Conditions of restriction for the following entries should be considered: Number on list 3
REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII)	:	Conditions of restriction for the following entries should be considered: Number on list 3
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	:	Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	:	Not applicable

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



COLOR FACADE PAINT

Version	Revision Date:	SDS Number:	Date of last issue: 02.04.2021
1.2	03.05.2022	MAT000476446	Date of first issue: 18.05.2020
		GB / EN	

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. Not applicable

Seveso III Directive (2012/18/EU) implemented by Control of Major Accident Hazards Regulations 2015 (COMAH) Not applicable

Volatile organic compounds : Directive 2004/42/EC
Volatile organic compounds (VOC) content: 23 g/l

Other regulations:

15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

SECTION 16: Other information

Full text of H-Statements

H301	: Toxic if swallowed.
H302	: Harmful if swallowed.
H310	: Fatal in contact with skin.
H311	: Toxic in contact with skin.
H314	: Causes severe skin burns and eye damage.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H330	: Fatal if inhaled.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.
H411	: Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Acute	: Short-term (acute) aquatic hazard
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Eye Dam.	: Serious eye damage
Skin Corr.	: Skin corrosion
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitisation

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergen-

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



COLOR FACADE PAINT

Version	Revision Date:	SDS Number:	Date of last issue: 02.04.2021
1.2	03.05.2022	MAT000476446	Date of first issue: 18.05.2020
		GB / EN	

cy Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECL - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Classification of the mixture:

Skin Sens. 1

H317

Classification procedure:

Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN