

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TESSAROL enamel for tin plated sheet metal

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	20.07.2023	MAT0GA00_023 IE/EN	Date of first issue: 20.07.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : TESSAROL enamel for tin plated sheet metal

Product code : Please see section 16 for detailed data

Unique Formula Identifier (UFI) : MH30-C0T0-K00R-YRSV

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : SU19 Building and construction work
PROC10, PROC11 Roller application or brushing, Non industrial spraying
PC9a Coatings and paints, thinners, paint removers

Recommended restrictions on use : Professional and consumer use of coatings

1.3 Details of the supplier of the safety data sheet

Company : Helios TBLUS d.o.o.
Količevo 65
1230 Domžale
Slovenia

Telephone Company : 386 (1) 722 4383

Telefax Company : 386 (1) 722 4310

Responsible/issuing person : 386 (1) 722 4383
productsafety@helios.si

1.4 Emergency telephone number

01 809 2166 National Poisons Information Centre 01 809 2166

01 809 2566 Healthcare Professionals 01 809 2566

01 809 2566 Healthcare Professionals 01 809 2566

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 H226: Flammable liquid and vapour.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TESSAROL enamel for tin plated sheet metal

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	20.07.2023	MAT0GA00_023 IE/EN	Date of first issue: 20.07.2023

Specific target organ toxicity - single exposure, Category 3, Central nervous system

H336: May cause drowsiness or dizziness.

Long-term (chronic) aquatic hazard, Category 3

H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Warning

Hazard statements :
H226 Flammable liquid and vapour.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Supplemental Hazard Statements : EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements :
P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P271 Use only outdoors or in a well-ventilated area.

Response:

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label:

n-butyl acetate
Hydrocarbons, C9 aromatics
1-methoxy-2-propanol

Additional Labelling

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TESSAROL enamel for tin plated sheet metal

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	20.07.2023	MAT0GA00_023	Date of first issue: 20.07.2023
		IE/EN	

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
n-butyl acetate	123-86-4 204-658-1 607-025-00-1 01-2119485493-29	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) EUH066	>= 20 - < 30
Hydrocarbons, C9 aromatics	128601-23-0 918-668-5 01-2119455851-35	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>= 10 - < 20
1-methoxy-2-propanol	107-98-2 203-539-1 603-064-00-3 01-2119457435-35	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system)	>= 1 - < 10
Substances with a workplace exposure limit :			
Talc	14807-96-6 238-877-9 01-2120140278-58		>= 1 - < 10

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TESSAROL enamel for tin plated sheet metal

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	20.07.2023	MAT0GA00_023 IE/EN	Date of first issue: 20.07.2023

SECTION 4: First aid measures

4.1 Description of first aid measures

- | | |
|-------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| General advice | : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended. |
| If inhaled | : Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice. |
| In case of skin contact | : If on skin, rinse well with water.
If on clothes, remove clothes. |
| In case of eye contact | : Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist. |
| If swallowed | : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician. |

4.2 Most important symptoms and effects, both acute and delayed

- | | |
|-------|-----------------------------------------------------------------------------------------------|
| Risks | : May cause drowsiness or dizziness.
Repeated exposure may cause skin dryness or cracking. |
|-------|-----------------------------------------------------------------------------------------------|

4.3 Indication of any immediate medical attention and special treatment needed

- | | |
|-----------|--------------------------|
| Treatment | : Treat symptomatically. |
|-----------|--------------------------|

SECTION 5: Firefighting measures

5.1 Extinguishing media

- | | |
|--------------------------------|-------------------------------------------------------------------------------|
| Suitable extinguishing media | : Alcohol-resistant foam
Carbon dioxide (CO ₂)
Dry chemical |
| Unsuitable extinguishing media | : High volume water jet |

5.2 Special hazards arising from the substance or mixture

- | | |
|---------------------------------------|-----------------------------------------------------------------------------|
| Specific hazards during fire-fighting | : Do not allow run-off from fire fighting to enter drains or water courses. |
| Hazardous combustion products | : No hazardous combustion products are known |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TESSAROL enamel for tin plated sheet metal

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	20.07.2023	MAT0GA00_023 IE/EN	Date of first issue: 20.07.2023

5.3 Advice for firefighters

- Special protective equipment : In the event of fire, wear self-contained breathing apparatus. for firefighters
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
-

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- Personal precautions : Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

- Environmental precautions : Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

- Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : Avoid formation of aerosol. Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TESSAROL enamel for tin plated sheet metal

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	20.07.2023	MAT0GA00_023 IE/EN	Date of first issue: 20.07.2023

Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : For further information, refer to the product technical data sheet.

Consult the technical guidelines for the use of this substance/mixture.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
n-butyl acetate	123-86-4	OELV - 8 hrs (TWA)	50 ppm 241 mg/m ³	IE OEL
		OELV - 15 min (STEL)	150 ppm 723 mg/m ³	IE OEL
		STEL	150 ppm 723 mg/m ³	2019/1831/EU
Further information: Indicative				
		TWA	50 ppm 241 mg/m ³	2019/1831/EU
Further information: Indicative				
titanium dioxide	13463-67-7	OELV - 8 hrs (TWA) (Respirable dust)	4 mg/m ³	IE OEL
		OELV - 8 hrs (TWA) (inhalable)	10 mg/m ³	IE OEL

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TESSAROL enamel for tin plated sheet metal

Version
1.0

Revision Date:
20.07.2023

SDS Number:
MAT0GA00_023
IE/EN

Date of last issue: -
Date of first issue: 20.07.2023

		dust)		
Talc	14807-96-6	OELV - 8 hrs (TWA) (Respirable dust)	0.8 mg/m ³	IE OEL
		OELV - 8 hrs (TWA) (inhalable dust)	10 mg/m ³	IE OEL
		TWA (Respirable dust)	0.1 mg/m ³	2004/37/EC
Further information: Carcinogens or mutagens				
1-methoxy-2-propanol	107-98-2	TWA	100 ppm 375 mg/m ³	2000/39/EC
Further information: Identifies the possibility of significant uptake through the skin, Indicative				
		STEL	150 ppm 568 mg/m ³	2000/39/EC
Further information: Identifies the possibility of significant uptake through the skin, Indicative				
		OELV - 8 hrs (TWA)	100 ppm 375 mg/m ³	IE OEL
		OELV - 15 min (STEL)	150 ppm 568 mg/m ³	IE OEL

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
n-butyl acetate	Workers	Inhalation	Acute systemic effects	600 mg/m ³
	Workers	Inhalation	Acute local effects	600 mg/m ³
	Workers	Inhalation	Long-term systemic effects	48 mg/m ³
	Workers	Inhalation	Long-term local effects	300 mg/m ³
	Consumers	Inhalation	Acute systemic effects	300 mg/m ³
	Consumers	Inhalation	Acute local effects	300 mg/m ³
	Consumers	Inhalation	Long-term systemic effects	12 mg/m ³
	Consumers	Inhalation	Long-term local effects	35.7 mg/m ³
	Consumers	Dermal	Long-term systemic effects	3.4 mg/kg bw/day
	Consumers	Dermal	Acute systemic effects	6 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	2 mg/kg bw/day
	Consumers	Oral	Acute systemic effects	2 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	7 mg/kg bw/day
	Workers	Dermal	Acute systemic effects	11 mg/kg bw/day

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TESSAROL enamel for tin plated sheet metal

Version
1.0

Revision Date:
20.07.2023

SDS Number:
MAT0GA00_023
IE/EN

Date of last issue: -
Date of first issue: 20.07.2023

titanium dioxide	Workers	Inhalation	Long-term local effects	10 mg/m3
	Consumers	Oral	Long-term systemic effects	700 mg/kg bw/day
Hydrocarbons, C9 aromatics	Workers	Inhalation	Long-term systemic effects	150 mg/m3
	Workers	Oral	Long-term systemic effects	150 mg/m3
	Consumers	Inhalation	Long-term exposure	32 mg/m3
	Workers	Dermal	Long-term systemic effects	25 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	11 mg/kg bw/day
Talc	Workers	Inhalation	Acute systemic effects	2.16 mg/m3
	Workers	Inhalation	Acute local effects	3.6 mg/m3
	Consumers	Inhalation	Acute systemic effects	1.08 mg/m3
	Consumers	Inhalation	Acute local effects	1.8 mg/m3
	Consumers	Dermal	Long-term local effects	2.27 mg/cm2
	Workers	Dermal	Long-term local effects	4.54 mg/cm2
	Consumers	Oral	Long-term systemic effects	160 mg/kg bw/day
	Consumers	Oral	Acute systemic effects	160 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	43.2 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	21.6 mg/kg bw/day
Calcium carbonate	Workers	Inhalation	Long-term local effects	4.26 mg/m3
	Consumers	Inhalation	Long-term local effects	1.06 mg/m3
1-methoxy-2-propanol	Workers	Inhalation	Long-term systemic effects	369 mg/m3
	Workers	Inhalation	Acute systemic effects	553.5 mg/m3
	Workers	Inhalation	Acute local effects	553.5 mg/m3
	Workers	Inhalation	Long-term systemic effects	43.9 mg/m3
	Workers	Dermal	Long-term systemic effects	183 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	78 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	33 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
n-butyl acetate	Soil	0.0903 mg/kg dry

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TESSAROL enamel for tin plated sheet metal

Version
1.0

Revision Date:
20.07.2023

SDS Number:
MAT0GA00_023
IE/EN

Date of last issue: -
Date of first issue: 20.07.2023

		weight (d.w.)
	Marine water	0.018 mg/l
	Fresh water	0.18 mg/l
	Marine sediment	0.0981 mg/kg dry weight (d.w.)
	Fresh water sediment	0.981 mg/kg dry weight (d.w.)
	Sewage treatment plant	35.6 mg/l
	Intermittent use/release	0.36 mg/l
titanium dioxide	Soil	100 mg/kg dry weight (d.w.)
	Marine water	0.0184 mg/l
	Fresh water	0.184 mg/l
	Marine sediment	100 mg/kg dry weight (d.w.)
	Fresh water sediment	1000 mg/kg dry weight (d.w.)
	Sewage treatment plant	100 mg/l
	Intermittent use/release	0.193 mg/l
Talc	Marine water	141.26 mg/l
	Fresh water	597.97 mg/l
	Marine sediment	3.13 mg/kg dry weight (d.w.)
	Fresh water sediment	31.33 mg/kg dry weight (d.w.)
	Intermittent use/release	597.97 mg/l
Calcium carbonate	Sewage treatment plant	100 mg/l
1-methoxy-2-propanol	Soil	4.59 mg/kg dry weight (d.w.)
	Marine water	1 mg/l
	Fresh water	10 mg/l
	Marine sediment	5.2 mg/kg dry weight (d.w.)
	Fresh water sediment	52.3 mg/kg dry weight (d.w.)
	Sewage treatment plant	100 mg/l
	Intermittent use/release	100 mg/l
Sulfonic acids, C10-21-alkane, Ph esters	Soil	27.1 mg/kg dry weight (d.w.)

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Equipment should conform to EN 166
Eye wash bottle with pure water
Tightly fitting safety goggles

Hand protection

Gloves : Nitrile rubber (> 0,1 mm; < 60 min); DIN EN374 |
Viton® (> 0,6 mm; < 240 min); DIN EN374 |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TESSAROL enamel for tin plated sheet metal

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	20.07.2023	MAT0GA00_023 IE/EN	Date of first issue: 20.07.2023

	PE laminate (> 0,1 mm; < 240 min); DIN EN374
Remarks	: The suitability for a specific workplace should be discussed with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.
Skin and body protection	: Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Respiratory protection	: No personal respiratory protective equipment normally required.
Protective measures	: Wash thoroughly after handling. Avoid contact with skin, eyes and clothing. Keep away from food, drink and animal feedingstuffs.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	: liquid
Colour	: in accordance with the product description
Odour	: solvent-like
Odour Threshold	: No data available
Melting point/freezing point	: -78.0 °C (calculation method (principal components, lowest value))
Boiling point/boiling range	: 126 °C (calculation method (principal components, lowest value))
Flammability	: Static-accumulating flammable liquid., Combustible Solids
Upper explosion limit / Upper flammability limit	: 7.5 %(V) (calculation method (principal components, highest value))
Lower explosion limit / Lower flammability limit	: 1.2 %(V) (calculation method (principal components, highest value))
Flash point	: 29 °C (calculation method (principal components, lowest value))

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TESSAROL enamel for tin plated sheet metal

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	20.07.2023	MAT0GA00_023	Date of first issue: 20.07.2023
		IE/EN	

Ignition temperature	:	425 °C (calculation method (principal components, highest value))
Decomposition temperature	:	No decomposition if stored and applied as directed. Hazardous decomposition products formed under fire conditions.
pH	:	No data available
Viscosity	:	
Viscosity, kinematic	:	> 20.5 mm ² /s (40 °C)
Flow time	:	> 60 s at 23 °C Cross section: 6 mm Method: ISO 2431
Solubility(ies)	:	
Water solubility	:	insoluble
Solubility in other solvents	:	Description: miscible with most organic solvents
Partition coefficient: n-octanol/water	:	log Pow: < 4 (calculation method (principal components, highest value))
Vapour pressure	:	13 hPa (calculation method (principal components, highest value))
Relative density	:	No data available
Density	:	1.10 - 1.25 g/cm ³ Method: ISO 2811
Relative vapour density	:	No data available

9.2 Other information

Explosives	:	Not applicable
Oxidizing properties	:	Sustains combustion
VOC	:	(Directive 2004/42/EC) 500 g/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TESSAROL enamel for tin plated sheet metal

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	20.07.2023	MAT0GA00_023 IE/EN	Date of first issue: 20.07.2023

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Incompatible with strong acids and bases.

10.6 Hazardous decomposition products

Adequate ventilation is required.

Heating can release vapours which can be ignited.

Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Components:

n-butyl acetate:

Acute oral toxicity : LD50 Oral (Rat): $\geq 10,760$ mg/kg

Acute dermal toxicity : LD50 (Rabbit): $\geq 5,000$ mg/kg

Hydrocarbons, C9 aromatics:

Acute dermal toxicity : LD50 (Rabbit): $> 3,160$ mg/kg

1-methoxy-2-propanol:

Acute oral toxicity : LD50 Oral (Rabbit): $> 2,000$ mg/kg

Acute dermal toxicity : LD50 (Rabbit): $> 2,000$ mg/kg

Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TESSAROL enamel for tin plated sheet metal

Version
1.0

Revision Date:
20.07.2023

SDS Number:
MAT0GA00_023
IE/EN

Date of last issue: -
Date of first issue: 20.07.2023

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause drowsiness or dizziness.

Components:

n-butyl acetate:

Assessment : May cause drowsiness or dizziness.

Hydrocarbons, C9 aromatics:

Assessment : May cause drowsiness or dizziness.

Assessment : May cause respiratory irritation.

1-methoxy-2-propanol:

Assessment : May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Components:

Hydrocarbons, C9 aromatics:

May be fatal if swallowed and enters airways.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TESSAROL enamel for tin plated sheet metal

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	20.07.2023	MAT0GA00_023 IE/EN	Date of first issue: 20.07.2023

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Further information

Product:

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.
Concentrations substantially above the TLV value may cause narcotic effects.
Solvents may degrease the skin.

SECTION 12: Ecological information

12.1 Toxicity

Components:

n-butyl acetate:

Toxicity to algae/aquatic plants : NOEC (Desmodesmus subspicatus (green algae)): > 200 mg/l

EC50 (Desmodesmus subspicatus (green algae)): \geq 647.7 mg/l
Exposure time: 72 h

Toxicity to microorganisms : IC50 (Tetrahymena pyriformis): 356 mg/l
Exposure time: 40 h

Hydrocarbons, C9 aromatics:

Toxicity to fish : LC50 (Fish): \geq 9.2 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): \geq 3.2 mg/l
Exposure time: 48 h

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

1-methoxy-2-propanol:

Toxicity to fish : LC50 (Fish): > 1,000 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)): > 1,000 mg/l

Toxicity to algae/aquatic : LC50 (algae): > 1,000 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TESSAROL enamel for tin plated sheet metal

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	20.07.2023	MAT0GA00_023	Date of first issue: 20.07.2023
		IE/EN	

plants

12.2 Persistence and degradability

Components:

n-butyl acetate:

Biodegradability	:	Result: Biodegradable Biodegradation: 83 % Exposure time: 28 d Method: OECD Test Guideline 301D
Stability in water	:	Degradation half life: 78 d pH: 8 Hydrolyses slowly.
Photodegradation	:	Decomposes rapidly in contact with light.

12.3 Bioaccumulative potential

Components:

n-butyl acetate:

Bioaccumulation	:	Bioconcentration factor (BCF): 15 Bioaccumulation is unlikely.
-----------------	---	-------------------------------------------------------------------

Partition coefficient: n-octanol/water	:	log Pow: 1.81
----------------------------------------	---	---------------

Hydrocarbons, C9 aromatics:

Partition coefficient: n-octanol/water	:	log Pow: < 4
----------------------------------------	---	--------------

1-methoxy-2-propanol:

Partition coefficient: n-octanol/water	:	log Pow: -0.437
----------------------------------------	---	-----------------

12.4 Mobility in soil

Components:

Hydrocarbons, C9 aromatics:

Mobility	:	Medium: Air Content: 92.9 %
	:	Medium: Water Content: 3.5 %
	:	Medium: Soil Content: 1.9 %

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TESSAROL enamel for tin plated sheet metal

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	20.07.2023	MAT0GA00_023 IE/EN	Date of first issue: 20.07.2023

: Medium: Sediment
Content: 1.8 %

Distribution among environmental compartments : Koc: 1.71 - 14.70
Mobile in soils

The product is insoluble and floats on water.

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	: The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.
Contaminated packaging	: Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.
Waste Code	: 08 00 00, WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TESSAROL enamel for tin plated sheet metal

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	20.07.2023	MAT0GA00_023	Date of first issue: 20.07.2023
		IE/EN	

08 01 00, wastes from MFSU and removal of paint and varnish
08 01 11, waste paint and varnish containing organic solvents or other hazardous substances
15 00 00, WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED
15 01 00, packaging (including separately collected municipal packaging waste)
15 01 10, packaging containing residues of or contaminated by hazardous substances
HP3, Flammable
HP14, Ecotoxic

SECTION 14: Transport information

14.1 UN number or ID number

ADN	:	UN 1263
ADR	:	UN 1263
RID	:	UN 1263
IMDG	:	UN 1263
IATA	:	UN 1263

14.2 UN proper shipping name

ADN	:	PAINT
ADR	:	PAINT
RID	:	PAINT
IMDG	:	PAINT
IATA	:	Paint

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADN	:	3
ADR	:	3
RID	:	3
IMDG	:	3
IATA	:	3

14.4 Packing group

ADN		
Packing group	:	III
Classification Code	:	F1
Hazard Identification Number	:	30

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TESSAROL enamel for tin plated sheet metal

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	20.07.2023	MAT0GA00_023	Date of first issue: 20.07.2023
		IE/EN	

Labels : 3

ADR

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3
Tunnel restriction code : (D/E)

RID

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

IMDG

Packing group : III
Labels : 3
EmS Code : F-E, S-E

IATA (Cargo)

Packing instruction (cargo aircraft) : 366
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids

IATA (Passenger)

Packing instruction (passenger aircraft) : 355
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

Remarks : ADR: Packages smaller than or equal to 450 litres, not goods/merchandise of Class 3 (exemption ADR 2.2.3.1.5)
IMDG: Packages smaller than or equal to 450 litres, not goods/merchandise of Class 3; "transport acc. IMDG-code 2.3.2.5"

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TESSAROL enamel for tin plated sheet metal

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	20.07.2023	MAT0GA00_023 IE/EN	Date of first issue: 20.07.2023

Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 75, 3

If you intend to use this product as tattoo ink, please contact your vendor.

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P5c FLAMMABLE LIQUIDS

Volatile organic compounds : Directive 2004/42/EC
Volatile organic compounds (VOC) content: 500 g/l

Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TESSAROL enamel for tin plated sheet metal

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	20.07.2023	MAT0GA00_023 IE/EN	Date of first issue: 20.07.2023

15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

SECTION 16: Other information

Full text of H-Statements

H226	: Flammable liquid and vapour.
H304	: May be fatal if swallowed and enters airways.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H411	: Toxic to aquatic life with long lasting effects.
EUH066	: Repeated exposure may cause skin dryness or cracking.

Full text of other abbreviations

Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Flam. Liq.	: Flammable liquids
STOT SE	: Specific target organ toxicity - single exposure
2000/39/EC	: Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2004/37/EC	: Europe. Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens or mutagens at work
2019/1831/EU	: Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values
IE OEL	: Ireland. List of Chemical Agents and Occupational Exposure Limit Values - Schedule 1
2000/39/EC / TWA	: Limit Value - eight hours
2000/39/EC / STEL	: Short term exposure limit
2004/37/EC / TWA	: Long term exposure limit
2019/1831/EU / TWA	: Limit Value - eight hours
2019/1831/EU / STEL	: Short term exposure limit
IE OEL / OELV - 8 hrs (TWA)	: Occupational exposure limit value (8-hour reference period)
IE OEL / OELV - 15 min (STEL)	: Occupational exposure limit value (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization;

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TESSAROL enamel for tin plated sheet metal

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	20.07.2023	MAT0GA00_023	Date of first issue: 20.07.2023
		IE/EN	

KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECl - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Flam. Liq. 3	H226
STOT SE 3	H336
Aquatic Chronic 3	H412

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method

Material codes (bulk) for which the SDS is valid	477873 , 477874, 477875, 477876, 477877, 477878, 477879, 477880
--------------------------------------------------	-----------------------------------------------------------------

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.