according to Regulation (EC) No. 1907/2006

COLOR FACADE PAINT



Version Revision Date: SDS Number: Date of last issue: -

1.0 16.11.2023 MAT000476446 Date of first issue: 16.11.2023

IE/EN

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : COLOR FACADE PAINT

Product code : 47644605

Unique Formula Identifier

(UFI)

: 8CJ1-K037-G002-8XYJ

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : SU19Building and construction work

stance/Mixture , PROC10, PROC11 Professional and consumer use of coat-

ings, Roller application or brushing, Non industrial spraying

PC9a Coatings and paints, thinners, paint removers

1.3 Details of the supplier of the safety data sheet

Company : Helios TBLUS d.o.o.

Količevo 65 1230 Domžale Slovenia

Telephone Company : 386 (1) 722 4383

Telefax Company : 386 (1) 722 4310

Responsible/issuing person : 386 (1) 722 4383

productsafety@helios.si

1.4 Emergency telephone number

01 809 2166 National Poisons Information Centre 01 809 2166

01 809 2566 Healtcare Professionals 01 809 2566

01 809 2566 Healtcare Professionals 01 809 2566

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

according to Regulation (EC) No. 1907/2006

COLOR FACADE PAINT



Version Revision Date: SDS Number: Date of last issue: -

1.0 16.11.2023 MAT000476446 Date of first issue: 16.11.2023

IE/EN

Hazard pictograms :

Signal word : Warning

Hazard statements : H317 May cause an allergic skin reaction.

Precautionary statements : P101 If medical advice is needed, have product container or

label at hand.

P102 Keep out of reach of children.

Prevention:

P261 Avoid breathing mist or vapours.

P280 Wear protective gloves.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

Hazardous components which must be listed on the label:

1,2-benzisothiazol-3(2H)-one

2-methylisothiazol-3(2H)-one

reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one and 2-methyl-2H -isothiazol-3- one (3:1)

Additional Labelling

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not

breathe spray or mist.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Waterborne paint

according to Regulation (EC) No. 1907/2006

COLOR FACADE PAINT



Version Revision Date: SDS Number: Date of last issue: -

1.0 16.11.2023 MAT000476446 Date of first issue: 16.11.2023

IE/EN

Components	1		
Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
1,2-benzisothiazol-3(2H)-one	2634-33-5 220-120-9 613-088-00-6 01-2120761540-60	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 2; H411 ——————————————————————————————————	>= 0.0025 - < 0.025
2-methylisothiazol-3(2H)-one	2682-20-4 220-239-6 613-326-00-9 01-2120764690-50	Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 3; H311 Skin Corr. 1B; H314 Eye Dam. 1; H318 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071 M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 1 specific concentration limit Skin Sens. 1A; H317 >= 0.0015 %	>= 0.0025 - < 0.025
reaction mass of: 5-chloro-2- me- thyl-4-isothiazolin-3-one and 2- methyl-2H -isothiazol-3- one (3:1)	55965-84-9 613-167-00-5 01-2120764691-48	Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 2; H310 Skin Corr. 1C; H314 Eye Dam. 1; H318 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071	<= 0.0002

according to Regulation (EC) No. 1907/2006

COLOR FACADE PAINT



Version Revision Date: SDS Number: Date of last issue: -

1.0 16.11.2023 MAT000476446 Date of first issue: 16.11.2023

IE/EN

		M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100 specific concentration limit Skin Corr. 1C; H314 >= 0.6 % Skin Irrit. 2; H315 0.06 - < 0.6 % Eye Irrit. 2; H319 0.06 - < 0.6 % Skin Sens. 1A; H317 >= 0.0015 % Eye Dam. 1; H318 >= 0.6 %	
Substances with a workplace expos		l I	4 40
Talc	14807-96-6 238-877-9 01-2120140278-58		>= 1 - < 10

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : In case of contact, immediately flush skin with plenty of water.

Remove contaminated clothing and shoes.

In case of eye contact : Remove contact lenses.

Protect unharmed eye.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

Risks : May cause an allergic skin reaction.

according to Regulation (EC) No. 1907/2006

COLOR FACADE PAINT



Version Revision Date: SDS Number: Date of last issue: -

1.0 16.11.2023 MAT000476446 Date of first issue: 16.11.2023

IE/EN

May cause an allergic skin reaction.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Unsuitable extinguishing

media

High volume water jet

5.2 Special hazards arising from the substance or mixture

ucts

Hazardous combustion prod- : No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment:

for firefighters

Wear self-contained breathing apparatus for firefighting if nec-

essary.

Further information Standard procedure for chemical fires.

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Avoid contact with skin and eyes.

> Do not flush into surface water or sanitary sewer system. Prevent further leakage or spillage if safe to do so.

6.2 Environmental precautions

Environmental precautions If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up Wipe up with absorbent material (e.g. cloth, fleece).

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

according to Regulation (EC) No. 1907/2006

COLOR FACADE PAINT



Version Revision Date: SDS Number: Date of last issue: -

1.0 16.11.2023 MAT000476446 Date of first issue: 16.11.2023

IE/EN

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Advice on protection against :

fire and explosion

Normal measures for preventive fire protection.

Hygiene measures : General industrial hygiene practice.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage

areas and containers

Electrical installations / working materials must comply with

the technological safety standards.

Advice on common storage : No materials to be especially mentioned.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : For further information, refer to the product technical data

sheet.

Consult the technical guidelines for the use of this sub-

stance/mixture.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
titanium dioxide	13463-67-7	OELV - 8 hrs (TWA) (Respira- ble dust)	4 mg/m3	IE OEL
		OELV - 8 hrs (TWA) (inhalable dust)	10 mg/m3	IE OEL
Talc	14807-96-6	OELV - 8 hrs (TWA) (Respira- ble dust)	0.8 mg/m3	IE OEL
		OELV - 8 hrs (TWA) (inhalable dust)	10 mg/m3	IE OEL
		TWA (Respirable dust)	0.1 mg/m3	2004/37/EC
	Further information: Carcinogens or mutagens			
Limestone	1317-65-3	OELV - 8 hrs	4 mg/m3	IE OEL

according to Regulation (EC) No. 1907/2006



COLOR FACADE PAINT

Version Revision Date: SDS Number: Date of last issue: -

1.0 16.11.2023 MAT000476446 Date of first issue: 16.11.2023

IE/EN

(TWA) (Respirable dust)		
OELV - 8 hrs (TWA) (inhalable	10 mg/m3	IE OEL
dust)		

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Calcium carbonate	Workers	Inhalation	Long-term local ef- fects	4.26 mg/m3
	Consumers	Inhalation	Long-term local ef- fects	1.06 mg/m3
titanium dioxide	Workers	Inhalation	Long-term local effects	10 mg/m3
	Consumers	Oral	Long-term systemic effects	700 mg/kg bw/day
Talc	Workers	Inhalation	Acute systemic effects	2.16 mg/m3
	Workers	Inhalation	Acute local effects	3.6 mg/m3
	Consumers	Inhalation	Acute systemic effects	1.08 mg/m3
	Consumers	Inhalation	Acute local effects	1.8 mg/m3
	Consumers	Dermal	Long-term local effects	2.27 mg/cm2
	Workers	Dermal	Long-term local effects	4.54 mg/cm2
	Consumers	Oral	Long-term systemic effects	160 mg/kg bw/day
	Consumers	Oral	Acute systemic effects	160 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	43.2 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	21.6 mg/kg bw/day
1,2-benzisothiazol- 3(2H)-one	Workers	Inhalation	Long-term systemic effects	6.81 mg/m3
	Workers	Dermal	Long-term systemic effects	0.966 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	1.2 mg/m3
	Consumers	Dermal	Long-term systemic effects	0.345 mg/kg bw/day
reaction mass of: 5- chloro-2- methyl-4- isothiazolin-3-one and 2-methyl-2H - isothiazol-3- one (3:1)	Consumers	Inhalation	Acute local effects	0.04 mg/m3
	Workers	Inhalation	Long-term local ef- fects	0.02 mg/m3
	Workers	Inhalation	Acute local effects	0.04 mg/m3
	Consumers	Inhalation	Long-term local ef-	0.02 mg/m3

according to Regulation (EC) No. 1907/2006



COLOR FACADE PAINT

Version Revision Date: SDS Number: Date of last issue: -

1.0 16.11.2023 MAT000476446 Date of first issue: 16.11.2023

IE/EN

		fects	
Consumers	Oral	Long-term systemic effects	0.09 mg/kg bw/day
Consumers	Oral	Acute systemic effects	0.11 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Calcium carbonate	Sewage treatment plant	100 mg/l
titanium dioxide	Soil	100 mg/kg dry
		weight (d.w.)
	Marine water	0.0184 mg/l
	Fresh water	0.184 mg/l
	Marine sediment	100 mg/kg dry
		weight (d.w.)
	Fresh water sediment	1000 mg/kg dry
		weight (d.w.)
	Sewage treatment plant	100 mg/l
	Intermittent use/release	0.193 mg/l
Talc	Marine water	141.26 mg/l
	Fresh water	597.97 mg/l
	Marine sediment	3.13 mg/kg dry
		weight (d.w.)
	Fresh water sediment	31.33 mg/kg dry
		weight (d.w.)
	Intermittent use/release	597.97 mg/l
1,2-benzisothiazol-3(2H)-one	Fresh water	0.00403 mg/l
	Intermittent use/release	0.0011 mg/l
	Marine water	0.000403 mg/l
	Sewage treatment plant	1.03 mg/l
	Fresh water sediment	0.0499 mg/kg dry
		weight (d.w.)
	Marine sediment	0.00499 mg/kg
		dry weight (d.w.)
	Soil	3 mg/kg dry
		weight (d.w.)
reaction mass of: 5-chloro-2-	Soil	0.01 mg/kg dry
methyl-4-isothiazolin-3-one and		weight (d.w.)
2-methyl-2H -isothiazol-3- one		
(3:1)		0.00000 #
	Marine water	0.00339 mg/l
	Fresh water	0.00339 mg/l
	Marine sediment	0.027 mg/kg dry
	Freeh water en dies sist	weight (d.w.)
	Fresh water sediment	0.027 mg/kg dry
	Course treetment plant	weight (d.w.)
	Sewage treatment plant Intermittent use/release	0.23 mg/l
	intermittent use/release	0.00339 mg/l

8.2 Exposure controls

Personal protective equipment

according to Regulation (EC) No. 1907/2006

COLOR FACADE PAINT



Version Revision Date: SDS Number: Date of last issue: -

1.0 16.11.2023 MAT000476446 Date of first issue: 16.11.2023

IE/EN

Eye/face protection

Hand protection

: Equipment should conform to EN 166

Gloves : Nitrile rubber (> 0,1 mm; < 60 min); DIN EN374

butyl-rubber (> 0,6 mm; < 240 min); DIN EN374 | Viton® (> 0,6 mm; < 240 min); DIN EN374 | PE laminate (> 0,1 mm; < 240 min); DIN EN374 |

Remarks : Please observe the instructions regarding permeability and

breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of

cuts, abrasion, and the contact time.

Skin and body protection : Protective suit

Respiratory protection : No personal respiratory protective equipment normally re-

quired.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid

Colour : in accordance with the product description

Odour : No information available.

Odour Threshold : No data available

Flammability : Not applicable

Flash point : Not applicable

pH : 9 - 10

Concentration: 10 %

Viscosity

Viscosity, kinematic : > 20.5 mm2/s (40 °C)

Solubility(ies)

Water solubility : completely miscible Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Density : 1.53 - 1.58 g/cm3

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

according to Regulation (EC) No. 1907/2006

HELIOS

COLOR FACADE PAINT

Version Revision Date: SDS Number: Date of last issue: -

1.0 16.11.2023 MAT000476446 Date of first issue: 16.11.2023

IE/EN

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : Incompatible with strong acids and bases.

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Components:

1,2-benzisothiazol-3(2H)-one:

Acute oral toxicity : Assessment: The component/mixture is moderately toxic after

single ingestion.

2-methylisothiazol-3(2H)-one:

Acute oral toxicity : Assessment: The component/mixture is toxic after single in-

gestion.

Acute inhalation toxicity : Test atmosphere: vapour

Assessment: The component/mixture is highly toxic after short

term inhalation.

Acute dermal toxicity : Assessment: The component/mixture is toxic after single con-

tact with skin.

Skin corrosion/irritation

Not classified based on available information.

Components:

1,2-benzisothiazol-3(2H)-one:

Result : irritating

2-methylisothiazol-3(2H)-one:

Result : Corrosive after 3 minutes to 1 hour of exposure

according to Regulation (EC) No. 1907/2006

COLOR FACADE PAINT



Version Revision Date: SDS Number: Date of last issue: -

1.0 16.11.2023 MAT000476446 Date of first issue: 16.11.2023

IE/EN

Serious eye damage/eye irritation

Not classified based on available information.

Components:

1,2-benzisothiazol-3(2H)-one:

Result : Corrosive

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Components:

1,2-benzisothiazol-3(2H)-one:

Result : Probability or evidence of skin sensitisation in humans

2-methylisothiazol-3(2H)-one:

Result : Probability or evidence of skin sensitisation in humans

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006

HELIOS

COLOR FACADE PAINT

Version Revision Date: SDS Number: Date of last issue: -

1.0 16.11.2023 MAT000476446 Date of first issue: 16.11.2023

IE/EN

Further information

Product:

Remarks : No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

1,2-benzisothiazol-3(2H)-one:

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

2-methylisothiazol-3(2H)-one:

M-Factor (Acute aquatic tox- : 10

icity)

M-Factor (Chronic aquatic

toxicity)

: 1

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one and 2-methyl-2H -isothiazol-3-

one (3:1):

Toxicity to fish : LC50 (Salvelinus namaycush (lake trout)): >= 10.85 mg/l

Exposure time: 96 h

Toxicity to algae/aquatic

plants

LC50 (algae): >= 0.82 mg/l

Exposure time: 48 h

LC50 (algae): 0.018 mg/l Exposure time: 72 h

M-Factor (Acute aquatic tox- :

icity)

100

M-Factor (Chronic aquatic

toxicity)

: 100

12.2 Persistence and degradability

Components:

2-methylisothiazol-3(2H)-one:

Biodegradability : Result: Biodegradable

according to Regulation (EC) No. 1907/2006

COLOR FACADE PAINT



Version Revision Date: SDS Number: Date of last issue: -

1.0 16.11.2023 MAT000476446 Date of first issue: 16.11.2023

IE/EN

12.3 Bioaccumulative potential

Components:

1,2-benzisothiazol-3(2H)-one:

Partition coefficient: n-

octanol/water

: log Pow: 1.3

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological infor-

mation

: No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not release the product to the aquatic environment

Contaminated packaging : Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

Waste Code : 08 00 00, WASTES FROM THE MANUFACTURE,

FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS

(PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS

08 01 00, wastes from MFSU and removal of paint and var-

nish

08 01 11, waste paint and varnish containing organic solvents

or other hazardoussubstances

15 00 00, WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE

according to Regulation (EC) No. 1907/2006

COLOR FACADE PAINT



Version Revision Date: SDS Number: Date of last issue: -

1.0 16.11.2023 MAT000476446 Date of first issue: 16.11.2023

IE/EN

CLOTHING NOT OTHERWISE SPECIFIED

15 01 00, packaging (including separately collected municipal

packaging waste)

15 01 10, packaging containing residues of or contaminated

by hazardoussubstances

HP13, Sensitising

SECTION 14: Transport information

14.1 UN number or ID number

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.2 UN proper shipping name

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.4 Packing group

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA (Cargo) : Not regulated as a dangerous good
IATA (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

according to Regulation (EC) No. 1907/2006

COLOR FACADE PAINT



Version Revision Date: SDS Number: Date of last issue: -

1.0 16.11.2023 MAT000476446 Date of first issue: 16.11.2023

IE/EN

14.6 Special precautions for user

Not applicable

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) Conditions of restriction for the following entries should be considered: Number on list 75, 3

If you intend to use this product as tattoo ink, please contact your ven-

dor.

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import

of dangerous chemicals

REACH - List of substances subject to authorisation

(Annex XIV)

Not applicable

Not applicable

Not applicable

Not applicable

: Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

Volatile organic compounds : Directive 2004/42/EC

Volatile organic compounds (VOC) content: 23 g/l

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

SECTION 16: Other information

Full text of H-Statements

H301 : Toxic if swallowed.

according to Regulation (EC) No. 1907/2006



COLOR FACADE PAINT

Version Revision Date: SDS Number: Date of last issue: -

1.0 16.11.2023 MAT000476446 Date of first issue: 16.11.2023

IE/EN

H302 : Harmful if swallowed.
H310 : Fatal in contact with skin.
H311 : Toxic in contact with skin.

H314 : Causes severe skin burns and eye damage.

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.

H318 : Causes serious eye damage.

H330 : Fatal if inhaled.

H400 : Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long lasting effects.H411 : Toxic to aquatic life with long lasting effects.

EUH071 : Corrosive to the respiratory tract.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Acute : Short-term (acute) aquatic hazard Aquatic Chronic : Long-term (chronic) aquatic hazard

Eye Dam. : Serious eye damage
Skin Corr. : Skin corrosion
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation

2004/37/EC : Europe. Directive 2004/37/EC on the protection of workers

from the risks related to exposure to carcinogens or mutagens

at work

IE OEL : Ireland. List of Chemical Agents and Occupational Exposure

Limit Values - Schedule 1

2004/37/EC / TWA : Long term exposure limit

IE OEL / OELV - 8 hrs (TWA) : Occupational exposure limit value (8-hour reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways: ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA -European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals: OECD - Organization for Economic Co-operation and Development: OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quanti-

according to Regulation (EC) No. 1907/2006

COLOR FACADE PAINT



Version Revision Date: SDS Number: Date of last issue: -

1.0 16.11.2023 MAT000476446 Date of first issue: 16.11.2023

IE/EN

tative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture: Classification procedure:

Skin Sens. 1 H317 Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.