

# SAFETY DATA SHEET

## MOBIHEL PRIMER THINNER



Version	Revision	SDS Number:	Date of last issue: -
1.0	Date: 16.11.2023	MAT000407581 AU/EN	Date of first issue: 16.11.2023

---

### SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : MOBIHEL PRIMER THINNER

Product code : 40758112

#### Manufacturer or supplier's details

##### Details of the supplier of the safety data sheet

Company : Helios Coatings Australia Pty Ltd  
50 Clapham Road  
SEFTON NSW 2162  
Australia

Telephone : 61 2 9645 3188  
E-mail address Responsible/issuing person : 61 2 9645 3188  
info@helioscoatings.com.au

#### Emergency telephone number

112 (mobile) Ambulance 000, Poisons Information Centre: 131 126

---

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS Classification

Flammable liquids : Category 2

Acute toxicity (Oral) : Category 4

Skin corrosion/irritation : Category 2

Serious eye damage/eye irritation : Category 1

Specific target organ toxicity - single exposure : Category 3 (Respiratory system, Central nervous system)

Specific target organ toxicity - repeated exposure : Category 2

Aspiration hazard : Category 1

#### GHS label elements

Hazard pictograms : Four GHS hazard pictograms in red diamond shapes: 1. A flame (Flammable liquid). 2. A silhouette of a person with a star on their chest (Health hazard). 3. A hand dropping a coin into a scale (Environment). 4. An exclamation mark (Danger).

Signal word : Danger

---

# SAFETY DATA SHEET

## MOBIHEL PRIMER THINNER



Version	Revision	SDS Number:	Date of last issue: -
1.0	Date: 16.11.2023	MAT000407581 AU/EN	Date of first issue: 16.11.2023

---

Hazard statements : H225 Highly flammable liquid and vapour.  
H302 Harmful if swallowed.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H318 Causes serious eye damage.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements : **Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 Keep container tightly closed.  
P240 Ground and bond container and receiving equipment.  
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.  
P242 Use non-sparking tools.  
P243 Take action to prevent static discharges.  
P260 Do not breathe mist or vapours.  
P264 Wash skin thoroughly after handling.  
P270 Do not eat, drink or smoke when using this product.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

**Response:**  
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.  
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.  
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.  
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.  
P314 Get medical advice/ attention if you feel unwell.  
P331 Do NOT induce vomiting.  
P332 + P313 If skin irritation occurs: Get medical advice/ attention.  
P362 + P364 Take off contaminated clothing and wash it before reuse.  
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

**Storage:**  
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
P403 + P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.

# SAFETY DATA SHEET

## MOBIHEL PRIMER THINNER



Version	Revision	SDS Number:	Date of last issue: -
1.0	Date: 16.11.2023	MAT000407581 AU/EN	Date of first issue: 16.11.2023

### Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

### Other hazards which do not result in classification

None known.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

### Components

Chemical name	CAS-No.	Concentration (% w/w)
reaction mixture of ethylbenzene, m-xylene and p-xylene	1330-20-7	>= 30 -< 60
1-butanol	71-36-3	>= 30 -< 60
ethanol	64-17-5	>= 10 -< 30

## SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.  
Symptoms of poisoning may appear several hours later.  
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.  
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If skin irritation persists, call a physician.  
If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.  
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
Continue rinsing eyes during transport to hospital.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do NOT induce vomiting.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.
- Most important symptoms and effects, both acute and delayed : None known.
- Notes to physician : Treat symptomatically.

# SAFETY DATA SHEET

## MOBIHEL PRIMER THINNER



Version	Revision	SDS Number:	Date of last issue: -
1.0	Date: 16.11.2023	MAT000407581 AU/EN	Date of first issue: 16.11.2023

---

### SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : No hazardous combustion products are known
- Specific extinguishing methods : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
- Hazchem Code : •3YE
- 

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Ensure adequate ventilation.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
- 

### SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).  
Use only explosion-proof equipment.  
Keep away from open flames, hot surfaces and sources of ignition.

# SAFETY DATA SHEET

## MOBIHEL PRIMER THINNER



Version 1.0      Revision Date: 16.11.2023      SDS Number: MAT000407581 AU/EN      Date of last issue: -      Date of first issue: 16.11.2023

- Advice on safe handling : Avoid formation of aerosol.  
Do not breathe vapours/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Container may be opened only under exhaust ventilation hood.  
Open drum carefully as content may be under pressure.  
To avoid spills during handling keep bottle on a metal tray.  
Dispose of rinse water in accordance with local and national regulations.
- Hygiene measures : When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.
- Conditions for safe storage : No smoking.  
Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage stability : No decomposition if stored and applied as directed.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
reaction mixture of ethylbenzene, m-xylene and p-xylene	1330-20-7	STEL	150 ppm 655 mg/m <sup>3</sup>	AU OEL
		TWA	80 ppm 350 mg/m <sup>3</sup>	AU OEL
		TWA	20 ppm	ACGIH
butan-1-ol	71-36-3	Peak limit	50 ppm 152 mg/m <sup>3</sup>	AU OEL
Further information: Skin absorption				
		TWA	20 ppm	ACGIH
ethanol	64-17-5	TWA	1,000 ppm 1,880 mg/m <sup>3</sup>	AU OEL
		STEL	1,000 ppm	ACGIH

#### Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
------------	---------	--------------------	---------------------	---------------	---------------------------	-------

# SAFETY DATA SHEET

## MOBIHEL PRIMER THINNER



Version 1.0      Revision Date: 16.11.2023      SDS Number: MAT000407581 AU/EN      Date of last issue: -      Date of first issue: 16.11.2023

reaction mixture of ethylbenzene, m-xylene and p-xylene	1330-20-7	Methylhippuric acids	Urine	End of shift (As soon as possible after exposure ceases)	1.5 g/g creatinine	ACGIH BEI
---	-----------	----------------------	-------	--	--------------------	-----------

### Personal protective equipment

- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
- Filter type : Organic vapour type
- Hand protection
- Gloves : Viton® (> 0,6 mm; < 240 min); DIN EN374 |  
PE laminate (> 0,1 mm; < 240 min); DIN EN374 |
- Remarks : Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.
- Eye protection : Equipment should conform to EN 166  
Eye wash bottle with pure water  
Tightly fitting safety goggles  
Wear face-shield and protective suit for abnormal processing problems.
- Skin and body protection : Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Colour : colourless
- Odour : solvent-like
- Odour Threshold : No data available
- pH : Not applicable
- Melting point/freezing point : -114.1 °C  
(calculation method (principal components, lowest value))
- Boiling point/boiling range : 78 °C  
(calculation method (principal components, lowest value))
- Flash point : 16 °C  
Method: ISO 3679, closed cup

# SAFETY DATA SHEET

## MOBIHEL PRIMER THINNER



Version	Revision	SDS Number:	Date of last issue: -
1.0	Date: 16.11.2023	MAT000407581 AU/EN	Date of first issue: 16.11.2023

---

Evaporation rate : No data available

Flammability (solid, gas) : Static-accumulating flammable liquid., Combustible Solids

Upper explosion limit / Upper flammability limit : 19 %(V)

Lower explosion limit / Lower flammability limit : 1.1 %(V)

Vapour pressure : 57.3 hPa (20 °C)

Relative vapour density : 2.6  
(Air = 1.0)

Relative density : 0.82

Density : 0.828 g/cm<sup>3</sup>

Solubility(ies)

    Water solubility : immiscible, partly soluble

    Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : log Pow: 2.77 - 3.15

Auto-ignition temperature : 343 °C

Decomposition temperature : No decomposition if used as directed.  
Hazardous decomposition products formed under fire conditions.

Viscosity

    Viscosity, kinematic : < 20.5 mm<sup>2</sup>/s ( 40 °C)

Explosive properties : Not applicable

Oxidizing properties : Sustains combustion

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reactions : No decomposition if stored and applied as directed.  
Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Incompatible with strong acids and bases.

Hazardous decomposition products : Adequate ventilation is required.  
Heating can release vapours which can be ignited.  
Carbon monoxide, carbon dioxide and unburned hydrocar-

# SAFETY DATA SHEET

## MOBIHEL PRIMER THINNER



Version	Revision	SDS Number:	Date of last issue: -
1.0	Date: 16.11.2023	MAT000407581 AU/EN	Date of first issue: 16.11.2023

---

bons (smoke).

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Acute toxicity

##### Product:

- Acute oral toxicity : Acute toxicity estimate: 1,471 mg/kg  
Method: Calculation method
- Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method
- Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg  
Method: Calculation method

##### Components:

##### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

- Acute oral toxicity : LD50 Oral (Rat):  $\geq$  8,700 mg/kg
- Acute inhalation toxicity : LC50 (Rat): 27.14 mg/l  
Test atmosphere: vapour
- Acute dermal toxicity : Assessment: The component/mixture is moderately toxic after single contact with skin.

##### **butan-1-ol:**

- Acute oral toxicity : Assessment: The component/mixture is moderately toxic after single ingestion.  
LD50 Oral (Rat): > 2,000 mg/kg
- Acute inhalation toxicity : LC50 (Rat): > 5 mg/l  
Test atmosphere: vapour
- Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

##### **ethanol:**

- Acute oral toxicity : LD50 Oral (Rat):  $\geq$  7,060 mg/kg
- Acute inhalation toxicity : LC50 (Rat):  $\geq$  39 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

# SAFETY DATA SHEET

## MOBIHEL PRIMER THINNER



Version	Revision	SDS Number:	Date of last issue: -
1.0	Date: 16.11.2023	MAT000407581 AU/EN	Date of first issue: 16.11.2023

---

### Skin corrosion/irritation

#### Product:

Remarks : Extremely corrosive and destructive to tissue.

#### Components:

##### reaction mixture of ethylbenzene, m-xylene and p-xylene:

Result : irritating

##### butan-1-ol:

Result : irritating

### Serious eye damage/eye irritation

#### Product:

Remarks : May cause irreversible eye damage.

#### Components:

##### reaction mixture of ethylbenzene, m-xylene and p-xylene:

Result : Eye irritation

##### butan-1-ol:

Result : Corrosive

##### ethanol:

Result : Eye irritation

### Chronic toxicity

#### STOT - single exposure

#### Components:

##### reaction mixture of ethylbenzene, m-xylene and p-xylene:

Assessment : May cause respiratory irritation.

##### butan-1-ol:

Assessment : May cause drowsiness or dizziness.

Assessment : May cause respiratory irritation.

# SAFETY DATA SHEET

## MOBIHEL PRIMER THINNER



Version	Revision	SDS Number:	Date of last issue: -
1.0	Date: 16.11.2023	MAT000407581 AU/EN	Date of first issue: 16.11.2023

---

### STOT - repeated exposure

#### Components:

##### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Assessment : May cause damage to organs through prolonged or repeated exposure.

### Aspiration toxicity

#### Components:

##### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

May be fatal if swallowed and enters airways.

### Further information

#### Product:

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.  
Concentrations substantially above the TLV value may cause narcotic effects.  
Solvents may degrease the skin.

---

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Components:

##### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Toxicity to fish : LC50 (Fish):  $\geq 1 - 10$  mg/l

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)):  $\geq 1 - 10$  mg/l

Toxicity to microorganisms : EC50 (Bacteria):  $\geq 1 - 100$  mg/l

##### **butan-1-ol:**

Toxicity to fish : LC50 (Fish):  $> 1,000$  mg/l

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)):  $> 1,000$  mg/l

Toxicity to microorganisms : EC50 (Bacteria):  $> 1,000$  mg/l

##### **ethanol:**

Toxicity to fish : LC50 (Fish):  $\geq 13,500$  mg/l

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)):  $\geq 5,000$  mg/l

# SAFETY DATA SHEET

## MOBIHEL PRIMER THINNER



Version	Revision	SDS Number:	Date of last issue: -
1.0	Date: 16.11.2023	MAT000407581 AU/EN	Date of first issue: 16.11.2023

---

### Persistence and degradability

#### Components:

##### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Biodegradability : Remarks: Readily biodegradable.

Photodegradation : Remarks: Decomposes rapidly in contact with light.

### Bioaccumulative potential

#### Components:

##### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Bioaccumulation : Bioconcentration factor (BCF): 25.9  
Remarks: Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water : log Pow: 2.77 - 3.15

##### **butan-1-ol:**

Partition coefficient: n-octanol/water : log Pow: 0.785

##### **ethanol:**

Partition coefficient: n-octanol/water : log Pow: -0.32

### Mobility in soil

#### Components:

##### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Distribution among environmental compartments : Koc: 537, log Koc: 2.73  
Remarks: Moderately mobile in soils  
The product evaporates from soil.

Stability in soil : Dissipation time: 23 d  
Percentage dissipation: 50 % (DT50)

### Other adverse effects

#### Product:

Additional ecological information : No data available

---

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : Do not dispose of waste into sewer.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

---

# SAFETY DATA SHEET

## MOBIHEL PRIMER THINNER



Version	Revision	SDS Number:	Date of last issue: -
1.0	Date: 16.11.2023	MAT000407581 AU/EN	Date of first issue: 16.11.2023

---

Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

---

### SECTION 14. TRANSPORT INFORMATION

#### International Regulations

##### UNRTDG

UN number : UN 1263  
Proper shipping name : PAINT RELATED MATERIAL  
Class : 3  
Packing group : II  
Labels : 3

##### IATA-DGR

UN/ID No. : UN 1263  
Proper shipping name : Paint related material  
Class : 3  
Packing group : II  
Labels : Flammable Liquids  
Packing instruction (cargo aircraft) : 364  
Packing instruction (passenger aircraft) : 353

##### IMDG-Code

UN number : UN 1263  
Proper shipping name : PAINT RELATED MATERIAL  
Class : 3  
Packing group : II  
Labels : 3  
EmS Code : F-E, S-E  
Marine pollutant : no

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### National Regulations

##### ADG

UN number : UN 1263  
Proper shipping name : PAINT RELATED MATERIAL  
Class : 3  
Packing group : II  
Labels : 3  
Hazchem Code : •3YE

#### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

# SAFETY DATA SHEET

## MOBIHEL PRIMER THINNER



Version	Revision	SDS Number:	Date of last issue: -
1.0	Date: 16.11.2023	MAT000407581 AU/EN	Date of first issue: 16.11.2023

---

### SECTION 15. REGULATORY INFORMATION

#### **Safety, health and environmental regulations/legislation specific for the substance or mixture**

Standard for the Uniform : Schedule 6  
Scheduling of Medicines and  
Poisons

Prohibition/Licensing Requirements : There is no applicable prohibition, authorisation and restricted use requirements, including for carcinogens referred to in Schedule 10 of the model WHS Act and Regulations.

### SECTION 16. OTHER INFORMATION

Revision Date : 16.11.2023  
Date format : dd.mm.yyyy

#### **Full text of other abbreviations**

ACGIH : USA. ACGIH Threshold Limit Values (TLV)  
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)  
AU OEL : Australia. Workplace Exposure Standards for Airborne Contaminants.

ACGIH / TWA : 8-hour, time-weighted average  
ACGIH / STEL : Short-term exposure limit  
AU OEL / TWA : Exposure standard - time weighted average  
AU OEL / STEL : Exposure standard - short term exposure limit  
AU OEL / Peak limit : Exposure standard - peak

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect

# SAFETY DATA SHEET

## MOBIHEL PRIMER THINNER



Version	Revision	SDS Number:	Date of last issue: -
1.0	Date: 16.11.2023	MAT000407581 AU/EN	Date of first issue: 16.11.2023

---

Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECL - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

AU / EN