# **MOBIHEL ANTISILICONE CLEANER**



Version 1.0	Revision Date: 16.11.2023	SDS Number: MAT000407597 AU/EN	Date of last issue: - Date of first issue: 16.11.2023			
SECTION	1. PRODUCT A	ND COMPANY IDENTIFICA	TION			
Produ	ict name	: MOBIHEL ANT	MOBIHEL ANTISILICONE CLEANER			
Product code		: 40759722				
Manu	facturer or sup	plier's details				
Detai	Is of the supplie	er of the safety data sheet				
Comp	bany	: Helios Coatings 50 Clapham Ro SEFTON NSW	ad			

Talanhana		61 2 0645 2188
Telephone	•	61 2 9645 3188
E-mail address Responsi-	:	61 2 9645 3188
ble/issuing person		info@helioscoatings.com.au

Australia

#### **Emergency telephone number**

112 (mobile) Ambulance 000, Poisons Information Centre: 131 126

### **SECTION 2. HAZARDS IDENTIFICATION**

GHS Classification Flammable liquids	:	Category 3
Skin corrosion/irritation	:	Category 2
Serious eye damage/eye irri- tation	:	Category 2A
Specific target organ toxicity - single exposure	:	Category 3 (Respiratory system, Central nervous system)
Specific target organ toxicity - repeated exposure	:	Category 2
Aspiration hazard	:	Category 1
GHS label elements Hazard pictograms	:	
Signal word	:	Danger
Hazard statements	:	H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways.

# MOBIHEL ANTISILICONE CLEANER



Version 1.0	Revision Date: 16.11.2023	SDS Nun MAT0004 AU/EN		Date of last issue: - Date of first issue: 16.11.2023
			H335 May cau H336 May cau	serious eye irritation. ise respiratory irritation. ise drowsiness or dizziness. ise damage to organs through prolonged or re-
Preca	autionary stateme	ents :	and other ignit P233 Keep co P240 Ground P241 Use exp ment. P242 Use non P243 Take ac P260 Do not b P264 Wash sk P271 Use only P280 Wear pr	vay from heat, hot surfaces, sparks, open flames ion sources. No smoking. ntainer tightly closed. and bond container and receiving equipment. losion-proof electrical/ ventilating/ lighting equip- -sparking tools. tion to prevent static discharges. wreathe mist or vapours. tin thoroughly after handling. v outdoors or in a well-ventilated area. otective gloves/ protective clothing/ eye protec- ection/ hearing protection.
			<b>Response:</b> P301 + P310 CENTER/ doc P303 + P361 Iy all contamin P304 + P340 and keep com doctor if you fe P305 + P351 for several min easy to do. Co P314 Get meo P331 Do NOT P332 + P313 tion. P337 + P313 tention. P362 + P364 reuse. P370 + P378	F SWALLOWED: Immediately call a POISON tor. + P353 IF ON SKIN (or hair): Take off immediate- ated clothing. Rinse skin with water. + P312 IF INHALED: Remove person to fresh air fortable for breathing. Call a POISON CENTER/
			tightly closed. P403 + P235 P405 Store loo <b>Disposal:</b>	of contents/ container to an approved waste

# MOBIHEL ANTISILICONE CLEANER



Version	Revision	SDS Number:	Date of last issue: -
1.0	Date:	MAT000407597	Date of first issue: 16.11.2023
	16.11.2023	AU/EN	

### Other hazards which do not result in classification

None known.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture

: Mixture

#### Components

Chemical name	CAS-No.	Concentration (% w/w)
hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclic, <2% aromatics	64742-49-0	>= 30 -< 60
hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics	64742-48-9	>= 20 -< 30
reaction mixture of ethylbenzene, m-xylene and p-xylene	1330-20-7	>= 10 -< 20
Hydrocarbons, C9 aromatics	128601-23-0	>= 10 -< 20
n-butyl acetate	123-86-4	< 10

#### **SECTION 4. FIRST AID MEASURES**

General advice	:	Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Symptoms of poisoning may appear several hours later. Do not leave the victim unattended.
If inhaled	:	Consult a physician after significant exposure. If unconscious, place in recovery position and seek medical advice.
In case of skin contact	:	If skin irritation persists, call a physician. If on skin, rinse well with water. If on clothes, remove clothes.
In case of eye contact	:	
If swallowed	:	Keep respiratory tract clear. Do NOT induce vomiting. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.
Most important symptoms and effects, both acute and delayed	:	None known.
Notes to physician	:	Treat symptomatically.

#### **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Alcohol-resistant foam

# MOBIHEL ANTISILICONE CLEANER



Version 1.0	Revision Date: 16.11.2023	SDS I MATC AU/EI	000	nber: 407597	Date of last issue: - Date of first issue: 16.11.2023
med	cific hazards during	-	:	Carbon dioxide (CO2) Dry chemical High volume water jet Do not allow run-off from courses.	n fire fighting to enter drains or water
Haz ucts	ardous combustior	n prod-	:	No hazardous combusti	on products are known
ods	cific extinguishing		:	must not be discharged Fire residues and conta be disposed of in accord For safety reasons in ca rately in closed contain Use a water spray to co	minated fire extinguishing water must dance with local regulations. ase of fire, cans should be stored sepa-
for f	refighters chem Code	•	:	•3Y	5 11

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- tive equipment and emer- gency procedures	:	Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentra- tions. Vapours can accumulate in low areas.
Environmental precautions	:	Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	•	Contain spillage, and then collect with non-combustible ab- sorbent material, (e.g. sand, earth, diatomaceous earth, ver- miculite) and place in container for disposal according to local / national regulations (see section 13).

### SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion	:	Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.
Advice on safe handling	:	Avoid formation of aerosol. Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes.

# MOBIHEL ANTISILICONE CLEANER



Version 1.0	Revision Date: 16.11.2023	SDS Nu MAT000 AU/EN		Date of last issue: - Date of first issue: 16.11.2023
Hygiene measures :		For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations. When using do not eat or drink. When using do not smoke.		
Conditions for safe storage : Further information on stor- : age stability		Wash hands before breaks and at the end of workday. No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards. No decomposition if stored and applied as directed.		

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
reaction mixture of ethylben- zene, m-xylene and p-xylene	1330-20-7	STEL	150 ppm 655 mg/m3	AU OEL
		TWA	80 ppm 350 mg/m3	AU OEL
		TWA	20 ppm	ACGIH
n-butyl acetate	123-86-4	STEL	200 ppm 950 mg/m3	AU OEL
		TWA	150 ppm 713 mg/m3	AU OEL
		TWA	50 ppm	ACGIH
		STEL	150 ppm	ACGIH

#### **Biological occupational exposure limits**

Components	CAS-No.	Control parameters	Biological specimen	Sam- pling time	Permissible concentra- tion	Basis
reaction mixture of ethylbenzene, m-xylene and p-xylene	1330-20-7	Methylhip- puric acids	Urine	End of shift (As soon as possible after exposure ceases)	1.5 g/g cre- atinine	ACGIH BEI

# MOBIHEL ANTISILICONE CLEANER



Versior 1.0	n Revision Date: 16.11.2023	SDS Nur MAT000 AU/EN		Date of last issue: - Date of first issue: 16.11.2023
Pe	ersonal protective e	quipment		
	espiratory protection	:	Use respi ventilatior	ratory protection unless adequate local exhaust is provided or exposure assessment demonstrates
Ha	Filter type and protection	:		sures are within recommended exposure guidelines. apour type
	Gloves	:	Nitrile ru Viton® PE lami	ubber (> 0,1 mm; < 60 min); DIN EN374   (> 0,6 mm; < 240 min); DIN EN374   nate (> 0,1 mm; < 240 min); DIN EN374
	Remarks	:	with the p Please ob breakthro gloves. Al tions unde	bility for a specific workplace should be discussed roducers of the protective gloves. serve the instructions regarding permeability and ugh time which are provided by the supplier of the so take into consideration the specific local condi- er which the product is used, such as the danger of sion, and the contact time.
Ey	e protection	:	Equipmer Eye wash Tightly fitt	at should conform to EN 166 bottle with pure water ing safety goggles b-shield and protective suit for abnormal processing
Sł	kin and body protection	on :	İmperviou Choose b	
SECTI	ON 9. PHYSICAL AI		CAL PROP	PERTIES
Ap	opearance	:	liquid	
Co	blour	:	colourles	S
00	dour	:	solvent-li	ke
00	dour Threshold	:	No data a	available
p⊦	ł	:	Not appli	cable
M	elting point/freezing p	oint :		an method (principal components, lowest value))

(calculation method (principal components, lowest value))

Boiling point/boiling range	:	80 - 110 °C
		(calculation method (principal components, lowest value))

Flash point : 25 °C

: No data available

Evaporation rate

Flammability (solid, gas) : Static-accumulating flammable liquid., Combustible Solids

# MOBIHEL ANTISILICONE CLEANER



Vers 1.0	sion	Revision Date: 16.11.2023	SDS N MATO AU/EN	004	nber: 07597	Date of last issue: - Date of first issue: 16.11.2023
		explosion limit / ability limit	Upper	:	7.5 %(V)	
		explosion limit / ability limit	Lower	:	0.7 %(V)	
	Vapou	rpressure		:	< 1,100 hPa (50 °C)	
	Relativ	e vapour density	/	:	4	
	Relativ	e density		:	0.90	
	Density	/		:	0.785 g/cm3	
	Solubil Wat	ity(ies) ter solubility		:	immiscible, partly solub	le
	Solu	ubility in other so	lvents	:	No data available	
	Partitio octano	n coefficient: n-		:	log Pow: < 4	
		nition temperatu	ire	:	425 °C	
	Decom	position tempera	ature	:	No decomposition if use Hazardous decomposit tions.	ed as directed. ion products formed under fire condi-
	Viscosi Visc	ity cosity, kinematic		:	< 20.5 mm2/s ( 40 °C)	
	Explos	ive properties		:	Not applicable	
	Oxidizi	ng properties		:	Sustains combustion	
	VOC			:	(Directive 2004/42/EC) 810 g/l	

### SECTION 10. STABILITY AND REACTIVITY

Reactivity Chemical stability Possibility of hazardous reac- tions	:	No decomposition if stored and applied as directed. No decomposition if stored and applied as directed. No decomposition if stored and applied as directed. Vapours may form explosive mixture with air.
Conditions to avoid Incompatible materials Hazardous decomposition products	:	Heat, flames and sparks. Incompatible with strong acids and bases. Adequate ventilation is required. Heating can release vapours which can be ignited. Carbon monoxide, carbon dioxide and unburned hydrocar- bons (smoke).

# MOBIHEL ANTISILICONE CLEANER



Version 1.0	Revision Date: 16.11.2023	SDS Number: MAT000407597 AU/EN	Date of last issue: - Date of first issue: 16.11.2023
----------------	---------------------------------	--------------------------------------	--

### SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity		
Product:		
Acute inhalation toxicity	:	Acute toxicity estimate: > 20 mg/l Exposure time: 4 h Test atmosphere: vapour Method: Calculation method
Acute dermal toxicity	:	Acute toxicity estimate: > 2,000 mg/kg Method: Calculation method
Components:		
reaction mixture of ethylb	enzei	ne, m-xylene and p-xylene:
Acute oral toxicity	:	LD50 Oral (Rat): >= 8,700 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): 27.14 mg/l Test atmosphere: vapour
Acute dermal toxicity	:	Assessment: The component/mixture is moderately toxic after single contact withskin.
Hydrocarbons, C9 aromat	ics:	
Acute dermal toxicity	:	LD50 (Rabbit): > 3,160 mg/kg
n-butyl acetate:		
Acute oral toxicity	:	LD50 Oral (Rat): >= 10,760 mg/kg
Acute dermal toxicity	:	LD50 (Rabbit): >= 5,000 mg/kg
Skin corrosion/irritation		
Product:		
Remarks	:	May cause skin irritation in susceptible persons.
Components:		
reaction mixture of ethylb	enzei	ne, m-xylene and p-xylene:
Result	:	irritating
Serious eye damage/eye i	rritati	on
Product:		
Remarks	:	May cause irreversible eye damage.

# MOBIHEL ANTISILICONE CLEANER



rsion	Revision Date: 16.11.2023	SDS Number: MAT000407597 AU/EN	Date of last issue: - Date of first issue: 16.11.2023
<u>Com</u>	oonents:		
<b>react</b> i Resul		thylbenzene, m-xylene and	l p-xylene:
Resul	l	: Eye irritation	
Chro	nic toxicity		
стот	- single exposi	ure	
<u>Com</u>	oonents:		
hydro	ocarbons, C9-C1	I0, n-alkanes, isoalkanes, o	cyclic, <2% aromatics:
Asses	ssment	: May cause drow	vsiness or dizziness.
hydro	ocarbons, C9-C1	1, n-alkanes, isoalkanes, o	cyclic, <2% aromatics:
Asses	ssment	: May cause drow	vsiness or dizziness.
react	ion mixture of e	thylbenzene, m-xylene and	l p-xylene:
Asses	ssment	: May cause resp	iratory irritation.
Hydro	ocarbons, C9 ar	omatics:	
Asses	ssment	: May cause drow	vsiness or dizziness.
Asses	ssment	: May cause resp	iratory irritation.
n-but	yl acetate:		
Asses	ssment	: May cause drow	vsiness or dizziness.
стот	- repeated exp	osure	
Com	oonents:		
react	ion mixture of e	thylbenzene, m-xylene and	l p-xylene:
Asses	ssment	: May cause dam exposure.	age to organs through prolonged or repeate
Aspir	ation toxicity		
<u>Com</u>	oonents:		
-		1 <b>0, n-alkanes, isoalkanes, d</b> red and enters airways.	cyclic, <2% aromatics:
hydro	ocarbons, C9-C1	1, n-alkanes, isoalkanes, o	cyclic, <2% aromatics:
-		red and enters airways.	····

# **MOBIHEL ANTISILICONE CLEANER**



Version	Revision	SDS Number:	Date of last issue: -
1.0	Date:	MAT000407597	Date of first issue: 16.11.2023
	16.11.2023	AU/EN	

reaction mixture of ethylbenzene, m-xylene and p-xylene:

May be fatal if swallowed and enters airways.

#### Hydrocarbons, C9 aromatics:

May be fatal if swallowed and enters airways.

#### **Further information**

#### Product:

Remarks

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.
 Concentrations substantially above the TLV value may cause narcotic effects.
 Solvents may degrease the skin.

#### SECTION 12. ECOLOGICAL INFORMATION

#### Ecotoxicity

#### **Components:**

#### hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclic, <2% aromatics:

Ecotoxicology Assessment		
Chronic aquatic toxicity	:	Harmful to aquatic life with long lasting effects.

#### reaction mixture of ethylbenzene, m-xylene and p-xylene:

Toxicity to fish		LC50 (Fish): $\geq 1 - 10 \text{ mg/l}$
Toxicity to daphnia and other aquatic invertebrates	:	LC50 (Daphnia (water flea)): >= 1 - 10 mg/l
Toxicity to microorganisms	:	EC50 (Bacteria): >= 1 - 100 mg/l
Hydrocarbons, C9 aromatics	5:	
Toxicity to fish	:	LC50 (Fish): >= 9.2 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia (water flea)): >= 3.2 mg/l Exposure time: 48 h
Ecotoxicology Assessment Chronic aquatic toxicity	:	Toxic to aquatic life with long lasting effects.
n-butyl acetate:		
Toxicity to algae/aquatic plants	:	NOEC (Desmodesmus subspicatus (green algae)): > 200 mg/l
		EC50 (Desmodesmus subspicatus (green algae)): >= 647.7

# MOBIHEL ANTISILICONE CLEANER



rsion )	Revision Date: 16.11.2023	SDS Nu MAT000 AU/EN		Date of last issue: - Date of first issue: 16.11.2023
			mg/l Exposure time:	72 h
Toxici	ty to microorgan	isms :	IC50 (Tetrahym Exposure time:	ena pyriformis): 356 mg/l 40 h
Persis	stence and deg	radability		
Comp	onents:			
reacti	on mixture of e	thylbenze	ne, m-xylene an	d p-xylene:
Biode	gradability	:	Remarks: Read	ily biodegradable.
Photo	degradation	:	Remarks: Deco	mposes rapidly in contact with light.
n-but	yl acetate:			
	gradability	:	Result: Biodegr Biodegradation Exposure time: Method: OECD	83 %
Stabili	ity in water	:	Degradation ha Remarks: Hydro	lf life: 78 d pH: 8 blyses slowly.
Photo	degradation	:	Remarks: Deco	mposes rapidly in contact with light.
Bioac	cumulative pot	ential		
Comp	onents:			
reacti	on mixture of e	thylbenze	ne, m-xylene and	d p-xylene:
Bioac	cumulation	:		n factor (BCF): 25.9 cumulation is unlikely.
	on coefficient: n- ol/water	:	log Pow: 2.77 -	3.15
Hydro	ocarbons, C9 ar	omatics:		
	on coefficient: n- ol/water	:	log Pow: < 4	
	yl acetate:			
Bioac	cumulation	:		n factor (BCF): 15 ccumulation is unlikely.
	on coefficient: n- ol/water	:	log Pow: 1.81	
Mobil	ity in soil			
	onents:			

reaction mixture of ethylbenzene, m-xylene and p-xylene:

# MOBIHEL ANTISILICONE CLEANER



/ersion .0	Revision Date: 16.11.2023	SDS Nu MAT000 AU/EN	imber: 0407597	Date of last issue: - Date of first issue: 16.11.2023
	Distribution among environ- : mental compartments		Koc: 537, log Koc: 2.73 Remarks: Moderately mobile in soils The product evaporates from soil.	
Stabil	Stability in soil :		Dissipation time: 23 d Percentage dissipation: 50 % (DT50)	
Hydro	ocarbons, C9 ar	omatics:		
Mobil		:	Medium: Air Content: 92.9 %	
			Medium: Water Content: 3.5 %	
			Medium: Soil Content: 1.9 %	
			Medium: Sedime Content: 1.8 %	nt
	oution among en al compartments	viron- :	Koc: 1.71 - 14.70 Remarks: Mobile	
			Remarks: The pro	oduct is insoluble and floats on water.
Othe	adverse effects	S		
Prod	uct:			
Additi matio	onal ecological ir n	nfor- :	unprofessional ha	l hazard cannot be excluded in the event of andling or disposal. c life with long lasting effects.

### SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	<ul> <li>The product should not be allowed to enter drains, water courses or the soil.</li> <li>Do not contaminate ponds, waterways or ditches with chemi- cal or used container.</li> </ul>
Contaminated packaging	<ul> <li>Send to a licensed waste management company.</li> <li>Empty remaining contents.</li> <li>Dispose of as unused product.</li> <li>Do not re-use empty containers.</li> <li>Do not burn, or use a cutting torch on, the empty drum.</li> </ul>

### SECTION 14. TRANSPORT INFORMATION

### **International Regulations**

# UNRTDG

UN number

: UN 1263

# MOBIHEL ANTISILICONE CLEANER



Version 1.0	Revision Date: 16.11.2023	SDS Number: MAT000407597 AU/EN	Date of last issue: - Date of first issue: 16.11.2023
Class	r shipping name ng group s	: PAINT RELATED : 3 : III : 3	MATERIAL
Class Packir Labels Packir aircraf	No. r shipping name ng group ng instruction (ca it) ng instruction (pa	-	
UN nu Prope Class Packii Labels EmS (	ng group	: UN 1263 : PAINT RELATED : 3 : III : 3 : F-E, <u>S-E</u> : no	MATERIAL
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable for product as supplied.			

#### National Regulations

A	DG
	~~

ADO		
UN number	:	UN 1263
Proper shipping name	:	PAINT RELATED MATERIAL
Class	:	3
Packing group	:	III
Labels	:	3
Hazchem Code	:	•3Y

#### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### **SECTION 15. REGULATORY INFORMATION**

#### Safety, health and environmental regulations/legislation specific for the substance or mixture

Standard for the Uniform : Schedule 7 Scheduling of Medicines and Poisons

Prohibition/Licensing Requirements

: There is no applicable prohibition, authorisation and restricted use

# MOBIHEL ANTISILICONE CLEANER



Version 1.0 Revision Date: 16.11.2023 SDS Number: MAT000407597 AU/EN Date of last issue: -Date of first issue: 16.11.2023

requirements, including for carcinogens referred to in Schedule 10 of the model WHS Act and Regulations.

#### **SECTION 16. OTHER INFORMATION**

Revision Date Date format	-	16.11.2023 dd.mm.yyyy		
Full text of other abbreviations				
ACGIH ACGIH BEI AU OEL	:	USA. ACGIH Threshold Limit Values (TLV) ACGIH - Biological Exposure Indices (BEI) Australia. Workplace Exposure Standards for Airborne Con- taminants.		
ACGIH / TWA ACGIH / STEL AU OEL / TWA AU OEL / STEL		8-hour, time-weighted average Short-term exposure limit Exposure standard - time weighted average Exposure standard - short term exposure limit		

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose): MARPOL - International Convention for the Prevention of Pollution from Ships: n.o.s. - Not Otherwise Specified: Nch - Chilean Norm: NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

# MOBIHEL ANTISILICONE CLEANER



Version	Revision	SDS Number:	Date of last issue: -
1.0	Date: 16.11.2023	MAT000407597 AU/EN	Date of first issue: 16.11.2023
	10.11.2020		

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

AU / EN