MOBIHEL ANTISILICONE CLEANER



Date of last issue: -Version Revision SDS Number:

1.0 Date: MAT000407597 Date of first issue: 16.11.2023

> 16.11.2023 AU/EN

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name MOBIHEL ANTISILICONE CLEANER

Product code 40759704

Manufacturer or supplier's details

Details of the supplier of the safety data sheet

: Helios Coatings Australia Pty Ltd Company

> 50 Clapham Road SEFTON NSW 2162

Australia

: 61 2 9645 3188 Telephone E-mail address Responsi-61 2 9645 3188

ble/issuing person info@helioscoatings.com.au

Emergency telephone number

112 (mobile) Ambulance 000, Poisons Information Centre: 131 126

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids Category 3

Skin corrosion/irritation Category 2

Serious eye damage/eye irri-

tation

Category 2A

single exposure

Specific target organ toxicity - : Category 3 (Respiratory system, Central nervous system)

Specific target organ toxicity - :

repeated exposure

Category 2

Aspiration hazard Category 1

GHS label elements

Hazard pictograms



Signal word Danger

Hazard statements H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

MOBIHEL ANTISILICONE CLEANER



Version Revision SDS Number:

1.0 Date: MAT000407597 Date of first issue: 16.11.2023

16.11.2023 AU/EN

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or re-

Date of last issue: -

peated exposure.

Precautionary statements

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P260 Do not breathe mist or vapours.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P314 Get medical advice/ attention if you feel unwell.

P331 Do NOT induce vomiting.

P332 + P313 If skin irritation occurs: Get medical advice/ attention

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P362 + P364 Take off contaminated clothing and wash it before

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

MOBIHEL ANTISILICONE CLEANER



Version Revision SDS Number: Date of last issue: -

1.0 Date: MAT000407597 Date of first issue: 16.11.2023

16.11.2023 AU/EN

Other hazards which do not result in classification

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

| Chemical name | CAS-No. | Concentration (% w/w) |
|--|-------------|-----------------------|
| hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclic, <2% aromatics | 64742-49-0 | >= 30 -< 60 |
| hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics | 64742-48-9 | >= 20 -< 30 |
| reaction mixture of ethylbenzene, m-xylene and p-xylene | 1330-20-7 | >= 10 -< 20 |
| Hydrocarbons, C9 aromatics | 128601-23-0 | >= 10 -< 20 |
| n-butyl acetate | 123-86-4 | < 10 |

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance. Symptoms of poisoning may appear several hours later.

Do not leave the victim unattended.

If inhaled : Consult a physician after significant exposure.

If unconscious, place in recovery position and seek medical

advice.

In case of skin contact : If skin irritation persists, call a physician.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.
Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

Most important symptoms

and effects, both acute and

delayed

None known.

Notes to physician : Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Alcohol-resistant foam

MOBIHEL ANTISILICONE CLEANER



Version Revision SDS Number: Date of last issue: -

Date: MAT000407597 Date of first issue: 16.11.2023 1.0

> 16.11.2023 AU/EN

> > Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

Specific hazards during fire-

fighting

High volume water jet

Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion prod: :

ucts

ods

No hazardous combustion products are known

Specific extinguishing meth-Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

For safety reasons in case of fire, cans should be stored sepa-

In the event of fire, wear self-contained breathing apparatus.

rately in closed containments.

Use a water spray to cool fully closed containers.

Special protective equipment :

for firefighters

Hazchem Code •3Y

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec: : tive equipment and emer-

gency procedures

Use personal protective equipment.

Ensure adequate ventilation. Remove all sources of ignition.

Evacuate personnel to safe areas.

Beware of vapours accumulating to form explosive concentra-

tions. Vapours can accumulate in low areas.

Prevent product from entering drains. **Environmental precautions**

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for

containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local

/ national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on protection against :

fire and explosion

Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge

(which might cause ignition of organic vapours).

Keep away from open flames, hot surfaces and sources of

ignition.

Avoid formation of aerosol. Advice on safe handling

Do not breathe vapours/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes.

MOBIHEL ANTISILICONE CLEANER



Version Revision SDS Number: Date of last issue: -

1.0 Date: MAT000407597 Date of first issue: 16.11.2023

16.11.2023 AU/EN

For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national

regulations.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

Conditions for safe storage : No smoking.

Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|--|-----------|-------------------------------------|--|--------|
| reaction mixture of ethylben- zene, m-xylene and p-xylene | 1330-20-7 | STEL | 150 ppm 655 mg/m3 | AU OEL |
| | | TWA | 80 ppm 350 mg/m3 | AU OEL |
| | | TWA | 20 ppm | ACGIH |
| n-butyl acetate | 123-86-4 | STEL | 200 ppm 950 mg/m3 | AU OEL |
| | | TWA | 150 ppm 713 mg/m3 | AU OEL |
| | | TWA | 50 ppm | ACGIH |
| | | STEL | 150 ppm | ACGIH |

Biological occupational exposure limits

| Components | CAS-No. | Control parameters | Biological specimen | Sam- pling time | Permissible concentration | Basis |
|---|-----------|---------------------------|---------------------|--|---------------------------|--------------|
| reaction mixture of ethylbenzene, m-xylene and p-xylene | 1330-20-7 | Methylhip- puric acids | Urine | End of shift (As soon as possible after exposure ceases) | 1.5 g/g creatinine | ACGIH BEI |

MOBIHEL ANTISILICONE CLEANER



Version Revision SDS Number: Date of last issue: -

1.0 Date: MAT000407597 Date of first issue: 16.11.2023

16.11.2023 AU/EN

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Organic vapour type

Hand protection

Gloves : Nitrile rubber (> 0,1 mm; < 60 min); DIN EN374

Viton® (> 0,6 mm; < 240 min); DIN EN374 | PE laminate (> 0,1 mm; < 240 min); DIN EN374 |

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of

cuts, abrasion, and the contact time.

Eye protection : Equipment should conform to EN 166

Eye wash bottle with pure water Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : colourless

Odour : solvent-like

Odour Threshold : No data available

pH : Not applicable

Melting point/freezing point : -78.0 °C

(calculation method (principal components, lowest value))

Boiling point/boiling range : 80 - 110 °C

(calculation method (principal components, lowest value))

Flash point : 25 °C

Evaporation rate : No data available

Flammability (solid, gas) : Static-accumulating flammable liquid., Combustible Solids

MOBIHEL ANTISILICONE CLEANER



Version Revision SDS Number: Date of last issue: -

1.0 Date: MAT000407597 Date of first issue: 16.11.2023

16.11.2023 AU/EN

Upper explosion limit / Upper : 7.5 %(V)

flammability limit

Lower explosion limit / Lower : 0.7 %(V)

flammability limit

Vapour pressure : < 1,100 hPa (50 °C)

Relative vapour density : 4

Relative density : 0.90

Density : 0.785 g/cm3

Solubility(ies)

Water solubility : immiscible, partly soluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

log Pow: < 4

Auto-ignition temperature : 425 °C

Decomposition temperature : No decomposition if used as directed.

Hazardous decomposition products formed under fire condi-

tions.

Viscosity

Viscosity, kinematic : < 20.5 mm2/s (40 °C)

Explosive properties : Not applicable

Oxidizing properties : Sustains combustion

VOC : (Directive 2004/42/EC)

810 g/l

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed. Possibility of hazardous reac- : No decomposition if stored and applied as directed.

tions Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Incompatible with strong acids and bases.

Hazardous decomposition : Adequate ventilation is required.

products Heating can release vapours which can be ignited.

Carbon monoxide, carbon dioxide and unburned hydrocar-

bons (smoke).

MOBIHEL ANTISILICONE CLEANER



Version Revision SDS Number: Date of last issue: -

1.0 Date: MAT000407597 Date of first issue: 16.11.2023

16.11.2023 AU/EN

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Product:

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l

Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg

Method: Calculation method

Components:

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Acute oral toxicity : LD50 Oral (Rat): >= 8,700 mg/kg

Acute inhalation toxicity : LC50 (Rat): 27.14 mg/l

Test atmosphere: vapour

Acute dermal toxicity : Assessment: The component/mixture is moderately toxic after

single contact withskin.

Hydrocarbons, C9 aromatics:

Acute dermal toxicity : LD50 (Rabbit): > 3,160 mg/kg

n-butyl acetate:

Acute oral toxicity : LD50 Oral (Rat): >= 10,760 mg/kg

Acute dermal toxicity : LD50 (Rabbit): >= 5,000 mg/kg

Skin corrosion/irritation

Product:

Remarks : May cause skin irritation in susceptible persons.

Components:

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Result : irritating

Serious eye damage/eye irritation

Product:

Remarks : May cause irreversible eye damage.

MOBIHEL ANTISILICONE CLEANER



Version 1.0

Revision Date:

SDS Number: MAT000407597

Date of last issue: -

Date of first issue: 16.11.2023

16.11.2023 AU/EN

Components:

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Result : Eye irritation

Chronic toxicity

STOT - single exposure

Components:

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclic, <2% aromatics:

Assessment : May cause drowsiness or dizziness.

hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics:

Assessment : May cause drowsiness or dizziness.

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Assessment : May cause respiratory irritation.

Hydrocarbons, C9 aromatics:

Assessment : May cause drowsiness or dizziness.

Assessment : May cause respiratory irritation.

n-butyl acetate:

Assessment : May cause drowsiness or dizziness.

STOT - repeated exposure

Components:

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Assessment : May cause damage to organs through prolonged or repeated

exposure.

Aspiration toxicity

Components:

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclic, <2% aromatics:

May be fatal if swallowed and enters airways.

hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics:

May be fatal if swallowed and enters airways.

MOBIHEL ANTISILICONE CLEANER



Version Revision SDS Number: Date of last issue: -

1.0 Date: MAT000407597 Date of first issue: 16.11.2023

> 16.11.2023 AU/EN

reaction mixture of ethylbenzene, m-xylene and p-xylene:

May be fatal if swallowed and enters airways.

Hydrocarbons, C9 aromatics:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks Symptoms of overexposure may be headache, dizziness,

tiredness, nausea and vomiting.

Concentrations substantially above the TLV value may cause

narcotic effects.

Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclic, <2% aromatics:

Ecotoxicology Assessment

Chronic aquatic toxicity Harmful to aquatic life with long lasting effects.

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Toxicity to fish LC50 (Fish): >= 1 - 10 mg/l

aquatic invertebrates

Toxicity to daphnia and other : LC50 (Daphnia (water flea)): >= 1 - 10 mg/l

Toxicity to microorganisms EC50 (Bacteria): >= 1 - 100 mg/l

Hydrocarbons, C9 aromatics:

Toxicity to fish LC50 (Fish): >= 9.2 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia (water flea)): >= 3.2 mg/l

Exposure time: 48 h

Ecotoxicology Assessment

Chronic aquatic toxicity Toxic to aquatic life with long lasting effects.

n-butyl acetate:

Toxicity to algae/aquatic

plants

NOEC (Desmodesmus subspicatus (green algae)): > 200 mg/l

EC50 (Desmodesmus subspicatus (green algae)): >= 647.7

MOBIHEL ANTISILICONE CLEANER



Version Revision SDS Number: Date of last issue: -

1.0 Date: MAT000407597 Date of first issue: 16.11.2023

16.11.2023 AU/EN

mg/l

Exposure time: 72 h

Toxicity to microorganisms : IC50 (Tetrahymena pyriformis): 356 mg/l

Exposure time: 40 h

Persistence and degradability

Components:

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Biodegradability : Remarks: Readily biodegradable.

Photodegradation : Remarks: Decomposes rapidly in contact with light.

n-butyl acetate:

Biodegradability : Result: Biodegradable

Biodegradation: 83 % Exposure time: 28 d

Method: OECD Test Guideline 301D

Stability in water : Degradation half life: 78 d pH: 8

Remarks: Hydrolyses slowly.

Photodegradation : Remarks: Decomposes rapidly in contact with light.

Bioaccumulative potential

Components:

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Bioaccumulation : Bioconcentration factor (BCF): 25.9

Remarks: Bioaccumulation is unlikely.

Partition coefficient: n-

octanol/water

log Pow: 2.77 - 3.15

Hydrocarbons, C9 aromatics:

Partition coefficient: n-

log Pow: < 4

octanol/water

n-butyl acetate:

Bioaccumulation : Bioconcentration factor (BCF): 15

Remarks: Bioaccumulation is unlikely.

Partition coefficient: n-

octanol/water

log Pow: 1.81

Mobility in soil

Components:

reaction mixture of ethylbenzene, m-xylene and p-xylene:

MOBIHEL ANTISILICONE CLEANER



Version Revision SDS Number: Date of last issue: -

1.0 Date: MAT000407597 Date of first issue: 16.11.2023

> 16.11.2023 AU/EN

Distribution among environ-

mental compartments

Koc: 537, log Koc: 2.73

Remarks: Moderately mobile in soils

The product evaporates from soil.

Stability in soil Dissipation time: 23 d

Percentage dissipation: 50 % (DT50)

Hydrocarbons, C9 aromatics:

Mobility Medium: Air

Content: 92.9 %

Medium: Water Content: 3.5 %

Medium: Soil Content: 1.9 %

Medium: Sediment Content: 1.8 %

Distribution among environ-

mental compartments

Koc: 1.71 - 14.70

Remarks: Mobile in soils

Remarks: The product is insoluble and floats on water.

Other adverse effects

Product:

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Harmful to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Send to a licensed waste management company.

Contaminated packaging Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number UN 1263

MOBIHEL ANTISILICONE CLEANER



Version Revision SDS Number: Date of last issue: -

1.0 Date: MAT000407597 Date of first issue: 16.11.2023

16.11.2023 AU/EN

Proper shipping name : PAINT RELATED MATERIAL

Class : 3
Packing group : III
Labels : 3

IATA-DGR

UN/ID No. : UN 1263

Proper shipping name : Paint related material

Class : 3 Packing group : III

Labels : Flammable Liquids

Packing instruction (cargo : 366

aircraft)

Packing instruction (passen: 355

ger aircraft)

IMDG-Code

UN number : UN 1263

Proper shipping name : PAINT RELATED MATERIAL

Class : 3
Packing group : III
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

ADG

UN number : UN 1263

Proper shipping name : PAINT RELATED MATERIAL

Class : 3
Packing group : III
Labels : 3
Hazchem Code : •3Y

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Standard for the Uniform : Schedule 7

Scheduling of Medicines and

Poisons

Prohibition/Licensing Requirements : There is no applicable prohibition,

authorisation and restricted use

MOBIHEL ANTISILICONE CLEANER



Version Revision SDS Number: Date of last issue: -

1.0 Date: MAT000407597 Date of first issue: 16.11.2023

16.11.2023 AU/EN

requirements, including for carcinogens referred to in Schedule 10 of the model WHS Act and Regula-

tions.

SECTION 16. OTHER INFORMATION

Revision Date : 16.11.2023 Date format : dd.mm.yyyy

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)

AU OEL : Australia. Workplace Exposure Standards for Airborne Con-

taminants.

ACGIH / TWA : 8-hour, time-weighted average ACGIH / STEL : Short-term exposure limit

AU OEL / TWA : Exposure standard - time weighted average AU OEL / STEL : Exposure standard - short term exposure limit

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan): ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose): MARPOL - International Convention for the Prevention of Pollution from Ships: n.o.s. - Not Otherwise Specified: Nch - Chilean Norm: NO(A)EC - No Observed (Adverse) Effect Concentration: NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

16.11.2023

MOBIHEL ANTISILICONE CLEANER

AU/EN



Version Revision SDS Number: Date of last issue: -

1.0 Date: MAT000407597 Date of first issue: 16.11.2023

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

AU / EN