according to Regulation (EC) No. 1907/2006



## **TESSAROL ALU BRONZE**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	21.11.2023	MAT000409336	Date of first issue: 21.11.2023
		LT/EN	

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name:TESSAROL ALU BRONZEProduct code:40933611

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-	: SU19Building and construction work
stance/Mixture	, PROC10, PROC11 Professional and consumer use of coat-
	ings, Roller application or brushing, Non industrial spraying
	PC9a Coatings and paints, thinners, paint removers

#### 1.3 Details of the supplier of the safety data sheet

Company	:	Helios TBLUS d.o.o. Količevo 65 1230 Domžale Slovenia
Telephone Company	:	386 (1) 722 4383
Telefax Company	:	386 (1) 722 4310
Responsible/issuing person	:	386 (1) 722 4383 productsafety@helios.si

#### 1.4 Emergency telephone number

(+370 5) 2362052 APSINUODIJIMŲ KONTROLĖS IR INFORMACIJOS BIURAS, SVEIKATOS APSAUGOS MINISTERIJOS (+370 5) 2362052 (+370 5) 236 2091 VšĮ Vilniaus greitosios pagalbos universitetinės ligoninės Ūmių apsinuodijimų sk (+370 5) 236 2091 112 Skubi pagalba 112

### **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)					
Flammable liquids, Category 2	H225: Highly flammable liquid and vapour.				
Skin irritation, Category 2	H315: Causes skin irritation.				
Reproductive toxicity, Category 2	H361d: Suspected of damaging the unborn child.				

according to Regulation (EC) No. 1907/2006



# **TESSAROL ALU BRONZE**

Version 1.0	Revision Date: 21.11.2023		Number: 000409336 N	Date of last issue: - Date of first issue: 21.11.2023
	ific target organ toxic re, Category 3, Centr m			H336: May cause drowsiness or dizziness.
	Specific target organ toxicity - repeate exposure, Category 2		peated	H373: May cause damage to organs through pro- longed or repeated exposure.
Long egory	-term (chronic) aquat / 3	ic haza	ard, Cat-	H412: Harmful to aquatic life with long lasting ef- fects.
2.2 Label	elements			
	Iling (REGULATION	(EC)	No 1272/20	
Signa	al word	:	Danger	
Haza	rd statements	:	H315 Ca H336 Ma H361d Su H373 Ma repeated e	ghly flammable liquid and vapour. auses skin irritation. ay cause drowsiness or dizziness. Ispected of damaging the unborn child. ay cause damage to organs through prolonged or exposure. armful to aquatic life with long lasting effects.
Preca	autionary statements	:	label at ha	medical advice is needed, have product container or nd. eep out of reach of children.
			read and u P210 Ke flames and P260 Do P271 Us P280 W	n: o not handle until all safety precautions have been inderstood. eep away from heat, hot surfaces, sparks, open d other ignition sources. No smoking. o not breathe mist or vapours. se only outdoors or in a well-ventilated area. ear protective gloves/ protective clothing/ eye protec- protection/ hearing protection.
			Response	::
			P370 + P3 alcohol-res	In case of fire: Use dry sand, dry chemical or sistant foam to extinguish.
			Storage:	

#### Storage:

P405 Store locked up.

#### Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

according to Regulation (EC) No. 1907/2006



# **TESSAROL ALU BRONZE**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	21.11.2023	MAT000409336	Date of first issue: 21.11.2023
		LT/EN	

#### Hazardous components which must be listed on the label:

toluene

Hydrocarbons, C9 aromatics

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
toluene	108-88-3 203-625-9 601-021-00-3 01-2119471310-51	Flam. Liq. 2; H225 Skin Irrit. 2; H315 Repr. 2; H361d STOT SE 3; H336 (Central nervous system) STOT RE 2; H373 Asp. Tox. 1; H304 Aquatic Chronic 3; H412	>= 50 - < 70
hydrocarbons, C10-C13 n- alkanes, isoalkanes, cyclic, <2% aromatics	- 918-481-9	Asp. Tox. 1; H304 EUH066	>= 1 - < 10
	01-2119457273-39		
Hydrocarbons, C9 aromatics	- 918-668-5 01-2119455851-35	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>= 2,5 - < 10

according to Regulation (EC) No. 1907/2006



# **TESSAROL ALU BRONZE**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	21.11.2023	MAT000409336	Date of first issue: 21.11.2023
		LT/EN	

#### **SECTION 4: First aid measures**

# 4.1 Description of first aid measures

General advice	: Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.				
If inhaled	: Consult a physician after significant exposure. If unconscious, place in recovery position and seek medical advice.				
In case of skin contact	<ul> <li>If skin irritation persists, call a physician.</li> <li>If on skin, rinse well with water.</li> <li>If on clothes, remove clothes.</li> </ul>				
In case of eye contact	<ul> <li>Flush eyes with water as a precaution.</li> <li>Remove contact lenses.</li> <li>Protect unharmed eye.</li> <li>Keep eye wide open while rinsing.</li> <li>If eye irritation persists, consult a specialist.</li> </ul>				
If swallowed	<ul> <li>Keep respiratory tract clear.</li> <li>Do not give milk or alcoholic beverages.</li> <li>Never give anything by mouth to an unconscious person.</li> <li>If symptoms persist, call a physician.</li> <li>Take victim immediately to hospital.</li> </ul>				
4.2 Most important symptoms and effects, both acute and delayed					
Risks	<ul> <li>Causes skin irritation.</li> <li>May cause drowsiness or dizziness.</li> <li>Suspected of damaging the unborn child.</li> <li>May cause damage to organs through prolonged or repeated exposure.</li> </ul>				

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment	: Treat symptomatically.
-----------	--------------------------

### **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

Suitable extinguishing media	:	Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical
Unsuitable extinguishing media	:	High volume water jet

according to Regulation (EC) No. 1907/2006



# **TESSAROL ALU BRONZE**

Version 1.0			Number: 000409336 N	Date of last issue: - Date of first issue: 21.11.2023		
5.2 Specia	al hazards arising fro	om the	e substance or mixtu	re		
•	Specific hazards during fire- fighting		Do not allow run-off from fire fighting to enter drains or water courses.			
Hazaı ucts	•		No hazardous combustion products are known			
5.3 Advice	5.3 Advice for firefighters					
	al protective equipme efighters	nt :	In the event of fire, w	ear self-contained breathing apparatus.		
Furthe	er information	:	must not be discharg Fire residues and co be disposed of in acc For safety reasons in rately in closed conta	ntaminated fire extinguishing water must cordance with local regulations. In case of fire, cans should be stored sepa-		

#### **SECTION 6:** Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.					
.2 Environmental precautions	tions. Vapours can accumulate in low areas.					

# 6.

Environmental precautions	:	Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform
		respective authorities.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up	:	Contain spillage, and then collect with non-combustible ab-
		sorbent material, (e.g. sand, earth, diatomaceous earth, ver-
		miculite) and place in container for disposal according to local
		/ national regulations (see section 13).

### 6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

#### **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

according to Regulation (EC) No. 1907/2006



# **TESSAROL ALU BRONZE**

Ver 1.0	sion	Revision Date: 21.11.2023		Number: 000409336 N	Date of last issue: - Date of first issue: 21.11.2023
	Advice	on safe handling	:	Avoid contact with sk For personal protecti Smoking, eating and plication area. Take precautionary r Provide sufficient air Open drum carefully	urs/dust. ain special instructions before use. kin and eyes.
		on protection agair d explosion	nst :	Take necessary action (which might cause in the second sec	aked flame or any incandescent material. on to avoid static electricity discharge gnition of organic vapours). Use only pment. Keep away from open flames, hot s of ignition.
	Hygien	e measures	:		at or drink. When using do not smoke. breaks and at the end of workday.
7.2	Conditi	ons for safe storag	ge, inc	luding any incompat	ibilities
		ements for storage and containers	:	ventilated place. Cor fully resealed and ke label precautions. Ele	ontainer tightly closed in a dry and well- ntainers which are opened must be care- pt upright to prevent leakage. Observe ectrical installations / working materials e technological safety standards.
	Furthei age sta	r information on sto ability	r- :	No decomposition if	stored and applied as directed.
7.3	Specific	c end use(s)			
	-	c use(s)	:	For further informatic sheet.	on, refer to the product technical data
				Consult the technica stance/mixture.	I guidelines for the use of this sub-

### **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

### **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis			
toluene	108-88-3	TWA	50 ppm 192 mg/m3	2006/15/EC			
	Further information: Indicative, Identifies the possibility of significant uptake through the skin						

according to Regulation (EC) No. 1907/2006



aluminium powe (stabilised)	tt F	hrough the s	kin TPR	: Indicative, Ide	384 entifie	ppm mg/m3 s the possibility of sign	2006/15/E
	tt F	hrough the s	kin TPR nation	RD	100	. , ,	nificant uptak
	F		nation				
	F		-	: Penetrating th	384	) ppm ⊦ mg/m3	LT OEL
	F		-			h the skin, Reproductiv	ve effects
		urther inforr		<u> </u>	50	opm 2 mg/m3	LT OEL
	der 7		nation	: Penetrating th	nroug	h the skin, Reproductiv	ve effects
		429-90-5	IPR	D		ig/m3 uminium)	LT OEL
			IPR fract	D (Respirable tion)		ig/m3 uminium)	LT OEL
				IPRD (Álveolar fraction)		ıg/m3 uminium)	LT OEL
Derived No Eff	fect Lev	/el (DNEL) a	accord	ling to Regula	tion	(EC) No. 1907/2006:	
Substance nam	ne	End Use		Exposure rou	tes	Potential health ef- fects	Value
toluene		Workers	Inhalation			Long-term systemic effects	192 mg/m
		Workers		Inhalation		Long-term local ef- fects	192 mg/m
		Consume	ſS	Inhalation		Acute systemic ef- fects	226 mg/m
		Consumer	ſS	Inhalation		Acute local effects	226 mg/m
aluminium powe (stabilised)	der	Workers		Inhalation		Long-term exposure	3,72 mg/r
		Workers		Inhalation		Long-term local ef- fects	3,72 mg/r
				Oral		Long-term systemic effects	3,95 mg/k bw/day
Hydrocarbons, aromatics	C9	Workers		Inhalation		Long-term systemic effects	150 mg/m
		Workers		Oral		Long-term systemic effects	150 mg/m
		Consumer	ſS	Inhalation		Long-term exposure	32 mg/m3
		Workers		Dermal		Long-term systemic effects	25 mg/kg bw/day
		Consume	rs	Dermal		Long-term systemic effects	11 mg/kg bw/day
Predicted No E	Effect C	oncentratio	on (PN	EC) according	g to F		

Environmental Compartment	Value
Soil	2,89 mg/kg dry
	weight (d.w.)
Marine water	0,68 mg/l
Fresh water	0,68 mg/l
Marine sediment	16,39 mg/kg dry
	weight (d.w.)
Fresh water sediment	16,39 mg/kg dry
	Soil Marine water Fresh water Marine sediment

according to Regulation (EC) No. 1907/2006



# **TESSAROL ALU BRONZE**

		lumber: 00409336	Date of last issue: - Date of first issue: 21.11	.2023		
				Sewage treatment		weight (d.w.) 13,61 mg/l
·	alumin	ium powder (stabil	ised)	Intermittent use/rele Sewage treatment		0,68 mg/l 20 mg/l
ا د ہ	8.2 Exposure controls			Comago acament	plant	20 1119/1
0.2	-					
			Equipment should co Eye wash bottle with Tightly fitting safety g	pure water		
	Hand	protection				
	Glo	ves	:	Viton® (> 0,6 mm; PE laminate (> 0,1	< 240 min); DIN EN374   mm; < 240 min); DIN EN	374
	Re	marks	:	with the producers of Please observe the i breakthrough time w gloves. Also take into	pecific workplace should I f the protective gloves. nstructions regarding perr hich are provided by the s o consideration the specifi e product is used, such as he contact time.	neability and upplier of the c local condi-
	Skin a	nd body protection	:		tion according to the amou gerous substance at the v	
	Respir	atory protection	:	In case of inadequate	e ventilation wear respirat	ory protection.
	Filt	er type	:	A/P2		
	Protec	ctive measures	:		er handling. kin, eyes and clothing. d, drink and animal feedin	gstuffs.

### **SECTION 9: Physical and chemical properties**

### 9.1 Information on basic physical and chemical properties

Physical state	:	liquid
Colour	:	in accordance with the product description
Odour	:	solvent-like
Odour Threshold	:	No data available
Melting point/freezing point	:	-95,0 °C (calculation method (principal components, lowest value))

according to Regulation (EC) No. 1907/2006



Ver 1.0	sion	Revision Date: 21.11.2023		lumber: 00409336	Date of last issue: - Date of first issue: 21.11.2023
	Boiling point/boiling range		:	111 °C (cal value))	culation method (principal components, lowest
	Flammability			Static-accu	mulating flammable liquid., Combustible Solids
	Upper explosion limit / Upper flammability limit			8 %(V) (cal value))	culation method (principal components, highest
	Lower explosion limit / Lower flammability limit			1,2 %(V) (c value))	alculation method (principal components, highest
	Flash p	point	:	5 °C	
	Ignition temperature		:	480 °C (cal value))	culation method (principal components, highest
	Decomposition temperature		e :		osition if stored and applied as directed. decomposition products formed under fire condi-
	рН		:	No data ava	ailable
	Viscosity Viscosity, kinematic Solubility(ies) Water solubility Solubility in other solvents Partition coefficient: n- octanol/water		:	> 20,5 mm2	2/s (40 °C)
			:	insoluble	
			nts :	Description	miscible with most organic solvents
			:	log Pow: 2, highest valı	65 (calculation method (principal components, ue))
	Vapour pressure		:	30 hPa (cal value)) (20 °C)	culation method (principal components, highest
	Relativ	e density	:	No data ava	ailable
	Densit	у	:	0,95 - 0,98	g/cm3
	Relativ	e vapour density	:	No data ava	ailable
9.2	<b>Other i</b> Explos	nformation ives	:	Not applica	ble

according to Regulation (EC) No. 1907/2006



# **TESSAROL ALU BRONZE**

Version 1.0	Revision Date: 21.11.2023		lumber: 00409336	Date of last issue: - Date of first issue: 21.11.2023
Oxic	lizing properties	:	Sustains combustio	n
whic	stances and mixtures, h in contact with wate flammable gases		The substance or m contact with water.	nixture does not emit flammable gases in
VOC	>	:	(Directive 2004/42/8 700 g/l	EC)
SECTIO	N 10: Stability and	reactiv	/ity	

#### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous rea	actions				
Hazardous reactions	: No decomposition if stored and applied as directed.				
	Vapours may form explosive mixture with air.				
10.4 Conditions to avoid					
Conditions to avoid	: Heat, flames and sparks.				
10.5 Incompatible materials					
Materials to avoid	: Incompatible with strong acids and bases.				
10.6 Hazardous decomposition	products				
Adequate ventilation is required. Heating can release vapours which can be ignited. Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).					
SECTION 11: Toxicological ir	nformation				

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Not classified based on available information.

#### **Components:**

<b>toluene:</b> Acute oral toxicity	:	LD50 Oral (Rat): > 5.000 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): > 28 mg/l Exposure time: 4 h Test atmosphere: vapour

according to Regulation (EC) No. 1907/2006



rsion	Revision Date: 21.11.2023	SDS Number: MAT000409336 LT/EN	Date of last issue: - Date of first issue: 21.11.2023
Acute	dermal toxicity	: LD50 (Rabbit): >	5.000 mg/kg
hydro	ocarbons, C10-C13	n-alkanes, isoalkanes, c	
Acute	oral toxicity	: LD50 Oral (Rat, ı Method: OECD T	male and female): > 5.000 mg/kg Test Guideline 401
Acute	inhalation toxicity	: LC50 (Rat): > 5.0 Test atmosphere Method: OECD T	
Acute	dermal toxicity		abbit, male and female): > 5.000 mg/kg ēst Guideline 402
Hydro	ocarbons, C9 arom	atics:	
Acute	dermal toxicity	: LD50 (Rabbit): >	3.160 mg/kg
	corrosion/irritatior es skin irritation.	1	
<u>Produ</u> Rema		: May cause skin i	rritation in susceptible persons.
Comp	oonents:		
tolue	ne:		
Resul	t	: irritating	
hydro	ocarbons, C10-C13	n-alkanes, isoalkanes, c	cyclic, <2% aromatics:
Speci		: Rabbit	
Metho Resul		: OECD Test Guid : No skin irritation	eline 404
GLP	l de la construcción de la constru	: yes	
Resul	t	: Repeated exposu	ure may cause skin dryness or cracking.
Serio	us eye damage/ey	e irritation	
Not cl	assified based on a	vailable information.	
<u>Produ</u>			
Rema	ırks	: Vapours may cau and the skin.	use irritation to the eyes, respiratory system
Comp	oonents:		
hydro	ocarbons, C10-C13	n-alkanes, isoalkanes, c	cyclic, <2% aromatics:
Speci		: Rabbit	
Metho	bd	: OECD Test Guid	eline 405
Resul	t	: No eye irritation	

according to Regulation (EC) No. 1907/2006



# **TESSAROL ALU BRONZE**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	21.11.2023	MAT000409336	Date of first issue: 21.11.2023
		LT/EN	

#### Respiratory or skin sensitisation

#### Skin sensitisation

Not classified based on available information.

#### Respiratory sensitisation

Not classified based on available information.

#### **Components:**

#### hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Exposure routes Species Method Result Skin contact
Guinea pig
OECD Test Guideline 406
Not a skin sensitizer.

#### Germ cell mutagenicity

Not classified based on available information.

#### **Components:**

#### hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Genotoxicity in vitro	:	Result: negative

Genotoxicity in vivo	: Result: negative
----------------------	--------------------

#### Carcinogenicity

Not classified based on available information.

#### Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

: negative

#### **Reproductive toxicity**

Suspected of damaging the unborn child.

#### Components:

#### toluene:

Result

Reproductive toxicity - As- : Some evidence of adverse effects on sexual function and fertility,and/or on development, based on animal experiments.

#### hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

:

Effects on foetal development

#### STOT - single exposure

May cause drowsiness or dizziness.

according to Regulation (EC) No. 1907/2006



Version 1.0	Revision Date: 21.11.2023	SDS Number: MAT000409336 LT/EN	Date of last issue: - Date of first issue: 21.11.2023
Com	ponents:		
tolue	ne:		
Asse	ssment	: May cause drows	iness or dizziness.
hydro	ocarbons, C10-C13	n-alkanes, isoalkanes, c	yclic, <2% aromatics:
Rema	arks	: Based on availab	le data, the classification criteria are not met
Hydr	ocarbons, C9 aron	atics:	
Asse	ssment	: May cause drows	iness or dizziness.
Asse	ssment	: May cause respire	atory irritation.
STO	F - repeated expos	ure	
Mayo	cause damage to or	gans through prolonged or	repeated exposure.
Com	ponents:		
tolue	ne:		
Asse	ssment	: May cause dama exposure.	ge to organs through prolonged or repeated
hydro	ocarbons, C10-C13	n-alkanes, isoalkanes, c	yclic, <2% aromatics:
Rema	arks	: Based on availab	le data, the classification criteria are not met
Aspii	ration toxicity		
Not c	lassified based on a	vailable information.	
Com	ponents:		
tolue	-		
May	be fatal if swallowed	and enters airways.	
hydro	ocarbons, C10-C13	n-alkanes, isoalkanes, c	yclic, <2% aromatics:
May I	be fatal if swallowed	and enters airways.	
•	ocarbons, C9 aron be fatal if swallowed	natics: and enters airways.	
11.2 Infor	mation on other ha	zards	
Endo	ocrine disrupting p	roperties	
Prod	uct:		
	ssment	ered to have endo REACH Article 57	ixture does not contain components consid- ocrine disrupting properties according to 7(f) or Commission Delegated regulation or Commission Regulation (EU) 2018/605 at

according to Regulation (EC) No. 1907/2006



Version 1.0	Revision Date: 21.11.2023		Number: )00409336 N	Date of last issue: - Date of first issue: 21.11.2023
			levels of 0.1% or h	nigher.
Furth	ner information			
Prod	uct:			
Rema	arks	:	tiredness, nausea	bstantially above the TLV value may cause
SECTIO	N 12: Ecological in	forma	ition	
12.1 Toxi	city			
<u>Com</u>	ponents:			
tolue	ene:			
Ecot	oxicology Assessm	ent		
Chro	nic aquatic toxicity	:	Harmful to aquatic	life with long lasting effects.
hvdr	ocarbons. C10-C13	n-alka	nes, isoalkanes, cv	/clic, <2% aromatics:
-	sity to fish	:	· · · ·	nus mykiss (rainbow trout)): > 1.000 mg/l h
	city to daphnia and oth tic invertebrates	ner :	EC50 : > 1.000 mg Exposure time: 48 Method: OECD Te	ĥ
Toxic plant	bity to algae/aquatic s	:	NOEC (Pseudokin mg/l Exposure time: 72 Method: OECD Te	
			EC50 (Pseudokirc mg/l Exposure time: 72 Method: OECD Te	
Hydr	ocarbons, C9 aroma	atics:		
Toxic	city to fish	:	LC50 (Fish): >= 9, Exposure time: 96	
	city to daphnia and oth tic invertebrates	ner :	EC50 (Daphnia (w Exposure time: 48	vater flea)): >= 3,2 mg/l h

according to Regulation (EC) No. 1907/2006



# **TESSAROL ALU BRONZE**

Ecctoxicology Assessment Chronic aquatic toxicity       : Toxic to aquatic life with long lasting effects.         12.2 Persistence and degradability       :         Semponents: hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics: Biodegradability       :         Biodegradability       :         Result: Readily biodegradable. Biodegradation: 80 % Exposure time: 28 d Method: OECD Test Guideline 301F         12.3 Bioaccumulative potential         Components: toluene: Partition coefficient: n-         Partition coefficient: n-         error         Partition coefficient: n-         cotanol/water         12.4 Mobility in soil         Components: Hydrocarbons, C9 aromatics: Partition coefficient: n-         Mobility in soil         Components: Hydrocarbons, C9 aromatics: Mobility         Mobility in soil         Content: 3,5 %         :       Medium: Water Content: 3,5 %         :       Medium: Sediment Content: 1,8 %         Distribution among environ- mental compartments       :         Distribution among environ- mental compartments       :         The product is insoluble and floats on water.         12.5 Results of PBT and vPvB assessment Product;	Version 1.0	Revision Date: 21.11.2023	SDS Number:Date of last issue: -MAT000409336Date of first issue: 21.11.2023LT/EN	
Somponents:         hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:		•••		
hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:	12.2 Per:	sistence and degrad	bility	
Biodegradability : Result: Readily biodegradable. Biodegradation: 80 % Exposure time: 28 d Method: OECD Test Guideline 301F <b>12.3 Bioaccumulative potential</b> Components: toluene: Partition coefficient: n- : log Pow: 2,65 Hydrocarbons, C9 aromatics: Partition coefficient: n- : log Pow: < 4 octanol/water <b>12.4 Mobility in soil</b> Components: Hydrocarbons, C9 aromatics: Mobility : Medium: Air Content: 92,9 % : Medium: Water Content: 3,5 % : Medium: Soil Content: 1,9 % : Medium: Sediment Content: 1,8 % Distribution among environ- mental compartments : Koc: 1,71 - 14,70 Mobile in soils The product is insoluble and floats on water. <b>12.5 Results of PBT and vPvB assessment</b>	<u>Con</u>	<u>iponents:</u>		
Components:         toluene:         Partition coefficient: n-       : log Pow: 2,65         octanol/water         Partition coefficient: n-       : log Pow: < 4	-		: Result: Readily biodegradable. Biodegradation: 80 % Exposure time: 28 d	
Image: Partition coefficient: n- octanol/water       i log Pow: 2,65         Hydrocarbons, C9 aromatics: Partition coefficient: n- octanol/water       i log Pow: < 4	12.3 Bioa	accumulative potent	I	
Partition coefficient: n- octanol/water       i log Pow: 2,65         Hydrocarbons, C9 aromatics:       Partition coefficient: n- octanol/water         12.4 Mobility in soil       i log Pow: < 4	Con	<u>iponents:</u>		
Partition coefficient: n- octanol/water       :       log Pow: < 4	Part	ition coefficient: n-	: log Pow: 2,65	
Components:         Hydrocarbons, C9 aromatics:         Mobility       :         Medium: Air Content: 92,9 %         :       Medium: Water Content: 3,5 %         :       Medium: Soil Content: 1,9 %         :       Medium: Sediment Content: 1,8 %         Distribution among environ- mental compartments       :       Koc: 1,71 - 14,70 Mobile in soils         The product is insoluble and floats on water.       :	Part	ition coefficient: n-		
Hydrocarbons, C9 aromatics:         Mobility       Medium: Air Content: 92,9 %         Medium: Water Content: 3,5 %         Medium: Soil Content: 1,9 %         Medium: Sediment Content: 1,8 %         Distribution among environ- mental compartments       Koc: 1,71 - 14,70 Mobile in soils         The product is insoluble and floats on water.	12.4 Mot	oility in soil		
Mobility       : Medium: Air Content: 92,9 %         : Medium: Water Content: 3,5 %         : Medium: Soil Content: 1,9 %         : Medium: Sediment Content: 1,8 %         Distribution among environ- mental compartments       : Koc: 1,71 - 14,70 Mobile in soils The product is insoluble and floats on water.         12.5 Results of PBT and vPvB assessment	<u>Con</u>	nponents:		
Content: 92,9 % Medium: Water Content: 3,5 % Medium: Soil Content: 1,9 % Medium: Sediment Content: 1,8 % Distribution among environ- mental compartments Koc: 1,71 - 14,70 Mobile in soils The product is insoluble and floats on water. 12.5 Results of PBT and vPvB assessment	Hyd	rocarbons, C9 arom	ics:	
Content: 3,5 % : Medium: Soil Content: 1,9 % : Medium: Sediment Content: 1,8 % Distribution among environ- mental compartments : Koc: 1,71 - 14,70 Mobile in soils The product is insoluble and floats on water. 12.5 Results of PBT and vPvB assessment	Mob	ility		
Content: 1,9 % : Medium: Sediment Content: 1,8 % Distribution among environ- mental compartments : Koc: 1,71 - 14,70 Mobile in soils The product is insoluble and floats on water. 12.5 Results of PBT and vPvB assessment				
Content: 1,8 % Distribution among environ- mental compartments Koc: 1,71 - 14,70 Mobile in soils The product is insoluble and floats on water. 12.5 Results of PBT and vPvB assessment				
mental compartments Mobile in soils The product is insoluble and floats on water. 12.5 Results of PBT and vPvB assessment				
12.5 Results of PBT and vPvB assessment				
			The product is insoluble and floats on water.	
Product:	12.5 Res	ults of PBT and vPv	assessment	
	Proc	duct:		

Assessment

: This substance/mixture contains no components considered

according to Regulation (EC) No. 1907/2006



## **TESSAROL ALU BRONZE**

Version 1.0	Revision Date: 21.11.2023	SDS Number: MAT000409336 LT/EN	Date of last issue: - Date of first issue: 21.11.2023
			er persistent, bioaccumulative and toxic (PBT), or istent and very bioaccumulative (vPvB) at levels of nigher.
Com	ponents:		
bydr	ocarbons C10-C13	n-alkanes isoall	anes, cyclic, <2% aromatics:
•	essment	: This sub	stance is not considered to be persistent, bioaccumu- d toxic (PBT).
12.6 Ende	ocrine disrupting p	roperties	
Prod	luct:		
	essment	ered to h REACH (EU) 201	atance/mixture does not contain components consid- ave endocrine disrupting properties according to Article 57(f) or Commission Delegated regulation 7/2100 or Commission Regulation (EU) 2018/605 at 0.1% or higher.
12.7 Othe	er adverse effects		
Prod	luct:		
	tional ecological info	unprofes	onmental hazard cannot be excluded in the event of sional handling or disposal. o aquatic life with long lasting effects.
SECTIO	N 13: Disposal co	nsiderations	
13 1 Was	te treatment metho	de	
Prod		: The prod courses o Do not co cal or use	uct should not be allowed to enter drains, water or the soil. ontaminate ponds, waterways or ditches with chemi- ed container. a licensed waste management company.
Cont	aminated packaging		maining contents. of as unused product.

Do not re-use empty containers.<br/>Do not burn, or use a cutting torch on, the empty drum.Waste Code: 08 00 00, WASTES FROM THE MANUFACTURE,<br/>FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS<br/>(PAINTS, VARNISHES AND VITREOUS ENAMELS),<br/>ADHESIVES, SEALANTS AND PRINTING INKS<br/>08 01 00, wastes from MFSU and removal of paint and var-<br/>nish<br/>08 01 11, waste paint and varnish containing organic solvents<br/>or other hazardoussubstances<br/>15 00 00, WASTE PACKAGING; ABSORBENTS, WIPING<br/>CLOTHS, FILTER MATERIALS AND PROTECTIVE

according to Regulation (EC) No. 1907/2006



# **TESSAROL ALU BRONZE**

Version 1.0	Revision Date: 21.11.2023	SDS Number: MAT000409336 LT/EN	Date of last issue: - Date of first issue: 21.11.2023
		15 01 00, packagin packaging waste) 15 01 10, packagin by hazardoussubs HP3, Flammable HP4, Irritant - skin	irritation and eye damage get Organ Toxicity (STOT)/Aspiration Toxici-

### **SECTION 14: Transport information**

14.1 U	N nu	mber	or	ID	number
--------	------	------	----	----	--------

	ADN	:	UN 1263	
	ADR	:	UN 1263	
	RID	:	UN 1263	
	IMDG	:	UN 1263	
	ΙΑΤΑ	:	UN 1263	
14.2	2 UN proper shipping name			
	ADN	:	PAINT	
	ADR	:	PAINT	
	RID	:	PAINT	
	IMDG	:	PAINT	
	ΙΑΤΑ	:	Paint	
14.:	3 Transport hazard class(es)			
			Class	Subsidiary risks
	ADN	:	Class 3	Subsidiary risks
	ADN ADR	:		Subsidiary risks
		::	3	Subsidiary risks
	ADR		3 3	Subsidiary risks
	ADR RID		3 3 3	Subsidiary risks
14.4	ADR RID IMDG	:	3 3 3 3	Subsidiary risks
14.4	ADR RID IMDG IATA	:	3 3 3 3	Subsidiary risks

according to Regulation (EC) No. 1907/2006



# **TESSAROL ALU BRONZE**

Vers 1.0	sion	Revision Date: 21.11.2023		Number: 000409336 N	Date of last issue: - Date of first issue: 21.11.2023
	Hazard Labels	cation Code Identification Numb restriction code	: er : :	F1 33 3 (D/E)	
		g group cation Code Identification Numb	: er : :	ll F1 33 3	
	IMDG Packing Labels EmS C		:	ll 3 F-E, <u>S-E</u>	
	aircraft)	instruction (cargo	:	364 Y341 II Flammable Liquids	
	Packing ger airc	instruction (LQ)	ו- : : :	353 Y341 II Flammable Liquids	
14.5 Environmental hazards					
	<b>ADN</b> Environ	mentally hazardous	6 :	no	
	<b>ADR</b> Environ	mentally hazardous	6 :	no	
	<b>RID</b> Environ	mentally hazardous	6 :	no	
	<b>IMDG</b> Marine	pollutant	:	no	

#### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

according to Regulation (EC) No. 1907/2006



# **TESSAROL ALU BRONZE**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	21.11.2023	MAT000409336	Date of first issue: 21.11.2023
		LT/EN	

### **SECTION 15: Regulatory information**

15.1 Safet ture	y, health and environmental regulations/legisla	ation	specific for the substance or mix-
the m	CH - Restrictions on the manufacture, placing on arket and use of certain dangerous substances, res and articles (Annex XVII)	:	Conditions of restriction for the fol- lowing entries should be considered: Number on list 75, 3
			If you intend to use this product as tattoo ink, please contact your ven- dor.
			toluene (Number on list 48)
	CH - Candidate List of Substances of Very High ern for Authorisation (Article 59).	:	Not applicable
	ation (EC) No 1005/2009 on substances that de- the ozone layer	÷	Not applicable
	ation (EU) 2019/1021 on persistent organic pollu- (recast)	:	Not applicable
ment	ation (EC) No 649/2012 of the European Parlia- and the Council concerning the export and import ngerous chemicals	:	Not applicable
	CH - List of substances subject to authorisation ex XIV)	:	Not applicable
pean contro	so III: Directive 2012/18/EU of the Euro-P5c Parliament and of the Council on the of major-accident hazards involving erous substances.	FLA	AMMABLE LIQUIDS
Volati	le organic compounds : Directive 2004/42/EC Volatile organic com		ds (VOC) content: 700 g/l

#### Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

#### 15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

according to Regulation (EC) No. 1907/2006



## **TESSAROL ALU BRONZE**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	21.11.2023	MAT000409336 LT/EN	Date of first issue: 21.11.2023

#### **SECTION 16: Other information**

#### **Full text of H-Statements**

LT OEL / TPRD

H225 H226 H304 H315 H335 H336 H361d	::	Highly flammable liquid and vapour. Flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes skin irritation. May cause respiratory irritation. May cause drowsiness or dizziness. Suspected of damaging the unborn child.		
H373	:	May cause damage to organs through prolonged or repeated exposure.		
H411 H412 EUH066	::	Toxic to aquatic life with long lasting effects. Harmful to aquatic life with long lasting effects. Repeated exposure may cause skin dryness or cracking.		
Full text of other abbreviations				
Aquatic Chronic	:	Long-term (chronic) aquatic hazard		
Asp. Tox.	:	Aspiration hazard		
Flam. Liq.	:	Flammable liquids		
Repr.	:	Reproductive toxicity		
Skin Irrit.	:	Skin irritation		
STOT RE	:	Specific target organ toxicity - repeated exposure		
STOT SE	:	Specific target organ toxicity - single exposure		
2006/15/EC	:	Europe. Indicative occupational exposure limit values		
LT OEL	:	Lithuania. Occupational Exposure Limits		
2006/15/EC / TWA		Limit Value - eight hours		
2006/15/EC / STEL	:	Short term exposure limit		
LT OEL / IPRD	:	Long term exposure limit		

: Short term exposure limit

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA -European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of according to Regulation (EC) No. 1907/2006



## **TESSAROL ALU BRONZE**

Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

#### Further information

Classification of the mixtu	re:	Classification procedure:
Flam. Liq. 2	H225	Based on product data or assessment
Skin Irrit. 2	H315	Calculation method
Repr. 2	H361d	Calculation method
STOT SE 3	H336	Calculation method
STOT RE 2	H373	Calculation method
Aquatic Chronic 3	H412	Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.