

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL 2K FADE OUT THINNER 2400

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	27.11.2023	MAT000470173	Date of first issue: 27.11.2023
		ES/EN	

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : MOBIHEL 2K FADE OUT THINNER 2400  
Product code : 47017331

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : PC9a Coatings and paints, thinners, paint removers  
Recommended restrictions on use : Reserved for industrial and professional use.

#### 1.3 Details of the supplier of the safety data sheet

Company : Helios TBLUS d.o.o.  
Količevo 65  
1230 Domžale  
Slovenia  
Telephone Company : 386 (1) 722 4383  
Telefax Company : 386 (1) 722 4310  
Responsible/issuing person : 386 (1) 722 4383  
productsafety@helios.si

#### 1.4 Emergency telephone number

Instituto Nacional de Toxicología y Ciencias Forenses Servicio de Información Toxicológica + 34  
91 562 04 20

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Specific target organ toxicity - single exposure, Category 3, Central nervous	H336: May cause drowsiness or dizziness.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL 2K FADE OUT THINNER 2400

Version  
1.0

Revision Date:  
27.11.2023

SDS Number:  
MAT000470173  
ES/EN

Date of last issue: -  
Date of first issue: 27.11.2023

system

Specific target organ toxicity - repeated exposure, Category 2

H373: May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard, Category 1

H304: May be fatal if swallowed and enters airways.

### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements : **Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.  
P264 Wash skin thoroughly after handling.

#### **Response:**

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.  
P331 Do NOT induce vomiting.  
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

#### **Hazardous components which must be listed on the label:**

n-butyl acetate  
2-methoxy-1-methylethyl acetate  
reaction mixture of ethylbenzene, m-xylene and p-xylene  
Hydrocarbons, C9 aromatics

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL 2K FADE OUT THINNER 2400

Version  
1.0

Revision Date:  
27.11.2023

SDS Number:  
MAT000470173  
ES/EN

Date of last issue: -  
Date of first issue: 27.11.2023

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

##### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
n-butyl acetate	123-86-4 204-658-1 607-025-00-1 01-2119485493-29	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) EUH066	>= 30 - < 50
2-methoxy-1-methylethyl acetate	108-65-6 203-603-9 607-195-00-7 01-2119475791-29	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system)	>= 30 - < 50
reaction mixture of ethylbenzene, m-xylene and p-xylene	- 905-562-9 01-2119555267-33	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 Asp. Tox. 1; H304	>= 10 - < 20
2-butoxyethyl acetate	112-07-2 203-933-3 607-038-00-2 01-2119475112-47	Acute Tox. 4; H302 Acute Tox. 4; H332 Acute Tox. 4; H312	>= 1 - < 10
Hydrocarbons, C9 aromatics	- 918-668-5 01-2119455851-35	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>= 1 - < 2,5

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL 2K FADE OUT THINNER 2400

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	27.11.2023	MAT000470173	Date of first issue: 27.11.2023
		ES/EN	

---

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Symptoms of poisoning may appear several hours later.  
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.  
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If skin irritation persists, call a physician.  
If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do NOT induce vomiting.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.

#### 4.2 Most important symptoms and effects, both acute and delayed

- Risks : May be fatal if swallowed and enters airways.  
Causes skin irritation.  
Causes serious eye irritation.  
May cause drowsiness or dizziness.  
May cause damage to organs through prolonged or repeated exposure.

#### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.

---

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

- Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : High volume water jet

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL 2K FADE OUT THINNER 2400

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	27.11.2023	MAT000470173 ES/EN	Date of first issue: 27.11.2023

---

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : No hazardous combustion products are known

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Ensure adequate ventilation.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

### 6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL 2K FADE OUT THINNER 2400

Version  
1.0

Revision Date:  
27.11.2023

SDS Number:  
MAT000470173  
ES/EN

Date of last issue: -  
Date of first issue: 27.11.2023

---

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

- Advice on safe handling : Avoid formation of aerosol.  
Do not breathe vapours/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Open drum carefully as content may be under pressure.  
Dispose of rinse water in accordance with local and national regulations.
- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.
- Hygiene measures : When using do not eat or drink. When using do not smoke.  
Wash hands before breaks and at the end of workday.

#### 7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage stability : No decomposition if stored and applied as directed.

#### 7.3 Specific end use(s)

- Specific use(s) : For further information, refer to the product technical data sheet.
- Consult the technical guidelines for the use of this substance/mixture.

---

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

##### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
n-butyl acetate	123-86-4	VLA-ED	50 ppm	ES VLA

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL 2K FADE OUT THINNER 2400

Version  
1.0

Revision Date:  
27.11.2023

SDS Number:  
MAT000470173  
ES/EN

Date of last issue: -  
Date of first issue: 27.11.2023

			241 mg/m <sup>3</sup>	
		VLA-EC	150 ppm 723 mg/m <sup>3</sup>	ES VLA
		STEL	150 ppm 723 mg/m <sup>3</sup>	2019/1831/E U
	Further information: Indicative			
		TWA	50 ppm 241 mg/m <sup>3</sup>	2019/1831/E U
	Further information: Indicative			
2-methoxy-1-methylethyl acetate	108-65-6	STEL	100 ppm 550 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	50 ppm 275 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		VLA-EC	100 ppm 550 mg/m <sup>3</sup>	ES VLA
	Further information: Skin			
		VLA-ED	50 ppm 275 mg/m <sup>3</sup>	ES VLA
	Further information: Skin			
reaction mixture of ethylbenzene, m-xylene and p-xylene	1330-20-7	VLA-ED	50 ppm 221 mg/m <sup>3</sup>	ES VLA
	Further information: Skin			
		VLA-EC	100 ppm 442 mg/m <sup>3</sup>	ES VLA
	Further information: Skin			
		TWA	50 ppm 221 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	100 ppm 442 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
2-butoxyethyl acetate	112-07-2	TWA	20 ppm 133 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	50 ppm 333 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		VLA-ED	20 ppm 133 mg/m <sup>3</sup>	ES VLA
	Further information: Skin			

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL 2K FADE OUT THINNER 2400

Version  
1.0

Revision Date:  
27.11.2023

SDS Number:  
MAT000470173  
ES/EN

Date of last issue: -  
Date of first issue: 27.11.2023

	VLA-EC	50 ppm 333 mg/m <sup>3</sup>	ES VLA
Further information: Skin			

### Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
reaction mixture of ethylbenzene, m-xylene and p-xylene	1330-20-7	methylhippuric acids: 1 g/g creatinine (Urine)	End of workday	ES VLB

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
n-butyl acetate	Workers	Inhalation	Acute systemic effects	600 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	600 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term systemic effects	48 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	300 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute systemic effects	300 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute local effects	300 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term systemic effects	12 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local effects	35,7 mg/m <sup>3</sup>
	Consumers	Dermal	Long-term systemic effects	3,4 mg/kg bw/day
	Consumers	Dermal	Acute systemic effects	6 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	2 mg/kg bw/day
	Consumers	Oral	Acute systemic effects	2 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	7 mg/kg bw/day
	Workers	Dermal	Acute systemic effects	11 mg/kg bw/day
2-methoxy-1-methylethyl acetate	Workers	Inhalation	Long-term systemic effects	275 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	550 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term systemic effects	33 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local effects	33 mg/m <sup>3</sup>
	Workers	Dermal	Long-term systemic effects	796 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	320 mg/kg bw/day
	Consumers	Oral	Long-term systemic	36 mg/kg



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL 2K FADE OUT THINNER 2400

Version  
1.0

Revision Date:  
27.11.2023

SDS Number:  
MAT000470173  
ES/EN

Date of last issue: -  
Date of first issue: 27.11.2023

			effects	bw/day
reaction mixture of ethylbenzene, m-xylene and p-xylene	Workers	Inhalation	Long-term systemic effects	77 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local effects	65,3 mg/m <sup>3</sup>
	Workers	Inhalation	Acute systemic effects	442 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	289 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute systemic effects	260 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	221 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term systemic effects	14,8 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute local effects	260 mg/m <sup>3</sup>
	Consumers	Dermal	Long-term systemic effects	108 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	16 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	180 mg/kg bw/day
2-butoxyethyl acetate	Workers	Inhalation	Long-term systemic effects	333 mg/m <sup>3</sup>
	Consumers	Oral	Long-term systemic effects	86 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	169 mg/kg bw/day
	Workers	Dermal	Acute systemic effects	120 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	102 mg/kg bw/day
	Consumers	Dermal	Acute systemic effects	72 mg/kg bw/day
	Consumers	Oral	Acute systemic effects	36 mg/kg bw/day
Hydrocarbons, C9 aromatics	Workers	Inhalation	Long-term systemic effects	150 mg/m <sup>3</sup>
	Workers	Oral	Long-term systemic effects	150 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term exposure	32 mg/m <sup>3</sup>
	Workers	Dermal	Long-term systemic effects	25 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	11 mg/kg bw/day

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
n-butyl acetate	Soil	0,0903 mg/kg dry weight (d.w.)
	Marine water	0,018 mg/l
	Fresh water	0,18 mg/l

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL 2K FADE OUT THINNER 2400

Version  
1.0

Revision Date:  
27.11.2023

SDS Number:  
MAT000470173  
ES/EN

Date of last issue: -  
Date of first issue: 27.11.2023

	Marine sediment	0,0981 mg/kg dry weight (d.w.)
	Fresh water sediment	0,981 mg/kg dry weight (d.w.)
	Sewage treatment plant	35,6 mg/l
	Intermittent use/release	0,36 mg/l
2-methoxy-1-methylethyl acetate	Soil	0,29 mg/kg dry weight (d.w.)
	Marine water	0,0635 mg/l
	Fresh water	0,635 mg/l
	Marine sediment	0,329 mg/kg dry weight (d.w.)
	Fresh water sediment	3,29 mg/kg dry weight (d.w.)
	Sewage treatment plant	100 mg/l
	Intermittent use/release	0,00635 mg/l
reaction mixture of ethylbenzene, m-xylene and p-xylene	Soil	2,31 mg/kg dry weight (d.w.)
	Marine water	0,327 mg/l
	Fresh water	0,327 mg/l
	Marine sediment	12,46 mg/kg dry weight (d.w.)
	Fresh water sediment	12,46 mg/kg dry weight (d.w.)
	Sewage treatment plant	6,58 mg/l
	Intermittent use/release	0,327 mg/l
2-butoxyethyl acetate	Soil	0,415 mg/kg dry weight (d.w.)
	Marine water	0,0304 mg/l
	Fresh water	0,304 mg/l
	Marine sediment	0,203 mg/kg dry weight (d.w.)
	Fresh water sediment	2,03 mg/kg dry weight (d.w.)
	Sewage treatment plant	90 mg/l
	Intermittent use/release	0,56 mg/l

### 8.2 Exposure controls

#### Personal protective equipment

Eye/face protection : Equipment should conform to EN 166  
Eye wash bottle with pure water  
Tightly fitting safety goggles  
Wear face-shield and protective suit for abnormal processing problems.

#### Hand protection

Gloves : Viton® (> 0,6 mm; < 240 min); DIN EN374 |  
PE laminate (> 0,1 mm; < 240 min); DIN EN374 |

Remarks : Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL 2K FADE OUT THINNER 2400

Version 1.0	Revision Date: 27.11.2023	SDS Number: MAT000470173 ES/EN	Date of last issue: - Date of first issue: 27.11.2023
----------------	------------------------------	--------------------------------------	--

gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

- Skin and body protection : Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.  
Equipment should conform to EN 14387
- Filter type : Organic vapour type (A)

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

- Physical state : liquid
- Colour : in accordance with the product description
- Odour : none
- Odour Threshold : No data available
- Melting point/freezing point : -78,0 °C (calculation method (principal components, lowest value))
- Boiling point/boiling range : 126 °C (calculation method (principal components, lowest value))
- Flammability : Static-accumulating flammable liquid., Combustible Solids
- Upper explosion limit / Upper flammability limit : 8,4 %(V) (calculation method (principal components, highest value))
- Lower explosion limit / Lower flammability limit : 1,1 %(V) (calculation method (principal components, highest value))
- Flash point : 37 °C
- Ignition temperature : 280 °C (calculation method (principal components, highest value))
- Decomposition temperature : No decomposition if used as directed.  
Hazardous decomposition products formed under fire condi-

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL 2K FADE OUT THINNER 2400

Version 1.0	Revision Date: 27.11.2023	SDS Number: MAT000470173 ES/EN	Date of last issue: - Date of first issue: 27.11.2023
----------------	------------------------------	--------------------------------------	--

---

tions.

pH : Not applicable

Viscosity  
Viscosity, kinematic : < 20,5 mm<sup>2</sup>/s (40 °C)

Solubility(ies)  
Water solubility : immiscible, partly soluble

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : log Pow: 2,77 - 3,15 (calculation method (principal components, highest value))

Vapour pressure : < 1.100 hPa (calculation method (principal components, highest value)) (50 °C)

Relative density : 0,91 (calculation method (principal components, highest value))

Density : 0,913 g/cm<sup>3</sup>

Relative vapour density : 5,5 (calculation method (principal components, lowest value)) (Air = 1.0)

### 9.2 Other information

Explosives : Not applicable

Oxidizing properties : Sustains combustion

Evaporation rate : No data available

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL 2K FADE OUT THINNER 2400

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	27.11.2023	MAT000470173	Date of first issue: 27.11.2023
		ES/EN	

### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

### 10.5 Incompatible materials

Materials to avoid : Incompatible with strong acids and bases.

### 10.6 Hazardous decomposition products

Adequate ventilation is required.

Heating can release vapours which can be ignited.

Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Not classified based on available information.

#### Product:

Acute oral toxicity : Acute toxicity estimate: > 2.000 mg/kg  
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg  
Method: Calculation method

#### Components:

##### **n-butyl acetate:**

Acute oral toxicity : LD50 Oral (Rat): >= 10.760 mg/kg

Acute dermal toxicity : LD50 (Rabbit): >= 5.000 mg/kg

##### **2-methoxy-1-methylethyl acetate:**

Acute oral toxicity : LD50 Oral (Rat): > > 2.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l  
Test atmosphere: vapour

LC0 (Rat): 2000 ppm  
Exposure time: 3 h

Acute dermal toxicity : LD50 (Rabbit): > > 2.000 mg/kg

#### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL 2K FADE OUT THINNER 2400

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	27.11.2023	MAT000470173	Date of first issue: 27.11.2023
		ES/EN	

Acute oral toxicity : LD50 Oral (Rat):  $\geq 8.700$  mg/kg

Acute inhalation toxicity : LC50 (Rat): 27,14 mg/l  
Test atmosphere: vapour

Acute dermal toxicity : Assessment: The component/mixture is moderately toxic after single contact with skin.

### **2-butoxyethyl acetate:**

Acute oral toxicity : Assessment: The component/mixture is moderately toxic after single ingestion.  
LD50 Oral (Rat):  $\geq 2.400$  mg/kg

Acute inhalation toxicity : LC50 (Rat):  $\geq 50$  mg/l  
Exposure time: 2 h  
Test atmosphere: vapour

Acute dermal toxicity : Assessment: The component/mixture is moderately toxic after single contact with skin.  
LD50 (Rabbit):  $\geq 1.500$  mg/kg

### **Hydrocarbons, C9 aromatics:**

Acute dermal toxicity : LD50 (Rabbit):  $> 3.160$  mg/kg

### **Skin corrosion/irritation**

Causes skin irritation.

#### **Product:**

Remarks : May cause skin irritation in susceptible persons.

#### **Components:**

##### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Result : irritating

##### **Serious eye damage/eye irritation**

Causes serious eye irritation.

#### **Product:**

Remarks : May cause irreversible eye damage.

#### **Components:**

##### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Result : Eye irritation

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL 2K FADE OUT THINNER 2400

Version  
1.0

Revision Date:  
27.11.2023

SDS Number:  
MAT000470173  
ES/EN

Date of last issue: -  
Date of first issue: 27.11.2023

---

### **Respiratory or skin sensitisation**

#### **Skin sensitisation**

Not classified based on available information.

#### **Respiratory sensitisation**

Not classified based on available information.

#### **Germ cell mutagenicity**

Not classified based on available information.

#### **Carcinogenicity**

Not classified based on available information.

#### **Reproductive toxicity**

Not classified based on available information.

#### **STOT - single exposure**

May cause drowsiness or dizziness.

#### **Components:**

##### **n-butyl acetate:**

Assessment : May cause drowsiness or dizziness.

##### **2-methoxy-1-methylethyl acetate:**

Assessment : May cause drowsiness or dizziness.

##### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Assessment : May cause respiratory irritation.

##### **Hydrocarbons, C9 aromatics:**

Assessment : May cause drowsiness or dizziness.

Assessment : May cause respiratory irritation.

#### **STOT - repeated exposure**

May cause damage to organs through prolonged or repeated exposure.

#### **Components:**

##### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Assessment : May cause damage to organs through prolonged or repeated exposure.

#### **Aspiration toxicity**

May be fatal if swallowed and enters airways.

#### **Components:**

##### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

May be fatal if swallowed and enters airways.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL 2K FADE OUT THINNER 2400

Version  
1.0

Revision Date:  
27.11.2023

SDS Number:  
MAT000470173  
ES/EN

Date of last issue: -  
Date of first issue: 27.11.2023

### Hydrocarbons, C9 aromatics:

May be fatal if swallowed and enters airways.

### 11.2 Information on other hazards

#### Endocrine disrupting properties

##### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

#### Further information

##### Product:

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.  
Concentrations substantially above the TLV value may cause narcotic effects.  
Solvents may degrease the skin.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

##### **n-butyl acetate:**

Toxicity to algae/aquatic plants : NOEC (Desmodesmus subspicatus (green algae)): > 200 mg/l  
EC50 (Desmodesmus subspicatus (green algae)): >= 647,7 mg/l  
Exposure time: 72 h

Toxicity to microorganisms : IC50 (Tetrahymena pyriformis): 356 mg/l  
Exposure time: 40 h

##### **2-methoxy-1-methylethyl acetate:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 130 mg/l  
Exposure time: 96 h  
NOEC : 100 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other : LC50 : 408 mg/l



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL 2K FADE OUT THINNER 2400

Version  
1.0

Revision Date:  
27.11.2023

SDS Number:  
MAT000470173  
ES/EN

Date of last issue: -  
Date of first issue: 27.11.2023

aquatic invertebrates Exposure time: 48 h

Toxicity to fish (Chronic toxicity) : EC10: 47,5 mg/l

### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Toxicity to fish : LC50 (Fish):  $\geq 1 - 10$  mg/l

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)):  $\geq 1 - 10$  mg/l

Toxicity to microorganisms : EC50 (Bacteria):  $\geq 1 - 100$  mg/l

### **2-butoxyethyl acetate:**

Toxicity to fish : LC50 (Fish):  $\geq 31$  mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)):  $\geq 142,5$  mg/l  
Exposure time: 48 h

Toxicity to microorganisms : EC50 (Bacteria):  $\geq 2.800$  mg/l

### **Hydrocarbons, C9 aromatics:**

Toxicity to fish : LC50 (Fish):  $\geq 9,2$  mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)):  $\geq 3,2$  mg/l  
Exposure time: 48 h

### **Ecotoxicology Assessment**

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

## **12.2 Persistence and degradability**

### **Components:**

#### **n-butyl acetate:**

Biodegradability : Result: Biodegradable  
Biodegradation: 83 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301D

Stability in water : Degradation half life: 78 d  
pH: 8  
Hydrolyses slowly.

Photodegradation : Decomposes rapidly in contact with light.

#### **2-methoxy-1-methylethyl acetate:**

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL 2K FADE OUT THINNER 2400

Version 1.0      Revision Date: 27.11.2023      SDS Number: MAT000470173      Date of last issue: -  
Date of first issue: 27.11.2023  
ES/EN

---

Biodegradability : Readily biodegradable.

### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Biodegradability : Readily biodegradable.

Photodegradation : Decomposes rapidly in contact with light.

### **2-butoxyethyl acetate:**

Biodegradability : Result: Biodegradable

## 12.3 Bioaccumulative potential

### Components:

#### **n-butyl acetate:**

Bioaccumulation : Bioconcentration factor (BCF): 15  
Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water : log Pow: 1,81

#### **2-methoxy-1-methylethyl acetate:**

Partition coefficient: n-octanol/water : log Pow: 1,2 (20 °C)  
pH: 6,8

### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Bioaccumulation : Bioconcentration factor (BCF): 25,9  
Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water : log Pow: 2,77 - 3,15

#### **2-butoxyethyl acetate:**

Partition coefficient: n-octanol/water : log Pow: 1,51

#### **Hydrocarbons, C9 aromatics:**

Partition coefficient: n-octanol/water : log Pow: < 4

## 12.4 Mobility in soil

### Components:

#### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Distribution among environmental compartments : Koc: 537, log Koc: 2,73  
Moderately mobile in soils  
The product evaporates from soil.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL 2K FADE OUT THINNER 2400

Version  
1.0

Revision Date:  
27.11.2023

SDS Number:  
MAT000470173  
ES/EN

Date of last issue: -  
Date of first issue: 27.11.2023

---

Stability in soil : Dissipation time: 23 d  
Percentage dissipation: 50 % (DT50)

### Hydrocarbons, C9 aromatics:

Mobility : Medium: Air  
Content: 92,9 %  
  
: Medium: Water  
Content: 3,5 %  
  
: Medium: Soil  
Content: 1,9 %  
  
: Medium: Sediment  
Content: 1,8 %

Distribution among environmental compartments : Koc: 1,71 - 14,70  
Mobile in soils

The product is insoluble and floats on water.

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

#### Product:

Additional ecological information : No data available

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL 2K FADE OUT THINNER 2400

Version  
1.0

Revision Date:  
27.11.2023

SDS Number:  
MAT000470173  
ES/EN

Date of last issue: -  
Date of first issue: 27.11.2023

Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

Waste Code : 08 00 00, WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS  
08 01 00, wastes from MFSU and removal of paint and varnish  
08 01 11, waste paint and varnish containing organic solvents or other hazardous substances  
15 00 00, WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED  
15 01 00, packaging (including separately collected municipal packaging waste)  
15 01 10, packaging containing residues of or contaminated by hazardous substances  
HP3, Flammable  
HP4, Irritant - skin irritation and eye damage  
HP5, Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

### SECTION 14: Transport information

#### 14.1 UN number or ID number

ADN : UN 1263  
ADR : UN 1263  
RID : UN 1263  
IMDG : UN 1263  
IATA : UN 1263

#### 14.2 UN proper shipping name

ADN : PAINT RELATED MATERIAL  
ADR : PAINT RELATED MATERIAL  
RID : PAINT RELATED MATERIAL  
IMDG : PAINT RELATED MATERIAL  
IATA : Paint related material

#### 14.3 Transport hazard class(es)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL 2K FADE OUT THINNER 2400

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	27.11.2023	MAT000470173	Date of first issue: 27.11.2023
		ES/EN	

---

	Class	Subsidiary risks
<b>ADN</b>	: 3	
<b>ADR</b>	: 3	
<b>RID</b>	: 3	
<b>IMDG</b>	: 3	
<b>IATA</b>	: 3	

### 14.4 Packing group

#### **ADN**

Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3

#### **ADR**

Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3  
Tunnel restriction code : (D/E)

#### **RID**

Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3

#### **IMDG**

Packing group : III  
Labels : 3  
EmS Code : F-E, S-E

#### **IATA (Cargo)**

Packing instruction (cargo aircraft) : 366  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable Liquids

#### **IATA (Passenger)**

Packing instruction (passenger aircraft) : 355  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable Liquids

### 14.5 Environmental hazards

#### **ADN**

Environmentally hazardous : no

#### **ADR**

Environmentally hazardous : no

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL 2K FADE OUT THINNER 2400

Version 1.0	Revision Date: 27.11.2023	SDS Number: MAT000470173 ES/EN	Date of last issue: - Date of first issue: 27.11.2023
----------------	------------------------------	--------------------------------------	--

---

### RID

Environmentally hazardous : no

### IMDG

Marine pollutant : no

### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 3

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P5c FLAMMABLE LIQUIDS

### Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

Take note of Directive 94/33/EC on the protection of young people at work or stricter national

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL 2K FADE OUT THINNER 2400

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	27.11.2023	MAT000470173	Date of first issue: 27.11.2023
		ES/EN	

regulations, where applicable.

### 15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

## SECTION 16: Other information

### Full text of H-Statements

H226	:	Flammable liquid and vapour.
H302	:	Harmful if swallowed.
H304	:	May be fatal if swallowed and enters airways.
H312	:	Harmful in contact with skin.
H315	:	Causes skin irritation.
H319	:	Causes serious eye irritation.
H332	:	Harmful if inhaled.
H335	:	May cause respiratory irritation.
H336	:	May cause drowsiness or dizziness.
H373	:	May cause damage to organs through prolonged or repeated exposure.
H411	:	Toxic to aquatic life with long lasting effects.
EUH066	:	Repeated exposure may cause skin dryness or cracking.

### Full text of other abbreviations

Acute Tox.	:	Acute toxicity
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard
Eye Irrit.	:	Eye irritation
Flam. Liq.	:	Flammable liquids
Skin Irrit.	:	Skin irritation
STOT RE	:	Specific target organ toxicity - repeated exposure
STOT SE	:	Specific target organ toxicity - single exposure
2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2019/1831/EU	:	Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values
ES VLA	:	Spain. Environmental Limits for exposure to Chemical agents - Table 1: Occupational Exposure Values
ES VLB	:	Occupational Exposure Limits for Chemical Agents in Spain - Biological Exposure Values
2000/39/EC / TWA	:	Limit Value - eight hours
2000/39/EC / STEL	:	Short term exposure limit
2019/1831/EU / TWA	:	Limit Value - eight hours
2019/1831/EU / STEL	:	Short term exposure limit
ES VLA / VLA-ED	:	Environmental Daily Limit Value
ES VLA / VLA-EC	:	Environmental Short Term Value

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL 2K FADE OUT THINNER 2400

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	27.11.2023	MAT000470173	Date of first issue: 27.11.2023
		ES/EN	

of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

#### Classification of the mixture:

Flam. Liq. 3	H226
Skin Irrit. 2	H315
Eye Irrit. 2	H319
STOT SE 3	H336
STOT RE 2	H373
Asp. Tox. 1	H304

#### Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.