

MOBIHEL ANTISILICONE CLEANER

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	27.11.2023	MAT000407597 ES/EN	Date of first issue: 27.11.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier		
Trade name	: MOBIHEL ANTISILICONE CLEANER	
Product code	: 40759705	
1.2 Relevant identified use	f the substance or mixture and uses advised ag	ainst
Use of the Sub- stance/Mixture	: PC9a Coatings and paints, thinners, paint r	emovers
Recommended restricti on use	: Reserved for industrial and professional use	9.
1.3 Details of the supplier	the safety data sheet	
Company	: Helios TBLUS d.o.o. Količevo 65 1230 Domžale Slovenia	
Telephone Company	: 386 (1) 722 4383	
Telefax Company	: 386 (1) 722 4310	
Responsible/issuing pe	n : 386 (1) 722 4383 productsafety@helios.si	

1.4 Emergency telephone number

Instituto Nacional de Toxicología y Ciencias Forenses Servicio de Información Toxicológica + 34 91 562 04 20

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 Skin irritation, Category 2 Eye irritation, Category 2 Specific target organ toxicity - single exposure, Category 3, Respiratory system Specific target organ toxicity - single exposure, Category 3, Central nervous system

- H226: Flammable liquid and vapour.
- H315: Causes skin irritation.
- H319: Causes serious eye irritation.
- H335: May cause respiratory irritation.

H336: May cause drowsiness or dizziness.

MOBIHEL ANTISILICONE CLEANER



Vers 1.0	sion	Revision Date: 27.11.2023		5 Number: 7000407597 EN	Date of last issue: - Date of first issue: 27.11.2023
	Specific target organ toxicity - repeated exposure, Category 2 Aspiration hazard, Category 1			-	H373: May cause damage to organs through pro- longed or repeated exposure. H304: May be fatal if swallowed and enters air- ways.
	egory 3		ic haz	ard, Cat-	H412: Harmful to aquatic life with long lasting effects.
2.2	Label el	lements			
		ng (REGULATION I pictograms	l (EC) :	No 1272/20	
	Signal	word	:	Danger	• •
	Hazard	statements	:	H304 Ma H315 Ca H319 Ca H335 Ma H336 Ma H373 Ma repeated e	ammable liquid and vapour. ay be fatal if swallowed and enters airways. auses skin irritation. auses serious eye irritation. ay cause respiratory irritation. ay cause drowsiness or dizziness. ay cause damage to organs through prolonged or exposure. armful to aquatic life with long lasting effects.
	Precau	tionary statements	:	flames and P260 Do	n: eep away from heat, hot surfaces, sparks, open d other ignition sources. No smoking. o not breathe mist or vapours. ash skin thoroughly after handling.
				P370 + P3	10 IF SWALLOWED: Immediately call a POISON doctor. NOT induce vomiting.

Hazardous components which must be listed on the label:

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclic, <2% aromatics hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics reaction mixture of ethylbenzene, m-xylene and p-xylene Hydrocarbons, C9 aromatics

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.



MOBIHEL ANTISILICONE CLEANER

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	27.11.2023	MAT000407597	Date of first issue: 27.11.2023
		ES/EN	

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclic, <2% aromatics	- 01-2119471843-32	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) Asp. Tox. 1; H304 Aquatic Chronic 3; H412	>= 50 - < 70
hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics	- 919-857-5 01-2119463258-33	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) Asp. Tox. 1; H304	>= 20 - < 30
reaction mixture of ethylbenzene, m-xylene and p-xylene	- 905-562-9 01-2119555267-33	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 Asp. Tox. 1; H304	>= 10 - < 20
Hydrocarbons, C9 aromatics	- 918-668-5 01-2119455851-35	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>= 10 - < 20
n-butyl acetate	123-86-4 204-658-1 607-025-00-1 01-2119485493-29	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) EUH066	>= 1 - < 10

according to Regulation (EC) No. 1907/2006



MOBIHEL ANTISILICONE CLEANER

Version 1.0	Revision Date: 27.11.2023	SDS Number: MAT000407597 ES/EN	 Date of last issue: - Date of first issue: 27.11.2023	

SECTION 4: First aid measures

4.1 Description of first aid measure	S
General advice :	Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Symptoms of poisoning may appear several hours later. Do not leave the victim unattended.
If inhaled :	Consult a physician after significant exposure. If unconscious, place in recovery position and seek medical advice.
In case of skin contact :	If skin irritation persists, call a physician. If on skin, rinse well with water. If on clothes, remove clothes.
In case of eye contact :	Immediately flush eye(s) with plenty of water. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed :	Keep respiratory tract clear. Do NOT induce vomiting. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.
4.2 Most important symptoms and e	effects, both acute and delayed
Risks :	May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure.
4.3 Indication of any immediate med	dical attention and special treatment needed
Treatment :	Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media	:	Alcohol-resistant foam
		Carbon dioxide (CO2)



MOBIHEL ANTISILICONE CLEANER

Vers 1.0	sion	Revision Date: 27.11.2023		Number: 000407597 N	Date of last issue: - Date of first issue: 27.11.2023
				Dry chemical	
	Unsuita media	ble extinguishing	:	High volume water je	t
5.2 \$	Special	hazards arising fr	om the	e substance or mixtu	re
	Specific fighting	c hazards during fire	9- :	Do not allow run-off f courses.	rom fire fighting to enter drains or water
	Hazard ucts	ous combustion pro	od- :	No hazardous combu	ustion products are known
5.3	Advice	for firefighters			
	Special for firefi	protective equipme	ent :	In the event of fire, w	ear self-contained breathing apparatus.
	Further	information	:	must not be discharg Fire residues and cor be disposed of in acc For safety reasons in rately in closed conta	ntaminated fire extinguishing water must cordance with local regulations. case of fire, cans should be stored sepa-

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures Personal precautions : Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition.

Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentra-
tions. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions	:	Prevent product from entering drains. Prevent further leakage or spillage if safe to do so.
		If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up	:	Contain spillage, and then collect with non-combustible ab-
		sorbent material, (e.g. sand, earth, diatomaceous earth, ver-
		miculite) and place in container for disposal according to local
		/ national regulations (see section 13).

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

according to Regulation (EC) No. 1907/2006



MOBIHEL ANTISILICONE CLEANER

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	27.11.2023	MAT000407597 ES/EN	Date of first issue: 27.11.2023

SECTION 7: Handling and storage

7.1 Precautions for safe handling	9	
Advice on safe handling	:	 Avoid formation of aerosol. Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.
Advice on protection against fire and explosion	:	Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.
Hygiene measures	:	When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
7.2 Conditions for safe storage, i	inc	luding any incompatibilities
Requirements for storage areas and containers	•	No smoking. Keep container tightly closed in a dry and well- ventilated place. Containers which are opened must be care- fully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.
Further information on stor- age stability	:	No decomposition if stored and applied as directed.
7.3 Specific end use(s)		
Specific use(s)	:	For further information, refer to the product technical data sheet.
		Consult the technical guidelines for the use of this sub- stance/mixture.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
reaction mixture of ethylbenzene, m- xylene and p- xylene	1330-20-7	VLA-ED	50 ppm 221 mg/m3	ES VLA

according to Regulation (EC) No. 1907/2006



MOBIHEL ANTISILICONE CLEANER

Version 1.0	Revision Date: 27.11.2023	SDS Number: MAT000407597 ES/EN	Date of last issue: - Date of first issue: 27.11.2023

	Further infor	mation: Skin			
		VLA-EC	100 ppm 442 mg/m3	ES VLA	
	Further infor	mation: Skin			
		TWA	50 ppm 221 mg/m3	2000/39/EC	
	Further infor skin, Indicati		e possibility of significant	uptake through the	
		STEL	100 ppm 442 mg/m3	2000/39/EC	
	Further infor skin, Indicati	information: Identifies the possibility of significant uptake through the dicative			
n-butyl acetate	123-86-4	VLA-ED	50 ppm 241 mg/m3	ES VLA	
		VLA-EC	150 ppm 723 mg/m3	ES VLA	
		STEL	150 ppm 723 mg/m3	2019/1831/E U	
	Further information: Indicative				
		TWA	50 ppm 241 mg/m3	2019/1831/E U	
	Further infor	mation: Indicative	· •		

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
reaction mixture of ethylbenzene, m-xylene and p-xylene	1330-20-7	methylhippuric acids: 1 g/g creati- nine (Urine)	End of workday	ES VLB

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health ef- fects	Value
hydrocarbons, C9- C10, n-alkanes, isoal- kanes, cyclic, <2% aromatics	Workers	Inhalation	Long-term systemic effects	871 mg/m3
	Consumers	Inhalation	Long-term systemic effects	185 mg/m3
	Workers	Dermal	Long-term systemic effects	208 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	125 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	125 mg/kg bw/day
hydrocarbons, C9- C11, n-alkanes, isoal- kanes, cyclic, <2% aromatics	Workers	Inhalation	Long-term systemic effects	1500 mg/m3
	Consumers	Inhalation	Long-term systemic effects	900 mg/m3
	Workers	Dermal	Long-term systemic	300 mg/kg

according to Regulation (EC) No. 1907/2006



MOBIHEL ANTISILICONE CLEANER

Version	
1.0	

Revision Date: 27.11.2023

SDS Number: MAT000407597 ES/EN Date of last issue: -Date of first issue: 27.11.2023

			effects	bw/day
	Consumers	Dermal	Long-term systemic effects	300 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	300 mg/kg bw/day
reaction mixture of ethylbenzene, m- xylene and p-xylene	Workers	Inhalation	Long-term systemic effects	77 mg/m3
	Consumers	Inhalation	Long-term local ef- fects	65,3 mg/m3
	Workers	Inhalation	Acute systemic ef- fects	442 mg/m3
	Workers	Inhalation	Acute local effects	289 mg/m3
	Consumers	Inhalation	Acute systemic ef- fects	260 mg/m3
	Workers	Inhalation	Long-term local ef- fects	221 mg/m3
	Consumers	Inhalation	Long-term systemic effects	14,8 mg/m3
	Consumers	Inhalation	Acute local effects	260 mg/m3
	Consumers	Dermal	Long-term systemic effects	108 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	16 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	180 mg/kg bw/day
Hydrocarbons, C9 aromatics	Workers	Inhalation	Long-term systemic effects	150 mg/m3
	Workers	Oral	Long-term systemic effects	150 mg/m3
	Consumers	Inhalation	Long-term exposure	32 mg/m3
	Workers	Dermal	Long-term systemic effects	25 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	11 mg/kg bw/day
n-butyl acetate	Workers	Inhalation	Acute systemic ef- fects	600 mg/m3
	Workers	Inhalation	Acute local effects	600 mg/m3
	Workers	Inhalation	Long-term systemic effects	48 mg/m3
	Workers	Inhalation	Long-term local ef- fects	300 mg/m3
	Consumers	Inhalation	Acute systemic ef- fects	300 mg/m3
	Consumers	Inhalation	Acute local effects	300 mg/m3
	Consumers	Inhalation	Long-term systemic effects	12 mg/m3
	Consumers	Inhalation	Long-term local ef- fects	35,7 mg/m3
	Consumers	Dermal	Long-term systemic effects	3,4 mg/kg bw/day
	Consumers	Dermal	Acute systemic ef-	6 mg/kg

according to Regulation (EC) No. 1907/2006



MOBIHEL ANTISILICONE CLEANER

VersionRevision Date:SDS Number:Date of las1.027.11.2023MAT000407597Date of firsES/ENES/ENDate of firs	st issue: - st issue: 27.11.2023
--	-------------------------------------

		fects	bw/day
Consumers	Oral	Long-term systemic effects	2 mg/kg bw/day
Consumers	Oral	Acute systemic ef- fects	2 mg/kg bw/day
Workers	Dermal	Long-term systemic effects	7 mg/kg bw/day
Workers	Dermal	Acute systemic ef- fects	11 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
reaction mixture of ethylbenzene,	Soil	2,31 mg/kg dry
m-xylene and p-xylene		weight (d.w.)
	Marine water	0,327 mg/l
	Fresh water	0,327 mg/l
	Marine sediment	12,46 mg/kg dry
		weight (d.w.)
	Fresh water sediment	12,46 mg/kg dry
		weight (d.w.)
	Sewage treatment plant	6,58 mg/l
	Intermittent use/release	0,327 mg/l
n-butyl acetate	Soil	0,0903 mg/kg dry
		weight (d.w.)
	Marine water	0,018 mg/l
	Fresh water	0,18 mg/l
	Marine sediment	0,0981 mg/kg dry
		weight (d.w.)
	Fresh water sediment	0,981 mg/kg dry
		weight (d.w.)
	Sewage treatment plant	35,6 mg/l
	Intermittent use/release	0,36 mg/l

8.2 Exposure controls

Personal protective equipment

Eye/face protection	:	Equipment should conform to EN 166 Eye wash bottle with pure water Tightly fitting safety goggles Wear face-shield and protective suit for abnormal processing problems.	
Hand protection			
Gloves	:	Nitrile rubber (> 0,1 mm; < 60 min); DIN EN374 Viton® (> 0,6 mm; < 240 min); DIN EN374 PE laminate (> 0,1 mm; < 240 min); DIN EN374	
Remarks	:	The suitability for a specific workplace should be discussed with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local condi-	

according to Regulation (EC) No. 1907/2006



MOBIHEL ANTISILICONE CLEANER

Version 1.0	Revision Date: 27.11.2023	SDS Number: MAT000407597 ES/EN	Date of last issue: - Date of first issue: 27.11.2023
Skin	and body protection	cuts, abrasion, and : Impervious clothin Choose body prot	the product is used, such as the danger of d the contact time. g ection according to the amount and con- angerous substance at the work place.
	Respiratory protection : Use res tilation i exposur		otection unless adequate local exhaust ven- or exposure assessment demonstrates that hin recommended exposure guidelines. conform to EN 14387 pe (A)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state Colour Odour Odour Threshold	: : :	liquid colourless solvent-like No data available
Melting point/freezing point	:	-78,0 °C (calculation method (principal components, lowest value))
Boiling point/boiling range	:	80 - 110 °C (calculation method (principal components, lowest value))
Flammability	:	Static-accumulating flammable liquid., Combustible Solids
Upper explosion limit / Upper flammability limit	:	7,5 %(V) (calculation method (principal components, highest value))
Lower explosion limit / Lower flammability limit	:	0,7 %(V) (calculation method (principal components, highest value))
Flash point	:	25 °C
Ignition temperature	:	425 °C (calculation method (principal components, highest value))
Decomposition temperature	:	No decomposition if used as directed. Hazardous decomposition products formed under fire condi- tions.
рН	:	Not applicable
Viscosity Viscosity, kinematic	:	< 20,5 mm2/s (40 °C)
Solubility(ies)		

according to Regulation (EC) No. 1907/2006

MOBIHEL ANTISILICONE CLEANER



Versio 1.0	on	Revision Date: 27.11.2023		00	lumber:)0407597	Date of last issue: - Date of first issue: 27.11.2023
		er solubility ıbility in other solve			immiscible, partly so No data available	bluble
	Partitio octanol	n coefficient: n- /water	:		log Pow: < 4 (calcula est value))	ation method (principal components, high-
١	Vapour	pressure	:	:	< 1.100 hPa (calcula est value)) (50 °C)	ation method (principal components, high-
F	Relativ	e density	:	:	0,90 (calculation me ue))	ethod (principal components, highest val-
[Density	1	:	:	0,785 g/cm3	
F	Relativ	e vapour density	:	:	4 (calculation metho	od (principal components, lowest value))
)ther ir Explosi	formation ves	:	:	Not applicable	
C	Oxidizii	ng properties	:	:	Sustains combustion	n
E	Evapor	ation rate	:	:	No data available	
١	VOC		:	:	(Directive 2004/42/E	EC)

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions Hazardous reactions : No decomposition if stored and applied as directed.				
		Vapours may form explosive mixture with air.		
10.4 Conditions to avoid Conditions to avoid :		Heat, flames and sparks.		
10.5 Incompatible materials Materials to avoid :		Incompatible with strong acids and bases.		

810 g/l



MOBIHEL ANTISILICONE CLEANER

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	27.11.2023	MAT000407597 ES/EN	Date of first issue: 27.11.2023

10.6 Hazardous decomposition products

Adequate ventilation is required. Heating can release vapours which can be ignited. Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Product:

Acute inhalation toxicity	:	Acute toxicity estimate: > 20 mg/l Exposure time: 4 h Test atmosphere: vapour Method: Calculation method
Acute dermal toxicity	:	Acute toxicity estimate: > 2.000 mg/kg

Method: Calculation method

Components:

reaction mixture of ethylbenzene, m-xylene and p-xylene: Acute oral toxicity : LD50 Oral (Rat): >= 8.700 mg/kg Acute inhalation toxicity : LC50 (Rat): 27,14 mg/l Test atmosphere: vapour Acute dermal toxicity : Assessment: The component/mixture is moderately toxic after single contact withskin.

Hydrocarbons, C9 aromatics:

Acute dermal toxicity	: LD50 (Rabbit): > 3.160 mg/kg	
n-butyl acetate: Acute oral toxicity	: LD50 Oral (Rat): >= 10.760 mg/kg	
Acute dermal toxicity	: LD50 (Rabbit): >= 5.000 mg/kg	
Skin corrosion/irritation		

Causes skin irritation.

Product:

Remarks	: May cause skin irritation in susceptible persons.	
---------	---	--

Components:

reaction mixture of ethylbenzene, m-xylene and p-xylene:

according to Regulation (EC) No. 1907/2006



MOBIHEL ANTISILICONE CLEANER

rsion	Revision Date: 27.11.2023	SDS Number: MAT000407597 ES/EN	Date of last issue: - Date of first issue: 27.11.2023	
Resul	t	: irritating		
	us eye damage/ey es serious eye irrita			
<u>Produ</u> Rema		: May cause irrev	versible eye damage.	
<u>Comp</u>	oonents:			
react i Resul		ylbenzene, m-xylene and : Eye irritation	d p-xylene:	
Resp	iratory or skin sen	sitisation		
-	sensitisation assified based on a	available information.		
•	iratory sensitisation assified based on a	on available information.		
Germ cell mutagenicity Not classified based on available information.				
	nogenicity assified based on a	available information.		
-	oductive toxicity assified based on a	available information.		
May c	- single exposure cause respiratory irr cause drowsiness o	itation.		
<u>Comp</u>	oonents:			
-	ocarbons, C9-C10, ssment	n-alkanes, isoalkanes, : May cause drov	cyclic, <2% aromatics: vsiness or dizziness.	
•	ocarbons, C9-C11, ssment	n-alkanes, isoalkanes, : May cause drov	cyclic, <2% aromatics: vsiness or dizziness.	
reacti	ion mixture of eth	ylbenzene, m-xylene an	d p-xylene:	
	ssment		piratory irritation.	
Hydro	ocarbons, C9 aron	natics:		
Asses	ssment	: May cause drov	vsiness or dizziness.	
Asses	ssment	: May cause resp	piratory irritation.	

according to Regulation (EC) No. 1907/2006



MOBIHEL ANTISILICONE CLEANER

Version 1.0	Revision Date: 27.11.2023	SDS Number: MAT000407597 ES/EN	Date of last issue: - Date of first issue: 27.11.2023
	ityl acetate: essment	: May cause drow	siness or dizziness.
	T - repeated exposic cause damage to org	ire gans through prolonged oi	repeated exposure.
<u>Com</u>	ponents:		
reac	tion mixture of ethy	lbenzene, m-xylene and	p-xylene:
Asse	essment	: May cause dama exposure.	age to organs through prolonged or repeated
-	iration toxicity be fatal if swallowed	and enters airways.	
<u>Com</u>	ponents:		
-	ocarbons, C9-C10, be fatal if swallowed	n-alkanes, isoalkanes, c and enters airways.	yclic, <2% aromatics:
-	ocarbons, C9-C11, be fatal if swallowed	n-alkanes, isoalkanes, c and enters airways.	yclic, <2% aromatics:
	tion mixture of ethy be fatal if swallowed	Ibenzene, m-xylene and and enters airways.	p-xylene:
•	rocarbons, C9 arom be fatal if swallowed		
11.2 Info	rmation on other ha	zards	
End	ocrine disrupting pr	operties	
	<u>luct:</u> essment	ered to have end REACH Article 5	nixture does not contain components consid- locrine disrupting properties according to 7(f) or Commission Delegated regulation or Commission Regulation (EU) 2018/605 at higher.
Furt	her information		
Proc	luct:		
Rem	arks	tiredness, nause	ubstantially above the TLV value may cause

according to Regulation (EC) No. 1907/2006



MOBIHEL ANTISILICONE CLEANER

Version 1.0	Revision Date: 27.11.2023	SDS Number: MAT000407597 ES/EN	Date of last issue: - Date of first issue: 27.11.2023

SECTION 12: Ecological information

12.1 Toxicity

Components:

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclic, <2% aromatics:				
Ecotoxicology Assessment Chronic aquatic toxicity :	:	Harmful to aquatic life with long lasting effects.		
reaction mixture of ethylbenzon Toxicity to fish	er :	ne, m-xylene and p-xylene: LC50 (Fish): >= 1 - 10 mg/l		
Toxicity to daphnia and other : aquatic invertebrates	:	LC50 (Daphnia (water flea)): >= 1 - 10 mg/l		
•	:	EC50 (Bacteria): >= 1 - 100 mg/l		
Hydrocarbons, C9 aromatics:				
Toxicity to fish :	:	LC50 (Fish): >= 9,2 mg/l Exposure time: 96 h		
		EC50 (Daphnia (water flea)): >= 3,2 mg/l Exposure time: 48 h		
Ecotoxicology Assessment Chronic aquatic toxicity :	:	Toxic to aquatic life with long lasting effects.		
n-butyl acetate:				
Toxicity to algae/aquatic : plants	:	NOEC (Desmodesmus subspicatus (green algae)): > 200 mg/l		
		EC50 (Desmodesmus subspicatus (green algae)): >= 647,7 mg/l Exposure time: 72 h		
Toxicity to microorganisms	:	IC50 (Tetrahymena pyriformis): 356 mg/l Exposure time: 40 h		

12.2 Persistence and degradability

Components:

Photodegradation	:	Decomposes rapidly in contact with light.
1 notodogradation	•	Beeenpeeee rapidity in contact manight

n-butyl acetate:

according to Regulation (EC) No. 1907/2006



MOBIHEL ANTISILICONE CLEANER

1.0	27.11.2023	SDS Number:Date of last issue: -MAT000407597Date of first issue: 27.11.2023ES/ENES/EN
Biode	gradability	 Result: Biodegradable Biodegradation: 83 % Exposure time: 28 d Method: OECD Test Guideline 301D
Stabili	ity in water	: Degradation half life: 78 d pH: 8 Hydrolyses slowly.
Photo	degradation	: Decomposes rapidly in contact with light.
12.3 Bioac	cumulative poten	al
<u>Comp</u>	oonents:	
reacti	on mixture of ethy	benzene, m-xylene and p-xylene:
Bioaco	cumulation	: Bioconcentration factor (BCF): 25,9 Bioaccumulation is unlikely.
	on coefficient: n- ol/water	: log Pow: 2,77 - 3,15
Hydro	ocarbons, C9 aron	itics:
	on coefficient: n- ol/water	: log Pow: < 4
n-but	yl acetate:	
Bioac	cumulation	: Bioconcentration factor (BCF): 15 Bioaccumulation is unlikely.
	on coefficient: n- ol/water	: log Pow: 1,81
12.4 Mobil	lity in soil	
<u>Comp</u>	oonents:	
reacti	on mixture of ethy	benzene, m-xylene and p-xylene:
	oution among enviro al compartments	 Koc: 537, log Koc: 2,73 Moderately mobile in soils The product evaporates from soil.
Stabili	ity in soil	: Dissipation time: 23 d Percentage dissipation: 50 % (DT50)
Hydro	ocarbons, C9 aron	itics:
Mobili	ty	: Medium: Air Content: 92,9 %
		: Medium: Water Content: 3,5 %
		: Medium: Soil Content: 1,9 %

according to Regulation (EC) No. 1907/2006



MOBIHEL ANTISILICONE CLEANER

Version 1.0	Revision Date: 27.11.2023		Number: 000407597 N	Date of last issue: - Date of first issue: 27.11.2023			
		:	Medium: Sediment Content: 1,8 %				
	oution among enviro Il compartments	n- :	Koc: 1,71 - 14,70 Mobile in soils				
			The product is insol	uble and floats on water.			
12.5 Resu	lts of PBT and vPv	'B asse	ssment				
<u>Produ</u> Asses	<u>ıct:</u> sment	:	to be either persiste	ture contains no components considered nt, bioaccumulative and toxic (PBT), or very bioaccumulative (vPvB) at levels of			
12.6 Endo	12.6 Endocrine disrupting properties						
<u>Produ</u> Asses	<u>ict:</u> sment	:	ered to have endocu REACH Article 57(f)	ure does not contain components consid- rine disrupting properties according to) or Commission Delegated regulation Commission Regulation (EU) 2018/605 at gher.			
12.7 Other	adverse effects						
<u>Prodι</u> Additio mation	onal ecological infor	~ :	unprofessional hand	azard cannot be excluded in the event of dling or disposal. ife with long lasting effects.			
SECTION 13: Disposal considerations							
13.1 Waste	e treatment metho	ds					
Produ	ct	:	courses or the soil. Do not contaminate cal or used containe	not be allowed to enter drains, water ponds, waterways or ditches with chemi- er. waste management company.			
Oranta			F				

Contaminated packaging	:	Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.
Waste Code	:	08 00 00, WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS),

according to Regulation (EC) No. 1907/2006



MOBIHEL ANTISILICONE CLEANER

Version 1.0	Revision Date: 27.11.2023	SDS Number: MAT000407597 ES/EN	Date of last issue: - Date of first issue: 27.11.2023
		08 01 00, wastes nish 08 01 11, waste p or other hazardou 15 00 00, WASTE CLOTHS, FILTER CLOTHING NOT 15 01 00, packagi packaging waste) 15 01 10, packagi by hazardoussubs HP3, Flammable HP4, Irritant - skir	E PACKAGING; ABSORBENTS, WIPING & MATERIALS AND PROTECTIVE OTHERWISE SPECIFIED ing (including separately collected municipal ing containing residues of or contaminated

SECTION 14: Transport information

14.1 UN number or ID number

ADN	: UN 1263
ADR	: UN 1263
RID	: UN 1263
IMDG	: UN 1263
ΙΑΤΑ	: UN 1263

14.2 UN proper shipping name

ADN	:	PAINT RELATED MATERIAL
ADR	:	PAINT RELATED MATERIAL
RID	:	PAINT RELATED MATERIAL
IMDG	:	PAINT RELATED MATERIAL
ΙΑΤΑ	:	Paint related material

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADN	: 3	
ADR	: 3	
RID	: 3	
IMDG	: 3	
ΙΑΤΑ	: 3	
14.4 Packing group		
ADN		

according to Regulation (EC) No. 1907/2006



MOBIHEL ANTISILICONE CLEANER

Vers 1.0	sion	Revision Date: 27.11.2023		Number: 000407597 N	Date of last issue: - Date of first issue: 27.11.2023
	Classifi	g group ication Code I Identification Numb	: Der :	III F1 30 3	
	Classifi Hazard Labels	g group cation Code I Identification Numb restriction code	: ber : :	III F1 30 3 (D/E)	
	Classifi	g group ication Code I Identification Numb	: Der :	III F1 30 3	
	IMDG Packing Labels EmS C	g group ode	:	III 3 F-E, <u>S-E</u>	
	aircraft Packing	g instruction (cargo	:	366 Y344 III Flammable Liquids	
	Packing ger airc Packing	g instruction (LQ) g group	n- : : :	355 Y344 III Flammable Liquids	
14.5	5 Enviro	nmental hazards			
	ADN Enviror	nmentally hazardous	s :	no	
	ADR Enviror	nmentally hazardous	s :	no	
	RID Enviror	nmentally hazardous	s :	no	
	IMDG Marine	pollutant	:	no	
14.6	Specia	Il precautions for u	user		

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the uppackaged material as it is described within this Safety Date

based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.



MOBIHEL ANTISILICONE CLEANER

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	27.11.2023	MAT000407597	Date of first issue: 27.11.2023
		ES/EN	

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mix- ture				
REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	lo	Conditions of restriction for the fol- owing entries should be considered: lumber on list 75, 3		
	ta	you intend to use this product as attoo ink, please contact your ven-		
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	: N	lot applicable		
Regulation (EC) No 1005/2009 on substances that de- plete the ozone layer	: N	lot applicable		
Regulation (EU) 2019/1021 on persistent organic pollu- tants (recast)	: N	lot applicable		
Regulation (EC) No 649/2012 of the European Parlia- ment and the Council concerning the export and import of dangerous chemicals	: N	lot applicable		
REACH - List of substances subject to authorisation (Annex XIV)	: N	lot applicable		
Seveso III: Directive 2012/18/EU of the Euro-P5c pean Parliament and of the Council on the control of major-accident hazards involving dangerous substances.	FLAM	MABLE LIQUIDS		
Volatile organic compounds : Directive 2004/42/EC Volatile organic comp		(VOC) content: 810 g/l		
Other regulations:				
Take note of Directive 92/85/EEC regarding maternity pr where applicable. Take note of Directive 94/33/EC on the protection of you regulations, where applicable.		-		
15.2 Chemical safety assessment				

15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

SECTION 16: Other information

Full text of H-Statements

H226	:	Flammable liquid and vapour.
H304	:	May be fatal if swallowed and enters airways.

according to Regulation (EC) No. 1907/2006



MOBIHEL ANTISILICONE CLEANER

Version 1.0	Revision Date: 27.11.2023		lumber: 00407597	Date of last issue: - Date of first issue: 27.11.2023
H312 H315 H319 H332 H335 H336 H373 H411 H412 EUH0	66		exposure. Toxic to aquatic life v Harmful to aquatic lif	ry irritation.
Full text of other abbreviations				
Acute Aquati Asp. T Eye In Flam. Skin Ir STOT STOT 2000/3	Tox. c Chronic ox. -it. Liq. rit. RE SE 39/EC 1831/EU		Specific target organ Europe. Commission list of indicative occu Europe. Commission fifth list of indicative Spain. Environmenta - Table 1: Occupatio	toxicity - repeated exposure toxicity - single exposure Directive 2000/39/EC establishing a first pational exposure limit values Directive 2019/1831/EU establishing a occupational exposure limit values al Limits for exposure to Chemical agents
2000/3 2000/3 2019/ ⁻ 2019/- ES VL	89/EC / TWA 89/EC / STEL 831/EU / TWA 831/EU / STEL A / VLA-ED A / VLA-EC	:	 Biological Exposure Values Limit Value - eight hours Short term exposure limit Limit Value - eight hours Short term exposure limit Environmental Daily Limit Value Environmental Short Term Value 	

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA -European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test popula-



Classification procedure:

MOBIHEL ANTISILICONE CLEANER

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	27.11.2023	MAT000407597 ES/EN	Date of first issue: 27.11.2023

tion; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI -Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

olassification of the mixture.		olassification procedure.
Flam. Liq. 3	H226	Based on product data or assessment
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
STOT SE 3	H335	Calculation method
STOT SE 3	H336	Calculation method
STOT RE 2	H373	Calculation method
Asp. Tox. 1	H304	Calculation method
Aquatic Chronic 3	H412	Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.