

# SAFETY DATA SHEET

## MOBIHEL Antisilicone cleaner low VOC



|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: -           |
| 1.0     | 28.11.2023     | MAT000407597 | Date of first issue: 28.11.2023 |
|         |                | IL/EN        |                                 |

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : MOBIHEL Antisilicone cleaner low VOC

Product code : 407597

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Coatings and paints, thinners, paint removers

Recommended restrictions on use : Reserved for industrial and professional use.

#### 1.3 Details of the supplier of the safety data sheet

Company : Helios TBLUS d.o.o.  
Količevo 65  
1230 Domžale  
Slovenia

Telephone Company : 386 (1) 722 4383

Telefax Company : 386 (1) 722 4310

Responsible/issuing person : 386 (1) 722 4383  
productsafety@helios.si

#### 1.4 Emergency telephone number

Ambulance (972) 101

Israel Poison Information Center +972 4 854 19 00

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

|  |  |
|--|--|
| Flammable liquids, Category 3  | H226: Flammable liquid and vapour.                                       |
| Skin irritation, Category 2  | H315: Causes skin irritation.  |
| Eye irritation, Category 2   | H319: Causes serious eye irritation.                                     |
| Specific target organ toxicity - single exposure, Category 3, Respiratory system     | H335: May cause respiratory irritation.                                  |
| Specific target organ toxicity - single exposure, Category 3, Central nervous system | H336: May cause drowsiness or dizziness.                                 |
| Specific target organ toxicity - repeated exposure, Category 2                       | H373: May cause damage to organs through prolonged or repeated exposure. |

# SAFETY DATA SHEET

## MOBIHEL Antisilicone cleaner low VOC



Version  
1.0

Revision Date:  
28.11.2023

SDS Number:  
MAT000407597  
IL/EN

Date of last issue: -  
Date of first issue: 28.11.2023

Aspiration hazard, Category 1

H304: May be fatal if swallowed and enters airways.

Long-term (chronic) aquatic hazard, Category 3

H412: Harmful to aquatic life with long lasting effects.

### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements :  
H226 Flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements :

#### Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P260 Do not breathe mist or vapours.  
P264 Wash skin thoroughly after handling.

#### Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.  
P331 Do NOT induce vomiting.  
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclic, <2% aromatics  
hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics  
reaction mixture of ethylbenzene, m-xylene and p-xylene  
Hydrocarbons, C9 aromatics

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

# SAFETY DATA SHEET

## MOBIHEL Antisilicone cleaner low VOC



Version  
1.0

Revision Date:  
28.11.2023

SDS Number:  
MAT000407597  
IL/EN

Date of last issue: -  
Date of first issue: 28.11.2023

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

##### Components

| Chemical name  | CAS-No.<br>EC-No.<br>Index-No.<br>Registration number         | Classification   | Concentration<br>(% w/w) |
|--|---|--|--------------------------|
| hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclic, <2% aromatics | -<br><br>01-2119471843-32                                     | Flam. Liq. 3; H226<br>STOT SE 3; H336<br>(Central nervous system)<br>Asp. Tox. 1; H304<br>Aquatic Chronic 3; H412  | >= 50 - < 70             |
| hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics | -<br><br>919-857-5<br>01-2119463258-33                        | Flam. Liq. 3; H226<br>STOT SE 3; H336<br>(Central nervous system)<br>Asp. Tox. 1; H304   | >= 20 - < 30             |
| reaction mixture of ethylbenzene, m-xylene and p-xylene            | -<br><br>905-562-9<br>01-2119555267-33                        | Flam. Liq. 3; H226<br>Acute Tox. 4; H332<br>Acute Tox. 4; H312<br>Skin Irrit. 2; H315<br>Eye Irrit. 2; H319<br>STOT SE 3; H335<br>(Respiratory system)<br>STOT RE 2; H373<br>Asp. Tox. 1; H304 | >= 10 - < 20             |
| Hydrocarbons, C9 aromatics   | -<br><br>918-668-5<br>01-2119455851-35                        | Flam. Liq. 3; H226<br>STOT SE 3; H336<br>(Central nervous system)<br>STOT SE 3; H335<br>(Respiratory system)<br>Asp. Tox. 1; H304<br>Aquatic Chronic 2; H411                                   | >= 10 - < 20             |
| n-butyl acetate  | 123-86-4<br><br>204-658-1<br>607-025-00-1<br>01-2119485493-29 | Flam. Liq. 3; H226<br>STOT SE 3; H336<br>(Central nervous system)  | >= 1 - < 10              |

# SAFETY DATA SHEET

## MOBIHEL Antisilicone cleaner low VOC



|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: -           |
| 1.0     | 28.11.2023     | MAT000407597 | Date of first issue: 28.11.2023 |
|         |                | IL/EN        |                                 |

---

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- |                         |  |
|-------------------------|--|
| General advice          | : Move out of dangerous area.<br>Show this safety data sheet to the doctor in attendance.<br>Symptoms of poisoning may appear several hours later.<br>Do not leave the victim unattended.  |
| If inhaled              | : Consult a physician after significant exposure.<br>If unconscious, place in recovery position and seek medical advice.   |
| In case of skin contact | : If skin irritation persists, call a physician.<br>If on skin, rinse well with water.<br>If on clothes, remove clothes.   |
| In case of eye contact  | : Immediately flush eye(s) with plenty of water.<br>Remove contact lenses.<br>Protect unharmed eye.<br>Keep eye wide open while rinsing.<br>If eye irritation persists, consult a specialist.  |
| If swallowed            | : Keep respiratory tract clear.<br>Do NOT induce vomiting.<br>Do not give milk or alcoholic beverages.<br>Never give anything by mouth to an unconscious person.<br>If symptoms persist, call a physician.<br>Take victim immediately to hospital. |

#### 4.2 Most important symptoms and effects, both acute and delayed

- |       |   |
|-------|---|
| Risks | : May be fatal if swallowed and enters airways.<br>Causes skin irritation.<br>Causes serious eye irritation.<br>May cause respiratory irritation.<br>May cause drowsiness or dizziness.<br>May cause damage to organs through prolonged or repeated exposure. |
|-------|---|

#### 4.3 Indication of any immediate medical attention and special treatment needed

- |           |                          |
|-----------|--------------------------|
| Treatment | : Treat symptomatically. |
|-----------|--------------------------|

---

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

- |                              |   |
|------------------------------|---|
| Suitable extinguishing media | : Alcohol-resistant foam<br>Carbon dioxide (CO <sub>2</sub> )<br>Dry chemical |
| Unsuitable extinguishing     | : High volume water jet   |

# SAFETY DATA SHEET

## MOBIHEL Antisilicone cleaner low VOC



|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: -           |
| 1.0     | 28.11.2023     | MAT000407597 | Date of first issue: 28.11.2023 |
|         |                | IL/EN        |                                 |

---

media

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : No hazardous combustion products are known

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Ensure adequate ventilation.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

### 6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

# SAFETY DATA SHEET

## MOBIHEL Antisilicone cleaner low VOC



Version  
1.0

Revision Date:  
28.11.2023

SDS Number:  
MAT000407597  
IL/EN

Date of last issue: -  
Date of first issue: 28.11.2023

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

- Advice on safe handling : Avoid formation of aerosol.  
Do not breathe vapours/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Open drum carefully as content may be under pressure.  
Dispose of rinse water in accordance with local and national regulations.
- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.
- Hygiene measures : When using do not eat or drink. When using do not smoke.  
Wash hands before breaks and at the end of workday.

#### 7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage stability : No decomposition if stored and applied as directed.

#### 7.3 Specific end use(s)

- Specific use(s) : For further information, refer to the product technical data sheet.
- Consult the technical guidelines for the use of this substance/mixture.

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

##### Occupational Exposure Limits

| Components  | CAS-No.   | Value type (Form of exposure) | Control parameters | Basis  |
|---|-----------|-------------------------------|--------------------|--------|
| reaction mixture of ethylbenzene, m-xylene and p-xylene | 1330-20-7 | TLV-TWA                       | 100 ppm            | IL OEL |

## SAFETY DATA SHEET

## MOBIHEL Antisilicone cleaner low VOC

Version  
1.0Revision Date:  
28.11.2023SDS Number:  
MAT000407597  
IL/ENDate of last issue: -  
Date of first issue: 28.11.2023

|                 |  |       |                                  |                  |
|-----------------|--|-------|----------------------------------|------------------|
|                 |  | TLV-C | 150 mg/m <sup>3</sup>            | IL OEL           |
|                 |  | TWA   | 50 ppm<br>221 mg/m <sup>3</sup>  | 2000/39/EC       |
|                 | Further information: Identifies the possibility of significant uptake through the skin, Indicative |       |                                  |                  |
|                 |  | STEL  | 100 ppm<br>442 mg/m <sup>3</sup> | 2000/39/EC       |
|                 | Further information: Identifies the possibility of significant uptake through the skin, Indicative |       |                                  |                  |
|                 |  | TWA   | 20 ppm                           | ACGIH            |
| n-butyl acetate | 123-86-4   | STEL  | 150 ppm<br>723 mg/m <sup>3</sup> | 2019/1831/E<br>U |
|                 | Further information: Indicative  |       |                                  |                  |
|                 |  | TWA   | 50 ppm<br>241 mg/m <sup>3</sup>  | 2019/1831/E<br>U |
|                 | Further information: Indicative  |       |                                  |                  |
|                 |  | TWA   | 50 ppm                           | ACGIH            |
|                 |  | STEL  | 150 ppm                          | ACGIH            |

**Biological occupational exposure limits**

| Substance name  | CAS-No.   | Control parameters                               | Sampling time  | Basis     |
|---|-----------|--|--|-----------|
| reaction mixture of ethylbenzene, m-xylene and p-xylene | 1330-20-7 | methyl hippuric acid: 1.5 g/g creatinine (Urine) |  | IL BEI    |
|   |           | Methylhippuric acids: 1.5 g/g creatinine (Urine) | End of shift (As soon as possible after exposure ceases) | ACGIH BEI |

**Derived No Effect Level (DNEL)****according to Regulation (EC) No. 1907/2006:**

| Substance name   | End Use   | Exposure routes | Potential health effects   | Value                  |
|--|-----------|-----------------|----------------------------|------------------------|
| hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclic, <2% aromatics | Workers   | Inhalation      | Long-term systemic effects | 871 mg/m <sup>3</sup>  |
|  | Consumers | Inhalation      | Long-term systemic effects | 185 mg/m <sup>3</sup>  |
|  | Workers   | Dermal          | Long-term systemic effects | 208 mg/kg bw/day       |
|  | Consumers | Dermal          | Long-term systemic effects | 125 mg/kg bw/day       |
|  | Consumers | Oral            | Long-term systemic effects | 125 mg/kg bw/day       |
| hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics | Workers   | Inhalation      | Long-term systemic effects | 1500 mg/m <sup>3</sup> |
|  | Consumers | Inhalation      | Long-term systemic effects | 900 mg/m <sup>3</sup>  |

# SAFETY DATA SHEET

## MOBIHEL Antisilicone cleaner low VOC



Version  
1.0

Revision Date:  
28.11.2023

SDS Number:  
MAT000407597  
IL/EN

Date of last issue: -  
Date of first issue: 28.11.2023

|   |           |            |                            |                  |
|---|-----------|------------|----------------------------|------------------|
|   | Workers   | Dermal     | Long-term systemic effects | 300 mg/kg bw/day |
|   | Consumers | Dermal     | Long-term systemic effects | 300 mg/kg bw/day |
|   | Consumers | Oral       | Long-term systemic effects | 300 mg/kg bw/day |
| reaction mixture of ethylbenzene, m-xylene and p-xylene | Workers   | Inhalation | Long-term systemic effects | 77 mg/m3         |
|   | Consumers | Inhalation | Long-term local effects    | 65.3 mg/m3       |
|   | Workers   | Inhalation | Acute systemic effects     | 442 mg/m3        |
|   | Workers   | Inhalation | Acute local effects        | 289 mg/m3        |
|   | Consumers | Inhalation | Acute systemic effects     | 260 mg/m3        |
|   | Workers   | Inhalation | Long-term local effects    | 221 mg/m3        |
|   | Consumers | Inhalation | Long-term systemic effects | 14.8 mg/m3       |
|   | Consumers | Inhalation | Acute local effects        | 260 mg/m3        |
|   | Consumers | Dermal     | Long-term systemic effects | 108 mg/kg bw/day |
|   | Consumers | Oral       | Long-term systemic effects | 16 mg/kg bw/day  |
|   | Workers   | Dermal     | Long-term systemic effects | 180 mg/kg bw/day |
| Hydrocarbons, C9 aromatics                              | Workers   | Inhalation | Long-term systemic effects | 150 mg/m3        |
|   | Workers   | Oral       | Long-term systemic effects | 150 mg/m3        |
|   | Consumers | Inhalation | Long-term exposure         | 32 mg/m3         |
|   | Workers   | Dermal     | Long-term systemic effects | 25 mg/kg bw/day  |
|   | Consumers | Dermal     | Long-term systemic effects | 11 mg/kg bw/day  |
| n-butyl acetate   | Workers   | Inhalation | Acute systemic effects     | 600 mg/m3        |
|   | Workers   | Inhalation | Acute local effects        | 600 mg/m3        |
|   | Workers   | Inhalation | Long-term systemic effects | 48 mg/m3         |
|   | Workers   | Inhalation | Long-term local effects    | 300 mg/m3        |
|   | Consumers | Inhalation | Acute systemic effects     | 300 mg/m3        |
|   | Consumers | Inhalation | Acute local effects        | 300 mg/m3        |
|   | Consumers | Inhalation | Long-term systemic effects | 12 mg/m3         |
|   | Consumers | Inhalation | Long-term local effects    | 35.7 mg/m3       |
|   | Consumers | Dermal     | Long-term systemic effects | 3.4 mg/kg bw/day |
|   | Consumers | Dermal     | Acute systemic ef-         | 6 mg/kg          |



# SAFETY DATA SHEET

## MOBIHEL Antisilicone cleaner low VOC



Version  
1.0

Revision Date:  
28.11.2023

SDS Number:  
MAT000407597  
IL/EN

Date of last issue: -  
Date of first issue: 28.11.2023

|  |           |        | fects                      | bw/day          |
|--|-----------|--------|----------------------------|-----------------|
|  | Consumers | Oral   | Long-term systemic effects | 2 mg/kg bw/day  |
|  | Consumers | Oral   | Acute systemic effects     | 2 mg/kg bw/day  |
|  | Workers   | Dermal | Long-term systemic effects | 7 mg/kg bw/day  |
|  | Workers   | Dermal | Acute systemic effects     | 11 mg/kg bw/day |

### Predicted No Effect Concentration (PNEC)

according to Regulation (EC) No. 1907/2006:

| Substance name  | Environmental Compartment | Value                          |
|---|---------------------------|--------------------------------|
| reaction mixture of ethylbenzene, m-xylene and p-xylene | Soil                      | 2.31 mg/kg dry weight (d.w.)   |
|   | Marine water              | 0.327 mg/l                     |
|   | Fresh water               | 0.327 mg/l                     |
|   | Marine sediment           | 12.46 mg/kg dry weight (d.w.)  |
|   | Fresh water sediment      | 12.46 mg/kg dry weight (d.w.)  |
| n-butyl acetate   | Sewage treatment plant    | 6.58 mg/l                      |
|   | Intermittent use/release  | 0.327 mg/l                     |
|   | Soil                      | 0.0903 mg/kg dry weight (d.w.) |
|   | Marine water              | 0.018 mg/l                     |
|   | Fresh water               | 0.18 mg/l                      |
|   | Marine sediment           | 0.0981 mg/kg dry weight (d.w.) |
|   | Fresh water sediment      | 0.981 mg/kg dry weight (d.w.)  |
|   | Sewage treatment plant    | 35.6 mg/l                      |
|   | Intermittent use/release  | 0.36 mg/l                      |

## 8.2 Exposure controls

### Personal protective equipment

Eye/face protection : Equipment should conform to EN 166  
Eye wash bottle with pure water  
Tightly fitting safety goggles  
Wear face-shield and protective suit for abnormal processing problems.

Hand protection

Gloves : Nitrile rubber (> 0,1 mm; < 60 min); DIN EN374 |  
Viton® (> 0,6 mm; < 240 min); DIN EN374 |  
PE laminate (> 0,1 mm; < 240 min); DIN EN374 |

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.  
Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the

# SAFETY DATA SHEET

## MOBIHEL Antisilicone cleaner low VOC



|         |                |                       |                                 |
|---------|----------------|-----------------------|---------------------------------|
| Version | Revision Date: | SDS Number:           | Date of last issue: -           |
| 1.0     | 28.11.2023     | MAT000407597<br>IL/EN | Date of first issue: 28.11.2023 |

|                          |   |  |
|--------------------------|---|--|
| Skin and body protection | : | gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.<br>Impervious clothing<br>Choose body protection according to the amount and concentration of the dangerous substance at the work place. |
| Respiratory protection   | : | Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.  |
| Filter type              | : | Organic vapour type (A)  |

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

|  |   |   |
|--|---|---|
| Appearance                                       | : | liquid  |
| Colour   | : | colourless  |
| Odour  | : | solvent-like  |
| Odour Threshold                                  | : | No data available   |
| pH   | : | Not applicable  |
| Melting point/freezing point                     | : | -78.0 °C<br>(calculation method (principal components, lowest value))             |
| Boiling point/boiling range                      | : | 80 - 110 °C (calculation method (principal components, lowest value))             |
| Flash point                                      | : | 25 °C   |
| Evaporation rate                                 | : | No data available   |
| Flammability (solid, gas)                        | : | Static-accumulating flammable liquid., Combustible Solids                         |
| Upper explosion limit / Upper flammability limit | : | 7.5 %(V) (calculation method (principal components, highest value))               |
| Lower explosion limit / Lower flammability limit | : | 0.7 %(V) (calculation method (principal components, highest value))               |
| Vapour pressure                                  | : | < 1,100 hPa (calculation method (principal components, highest value))<br>(50 °C) |
| Relative vapour density                          | : | 4 (calculation method (principal components, highest value))                      |
| Relative density                                 | : | 0.90 (calculation method (principal components, highest value))                   |
| Density  | : | 0.785 g/cm <sup>3</sup>   |

# SAFETY DATA SHEET

## MOBIHEL Antisilicone cleaner low VOC



|         |                |                       |                                 |
|---------|----------------|-----------------------|---------------------------------|
| Version | Revision Date: | SDS Number:           | Date of last issue: -           |
| 1.0     | 28.11.2023     | MAT000407597<br>IL/EN | Date of first issue: 28.11.2023 |

---

|  |   |
|--|---|
| Solubility(ies)                        |   |
| Water solubility                       | : immiscible, partly soluble  |
| Solubility in other solvents           | : No data available   |
| Partition coefficient: n-octanol/water | : log Pow: < 4 (calculation method (principal components, highest value))                                 |
| Auto-ignition temperature              | : 425 °C (calculation method (principal components, highest value))                                       |
| Decomposition temperature              | : No decomposition if used as directed.<br>Hazardous decomposition products formed under fire conditions. |
| Viscosity                              |   |
| Viscosity, kinematic                   | : < 20.5 mm <sup>2</sup> /s (40 °C)   |
| Explosive properties                   | : Not applicable  |
| Oxidizing properties                   | : Sustains combustion   |

### 9.2 Other information

|                   |                                     |
|-------------------|-------------------------------------|
| No data available |                                     |
| VOC               | : (Directive 2004/42/EC)<br>810 g/l |

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

|                     |   |
|---------------------|---|
| Hazardous reactions | : No decomposition if stored and applied as directed. |
|---------------------|---|

Vapours may form explosive mixture with air.

### 10.4 Conditions to avoid

|                     |                            |
|---------------------|----------------------------|
| Conditions to avoid | : Heat, flames and sparks. |
|---------------------|----------------------------|

### 10.5 Incompatible materials

|                    |   |
|--------------------|---|
| Materials to avoid | : Incompatible with strong acids and bases. |
|--------------------|---|

# SAFETY DATA SHEET

## MOBIHEL Antisilicone cleaner low VOC



|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: -           |
| 1.0     | 28.11.2023     | MAT000407597 | Date of first issue: 28.11.2023 |
|         |                | IL/EN        |                                 |

### 10.6 Hazardous decomposition products

Adequate ventilation is required.  
Heating can release vapours which can be ignited.  
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

Not classified based on available information.

#### Product:

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg  
Method: Calculation method

#### Components:

##### reaction mixture of ethylbenzene, m-xylene and p-xylene:

Acute oral toxicity : LD50 Oral (Rat): >= 8,700 mg/kg

Acute inhalation toxicity : LC50 (Rat): 27.14 mg/l  
Test atmosphere: vapour

Acute dermal toxicity : Assessment: The component/mixture is moderately toxic after single contact with skin.

##### Hydrocarbons, C9 aromatics:

Acute dermal toxicity : LD50 (Rabbit): > 3,160 mg/kg

##### n-butyl acetate:

Acute oral toxicity : LD50 Oral (Rat): >= 10,760 mg/kg

Acute dermal toxicity : LD50 (Rabbit): >= 5,000 mg/kg

#### Skin corrosion/irritation

Causes skin irritation.

#### Product:

Remarks : May cause skin irritation in susceptible persons.

#### Components:

##### reaction mixture of ethylbenzene, m-xylene and p-xylene:

Result : irritating

# SAFETY DATA SHEET

## MOBIHEL Antisilicone cleaner low VOC



Version  
1.0

Revision Date:  
28.11.2023

SDS Number:  
MAT000407597  
IL/EN

Date of last issue: -  
Date of first issue: 28.11.2023

---

### Serious eye damage/eye irritation

Causes serious eye irritation.

#### Product:

Remarks : May cause irreversible eye damage.

#### Components:

##### reaction mixture of ethylbenzene, m-xylene and p-xylene:

Result : Eye irritation

### Respiratory or skin sensitisation

#### Skin sensitisation

Not classified based on available information.

#### Respiratory sensitisation

Not classified based on available information.

#### Germ cell mutagenicity

Not classified based on available information.

#### Carcinogenicity

Not classified based on available information.

#### Reproductive toxicity

Not classified based on available information.

#### STOT - single exposure

May cause respiratory irritation.

May cause drowsiness or dizziness.

#### Components:

##### hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclic, <2% aromatics:

Assessment : May cause drowsiness or dizziness.

##### hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics:

Assessment : May cause drowsiness or dizziness.

##### reaction mixture of ethylbenzene, m-xylene and p-xylene:

Assessment : May cause respiratory irritation.

##### Hydrocarbons, C9 aromatics:

Assessment : May cause drowsiness or dizziness.

Assessment : May cause respiratory irritation.

##### n-butyl acetate:

Assessment : May cause drowsiness or dizziness.

# SAFETY DATA SHEET

## MOBIHEL Antisilicone cleaner low VOC



Version  
1.0

Revision Date:  
28.11.2023

SDS Number:  
MAT000407597  
IL/EN

Date of last issue: -  
Date of first issue: 28.11.2023

### STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

#### Components:

##### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Assessment : May cause damage to organs through prolonged or repeated exposure.

### Aspiration toxicity

May be fatal if swallowed and enters airways.

#### Components:

##### **hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclic, <2% aromatics:**

May be fatal if swallowed and enters airways.

##### **hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics:**

May be fatal if swallowed and enters airways.

##### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

May be fatal if swallowed and enters airways.

##### **Hydrocarbons, C9 aromatics:**

May be fatal if swallowed and enters airways.

### Further information

#### Product:

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.  
Concentrations substantially above the TLV value may cause narcotic effects.  
Solvents may degrease the skin.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

##### **hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclic, <2% aromatics:**

##### **Ecotoxicology Assessment**

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

##### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Toxicity to fish : LC50 (Fish): >= 1 - 10 mg/l

# SAFETY DATA SHEET

## MOBIHEL Antisilicone cleaner low VOC



|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: -           |
| 1.0     | 28.11.2023     | MAT000407597 | Date of first issue: 28.11.2023 |
|         |                | IL/EN        |                                 |

---

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)):  $\geq 1 - 10$  mg/l  
Toxicity to microorganisms : EC50 (Bacteria):  $\geq 1 - 100$  mg/l

### Hydrocarbons, C9 aromatics:

Toxicity to fish : LC50 (Fish):  $\geq 9.2$  mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)):  $\geq 3.2$  mg/l  
Exposure time: 48 h

### Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

### n-butyl acetate:

Toxicity to algae/aquatic plants : NOEC (Desmodesmus subspicatus (green algae)):  $> 200$  mg/l  
EC50 (Desmodesmus subspicatus (green algae)):  $\geq 647.7$  mg/l  
Exposure time: 72 h

Toxicity to microorganisms : IC50 (Tetrahymena pyriformis): 356 mg/l  
Exposure time: 40 h

## 12.2 Persistence and degradability

### Components:

#### reaction mixture of ethylbenzene, m-xylene and p-xylene:

Biodegradability : Remarks: Readily biodegradable.

Photodegradation : Remarks: Decomposes rapidly in contact with light.

### n-butyl acetate:

Biodegradability : Result: Biodegradable  
Biodegradation: 83 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301D

Stability in water : Degradation half life: 78 d  
pH: 8  
Remarks: Hydrolyses slowly.

Photodegradation : Remarks: Decomposes rapidly in contact with light.

# SAFETY DATA SHEET

## MOBIHEL Antisilicone cleaner low VOC



|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: -           |
| 1.0     | 28.11.2023     | MAT000407597 | Date of first issue: 28.11.2023 |
|         |                | IL/EN        |                                 |

---

### 12.3 Bioaccumulative potential

#### Components:

##### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Bioaccumulation : Bioconcentration factor (BCF): 25.9  
Remarks: Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water : log Pow: 2.77 - 3.15

##### **Hydrocarbons, C9 aromatics:**

Partition coefficient: n-octanol/water : log Pow: < 4

##### **n-butyl acetate:**

Bioaccumulation : Bioconcentration factor (BCF): 15  
Remarks: Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water : log Pow: 1.81

### 12.4 Mobility in soil

#### Components:

##### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Distribution among environmental compartments : Koc: 537, log Koc: 2.73  
Remarks: Moderately mobile in soils  
The product evaporates from soil.

Stability in soil : Dissipation time: 23 d  
Percentage dissipation: 50 % (DT50)

##### **Hydrocarbons, C9 aromatics:**

Mobility : Medium: Air  
Content: 92.9 %

: Medium: Water  
Content: 3.5 %

: Medium: Soil  
Content: 1.9 %

: Medium: Sediment  
Content: 1.8 %

Distribution among environmental compartments : Koc: 1.71 - 14.70  
Remarks: Mobile in soils

Remarks: The product is insoluble and floats on water.

### 12.5 Results of PBT and vPvB assessment

#### Product:



# SAFETY DATA SHEET

## MOBIHEL Antisilicone cleaner low VOC



|         |                |                       |                                 |
|---------|----------------|-----------------------|---------------------------------|
| Version | Revision Date: | SDS Number:           | Date of last issue: -           |
| 1.0     | 28.11.2023     | MAT000407597<br>IL/EN | Date of first issue: 28.11.2023 |

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Other adverse effects

#### **Product:**

Endocrine disrupting potential : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Harmful to aquatic life with long lasting effects.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

## SECTION 14: Transport information

### 14.1 UN number

|      |           |
|------|-----------|
| ADN  | : UN 1263 |
| ADR  | : UN 1263 |
| RID  | : UN 1263 |
| IMDG | : UN 1263 |
| IATA | : UN 1263 |

### 14.2 UN proper shipping name

|     |                          |
|-----|--------------------------|
| ADN | : PAINT RELATED MATERIAL |
| ADR | : PAINT RELATED MATERIAL |
| RID | : PAINT RELATED MATERIAL |

# SAFETY DATA SHEET

## MOBIHEL Antisilicone cleaner low VOC



|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: -           |
| 1.0     | 28.11.2023     | MAT000407597 | Date of first issue: 28.11.2023 |
|         |                | IL/EN        |                                 |

---

**IMDG** : PAINT RELATED MATERIAL

**IATA** : Paint related material

### 14.3 Transport hazard class(es)

**ADN** : 3

**ADR** : 3

**RID** : 3

**IMDG** : 3

**IATA** : 3

### 14.4 Packing group

#### **ADN**

Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3

#### **ADR**

Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3  
Tunnel restriction code : (D/E)

#### **RID**

Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3

#### **IMDG**

Packing group : III  
Labels : 3  
EmS Code : F-E, S-E

#### **IATA (Cargo)**

Packing instruction (cargo aircraft) : 366  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable Liquids

#### **IATA (Passenger)**

Packing instruction (passenger aircraft) : 355  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable Liquids

### 14.5 Environmental hazards

#### **ADN**

Environmentally hazardous : no

# SAFETY DATA SHEET

## MOBIHEL Antisilicone cleaner low VOC



|         |                |                       |                                 |
|---------|----------------|-----------------------|---------------------------------|
| Version | Revision Date: | SDS Number:           | Date of last issue: -           |
| 1.0     | 28.11.2023     | MAT000407597<br>IL/EN | Date of first issue: 28.11.2023 |

---

### ADR

Environmentally hazardous : no

### RID

Environmentally hazardous : no

### IMDG

Marine pollutant : no

### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Volatile organic compounds : Directive 2004/42/EC  
Volatile organic compounds (VOC) content: 810 g/l

### 15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

---

## SECTION 16: Other information

### Full text of H-Statements

|      |  |
|------|--|
| H226 | : Flammable liquid and vapour.                                       |
| H304 | : May be fatal if swallowed and enters airways.                      |
| H312 | : Harmful in contact with skin.                                      |
| H315 | : Causes skin irritation.  |
| H319 | : Causes serious eye irritation.                                     |
| H332 | : Harmful if inhaled.  |
| H335 | : May cause respiratory irritation.                                  |
| H336 | : May cause drowsiness or dizziness.                                 |
| H373 | : May cause damage to organs through prolonged or repeated exposure. |
| H411 | : Toxic to aquatic life with long lasting effects.                   |
| H412 | : Harmful to aquatic life with long lasting effects.                 |

### Full text of other abbreviations

|                 |                                      |
|-----------------|--------------------------------------|
| Acute Tox.      | : Acute toxicity                     |
| Aquatic Chronic | : Long-term (chronic) aquatic hazard |
| Asp. Tox.       | : Aspiration hazard                  |
| Eye Irrit.      | : Eye irritation                     |
| Flam. Liq.      | : Flammable liquids                  |
| Skin Irrit.     | : Skin irritation                    |

# SAFETY DATA SHEET

## MOBIHEL Antisilicone cleaner low VOC



|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: -           |
| 1.0     | 28.11.2023     | MAT000407597 | Date of first issue: 28.11.2023 |
|         |                | IL/EN        |                                 |

|                     |  |
|---------------------|--|
| STOT RE             | : Specific target organ toxicity - repeated exposure   |
| STOT SE             | : Specific target organ toxicity - single exposure   |
| 2000/39/EC          | : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values   |
| 2019/1831/EU        | : Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values |
| ACGIH               | : USA. ACGIH Threshold Limit Values (TLV)  |
| ACGIH BEI           | : ACGIH - Biological Exposure Indices (BEI)  |
| IL BEI              | : Israel. Safety at Work Regulations - Annex III Biological Exposure Indices   |
| IL OEL              | : Israel. Safety at Work Regulations (Environmental monitoring and biological monitoring of workers)                   |
| 2000/39/EC / TWA    | : Limit Value - eight hours  |
| 2000/39/EC / STEL   | : Short term exposure limit  |
| 2019/1831/EU / TWA  | : Limit Value - eight hours  |
| 2019/1831/EU / STEL | : Short term exposure limit  |
| ACGIH / TWA         | : 8-hour, time-weighted average  |
| ACGIH / STEL        | : Short-term exposure limit  |
| IL OEL / TLV-TWA    | : Threshold Limit Value - Time Weighted (TLV-TWA)  |
| IL OEL / TLV-C      | : Threshold Limit Value - Ceiling (TLV-C)  |

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

# SAFETY DATA SHEET

## MOBIHEL Antisilicone cleaner low VOC



Version  
1.0

Revision Date:  
28.11.2023

SDS Number:  
MAT000407597  
IL/EN

Date of last issue: -  
Date of first issue: 28.11.2023

### Further information

#### Classification of the mixture:

|                   |      |
|-------------------|------|
| Flam. Liq. 3      | H226 |
| Skin Irrit. 2     | H315 |
| Eye Irrit. 2      | H319 |
| STOT SE 3         | H335 |
| STOT SE 3         | H336 |
| STOT RE 2         | H373 |
| Asp. Tox. 1       | H304 |
| Aquatic Chronic 3 | H412 |

#### Classification procedure:

|                                     |
|-------------------------------------|
| Based on product data or assessment |
| Calculation method                  |
| Calculation method                  |
| Calculation method                  |
| Calculation method                  |
| Calculation method                  |
| Calculation method                  |
| Calculation method                  |

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

IL / EN