

# SAFETY DATA SHEET

## MOBIHEL 2K HARDENER 7750



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	28.11.2023	MAT000479012 IL/EN	Date of first issue: 28.11.2023

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : MOBIHEL 2K HARDENER 7750

Product code : 47901203

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-  
stance/Mixture : Coatings and paints, thinners, paint removers

Recommended restrictions  
on use : Reserved for industrial and professional use.

#### 1.3 Details of the supplier of the safety data sheet

Company : Helios TBLUS d.o.o.  
Količevo 65  
1230 Domžale  
Slovenia

Telephone Company : 386 (1) 722 4383

Telefax Company : 386 (1) 722 4310

Responsible/issuing person : 386 (1) 722 4383  
productsafety@helios.si

#### 1.4 Emergency telephone number

Ambulance (972) 101

Israel Poison Information Center +972 4 854 19 00

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

# SAFETY DATA SHEET

## MOBIHEL 2K HARDENER 7750



Version  
1.0

Revision Date:  
28.11.2023

SDS Number:  
MAT000479012  
IL/EN

Date of last issue: -  
Date of first issue: 28.11.2023

Hazard pictograms :



Signal word : Warning

Hazard statements :  
H226 Flammable liquid and vapour.  
H317 May cause an allergic skin reaction.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.

Supplemental Hazard Statements : EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements :  
**Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P261 Avoid breathing mist or vapours.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

**Response:**

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

Hexamethylene-di-isocyanate, polymer  
n-butyl acetate  
isobutyl acetate  
reaction mixture of ethylbenzene, m-xylene and p-xylene

**Additional Labelling**

EUH204 Contains isocyanates. May produce an allergic reaction.

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

**Components**

Chemical name	CAS-No. EC-No.	Classification	Concentration (% w/w)
---------------	-------------------	----------------	--------------------------

# SAFETY DATA SHEET

## MOBIHEL 2K HARDENER 7750



Version  
1.0

Revision Date:  
28.11.2023

SDS Number:  
MAT000479012  
IL/EN

Date of last issue: -  
Date of first issue: 28.11.2023

	Index-No. Registration number		
Hexamethylene diisocyanate, oligomers	28182-81-2 500-060-2 01-2119485796-17	Acute Tox. 4; H332 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system)	>= 30 - < 50
n-butyl acetate	123-86-4 204-658-1 607-025-00-1 01-2119485493-29	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system)	>= 30 - < 50
isobutyl acetate	110-19-0 203-745-1 607-026-00-7 01-2119488971-22	Flam. Liq. 2; H225 STOT SE 3; H336 (Central nervous system)	>= 10 - < 20
reaction mixture of ethylbenzene, m-xylene and p-xylene	- 905-562-9 01-2119555267-33	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 Asp. Tox. 1; H304	>= 1 - < 10
2-methoxy-1-methylethyl acetate	108-65-6 203-603-9 607-195-00-7 01-2119475791-29	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system)	>= 1 - < 10
solvent naphtha (petroleum), light aromatic	64742-95-6 265-199-0 649-356-00-4 01-2119455851-35	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>= 1 - < 2.5

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.

# SAFETY DATA SHEET

## MOBIHEL 2K HARDENER 7750



Version 1.0	Revision Date: 28.11.2023	SDS Number: MAT000479012 IL/EN	Date of last issue: - Date of first issue: 28.11.2023
----------------	------------------------------	--------------------------------------	--

---

- If inhaled : Consult a physician after significant exposure.  
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If skin irritation persists, call a physician.  
If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Flush eyes with water as a precaution.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.

### 4.2 Most important symptoms and effects, both acute and delayed

- Risks : May cause an allergic skin reaction.  
May cause respiratory irritation.  
May cause drowsiness or dizziness.  
Repeated exposure may cause skin dryness or cracking.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.
- 

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

- Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : No hazardous combustion products are known

### 5.3 Advice for firefighters

- Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

# SAFETY DATA SHEET

## MOBIHEL 2K HARDENER 7750



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	28.11.2023	MAT000479012 IL/EN	Date of first issue: 28.11.2023

---

for firefighters

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.

---

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

#### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

#### 6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

---

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol.  
Do not breathe vapours/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Open drum carefully as content may be under pressure.  
Dispose of rinse water in accordance with local and national regulations.

# SAFETY DATA SHEET

## MOBIHEL 2K HARDENER 7750



Version 1.0      Revision Date: 28.11.2023      SDS Number: MAT000479012 IL/EN      Date of last issue: -  
Date of first issue: 28.11.2023

- Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.
- Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage conditions : Protect from moisture.
- Further information on storage stability : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

- Specific use(s) : For further information, refer to the product technical data sheet.
- Consult the technical guidelines for the use of this substance/mixture.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Hexamethylene-diisocyanate, polymer	28182-81-2	TLV-TWA	0.005 ppm (Isocyanates)	IL OEL
		TLV-STEL	0.02 ppm (Isocyanates)	IL OEL
n-butyl acetate	123-86-4	STEL	150 ppm 723 mg/m <sup>3</sup>	2019/1831/EU
	Further information: Indicative			
		TWA	50 ppm 241 mg/m <sup>3</sup>	2019/1831/EU
	Further information: Indicative			
		TWA	50 ppm	ACGIH
		STEL	150 ppm	ACGIH

# SAFETY DATA SHEET

## MOBIHEL 2K HARDENER 7750



Version  
1.0

Revision Date:  
28.11.2023

SDS Number:  
MAT000479012  
IL/EN

Date of last issue: -  
Date of first issue: 28.11.2023

isobutyl acetate	110-19-0	TWA	50 ppm 241 mg/m <sup>3</sup>	2019/1831/E U
Further information: Indicative				
		STEL	150 ppm 723 mg/m <sup>3</sup>	2019/1831/E U
Further information: Indicative				
		TWA	50 ppm	ACGIH
		STEL	150 ppm	ACGIH
reaction mixture of ethylbenzene, m-xylene and p-xylene	1330-20-7	TLV-TWA	100 ppm	IL OEL
		TLV-C	150 mg/m <sup>3</sup>	IL OEL
		TWA	50 ppm 221 mg/m <sup>3</sup>	2000/39/EC
Further information: Identifies the possibility of significant uptake through the skin, Indicative				
		STEL	100 ppm 442 mg/m <sup>3</sup>	2000/39/EC
Further information: Identifies the possibility of significant uptake through the skin, Indicative				
		TWA	20 ppm	ACGIH
2-methoxy-1-methylethyl acetate	108-65-6	STEL	100 ppm 550 mg/m <sup>3</sup>	2000/39/EC
Further information: Identifies the possibility of significant uptake through the skin, Indicative				
		TWA	50 ppm 275 mg/m <sup>3</sup>	2000/39/EC
Further information: Identifies the possibility of significant uptake through the skin, Indicative				

### Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
reaction mixture of ethylbenzene, m-xylene and p-xylene	1330-20-7	methyl hippuric acid: 1.5 g/g creatinine (Urine)		IL BEI
		Methylhippuric acids: 1.5 g/g creatinine (Urine)	End of shift (As soon as possible after exposure ceases)	ACGIH BEI

### Derived No Effect Level (DNEL)

according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Hexamethylene-diisocyanate, polymer	Workers	Inhalation	Long-term local effects	0.5 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term systemic effects	1 mg/m <sup>3</sup>
n-butyl acetate	Workers	Inhalation	Acute systemic ef-	600 mg/m <sup>3</sup>

# SAFETY DATA SHEET

## MOBIHEL 2K HARDENER 7750



Version  
1.0

Revision Date:  
28.11.2023

SDS Number:  
MAT000479012  
IL/EN

Date of last issue: -  
Date of first issue: 28.11.2023

			fects	
	Workers	Inhalation	Acute local effects	600 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term systemic effects	48 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	300 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute systemic effects	300 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute local effects	300 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term systemic effects	12 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local effects	35.7 mg/m <sup>3</sup>
	Consumers	Dermal	Long-term systemic effects	3.4 mg/kg bw/day
	Consumers	Dermal	Acute systemic effects	6 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	2 mg/kg bw/day
	Consumers	Oral	Acute systemic effects	2 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	7 mg/kg bw/day
	Workers	Dermal	Acute systemic effects	11 mg/kg bw/day
isobutyl acetate	Workers	Inhalation	Long-term systemic effects	300 mg/m <sup>3</sup>
	Workers	Inhalation	Acute systemic effects	600 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	300 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	600 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term systemic effects	35.7 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local effects	35.7 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute local effects	300 mg/m <sup>3</sup>
	Workers	Dermal	Long-term systemic effects	10 mg/kg bw/day
	Consumers	Oral	Acute systemic effects	5 mg/kg bw/day
	Workers	Dermal	Acute systemic effects	10 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	5 mg/kg bw/day
	Consumers	Dermal	Acute systemic effects	5 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	5 mg/kg bw/day
reaction mixture of ethylbenzene, m-xylene and p-xylene	Workers	Inhalation	Long-term systemic effects	77 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local ef-	65.3 mg/m <sup>3</sup>



# SAFETY DATA SHEET

## MOBIHEL 2K HARDENER 7750



Version  
1.0

Revision Date:  
28.11.2023

SDS Number:  
MAT000479012  
IL/EN

Date of last issue: -  
Date of first issue: 28.11.2023

			fects	
	Workers	Inhalation	Acute systemic effects	442 mg/m3
	Workers	Inhalation	Acute local effects	289 mg/m3
	Consumers	Inhalation	Acute systemic effects	260 mg/m3
	Workers	Inhalation	Long-term local effects	221 mg/m3
	Consumers	Inhalation	Long-term systemic effects	14.8 mg/m3
	Consumers	Inhalation	Acute local effects	260 mg/m3
	Consumers	Dermal	Long-term systemic effects	108 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	16 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	180 mg/kg bw/day
2-methoxy-1-methylethyl acetate	Workers	Inhalation	Long-term systemic effects	275 mg/m3
	Workers	Inhalation	Acute local effects	550 mg/m3
	Consumers	Inhalation	Long-term systemic effects	33 mg/m3
	Consumers	Inhalation	Long-term local effects	33 mg/m3
	Workers	Dermal	Long-term systemic effects	796 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	320 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	36 mg/kg bw/day
ethyl 3-ethoxypropionate	Workers	Inhalation	Long-term systemic effects	610 mg/m3
	Workers	Inhalation	Long-term local effects	610 mg/m3
	Consumers	Inhalation	Long-term systemic effects	72.6 mg/m3
	Consumers	Inhalation	Long-term local effects	72.6 mg/m3
	Workers	Dermal	Long-term local effects	102 mg/cm2
	Workers	Dermal	Long-term systemic effects	102 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	24.2 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	1.2 mg/kg bw/day
Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified	Workers	Inhalation	Long-term systemic effects	150 mg/m3
	Consumers	Inhalation	Long-term systemic effects	32 mg/m3
	Consumers	Dermal	Long-term systemic	11 mg/kg

# SAFETY DATA SHEET

## MOBIHEL 2K HARDENER 7750



Version  
1.0

Revision Date:  
28.11.2023

SDS Number:  
MAT000479012  
IL/EN

Date of last issue: -  
Date of first issue: 28.11.2023

			effects	bw/day
	Workers	Dermal	Long-term systemic effects	25 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	11 mg/kg bw/day

### Predicted No Effect Concentration (PNEC)

according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Hexamethylene-di-isocyanate, polymer	Soil	505 mg/kg dry weight (d.w.)
	Marine water	0.01 mg/l
	Fresh water	0.1 mg/l
	Marine sediment	253 mg/kg dry weight (d.w.)
	Fresh water sediment	2530 mg/kg dry weight (d.w.)
	Sewage treatment plant	100 mg/l
n-butyl acetate	Intermittent use/release	1 mg/l
	Soil	0.0903 mg/kg dry weight (d.w.)
	Marine water	0.018 mg/l
	Fresh water	0.18 mg/l
	Marine sediment	0.0981 mg/kg dry weight (d.w.)
	Fresh water sediment	0.981 mg/kg dry weight (d.w.)
isobutyl acetate	Sewage treatment plant	35.6 mg/l
	Intermittent use/release	0.36 mg/l
	Soil	0.0755 mg/kg dry weight (d.w.)
	Marine water	0.017 mg/l
	Fresh water	0.17 mg/l
	Marine sediment	0.0877 mg/kg dry weight (d.w.)
reaction mixture of ethylbenzene, m-xylene and p-xylene	Fresh water sediment	0.877 mg/kg dry weight (d.w.)
	Sewage treatment plant	200 mg/l
	Intermittent use/release	0.34 mg/l
	Soil	2.31 mg/kg dry weight (d.w.)
	Marine water	0.327 mg/l
	Fresh water	0.327 mg/l
2-methoxy-1-methylethyl acetate	Marine sediment	12.46 mg/kg dry weight (d.w.)
	Fresh water sediment	12.46 mg/kg dry weight (d.w.)
	Sewage treatment plant	6.58 mg/l
	Intermittent use/release	0.327 mg/l
	Soil	0.29 mg/kg dry weight (d.w.)
	Marine water	0.0635 mg/l

# SAFETY DATA SHEET

## MOBIHEL 2K HARDENER 7750



Version  
1.0

Revision Date:  
28.11.2023

SDS Number:  
MAT000479012  
IL/EN

Date of last issue: -  
Date of first issue: 28.11.2023

	Fresh water	0.635 mg/l
	Marine sediment	0.329 mg/kg dry weight (d.w.)
	Fresh water sediment	3.29 mg/kg dry weight (d.w.)
	Sewage treatment plant	100 mg/l
	Intermittent use/release	0.00635 mg/l
ethyl 3-ethoxypropionate	Soil	0.048 mg/kg dry weight (d.w.)
	Marine water	0.00609 mg/l
	Fresh water	0.0609 mg/l
	Marine sediment	0.0419 mg/kg dry weight (d.w.)
	Fresh water sediment	0.419 mg/kg dry weight (d.w.)
	Sewage treatment plant	50 mg/l
	Intermittent use/release	0.609 mg/l

### 8.2 Exposure controls

#### Personal protective equipment

Eye/face protection : Equipment should conform to EN 166  
Eye wash bottle with pure water  
Tightly fitting safety goggles

Hand protection

Gloves : Viton® (> 0,6 mm; < 240 min); DIN EN374 |  
PE laminate (> 0,1 mm; < 240 min); DIN EN374 |

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.  
Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

Skin and body protection : Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Organic vapour type (A)

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Appearance : liquid  
Colour : colourless  
Odour : solvent-like  
Odour Threshold : No data available

# SAFETY DATA SHEET

## MOBIHEL 2K HARDENER 7750



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	28.11.2023	MAT000479012 IL/EN	Date of first issue: 28.11.2023

---

pH	:	Not applicable
Melting point/freezing point	:	-98.8 °C (calculation method (principal components, lowest value))
Boiling point/boiling range	:	117 °C (calculation method (principal components, lowest value))
Flash point	:	31 °C
Flammability (solid, gas)	:	Static-accumulating flammable liquid., Combustible Solids
Upper explosion limit / Upper flammability limit	:	10.5 %(V) (calculation method (principal components, highest value))
Lower explosion limit / Lower flammability limit	:	1.1 %(V) (calculation method (principal components, highest value))
Relative vapour density	:	No data available
Relative density	:	No data available
Density	:	0.971 g/cm <sup>3</sup>
Solubility(ies)	:	
Water solubility	:	partly miscible
Solubility in other solvents	:	Description: miscible with most organic solvents
Partition coefficient: n-octanol/water	:	log Pow: 2.77 - 3.15 (calculation method (principal components, highest value))
Auto-ignition temperature	:	315 °C (calculation method (principal components, highest value))
Decomposition temperature	:	No decomposition if stored and applied as directed. Hazardous decomposition products formed under fire conditions.
Viscosity	:	
Viscosity, kinematic	:	> 20.5 mm <sup>2</sup> /s (40 °C)
Explosive properties	:	Not applicable
Oxidizing properties	:	Sustains combustion

### 9.2 Other information

No data available

# SAFETY DATA SHEET

## MOBIHEL 2K HARDENER 7750



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	28.11.2023	MAT000479012 IL/EN	Date of first issue: 28.11.2023

---

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

No decomposition if stored and applied as directed.

#### 10.2 Chemical stability

No decomposition if stored and applied as directed.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

#### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

#### 10.5 Incompatible materials

Materials to avoid : Incompatible with strong acids and bases.

#### 10.6 Hazardous decomposition products

Adequate ventilation is required.

Heating can release vapours which can be ignited.

Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

---

### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

##### Acute toxicity

Not classified based on available information.

##### Product:

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg  
Method: Calculation method

##### Components:

##### **Hexamethylene-di-isocyanate, polymer:**

Acute inhalation toxicity : Assessment: The component/mixture is moderately toxic after short term inhalation.

##### **n-butyl acetate:**

Acute oral toxicity : LD50 Oral (Rat): >= 10,760 mg/kg

# SAFETY DATA SHEET

## MOBIHEL 2K HARDENER 7750



Version 1.0      Revision Date: 28.11.2023      SDS Number: MAT000479012 IL/EN      Date of last issue: -  
Date of first issue: 28.11.2023

---

Acute dermal toxicity : LD50 (Rabbit):  $\geq$  5,000 mg/kg

**reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Acute oral toxicity : LD50 Oral (Rat):  $\geq$  8,700 mg/kg

Acute inhalation toxicity : LC50 (Rat): 27.14 mg/l  
Test atmosphere: vapour

Acute dermal toxicity : Assessment: The component/mixture is moderately toxic after single contact with skin.

**2-methoxy-1-methylethyl acetate:**

Acute oral toxicity : LD50 Oral (Rat):  $> >$  2,000 mg/kg

Acute inhalation toxicity : LC50 (Rat):  $>$  5 mg/l  
Test atmosphere: vapour

LC0 (Rat): 2000 ppm  
Exposure time: 3 h

Acute dermal toxicity : LD50 (Rabbit):  $> >$  2,000 mg/kg

**Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Acute oral toxicity : LD50 Oral (Rat):  $>$  2,000 mg/kg

Acute inhalation toxicity : LC50 (Rat):  $>$  5 mg/l  
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit):  $>$  2,000 mg/kg

**Skin corrosion/irritation**

Repeated exposure may cause skin dryness or cracking.

**Product:**

Remarks : May cause skin irritation and/or dermatitis.

**Components:**

**reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Result : irritating

**Serious eye damage/eye irritation**

Not classified based on available information.

**Product:**

Remarks : Vapours may cause irritation to the eyes, respiratory system and the skin.

# SAFETY DATA SHEET

## MOBIHEL 2K HARDENER 7750



Version  
1.0

Revision Date:  
28.11.2023

SDS Number:  
MAT000479012  
IL/EN

Date of last issue: -  
Date of first issue: 28.11.2023

---

### Components:

#### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Result : Eye irritation

### **Respiratory or skin sensitisation**

#### **Skin sensitisation**

May cause an allergic skin reaction.

#### **Respiratory sensitisation**

Not classified based on available information.

### Product:

Remarks : Causes sensitisation.

### Components:

#### **Hexamethylene-di-isocyanate, polymer:**

Result : Probability or evidence of skin sensitisation in humans

### **Germ cell mutagenicity**

Not classified based on available information.

### Components:

#### **Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Germ cell mutagenicity- Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

### **Carcinogenicity**

Not classified based on available information.

### Components:

#### **Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Carcinogenicity - Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

### **Reproductive toxicity**

Not classified based on available information.

### **STOT - single exposure**

May cause respiratory irritation.

May cause drowsiness or dizziness.

### Components:

#### **Hexamethylene-di-isocyanate, polymer:**

Assessment : May cause respiratory irritation.

# SAFETY DATA SHEET

## MOBIHEL 2K HARDENER 7750



Version  
1.0

Revision Date:  
28.11.2023

SDS Number:  
MAT000479012  
IL/EN

Date of last issue: -  
Date of first issue: 28.11.2023

---

### **n-butyl acetate:**

Assessment : May cause drowsiness or dizziness.

### **isobutyl acetate:**

Assessment : May cause drowsiness or dizziness.

### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Assessment : May cause respiratory irritation.

### **2-methoxy-1-methylethyl acetate:**

Assessment : May cause drowsiness or dizziness.

### **Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Assessment : May cause drowsiness or dizziness.

Assessment : May cause respiratory irritation.

### **STOT - repeated exposure**

Not classified based on available information.

### **Components:**

### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Assessment : May cause damage to organs through prolonged or repeated exposure.

### **Aspiration toxicity**

Not classified based on available information.

### **Components:**

### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

May be fatal if swallowed and enters airways.

### **Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

May be fatal if swallowed and enters airways.

### **Further information**

### **Product:**

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.  
Concentrations substantially above the TLV value may cause narcotic effects.  
Solvents may degrease the skin.



# SAFETY DATA SHEET

## MOBIHEL 2K HARDENER 7750



Version 1.0      Revision Date: 28.11.2023      SDS Number: MAT000479012 IL/EN      Date of last issue: -  
Date of first issue: 28.11.2023

---

### SECTION 12: Ecological information

#### 12.1 Toxicity

##### Components:

##### **n-butyl acetate:**

Toxicity to algae/aquatic plants : NOEC (Desmodesmus subspicatus (green algae)): > 200 mg/l  
EC50 (Desmodesmus subspicatus (green algae)): >= 647.7 mg/l  
Exposure time: 72 h

Toxicity to microorganisms : IC50 (Tetrahymena pyriformis): 356 mg/l  
Exposure time: 40 h

##### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Toxicity to fish : LC50 (Fish): >= 1 - 10 mg/l

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)): >= 1 - 10 mg/l

Toxicity to microorganisms : EC50 (Bacteria): >= 1 - 100 mg/l

##### **2-methoxy-1-methylethyl acetate:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 130 mg/l  
Exposure time: 96 h

NOEC : 100 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : LC50 : 408 mg/l  
Exposure time: 48 h

Toxicity to fish (Chronic toxicity) : EC10: 47.5 mg/l

##### **Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Toxicity to fish : LC50 (Fish): > 1 - 10 mg/l

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)): > 1 - 10 mg/l

Toxicity to microorganisms : EC50 (Bacteria): > 1 - 10 mg/l

##### **Ecotoxicology Assessment**

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

#### 12.2 Persistence and degradability

##### Components:

##### **n-butyl acetate:**

# SAFETY DATA SHEET

## MOBIHEL 2K HARDENER 7750



Version 1.0      Revision Date: 28.11.2023      SDS Number: MAT000479012 IL/EN      Date of last issue: -  
Date of first issue: 28.11.2023

---

Biodegradability : Result: Biodegradable  
Biodegradation: 83 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301D

Stability in water : Degradation half life: 78 d  
pH: 8  
Remarks: Hydrolyses slowly.

Photodegradation : Remarks: Decomposes rapidly in contact with light.

### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Biodegradability : Remarks: Readily biodegradable.

Photodegradation : Remarks: Decomposes rapidly in contact with light.

### **2-methoxy-1-methylethyl acetate:**

Biodegradability : Remarks: Readily biodegradable.

## 12.3 Bioaccumulative potential

### Components:

#### **n-butyl acetate:**

Bioaccumulation : Bioconcentration factor (BCF): 15  
Remarks: Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water : log Pow: 1.81

#### **isobutyl acetate:**

Partition coefficient: n-octanol/water : log Pow: 1.72

### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Bioaccumulation : Bioconcentration factor (BCF): 25.9  
Remarks: Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water : log Pow: 2.77 - 3.15

### **2-methoxy-1-methylethyl acetate:**

Partition coefficient: n-octanol/water : log Pow: 1.2 (20 °C)  
pH: 6.8

## 12.4 Mobility in soil

### Components:

### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Distribution among environmental compartments : Koc: 537, log Koc: 2.73  
Remarks: Moderately mobile in soils

# SAFETY DATA SHEET

## MOBIHEL 2K HARDENER 7750



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	28.11.2023	MAT000479012 IL/EN	Date of first issue: 28.11.2023

---

The product evaporates from soil.

Stability in soil : Dissipation time: 23 d  
Percentage dissipation: 50 % (DT50)

### 12.5 Results of PBT and vPvB assessment

**Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Other adverse effects

**Product:**

Endocrine disrupting potential : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Additional ecological information : No data available

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

---

## SECTION 14: Transport information

### 14.1 UN number

ADN : UN 1263  
ADR : UN 1263  
RID : UN 1263  
IMDG : UN 1263  
IATA : UN 1263

### 14.2 UN proper shipping name

# SAFETY DATA SHEET

## MOBIHEL 2K HARDENER 7750



Version 1.0  
Revision Date: 28.11.2023  
SDS Number: MAT000479012  
IL/EN

Date of last issue: -  
Date of first issue: 28.11.2023

**ADN** : PAINT  
**ADR** : PAINT  
**RID** : PAINT  
**IMDG** : PAINT  
**IATA** : Paint

### 14.3 Transport hazard class(es)

**ADN** : 3  
**ADR** : 3  
**RID** : 3  
**IMDG** : 3  
**IATA** : 3

### 14.4 Packing group

**ADN**  
Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3

**ADR**  
Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3  
Tunnel restriction code : (D/E)

**RID**  
Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3

**IMDG**  
Packing group : III  
Labels : 3  
EmS Code : F-E, S-E

**IATA (Cargo)**  
Packing instruction (cargo aircraft) : 366  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable Liquids

**IATA (Passenger)**  
Packing instruction (passenger aircraft) : 355  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable Liquids

# SAFETY DATA SHEET

## MOBIHEL 2K HARDENER 7750



Version  
1.0

Revision Date:  
28.11.2023

SDS Number:  
MAT000479012  
IL/EN

Date of last issue: -  
Date of first issue: 28.11.2023

### 14.5 Environmental hazards

#### ADN

Environmentally hazardous : no

#### ADR

Environmentally hazardous : no

#### RID

Environmentally hazardous : no

#### IMDG

Marine pollutant : no

### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

### 15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

## SECTION 16: Other information

### Full text of H-Statements

H225 : Highly flammable liquid and vapour.  
H226 : Flammable liquid and vapour.  
H304 : May be fatal if swallowed and enters airways.  
H312 : Harmful in contact with skin.  
H315 : Causes skin irritation.  
H317 : May cause an allergic skin reaction.  
H319 : Causes serious eye irritation.  
H332 : Harmful if inhaled.  
H335 : May cause respiratory irritation.  
H336 : May cause drowsiness or dizziness.  
H373 : May cause damage to organs through prolonged or repeated exposure.  
H411 : Toxic to aquatic life with long lasting effects.

### Full text of other abbreviations

Acute Tox. : Acute toxicity  
Aquatic Chronic : Long-term (chronic) aquatic hazard  
Asp. Tox. : Aspiration hazard  
Eye Irrit. : Eye irritation

# SAFETY DATA SHEET

## MOBIHEL 2K HARDENER 7750



Version 1.0      Revision Date: 28.11.2023      SDS Number: MAT000479012 IL/EN      Date of last issue: -      Date of first issue: 28.11.2023

Flam. Liq.	:	Flammable liquids
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitisation
STOT RE	:	Specific target organ toxicity - repeated exposure
STOT SE	:	Specific target organ toxicity - single exposure
2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2019/1831/EU	:	Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values
ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	:	ACGIH - Biological Exposure Indices (BEI)
IL BEI	:	Israel. Safety at Work Regulations - Annex III Biological Exposure Indices
IL OEL	:	Israel. Safety at Work Regulations (Environmental monitoring and biological monitoring of workers)
2000/39/EC / TWA	:	Limit Value - eight hours
2000/39/EC / STEL	:	Short term exposure limit
2019/1831/EU / TWA	:	Limit Value - eight hours
2019/1831/EU / STEL	:	Short term exposure limit
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
IL OEL / TLV-TWA	:	Threshold Limit Value - Time Weighted (TLV-TWA)
IL OEL / TLV-STEL	:	Threshold Limit Value - Short Term (TLV-STEL)
IL OEL / TLV-C	:	Threshold Limit Value - Ceiling (TLV-C)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECl -

# SAFETY DATA SHEET

## MOBIHEL 2K HARDENER 7750



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	28.11.2023	MAT000479012	Date of first issue: 28.11.2023
		IL/EN	

---

Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

### Further information

#### Classification of the mixture:

Flam. Liq. 3	H226
Skin Sens. 1	H317
STOT SE 3	H336
STOT SE 3	H335

#### Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

IL / EN