

SAFETY DATA SHEET

TESSAROL primer for iron



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	28.11.2023	MAT0GA00_006 IL/EN	Date of first issue: 28.11.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : TESSAROL primer for iron

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-
stance/Mixture : Building and construction work
Roller application or brushing, Non industrial spraying
Coatings and paints, thinners, paint removers

Recommended restrictions : Professional and consumer use of coatings
on use

1.3 Details of the supplier of the safety data sheet

Company : Helios TBLUS d.o.o.
Količevo 65
1230 Domžale
Slovenia

Telephone Company : 386 (1) 722 4383

Telefax Company : 386 (1) 722 4310

Responsible/issuing person : 386 (1) 722 4383
productsafety@helios.si

1.4 Emergency telephone number

Ambulance (972) 101

Israel Poison Information Center +972 4 854 19 00

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 H226: Flammable liquid and vapour.

Specific target organ toxicity - single ex-
posure, Category 3, Central nervous
system H336: May cause drowsiness or dizziness.

Long-term (chronic) aquatic hazard, Cat-
egory 3 H412: Harmful to aquatic life with long lasting ef-
fects.

SAFETY DATA SHEET

TESSAROL primer for iron



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	28.11.2023	MAT0GA00_006	Date of first issue: 28.11.2023
		IL/EN	

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Warning

Hazard statements :
H226 Flammable liquid and vapour.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements :
P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P271 Use only outdoors or in a well-ventilated area.

Response:

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label:
hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics

Additional Labelling

EUH208 Contains rosin, cobalt bis(2-ethylhexanoate). May produce an allergic reaction.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

SAFETY DATA SHEET

TESSAROL primer for iron



Version
1.0

Revision Date:
28.11.2023

SDS Number:
MAT0GA00_006
IL/EN

Date of last issue: -
Date of first issue: 28.11.2023

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics	- 919-857-5 01-2119463258-33	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) Asp. Tox. 1; H304	>= 20 - < 30
trizinc bis(orthophosphate)	7779-90-0 231-944-3 030-011-00-6 01-2119485044-40	Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 1 - < 2.5
reaction mixture of ethylbenzene, m-xylene and p-xylene	- 905-562-9 01-2119555267-33	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 Asp. Tox. 1; H304	>= 1 - < 10
hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics	- 918-481-9 01-2119457273-39	Asp. Tox. 1; H304	>= 1 - < 10
zinc oxide	1314-13-2 215-222-5 030-013-00-7 01-2119463881-32	Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 0.1 - < 0.25
strontium bis(2-ethylhexanoate)	2457-02-5 219-536-3	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 Repr. 1B; H360D	>= 0.1 - < 0.3
rosin	8050-09-7 232-475-7 650-015-00-7 01-2119480418-32	Skin Sens. 1; H317	>= 0.1 - < 1
zinc 5-nitroisophthalate	60580-61-2	Aquatic Acute 1; H400 Aquatic Chronic 2; H411	>= 0.1 - < 0.25
cobalt bis(2-ethylhexanoate)	136-52-7 205-250-6	Eye Irrit. 2; H319 Skin Sens. 1A; H317	>= 0.025 - < 0.1

SAFETY DATA SHEET

TESSAROL primer for iron



Version
1.0

Revision Date:
28.11.2023

SDS Number:
MAT0GA00_006
IL/EN

Date of last issue: -
Date of first issue: 28.11.2023

	01-2119524678-29	Repr. 1B; H360D Aquatic Acute 1; H400 Aquatic Chronic 3; H412	
Substances with a workplace exposure limit :			
talc	14807-96-6 238-877-9 01-2120140278-58		>= 10 - < 20
aluminum silicate dihydrate	1332-58-7 310-194-1		>= 10 - < 20

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

- Risks : May cause drowsiness or dizziness.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.

SAFETY DATA SHEET

TESSAROL primer for iron



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	28.11.2023	MAT0GA00_006 IL/EN	Date of first issue: 28.11.2023

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local

SAFETY DATA SHEET

TESSAROL primer for iron



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	28.11.2023	MAT0GA00_006 IL/EN	Date of first issue: 28.11.2023

/ national regulations (see section 13).

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national regulations.
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.
- Hygiene measures : When using do not eat or drink. When using do not smoke.
Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

- Specific use(s) : For further information, refer to the product technical data sheet.
- Consult the technical guidelines for the use of this substance/mixture.

SAFETY DATA SHEET

TESSAROL primer for iron



Version
1.0

Revision Date:
28.11.2023

SDS Number:
MAT0GA00_006
IL/EN

Date of last issue: -
Date of first issue: 28.11.2023

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Talc	14807-96-6	TWA (Respirable dust)	0.1 mg/m ³	2004/37/EC
Further information: Carcinogens or mutagens				
		TWA (Respirable particulate matter)	2 mg/m ³	ACGIH
Kaolin	1332-58-7	TWA (Respirable dust)	0.1 mg/m ³	2004/37/EC
Further information: Carcinogens or mutagens				
		TWA (Respirable particulate matter)	2 mg/m ³	ACGIH
titanium dioxide	13463-67-7	TWA (Respirable particulate matter)	0.2 mg/m ³ (Titanium dioxide)	ACGIH
		TWA (Respirable particulate matter)	2.5 mg/m ³ (Titanium dioxide)	ACGIH
reaction mixture of ethylbenzene, m-xylene and p-xylene	1330-20-7	TLV-TWA	100 ppm	IL OEL
		TLV-C	150 mg/m ³	IL OEL
		TWA	50 ppm 221 mg/m ³	2000/39/EC
Further information: Identifies the possibility of significant uptake through the skin, Indicative				
		STEL	100 ppm 442 mg/m ³	2000/39/EC
Further information: Identifies the possibility of significant uptake through the skin, Indicative				
		TWA	20 ppm	ACGIH
zinc oxide	1314-13-2	TWA (Respirable particulate matter)	2 mg/m ³	ACGIH
		STEL (Respirable particulate matter)	10 mg/m ³	ACGIH
rosin	8050-09-7	TWA (Inhalable particulate matter)	0.001 mg/m ³ (total Resin acids)	ACGIH

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
reaction mixture of	1330-20-7	methyl hippuric		IL BEI

SAFETY DATA SHEET

TESSAROL primer for iron



Version
1.0

Revision Date:
28.11.2023

SDS Number:
MAT0GA00_006
IL/EN

Date of last issue: -
Date of first issue: 28.11.2023

ethylbenzene, m-xylene and p-xylene		acid: 1.5 g/g creatinine (Urine)		
		Methylhippuric acids: 1.5 g/g creatinine (Urine)	End of shift (As soon as possible after exposure ceases)	ACGIH BEI

Derived No Effect Level (DNEL)

according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics	Workers	Inhalation	Long-term systemic effects	1500 mg/m3
	Consumers	Inhalation	Long-term systemic effects	900 mg/m3
	Workers	Dermal	Long-term systemic effects	300 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	300 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	300 mg/kg bw/day
Calcium carbonate	Workers	Inhalation	Long-term local effects	4.26 mg/m3
	Consumers	Inhalation	Long-term local effects	1.06 mg/m3
Talc	Workers	Inhalation	Acute systemic effects	2.16 mg/m3
	Workers	Inhalation	Acute local effects	3.6 mg/m3
	Consumers	Inhalation	Acute systemic effects	1.08 mg/m3
	Consumers	Inhalation	Acute local effects	1.8 mg/m3
	Consumers	Dermal	Long-term local effects	2.27 mg/cm2
	Workers	Dermal	Long-term local effects	4.54 mg/cm2
	Consumers	Oral	Long-term systemic effects	160 mg/kg bw/day
	Consumers	Oral	Acute systemic effects	160 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	43.2 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	21.6 mg/kg bw/day
titanium dioxide	Workers	Inhalation	Long-term local effects	10 mg/m3
	Consumers	Oral	Long-term systemic effects	700 mg/kg bw/day
trizinc bis(orthophosphate)	Workers	Inhalation	Long-term systemic effects	5 mg/m3

SAFETY DATA SHEET

TESSAROL primer for iron



Version
1.0

Revision Date:
28.11.2023

SDS Number:
MAT0GA00_006
IL/EN

Date of last issue: -
Date of first issue: 28.11.2023

	Consumers	Inhalation	Long-term systemic effects	2.5 mg/m3
	Workers	Dermal	Long-term systemic effects	83 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	83 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	0.83 mg/kg bw/day
reaction mixture of ethylbenzene, m-xylene and p-xylene	Workers	Inhalation	Long-term systemic effects	77 mg/m3
	Consumers	Inhalation	Long-term local effects	65.3 mg/m3
	Workers	Inhalation	Acute systemic effects	442 mg/m3
	Workers	Inhalation	Acute local effects	289 mg/m3
	Consumers	Inhalation	Acute systemic effects	260 mg/m3
	Workers	Inhalation	Long-term local effects	221 mg/m3
	Consumers	Inhalation	Long-term systemic effects	14.8 mg/m3
	Consumers	Inhalation	Acute local effects	260 mg/m3
	Consumers	Dermal	Long-term systemic effects	108 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	16 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	180 mg/kg bw/day
zinc oxide	Workers	Inhalation	Long-term systemic effects	5 mg/m3
	Workers	Inhalation	Long-term local effects	0.5 mg/m3
	Consumers	Inhalation	Long-term systemic effects	2.5 mg/m3
	Workers	Dermal	Long-term systemic effects	83 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	83 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	0.83 mg/kg bw/day
strontium bis(2-ethylhexanoate)	Workers	Inhalation	Long-term systemic effects	0.730 mg/m3
	Workers	Dermal	Long-term systemic effects	0.410 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	0.180 mg/m3
	Consumers	Dermal	Long-term systemic effects	0.210 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	0.210 mg/kg bw/day
rosin	Workers	Inhalation	Long-term systemic effects	117 mg/m3

SAFETY DATA SHEET

TESSAROL primer for iron



Version
1.0

Revision Date:
28.11.2023

SDS Number:
MAT0GA00_006
IL/EN

Date of last issue: -
Date of first issue: 28.11.2023

	Consumers	Inhalation	Long-term systemic effects	35 mg/m3
	Workers	Dermal	Long-term systemic effects	17 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	10 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	10 mg/kg bw/day
cobalt bis(2-ethylhexanoate)	Workers	Inhalation	Long-term systemic effects	0.2351 mg/m3
	Consumers	Inhalation	Long-term local effects	0.037 mg/m3
	Consumers	Oral	Long-term systemic effects	0.0276 mg/kg bw/day

Predicted No Effect Concentration (PNEC)

according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Calcium carbonate	Sewage treatment plant	100 mg/l
Talc	Marine water	141.26 mg/l
	Fresh water	597.97 mg/l
	Marine sediment	3.13 mg/kg dry weight (d.w.)
	Fresh water sediment	31.33 mg/kg dry weight (d.w.)
	Intermittent use/release	597.97 mg/l
titanium dioxide	Soil	100 mg/kg dry weight (d.w.)
	Marine water	0.0184 mg/l
	Fresh water	0.184 mg/l
	Marine sediment	100 mg/kg dry weight (d.w.)
	Fresh water sediment	1000 mg/kg dry weight (d.w.)
	Sewage treatment plant	100 mg/l
	Intermittent use/release	0.193 mg/l
trizinc bis(orthophosphate)	Soil	35.6 mg/kg dry weight (d.w.)
	Marine water	0.0061 mg/l
	Fresh water	0.0206 mg/l
	Marine sediment	56.5 mg/kg dry weight (d.w.)
	Fresh water sediment	117.8 mg/kg dry weight (d.w.)
	Sewage treatment plant	0.1 mg/l
reaction mixture of ethylbenzene, m-xylene and p-xylene	Soil	2.31 mg/kg dry weight (d.w.)
	Marine water	0.327 mg/l
	Fresh water	0.327 mg/l
	Marine sediment	12.46 mg/kg dry weight (d.w.)
	Fresh water sediment	12.46 mg/kg dry

SAFETY DATA SHEET

TESSAROL primer for iron



Version
1.0

Revision Date:
28.11.2023

SDS Number:
MAT0GA00_006
IL/EN

Date of last issue: -
Date of first issue: 28.11.2023

		weight (d.w.)
	Sewage treatment plant	6.58 mg/l
	Intermittent use/release	0.327 mg/l
zinc oxide	Soil	35.6 mg/kg dry weight (d.w.)
	Marine water	0.0061 mg/l
	Fresh water	0.0206 mg/l
	Marine sediment	56.5 mg/kg dry weight (d.w.)
	Fresh water sediment	117.8 mg/kg dry weight (d.w.)
	Sewage treatment plant	0.1 mg/l
strontium bis(2-ethylhexanoate)	Fresh water	0.360 - 0.440 mg/l
	Intermittent use/release	0.493 - 0.610 mg/l
	Marine water	0.036 - 0.040 mg/l
	Sewage treatment plant	71.7 - 88.52 mg/l
	Fresh water sediment	6.37 - 7.86 mg/kg dry weight (d.w.)
	Marine sediment	0.637 - 0.790 mg/kg dry weight (d.w.)
	Soil	1.06 - 1.31 mg/kg dry weight (d.w.)
rosin	Soil	0.00045 mg/kg dry weight (d.w.)
	Marine water	0.00016 mg/l
	Fresh water	0.0016 mg/l
	Marine sediment	0.0007 mg/kg dry weight (d.w.)
	Fresh water sediment	0.007 mg/kg dry weight (d.w.)
	Sewage treatment plant	1 mg/l
	Intermittent use/release	0.016 mg/l
zinc 5-nitroisophthalate	Fresh water	0.0206 - 0.0808 mg/l
	Marine water	0.0061 - 0.0239 mg/l
	Sewage treatment plant	0.100 - 0.3922 mg/l
	Fresh water sediment	117.8 - 462 mg/kg dry weight (d.w.)
	Marine sediment	56.5 - 221 mg/kg dry weight (d.w.)
	Soil	56.5 - 221 mg/kg dry weight (d.w.)
cobalt bis(2-ethylhexanoate)	Soil	10.9 mg/kg dry weight (d.w.)
	Marine water	0.00236 mg/l
	Fresh water	0.0006 mg/l

SAFETY DATA SHEET

TESSAROL primer for iron



Version 1.0 Revision Date: 28.11.2023 SDS Number: MAT0GA00_006 IL/EN Date of last issue: -
Date of first issue: 28.11.2023

	Marine sediment	9.5 mg/kg dry weight (d.w.)
	Fresh water sediment	9.5 mg/kg dry weight (d.w.)
	Sewage treatment plant	0.37 mg/l

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Equipment should conform to EN 166
Eye wash bottle with pure water
Tightly fitting safety goggles

Hand protection

Gloves : Nitrile rubber (> 0,1 mm; < 60 min); DIN EN374 |
butyl-rubber (> 0,6 mm; < 240 min); DIN EN374 |
Viton® (> 0,6 mm; < 240 min); DIN EN374 |
PE laminate (> 0,1 mm; < 240 min); DIN EN374 |

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Combined particulates and organic vapour type (A-P)

Protective measures : Wash thoroughly after handling.
Avoid contact with skin, eyes and clothing.
Keep away from food, drink and animal feedingstuffs.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : in accordance with the product description

Odour : solvent-like

Odour Threshold : No data available

SAFETY DATA SHEET

TESSAROL primer for iron



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	28.11.2023	MAT0GA00_006	Date of first issue: 28.11.2023
		IL/EN	

pH	:	No data available
Melting point/freezing point	:	825.0 °C (calculation method (principal components, lowest value))
Flash point	:	40 °C
Flammability (solid, gas)	:	Static-accumulating flammable liquid., Combustible Solids
Upper explosion limit / Upper flammability limit	:	6 %(V) (calculation method (principal components, highest value))
Lower explosion limit / Lower flammability limit	:	0.7 %(V) (calculation method (principal components, highest value))
Relative vapour density	:	No data available
Relative density	:	No data available
Density	:	1.25 - 1.40 g/cm3
Solubility(ies)		
Water solubility	:	insoluble
Solubility in other solvents	:	Description: miscible with most organic solvents
Partition coefficient: n-octanol/water	:	No data available
Decomposition temperature	:	No decomposition if stored and applied as directed. Hazardous decomposition products formed under fire conditions.
Viscosity		
Viscosity, kinematic	:	> 20.5 mm2/s (40 °C)
Flow time	:	> 60 s at 23 °C Cross section: 6 mm Method: ISO 2431
Explosive properties	:	Not applicable
Oxidizing properties	:	Sustains combustion

9.2 Other information

No data available	:	
VOC	:	(Directive 1999/13/EC) 500 g/l

SAFETY DATA SHEET

TESSAROL primer for iron



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	28.11.2023	MAT0GA00_006 IL/EN	Date of first issue: 28.11.2023

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Incompatible with strong acids and bases.

10.6 Hazardous decomposition products

Adequate ventilation is required.

Heating can release vapours which can be ignited.

Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

Product:

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Components:

trizinc bis(orthophosphate):

Acute oral toxicity : LD50 (Rat): 5,000 mg/kg

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Acute oral toxicity : LD50 Oral (Rat): >= 8,700 mg/kg

Acute inhalation toxicity : LC50 (Rat): 27.14 mg/l

SAFETY DATA SHEET

TESSAROL primer for iron



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	28.11.2023	MAT0GA00_006 IL/EN	Date of first issue: 28.11.2023

Test atmosphere: vapour

Acute dermal toxicity : Assessment: The component/mixture is moderately toxic after single contact with skin.

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Acute oral toxicity : LD50 Oral (Rat, male and female): > 5,000 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 5,000 mg/l
Test atmosphere: vapour
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 Dermal (Rabbit, male and female): > 5,000 mg/kg
Method: OECD Test Guideline 402

strontium bis(2-ethylhexanoate):

Acute oral toxicity : Assessment: The component/mixture is moderately toxic after single ingestion.

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks : May cause skin irritation and/or dermatitis.

Components:

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Result : irritating

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation
GLP : yes

Result : Repeated exposure may cause skin dryness or cracking.

strontium bis(2-ethylhexanoate):

Result : irritating

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks : Vapours may cause irritation to the eyes, respiratory system and the skin.

SAFETY DATA SHEET

TESSAROL primer for iron



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	28.11.2023	MAT0GA00_006	Date of first issue: 28.11.2023
		IL/EN	

Components:

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Result : Eye irritation

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Species : Rabbit
Method : OECD Test Guideline 405
Result : No eye irritation

strontium bis(2-ethylhexanoate):

Result : Corrosive

cobalt bis(2-ethylhexanoate):

Result : Eye irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Product:

Remarks : Causes sensitisation.

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Exposure routes : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : Not a skin sensitizer.

rosin:

Result : Probability or evidence of skin sensitisation in humans

cobalt bis(2-ethylhexanoate):

Result : The product is a skin sensitizer, sub-category 1A.

Germ cell mutagenicity

Not classified based on available information.

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Genotoxicity in vitro : Result: negative

SAFETY DATA SHEET

TESSAROL primer for iron



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	28.11.2023	MAT0GA00_006 IL/EN	Date of first issue: 28.11.2023

Genotoxicity in vivo : Result: negative

Carcinogenicity

Not classified based on available information.

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Result : negative

Reproductive toxicity

Not classified based on available information.

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Effects on foetal development : Remarks: Fertility and developmental toxicity tests did not reveal any effect on reproduction.

STOT - single exposure

May cause drowsiness or dizziness.

Components:

hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics:

Assessment : May cause drowsiness or dizziness.

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Assessment : May cause respiratory irritation.

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Remarks : Based on available data, the classification criteria are not met.

STOT - repeated exposure

Not classified based on available information.

Components:

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Assessment : May cause damage to organs through prolonged or repeated exposure.

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Remarks : Based on available data, the classification criteria are not met.

Aspiration toxicity

Not classified based on available information.

SAFETY DATA SHEET

TESSAROL primer for iron



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	28.11.2023	MAT0GA00_006	Date of first issue: 28.11.2023
		IL/EN	

Components:

hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics:

May be fatal if swallowed and enters airways.

reaction mixture of ethylbenzene, m-xylene and p-xylene:

May be fatal if swallowed and enters airways.

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks	:	Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Concentrations substantially above the TLV value may cause narcotic effects. Solvents may degrease the skin.
---------	---	---

SECTION 12: Ecological information

12.1 Toxicity

Components:

trizinc bis(orthophosphate):

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity :

Very toxic to aquatic life with long lasting effects.

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Toxicity to fish : LC50 (Fish): $\geq 1 - 10$ mg/l

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)): $\geq 1 - 10$ mg/l

Toxicity to microorganisms : EC50 (Bacteria): $\geq 1 - 100$ mg/l

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): $> 1,000$ mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

SAFETY DATA SHEET

TESSAROL primer for iron



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	28.11.2023	MAT0GA00_006	Date of first issue: 28.11.2023
		IL/EN	

Toxicity to daphnia and other aquatic invertebrates : EC50 : > 1,000 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : NOEC (Pseudokirchneriella subcapitata (microalgae)): 1,000 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

EC50 (Pseudokirchneriella subcapitata (microalgae)): > 1,000 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

zinc oxide:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): >= 1.793 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): >= 2.6 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : IC50 (Desmodesmus subspicatus (green algae)): >= 0.136 mg/l
Exposure time: 72 h

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity :

Very toxic to aquatic life with long lasting effects.

zinc 5-nitroisophthalate:

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity :

Toxic to aquatic life with long lasting effects.

cobalt bis(2-ethylhexanoate):

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

SAFETY DATA SHEET

TESSAROL primer for iron



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	28.11.2023	MAT0GA00_006 IL/EN	Date of first issue: 28.11.2023

Chronic aquatic toxicity :

Harmful to aquatic life with long lasting effects.

12.2 Persistence and degradability

Components:

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Biodegradability : Remarks: Readily biodegradable.

Photodegradation : Remarks: Decomposes rapidly in contact with light.

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 80 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

zinc oxide:

Biodegradability : Result: Biodegradable

12.3 Bioaccumulative potential

Components:

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Bioaccumulation : Bioconcentration factor (BCF): 25.9
Remarks: Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water : log Pow: 2.77 - 3.15

12.4 Mobility in soil

Components:

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Distribution among environmental compartments : Koc: 537, log Koc: 2.73
Remarks: Moderately mobile in soils
The product evaporates from soil.

Stability in soil : Dissipation time: 23 d
Percentage dissipation: 50 % (DT50)

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

SAFETY DATA SHEET

TESSAROL primer for iron



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	28.11.2023	MAT0GA00_006 IL/EN	Date of first issue: 28.11.2023

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Assessment : This substance is not considered to be persistent, bioaccumulating and toxic (PBT).

12.6 Other adverse effects

Product:

Endocrine disrupting potential : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life.
Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

14.1 UN number

ADN	: UN 1263
ADR	: UN 1263
RID	: UN 1263
IMDG	: UN 1263
IATA	: UN 1263

SAFETY DATA SHEET

TESSAROL primer for iron



Version 1.0 Revision Date: 28.11.2023 SDS Number: MAT0GA00_006
IL/EN

Date of last issue: -
Date of first issue: 28.11.2023

14.2 UN proper shipping name

ADN : PAINT
ADR : PAINT
RID : PAINT
IMDG : PAINT
IATA : Paint

14.3 Transport hazard class(es)

ADN : 3
ADR : 3
RID : 3
IMDG : 3
IATA : 3

14.4 Packing group

ADN
Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

ADR
Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3
Tunnel restriction code : (D/E)

RID
Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

IMDG
Packing group : III
Labels : 3
EmS Code : F-E, S-E

IATA (Cargo)
Packing instruction (cargo aircraft) : 366
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids

IATA (Passenger)
Packing instruction (passenger aircraft) : 355
Packing instruction (LQ) : Y344
Packing group : III

SAFETY DATA SHEET

TESSAROL primer for iron



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	28.11.2023	MAT0GA00_006 IL/EN	Date of first issue: 28.11.2023

Labels : Flammable Liquids

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

Remarks : ADR: Packages smaller than or equal to 450 litres, not goods/merchandise of Class 3 (exemption ADR 2.2.3.1.5)
IMDG: Packages smaller than or equal to 450 litres, not goods/merchandise of Class 3; "transport acc. IMDG-code 2.3.2.5"

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Volatile organic compounds : Directive 1999/13/EC
Volatile organic compounds (VOC) content: 500 g/l

15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

SECTION 16: Other information

Full text of H-Statements

H226 : Flammable liquid and vapour.
H302 : Harmful if swallowed.
H304 : May be fatal if swallowed and enters airways.
H312 : Harmful in contact with skin.
H315 : Causes skin irritation.
H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.

SAFETY DATA SHEET

TESSAROL primer for iron



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	28.11.2023	MAT0GA00_006	Date of first issue: 28.11.2023
		IL/EN	

H332	: Harmful if inhaled.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H360D	: May damage the unborn child.
H373	: May cause damage to organs through prolonged or repeated exposure.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.
H411	: Toxic to aquatic life with long lasting effects.
H412	: Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Acute	: Short-term (acute) aquatic hazard
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Eye Dam.	: Serious eye damage
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Repr.	: Reproductive toxicity
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitisation
STOT RE	: Specific target organ toxicity - repeated exposure
STOT SE	: Specific target organ toxicity - single exposure
2000/39/EC	: Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2004/37/EC	: Europe. Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens or mutagens at work
ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	: ACGIH - Biological Exposure Indices (BEI)
IL BEI	: Israel. Safety at Work Regulations - Annex III Biological Exposure Indices
IL OEL	: Israel. Safety at Work Regulations (Environmental monitoring and biological monitoring of workers)
2000/39/EC / TWA	: Limit Value - eight hours
2000/39/EC / STEL	: Short term exposure limit
2004/37/EC / TWA	: Long term exposure limit
ACGIH / TWA	: 8-hour, time-weighted average
ACGIH / STEL	: Short-term exposure limit
IL OEL / TLV-TWA	: Threshold Limit Value - Time Weighted (TLV-TWA)
IL OEL / TLV-C	: Threshold Limit Value - Ceiling (TLV-C)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships car-

SAFETY DATA SHEET

TESSAROL primer for iron



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	28.11.2023	MAT0GA00_006	Date of first issue: 28.11.2023
		IL/EN	

rying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Flam. Liq. 3	H226
STOT SE 3	H336
Aquatic Chronic 3	H412

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method

402540; 409381; 418668

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

IL / EN