MOBIHEL 2K trdilec 7750



Version Revision Date: SDS Number: Date of last issue: -

1.0 18.12.2023 MAT000479012AZ/EN Date of first issue: 18.12.2023

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : MOBIHEL 2K trdilec 7750

Product code : 479012

Manufacturer or supplier's details

Details of the supplier of the safety data sheet

Company : Helios TBLUS d.o.o.

Količevo 65 Domžale 1230 Slovenia

Telephone : 386 (1) 722 4383 Telefax : 386 (1) 722 4310 E-mail address Responsi : 386 (1) 722 4383

ble/issuing person productsafety@helios.si

Emergency telephone number

112 - zəng mərkəzi

Recommended use of the chemical and restrictions on use

Recommended use : Coatings and paints, thinners, paint removers Restrictions on use : Reserved for industrial and professional use.

2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 3

Acute toxicity (Inhalation) : Category 5

Acute toxicity (Dermal) : Category 5

Skin corrosion/irritation : Category 3

Skin sensitisation : Category 1

Specific target organ toxicity - :

single exposure

Category 3 (Respiratory system, Central nervous system)

Specific target organ toxicity - :

repeated exposure

Category 2

GHS label elements

Hazard pictograms :







MOBIHEL 2K trdilec 7750



Version Revision Date: SDS Number: Date of last issue: -

1.0 18.12.2023 MAT000479012AZ/EN Date of first issue: 18.12.2023

Signal word : Warning

Hazard statements : H226 Flammable liquid and vapour.

H313 + H333 May be harmful in contact with skin or if inhaled.

H316 Causes mild skin irritation.

H317 May cause an allergic skin reaction. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or re-

peated exposure.

Precautionary statements

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting equip-

ment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P260 Do not breathe mist or vapours.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of

the workplace.

P280 Wear protective gloves/ protective clothing/ eve protec-

tion/ face protection/ hearing protection.

Response:

P303 + P361 + P353 + P317 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Get medical help.

P304 + P317 IF INHALED: Get medical help.

P304 + P340 + P319 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical help if you feel

P333 + P317 If skin irritation or rash occurs: Get medical help. P362 + P364 Take off contaminated clothing and wash it before

reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

None known.

MOBIHEL 2K trdilec 7750



Version Revision Date: SDS Number: Date of last issue: -

1.0 18.12.2023 MAT000479012AZ/EN Date of first issue: 18.12.2023

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : Consult a physician after significant exposure.

If unconscious, place in recovery position and seek medical

advice.

In case of skin contact : If skin irritation persists, call a physician.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Flush eyes with water as a precaution.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

Most important symptoms and effects, both acute and

and effects, both acute

: None known.

delayed

Notes to physician : Treat symptomatically.

5. FIREFIGHTING MEASURES

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

High volume water jet

Specific hazards during fire-

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion prod: :

ucts

No hazardous combustion products are known

Specific extinguishing meth-

ods

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

For safety reasons in case of fire, cans should be stored sepa-

rately in closed containments.

Use a water spray to cool fully closed containers.

Special protective equipment:

for firefighters

In the event of fire, wear self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

MOBIHEL 2K trdilec 7750



Version Revision Date: SDS Number: Date of last issue: -

1.0 18.12.2023 MAT000479012AZ/EN Date of first issue: 18.12.2023

Personal precautions, protective equipment and emer-

gency procedures

Use personal protective equipment. Remove all sources of ignition. Evacuate personnel to safe areas.

Beware of vapours accumulating to form explosive concentra-

tions. Vapours can accumulate in low areas.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local

/ national regulations (see section 13).

7. HANDLING AND STORAGE

Advice on protection against

fire and explosion

Do not spray on a naked flame or any incandescent material.

Take necessary action to avoid static electricity discharge

(which might cause ignition of organic vapours).

Keep away from open flames, hot surfaces and sources of

ignition.

Advice on safe handling : Avoid formation of aerosol.

Do not breathe vapours/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national

regulations.

Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Conditions for safe storage

No smoking.

Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Further information on stor-

age conditions

Protect from moisture.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

MOBIHEL 2K trdilec 7750



Version Revision Date: SDS Number: Date of last issue: -

1.0 18.12.2023 MAT000479012AZ/EN Date of first issue: 18.12.2023

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ven-

tilation is provided or exposure assessment demonstrates that

exposures are within recommended exposure guidelines.

Filter type

Organic vapour type

Hand protection

Gloves : | Viton® (> 0,6 mm; < 240 min); DIN EN374 |

PE laminate (> 0,1 mm; < 240 min); DIN EN374

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of

cuts, abrasion, and the contact time.

Eye protection : Equipment should conform to EN 166

Eye wash bottle with pure water

Tightly fitting safety goggles

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concen-

tration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : colourless

Odour : solvent-like

Odour Threshold : No data available

pH : Not applicable

Melting point/freezing point : -98,8 °C

(calculation method (principal components, lowest value))

Boiling point/boiling range : 117 °C

(calculation method (principal components, lowest value))

Flash point : 31 °C

Flammability (solid, gas) : Static-accumulating flammable liquid., Combustible Solids

MOBIHEL 2K trdilec 7750



Version Revision Date: SDS Number: Date of last issue: -

1.0 18.12.2023 MAT000479012AZ/EN Date of first issue: 18.12.2023

Upper explosion limit / Upper

flammability limit

10,5 %(V)

Lower explosion limit / Lower

flammability limit

1,1 %(V)

Relative vapour density : No data available

Relative density : No data available

Density : 0,971 g/cm3

Solubility(ies)

Water solubility : partly miscible

Solubility in other solvents : Description: miscible with most organic solvents

Partition coefficient: n-

octanol/water

: log Pow: 2,77 - 3,15

Auto-ignition temperature : 315 °C

Decomposition temperature : No decomposition if stored and applied as directed.

Hazardous decomposition products formed under fire condi-

tions.

Viscosity

Viscosity, kinematic : > 20,5 mm2/s (40 °C)

Explosive properties : Not applicable

Oxidizing properties : Sustains combustion

10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed. Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reac- : No decomposi

tions

tions

No decomposition if stored and applied as directed. No decomposition if stored and applied as directed. Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Incompatible with strong acids and bases.

Hazardous decomposition : Adequate ventilation is required.

products Heating can release vapours which can be ignited.

Carbon monoxide, carbon dioxide and unburned hydrocar-

bons (smoke).

11. TOXICOLOGICAL INFORMATION

Skin corrosion/irritation

Product:

Remarks : May cause skin irritation and/or dermatitis.

MOBIHEL 2K trdilec 7750



Version Revision Date: SDS Number: Date of last issue: -

1.0 18.12.2023 MAT000479012AZ/EN Date of first issue: 18.12.2023

Serious eye damage/eye irritation

Product:

Remarks : Vapours may cause irritation to the eyes, respiratory system

and the skin.

Respiratory or skin sensitisation

Product:

Remarks : Causes sensitisation.

Further information

Product:

Remarks : Symptoms of overexposure may be headache, dizziness,

tiredness, nausea and vomiting.

Concentrations substantially above the TLV value may cause

narcotic effects.

Solvents may degrease the skin.

12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor-

mation

No data available

13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

MOBIHEL 2K trdilec 7750



Version Revision Date: SDS Number: Date of last issue: -

1.0 18.12.2023 MAT000479012AZ/EN Date of first issue: 18.12.2023

14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 1263
Proper shipping name : PAINT
Class : 3
Packing group : III
Labels : 3

IATA-DGR

UN/ID No. : UN 1263
Proper shipping name : Paint
Class : 3
Packing group : III

Labels : Flammable Liquids

366

Packing instruction (cargo :

aircraft)

Packing instruction (passen: 355

ger aircraft)

IMDG-Code

UN number : UN 1263
Proper shipping name : PAINT
Class : 3
Packing group : III
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

16. OTHER INFORMATION

Revision Date : 18.12.2023

Full text of other abbreviations

MOBIHEL 2K trdilec 7750



Version Revision Date: SDS Number: Date of last issue: -

1.0 18.12.2023 MAT000479012AZ/EN Date of first issue: 18.12.2023

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration: NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

AZ / EN