

Version 1.1	Revision Date: 30.01.2024	SDS Number: MAT000419636 IL/EN	Date of last issue: 22.11.2023 Date of first issue: 22.11.2023

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1	<b>Product identifier</b> Trade name	:	TESSAROL PRIMER UNI white
	Product code	:	41963622
1.2	Relevant identified uses of the	e s	ubstance or mixture and uses advised against
	Use of the Sub- stance/Mixture	:	Building and construction work Roller application or brushing, Non industrial spraying Coatings and paints, thinners, paint removers
	Recommended restrictions on use	:	Professional and consumer use of coatings
1.3	Details of the supplier of the	sa	fety data sheet
	Company	:	Helios TBLUS d.o.o. Količevo 65 1230 Domžale Slovenia
	Telephone Company	:	386 (1) 722 4383
	Telefax Company	:	386 (1) 722 4310
	Responsible/issuing person	:	386 (1) 722 4383 productsafety@helios.si
1.4	Emergency telephone numb	er	

#### 1 rgency telep

Ambulance (972) 101

Israel Poison Information Center +972 4 854 19 00

# **SECTION 2: Hazards identification**

# 2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)			
Flammable liquids, Category 3	H226: Flammable liquid and vapour.		
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.		



Version 1.1	Revision Date: 30.01.2024		S Number: F000419636 N	Date of last issue: 22.11.2023 Date of first issue: 22.11.2023
	ng-term (chronic) aqua ory 3	tic haz	ard, Cat-	H412: Harmful to aquatic life with long lasting ef- fects.
2.2 Lab	el elements			
	belling (REGULATION zard pictograms	N (EC) :	No 1272/200	
Sig	nal word	:	Warning	
На	zard statements	:	H226 H336 H412	Flammable liquid and vapour. May cause drowsiness or dizziness. Harmful to aquatic life with long lasting effects.
Pre	ecautionary statements	i :	label at har	nedical advice is needed, have product container or nd. ep out of reach of children.
			Preventior	1:
			P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
			P271	Use only outdoors or in a well-ventilated area.
			Response	
			P370 + P37	78 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
			Storage:	
			P405	Store locked up.
			<b>Disposal:</b> P501	Dispose of contents/ container to an approved
				waste disposal plant.

Hazardous components which must be listed on the label: hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics 1-methoxy-2-propanol

### Additional Labelling

EUH208 Contains cobalt bis(2-ethylhexanoate). May produce an allergic reaction.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.



Version 1.1	Revision Date: 30.01.2024	SDS Number: MAT000419636 IL/EN	Date of last issue: 22.11.2023 Date of first issue: 22.11.2023
		IL/EN	

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

# **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

### Components

CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Not Assigned 919-857-5 01-2119463258-33	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) Asp. Tox. 1; H304	>= 20 - < 30
136-52-7 203-539-1 603-064-00-3 01-2119457435-35	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system)	>= 1 - < 10
231-944-3 030-011-00-6 01-2119485044-40	Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 1 - < 2.5
215-222-5 030-013-00-7 01-2119463881-32	Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 0.1 - < 0.25
219-536-3	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 Repr. 1B; H360D	>= 0.1 - < 0.3
	Aquatic Acute 1; H400 Aquatic Chronic 2; H411	>= 0.1 - < 0.25
205-250-6 01-2119524678-29	Eye Irrit. 2; H319 Skin Sens. 1A; H317 Repr. 1B; H360D Aquatic Acute 1; H400 Aquatic Chronic 3; H412	>= 0.025 - < 0.1
	EC-No. Index-No. Registration number Not Assigned 919-857-5 01-2119463258-33 136-52-7 203-539-1 603-064-00-3 01-2119457435-35 231-944-3 030-011-00-6 01-2119485044-40 215-222-5 030-013-00-7 01-2119463881-32 219-536-3 205-250-6	EC-No. Index-No. Registration number         Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) Asp. Tox. 1; H304           136-52-7 203-539-1 603-064-00-3 01-2119457435-35         Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system)           231-944-3 030-011-00-6 030-011-00-6 030-013-00-7 01-2119485044-40         Aquatic Acute 1; H400 Aquatic Chronic 1; H410           215-222-5 030-013-00-7 01-2119463881-32         Aquatic Acute 1; H400 Aquatic Chronic 1; H410           219-536-3         Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 Repr. 1B; H360D           219-536-6 01-2119524678-29         Aquatic Acute 1; H400 Aquatic Chronic 2; H411           205-250-6 01-2119524678-29         Aquatic Acute 1; H400 Aquatic Chronic 3; H412



Version 1.1	Revision Date: 30.01.2024	SDS Number: MAT000419636 IL/EN	Date of last issue: 22.11.2023 Date of first issue: 22.11.2023

talc	238-877-9	>= 10 - < 20	
	01-2120140278-58		

For explanation of abbreviations see section 16.

### **SECTION 4: First aid measures**

4.1 Description of first aid measures				
General advice	: Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.			
If inhaled	: Consult a physician after significant exposure. If unconscious, place in recovery position and seek medical advice.			
In case of skin contact	: If on skin, rinse well with water. If on clothes, remove clothes.			
In case of eye contact	<ul> <li>Flush eyes with water as a precaution.</li> <li>Remove contact lenses.</li> <li>Protect unharmed eye.</li> <li>Keep eye wide open while rinsing.</li> <li>If eye irritation persists, consult a specialist.</li> </ul>			
If swallowed	<ul> <li>Keep respiratory tract clear.</li> <li>Do not give milk or alcoholic beverages.</li> <li>Never give anything by mouth to an unconscious person.</li> <li>If symptoms persist, call a physician.</li> </ul>			
4.2 Most important symptoms and effects, both acute and delayed				
Risks	: May cause drowsiness or dizziness.			

**4.3 Indication of any immediate medical attention and special treatment needed** Treatment : Treat symptomatically.

# **SECTION 5: Firefighting measures**

5.1 Extinguishing media		
Suitable extinguishing media	:	Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical
Unsuitable extinguishing media	:	High volume water jet



Date of last issue: 22.11.2023 Date of first issue: 22.11.2023

Version	Revision Date:	SDS Number:
1.1	30.01.2024	MAT000419636
		IL/EN

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire- fighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion prod- ucts	:	No hazardous combustion products are known
5.3 Advice for firefighters		
Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus.
Further information	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored sepa- rately in closed containments.

Use a water spray to cool fully closed containers.

# **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	:	Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentra- tions. Vapours can accumulate in low areas.
6.2 Environmental precautions		
Environmental precautions	:	Prevent product from entering drains.

Environmental precautions	:	Prevent product from entering drains.
		Prevent further leakage or spillage if safe to do so.
		If the product contaminates rivers and lakes or drains inform
		respective authorities.

# 6.3 Methods and material for containment and cleaning up

Methods for cleaning up	:	Contain spillage, and then collect with non-combustible ab-
		sorbent material, (e.g. sand, earth, diatomaceous earth, ver-
		miculite) and place in container for disposal according to local
		/ national regulations (see section 13).

# 6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

### **SECTION 7: Handling and storage**

### 7.1 Precautions for safe handling



Vers 1.1	ion	Revision Date: 30.01.2024		Number: 000419636	Date of last issue: 22.11.2023 Date of first issue: 22.11.2023
	Advice	on safe handling	:	For personal protecti Smoking, eating and plication area. Take precautionary r Provide sufficient air Open drum carefully	urs/dust. ain special instructions before use.
		on protection agair d explosion	nst :	Take necessary action (which might cause i	aked flame or any incandescent material. on to avoid static electricity discharge gnition of organic vapours). Keep away ot surfaces and sources of ignition.
	Hygien	e measures	:	Wash hands before	breaks and at the end of workday.
7.2 0	Conditi	ons for safe stora	ge, inc	luding any incompat	ibilities
		ements for storage and containers	:	ventilated place. Cor fully resealed and ke label precautions. El	ontainer tightly closed in a dry and well- ntainers which are opened must be care- ept upright to prevent leakage. Observe ectrical installations / working materials e technological safety standards.
	Further age sta	r information on sto ability	r- :	No decomposition if	stored and applied as directed.
7.3 5	Specific	c end use(s)			
	-	c use(s)	:	For further information sheet.	on, refer to the product technical data
				Consult the technica stance/mixture.	I guidelines for the use of this sub-

# **SECTION 8: Exposure controls/personal protection**

# 8.1 Control parameters

# Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
titanium dioxide	13463-67-7	TWA (Respirable particulate mat- ter)	0.2 mg/m3 (Titanium dioxide)	ACGIH
		TWA (Respirable particulate mat- ter)	2.5 mg/m3 (Titanium dioxide)	ACGIH



Version	Revision Date:	SDS Number:	Date of last issue: 22.11.2023
1.1	30.01.2024	MAT000419636 IL/EN	Date of first issue: 22.11.2023

barium sulfate	7727-43-7	TWA (Inhalable particulate mat- ter)	5 mg/m3	ACGIH
Talc	14807-96-6	TWA (Respirable dust)	0.1 mg/m3	2004/37/EC
	Further inforn	nation: Carcinogens	or mutagens	
		TWA (Respirable particulate mat- ter)	2 mg/m3	ACGIH
1-methoxy-2- propanol	107-98-2	TWA	100 ppm 375 mg/m3	2000/39/EC
	Further inforn skin, Indicativ		possibility of significant upta	ke through the
		STEL	150 ppm 568 mg/m3	2000/39/EC
	Further inforn skin, Indicativ		possibility of significant uptal	ke through the
		TWA	50 ppm	ACGIH
		STEL	100 ppm	ACGIH
zinc oxide	1314-13-2	TWA (Respirable particulate mat- ter)	2 mg/m3	ACGIH
		STEL (Respira- ble particulate matter)	10 mg/m3	ACGIH

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health ef- fects	Value
hydrocarbons, C9- C11, n-alkanes, isoal- kanes, cyclic, <2% aromatics	Workers	Inhalation	Long-term systemic effects	1500 mg/m3
	Consumers	Inhalation	Long-term systemic effects	900 mg/m3
	Workers	Dermal	Long-term systemic effects	300 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	300 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	300 mg/kg bw/day
titanium dioxide	Workers	Inhalation	Long-term local ef- fects	10 mg/m3
	Consumers	Oral	Long-term systemic effects	700 mg/kg bw/day
Calcium carbonate	Workers	Inhalation	Long-term local ef- fects	4.26 mg/m3
	Consumers	Inhalation	Long-term local ef- fects	1.06 mg/m3
barium sulfate	Consumers	Inhalation	Long-term systemic effects	10 mg/m3



Version Revision Date: 1.1 30.01.2024	SDS Number: MAT000419636 IL/EN	Date of last issue: 22.11.2023 Date of first issue: 22.11.2023

	Workers	Inhalation	Long-term systemic effects	10 mg/m3
	Consumers	Oral	Long-term systemic effects	13000 mg/kg bw/day
Talc	Workers	Inhalation	Acute systemic ef- fects	2.16 mg/m3
	Workers	Inhalation	Acute local effects	3.6 mg/m3
	Consumers	Inhalation	Acute systemic ef- fects	1.08 mg/m3
	Consumers	Inhalation	Acute local effects	1.8 mg/m3
	Consumers	Dermal	Long-term local ef- fects	2.27 mg/cm2
	Workers	Dermal	Long-term local ef- fects	4.54 mg/cm2
	Consumers	Oral	Long-term systemic effects	160 mg/kg bw/day
	Consumers	Oral	Acute systemic ef- fects	160 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	43.2 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	21.6 mg/kg bw/day
1-methoxy-2-propanol	Workers	Inhalation	Long-term systemic effects	369 mg/m3
	Workers	Inhalation	Acute systemic ef- fects	553.5 mg/m3
	Workers	Inhalation	Acute local effects	553.5 mg/m3
	Workers	Inhalation	Long-term systemic effects	43.9 mg/m3
	Workers	Dermal	Long-term systemic effects	183 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	78 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	33 mg/kg bw/day
trizinc bis(orthophosphate)	Workers	Inhalation	Long-term systemic effects	5 mg/m3
	Consumers	Inhalation	Long-term systemic effects	2.5 mg/m3
	Workers	Dermal	Long-term systemic effects	83 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	83 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	0.83 mg/kg bw/day
zinc oxide	Workers	Inhalation	Long-term systemic effects	5 mg/m3
	Workers	Inhalation	Long-term local ef- fects	0.5 mg/m3
	Consumers	Inhalation	Long-term systemic effects	2.5 mg/m3



 evision Date: ).01.2024	SDS Number: MAT000419636 IL/EN	Date of last issue: 22.11.2023 Date of first issue: 22.11.2023

	Workers	Dermal	Long-term systemic effects	83 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	83 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	0.83 mg/kg bw/day
strontium bis(2- ethylhexanoate)	Workers	Inhalation	Long-term systemic effects	0.730 mg/m3
	Workers	Dermal	Long-term systemic effects	0.410 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	0.180 mg/m3
	Consumers	Dermal	Long-term systemic effects	0.210 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	0.210 mg/kg bw/day
cobalt bis(2- ethylhexanoate)	Workers	Inhalation	Long-term systemic effects	0.2351 mg/m3
	Consumers	Inhalation	Long-term local ef- fects	0.037 mg/m3
	Consumers	Oral	Long-term systemic effects	0.0276 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
titanium dioxide	Soil	100 mg/kg dry
		weight (d.w.)
	Marine water	0.0184 mg/l
	Fresh water	0.184 mg/l
	Marine sediment	100 mg/kg dry
		weight (d.w.)
	Fresh water sediment	1000 mg/kg dry
		weight (d.w.)
	Sewage treatment plant	100 mg/l
	Intermittent use/release	0.193 mg/l
Calcium carbonate	Sewage treatment plant	100 mg/l
barium sulfate	Soil	207.7 mg/kg dry
		weight (d.w.)
	Fresh water	0.115 mg/l
	Fresh water sediment	600.4 mg/kg dry
		weight (d.w.)
	Sewage treatment plant	62.2 mg/l
Talc	Marine water	141.26 mg/l
	Fresh water	597.97 mg/l
	Marine sediment	3.13 mg/kg dry
		weight (d.w.)
	Fresh water sediment	31.33 mg/kg dry
		weight (d.w.)
	Intermittent use/release	597.97 mg/l
1-methoxy-2-propanol	Soil	4.59 mg/kg dry
		weight (d.w.)



Version	Revision Date:	SD
1.1	30.01.2024	MA
		IL/E

DS Number: IAT000419636 /EN Date of last issue: 22.11.2023 Date of first issue: 22.11.2023

	Marine water	1 mg/l
	Fresh water	10 mg/l
	Marine sediment	5.2 mg/kg dry
		weight (d.w.)
	Fresh water sediment	52.3 mg/kg dry
		weight (d.w.)
	Sewage treatment plant	100 mg/l
	Intermittent use/release	100 mg/l
trizinc bis(orthophosphate)	Soil	35.6 mg/kg dry
inzine bis(orthophosphate)	301	weight (d.w.)
	Marine water	0.0061 mg/l
	Fresh water	0.0206 mg/l
	Marine sediment	56.5 mg/kg dry
		weight (d.w.)
	Fresh water sediment	117.8 mg/kg dry
	i lesti water sediment	weight (d.w.)
	Courses treatment plant	0.1 mg/l
-in a suida	Sewage treatment plant	U
zinc oxide	Soil	35.6 mg/kg dry
		weight (d.w.)
	Marine water	0.0061 mg/l
	Fresh water	0.0206 mg/l
	Marine sediment	56.5 mg/kg dry
		weight (d.w.)
	Fresh water sediment	117.8 mg/kg dry
		weight (d.w.)
	Sewage treatment plant	0.1 mg/l
strontium bis(2-ethylhexanoate)	Fresh water	0.360 - 0.440
, , , , , , , , , , , , , , , , , , ,		mg/l
	Intermittent use/release	0.493 - 0.610
		mg/l
	Marine water	0.036 - 0.040
		mg/l
	Sewage treatment plant	71.7 - 88.52 mg/l
	Fresh water sediment	6.37 - 7.86 mg/kg
		dry weight (d.w.)
	Marine sediment	0.637 - 0.790
	Marine Sediment	mg/kg dry weight
		(d.w.)
	Soil	1.06 - 1.31 mg/kg
		00
Ting E nitraigonathalata		dry weight (d.w.) 0.0206 - 0.0808
zinc 5-nitroisophthalate	Fresh water	
	Marine water	mg/l
	Marine water	0.0061 - 0.0239
		mg/l
	Sewage treatment plant	0.100 - 0.3922
		mg/l
	Fresh water sediment	117.8 - 462
		mg/kg dry weight
		(d.w.)
	Marine sediment	56.5 - 221 mg/kg
		dry weight (d.w.)



Version	Revision Date:	SDS Number:
1.1	30.01.2024	MAT000419636
		IL/EN

Date of last issue: 22.11.2023 Date of first issue: 22.11.2023

	Soil	56.5 - 221 mg/kg dry weight (d.w.)
cobalt bis(2-ethylhexanoate)	Soil	10.9 mg/kg dry weight (d.w.)
	Marine water	0.00236 mg/l
	Fresh water	0.0006 mg/l
	Marine sediment	9.5 mg/kg dry weight (d.w.)
	Fresh water sediment	9.5 mg/kg dry weight (d.w.)
	Sewage treatment plant	0.37 mg/l

#### 8.2 Exposure controls

Personal protective equipment	
Eye/face protection :	Equipment should conform to EN 166 Eye wash bottle with pure water Tightly fitting safety goggles
Hand protection	
Gloves :	Nitrile rubber (> 0,1 mm; < 60 min); ISO EN374
Remarks :	The suitability for a specific workplace should be discussed with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local condi- tions under which the product is used, such as the danger of cuts, abrasion, and the contact time.
Skin and body protection :	Impervious clothing Choose body protection according to the amount and concen- tration of the dangerous substance at the work place.
Respiratory protection :	Use respiratory protection unless adequate local exhaust ven- tilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
Filter type :	Combined particulates and organic vapour type (A-P)
Protective measures :	Wash thoroughly after handling. Avoid contact with skin, eyes and clothing. Keep away from food, drink and animal feedingstuffs.



Version	Revision Date:	SDS Number:	
1.1	30.01.2024	MAT000419636	
		IL/EN	

Date of last issue: 22.11.2023 Date of first issue: 22.11.2023

# **SECTION 9: Physical and chemical properties**

## 9.1 Information on basic physical and chemical properties

Appearance	:	liquid
Colour	:	in accordance with the product description
Odour	:	solvent-like
Odour Threshold	:	No data available
рН	:	No data available
Melting point/freezing point	:	
Boiling point/boiling range	:	(calculation method (principal components, lowest value)) 119 °C (calculation method (principal components, lowest
Flash point	:	value)) 29 °C
Flammability (solid, gas)	:	Static-accumulating flammable liquid., Combustible Solids
Upper explosion limit / Upper flammability limit	:	6 %(V) (calculation method (principal components, highest value))
Lower explosion limit / Lower flammability limit	:	0.7 %(V) (calculation method (principal components, highest value))
Vapour pressure	:	11.5 hPa (calculation method (principal components, highest value))
		(20 °C)
Relative vapour density	:	3.11 (calculation method (principal components, highest val-ue))
		(Air = 1.0)
Relative density	:	1.47 (calculation method (principal components, highest val-ue))
Density	:	1.38 - 1.42 g/cm3
Solubility(ies) Water solubility	:	insoluble
Solubility in other solvents	:	Description: miscible with most organic solvents
		10/00



Version 1.1	Revision Date: 30.01.2024		lumber: 00419636	Date of last issue: 22.11.2023 Date of first issue: 22.11.2023
	tion coefficient: n- nol/water	:	log Pow: -0. highest valu	437 (calculation method (principal components, e))
Ignit	ion temperature	:	287 °C (calc value))	ulation method (principal components, highest
Dec	omposition temperatur	e :		esition if stored and applied as directed. lecomposition products formed under fire condi-
	osity ′iscosity, kinematic	:	> 20.5 mm2	′s (40 °C)
Flow	r time	:	> 60 s at 23 Cross sectio Method: ISC	n: 6 mm
Expl	osive properties	:	Not applicat	le
Oxic	izing properties	:	Sustains cor	nbustion
	r <b>information</b> lata available ;	:	(Directive 20 500 g/l	04/42/EC)

# **SECTION 10: Stability and reactivity**

### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : No c	lecomposition if stored and applied as directed.
----------------------------	--

Vapours may form explosive mixture with air.

#### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

### 10.5 Incompatible materials



Version 1.1	Revision Date: 30.01.2024	SDS Number: MAT000419636 IL/EN	Date of last issue: 22.11.2023 Date of first issue: 22.11.2023

Materials to avoid : Incompatible with strong acids and bases.

### **10.6 Hazardous decomposition products**

Adequate ventilation is required. Heating can release vapours which can be ignited. Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

# **SECTION 11: Toxicological information**

### **11.1 Information on toxicological effects**

# Acute toxicity

Not classified based on available information.

# Components:

1-methoxy-2-propanol:	
Acute oral toxicity	: LD50 Oral (Rabbit): > 2,000 mg/kg
Acute dermal toxicity	: LD50 (Rabbit): > 2,000 mg/kg
trizinc bis(orthophosphate)	:
Acute oral toxicity	: LD50 (Rat): 5,000 mg/kg
strontium bis(2-ethylhexan	oate):
Acute oral toxicity	: Assessment: The component/mixture is moderately toxic after single ingestion.
Skin corrosion/irritation	
Not classified based on availa	able information.
Components:	
strontium bis(2-ethylhexan	oate):
Result	: irritating
Serious eye damage/eye irr	itation
Not classified based on availa	able information.
Components:	
strontium bis(2-ethylhexan	oate):
Result	: Corrosive

# cobalt bis(2-ethylhexanoate):

Result : Eye irritation





Date of last issue: 22.11.2023 Date of first issue: 22.11.2023

Version	Revision Date:	SDS Number:
1.1	30.01.2024	MAT000419636
		IL/EN

#### Respiratory or skin sensitisation

#### Skin sensitisation

Not classified based on available information.

#### **Respiratory sensitisation**

Not classified based on available information.

#### **Components:**

### cobalt bis(2-ethylhexanoate):

Result

The product is a skin sensitiser, sub-category 1A.

### Germ cell mutagenicity

Not classified based on available information.

1

### Carcinogenicity

Not classified based on available information.

# **Reproductive toxicity**

Not classified based on available information.

#### STOT - single exposure

May cause drowsiness or dizziness.

#### Components:

hydrocarbons, C9-C11, n-a	lkan	es, isoalkanes, cyclic, <2% aromatics:
Assessment	:	May cause drowsiness or dizziness.

#### 1-methoxy-2-propanol:

Assessment : May cause drowsiness or dizziness.

### STOT - repeated exposure

Not classified based on available information.

#### Aspiration toxicity

Not classified based on available information.

### Components:

hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics: May be fatal if swallowed and enters airways.

#### **Further information**

# Product:

Remarks

 Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.
 Concentrations substantially above the TLV value may cause narcotic effects.



Version Revision Date: SDS Number: 1.1 30.01.2024 MAT000419636 IL/EN	Date of last issue: 22.11.2023 Date of first issue: 22.11.2023
--	---

Solvents may degrease the skin.

# **SECTION 12: Ecological information**

## 12.1 Toxicity

Components:		
1-methoxy-2-propanol:		
Toxicity to fish	:	LC50 (Fish): > 1,000 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	LC50 (Daphnia (water flea)): > 1,000 mg/l
Toxicity to algae/aquatic plants	:	LC50 (algae): > 1,000 mg/l
trizinc bis(orthophosphate):		
Ecotoxicology Assessment		
Acute aquatic toxicity	:	Very toxic to aquatic life.
Chronic aquatic toxicity	:	
		Very toxic to aquatic life with long lasting effects.
		very toxic to aquatic life with long lasting effects.
zinc oxide:		
Toxicity to fish	:	LC50 (Danio rerio (zebra fish)): >= 1.793 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia (water flea)): >= 2.6 mg/l Exposure time: 48 h
Toxicity to algae/aquatic	•	IC50 (Desmodesmus subspicatus (green algae)): >= 0.136
plants	•	mg/l
		Exposure time: 72 h
Ecotoxicology Assessment		
Acute aquatic toxicity	:	Very toxic to aquatic life.
Chronic aquatic toxicity	:	
		Very toxic to aquatic life with long lasting effects.
		tory toxis to aqualis into with long labiling broots.



Version 1.1	Revision Date: 30.01.2024	SDS Number:Date of last issue: 22.11.2023MAT000419636Date of first issue: 22.11.2023IL/ENIL/EN	
zinc	5-nitroisophthalate		
	oxicology Assessn	nt	
	aquatic toxicity		
Chroi	nic aquatic toxicity	:	
		Toxic to aquatic life with long lasting effects.	
coba	lt bis(2-ethylhexan	ate):	
	oxicology Assessn		
Acute	aquatic toxicity	: Very toxic to aquatic life.	
Chroi	nic aquatic toxicity	:	
		Harmful to aquatic life with long lasting effects.	
12.2 Pers	istence and degrad	bility	
Com	ponents:		
zinc	oxide:		
Biode	egradability	: Result: Biodegradable	
12.3 Bioa	ccumulative potent	al	
Com	ponents:		
1-me	thoxy-2-propanol:		
	ion coefficient: n- ol/water	: log Pow: -0.437	
12.4 Mobi	lity in soil		
No da	ata available		
12.5 Resu	llts of PBT and vPv	assessment	
<u>Prod</u>			
Asse	ssment	: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.	



### 12.6 Other adverse effects

Product: Endocrine disrupting poten- : tial	The substance/mixture does not contain components consid- ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at
	levels of 0.1% or higher.
Additional ecological infor- : mation	An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Toxic to aquatic life. Harmful to aquatic life with long lasting effects.

# **SECTION 13: Disposal considerations**

### 13.1 Waste treatment methods

Product	:	The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemi- cal or used container. Send to a licensed waste management company.
Contaminated packaging	:	Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

# **SECTION 14: Transport information**

### 14.1 UN number

ADN	:	UN 1263
ADR	:	UN 1263
RID	:	UN 1263
IMDG	:	UN 1263
ΙΑΤΑ	:	UN 1263
14.2 UN proper shipping name		
ADN	:	PAINT
ADR	:	PAINT
RID	:	PAINT
IMDG	:	PAINT



Version 1.1	Revision Date: 30.01.2024	SDS Number: MAT000419636 IL/EN	Date of last issue: 22.11.2023 Date of first issue: 22.11.2023
----------------	------------------------------	--------------------------------------	---

	ΙΑΤΑ	:	Paint	
14.3	Transport hazard class(es)			
			Class	Subsidiary risks
	ADN	:	3	
	ADR	:	3	
	RID	:	3	
	IMDG	:	3	
	ΙΑΤΑ	:	3	
14.4	Packing group			
	ADN Packing group Classification Code Hazard Identification Number Labels	: : :	III F1 30 3	
	ADR Packing group Classification Code Hazard Identification Number Labels Tunnel restriction code	:	III F1 30 3 (D/E)	
	<b>RID</b> Packing group Classification Code Hazard Identification Number Labels	-	III F1 30 3	
	IMDG Packing group Labels EmS Code	:	III 3 F-E, <u>S-E</u>	
	IATA (Cargo) Packing instruction (cargo aircraft) Packing instruction (LQ) Packing group Labels	:	366 Y344 III Flammable Liquids	
	IATA (Passenger) Packing instruction (passen- ger aircraft) Packing instruction (LQ) Packing group Labels	:	355 Y344 III Flammable Liquids	

# 14.5 Environmental hazards



VersionRevision Date:1.130.01.2024	SDS Number: MAT000419636 IL/EN	Date of last issue: 22.11.2023 Date of first issue: 22.11.2023
------------------------------------	--------------------------------------	---

### ADN

Environmentally hazardous	:	no
ADR Environmentally hazardous	:	no
<b>RID</b> Environmentally hazardous	:	no
IMDG Marine pollutant	:	no

#### 14.6 Special precautions for user

Remarks

ADR: Packages smaller than or equal to 450 litres, not goods/merchandise ofClass 3 (exemption ADR 2.2.3.1.5) IMDG: Packages smaller than or equal to 450 litres, not goods/merchandise ofClass 3; "transport acc. IMDG-code 2.3.2.5"

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

5

Not applicable for product as supplied.

### **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Volatile organic compounds	:	Directive 2004/42/EC
		Volatile organic compounds (VOC) content: 500 g/l

#### 15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

### **SECTION 16: Other information**

### **Full text of H-Statements**

H226 :	Flammable liquid and vapour.
H302 :	Harmful if swallowed.
H304 :	May be fatal if swallowed and enters airways.
H315 :	Causes skin irritation.
H317 :	May cause an allergic skin reaction.
H318 :	Causes serious eye damage.
H319 :	Causes serious eye irritation.
H336 :	May cause drowsiness or dizziness.
H360D :	May damage the unborn child.



Version 1.1	Revision Date: 30.01.2024	SDS Number: MAT000419636 IL/EN	Date of last issue: 22.11.2023 Date of first issue: 22.11.2023	
H400 H410 H411			aquatic life. aquatic life with long lasting effects. atic life with long lasting effects.	
H412			quatic life with long lasting effects.	
Full te	Full text of other abbreviations			
	ic Acute ic Chronic Tox. am. rit. Liq. rrit. Sens. SE 39/EC	<ul> <li>Long-term (c)</li> <li>Aspiration hat</li> <li>Serious eye</li> <li>Eye irritation</li> <li>Flammable li</li> <li>Reproductive</li> <li>Skin irritation</li> <li>Skin sensitis</li> <li>Specific target</li> <li>Europe. Complist of indication</li> <li>Europe. Dire</li> </ul>	acute) aquatic hazard hronic) aquatic hazard azard damage quids e toxicity	
2000/3 2004/3 ACGII	H 39/EC / TWA 39/EC / STEL 37/EC / TWA H / TWA H / STEL	: Limit Value - : Short term e: : Long term ex	xposure limit cposure limit weighted average	

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road: AIIC - Australian Inventory of Industrial Chemicals: ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA -European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance: PICCS - Philippines Inventory of Chemicals and Chemical Substances: (Q)SAR - (Quanti-



Version 1.1	Revision Date: 30.01.2024	SDS Number: MAT000419636 IL/EN	Date of last issue: 22.11.2023 Date of first issue: 22.11.2023
----------------	---------------------------	--------------------------------------	---

tative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information		
Classification of the mix	ture:	Classification procedure:
Flam. Liq. 3	H226	Based on product data or assessment
STOT SE 3	H336	Calculation method
Aquatic Chronic 3	H412	Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.