

Version	Revision Date:	SDS Number:	Date of last issue: 11.05.2023
2.0	08.03.2024	MAT000401636 IE/EN	Date of first issue: 11.05.2023

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier					
Trade name	: TESSAROL Antik 3in1 anthracite				
Product code	: 40163603				
1.2 Relevant identified uses of	the substance or mixture and uses advised against				
Use of the Sub- stance/Mixture	<ul> <li>SU19: Building and construction work PROC10, PROC11: Roller application or brushing, Non indus- trial spraying PC9a: Coatings and paints, thinners, paint removers</li> </ul>				
Recommended restrictions on use	: professional use, public use				
1.3 Details of the supplier of the	he safety data sheet				
Company	: Helios TBLUS d.o.o. Količevo 65 1230 Domžale Slovenia				
Telephone Company	: 386 (1) 722 4383				
Telefax Company	: 386 (1) 722 4310				
Responsible/issuing person	: 386 (1) 722 4383 productsafety@helios.si				
1.4 Emergency telephone num	ıber				
01 809 2166 National Poisor	ns Information Centre 01 809 2166				
01 900 2566 Haaltaara Drofe	01 800 2566 Healteara Professionals 01 800 2566				

- 01 809 2566 Healtcare Professionals 01 809 2566
- 01 809 2566 Healtcare Professionals 01 809 2566

# **SECTION 2: Hazards identification**

# 2.1 Classification of the substance or mixture

### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 Specific target organ toxicity - single exposure, Category 3, Central nervous H226: Flammable liquid and vapour. H336: May cause drowsiness or dizziness.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



# **TESSAROL** Antik 3in1 anthracite

Version 2.0	Revision Date: 08.03.2024	SDS Number: MAT00040163 IE/EN	Date of last issue: 11.05.2023 Date of first issue: 11.05.2023			
syster		tic bozord Cat	H412: Harmful to aquatic life with long lasting ef-			
egory	term (chronic) aqua 3	lic hazard, Cal-	fects.			
2.2 Label						
Label	Labelling (REGULATION (EC) No 1272/2008)					
Hazaı	rd pictograms					
Signa	l word	: Warning				

Signal word	:	Warning	
Hazard statements	:	H226	Flammable liquid and vapour.
		H336	May cause drowsiness or dizziness.
		H412	Harmful to aquatic life with long lasting effects.
Precautionary statements	:	P101	If medical advice is needed, have product con- tainer or label at hand.
		P102	Keep out of reach of children.
		Prevention	:
		P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
		P271	Use only outdoors or in a well-ventilated area.
		Response:	
		P370 + P37	8 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
		Storage:	
		P405	Store locked up.
		Disposal:	
		P501	Dispose of contents/ container to an approved waste disposal plant.

# Hazardous components which must be listed on the label:

hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics 1-methoxy-2-propanol

### **Additional Labelling**

EUH208 Contains mixture of sterically composed sebacates. May produce an allergic reaction.

# 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.



Version	Revision Date:	SDS Number:	Date of last issue: 11.05.2023
2.0	08.03.2024	MAT000401636 IE/EN	Date of first issue: 11.05.2023

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

Components				
Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)	
hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics	- 919-857-5 01-2119463258-33	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) Asp. Tox. 1; H304	>= 20 - < 30	
1-methoxy-2-propanol	107-98-2 203-539-1 603-064-00-3 01-2119457435-35	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system)	>= 1 - < 10	
Reaction mass of bis(1,2,2,6,6- pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl- 4-piperidyl sebacate	1065336-91-5 915-687-0 01-2119491304-40	Skin Sens. 1; H317 Repr. 2; H361f Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 0.25 - < 1	
strontium bis(2-ethylhexanoate)	2457-02-5 219-536-3	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 Repr. 1B; H360D	>= 0.1 - < 0.3	
Substances with a workplace exposure limit :				
Talc	14807-96-6 238-877-9		>= 1 - < 10	
	01-2120140278-58			

### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

:

General advice

Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.



Version 2.0	Revision Date: 08.03.2024	DS Number: Date of last issue AT000401636 Date of first issue E/EN	
lf inha	aled	: Consult a physician after significant exp If unconscious, place in recovery position advice.	
In cas	se of skin contact	: If on skin, rinse well with water. If on clothes, remove clothes.	
In cas	se of eye contact	<ul> <li>Flush eyes with water as a precaution. Remove contact lenses.</li> <li>Protect unharmed eye.</li> <li>Keep eye wide open while rinsing.</li> <li>If eye irritation persists, consult a special</li> </ul>	alist.
lf swa	allowed	<ul> <li>Keep respiratory tract clear.</li> <li>Do not give milk or alcoholic beverages</li> <li>Never give anything by mouth to an uncount of symptoms persist, call a physician.</li> <li>Take victim immediately to hospital.</li> </ul>	
4.2 Most i	mportant symptoms	nd effects, both acute and delayed	
Risks	;	: May cause drowsiness or dizziness.	
		May cause drowsiness or dizziness.	
4.3 Indica	tion of any immedia	medical attention and special treatment n	eeded
Treat	-	: Treat symptomatically.	
SECTION	N 5: Firefighting m	sures	
5.1 Extind	uishing media		
-	-	: Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical	
Unsu media	itable extinguishing a	: High volume water jet	
5.2 Specia	al hazards arising fr	the substance or mixture	
Speci fightir	ific hazards during fire	: Do not allow run-off from fire fighting to courses.	enter drains or water
Haza ucts	rdous combustion pro	: No hazardous combustion products are	known
Speci	e for firefighters ial protective equipme efighters	: In the event of fire, wear self-contained	breathing apparatus.



Version 2.0	Revision Date: 08.03.2024	SDS Number: MAT000401636 IE/EN	Date of last issue: 11.05.2023 Date of first issue: 11.05.2023
Furthe	er information	must not be discha Fire residues and be disposed of in a For safety reasons rately in closed co	contaminated fire extinguishing water must accordance with local regulations. s in case of fire, cans should be stored sepa-

# **SECTION 6:** Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	<ul> <li>Use personal protective equipment. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentra- tions. Vapours can accumulate in low areas.</li> </ul>		
6.2 Environmental precautions			
Environmental precautions	<ul> <li>Prevent product from entering drains.</li> <li>Prevent further leakage or spillage if safe to do so.</li> <li>If the product contaminates rivers and lakes or drains inform respective authorities.</li> </ul>		
6.3 Methods and material for containment and cleaning up			

Methods for cleaning up	: Contain spillage, and then collect with non-combustible ab- sorbent material, (e.g. sand, earth, diatomaceous earth, ver- miculite) and place in container for disposal according to local / national regulations (see section 13).
	•

# 6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

# **SECTION 7: Handling and storage**

# 7.1 Precautions for safe handling

Advice on safe	e handling	:	Avoid formation of aerosol.
	-		Do not breathe vapours/dust.
			Avoid exposure - obtain special instructions before use.
			Avoid contact with skin and eyes.
			For personal protection see section 8.
			Smoking, eating and drinking should be prohibited in the ap-
			plication area.
			Take precautionary measures against static discharges.
			Provide sufficient air exchange and/or exhaust in work rooms.
			Open drum carefully as content may be under pressure.
			Dispose of rinse water in accordance with local and national

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



# **TESSAROL** Antik 3in1 anthracite

Version 2.0	Revision Date: 08.03.2024		Number: 000401636 I	Date of last issue: 11.05.2023 Date of first issue: 11.05.2023	
Advice on protection against : fire and explosion			regulations. Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.		
Hygie	ene measures	:	Wash hands before breaks and at the end of workday.		
7.2 Condi	tions for safe stora	ge, inc	luding any incom	patibilities	
Requirements for storage : areas and containers		:	No smoking. Keep container tightly closed in a dry and well- ventilated place. Containers which are opened must be care- fully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.		
	Further information on stor- : age stability		No decomposition if stored and applied as directed.		
7.3 Speci	fic end use(s)				
Spec	Specific use(s)		For further inforr sheet.	nation, refer to the product technical data	
			Consult the tech stance/mixture.	nical guidelines for the use of this sub-	

# **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

# **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis	
Talc	14807-96-6	OELV - 8 hrs (TWA) (Respira- ble dust)	0.8 mg/m3	IE OEL	
		OELV - 8 hrs (TWA) (inhalable dust)	10 mg/m3	IE OEL	
		TWA (Respirable dust)	0.1 mg/m3	2004/37/EC	
	Further inform	nation: Carcinogens	or mutagens		
1-methoxy-2- propanol	107-98-2	TWA	100 ppm 375 mg/m3	2000/39/EC	
		Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	150 ppm	2000/39/EC	

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



# **TESSAROL** Antik 3in1 anthracite

Version 2.0	Revision Date: 08.03.2024	SDS Number: MAT000401636 IE/EN	Date of last issue: 11.05.2023 Date of first issue: 11.05.2023

		568 mg/m3	
Further skin, Inc	information: Identifies the licative	e possibility of significa	ant uptake through the
	OELV - 8 hrs (TWA)	100 ppm 375 mg/m3	IE OEL
	OELV - 15 min (STEL)	150 ppm 568 mg/m3	IE OEL

# Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health ef- fects	Value
hydrocarbons, C9- C11, n-alkanes, isoal- kanes, cyclic, <2% aromatics	Workers	Inhalation	Long-term systemic effects	1500 mg/m3
	Consumers	Inhalation	Long-term systemic effects	900 mg/m3
	Workers	Dermal	Long-term systemic effects	300 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	300 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	300 mg/kg bw/day
Talc	Workers	Inhalation	Acute systemic ef- fects	2.16 mg/m3
	Workers	Inhalation	Acute local effects	3.6 mg/m3
	Consumers	Inhalation	Acute systemic ef- fects	1.08 mg/m3
	Consumers	Inhalation	Acute local effects	1.8 mg/m3
	Consumers	Dermal	Long-term local ef- fects	2.27 mg/cm2
	Workers	Dermal	Long-term local ef- fects	4.54 mg/cm2
	Consumers	Oral	Long-term systemic effects	160 mg/kg bw/day
	Consumers	Oral	Acute systemic ef- fects	160 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	43.2 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	21.6 mg/kg bw/day
1-methoxy-2-propanol	Workers	Inhalation	Long-term systemic effects	369 mg/m3
	Workers	Inhalation	Acute systemic ef- fects	553.5 mg/m3
	Workers	Inhalation	Acute local effects	553.5 mg/m3
	Workers	Inhalation	Long-term systemic effects	43.9 mg/m3
	Workers	Dermal	Long-term systemic effects	183 mg/kg bw/day
	Consumers	Dermal	Long-term systemic	78 mg/kg

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



# **TESSAROL** Antik 3in1 anthracite

Version 2.0	Revision Date: 08.03.2024	SDS Number: MAT000401636 IE/EN	Date of last issue: 11.05.2023 Date of first issue: 11.05.2023

			effects	bw/day
	Consumers	Oral	Long-term systemic effects	33 mg/kg bw/day
strontium bis(2- ethylhexanoate)	Workers	Inhalation	Long-term systemic effects	0.730 mg/m3
•	Workers	Dermal	Long-term systemic effects	0.410 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	0.180 mg/m3
	Consumers	Dermal	Long-term systemic effects	0.210 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	0.210 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Talc	Marine water	141.26 mg/l
	Fresh water	597.97 mg/l
	Marine sediment	3.13 mg/kg dry
		weight (d.w.)
	Fresh water sediment	31.33 mg/kg dry
		weight (d.w.)
	Intermittent use/release	597.97 mg/l
1-methoxy-2-propanol	Soil	4.59 mg/kg dry
		weight (d.w.)
	Marine water	1 mg/l
	Fresh water	10 mg/l
	Marine sediment	5.2 mg/kg dry
		weight (d.w.)
	Fresh water sediment	52.3 mg/kg dry
		weight (d.w.)
	Sewage treatment plant	100 mg/l
	Intermittent use/release	100 mg/l
strontium bis(2-ethylhexanoate)	Fresh water	0.360 - 0.440
		mg/l
	Intermittent use/release	0.493 - 0.610
		mg/l
	Marine water	0.036 - 0.040
		mg/l
	Sewage treatment plant	71.7 - 88.52 mg/l
	Fresh water sediment	6.37 - 7.86 mg/kg
		dry weight (d.w.)
	Marine sediment	0.637 - 0.790
		mg/kg dry weight
		(d.w.)
	Soil	1.06 - 1.31 mg/kg
		dry weight (d.w.)

#### 8.2 Exposure controls

### Personal protective equipment

Eye/face protection



Version 2.0	Revision Date: 08.03.2024	SDS Number: MAT000401636 IE/EN	Date of last issue: 11.05.2023 Date of first issue: 11.05.2023
Hand	protection	Eye wash bottl Tightly fitting sa	e with pure water afety goggles
Glo	oves	butyl-rubber Viton® (> 0,6	(> 0,1 mm; < 60 min); ISO EN374   (> 0,6 mm; < 240 min); ISO EN374   5 mm; < 240 min); ISO EN374   (> 0,1 mm; < 240 min); ISO EN374
Re	marks	with the produc Please observe breakthrough ti gloves. Also ta tions under wh	for a specific workplace should be discussed cers of the protective gloves. The instructions regarding permeability and me which are provided by the supplier of the ke into consideration the specific local condi- ich the product is used, such as the danger of and the contact time.
Skin a	and body protection		hing rotection according to the amount and con- e dangerous substance at the work place.
Respi	ratory protection	: Use respiratory tilation is provid exposures are	v protection unless adequate local exhaust ven- ded or exposure assessment demonstrates that within recommended exposure guidelines. uld conform to EN 14387
	ter type ctive measures	<ul> <li>Organic vapou</li> <li>Wash thorough</li> <li>Avoid contact v</li> </ul>	

# **SECTION 9: Physical and chemical properties**

### 9.1 Information on basic physical and chemical properties

Physical state	:	liquid
Colour	:	in accordance with the product description
Odour	:	solvent-like
Odour Threshold	:	No data available
Flammability	:	Static-accumulating flammable liquid., Combustible Solids
Upper explosion limit / Upper flammability limit	:	6 %(V) (calculation method (principal components, highest value))
Lower explosion limit / Lower flammability limit	:	0.7 %(V) (calculation method (principal components, highest value))



Vers 2.0	sion	Revision Date: 08.03.2024		Number: 00401636	Date of last issue: 11.05.2023 Date of first issue: 11.05.2023
	Flash p	point	:	43 °C(calculation n lue))	nethod (principal components, lowest va-
	Decom	position temperatu	re :		if stored and applied as directed. position products formed under fire condi-
	рН		:	No data available	
	Viscosi Visc	ity cosity, kinematic	:	> 20.5 mm2/s (40 °	°C)
	Flow tir	ne	:	> 60 s at 23 °C Cross section: 6 m Method: ISO 2431	m
	Solubil Wat	ity(ies) ter solubility	:	insoluble	
	Solu	ubility in other solve	ents :	Description: miscib	le with most organic solvents
	Partitio octano	n coefficient: n- I/water	:	No data available	
	Relativ	e density	:	97.31(calculation n ue))	nethod (principal components, highest val-
	Density	/	:	1.48 g/cm3	
	Relativ	e vapour density	:	No data available	
9.2	Other ir	nformation			
	Explos	ives	:	Not applicable	
	Oxidizi	ng properties	:	Sustains combustion	on
	VOC		:	(Directive 2004/42/ 500 g/l	ÆC)

# **SECTION 10: Stability and reactivity**

# 10.1 Reactivity

No decomposition if stored and applied as directed.

# 10.2 Chemical stability

No decomposition if stored and applied as directed.



Version 2.0	Revision Date: 08.03.2024	SDS Number: MAT000401636 IE/EN	Date of last issue: 11.05.2023 Date of first issue: 11.05.2023
10.3 Pos	sibility of hazardou	s reactions	
Haza	ardous reactions	: No decompositio	n if stored and applied as directed.
		Vapours may for	m explosive mixture with air.
10.4 Con	ditions to avoid		
Cond	litions to avoid	: Heat, flames and	l sparks.
	mpatible materials rials to avoid	: Incompatible with	n strong acids and bases.
	ardous decomposit azardous decompos	i <b>on products</b> ition products are known.	
SECTIO	N 11: Toxicologic	al information	
11.1 Infor	mation on hazard	classes as defined in Reg	ulation (EC) No 1272/2008
Not c	<b>e toxicity</b> classified based on a classified due to lack		
Com	ponents:		
	thoxy-2-propanol:		
Acute	e oral toxicity	: LD50 Oral (Rabbi	t): > 2,000 mg/kg
Acute	e dermal toxicity	: LD50 (Rabbit): > :	2,000 mg/kg
stror	ntium bis(2-ethylhe	kanoate):	
Acute	e oral toxicity	: Assessment: The single ingestion.	component/mixture is moderately toxic after
Skin	corrosion/irritation	I	
	classified based on a classified due to lack		
Prod			
Rem	arks	: May cause skin ir	ritation and/or dermatitis.
<u>Com</u>	ponents:		
stror	ntium bis(2-ethylhe	kanoate):	
Resu	ılt	: irritating	
	bus eye damage/ey		

Not classified based on available information.



2.0 08.03.2024 MA1000401636 Date of first issue: 11.05.2023 IE/EN	Version 2.0	Revision Date: 08.03.2024	SDS Number: MAT000401636 IE/EN	Date of last issue: 11.05.2023 Date of first issue: 11.05.2023	
--	----------------	------------------------------	--------------------------------------	---	--

Not classified due to lack of data.

### Product:

Remarks

: Vapours may cause irritation to the eyes, respiratory system and the skin.

#### **Components:**

strontium bis(2-ethylhexa	noate	):
Result	:	Corrosive

#### Respiratory or skin sensitisation

#### Skin sensitisation

Not classified based on available information.

#### Skin sensitisation

Not classified due to lack of data.

#### **Respiratory sensitisation**

Not classified based on available information.

#### Respiratory sensitisation

Not classified due to lack of data.

#### Product: Remarks

: Causes sensitisation.

### **Components:**

# mixture of sterically composed sebacates:

Result : May cause sensitisation by skin contact.

### Germ cell mutagenicity

Not classified based on available information. Not classified due to lack of data.

### Carcinogenicity

Not classified based on available information. Not classified due to lack of data.

#### **Reproductive toxicity**

Not classified based on available information. Not classified due to lack of data.

### **Components:**

### mixture of sterically composed sebacates:

•

Reproductive toxicity - As-	
sessment	

Some evidence of adverse effects on sexual function and fertility ,based on animal experiments.



Version	Revision Date: 08.03.2024	SDS Number:	Date of last issue: 11.05.2023
2.0		MAT000401636	Date of first issue: 11.05.2023
		IE/EN	

### STOT - single exposure

May cause drowsiness or dizziness. May cause drowsiness or dizziness.

#### **Components:**

hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics:			
Assessment	:	May cause drowsiness or dizziness.	

#### 1-methoxy-2-propanol:

Assessment

: May cause drowsiness or dizziness.

### STOT - repeated exposure

Not classified based on available information. Not classified due to lack of data.

#### Aspiration toxicity

Not classified based on available information. Not classified due to lack of data.

#### **Components:**

hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics: May be fatal if swallowed and enters airways.

### 11.2 Information on other hazards

### Endocrine disrupting properties

#### Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

#### **Further information**

# Product:

Remarks

 Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.
 Concentrations substantially above the TLV value may cause narcotic effects.
 Solvents may degrease the skin.



Version	Revision Date:	SDS Number:	Date of last issue: 11.05.2023
2.0	08.03.2024	MAT000401636 IE/EN	Date of first issue: 11.05.2023

# **SECTION 12: Ecological information**

#### 12.1 Toxicity

Com	pone	nts:
	-	

1-methoxy-2-propanol:		
Toxicity to fish	:	LC50 (Fish): > 1,000 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	LC50 (Daphnia (water flea)): > 1,000 mg/l
Toxicity to algae/aquatic plants	•	LC50 (algae): > 1,000 mg/l
mixture of sterically composition	sed	sebacates:
Ecotoxicology Assessment		
Acute aquatic toxicity	:	Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

# 12.2 Persistence and degradability

No data available

#### 12.3 Bioaccumulative potential

#### **Components:**

#### 1-methoxy-2-propanol:

Partition coefficient: n-		log Pow: -0.437
octanol/water		

### mixture of sterically composed sebacates:

Partition coefficient: n-	:	log Pow: 2.37 - 2.77
octanol/water		pH: 7

#### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

# Product:

Product:	
Assessment	<ul> <li>This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.</li> </ul>



Version	Revision Date: 08.03.2024	SDS Number:	Date of last issue: 11.05.2023
2.0		MAT000401636	Date of first issue: 11.05.2023
2.0	00.00.2021	IE/EN	

### **12.6 Endocrine disrupting properties**

# Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

13.1 Waste treatment methods

Product:		
Additional ecological infor- mation	:	An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
		Harmful to aquatic life with long lasting effects.

### **SECTION 13: Disposal considerations**

Product	<ul> <li>The product should not be allowed to enter drains, water courses or the soil.</li> <li>Do not contaminate ponds, waterways or ditches with chemical or used container.</li> <li>Send to a licensed waste management company.</li> </ul>
Contaminated packaging	: Empty remaining contents.

·	5 5	Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.
Waste Code	:	08 00 00, WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS 08 01 00, wastes from MFSU and removal of paint and var- nish 08 01 11, waste paint and varnish containing organic solvents or other hazardoussubstances 15 00 00, WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED 15 01 00, packaging (including separately collected municipal packaging waste) 15 01 10, packaging containing residues of or contaminated by hazardoussubstances HP3, Flammable



Version 2.0	Revision Date: 08.03.2024	SDS Number: MAT000401636 IE/EN	Date of last issue: 11.05.2023 Date of first issue: 11.05.2023
----------------	------------------------------	--------------------------------------	---

# **SECTION 14: Transport information**

### 14.1 UN number or ID number

ADN	:	UN 1263
ADR	:	UN 1263
RID	:	UN 1263
IMDG	:	UN 1263
ΙΑΤΑ	:	UN 1263
14.2 UN proper shipping name		
ADN	:	PAINT
ADR	:	PAINT
RID	:	PAINT
IMDG	:	PAINT
ΙΑΤΑ	:	Paint

# 14.3 Transport hazard class(es)

		Class
ADN	:	3
ADR	:	3
RID	:	3
IMDG	:	3
ΙΑΤΑ	:	3

# 14.4 Packing group

#### ADN

Packing group Classification Code Hazard Identification Number Labels	: : : :	III F1 30 3
ADR Packing group Classification Code Hazard Identification Number Labels Tunnel restriction code		III F1 30 3 (D/E)
<b>RID</b> Packing group Classification Code Hazard Identification Number Labels	: : : : : : : : : : : : : : : : : : : :	III F1 30 3

Subsidiary risks

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



# **TESSAROL** Antik 3in1 anthracite

Vers 2.0	sion	Revision Date: 08.03.2024		Number: 000401636 I	Date of last issue: 11.05.2023 Date of first issue: 11.05.2023
	Labels EmS C IATA ( Packin aircraft Packin Packin Labels IATA ( Packin ger airc	Cargo) g instruction (cargo ) g instruction (LQ) g group Passenger) g instruction (passe	: : : : : : : : : : : : : : : : : : :	III 3 F-E, <u>S-E</u> 366 Y344 III Flammable Liquids 355 Y344	
		g group	:	III Flammable Liquids	
14.5	5 Enviro	nmental hazards			
	<b>ADN</b> Enviror	nmentally hazardous	s :	no	
	ADR Enviror	nmentally hazardous	s :	no	
	<b>RID</b> Enviror	nmentally hazardous	s :	no	
	<b>IMDG</b> Marine	pollutant	:	no	
14.6	6 Specia	al precautions for u	user		
	Remar	ks	:	goods/merchandise IMDG: Packages sm	aller than or equal to 450 litres, not ofClass 3 (exemption ADR 2.2.3.1.5) haller than or equal to 450 litres, not ofClass 3; "transport acc. IMDG-code

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

# **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on : Conditions of restriction for the fol-

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



# **TESSAROL** Antik 3in1 anthracite

Versio 2.0	on	Revision Date: 08.03.2024		Number: )00401636 			e of last issue: 11.05.2023 e of first issue: 11.05.2023
the market and use of certain dangerous substances, mixtures and articles (Annex XVII)					lowing entries should be considered: Number on list 75, 3		
							If you intend to use this product as tattoo ink, please contact your ven- dor.
		I - Candidate List o n for Authorisation			High	:	Not applicable
R	Regulat	tion (EC) No 1005/2			hat de-	:	Not applicable
Ŕ	Regulat	e ozone layer tion (EU) 2019/102	1 on pe	ersistent organi	c pollu-	:	Not applicable
R	nent ar	ecast) tion (EU) No 649/20 nd the Council cond erous chemicals				:	Not applicable
R		I - List of substance	es subj	ect to authorisa	ation	:	Not applicable
p C	ean Pa control	III: Directive 2012/ arliament and of the of major-accident h ous substances.	e Coun	cil on the	P5c	FLA	MMABLE LIQUIDS
V	/olatile	organic compound	ls :	Directive 200 Volatile orgar			ls (VOC) content: 500 g/l

### Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

### 15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

### **SECTION 16: Other information**

### Full text of H-Statements

H226 :	Flammable liquid and vapour.
H302 :	Harmful if swallowed.
H304 :	May be fatal if swallowed and enters airways.
H315 :	Causes skin irritation.
H317 :	May cause an allergic skin reaction.
H318 :	Causes serious eye damage.
H336 :	May cause drowsiness or dizziness.
H360D :	May damage the unborn child.
H361f :	Suspected of damaging fertility.
H400 :	Very toxic to aquatic life.
H410 :	Very toxic to aquatic life with long lasting effects.

# Full text of other abbreviations

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



# **TESSAROL** Antik 3in1 anthracite

Version 2.0	08.03.2024		Number: 000401636	Date of last issue: 11.05.2023 Date of first issue: 11.05.2023		
Acute	Tox		Acute toxicity			
	c Acute	:	Short-term (acute)	) aquatic bazard		
	c Chronic		Long-term (chroni			
Asp. T			Aspiration hazard			
Eye Da			Serious eye dama			
Flam.		÷	Flammable liquids			
Repr.		÷	Reproductive toxi			
Skin Ir	rit.		Skin irritation			
Skin S	ens.	:	Skin sensitisation			
STOT SE		:	Specific target organ toxicity - single exposure			
2000/39/EC		:	Europe. Commission Directive 2000/39/EC establishing a first			
				ccupational exposure limit values		
2004/3	37/EC	:	Europe. Directive	2004/37/EC on the protection of workers		
			from the risks rela	ted to exposure to carcinogens or mutagens		
			at work			
IE OEI	_	:	Ireland. List of Ch	emical Agents and Carcinogens with Occu-		
			pational Exposure	Elimit Values - Code of Practice, Schedule 1		
			and 2			
	9/EC / TWA	:	Limit Value - eight			
	9/EC / STEL	:	Short term exposu			
	37/EC / TWA	:	Long term exposu			
	_ / OELV - 8 hrs (TW)	A) :		osure limit value (8-hour reference period)		
-	_ / OELV - 15 min	:		osure limit value (15-minute reference peri-		
(STEL	)		od)			

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA -European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance: PICCS - Philippines Inventory of Chemicals and Chemical Substances: (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous



Version	Revision Date:	SDS Number:	Date of last issue: 11.05.2023	
2.0	08.03.2024	MAT000401636 IE/EN	Date of first issue: 11.05.2023	

Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information					
Classification of the n	nixture:	Classification procedure:			
Flam. Liq. 3	H226	Based on product data or assessment			
STOT SE 3	H336	Calculation method			
Aquatic Chronic 3	H412	Calculation method			

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.