

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



M NITRO CLEANING AGENT

Version	Revision Date:	SDS Number:	Date of last issue: 26.11.2020
2.0	09.10.2023	MAT000480847	Date of first issue: 26.11.2020
		SI/EN	

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : M NITRO CLEANING AGENT

Product code : 48084706

Unique Formula Identifier (UFI) : 3881-W0X5-000M-4S6Q

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Professional and consumer use of coatings
PC9a Coatings and paints, thinners, paint removers

1.3 Details of the supplier of the safety data sheet

Company : HGtrade d.o.o.
Količevo 100
1230 Domžale
Slovenia

Telephone Company : 01 7298 200

Responsible/issuing person : 01 7298 200
kemijskavarnost@hgtrade.si

1.4 Emergency telephone number

V nujnih primerih poklicati 112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2	H225: Highly flammable liquid and vapour.
Skin irritation, Category 2	H315: Causes skin irritation.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.
Specific target organ toxicity - repeated exposure, Category 2	H373: May cause damage to organs through prolonged or repeated exposure.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



M NITRO CLEANING AGENT

Version 2.0
Revision Date: 09.10.2023
SDS Number: MAT000480847
SI/EN

Date of last issue: 26.11.2020
Date of first issue: 26.11.2020

Aspiration hazard, Category 1

H304: May be fatal if swallowed and enters airways.

Long-term (chronic) aquatic hazard, Category 3

H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements :

- H225 Highly flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H412 Harmful to aquatic life with long lasting effects.

Precautionary statements :

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.

Prevention:

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:

- P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
- P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.
- P331 Do NOT induce vomiting.
- P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

- P405 Store locked up.

Disposal:

- P501 Dispose of contents/ container to an approved waste disposal plant.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



M NITRO CLEANING AGENT

Version
2.0

Revision Date:
09.10.2023

SDS Number:
MAT000480847
SI/EN

Date of last issue: 26.11.2020
Date of first issue: 26.11.2020

Hazardous components which must be listed on the label:

n-butyl acetate
reaction mixture of ethylbenzene, m-xylene and p-xylene
hydrocarbons, C6-C7, isoalkanes, cyclic, <5% n-hexane
butan-1-ol

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
n-butyl acetate	123-86-4 204-658-1 607-025-00-1 01-2119485493-29	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) EUH066	>= 20 - < 30
reaction mixture of ethylbenzene, m-xylene and p-xylene	- 905-562-9 01-2119555267-33	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 Asp. Tox. 1; H304	>= 20 - < 30
hydrocarbons, C6-C7, isoalkanes, cyclic, <5% n-hexane	- 01-2119486291-36	Flam. Liq. 2; H225 STOT SE 3; H336 (Central nervous system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>= 10 - < 20
ethyl acetate	141-78-6 205-500-4 607-022-00-5 01-2119475103-46	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system) EUH066	>= 10 - < 20
butan-1-ol	71-36-3 200-751-6 603-004-00-6	Flam. Liq. 3; H226 Acute Tox. 4; H302 Skin Irrit. 2; H315	>= 10 - < 20

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



M NITRO CLEANING AGENT

Version
2.0

Revision Date:
09.10.2023

SDS Number:
MAT000480847
SI/EN

Date of last issue: 26.11.2020
Date of first issue: 26.11.2020

	01-2119484630-38	Eye Dam. 1; H318 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system)	
ethanol	64-17-5 200-578-6 603-002-00-5 01-2119457610-43	Flam. Liq. 2; H225 Eye Irrit. 2; H319	$\geq 1 - < 10$
n-hexane	110-54-3 203-777-6 601-037-00-0 01-2119480412-44	Flam. Liq. 2; H225 Skin Irrit. 2; H315 Repr. 2; H361f STOT SE 3; H336 (Central nervous system) STOT RE 2; H373 Asp. Tox. 1; H304 Aquatic Chronic 2; H411 specific concentration limit STOT RE 2; H373 $\geq 5\%$	$\geq 0,25 - < 1$
toluene	108-88-3 203-625-9 601-021-00-3 01-2119471310-51	Flam. Liq. 2; H225 Skin Irrit. 2; H315 Repr. 2; H361d STOT SE 3; H336 (Central nervous system) STOT RE 2; H373 Asp. Tox. 1; H304 Aquatic Chronic 3; H412	$\geq 0,1 - < 0,25$

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
Symptoms of poisoning may appear several hours later.
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If skin irritation persists, call a physician.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



M NITRO CLEANING AGENT

Version	Revision Date:	SDS Number:	Date of last issue: 26.11.2020
2.0	09.10.2023	MAT000480847	Date of first issue: 26.11.2020
		SI/EN	

If on skin, rinse well with water.
If on clothes, remove clothes.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

Risks : May be fatal if swallowed and enters airways.
Causes skin irritation.
Causes serious eye damage.
May cause respiratory irritation.
May cause drowsiness or dizziness.
May cause damage to organs through prolonged or repeated exposure.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Cool closed containers exposed to fire with water spray.

5.3 Advice for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



M NITRO CLEANING AGENT

Version	Revision Date:	SDS Number:	Date of last issue: 26.11.2020
2.0	09.10.2023	MAT000480847	Date of first issue: 26.11.2020
		SI/EN	

for firefighters

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For disposal considerations see section 13., For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Container may be opened only under exhaust ventilation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



M NITRO CLEANING AGENT

Version
2.0

Revision Date:
09.10.2023

SDS Number:
MAT000480847
SI/EN

Date of last issue: 26.11.2020
Date of first issue: 26.11.2020

- hood.
Open drum carefully as content may be under pressure.
To avoid spills during handling keep bottle on a metal tray.
Dispose of rinse water in accordance with local and national regulations.
- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.
- Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

- Specific use(s) : Consult the technical guidelines for the use of this substance/mixture.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
n-butyl acetate	123-86-4	MV	50 ppm 241 mg/m ³	SI OEL
		KTV	150 ppm 723 mg/m ³	SI OEL
		STEL	150 ppm 723 mg/m ³	2019/1831/EU
Further information: Indicative				
		TWA	50 ppm 241 mg/m ³	2019/1831/EU
Further information: Indicative				
reaction mixture of ethylbenzene, m-xylene and p-xylene	1330-20-7	TWA	50 ppm 221 mg/m ³	2000/39/EC
Further information: Identifies the possibility of significant uptake through the skin, Indicative				

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



M NITRO CLEANING AGENT

Version
2.0

Revision Date:
09.10.2023

SDS Number:
MAT000480847
SI/EN

Date of last issue: 26.11.2020
Date of first issue: 26.11.2020

		STEL	100 ppm 442 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		KTV	100 ppm 442 mg/m ³	SI OEL
	Further information: The properties of easier transport of substances into organism through (via) the skin			
		MV	50 ppm 221 mg/m ³	SI OEL
	Further information: The properties of easier transport of substances into organism through (via) the skin			
ethyl acetate	141-78-6	STEL	400 ppm 1.468 mg/m ³	2017/164/EU
	Further information: Indicative			
		TWA	200 ppm 734 mg/m ³	2017/164/EU
	Further information: Indicative			
		MV	200 ppm 734 mg/m ³	SI OEL
		KTV	400 ppm 1.468 mg/m ³	SI OEL
butan-1-ol	71-36-3	MV	100 ppm 310 mg/m ³	SI OEL
		KTV	100 ppm 310 mg/m ³	SI OEL
ethanol	64-17-5	MV	500 ppm 960 mg/m ³	SI OEL
		KTV	1.000 ppm 1.920 mg/m ³	SI OEL
n-hexane	110-54-3	TWA	20 ppm 72 mg/m ³	2006/15/EC
	Further information: Indicative			
		MV	20 ppm 72 mg/m ³	SI OEL
	Further information: Toxic for reproduction - may cause harm to the unborn child - category 2			
		KTV	160 ppm 576 mg/m ³	SI OEL
	Further information: Toxic for reproduction - may cause harm to the unborn child - category 2			
toluene	108-88-3	TWA	50 ppm 192 mg/m ³	2006/15/EC
	Further information: Indicative, Identifies the possibility of significant uptake through the skin			
		STEL	100 ppm 384 mg/m ³	2006/15/EC
	Further information: Indicative, Identifies the possibility of significant uptake through the skin			
		MV	50 ppm 192 mg/m ³	SI OEL

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



M NITRO CLEANING AGENT

Version
2.0

Revision Date:
09.10.2023

SDS Number:
MAT000480847
SI/EN

Date of last issue: 26.11.2020
Date of first issue: 26.11.2020

Further information: Toxic for reproduction - may cause harm to the unborn child - category 2, The properties of easier transport of substances into organism through (via) the skin				
		KTV	100 ppm 384 mg/m ³	SI OEL
Further information: Toxic for reproduction - may cause harm to the unborn child - category 2, The properties of easier transport of substances into organism through (via) the skin				

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
reaction mixture of ethylbenzene, m-xylene and p-xylene	1330-20-7	methylhippuric acid (all isomers): 2 g/l (Urine)	End of shift	SI BAT
butan-1-ol	71-36-3	1-butanol: 2 mg/g Creatinine (Urine)	Prior to shift	SI BAT
		1-butanol: 10 mg/g Creatinine (Urine)	End of shift	SI BAT
n-hexane	110-54-3	2,5-hexandion and 4,5-dihydroxy-2-hexanone: 5 mg/l (Urine)	End of shift	SI BAT
toluene	108-88-3	toluene: 600 micromol per litre (Blood)	End of shift	SI BAT
		toluene: 75 µg/l (Urine)	End of shift	SI BAT
		o-cresol: 1,5 mg/l (Urine)	during long-term exposure: at the end of the work shift after several consecutive work-days, End of shift	SI BAT

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
n-butyl acetate	Workers	Inhalation	Acute systemic effects	600 mg/m ³
	Workers	Inhalation	Acute local effects	600 mg/m ³
	Workers	Inhalation	Long-term systemic effects	48 mg/m ³
	Workers	Inhalation	Long-term local effects	300 mg/m ³
	Consumers	Inhalation	Acute systemic effects	300 mg/m ³
	Consumers	Inhalation	Acute local effects	300 mg/m ³
	Consumers	Inhalation	Long-term systemic effects	12 mg/m ³
	Consumers	Inhalation	Long-term local effects	35,7 mg/m ³

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



M NITRO CLEANING AGENT

Version
2.0

Revision Date:
09.10.2023

SDS Number:
MAT000480847
SI/EN

Date of last issue: 26.11.2020
Date of first issue: 26.11.2020

			fects	
	Consumers	Dermal	Long-term systemic effects	3,4 mg/kg bw/day
	Consumers	Dermal	Acute systemic effects	6 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	2 mg/kg bw/day
	Consumers	Oral	Acute systemic effects	2 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	7 mg/kg bw/day
	Workers	Dermal	Acute systemic effects	11 mg/kg bw/day
reaction mixture of ethylbenzene, m-xylene and p-xylene	Workers	Inhalation	Long-term systemic effects	77 mg/m3
	Consumers	Inhalation	Long-term local effects	65,3 mg/m3
	Workers	Inhalation	Acute systemic effects	442 mg/m3
	Workers	Inhalation	Acute local effects	289 mg/m3
	Consumers	Inhalation	Acute systemic effects	260 mg/m3
	Workers	Inhalation	Long-term local effects	221 mg/m3
	Consumers	Inhalation	Long-term systemic effects	14,8 mg/m3
	Consumers	Inhalation	Acute local effects	260 mg/m3
	Consumers	Dermal	Long-term systemic effects	108 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	16 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	180 mg/kg bw/day
hydrocarbons, C6-C7, isoalkanes, cyclic, <5% n-hexane	Workers	Inhalation	Long-term systemic effects	5306 mg/m3
	Consumers	Inhalation	Long-term systemic effects	1131 mg/m3
	Consumers	Oral	Long-term systemic effects	1301 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	13964 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	1377 mg/kg bw/day
ethyl acetate	Workers	Inhalation	Acute systemic effects	1468 mg/m3
	Workers	Inhalation	Long-term local effects	1468 mg/m3
	Workers	Inhalation	Long-term systemic effects	734 mg/m3
	Workers	Inhalation	Long-term local ef-	734 mg/m3

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



M NITRO CLEANING AGENT

Version
2.0

Revision Date:
09.10.2023

SDS Number:
MAT000480847
SI/EN

Date of last issue: 26.11.2020
Date of first issue: 26.11.2020

			fects	
	Consumers	Inhalation	Acute systemic effects	734 mg/m3
	Consumers	Inhalation	Acute local effects	734 mg/m3
	Consumers	Inhalation	Long-term systemic effects	367 mg/m3
	Consumers	Inhalation	Long-term local effects	367 mg/m3
	Workers	Dermal	Long-term systemic effects	63 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	37 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	4,5 mg/kg bw/day
butan-1-ol	Workers	Inhalation	Long-term local effects	310 mg/m3
	Consumers	Inhalation	Long-term systemic effects	55,357 mg/m3
	Consumers	Inhalation	Long-term local effects	155 mg/m3
	Consumers	Dermal	Long-term systemic effects	3,125 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	1,562 mg/kg bw/day
ethanol	Workers	Inhalation	Long-term systemic effects	950 mg/m3
	Consumers	Inhalation	Acute local effects	950 mg/m3
	Workers	Inhalation	Acute local effects	1900 mg/m3
	Consumers	Inhalation	Long-term systemic effects	114 mg/m3
	Consumers	Oral	Long-term systemic effects	87 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	343 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	206 mg/kg bw/day
toluene	Workers	Inhalation	Long-term systemic effects	192 mg/m3
	Workers	Inhalation	Long-term local effects	192 mg/m3
	Consumers	Inhalation	Acute systemic effects	226 mg/m3
	Consumers	Inhalation	Acute local effects	226 mg/m3

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
n-butyl acetate	Soil	0,0903 mg/kg dry weight (d.w.)
	Marine water	0,018 mg/l
	Fresh water	0,18 mg/l
	Marine sediment	0,0981 mg/kg dry weight (d.w.)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



M NITRO CLEANING AGENT

Version
2.0

Revision Date:
09.10.2023

SDS Number:
MAT000480847
SI/EN

Date of last issue: 26.11.2020
Date of first issue: 26.11.2020

	Fresh water sediment	0,981 mg/kg dry weight (d.w.)
	Sewage treatment plant	35,6 mg/l
	Intermittent use/release	0,36 mg/l
reaction mixture of ethylbenzene, m-xylene and p-xylene	Soil	2,31 mg/kg dry weight (d.w.)
	Marine water	0,327 mg/l
	Fresh water	0,327 mg/l
	Marine sediment	12,46 mg/kg dry weight (d.w.)
	Fresh water sediment	12,46 mg/kg dry weight (d.w.)
	Sewage treatment plant	6,58 mg/l
	Intermittent use/release	0,327 mg/l
ethyl acetate	Soil	0,24 mg/kg dry weight (d.w.)
	Marine water	0,026 mg/l
	Fresh water	0,26 mg/l
	Marine sediment	0,125 mg/kg dry weight (d.w.)
	Fresh water sediment	1,25 mg/kg dry weight (d.w.)
	Sewage treatment plant	650 mg/l
	Intermittent use/release	1,65 mg/l
butan-1-ol	Soil	0,0166 mg/kg dry weight (d.w.)
	Marine water	0,0082 mg/l
	Fresh water	0,082 mg/l
	Marine sediment	0,0324 mg/kg dry weight (d.w.)
	Fresh water sediment	0,324 mg/kg dry weight (d.w.)
	Sewage treatment plant	2476 mg/l
	Intermittent use/release	2,25 mg/l
ethanol	Soil	0,63 mg/kg dry weight (d.w.)
	Marine water	0,79 mg/l
	Fresh water	0,96 mg/l
	Marine sediment	2,9 mg/kg dry weight (d.w.)
	Fresh water sediment	3,6 mg/kg dry weight (d.w.)
	Sewage treatment plant	580 mg/l
toluene	Soil	2,89 mg/kg dry weight (d.w.)
	Marine water	0,68 mg/l
	Fresh water	0,68 mg/l
	Marine sediment	16,39 mg/kg dry weight (d.w.)
	Fresh water sediment	16,39 mg/kg dry weight (d.w.)
	Sewage treatment plant	13,61 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



M NITRO CLEANING AGENT

Version	Revision Date:	SDS Number:	Date of last issue: 26.11.2020
2.0	09.10.2023	MAT000480847	Date of first issue: 26.11.2020
		SI/EN	

	Intermittent use/release	0,68 mg/l
--	--------------------------	-----------

8.2 Exposure controls

Personal protective equipment

- | | | |
|--------------------------|---|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Eye/face protection | : | Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems. |
| Hand protection | : | |
| Remarks | : | The suitability for a specific workplace should be discussed with the producers of the protective gloves. |
| Skin and body protection | : | Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place. |
| Respiratory protection | : | Wear a full face respirator conforming to EN136 with Type A/P2 filter or better.
Self-contained closed-circuit breathing apparatus compressed (EN 145)
In the case of aerosol and mist formation use an approved respirator filter (EN 141). |

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- | | | |
|--------------------------------------------------|---|----------------------------------------------------------------------|
| Physical state | : | liquid |
| Colour | : | in accordance with the product description |
| Odour | : | solvent-like |
| Odour Threshold | : | No data available |
| Melting point/freezing point | : | -83,6 °C (calculation method (principal components, lowest value)) |
| Boiling point/boiling range | : | 77 °C (calculation method (principal components, lowest value)) |
| Upper explosion limit / Upper flammability limit | : | 11,3 %(V) (calculation method (principal components, highest value)) |
| Lower explosion limit / Lower flammability limit | : | 1,1 %(V) (calculation method (principal components, highest value)) |
| Flash point | : | -12 °C |
| Ignition temperature | : | 343 °C (calculation method (principal components, highest value)) |
| Decomposition temperature | : | No decomposition if stored and applied as directed. |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



M NITRO CLEANING AGENT

Version	Revision Date:	SDS Number:	Date of last issue: 26.11.2020
2.0	09.10.2023	MAT000480847	Date of first issue: 26.11.2020
		SI/EN	

Hazardous decomposition products formed under fire conditions.

pH : No data available

Viscosity
Viscosity, kinematic : < 20,5 mm²/s (40 °C)

Solubility(ies)
Water solubility : immiscible, partly soluble
Solubility in other solvents : Description: miscible with most organic solvents

Partition coefficient: n-octanol/water : log Pow: 2,77 - 3,15 (calculation method (principal components, highest value))

Vapour pressure : 11 kPa (calculation method (principal components, highest value))
(20 °C)

Density : 0,82 - 0,84 g/cm³

9.2 Other information

Oxidizing properties : Sustains combustion

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Not applicable

10.6 Hazardous decomposition products

Adequate ventilation is required.

Heating can release vapours which can be ignited.

Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



M NITRO CLEANING AGENT

Version	Revision Date:	SDS Number:	Date of last issue: 26.11.2020
2.0	09.10.2023	MAT000480847	Date of first issue: 26.11.2020
		SI/EN	

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

Components:

n-butyl acetate:

Acute oral toxicity : LD50 Oral (Rat): >= 10.760 mg/kg

Acute dermal toxicity : LD50 (Rabbit): >= 5.000 mg/kg

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Acute oral toxicity : LD50 Oral (Rat): >= 8.700 mg/kg

Acute inhalation toxicity : LC50 (Rat): 27,14 mg/l
Test atmosphere: vapour

Acute dermal toxicity : Assessment: The component/mixture is moderately toxic after single contact with skin.

ethyl acetate:

Acute oral toxicity : LD50 Oral (Rat): >= 5.620 mg/kg

Acute inhalation toxicity : LC50 (Rat): 1600 ppm
Exposure time: 8 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): >= 20.000 mg/kg

butan-1-ol:

Acute oral toxicity : Assessment: The component/mixture is moderately toxic after single ingestion.

LD50 Oral (Rat): > 2.000 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



M NITRO CLEANING AGENT

Version	Revision Date:	SDS Number:	Date of last issue: 26.11.2020
2.0	09.10.2023	MAT000480847	Date of first issue: 26.11.2020
		SI/EN	

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg

ethanol:

Acute oral toxicity : LD50 Oral (Rat): >= 7.060 mg/kg

Acute inhalation toxicity : LC50 (Rat): >= 39 mg/l
Exposure time: 4 h
Test atmosphere: vapour

toluene:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 28 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks : Extremely corrosive and destructive to tissue.

Components:

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Result : irritating

butan-1-ol:

Result : irritating

n-hexane:

Result : irritating

toluene:

Result : irritating

Serious eye damage/eye irritation

Causes serious eye damage.

Product:

Remarks : May cause irreversible eye damage.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



M NITRO CLEANING AGENT

Version
2.0

Revision Date:
09.10.2023

SDS Number:
MAT000480847
SI/EN

Date of last issue: 26.11.2020
Date of first issue: 26.11.2020

Components:

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Result : Eye irritation

ethyl acetate:

Result : Eye irritation

butan-1-ol:

Result : Corrosive

ethanol:

Result : Eye irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

Components:

n-hexane:

Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments.

toluene:

Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments.

STOT - single exposure

May cause respiratory irritation.

May cause drowsiness or dizziness.

Components:

n-butyl acetate:

Assessment : May cause drowsiness or dizziness.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



M NITRO CLEANING AGENT

Version	Revision Date:	SDS Number:	Date of last issue: 26.11.2020
2.0	09.10.2023	MAT000480847	Date of first issue: 26.11.2020
		SI/EN	

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Assessment : May cause respiratory irritation.

hydrocarbons, C6-C7, isoalkanes, cyclic, <5% n-hexane:

Assessment : May cause drowsiness or dizziness.

ethyl acetate:

Assessment : May cause drowsiness or dizziness.

butan-1-ol:

Assessment : May cause drowsiness or dizziness.

Assessment : May cause respiratory irritation.

n-hexane:

Assessment : May cause drowsiness or dizziness.

toluene:

Assessment : May cause drowsiness or dizziness.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Components:

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Assessment : May cause damage to organs through prolonged or repeated exposure.

n-hexane:

Assessment : May cause damage to organs through prolonged or repeated exposure.

toluene:

Assessment : May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

May be fatal if swallowed and enters airways.

Components:

reaction mixture of ethylbenzene, m-xylene and p-xylene:

May be fatal if swallowed and enters airways.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



M NITRO CLEANING AGENT

Version	Revision Date:	SDS Number:	Date of last issue: 26.11.2020
2.0	09.10.2023	MAT000480847	Date of first issue: 26.11.2020
		SI/EN	

hydrocarbons, C6-C7, isoalkanes, cyclic, <5% n-hexane:

May be fatal if swallowed and enters airways.

n-hexane:

May be fatal if swallowed and enters airways.

toluene:

May be fatal if swallowed and enters airways.

11.2 Information on other hazards

Further information

Product:

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.
Concentrations substantially above the TLV value may cause narcotic effects.
Solvents may degrease the skin.

SECTION 12: Ecological information

12.1 Toxicity

Components:

n-butyl acetate:

Toxicity to algae/aquatic plants : NOEC (Desmodesmus subspicatus (green algae)): > 200 mg/l
EC50 (Desmodesmus subspicatus (green algae)): >= 647,7 mg/l
Exposure time: 72 h

Toxicity to microorganisms : IC50 (Tetrahymena pyriformis): 356 mg/l
Exposure time: 40 h

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Toxicity to fish : LC50 (Fish): >= 1 - 10 mg/l

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)): >= 1 - 10 mg/l

Toxicity to microorganisms : EC50 (Bacteria): >= 1 - 100 mg/l

hydrocarbons, C6-C7, isoalkanes, cyclic, <5% n-hexane:

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



M NITRO CLEANING AGENT

Version	Revision Date:	SDS Number:	Date of last issue: 26.11.2020
2.0	09.10.2023	MAT000480847	Date of first issue: 26.11.2020
		SI/EN	

butan-1-ol:

Toxicity to fish : LC50 (Fish): > 1.000 mg/l

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)): > 1.000 mg/l

Toxicity to microorganisms : EC50 (Bacteria): > 1.000 mg/l

ethanol:

Toxicity to fish : LC50 (Fish): >= 13.500 mg/l

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)): >= 5.000 mg/l

n-hexane:

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

toluene:

Ecotoxicology Assessment

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

12.2 Persistence and degradability

Components:

n-butyl acetate:

Biodegradability : Result: Biodegradable
Biodegradation: 83 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

Stability in water : Degradation half life: 78 d
pH: 8
Hydrolyses slowly.

Photodegradation : Decomposes rapidly in contact with light.

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Biodegradability : Readily biodegradable.

Photodegradation : Decomposes rapidly in contact with light.

12.3 Bioaccumulative potential

Components:

n-butyl acetate:

Bioaccumulation : Bioconcentration factor (BCF): 15
Bioaccumulation is unlikely.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



M NITRO CLEANING AGENT

Version	Revision Date:	SDS Number:	Date of last issue: 26.11.2020
2.0	09.10.2023	MAT000480847	Date of first issue: 26.11.2020
		SI/EN	

Partition coefficient: n-octanol/water : log Pow: 1,81

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Bioaccumulation : Bioconcentration factor (BCF): 25,9
Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water : log Pow: 2,77 - 3,15

ethyl acetate:

Partition coefficient: n-octanol/water : log Pow: 0,6

butan-1-ol:

Partition coefficient: n-octanol/water : log Pow: 0,785

ethanol:

Partition coefficient: n-octanol/water : log Pow: -0,32

toluene:

Partition coefficient: n-octanol/water : log Pow: 2,65

12.4 Mobility in soil

Components:

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Distribution among environmental compartments : Koc: 537, log Koc: 2,73
Moderately mobile in soils
The product evaporates from soil.

Stability in soil : Dissipation time: 23 d
Percentage dissipation: 50 % (DT50)

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



M NITRO CLEANING AGENT

Version	Revision Date:	SDS Number:	Date of last issue: 26.11.2020
2.0	09.10.2023	MAT000480847	Date of first issue: 26.11.2020
		SI/EN	

Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	: The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.
Contaminated packaging	: Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.
Waste Code	: 08 01 11, waste paint and varnish containing organic solvents or other hazardous substances

SECTION 14: Transport information

14.1 UN number or ID number

ADN	: UN 1263
ADR	: UN 1263
RID	: UN 1263
IMDG	: UN 1263
IATA	: UN 1263

14.2 UN proper shipping name

ADN	: PAINT RELATED MATERIAL
ADR	: PAINT RELATED MATERIAL
RID	: PAINT RELATED MATERIAL
IMDG	: PAINT RELATED MATERIAL
IATA	: Paint related material

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADN	: 3	
ADR	: 3	
RID	: 3	
IMDG	: 3	
IATA	: 3	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



M NITRO CLEANING AGENT

Version 2.0 Revision Date: 09.10.2023 SDS Number: MAT000480847
SI/EN

Date of last issue: 26.11.2020
Date of first issue: 26.11.2020

14.4 Packing group

ADN

Packing group : II
Classification Code : F1
Hazard Identification Number : 33
Labels : 3

ADR

Packing group : II
Classification Code : F1
Hazard Identification Number : 33
Labels : 3
Tunnel restriction code : (D/E)

RID

Packing group : II
Classification Code : F1
Hazard Identification Number : 33
Labels : 3

IMDG

Packing group : II
Labels : 3
EmS Code : F-E, S-E

IATA (Cargo)

Packing instruction (cargo aircraft) : 364
Packing instruction (LQ) : Y341
Packing group : II
Labels : Flammable Liquids

IATA (Passenger)

Packing instruction (passenger aircraft) : 353
Packing instruction (LQ) : Y341
Packing group : II
Labels : Flammable Liquids

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



M NITRO CLEANING AGENT

Version	Revision Date:	SDS Number:	Date of last issue: 26.11.2020
2.0	09.10.2023	MAT000480847	Date of first issue: 26.11.2020
		SI/EN	

Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:
Number on list 3
toluene (Number on list 48)
benzene (Number on list 72, 5, 29, 28)

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P5c FLAMMABLE LIQUIDS

Other regulations:

Chemicals Act

Environment Protection Act

Decree on waste

Decree on the management of packaging and packaging waste

Rules on the protection of workers from the risks related to exposure to chemical substances at work (Official Gazette of RS, no. 72/21)

Rules on personal protective equipment used by workers at work

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



M NITRO CLEANING AGENT

Version	Revision Date:	SDS Number:	Date of last issue: 26.11.2020
2.0	09.10.2023	MAT000480847	Date of first issue: 26.11.2020
		SI/EN	

SECTION 16: Other information

Full text of H-Statements

H225	: Highly flammable liquid and vapour.
H226	: Flammable liquid and vapour.
H302	: Harmful if swallowed.
H304	: May be fatal if swallowed and enters airways.
H312	: Harmful in contact with skin.
H315	: Causes skin irritation.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H361d	: Suspected of damaging the unborn child.
H361f	: Suspected of damaging fertility.
H373	: May cause damage to organs through prolonged or repeated exposure.
H411	: Toxic to aquatic life with long lasting effects.
H412	: Harmful to aquatic life with long lasting effects.
EUH066	: Repeated exposure may cause skin dryness or cracking.

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Eye Dam.	: Serious eye damage
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Repr.	: Reproductive toxicity
Skin Irrit.	: Skin irritation
STOT RE	: Specific target organ toxicity - repeated exposure
STOT SE	: Specific target organ toxicity - single exposure
2000/39/EC	: Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2006/15/EC	: Europe. Indicative occupational exposure limit values
2017/164/EU	: Europe. Commission Directive 2017/164/EU establishing a fourth list of indicative occupational exposure limit values
2019/1831/EU	: Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values
SI BAT	: Slovenia. BAT-values
SI OEL	: Slovenia. Chemical agents at work - Appendix 1: Occupational exposure limits
2000/39/EC / TWA	: Limit Value - eight hours
2000/39/EC / STEL	: Short term exposure limit
2006/15/EC / TWA	: Limit Value - eight hours
2006/15/EC / STEL	: Short term exposure limit
2017/164/EU / STEL	: Short term exposure limit
2017/164/EU / TWA	: Limit Value - eight hours
2019/1831/EU / TWA	: Limit Value - eight hours
2019/1831/EU / STEL	: Short term exposure limit
SI OEL / MV	: Time Weighted Average

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



M NITRO CLEANING AGENT

Version	Revision Date:	SDS Number:	Date of last issue: 26.11.2020
2.0	09.10.2023	MAT000480847	Date of first issue: 26.11.2020
		SI/EN	

SI OEL / KTV : Short Term Exposure Limit

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Flam. Liq. 2	H225
Skin Irrit. 2	H315
Eye Dam. 1	H318
STOT SE 3	H336
STOT SE 3	H335
STOT RE 2	H373
Asp. Tox. 1	H304
Aquatic Chronic 3	H412

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



M NITRO CLEANING AGENT

Version
2.0

Revision Date:
09.10.2023

SDS Number:
MAT000480847
SI/EN

Date of last issue: 26.11.2020
Date of first issue: 26.11.2020

ance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.