

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL HYDRO Base MIX

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	06.09.2023	MAT0GA05_010 IE/EN	Date of first issue: 06.09.2023

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : MOBIHEL HYDRO Base MIX

Product code : Please see section 16 for detailed data

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : PC9a Coatings and paints, thinners, paint removers

Recommended restrictions on use : Reserved for industrial and professional use.

#### 1.3 Details of the supplier of the safety data sheet

Company : Helios TBLUS d.o.o.  
Količevo 65  
1230 Domžale  
Slovenia

Telephone Company : 386 (1) 722 4383

Telefax Company : 386 (1) 722 4310

Responsible/issuing person : 386 (1) 722 4383  
productsafety@helios.si

#### 1.4 Emergency telephone number

01 809 2166 National Poisons Information Centre 01 809 2166

01 809 2566 Healthcare Professionals 01 809 2566

01 809 2566 Healthcare Professionals 01 809 2566

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Serious eye damage, Category 1 H318: Causes serious eye damage.

Reproductive toxicity, Category 1B H360D: May damage the unborn child.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL HYDRO Base MIX

Version 1.0      Revision Date: 06.09.2023      SDS Number: MAT0GA05\_010 IE/EN      Date of last issue: -  
Date of first issue: 06.09.2023

- Hazard pictograms :
- Signal word : Danger
- Hazard statements : H318 Causes serious eye damage.  
H360D May damage the unborn child.
- Precautionary statements : **Prevention:**  
P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.
- Response:**  
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.  
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
- Disposal:**  
P501 Dispose of contents/ container to an approved waste disposal plant.

### Hazardous components which must be listed on the label:

butan-1-ol  
N-methyl-2-pyrrolidone

### Additional Labelling

EUH208 Contains 1,2-benzisothiazol-3(2H)-one, 2-methylisothiazol-3(2H)-one, reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one and 2-methyl-2H -isothiazol-3-one (3:1). May produce an allergic reaction.

Restricted to professional users.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL HYDRO Base MIX

Version  
1.0

Revision Date:  
06.09.2023

SDS Number:  
MAT0GA05\_010  
IE/EN

Date of last issue: -  
Date of first issue: 06.09.2023

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

##### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
2-butoxyethanol	111-76-2 203-905-0 603-014-00-0 01-2119475108-36	Acute Tox. 4; H302 Acute Tox. 3; H331 Skin Irrit. 2; H315 Eye Irrit. 2; H319  Acute toxicity estimate  Acute oral toxicity: 1,200 mg/kg	>= 1 - < 10
butan-1-ol	71-36-3 200-751-6 603-004-00-6 01-2119484630-38	Flam. Liq. 3; H226 Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system)	>= 3 - < 10
N-methyl-2-pyrrolidone	872-50-4 212-828-1 606-021-00-7 01-2119472430-46	Acute Tox. 3; H331 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Repr. 1B; H360D STOT SE 3; H335 (Respiratory system)  specific concentration limit STOT SE 3; H335 >= 10 %  Acute toxicity estimate  Acute inhalation toxicity (vapour): 5.1 mg/l	>= 1 - < 10

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL HYDRO Base MIX

Version  
1.0

Revision Date:  
06.09.2023

SDS Number:  
MAT0GA05\_010  
IE/EN

Date of last issue: -  
Date of first issue: 06.09.2023

2-dimethylaminoethanol	108-01-0 203-542-8 603-047-00-0 01-2119492298-24	Flam. Liq. 3; H226 Acute Tox. 4; H302 Acute Tox. 3; H331 Acute Tox. 4; H312 Skin Corr. 1B; H314 Eye Dam. 1; H318 STOT SE 3; H335 (Respiratory system)  specific concentration limit STOT SE 3; H335 >= 5 %	>= 0.1 - < 1
1,2-benzisothiazol-3(2H)-one	2634-33-5 220-120-9 613-088-00-6 01-2120761540-60	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 2; H411  specific concentration limit Skin Sens. 1; H317 >= 0.05 %	>= 0.0025 - < 0.025
2-methylisothiazol-3(2H)-one	2682-20-4 220-239-6 613-326-00-9 01-2120764690-50	Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 3; H311 Skin Corr. 1B; H314 Eye Dam. 1; H318 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071  M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 1  specific concentration limit Skin Sens. 1A; H317 >= 0.0015 %	>= 0.0002 - < 0.0015
reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one and 2-	55965-84-9	Acute Tox. 3; H301 Acute Tox. 2; H330	>= 0.0002 - < 0.0015

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL HYDRO Base MIX

Version  
1.0

Revision Date:  
06.09.2023

SDS Number:  
MAT0GA05\_010  
IE/EN

Date of last issue: -  
Date of first issue: 06.09.2023

methyl-2H -isothiazol-3- one (3:1)	613-167-00-5 01-2120764691-48	Acute Tox. 2; H310 Skin Corr. 1C; H314 Eye Dam. 1; H318 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071  M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100  specific concentration limit Skin Corr. 1C; H314 >= 0.6 % Skin Irrit. 2; H315 0.06 - < 0.6 % Eye Irrit. 2; H319 0.06 - < 0.6 % Skin Sens. 1A; H317 >= 0.0015 % Eye Dam. 1; H318 >= 0.6 %
------------------------------------	----------------------------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of skin contact : If skin irritation persists, call a physician.  
If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.  
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
Continue rinsing eyes during transport to hospital.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL HYDRO Base MIX

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	06.09.2023	MAT0GA05_010 IE/EN	Date of first issue: 06.09.2023

---

Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.  
Do NOT induce vomiting.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.

### 4.2 Most important symptoms and effects, both acute and delayed

Risks : Causes serious eye damage.  
May damage the unborn child.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Carbon dioxide (CO<sub>2</sub>)

Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : No hazardous combustion products are known

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL HYDRO Base MIX

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	06.09.2023	MAT0GA05_010 IE/EN	Date of first issue: 06.09.2023

---

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

#### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).  
Keep in suitable, closed containers for disposal.

#### 6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

---

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol.  
Do not breathe vapours/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Provide sufficient air exchange and/or exhaust in work rooms.  
To avoid spills during handling keep bottle on a metal tray.  
Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.  
Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : When using do not eat or drink. When using do not smoke.  
Wash hands before breaks and at the end of workday.

#### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : No smoking. Keep in a well-ventilated place. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL HYDRO Base MIX

Version  
1.0

Revision Date:  
06.09.2023

SDS Number:  
MAT0GA05\_010  
IE/EN

Date of last issue: -  
Date of first issue: 06.09.2023

Further information on storage stability : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

Specific use(s) : For further information, refer to the product technical data sheet.

Consult the technical guidelines for the use of this substance/mixture.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
2-butoxyethanol	111-76-2	TWA	20 ppm 98 mg/m <sup>3</sup>	2000/39/EC
		Further information: Identifies the possibility of significant uptake through the skin, Indicative		
		STEL	50 ppm 246 mg/m <sup>3</sup>	2000/39/EC
		Further information: Identifies the possibility of significant uptake through the skin, Indicative		
		OELV - 8 hrs (TWA)	20 ppm 98 mg/m <sup>3</sup>	IE OEL
		Further information: Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body		
		OELV - 15 min (STEL)	50 ppm 246 mg/m <sup>3</sup>	IE OEL
		Further information: Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body		
butan-1-ol	71-36-3	OELV - 8 hrs (TWA)	20 ppm	IE OEL
aluminium	7429-90-5	OELV - 8 hrs (TWA) (Respirable dust)	1 mg/m <sup>3</sup>	IE OEL
N-methyl-2-pyrrolidone	872-50-4	TWA	10 ppm 40 mg/m <sup>3</sup>	2009/161/EU
		Further information: Identifies the possibility of significant uptake through the skin, Indicative		
		STEL	20 ppm 80 mg/m <sup>3</sup>	2009/161/EU
		Further information: Identifies the possibility of significant uptake through the skin, Indicative		
		OELV - 15 min (STEL)	20 ppm 80 mg/m <sup>3</sup>	IE OEL
		Further information: Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body		



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL HYDRO Base MIX

Version  
1.0

Revision Date:  
06.09.2023

SDS Number:  
MAT0GA05\_010  
IE/EN

Date of last issue: -  
Date of first issue: 06.09.2023

		OELV - 8 hrs (TWA)	10 ppm 40 mg/m <sup>3</sup>	IE OEL
	Further information: Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body			
		TWA	10 ppm 40 mg/m <sup>3</sup>	2004/37/EC
	Further information: Skin, Carcinogens or mutagens			
		STEL	20 ppm 80 mg/m <sup>3</sup>	2004/37/EC
	Further information: Skin, Carcinogens or mutagens			
titanium dioxide	13463-67-7	OELV - 8 hrs (TWA) (Respirable dust)	4 mg/m <sup>3</sup>	IE OEL
		OELV - 8 hrs (TWA) (inhalable dust)	10 mg/m <sup>3</sup>	IE OEL

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
2-butoxyethanol	Workers	Inhalation	Long-term systemic effects	98 mg/m <sup>3</sup>
	Workers	Inhalation	Acute systemic effects	1091 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	246 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term systemic effects	59 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute systemic effects	426 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute local effects	147 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	125 mg/kg bw/day
	Workers	Dermal	Acute systemic effects	89 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	75 mg/kg bw/day
	Consumers	Dermal	Acute systemic effects	89 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	6.3 mg/kg bw/day
	Consumers	Oral	Acute systemic effects	26.7 mg/kg bw/day
butan-1-ol	Workers	Inhalation	Long-term local effects	310 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term systemic effects	55.357 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local effects	155 mg/m <sup>3</sup>
	Consumers	Dermal	Long-term systemic effects	3.125 mg/kg bw/day
	Consumers	Oral	Long-term systemic	1.562 mg/kg

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL HYDRO Base MIX

Version  
1.0

Revision Date:  
06.09.2023

SDS Number:  
MAT0GA05\_010  
IE/EN

Date of last issue: -  
Date of first issue: 06.09.2023

			effects	bw/day
aluminium	Workers	Inhalation	Long-term systemic effects	3.72 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	3.72 mg/m <sup>3</sup>
	Consumers	Oral	Long-term systemic effects	3.95 mg/kg bw/day
N-methyl-2-pyrrolidone	Workers	Inhalation	Long-term local effects	40 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term systemic effects	14.4 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term systemic effects	3.6 mg/m <sup>3</sup>
	Workers	Dermal	Long-term systemic effects	4.8 mg/kg bw/day
	Consumers	Inhalation	Long-term local effects	4.5 mg/m <sup>3</sup>
	Consumers	Dermal	Long-term systemic effects	2.4 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	0.85 mg/kg bw/day
titanium dioxide	Workers	Inhalation	Long-term local effects	10 mg/m <sup>3</sup>
	Consumers	Oral	Long-term systemic effects	700 mg/kg bw/day
2-dimethylaminoethanol	Workers	Inhalation	Long-term systemic effects	7.4 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	22 mg/m <sup>3</sup>
	Workers	Dermal	Acute local effects	0.08 mg/cm <sup>2</sup>
	Workers	Dermal	Long-term systemic effects	1.04 mg/kg bw/day
	Workers	Dermal	Acute systemic effects	5 mg/kg bw/day
1,2-benzisothiazol-3(2H)-one	Workers	Inhalation	Long-term systemic effects	6.81 mg/m <sup>3</sup>
	Workers	Dermal	Long-term systemic effects	0.966 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	1.2 mg/m <sup>3</sup>
	Consumers	Dermal	Long-term systemic effects	0.345 mg/kg bw/day
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	Consumers	Inhalation	Acute local effects	0.04 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	0.02 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	0.04 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local effects	0.02 mg/m <sup>3</sup>
	Consumers	Oral	Long-term systemic	0.09 mg/kg

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL HYDRO Base MIX

Version  
1.0

Revision Date:  
06.09.2023

SDS Number:  
MAT0GA05\_010  
IE/EN

Date of last issue: -  
Date of first issue: 06.09.2023

			effects	bw/day
	Consumers	Oral	Acute systemic effects	0.11 mg/kg bw/day

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value	
2-butoxyethanol	Soil	2.33 mg/kg dry weight (d.w.)	
	Marine water	0.88 mg/l	
	Fresh water	8.8 mg/l	
	Fresh water sediment	34.6 mg/kg dry weight (d.w.)	
	Sewage treatment plant	463 mg/l	
	Intermittent use/release	9.1 mg/l	
butan-1-ol	Soil	0.0166 mg/kg dry weight (d.w.)	
	Marine water	0.0082 mg/l	
	Fresh water	0.082 mg/l	
	Marine sediment	0.0324 mg/kg dry weight (d.w.)	
	Fresh water sediment	0.324 mg/kg dry weight (d.w.)	
	Sewage treatment plant	2476 mg/l	
aluminium	Intermittent use/release	2.25 mg/l	
	Sewage treatment plant	20 mg/l	
	N-methyl-2-pyrrolidone	Soil	0.07 mg/kg dry weight (d.w.)
		Marine water	0.025 mg/l
		Fresh water	0.25 mg/l
		Fresh water sediment	1.09 mg/kg dry weight (d.w.)
Sewage treatment plant		10 mg/l	
Intermittent use/release		5 mg/l	
titanium dioxide	Marine sediment	0.109 mg/kg dry weight (d.w.)	
	Soil	100 mg/kg dry weight (d.w.)	
	Marine water	0.0184 mg/l	
	Fresh water	0.184 mg/l	
	Marine sediment	100 mg/kg dry weight (d.w.)	
	Fresh water sediment	1000 mg/kg dry weight (d.w.)	
2-dimethylaminoethanol	Sewage treatment plant	100 mg/l	
	Intermittent use/release	0.193 mg/l	
	Soil	0.0177 mg/kg dry weight (d.w.)	
	Marine water	0.00661 mg/l	
	Fresh water	0.0661 mg/l	
	Fresh water sediment	0.0529 mg/kg dry weight (d.w.)	
Sewage treatment plant	10 mg/l		

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL HYDRO Base MIX

Version  
1.0

Revision Date:  
06.09.2023

SDS Number:  
MAT0GA05\_010  
IE/EN

Date of last issue: -  
Date of first issue: 06.09.2023

	Intermittent use/release	0.0661 mg/l
1,2-benzisothiazol-3(2H)-one	Fresh water	0.00403 mg/l
	Intermittent use/release	0.0011 mg/l
	Marine water	0.000403 mg/l
	Sewage treatment plant	1.03 mg/l
	Fresh water sediment	0.0499 mg/kg dry weight (d.w.)
	Marine sediment	0.00499 mg/kg dry weight (d.w.)
	Soil	3 mg/kg dry weight (d.w.)
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H -isothiazol-3- one (3:1)	Soil	0.01 mg/kg dry weight (d.w.)
	Marine water	0.00339 mg/l
	Fresh water	0.00339 mg/l
	Marine sediment	0.027 mg/kg dry weight (d.w.)
	Fresh water sediment	0.027 mg/kg dry weight (d.w.)
	Sewage treatment plant	0.23 mg/l
	Intermittent use/release	0.00339 mg/l

### 8.2 Exposure controls

#### Personal protective equipment

Eye/face protection : Equipment should conform to EN 166  
Eye wash bottle with pure water  
Tightly fitting safety goggles  
Wear face-shield and protective suit for abnormal processing problems.

#### Hand protection

Gloves : Nitrile rubber (> 0,1 mm; < 60 min); DIN EN374 |  
butyl-rubber (> 0,6 mm; < 240 min); DIN EN374 |  
Viton® (> 0,6 mm; < 240 min); DIN EN374 |  
PE laminate (> 0,1 mm; < 240 min); DIN EN374 |

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.  
Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

Skin and body protection : Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL HYDRO Base MIX

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	06.09.2023	MAT0GA05_010 IE/EN	Date of first issue: 06.09.2023

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Equipment should conform to EN 14387

Filter type : Combined particulates and organic vapour type (A-P)

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Physical state : liquid

Colour : in accordance with the product description

Odour : solvent-like

Odour Threshold : No data available

Melting point/freezing point : 0.0 °C (calculation method (principal components, lowest value))

Boiling point/boiling range : 100 °C (calculation method (principal components, lowest value))

Flammability : Static-accumulating flammable liquid., Combustible Solids

Flash point : 66 °C

Decomposition temperature : No decomposition if stored and applied as directed. Hazardous decomposition products formed under fire conditions.

pH : Not applicable

Viscosity  
Viscosity, kinematic : > 20.5 mm<sup>2</sup>/s (40 °C)

Flow time : 35 - 45 s at 20 °C  
Cross section: 4 mm  
Method: DIN4

Solubility(ies)  
Water solubility : immiscible, partly soluble

Solubility in other solvents : Description: miscible with most organic solvents

Partition coefficient: n-octanol/water : No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL HYDRO Base MIX

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	06.09.2023	MAT0GA05_010 IE/EN	Date of first issue: 06.09.2023

---

Vapour pressure	:	23 hPa (calculation method (principal components, highest value)) (20 °C)
Relative density	:	No data available
Density	:	0.99 - 1.213 g/cm <sup>3</sup>
Relative vapour density	:	No data available

### 9.2 Other information

Explosives	:	Not applicable
Oxidizing properties	:	Not applicable
VOC	:	(Directive 2004/42/EC) 410 g/l

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions	:	No decomposition if stored and applied as directed.
---------------------	---	-----------------------------------------------------

Vapours may form explosive mixture with air.

### 10.4 Conditions to avoid

Conditions to avoid	:	Heat, flames and sparks.
---------------------	---	--------------------------

### 10.5 Incompatible materials

Materials to avoid	:	Incompatible with strong acids and bases.
--------------------	---	-------------------------------------------

### 10.6 Hazardous decomposition products

Adequate ventilation is required.  
Heating can release vapours which can be ignited.  
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

---

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Not classified based on available information.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL HYDRO Base MIX

Version 1.0      Revision Date: 06.09.2023      SDS Number: MAT0GA05\_010 IE/EN      Date of last issue: -  
Date of first issue: 06.09.2023

---

### **Product:**

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg  
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method

### **Components:**

#### **2-butoxyethanol:**

Acute oral toxicity : Acute toxicity estimate: 1,200 mg/kg  
Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008

Acute inhalation toxicity : LC50 (Rat): 450 ppm  
Exposure time: 4 h  
Test atmosphere: vapour  
Assessment: The component/mixture is toxic after short term inhalation.

#### **butan-1-ol:**

Acute oral toxicity : Assessment: The component/mixture is moderately toxic after single ingestion.  
LD50 Oral (Rat): > 2,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l  
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

#### **N-methyl-2-pyrrolidone:**

Acute oral toxicity : LD50 Oral (Rat): >= 4,150 mg/kg

Acute inhalation toxicity : LC50 (Rat): >= 5.1 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 Dermal (Rat): >= 5,000 mg/kg

#### **2-dimethylaminoethanol:**

Acute inhalation toxicity : Assessment: The component/mixture is toxic after short term inhalation.

#### **1,2-benzisothiazol-3(2H)-one:**

Acute oral toxicity : Assessment: The component/mixture is moderately toxic after single ingestion.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL HYDRO Base MIX

Version  
1.0

Revision Date:  
06.09.2023

SDS Number:  
MAT0GA05\_010  
IE/EN

Date of last issue: -  
Date of first issue: 06.09.2023

---

### **2-methylisothiazol-3(2H)-one:**

- Acute oral toxicity : Assessment: The component/mixture is toxic after single ingestion.
- Acute inhalation toxicity : Test atmosphere: vapour  
Assessment: The component/mixture is highly toxic after short term inhalation.
- Acute dermal toxicity : Assessment: The component/mixture is toxic after single contact with skin.

### **Skin corrosion/irritation**

Not classified based on available information.

### **Product:**

Remarks : Extremely corrosive and destructive to tissue.

### **Components:**

#### **2-butoxyethanol:**

Result : irritating

#### **butan-1-ol:**

Result : irritating

#### **N-methyl-2-pyrrolidone:**

Result : irritating

#### **1,2-benzisothiazol-3(2H)-one:**

Result : irritating

#### **2-methylisothiazol-3(2H)-one:**

Result : Corrosive after 3 minutes to 1 hour of exposure

### **Serious eye damage/eye irritation**

Causes serious eye damage.

### **Product:**

Remarks : May cause irreversible eye damage.

### **Components:**

#### **2-butoxyethanol:**

Result : Eye irritation



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL HYDRO Base MIX

Version  
1.0

Revision Date:  
06.09.2023

SDS Number:  
MAT0GA05\_010  
IE/EN

Date of last issue: -  
Date of first issue: 06.09.2023

### **butan-1-ol:**

Result : Corrosive

### **N-methyl-2-pyrrolidone:**

Result : Eye irritation

### **1,2-benzisothiazol-3(2H)-one:**

Result : Corrosive

### **Respiratory or skin sensitisation**

#### **Skin sensitisation**

Not classified based on available information.

#### **Respiratory sensitisation**

Not classified based on available information.

#### **Components:**

#### **1,2-benzisothiazol-3(2H)-one:**

Result : Probability or evidence of skin sensitisation in humans

#### **2-methylisothiazol-3(2H)-one:**

Result : Probability or evidence of skin sensitisation in humans

#### **Germ cell mutagenicity**

Not classified based on available information.

#### **Carcinogenicity**

Not classified based on available information.

#### **Reproductive toxicity**

May damage the unborn child.

#### **Components:**

#### **N-methyl-2-pyrrolidone:**

Reproductive toxicity - Assessment : Clear evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments

#### **STOT - single exposure**

Not classified based on available information.

#### **Components:**

#### **butan-1-ol:**

Assessment : May cause drowsiness or dizziness.

Assessment : May cause respiratory irritation.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL HYDRO Base MIX

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	06.09.2023	MAT0GA05_010 IE/EN	Date of first issue: 06.09.2023

### **N-methyl-2-pyrrolidone:**

Assessment : May cause respiratory irritation.

### **2-dimethylaminoethanol:**

Assessment : May cause respiratory irritation.

### **STOT - repeated exposure**

Not classified based on available information.

### **Aspiration toxicity**

Not classified based on available information.

## 11.2 Information on other hazards

### **Endocrine disrupting properties**

#### **Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### **Further information**

#### **Product:**

Remarks : No data available

## SECTION 12: Ecological information

### 12.1 Toxicity

#### **Components:**

##### **2-butoxyethanol:**

Toxicity to fish : LC50 (Fish):  $\geq 1,700$  mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)):  $> 1,000$  mg/l  
Exposure time: 48 h

Toxicity to microorganisms : EC50 (Bacteria):  $> 5,000$  mg/l

##### **butan-1-ol:**

Toxicity to fish : LC50 (Fish):  $> 1,000$  mg/l

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)):  $> 1,000$  mg/l

Toxicity to microorganisms : EC50 (Bacteria):  $> 1,000$  mg/l

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL HYDRO Base MIX

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	06.09.2023	MAT0GA05_010 IE/EN	Date of first issue: 06.09.2023

---

### 1,2-benzisothiazol-3(2H)-one:

#### Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

### 2-methylisothiazol-3(2H)-one:

M-Factor (Acute aquatic toxicity) : 10

M-Factor (Chronic aquatic toxicity) : 1

#### Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

### reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1):

Toxicity to fish : LC50 (Salvelinus namaycush (lake trout)):  $\geq 10.85$  mg/l  
Exposure time: 96 h

Toxicity to algae/aquatic plants : LC50 (algae):  $\geq 0.82$  mg/l  
Exposure time: 48 h

LC50 (algae): 0.018 mg/l  
Exposure time: 72 h

M-Factor (Acute aquatic toxicity) : 100

M-Factor (Chronic aquatic toxicity) : 100

## 12.2 Persistence and degradability

### Components:

#### 2-butoxyethanol:

Biodegradability : Result: Biodegradable

Stability in water : Hydrolyses slowly.

Photodegradation : Decomposes slowly in contact with light.

#### 2-methylisothiazol-3(2H)-one:

Biodegradability : Result: Biodegradable

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL HYDRO Base MIX

Version  
1.0

Revision Date:  
06.09.2023

SDS Number:  
MAT0GA05\_010  
IE/EN

Date of last issue: -  
Date of first issue: 06.09.2023

### 12.3 Bioaccumulative potential

#### Components:

##### **2-butoxyethanol:**

Partition coefficient: n-octanol/water : log Pow: 0.81 (20 °C)

##### **butan-1-ol:**

Partition coefficient: n-octanol/water : log Pow: 0.785

##### **N-methyl-2-pyrrolidone:**

Partition coefficient: n-octanol/water : log Pow: -0.46

##### **2-dimethylaminoethanol:**

Partition coefficient: n-octanol/water : log Pow: -0.55

##### **1,2-benzisothiazol-3(2H)-one:**

Partition coefficient: n-octanol/water : log Pow: 1.3

### 12.4 Mobility in soil

#### Components:

##### **2-butoxyethanol:**

Mobility : Medium: Air  
Content: 1 %  
: Medium: Water  
Content: 47 %  
: Medium: Soil  
Content: 52 %

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

#### Components:

##### **2-butoxyethanol:**

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL HYDRO Base MIX

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	06.09.2023	MAT0GA05_010 IE/EN	Date of first issue: 06.09.2023

---

Assessment : This substance is not considered to be persistent, bioaccumulating and toxic (PBT).

### 12.6 Endocrine disrupting properties

**Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

**Product:**

Additional ecological information : No data available

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

Waste Code : 08 00 00, WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS  
08 01 00, wastes from MFSU and removal of paint and varnish  
08 01 11, waste paint and varnish containing organic solvents or other hazardous substances  
15 00 00, WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED  
15 01 00, packaging (including separately collected municipal packaging waste)  
15 01 10, packaging containing residues of or contaminated by hazardous substances  
HP4, Irritant - skin irritation and eye damage  
HP10, Toxic for reproduction

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL HYDRO Base MIX

Version  
1.0

Revision Date:  
06.09.2023

SDS Number:  
MAT0GA05\_010  
IE/EN

Date of last issue: -  
Date of first issue: 06.09.2023

---

### SECTION 14: Transport information

#### 14.1 UN number or ID number

ADN : Not regulated as a dangerous good  
ADR : Not regulated as a dangerous good  
RID : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA : Not regulated as a dangerous good

#### 14.2 UN proper shipping name

ADN : Not regulated as a dangerous good  
ADR : Not regulated as a dangerous good  
RID : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA : Not regulated as a dangerous good

#### 14.3 Transport hazard class(es)

ADN : Not regulated as a dangerous good  
ADR : Not regulated as a dangerous good  
RID : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA : Not regulated as a dangerous good

#### 14.4 Packing group

ADN : Not regulated as a dangerous good  
ADR : Not regulated as a dangerous good  
RID : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA (Cargo) : Not regulated as a dangerous good  
IATA (Passenger) : Not regulated as a dangerous good

#### 14.5 Environmental hazards

Not regulated as a dangerous good

#### 14.6 Special precautions for user

Not applicable

#### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL HYDRO Base MIX

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	06.09.2023	MAT0GA05_010 IE/EN	Date of first issue: 06.09.2023

---

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 75, 3

If you intend to use this product as tattoo ink, please contact your vendor.

N-methyl-2-pyrrolidone (Number on list 72, 71, 30)

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : N-methyl-2-pyrrolidone

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. : Not applicable

Volatile organic compounds : Directive 2004/42/EC  
Volatile organic compounds (VOC) content: 410 g/l

#### Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL HYDRO Base MIX

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	06.09.2023	MAT0GA05_010 IE/EN	Date of first issue: 06.09.2023

### 15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

## SECTION 16: Other information

### Full text of H-Statements

H226	: Flammable liquid and vapour.
H301	: Toxic if swallowed.
H302	: Harmful if swallowed.
H310	: Fatal in contact with skin.
H311	: Toxic in contact with skin.
H312	: Harmful in contact with skin.
H314	: Causes severe skin burns and eye damage.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H330	: Fatal if inhaled.
H331	: Toxic if inhaled.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H360D	: May damage the unborn child.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.
H411	: Toxic to aquatic life with long lasting effects.
EUH071	: Corrosive to the respiratory tract.

### Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Acute	: Short-term (acute) aquatic hazard
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Eye Dam.	: Serious eye damage
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Repr.	: Reproductive toxicity
Skin Corr.	: Skin corrosion
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitisation
STOT SE	: Specific target organ toxicity - single exposure
2000/39/EC	: Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2004/37/EC	: Europe. Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens or mutagens at work
2009/161/EU	: Europe. COMMISSION DIRECTIVE 2009/161/EU establishing a third list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC and amending Commission Directive 2000/39/EC
IE OEL	: Ireland. List of Chemical Agents and Occupational Exposure Limit Values - Schedule 1
2000/39/EC / TWA	: Limit Value - eight hours
2000/39/EC / STEL	: Short term exposure limit



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL HYDRO Base MIX

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	06.09.2023	MAT0GA05_010 IE/EN	Date of first issue: 06.09.2023

2004/37/EC / STEL	:	Short term exposure limit
2004/37/EC / TWA	:	Long term exposure limit
2009/161/EU / TWA	:	Limit Value - eight hours
2009/161/EU / STEL	:	Short term exposure limit
IE OEL / OELV - 8 hrs (TWA)	:	Occupational exposure limit value (8-hour reference period)
IE OEL / OELV - 15 min (STEL)	:	Occupational exposure limit value (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

#### Classification of the mixture:

Eye Dam. 1	H318
Repr. 1B	H360D

#### Classification procedure:

Calculation method
Calculation method

Material codes (bulk) for which the SDS is valid	400929 , 400996, 401107, 401194, 401196, 470600, 470601, 470608, 470610, 470612, 470613, 470614, 470616, 470617, 470618, 470619, 470621, 470622, 470625, 470626, 470627, 470628, 470629, 470630, 470631, 470632, 470633, 470641, 470642, 470643, 470644, 470645, 470646, 470651, 470652,
--------------------------------------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL HYDRO Base MIX

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	06.09.2023	MAT0GA05_010 IE/EN	Date of first issue: 06.09.2023

---

470661, 470662, 470663, 470665, 470700, 470701, 470702,  
470703, 470704, 470705, 470706, 470708, 470715, 470720,  
470721, 470722, 470730, 470740, 470750, 470751, 470752,  
470753, 470760, 470770, 470771, 470772, 470780, 470781,  
470795, 470796, 470800, 470801, 470802, 470803, 470804,  
470805

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.