According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



TESSAROL ENAMEL RAL----

Version Revision Date: SDS Number: Date of last issue: 18.07.2023 3.0 05.01.2024 MAT0GA00_103 Date of first issue: 22.10.2020

GB/EN

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : TESSAROL ENAMEL RAL----

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-Building and construction work

stance/Mixture Roller application or brushing, Non industrial spraying

Coatings and paints, thinners, paint removers

Recommended restrictions

on use

public use, professional use

1.3 Details of the supplier of the safety data sheet

Company : Helios TBLUS d.o.o.

> Količevo 65 1230 Domžale Slovenia

Telephone Company : 386 (1) 722 4383

Telefax Company : 386 (1) 722 4310

Responsible/issuing person : 386 (1) 722 4383

productsafety@helios.si

1.4 Emergency telephone number

Call 999 (or 112) for emergency medical attention

professionals only: National Poison Information Service (NPIS) 24h national number 0844 892

0111

consumer: National Health Service (NHS) 24h national number, England & Scotland 111

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Flammable liquids, Category 3 H226: Flammable liquid and vapour.

Specific target organ toxicity - single ex-

posure, Category 3, Central nervous

system

H336: May cause drowsiness or dizziness.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



TESSAROL ENAMEL RAL----

Version Revision Date: SDS Number: Date of last issue: 18.07.2023 3.0 05.01.2024 MAT0GA00_103 Date of first issue: 22.10.2020

GB/EN

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Hazard pictograms

Signal word : Warning

Hazard statements : H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

Precautionary statements : P101 If medical advice is needed, have product container or

label at hand.

P102 Keep out of reach of children.

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open

flames and other ignition sources. No smoking.

P271 Use only outdoors or in a well-ventilated area.

Response:

P370 + P378 In case of fire: Use dry sand, dry chemical or

alcohol-resistant foam to extinguish.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

Hazardous components which must be listed on the label:

hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics 1-methoxy-2-propanol

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Paint

Components

01	OAO NI.	01:	O (('
Chemical name	CAS-No.	Classification	Concentration

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



TESSAROL ENAMEL RAL----

Version Revision Date: SDS Number: Date of last issue: 18.07.2023 3.0 05.01.2024 MAT0GA00_103 Date of first issue: 22.10.2020

GB/EN

		_		
	EC-No.		(% w/w)	
	Index-No.			
la lacation 00 044 and lacation	Registration number	Fl I'. 0 11000	00 00	
hydrocarbons, C9-C11, n-alkanes,	64742-48-9	Flam. Liq. 3; H226	>= 20 - < 30	
isoalkanes, cyclic, <2% aromatics	919-857-5	STOT SE 3; H336 (Central nervous		
	01-2119463258-33	system)		
	01-2119403230-33	Asp. Tox. 1; H304		
hydrocarbons, C10-C13 n-alkanes,	-	Asp. Tox. 1; H304	>= 1 - < 10	
isoalkanes, cyclic, <2% aromatics		, 1001		
	918-481-9			
	01-2119457273-39			
1-methoxypropan-2-ol	107-98-2	Flam. Liq. 3; H226	>= 1 - < 10	
		STOT SE 3; H336		
	203-539-1	(Central nervous		
	603-064-00-3	system)		
	01-2119457435-35			
reaction mixture of ethylbenzene, m-	1330-20-7	Flam. Liq. 3; H226	>= 1 - < 10	
xylene and p-xylene		Acute Tox. 4; H332		
	905-562-9	Acute Tox. 4; H312		
	01-2119555267-33	Skin Irrit. 2; H315		
		Eye Irrit. 2; H319		
		STOT SE 3; H335		
		(Respiratory sys- tem)		
		STOT RE 2; H373		
		Asp. Tox. 1; H304		
strontium bis(2-ethylhexanoate)	2457-02-5	Acute Tox. 4; H302	>= 0,1 - < 0,3	
custilian bio(2 cutymoxanoate)	2 107 02 0	Skin Irrit. 2; H315	7 - 0,1 < 0,0	
	219-536-3	Eye Dam. 1; H318		
		Repr. 1B; H360D		
Substances with a workplace exposure limit :				
titanium dioxide	13463-67-7		>= 1 - < 10	
	236-675-5			
	01-2119489379-17			
highly dispersed silicic acid	112945-52-5		>= 1 - < 10	
	04 0440070400 40			
	01-2119379499-16			

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : Consult a physician after significant exposure.

If unconscious, place in recovery position and seek medical

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



TESSAROL ENAMEL RAL----

Version 3.0

Revision Date: 05.01.2024

SDS Number: MAT0GA00_103 Date of last issue: 18.07.2023 Date of first issue: 22.10.2020

GB/EN

advice.

In case of skin contact

If skin irritation persists, call a physician.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact

Flush eyes with water as a precaution.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed

Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

Risks May cause drowsiness or dizziness.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

ucts

Hazardous combustion prod- : No hazardous combustion products are known

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



TESSAROL ENAMEL RAL----

Version Revision Date: 3.0

SDS Number: 05.01.2024 MAT0GA00_103

GB/EN

Date of last issue: 18.07.2023 Date of first issue: 22.10.2020

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

For safety reasons in case of fire, cans should be stored sepa-

rately in closed containments.

Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment.

> Remove all sources of ignition. Evacuate personnel to safe areas.

Beware of vapours accumulating to form explosive concentra-

tions. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up Contain spillage, and then collect with non-combustible ab-

> sorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local

/ national regulations (see section 13).

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid formation of aerosol. Advice on safe handling

Do not breathe vapours/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national

regulations.

Advice on protection against

fire and explosion

Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



TESSAROL ENAMEL RAL----

Version Revision Date: SDS Number: Date of last issue: 18.07.2023 3.0 05.01.2024 MAT0GA00_103 Date of first issue: 22.10.2020

GB/EN

(which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : For further information, refer to the product technical data

sheet.

Consult the technical guidelines for the use of this sub-

stance/mixture.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
titanium dioxide	13463-67-7	TWA (inhalable dust)	10 mg/m3	GB EH40
		TWA (Respirable dust)	4 mg/m3	GB EH40
1-methoxy-2- propanol	107-98-2	TWA	100 ppm 375 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	150 ppm 560 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		TWA	100 ppm 375 mg/m3	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			ce through the
		STEL	150 ppm 568 mg/m3	2000/39/EC

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



TESSAROL ENAMEL RAL----

Version Revision Date: SDS Number: Date of last issue: 18.07.2023 3.0 05.01.2024 MAT0GA00_103 Date of first issue: 22.10.2020

GB/EN

	Further inform		possibility of significant uptak	te through the		
reaction mixture of ethylbenzene, m- xylene and p- xylene	1330-20-7	TWA	50 ppm 220 mg/m3	GB EH40		
	Further information: Can be absorbed through the skin. The assigned sub-			signed sub-		
			are concerns that dermal abs	sorption will		
	lead to systen	nic toxicity.				
		STEL	100 ppm 441 mg/m3	GB EH40		
	Further information: Can be absorbed through the skin. The assigned sub-					
	stances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			sorption will		
				-		
		TWA	50 ppm 221 mg/m3	2000/39/EC		
	Further information: Identifies the possibility of significant uptake thro skin, Indicative			e through the		
		STEL	100 ppm 442 mg/m3	2000/39/EC		
	Further information: Identifies the possibility of significant uptake to			e through the		
	skin, Indicative	e				
Siliciumdioxide	112945-52-	TWA (inhalable	6 mg/m3	GB EH40		
	5	dust)	(Silica)			
		TWA (Respirable dust)	2,4 mg/m3 (Silica)	GB EH40		

Biological occupational exposure limits

•	•			
Substance name	CAS-No.	Control parameters	Sampling time	Basis
reaction mixture of	1330-20-7	methyl hippuric	After shift	GB EH40
ethylbenzene, m-xylene		acid: 650 Millimo-		BAT
and p-xylene		les per mole Creat-		
		inine		
		(Urine)		

Derived No Effect Level (DNEL):

Substance name	End Use	Exposure routes	Potential health effects	Value
hydrocarbons, C9- C11, n-alkanes, isoal- kanes, cyclic, <2% aromatics	Workers	Inhalation	Long-term systemic effects	1500 mg/m3
	Consumers	Inhalation	Long-term systemic effects	900 mg/m3
	Workers	Dermal	Long-term systemic effects	300 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	300 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	300 mg/kg bw/day
titanium dioxide	Workers	Inhalation	Long-term local ef-	10 mg/m3

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



TESSAROL ENAMEL RAL----

VersionRevision Date:SDS Number:Date of last issue: 18.07.20233.005.01.2024MAT0GA00_103Date of first issue: 22.10.2020

GB/EN

		Ī	fects	
	Consumers	Oral	Long-term systemic effects	700 mg/kg bw/day
1-methoxy-2-propanol	Workers	Inhalation	Long-term systemic effects	369 mg/m3
	Workers	Inhalation	Acute systemic ef- fects	553,5 mg/m3
	Workers	Inhalation	Acute local effects	553,5 mg/m3
	Workers	Inhalation	Long-term systemic effects	43,9 mg/m3
	Workers	Dermal	Long-term systemic effects	183 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	78 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	33 mg/kg bw/day
reaction mixture of ethylbenzene, m-xylene and p-xylene	Workers	Inhalation	Long-term systemic effects	77 mg/m3
	Consumers	Inhalation	Long-term local effects	65,3 mg/m3
	Workers	Inhalation	Acute systemic effects	442 mg/m3
	Workers	Inhalation	Acute local effects	289 mg/m3
	Consumers	Inhalation	Acute systemic effects	260 mg/m3
	Workers	Inhalation	Long-term local ef- fects	221 mg/m3
	Consumers	Inhalation	Long-term systemic effects	14,8 mg/m3
	Consumers	Inhalation	Acute local effects	260 mg/m3
	Consumers	Dermal	Long-term systemic effects	108 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	16 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	180 mg/kg bw/day
Siliciumdioxide	Workers	Inhalation	Long-term systemic effects	4 mg/m3
strontium bis(2- ethylhexanoate)	Workers	Inhalation	Long-term systemic effects	0,730 mg/m3
	Workers	Dermal	Long-term systemic effects	0,410 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	0,180 mg/m3
	Consumers	Dermal	Long-term systemic effects	0,210 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	0,210 mg/kg bw/day

Predicted No Effect Concentration (PNEC):

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



TESSAROL ENAMEL RAL----

Version Revision Date: SDS Number: Date of last issue: 18.07.2023 3.0 05.01.2024 MAT0GA00_103 Date of first issue: 22.10.2020

GB/EN

Substance name	Environmental Compartment	Value
titanium dioxide	Soil	100 mg/kg dry
mariam diexide		weight (d.w.)
	Marine water	0,0184 mg/l
	Fresh water	0,184 mg/l
	Marine sediment	100 mg/kg dry
		weight (d.w.)
	Fresh water sediment	1000 mg/kg dry
		weight (d.w.)
	Sewage treatment plant	100 mg/l
	Intermittent use/release	0,193 mg/l
1-methoxy-2-propanol	Soil	4,59 mg/kg dry
		weight (d.w.)
	Marine water	1 mg/l
	Fresh water	10 mg/l
	Marine sediment	5,2 mg/kg dry
		weight (d.w.)
	Fresh water sediment	52,3 mg/kg dry
	Course treatment plant	weight (d.w.)
	Sewage treatment plant Intermittent use/release	100 mg/l
reaction mixture of athulbanzana	Soil	100 mg/l
reaction mixture of ethylbenzene, m-xylene and p-xylene	3011	2,31 mg/kg dry weight (d.w.)
m-xylene and p-xylene	Marine water	0,327 mg/l
	Fresh water	0,327 mg/l
	Marine sediment	12,46 mg/kg dry
	Warne Seament	weight (d.w.)
	Fresh water sediment	12,46 mg/kg dry
	The second secon	weight (d.w.)
	Sewage treatment plant	6,58 mg/l
	Intermittent use/release	0,327 mg/l
strontium bis(2-ethylhexanoate)	Fresh water	0,360 - 0,440
, , ,		mg/l
	Intermittent use/release	0,493 - 0,610
		mg/l
	Marine water	0,036 - 0,040
		mg/l
	Sewage treatment plant	71,7 - 88,52 mg/l
	Fresh water sediment	6,37 - 7,86 mg/kg
	1	dry weight (d.w.)
	Marine sediment	0,637 - 0,790
		mg/kg dry weight
	Coil	(d.w.)
	Soil	1,06 - 1,31 mg/kg
		dry weight (d.w.)

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Equipment should conform to EN 166

Eye wash bottle with pure water

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



TESSAROL ENAMEL RAL----

Version Revision Date: SDS Number: Date of last issue: 18.07.2023 3.0 05.01.2024 MAT0GA00_103 Date of first issue: 22.10.2020

GB/EN

Tightly fitting safety goggles

Hand protection

Gloves : Nitrile rubber (> 0,1 mm; < 60 min); DIN EN374

butyl-rubber (> 0,6 mm; < 240 min); DIN EN374 | Viton® (> 0,6 mm; < 240 min); DIN EN374 | PE laminate (> 0,1 mm; < 240 min); DIN EN374 |

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of

cuts, abrasion, and the contact time.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concen-

tration of the dangerous substance at the work place.

Respiratory protection : Use respiratory protection unless adequate local exhaust ven-

tilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. In the case of dust or aerosol formation use respirator with an

approved filter.

Respirator with a half face mask

Equipment should conform to EN-136; EN-143; EN-149; EN-

529

Filter type : Combined particulates and organic vapour type (A - P2)

Combined particulates and organic vapour type (A-P)

Protective measures : Wash thoroughly after handling.

Avoid contact with skin, eyes and clothing.

Keep away from food, drink and animal feedingstuffs.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : in accordance with the product description

Odour : solvent-like
Odour Threshold : No data available

pH : No data available

Melting point/freezing point : < 0,0 °C

(calculation method (principal components, lowest value))

Boiling point/boiling range : 155 - 192 °C (calculation method (principal components, low-

est value))

Flash point : 40 °C (calculation method (principal components, lowest val-

ıe))

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



TESSAROL ENAMEL RAL----

Version Revision Date: 3.0

SDS Number: 05.01.2024 MAT0GA00_103

Date of first issue: 22.10.2020

Date of last issue: 18.07.2023

GB/EN

Flammability (solid, gas) Static-accumulating flammable liquid., Combustible Solids

Vapour pressure 2 hPa (calculation method (principal components, highest

value))

Relative vapour density No data available

Relative density No data available

Density 0,9 - 1,3 g/cm3

Solubility(ies)

Water solubility insoluble

Solubility in other solvents : Description: miscible with most organic solvents

Partition coefficient: n-

octanol/water

No data available

Decomposition temperature No decomposition if stored and applied as directed.

Hazardous decomposition products formed under fire condi-

tions.

Viscosity

 $> 20,5 \text{ mm2/s} (40 ^{\circ}\text{C})$ Viscosity, kinematic

Flow time : > 60 s at 23 °C

> Cross section: 6 mm Method: ISO 2431

Not applicable Explosive properties

Oxidizing properties : Sustains combustion

9.2 Other information

No data available

(Directive 2004/42/EC) VOC

400 g/l

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions No decomposition if stored and applied as directed.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



TESSAROL ENAMEL RAL----

Version Revision Date: 3.0 05.01.2024

SDS Number: MAT0GA00_103

Date of last issue: 18.07.2023 Date of first issue: 22.10.2020

GB/EN

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Incompatible with strong acids and bases.

10.6 Hazardous decomposition products

Adequate ventilation is required.

Heating can release vapours which can be ignited.

Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

Product:

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l

Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg

Method: Calculation method

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Acute oral toxicity : LD50 Oral (Rat, male and female): > 5.000 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 5.000 mg/l

Test atmosphere: vapour

Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 Dermal (Rabbit, male and female): > 5.000 mg/kg

Method: OECD Test Guideline 402

1-methoxy-2-propanol:

Acute oral toxicity : LD50 Oral (Rabbit): > 2.000 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



TESSAROL ENAMEL RAL----

Version Revision Date: SDS Number: Date of last issue: 18.07.2023 3.0 05.01.2024 MAT0GA00_103 Date of first issue: 22.10.2020

GB/EN

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Acute oral toxicity : LD50 Oral (Rat): >= 8.700 mg/kg

Acute inhalation toxicity : LC50 (Rat): 27,14 mg/l

Test atmosphere: vapour

Acute dermal toxicity : Assessment: The component/mixture is moderately toxic after

single contact withskin.

strontium bis(2-ethylhexanoate):

Acute oral toxicity : Assessment: The component/mixture is moderately toxic after

single ingestion.

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks : May cause skin irritation and/or dermatitis.

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

GLP : yes

Result : Repeated exposure may cause skin dryness or cracking.

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Result : irritating

strontium bis(2-ethylhexanoate):

Result : irritating

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks : Vapours may cause irritation to the eyes, respiratory system

and the skin.

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Species : Rabbit

Method : OECD Test Guideline 405

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



TESSAROL ENAMEL RAL----

Version Revision Date: SDS Number: Date of last issue: 18.07.2023 3.0 05.01.2024 MAT0GA00_103 Date of first issue: 22.10.2020

GB/EN

Result : No eye irritation

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Result : Eye irritation

strontium bis(2-ethylhexanoate):

Result : Corrosive

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Exposure routes : Skin contact Species : Guinea pig

Method : OECD Test Guideline 406
Result : Not a skin sensitizer.

Germ cell mutagenicity

Not classified based on available information.

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Genotoxicity in vitro : Result: negative

Genotoxicity in vivo : Result: negative

Carcinogenicity

Not classified based on available information.

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Result : negative

Reproductive toxicity

Not classified based on available information.

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Effects on foetal develop- : Remarks: Fertility and developmental toxicity tests did not

ment reveal any effect on reproduction.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



TESSAROL ENAMEL RAL----

Version Revision Date: 3.0 05.01.2024

SDS Number: MAT0GA00_103

Date of last issue: 18.07.2023 Date of first issue: 22.10.2020

GB/EN

STOT - single exposure

May cause drowsiness or dizziness.

Components:

hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics:

Assessment : May cause drowsiness or dizziness.

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Remarks : Based on available data, the classification criteria are not met.

1-methoxy-2-propanol:

Assessment : May cause drowsiness or dizziness.

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Assessment : May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Remarks : Based on available data, the classification criteria are not met.

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Assessment : May cause damage to organs through prolonged or repeated

exposure.

Aspiration toxicity

Not classified based on available information.

Components:

hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics:

May be fatal if swallowed and enters airways.

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

May be fatal if swallowed and enters airways.

reaction mixture of ethylbenzene, m-xylene and p-xylene:

May be fatal if swallowed and enters airways.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



TESSAROL ENAMEL RAL----

Version Revision Date: SDS Number: Date of last issue: 18.07.2023 3.0 05.01.2024 MAT0GA00_103 Date of first issue: 22.10.2020

GB/EN

Further information

Product:

Remarks Symptoms of overexposure may be headache, dizziness,

tiredness, nausea and vomiting.

Concentrations substantially above the TLV value may cause

narcotic effects.

Solvents may degrease the skin.

SECTION 12: Ecological information

12.1 Toxicity

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Toxicity to fish LC50 (Oncorhynchus mykiss (rainbow trout)): > 1.000 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50: > 1.000 mg/l Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

NOEC (Pseudokirchneriella subcapitata (microalgae)): 1.000

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

EC50 (Pseudokirchneriella subcapitata (microalgae)): > 1.000

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

1-methoxy-2-propanol:

Toxicity to fish LC50 (Fish): > 1.000 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

LC50 (Daphnia (water flea)): > 1.000 mg/l

Toxicity to algae/aquatic

LC50 (algae): > 1.000 mg/l

plants

reaction mixture of ethylbenzene, m-xylene and p-xylene: Toxicity to fish : LC50 (Fish): >= 1 - 10 mg/l

aquatic invertebrates

Toxicity to daphnia and other : LC50 (Daphnia (water flea)): >= 1 - 10 mg/l

Toxicity to microorganisms

: EC50 (Bacteria): >= 1 - 100 mg/l

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



TESSAROL ENAMEL RAL----

Version Revision Date: SDS Number: Date of last issue: 18.07.2023 3.0 05.01.2024 MAT0GA00_103 Date of first issue: 22.10.2020

GB/EN

12.2 Persistence and degradability

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Biodegradability Result: Readily biodegradable.

> Biodegradation: 80 % Exposure time: 28 d

Method: OECD Test Guideline 301F

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Biodegradability Remarks: Readily biodegradable.

Remarks: Decomposes rapidly in contact with light. Photodegradation

12.3 Bioaccumulative potential

Components:

1-methoxy-2-propanol:

Partition coefficient: n-

octanol/water

: log Pow: -0,437

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Bioaccumulation Bioconcentration factor (BCF): 25,9

Remarks: Bioaccumulation is unlikely.

Partition coefficient: n-

octanol/water

log Pow: 2,77 - 3,15

12.4 Mobility in soil

Components:

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Distribution among environ-

Koc: 537, log Koc: 2,73

mental compartments Remarks: Moderately mobile in soils

The product evaporates from soil.

Dissipation time: 23 d Stability in soil

Percentage dissipation: 50 % (DT50)

12.5 Results of PBT and vPvB assessment

Product:

Assessment This substance/mixture contains no components considered

> to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



TESSAROL ENAMEL RAL----

Version Revision Date: SDS Number: Date of last issue: 18.07.2023 3.0 05.01.2024 MAT0GA00_103 Date of first issue: 22.10.2020

GB/EN

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Assessment : This substance is not considered to be persistent, bioaccumu-

lating and toxic (PBT).

12.6 Other adverse effects

Product:

Endocrine disrupting poten-

tial

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

Additional ecological infor-

mation

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

14.1 UN number

ADN : UN 1263
ADR : UN 1263
RID : UN 1263
IMDG : UN 1263
IATA : UN 1263

14.2 UN proper shipping name

ADN : PAINT
ADR : PAINT
RID : PAINT
IMDG : PAINT

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



TESSAROL ENAMEL RAL----

Version Revision Date: SDS Number: Date of last issue: 18.07.2023 3.0 05.01.2024 MAT0GA00_103 Date of first issue: 22.10.2020

GB/EN

IATA : Paint

14.3 Transport hazard class(es)

ADN : 3
ADR : 3
RID : 3
IMDG : 3
IATA : 3

14.4 Packing group

ADN

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

ADR

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3
Tunnel restriction code : (D/E)

RID

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

IMDG

Packing group : III
Labels : 3
EmS Code : F-E, <u>S-E</u>

IATA (Cargo)

Packing instruction (cargo : 366

aircraft)

Packing instruction (LQ) : Y344
Packing group : III

Labels : Flammable Liquids

IATA (Passenger)

Packing instruction (passen- : 355

ger aircraft)

Packing instruction (LQ) : Y344
Packing group : III

Labels : Flammable Liquids

14.5 Environmental hazards

ADN

Environmentally hazardous : no

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



TESSAROL ENAMEL RAL----

Version Revision Date: SDS Number: Date of last issue: 18.07.2023 3.0 05.01.2024 MAT0GA00_103 Date of first issue: 22.10.2020

GB/EN

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

Remarks : ADR: Packages smaller than or equal to 450 litres, not

goods/merchandise of Class 3 (exemption ADR 2.2.3.1.5) IMDG: Packages smaller than or equal to 450 litres, not goods/merchandise of Class 3; "transport acc. IMDG-code

2.3.2.5"

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mix-

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17) : Conditions of restriction for the fol-

lowing entries should be considered:

Number on list 3 Not applicable

Not applicable

UK REACH Candidate list of substances of very high

concern (SVHC) for Authorisation

The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Brit-

ain)

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone laver

UK REACH List of substances subject to authorisation :

(Annex XIV)

GB Export and import of hazardous chemicals - Prior

La Constant Constant (DIO) Description

Informed Consent (PIC) Regulation

Control of Major Accident Hazards Regulations P5c

2015 (COMAH)

: Not applicable

Not applicable

: Not applicable

FLAMMABLE LIQUIDS

Volatile organic compounds : Directive 2004/42/EC

Volatile organic compounds (VOC) content: 400 g/l

Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



TESSAROL ENAMEL RAL----

Version Revision Date: SDS Number: Date of last issue: 18.07.2023 3.0 05.01.2024 MAT0GA00_103 Date of first issue: 22.10.2020

GB/EN

Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

SECTION 16: Other information

Full text of H-Statements

H226 : Flammable liquid and vapour.

H302 : Harmful if swallowed.

H304 : May be fatal if swallowed and enters airways.

H312 : Harmful in contact with skin.

H315 : Causes skin irritation.

H318 : Causes serious eye damage. H319 : Causes serious eye irritation.

H332 : Harmful if inhaled.

H335 : May cause respiratory irritation.
H336 : May cause drowsiness or dizziness.
H360D : May damage the unborn child.

H373 : May cause damage to organs through prolonged or repeated

exposure.

Full text of other abbreviations

Acute Tox. : Acute toxicity
Asp. Tox. : Aspiration hazard
Eye Dam. : Serious eye damage
Eye Irrit. : Eye irritation
Flam. Liq. : Flammable liquids
Repr. : Reproductive toxicity

Skin Irrit. : Skin irritation

STOT RE : Specific target organ toxicity - repeated exposure STOT SE : Specific target organ toxicity - single exposure

2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first

list of indicative occupational exposure limit values

GB EH40 : UK. EH40 WEL - Workplace Exposure Limits
GB EH40 BAT : UK. Biological monitoring guidance values

2000/39/EC / TWA : Limit Value - eight hours 2000/39/EC / STEL : Short term exposure limit

GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergen-

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



TESSAROL ENAMEL RAL----

Version Revision Date: SDS Number: Date of last issue: 18.07.2023 3.0 05.01.2024 MAT0GA00_103 Date of first issue: 22.10.2020

GB/EN

cy Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI -Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Classification procedure:

Flam. Liq. 3	H226	Based on product data or assessment
STOT SE 3	H336	Calculation method

400678; 400679; 400680; 401600; 401601; 401602; 401603; 401604; 401605; 401606; 401607; 401608; 401609; 401610; 401611; 401612; 401613; 401614; 401751; 480874; 480875; 480876; 480877

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN