According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



TESSAROL DIRECT 3in1 RAL----

Version Revision Date: SDS Number: 2.0 08.03.2024

MAT0GA00_104

Date of last issue: 18.01.2024 Date of first issue: 09.03.2021

GB/EN

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : TESSAROL DIRECT 3in1 RAL----

Product code Please see section 16 for detailed data

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-Building and construction work

stance/Mixture Roller application or brushing, Non industrial spraying

Coatings and paints, thinners, paint removers

Recommended restrictions

on use

Professional and consumer use of coatings

1.3 Details of the supplier of the safety data sheet

Company : Helios TBLUS d.o.o.

> Količevo 65 1230 Domžale Slovenia

Telephone Company : 386 (1) 722 4383

Telefax Company : 386 (1) 722 4310

Responsible/issuing person : 386 (1) 722 4383

productsafety@helios.si

1.4 Emergency telephone number

Call 999 (or 112) for emergency medical attention

professionals only: National Poison Information Service (NPIS) 24h national number 0844 892

0111

consumer: National Health Service (NHS) 24h national number, England & Scotland 111

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



TESSAROL DIRECT 3in1 RAL----

Version Revision Date: SDS Number: Date of last issue: 18.01.2024 2.0 08.03.2024 MAT0GA00_104 Date of first issue: 09.03.2021

GB/EN

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Flammable liquids, Category 3 H226: Flammable liquid and vapour.

Specific target organ toxicity - single exposure, Category 3, Central nervous

H336: May cause drowsiness or dizziness.

system

Long-term (chronic) aquatic hazard, Cat- H412: Harmful to aquatic life with long lasting ef-

egory 3 fects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Hazard pictograms :



Signal word : Warning

Hazard statements : H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : P101 If medical advice is needed, have product con-

tainer or label at hand.

P102 Keep out of reach of children.

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open

flames and other ignition sources. No smoking.

P271 Use only outdoors or in a well-ventilated area.

Response:

P370 + P378 In case of fire: Use dry sand, dry chemical or

alcohol-resistant foam to extinguish.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved

waste disposal plant.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



TESSAROL DIRECT 3in1 RAL----

Version Revision Date: SDS Number: Date of last issue: 18.01.2024 2.0 08.03.2024 MAT0GA00_104 Date of first issue: 09.03.2021

GB/EN

Hazardous components which must be listed on the label:

hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics

1-methoxy-2-propanol

2-methoxy-1-methylethyl acetate

Additional Labelling

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics	64742-48-9 919-857-5 01-2119463258-33	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) Asp. Tox. 1; H304	>= 20 - < 30
1-methoxypropan-2-ol	107-98-2 203-539-1 603-064-00-3 01-2119457435-35	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system)	>= 1 - < 10
2-methoxy-1-methylethyl acetate	108-65-6 203-603-9 607-195-00-7 01-2119475791-29	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system)	>= 1 - < 10
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	1065336-91-5 915-687-0 01-2119491304-40	Skin Sens. 1; H317 Repr. 2; H361f Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 0,25 - < 1
strontium bis(2-ethylhexanoate)	2457-02-5 219-536-3	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318	>= 0,1 - < 0,3
Substances with a workplace exposure limit :			
titanium dioxide	13463-67-7 236-675-5 01-2119489379-17		>= 10 - < 20
aluminum silicate dihydrate	1332-58-7		>= 1 - < 10

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



TESSAROL DIRECT 3in1 RAL----

Version Revision Date: SDS Number: Date of last issue: 18.01.2024 2.0 08.03.2024 MAT0GA00_104 Date of first issue: 09.03.2021

GB/EN

	310-194-1	
barium sulphate, natural	7727-43-7	>= 1 - < 10
-	231-784-4	
	01-2119491274-35	
talc	14807-96-6	>= 1 - < 10
	238-877-9	
	01-2120140278-58	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : Consult a physician after significant exposure.

If unconscious, place in recovery position and seek medical

advice.

In case of skin contact : If on skin, rinse well with water.

If on clothes, remove clothes.

In case of eye contact : Flush eyes with water as a precaution.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

Risks : May cause drowsiness or dizziness.

May cause drowsiness or dizziness.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



TESSAROL DIRECT 3in1 RAL----

Version Revision Date: 2.0 08.03.2024

SDS Number: MAT0GA00_104 Date of last issue: 18.01.2024 Date of first issue: 09.03.2021

GB/EN

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

ucts

Hazardous combustion prod- : No hazardous combustion products are known

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

For safety reasons in case of fire, cans should be stored sepa-

rately in closed containments.

Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment.

Remove all sources of ignition. Evacuate personnel to safe areas.

Beware of vapours accumulating to form explosive concentra-

tions. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



TESSAROL DIRECT 3in1 RAL----

Version 2.0

Revision Date: 08.03.2024

SDS Number: MAT0GA00_104 Date of last issue: 18.01.2024 Date of first issue: 09.03.2021

GB/EN

6.3 Methods and material for containment and cleaning up

Methods for cleaning up Contain spillage, and then collect with non-combustible ab-

> sorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local

/ national regulations (see section 13).

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling Avoid formation of aerosol.

Do not breathe vapours/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national

regulations.

Persons susceptible to skin sensitisation problems or asthma. allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Advice on protection against

fire and explosion

Hygiene measures

Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.

: Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

No smoking. Keep container tightly closed in a dry and wellventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials

must comply with the technological safety standards.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) For further information, refer to the product technical data

sheet.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



TESSAROL DIRECT 3in1 RAL----

Version Revision Date: SDS Number: Date of last issue: 18.01.2024 2.0 08.03.2024 MAT0GA00_104

GB/EN

Date of first issue: 09.03.2021

Consult the technical guidelines for the use of this substance/mixture.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
titanium dioxide	13463-67-7	TWA (inhalable dust)	10 mg/m3	GB EH40
		TWA (Respirable dust)	4 mg/m3	GB EH40
Kaolin	1332-58-7	TWA (Respirable dust)	2 mg/m3	GB EH40
		TWA (Respirable dust)	0,1 mg/m3	2004/37/EC
		nation: Carcinogens	or mutagens	
barium sulfate	7727-43-7	TWA (inhalable dust)	10 mg/m3	GB EH40
		TWA (Respirable dust)	4 mg/m3	GB EH40
1-methoxy-2-	107-98-2	TWA	100 ppm	GB EH40
propanol			375 mg/m3	
	Further information: Can be absorbed through the skin stances are those for which there are concerns that de lead to systemic toxicity.			absorption will
		STEL	150 ppm 560 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		TWA	100 ppm 375 mg/m3	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	150 ppm 568 mg/m3	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			take through the
Talc	14807-96-6	TWA (Respirable dust)	1 mg/m3	GB EH40
		TWA (Respirable dust)	0,1 mg/m3	2004/37/EC
	Further information: Carcinogens or mutagens			
2-methoxy-1-	108-65-6	TWA	50 ppm	GB EH40

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



TESSAROL DIRECT 3in1 RAL----

Version Revision Date: SDS Number: Date of last issue: 18.01.2024 2.0 08.03.2024 MAT0GA00_104 Date of first issue: 09.03.2021

GB/EN

methylethyl ace- tate			274 mg/m3	
		ose for which there	bed through the skin. The as are concerns that dermal abs	
		STEL	100 ppm 548 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	100 ppm 550 mg/m3	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	50 ppm 275 mg/m3	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			

Derived No Effect Level (DNEL):

according to Regulation (EC) No. 1907/2006

Substance name	End Use	Exposure routes	Potential health effects	Value
hydrocarbons, C9- C11, n-alkanes, isoal- kanes, cyclic, <2% aromatics	Workers	Inhalation	Long-term systemic effects	1500 mg/m3
	Consumers	Inhalation	Long-term systemic effects	900 mg/m3
	Workers	Dermal	Long-term systemic effects	300 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	300 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	300 mg/kg bw/day
titanium dioxide	Workers	Inhalation	Long-term local effects	10 mg/m3
	Consumers	Oral	Long-term systemic effects	700 mg/kg bw/day
barium sulfate	Consumers	Inhalation	Long-term systemic effects	10 mg/m3
	Workers	Inhalation	Long-term systemic effects	10 mg/m3
	Consumers	Oral	Long-term systemic effects	13000 mg/kg bw/day
1-methoxy-2-propanol	Workers	Inhalation	Long-term systemic effects	369 mg/m3
	Workers	Inhalation	Acute systemic ef- fects	553,5 mg/m3

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



TESSAROL DIRECT 3in1 RAL----

Version Revision Date: SDS Number: 2.0 08.03.2024 MAT0GA00_10

MAT0GA00_104 GB/EN Date of last issue: 18.01.2024 Date of first issue: 09.03.2021

	Workers	Inhalation	Acute local effects	553,5 mg/m3
	Workers	Inhalation	Long-term systemic effects	43,9 mg/m3
	Workers	Dermal	Long-term systemic effects	183 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	78 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	33 mg/kg bw/day
Talc	Workers	Inhalation	Acute systemic effects	2,16 mg/m3
	Workers	Inhalation	Acute local effects	3,6 mg/m3
	Consumers	Inhalation	Acute systemic effects	1,08 mg/m3
	Consumers	Inhalation	Acute local effects	1,8 mg/m3
	Consumers	Dermal	Long-term local effects	2,27 mg/cm2
	Workers	Dermal	Long-term local effects	4,54 mg/cm2
	Consumers	Oral	Long-term systemic	160 mg/kg
			effects	bw/day
	Consumers	Oral	Acute systemic effects	160 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	43,2 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	21,6 mg/kg bw/day
2-methoxy-1- methylethyl acetate	Workers	Inhalation	Long-term systemic effects	275 mg/m3
	Workers	Inhalation	Acute local effects	550 mg/m3
	Consumers	Inhalation	Long-term systemic effects	33 mg/m3
	Consumers	Inhalation	Long-term local effects	33 mg/m3
	Workers	Dermal	Long-term systemic effects	796 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	320 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	36 mg/kg bw/day
strontium bis(2- ethylhexanoate)	Workers	Inhalation	Long-term systemic effects	0,730 mg/m3
	Workers	Dermal	Long-term systemic effects	0,410 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	0,180 mg/m3
	Consumers	Dermal	Long-term systemic effects	0,210 mg/kg bw/day
	Consumers	Oral	Long-term systemic	0,210 mg/kg

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



TESSAROL DIRECT 3in1 RAL----

Version Revision Date: SDS Number: Date of last issue: 18.01.2024 2.0 08.03.2024 MAT0GA00_104 Date of first issue: 09.03.2021

GB/EN

effects bw/day

Predicted No Effect Concentration (PNEC):

according to Regulation (EC) No. 1907/2006

Substance name	Environmental Compartment	Value
titanium dioxide	Soil	100 mg/kg dry
		weight (d.w.)
	Marine water	0,0184 mg/l
	Fresh water	0,184 mg/l
	Marine sediment	100 mg/kg dry
		weight (d.w.)
	Fresh water sediment	1000 mg/kg dry
		weight (d.w.)
	Sewage treatment plant	100 mg/l
	Intermittent use/release	0,193 mg/l
barium sulfate	Soil	207,7 mg/kg dry
		weight (d.w.)
	Fresh water	0,115 mg/l
	Fresh water sediment	600,4 mg/kg dry
		weight (d.w.)
	Sewage treatment plant	62,2 mg/l
1-methoxy-2-propanol	Soil	4,59 mg/kg dry
, , ,		weight (d.w.)
	Marine water	1 mg/l
	Fresh water	10 mg/l
	Marine sediment	5,2 mg/kg dry
		weight (d.w.)
	Fresh water sediment	52,3 mg/kg dry
		weight (d.w.)
	Sewage treatment plant	100 mg/l
	Intermittent use/release	100 mg/l
Talc	Marine water	141,26 mg/l
	Fresh water	597,97 mg/l
	Marine sediment	3,13 mg/kg dry
		weight (d.w.)
	Fresh water sediment	31,33 mg/kg dry
		weight (d.w.)
	Intermittent use/release	597,97 mg/l
2-methoxy-1-methylethyl acetate	Soil	0,29 mg/kg dry
		weight (d.w.)
	Marine water	0,0635 mg/l
	Fresh water	0,635 mg/l
	Marine sediment	0,329 mg/kg dry
		weight (d.w.)
	Fresh water sediment	3,29 mg/kg dry
		weight (d.w.)
	Sewage treatment plant	100 mg/l
	Intermittent use/release	0,00635 mg/l
strontium bis(2-ethylhexanoate)	Fresh water	0,360 - 0,440

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



TESSAROL DIRECT 3in1 RAL----

Version Revision Date: SDS Number: Date of last issue: 18.01.2024 2.0 08.03.2024 MAT0GA00_104 Date of first issue: 09.03.2021

GB/EN

	mg/l
Intermittent use/release	0,493 - 0,610 mg/l
Marine water	0,036 - 0,040 mg/l
Sewage treatment plant	71,7 - 88,52 mg/l
Fresh water sediment	6,37 - 7,86 mg/kg dry weight (d.w.)
Marine sediment	0,637 - 0,790 mg/kg dry weight (d.w.)
Soil	1,06 - 1,31 mg/kg dry weight (d.w.)

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Equipment should conform to EN 166

Eye wash bottle with pure water Tightly fitting safety goggles

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of

cuts, abrasion, and the contact time.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concen-

tration of the dangerous substance at the work place.

Respiratory protection : Use respiratory protection unless adequate local exhaust ven-

tilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Equipment should conform to EN 14387

Filter type : Combined particulates and organic vapour type (A-P)

Protective measures : Wash thoroughly after handling.

Avoid contact with skin, eyes and clothing.

Keep away from food, drink and animal feedingstuffs.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : in accordance with the product description

Odour : solvent-like
Odour Threshold : No data available

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



TESSAROL DIRECT 3in1 RAL----

Version 2.0

Revision Date: 08.03.2024

SDS Number: MAT0GA00_104

Date of last issue: 18.01.2024 Date of first issue: 09.03.2021

GB/EN

рΗ : No data available

< 0.0 °C Melting point/freezing point

(calculation method (principal components, lowest value)) 155 - 192 °C (calculation method (principal components, low-Boiling point/boiling range

est value))

Flash point 40 °C (calculation method (principal components, lowest val-

ue))

Static-accumulating flammable liquid., Combustible Solids Flammability (solid, gas)

Vapour pressure 2 hPa (calculation method (principal components, highest

value))

Relative vapour density No data available

Relative density No data available

Density 1,10 - 1,20 g/cm3

Solubility(ies)

Water solubility insoluble

Solubility in other solvents Description: miscible with most organic solvents

Partition coefficient: n-

octanol/water

No data available

Decomposition temperature No decomposition if stored and applied as directed.

Hazardous decomposition products formed under fire condi-

tions.

Viscosity

Viscosity, kinematic $> 20,5 \text{ mm}2/\text{s} (40 ^{\circ}\text{C})$

Flow time > 40 s at 23 °C

> Cross section: 6 mm Method: ISO 2431

Explosive properties Not applicable

Sustains combustion Oxidizing properties

9.2 Other information

No data available

VOC (Directive 2004/42/EC)

500 g/l

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



TESSAROL DIRECT 3in1 RAL----

Version 2.0

Revision Date: 08.03.2024

SDS Number: MAT0GA00_104

Date of last issue: 18.01.2024 Date of first issue: 09.03.2021

GB/EN

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Not applicable

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

Not classified due to lack of data.

Components:

1-methoxy-2-propanol:

Acute oral toxicity : LD50 Oral (Rabbit): > 2.000 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg

2-methoxy-1-methylethyl acetate:

Acute oral toxicity : LD50 Oral (Rat): > > 2.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l

Test atmosphere: vapour

LC0 (Rat): 2000 ppm Exposure time: 3 h

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



TESSAROL DIRECT 3in1 RAL----

Version Revision Date: SDS Number: Date of last issue: 18.01.2024 2.0 08.03.2024 MAT0GA00_104 Date of first issue: 09.03.2021

GB/EN

Acute dermal toxicity : LD50 (Rabbit): > > 2.000 mg/kg

strontium bis(2-ethylhexanoate):

Acute oral toxicity : Assessment: The component/mixture is moderately toxic after

single ingestion.

Skin corrosion/irritation

Not classified based on available information.

Not classified due to lack of data.

Product:

Remarks : May cause skin irritation and/or dermatitis.

Components:

strontium bis(2-ethylhexanoate):

Result : irritating

Serious eye damage/eye irritation

Not classified based on available information.

Not classified due to lack of data.

Product:

Remarks : Vapours may cause irritation to the eyes, respiratory system

and the skin.

Components:

strontium bis(2-ethylhexanoate):

Result : Corrosive

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Skin sensitisation

Not classified due to lack of data.

Respiratory sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified due to lack of data.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



TESSAROL DIRECT 3in1 RAL----

Version Revision Date: SDS Number: Date of last issue: 18.01.2024 2.0 08.03.2024 MAT0GA00_104 Date of first issue: 09.03.2021

GB/EN

Product:

Remarks : Causes sensitisation.

Components:

mixture of sterically composed sebacates:

Result : May cause sensitisation by skin contact.

Germ cell mutagenicity

Not classified based on available information.

Not classified due to lack of data.

Carcinogenicity

Not classified based on available information.

Not classified due to lack of data.

Reproductive toxicity

Not classified based on available information.

Not classified due to lack of data.

Components:

mixture of sterically composed sebacates:

Reproductive toxicity - As- : Some evidence of adverse effects on sexual function and

sessment fertility ,based on animal experiments.

STOT - single exposure

May cause drowsiness or dizziness. May cause drowsiness or dizziness.

Components:

hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics:

Assessment : May cause drowsiness or dizziness.

1-methoxy-2-propanol:

Assessment : May cause drowsiness or dizziness.

2-methoxy-1-methylethyl acetate:

Assessment : May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Not classified due to lack of data.

Aspiration toxicity

Not classified based on available information.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



TESSAROL DIRECT 3in1 RAL----

Version Revision Date: 2.0 08.03.2024

SDS Number: MAT0GA00_104 Date of last issue: 18.01.2024 Date of first issue: 09.03.2021

GB/EN

Not classified due to lack of data.

Components:

hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks Symptoms of overexposure may be headache, dizziness,

tiredness, nausea and vomiting.

Concentrations substantially above the TLV value may cause

narcotic effects.

Solvents may degrease the skin.

SECTION 12: Ecological information

12.1 Toxicity

Components:

1-methoxy-2-propanol:

Toxicity to fish : LC50 (Fish): > 1.000 mg/l

Exposure time: 96 h

aquatic invertebrates

Toxicity to algae/aquatic

plants

Toxicity to daphnia and other : LC50 (Daphnia (water flea)): > 1.000 mg/l

LC50 (algae): > 1.000 mg/l

2-methoxy-1-methylethyl acetate:

Toxicity to fish LC50 (Oncorhynchus mykiss (rainbow trout)): 130 mg/l

Exposure time: 96 h

NOEC: 100 mg/l Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

LC50: 408 mg/l Exposure time: 48 h

EC10: 47,5 mg/l

Toxicity to fish (Chronic tox-

icity)

mixture of sterically composed sebacates:

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



TESSAROL DIRECT 3in1 RAL----

Version Revision Date: SDS Number: Date of last issue: 18.01.2024 2.0 08.03.2024 MAT0GA00_104 Date of first issue: 09.03.2021

GB/EN

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

Components:

2-methoxy-1-methylethyl acetate:

Biodegradability : Readily biodegradable.

12.3 Bioaccumulative potential

Components:

1-methoxy-2-propanol:

Partition coefficient: n- : log Pow: -0,437

octanol/water

2-methoxy-1-methylethyl acetate:

Partition coefficient: n- : log Pow: 1,2 (20 °C)

octanol/water pH: 6,8

mixture of sterically composed sebacates:

Partition coefficient: n- : log Pow: 2,37 - 2,77

octanol/water pH: 7

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Other adverse effects

Product:

Endocrine disrupting poten-

ial

This substance/mixture does not contain components considered to have endocrine disrupting properties for environment

according to UK REACH Article 57(f).

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Harmful to aquatic life with long lasting effects.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



TESSAROL DIRECT 3in1 RAL----

Version 2.0

Revision Date: 08.03.2024

SDS Number: MAT0GA00_104

GB/EN

Date of last issue: 18.01.2024 Date of first issue: 09.03.2021

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

Waste Code : 08 01 11, waste paint and varnish containing organic solvents

or other hazardoussubstances

SECTION 14: Transport information

14.1 UN number

ADN : UN 1263
ADR : UN 1263
RID : UN 1263
IMDG : UN 1263
IATA : UN 1263

14.2 UN proper shipping name

ADN : PAINT
ADR : PAINT
RID : PAINT
IMDG : PAINT
IATA : PAINT

14.3 Transport hazard class(es)

Class Subsidiary risks

 ADN
 : 3

 ADR
 : 3

 RID
 : 3

 IMDG
 : 3

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



TESSAROL DIRECT 3in1 RAL----

Version Revision Date: 2.0

SDS Number: 08.03.2024 MAT0GA00_104

GB/EN

Date of last issue: 18.01.2024 Date of first issue: 09.03.2021

IATA 3

14.4 Packing group

ADN

Packing group Ш Classification Code F1 Hazard Identification Number : 30 Labels 3

ADR

Packing group Ш Classification Code F1 Hazard Identification Number : 30 Labels 3 Tunnel restriction code (D/E)

RID

Packing group Ш Classification Code F1 Hazard Identification Number : 30 Labels 3

IMDG

Packing group Ш Labels 3 **EmS Code** F-E, <u>S-E</u>

IATA (Cargo)

Packing instruction (cargo 366

aircraft)

Packing instruction (LQ) Y344 Packing group Ш

Labels Flammable Liquids

IATA (Passenger)

Packing instruction (passen-355

ger aircraft)

Packing instruction (LQ) Y344 Packing group Ш

Labels Flammable Liquids

14.5 Environmental hazards

ADN

Environmentally hazardous no

Environmentally hazardous no

Environmentally hazardous no

IMDG

Marine pollutant no

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



TESSAROL DIRECT 3in1 RAL----

Version Revision Date: SDS Number: Date of last issue: 18.01.2024 08.03.2024 MAT0GA00_104 Date of first issue: 09.03.2021 2.0

GB/EN

14.6 Special precautions for user

Remarks ADR: Packages smaller than or equal to 450 litres, not

> goods/merchandise of Class 3 (exemption ADR 2.2.3.1.5) IMDG: Packages smaller than or equal to 450 litres, not goods/merchandise of Class 3; "transport acc. IMDG-code

2.3.2.5"

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17) : Conditions of restriction for the fol-

lowing entries should be considered:

Number on list 3

: Not applicable

Not applicable

UK REACH Candidate list of substances of very high

concern (SVHC) for Authorisation

The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Brit-

ain)

Regulation (EC) No 1005/2009 on substances that de-Not applicable

plete the ozone layer

UK REACH List of substances subject to authorisation Not applicable

(Annex XIV)

GB Export and import of hazardous chemicals - Prior Not applicable

Informed Consent (PIC) Regulation

Control of Major Accident Hazards Regulations P5c FLAMMABLE LIQUIDS

2015 (COMAH)

Volatile organic compounds Directive 2004/42/EC

Volatile organic compounds (VOC) content: 500 g/l

Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



TESSAROL DIRECT 3in1 RAL----

Version Revision Date: SDS Number: Date of last issue: 18.01.2024 2.0 08.03.2024 MAT0GA00_104 Date of first issue: 09.03.2021

GB/EN

15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

SECTION 16: Other information

Full text of H-Statements

H226 : Flammable liquid and vapour.

H302 : Harmful if swallowed.

H304 : May be fatal if swallowed and enters airways.

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H336 : May cause drowsiness or dizziness.
H361f : Suspected of damaging fertility.

H400 : Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Acute : Short-term (acute) aquatic hazard
Aquatic Chronic : Long-term (chronic) aquatic hazard

Asp. Tox. : Aspiration hazard
Eye Dam. : Serious eye damage
Flam. Liq. : Flammable liquids
Repr. : Reproductive toxicity

Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation

STOT SE : Specific target organ toxicity - single exposure

2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first

list of indicative occupational exposure limit values

2004/37/EC : Europe. Directive 2004/37/EC on the protection of workers

from the risks related to exposure to carcinogens or mutagens

at work

GB EH40 : UK. EH40 WEL - Workplace Exposure Limits

2000/39/EC / TWA : Limit Value - eight hours 2000/39/EC / STEL : Short term exposure limit 2004/37/EC / TWA : Long term exposure limit

GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good La-

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



TESSAROL DIRECT 3in1 RAL----

Version Revision Date: SDS Number: Date 2.0 08.03.2024 MAT0GA00_104 Date

GB/EN

Date of last issue: 18.01.2024 Date of first issue: 09.03.2021

boratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI -Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:	Classification procedure:

Flam. Liq. 3 H226 Based on product data or assessment

STOT SE 3 H336 Calculation method
Aquatic Chronic 3 H412 Calculation method

Material codes (bulk) for : 400677; 401630; 401631; 401632; 401633; 401634; 401635; which the SDS is valid : 401638; 401703; 401704; 401705; 401706; 401707; 401791;

401796; 401797

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.