

# SAFETY DATA SHEET



## MasterMix Universal Putty

Version	Revision Date:	SDS Number:	Date of last issue: 31.01.2024
1.2	09.02.2024	MAT0PL400902 ZA/EN	Date of first issue: 30.01.2024

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : MasterMix Universal Putty

Product code : 40090213  
PLA000020-0218

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-  
stance/Mixture : Body filler/stopper

Recommended restrictions  
on use : Reserved for industrial and professional use.

#### 1.3 Details of the supplier of the safety data sheet

Company : Kansai Plascon  
Frederick Cooper Drive 10  
Factoria, Krugersdorp  
South Africa  
[www.plascon.com](http://www.plascon.com)

Telephone Company : 2711 951 4500  
2783 991 5782

Telefax Company : 2711 955 2841

Responsible/issuing person : 2711 951 4500  
2783 991 5782  
[mmundondo@kansaiplascon.co.za](mailto:mmundondo@kansaiplascon.co.za)

#### 1.4 Emergency telephone number

Emergency Number: 112; Ambulance: 10177

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Reproductive toxicity, Category 2	H361d: Suspected of damaging the unborn child.
Specific target organ toxicity - repeated	H372: Causes damage to organs through pro-

# SAFETY DATA SHEET



## MasterMix Universal Putty

Version  
1.2

Revision Date:  
09.02.2024

SDS Number:  
MAT0PL400902  
ZA/EN

Date of last issue: 31.01.2024  
Date of first issue: 30.01.2024

exposure, Category 1

longed or repeated exposure.

### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements :  
H226 Flammable liquid and vapour.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H361d Suspected of damaging the unborn child.  
H372 Causes damage to organs through prolonged or repeated exposure.

Precautionary statements :

#### Prevention:

P201 Obtain special instructions before use.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P260 Do not breathe mist or vapours.  
P264 Wash skin thoroughly after handling.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

#### Response:

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

styrene  
maleic anhydride

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)

# SAFETY DATA SHEET

## MasterMix Universal Putty



Version  
1.2

Revision Date:  
09.02.2024

SDS Number:  
MAT0PL400902  
ZA/EN

Date of last issue: 31.01.2024  
Date of first issue: 30.01.2024

styrene	108-31-6 202-851-5 601-026-00-0 01-2119457861-32	Flam. Liq. 3; H226 Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Repr. 2; H361d STOT SE 3; H335 (Respiratory system) STOT RE 1; H372 (hearing organs) Asp. Tox. 1; H304 Aquatic Chronic 3; H412	$\geq 10 - < 20$
toluene	203-625-9 601-021-00-3 01-2119471310-51	Flam. Liq. 2; H225 Skin Irrit. 2; H315 Repr. 2; H361d STOT SE 3; H336 (Central nervous system) STOT RE 2; H373 Asp. Tox. 1; H304 Aquatic Chronic 3; H412	$\geq 1 - < 2,5$
maleic anhydride	203-571-6 607-096-00-9 01-2119472428-31	Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 Resp. Sens. 1; H334 STOT RE 1; H372 (Respiratory system)	$\geq 0,001 - < 0,1$
Substances with a workplace exposure limit :			
talc	238-877-9 01-2120140278-58		$\geq 30 - < 50$

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.

**MasterMix Universal Putty**

Version  
1.2

Revision Date:  
09.02.2024

SDS Number:  
MAT0PL400902  
ZA/EN

Date of last issue: 31.01.2024  
Date of first issue: 30.01.2024

- In case of skin contact : If skin irritation persists, call a physician.  
If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.

**4.2 Most important symptoms and effects, both acute and delayed**

- Risks : Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye irritation.  
Suspected of damaging the unborn child.  
Causes damage to organs through prolonged or repeated exposure.

**4.3 Indication of any immediate medical attention and special treatment needed**

- Treatment : Treat symptomatically.

---

**SECTION 5: Firefighting measures****5.1 Extinguishing media**

- Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : High volume water jet

**5.2 Special hazards arising from the substance or mixture**

- Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : No hazardous combustion products are known

**5.3 Advice for firefighters**

- Special protective equipment : Wear self-contained breathing apparatus for firefighting if nec-

**MasterMix Universal Putty**

Version	Revision Date:	SDS Number:	Date of last issue: 31.01.2024
1.2	09.02.2024	MAT0PL400902 ZA/EN	Date of first issue: 30.01.2024

---

for firefighters

essary.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.

---

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**

Personal precautions : Use personal protective equipment.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

**6.2 Environmental precautions**

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

**6.3 Methods and material for containment and cleaning up**

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

**6.4 Reference to other sections**

See sections: 7, 8, 11, 12 and 13.

---

**SECTION 7: Handling and storage****7.1 Precautions for safe handling**

Advice on safe handling : Avoid formation of aerosol.  
Do not breathe vapours/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Open drum carefully as content may be under pressure.

# SAFETY DATA SHEET



## MasterMix Universal Putty

Version  
1.2

Revision Date:  
09.02.2024

SDS Number:  
MAT0PL400902  
ZA/EN

Date of last issue: 31.01.2024  
Date of first issue: 30.01.2024

- Advice on protection against fire and explosion : Dispose of rinse water in accordance with local and national regulations.  
Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.
- Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage stability : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

- Specific use(s) : For further information, refer to the product technical data sheet.
- Consult the technical guidelines for the use of this substance/mixture.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Talc	14807-96-6	TWA OEL-RL (respirable dust fraction)	4 mg/m <sup>3</sup>	ZA OEL
Further information: Recommended Limit				
		TWA (Respirable dust)	0,1 mg/m <sup>3</sup>	2004/37/EC
styrene	100-42-5	TWA OEL-CL	40 ppm	ZA OEL
Further information: Control Limit, denotes carcinogenicity, which is based on GHS categorisation, including category 1A, 1B				
		STEL OEL-CL	80 ppm	ZA OEL
Further information: Control Limit, denotes carcinogenicity, which is based on GHS categorisation, including category 1A, 1B				
titanium dioxide	13463-67-7	TWA OEL-RL	10 mg/m <sup>3</sup>	ZA OEL
Further information: Recommended Limit, denotes carcinogenicity, which is based on GHS categorisation, including category 1A, 1B				
toluene	108-88-3	TWA OEL-RL	40 ppm	ZA OEL

# SAFETY DATA SHEET



## MasterMix Universal Putty

Version  
1.2

Revision Date:  
09.02.2024

SDS Number:  
MAT0PL400902  
ZA/EN

Date of last issue: 31.01.2024  
Date of first issue: 30.01.2024

	Further information: Absorption through the skin, Recommended Limit			
		TWA	50 ppm 192 mg/m <sup>3</sup>	2006/15/EC
		STEL	100 ppm 384 mg/m <sup>3</sup>	2006/15/EC
maleic anhydride	108-31-6	TWA OEL-RL (inhalable fraction and vapour)	0,02 mg/m <sup>3</sup>	ZA OEL
	Further information: Recommended Limit, dermal sensitisation, potential to produce dermal sensitisation, respiratory sensitisation, potential to produce respiratory sensitisation			

### Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
styrene	100-42-5	Mandelic acid and phenylglyoxylic acid: 400 mg/g creatinine (Urine)	End of shift	ZA BEI
		Styrene: 40 µg/l (Urine)	End of shift	ZA BEI
toluene	108-88-3	Toluene: 0,02 mg/l (Blood)	Prior to last shift of workweek	ZA BEI
		Toluene: 0,03 mg/l (Urine)	End of shift	ZA BEI
		o-Cresol: 0.3 mg/g creatinine (Urine)	End of shift	ZA BEI

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Talc	Workers	Inhalation	Acute systemic effects	2,16 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	3,6 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute systemic effects	1,08 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute local effects	1,8 mg/m <sup>3</sup>
	Consumers	Dermal	Long-term local effects	2,27 mg/cm <sup>2</sup>
	Workers	Dermal	Long-term local effects	4,54 mg/cm <sup>2</sup>
	Consumers	Oral	Long-term systemic effects	160 mg/kg bw/day
	Consumers	Oral	Acute systemic effects	160 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	43,2 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	21,6 mg/kg bw/day
styrene	Workers	Inhalation	Acute systemic ef-	100 mg/m <sup>3</sup>

## SAFETY DATA SHEET



## MasterMix Universal Putty

Version  
1.2Revision Date:  
09.02.2024SDS Number:  
MAT0PL400902  
ZA/ENDate of last issue: 31.01.2024  
Date of first issue: 30.01.2024

			fects	
	Workers	Inhalation	Acute local effects	100 mg/m3
	Workers	Inhalation	Long-term systemic effects	85 mg/m3
	Consumers	Inhalation	Acute systemic effects	10 mg/m3
	Consumers	Inhalation	Acute local effects	10 mg/m3
	Consumers	Inhalation	Long-term systemic effects	1 mg/m3
	Workers	Inhalation	Long-term local effects	100 mg/m3
	Workers	Inhalation	Long-term local effects	1 mg/m3
	Workers	Dermal	Long-term systemic effects	406 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	343 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	0,0077 mg/kg bw/day
titanium dioxide	Workers	Inhalation	Long-term local effects	10 mg/m3
	Consumers	Oral	Long-term systemic effects	700 mg/kg bw/day
toluene	Workers	Inhalation	Long-term systemic effects	192 mg/m3
	Workers	Inhalation	Long-term local effects	192 mg/m3
	Consumers	Inhalation	Acute systemic effects	226 mg/m3
	Consumers	Inhalation	Acute local effects	226 mg/m3

**Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:**

Substance name	Environmental Compartment	Value
Talc	Marine water	141,26 mg/l
	Fresh water	597,97 mg/l
	Marine sediment	3,13 mg/kg dry weight (d.w.)
	Fresh water sediment	31,33 mg/kg dry weight (d.w.)
	Intermittent use/release	597,97 mg/l
styrene	Soil	0,146 - 0,200 mg/kg dry weight (d.w.)
	Marine water	0,014 - 0,040 mg/l
	Fresh water	0,028 - 0,040 mg/l
	Marine sediment	0,307 - 0,418 mg/kg dry weight (d.w.)
	Fresh water sediment	0,418 - 0,614



# SAFETY DATA SHEET



## MasterMix Universal Putty

Version  
1.2

Revision Date:  
09.02.2024

SDS Number:  
MAT0PL400902  
ZA/EN

Date of last issue: 31.01.2024  
Date of first issue: 30.01.2024

		mg/kg dry weight (d.w.)
	Sewage treatment plant	5 mg/l
titanium dioxide	Soil	100 mg/kg dry weight (d.w.)
	Marine water	0,0184 mg/l
	Fresh water	0,184 mg/l
	Marine sediment	100 mg/kg dry weight (d.w.)
	Fresh water sediment	1000 mg/kg dry weight (d.w.)
	Sewage treatment plant	100 mg/l
	Intermittent use/release	0,193 mg/l
toluene	Soil	2,89 mg/kg dry weight (d.w.)
	Marine water	0,68 mg/l
	Fresh water	0,68 mg/l
	Marine sediment	16,39 mg/kg dry weight (d.w.)
	Fresh water sediment	16,39 mg/kg dry weight (d.w.)
	Sewage treatment plant	13,61 mg/l
	Intermittent use/release	0,68 mg/l

### 8.2 Exposure controls

#### Personal protective equipment

Eye/face protection : Equipment should conform to EN 166  
Eye wash bottle with pure water  
Tightly fitting safety goggles  
Wear face-shield and protective suit for abnormal processing problems.

Hand protection

Gloves : Nitrile rubber (> 0,1 mm; < 60 min); ISO EN374 |  
butyl-rubber (> 0,6 mm; < 240 min); ISO EN374 |  
Viton® (> 0,6 mm; < 240 min); ISO EN374 |  
PE laminate (> 0,1 mm; < 240 min); ISO EN374 |

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.  
Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

Skin and body protection : Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : Wear a full face respirator conforming to EN136 with Type A/P2 filter or better.

## MasterMix Universal Putty

Version  
1.2Revision Date:  
09.02.2024SDS Number:  
MAT0PL400902  
ZA/ENDate of last issue: 31.01.2024  
Date of first issue: 30.01.2024

Self-contained closed-circuit breathing apparatus compressed (EN 145)  
In the case of aerosol and mist formation use an approved respirator filter (EN 141).

**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties**

Appearance	: viscous liquid
Colour	: in accordance with the product description
Odour	: solvent-like
Odour Threshold	: No data available
pH	: Not applicable
Melting point/freezing point	: -31,0 °C (calculation method (principal components, lowest value))
Boiling point/boiling range	: 145 °C (calculation method (principal components, lowest value))
Flash point	: 32 °C Method: ISO 3679, closed cup
Evaporation rate	: No data available
Flammability (solid, gas)	: Static-accumulating flammable liquid., Combustible Solids
Upper explosion limit / Upper flammability limit	: 8 %(V) (calculation method (principal components, highest value))
Lower explosion limit / Lower flammability limit	: 1,1 %(V) (calculation method (principal components, highest value))
Relative vapour density	: 3,6 (calculation method (principal components, highest value))  (Air = 1.0)
Relative density	: No data available
Density	: 1,762 g/cm <sup>3</sup>
Solubility(ies)	
Water solubility	: immiscible partly soluble
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: log Pow: 2,95 (calculation method (principal components, highest value))

# SAFETY DATA SHEET



## MasterMix Universal Putty

Version  
1.2

Revision Date:  
09.02.2024

SDS Number:  
MAT0PL400902  
ZA/EN

Date of last issue: 31.01.2024  
Date of first issue: 30.01.2024

---

Ignition temperature : 490 °C (calculation method (principal components, highest value))

Decomposition temperature : No decomposition if stored and applied as directed.  
Hazardous decomposition products formed under fire conditions.

Viscosity  
Viscosity, kinematic : > 20,5 mm<sup>2</sup>/s (40 °C)

Explosive properties : Not applicable

Oxidizing properties : Sustains combustion

### 9.2 Other information

No data available  
VOC : (Directive 2004/42/EC)  
250 g/l

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.  
Vapours may form explosive mixture with air.

### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

### 10.5 Incompatible materials

Materials to avoid : Incompatible with strong acids and bases.

### 10.6 Hazardous decomposition products

No hazardous decomposition products are known.

## MasterMix Universal Putty

Version  
1.2Revision Date:  
09.02.2024SDS Number:  
MAT0PL400902  
ZA/ENDate of last issue: 31.01.2024  
Date of first issue: 30.01.2024

---

**SECTION 11: Toxicological information****11.1 Information on toxicological effects****Acute toxicity**

Not classified due to lack of data.

**Product:**

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method

**Components:****styrene:**

Acute oral toxicity : LD50 Oral (Rat):  $\geq 5.000$  mg/kg  
  
Acute inhalation toxicity : LC50 (Rat):  $\geq 24$  mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
  
Acute dermal toxicity : LD50 (Rabbit): > 2.650 mg/kg

**toluene:**

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg  
  
Acute inhalation toxicity : LC50 (Rat): > 28 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
  
Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

**maleic anhydride:**

Acute oral toxicity : Assessment: The component/mixture is moderately toxic after single ingestion.

**Skin corrosion/irritation**

Causes skin irritation.

**Product:**

Remarks : May cause skin irritation in susceptible persons.

**Components:****styrene:**

Result : irritating

# SAFETY DATA SHEET



## MasterMix Universal Putty

Version  
1.2

Revision Date:  
09.02.2024

SDS Number:  
MAT0PL400902  
ZA/EN

Date of last issue: 31.01.2024  
Date of first issue: 30.01.2024

---

### **toluene:**

Result : irritating

### **maleic anhydride:**

Result : Corrosive after 3 minutes to 1 hour of exposure

### **Serious eye damage/eye irritation**

Causes serious eye irritation.

### **Product:**

Remarks : May cause irreversible eye damage.

### **Components:**

#### **styrene:**

Result : Eye irritation

### **Respiratory or skin sensitisation**

#### **Skin sensitisation**

May cause an allergic skin reaction.

#### **Respiratory sensitisation**

Not classified due to lack of data.

### **Components:**

#### **maleic anhydride:**

Result : Probability of respiratory sensitisation in humans based on animal testing

Result : Probability or evidence of skin sensitisation in humans

### **Germ cell mutagenicity**

Not classified due to lack of data.

### **Carcinogenicity**

Not classified due to lack of data.

### **Reproductive toxicity**

Suspected of damaging the unborn child.

### **Components:**

#### **styrene:**

Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility ,and/or on development, based on animal experiments.

### **toluene:**

# SAFETY DATA SHEET



## MasterMix Universal Putty

Version  
1.2

Revision Date:  
09.02.2024

SDS Number:  
MAT0PL400902  
ZA/EN

Date of last issue: 31.01.2024  
Date of first issue: 30.01.2024

---

Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility ,and/or on development, based on animal experiments.

### STOT - single exposure

Not classified due to lack of data.

#### Components:

##### styrene:

Assessment : May cause respiratory irritation.

##### toluene:

Assessment : May cause drowsiness or dizziness.

### STOT - repeated exposure

Causes damage to organs through prolonged or repeated exposure.

#### Components:

##### styrene:

Assessment : Causes damage to organs through prolonged or repeated exposure.

##### toluene:

Assessment : May cause damage to organs through prolonged or repeated exposure.

##### maleic anhydride:

Assessment : May cause damage to organs through prolonged or repeated exposure.

### Aspiration toxicity

Not classified due to lack of data.

#### Components:

##### styrene:

May be fatal if swallowed and enters airways.

##### toluene:

May be fatal if swallowed and enters airways.

### Further information

#### Product:

Remarks : Solvents may degrease the skin.

## MasterMix Universal Putty

Version  
1.2Revision Date:  
09.02.2024SDS Number:  
MAT0PL400902  
ZA/ENDate of last issue: 31.01.2024  
Date of first issue: 30.01.2024

---

SECTION 12: Ecological information

## 12.1 Toxicity

Components:**styrene:**Toxicity to fish : LC50 (Fish):  $\geq 10 - 12$  mg/lToxicity to daphnia and other : LC50 (Daphnia (water flea)):  $\geq 4,7$  mg/l  
aquatic invertebrates**Ecotoxicology Assessment**

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

**toluene:****Ecotoxicology Assessment**

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

**maleic anhydride:**Toxicity to fish : LC50 : 75 mg/l  
Exposure time: 96 hToxicity to daphnia and other : NOEC: 10 mg/l  
aquatic invertebrates (Chronic toxicity) Exposure time: 21 d  
Species: Daphnia magna (Water flea)

## 12.2 Persistence and degradability

Components:**styrene:**Biodegradability : Test Type: aerobic  
Readily biodegradable.Test Type: anaerobic  
According to the results of tests of biodegradability this product is not readily biodegradable.Physico-chemical removability : The product evaporates readily.  
Readily biodegradable.

Stability in water : Hydrolyses slowly.

Photodegradation : Decomposes rapidly in contact with light.

**maleic anhydride:**

Biodegradability : Result: Biodegradable

# SAFETY DATA SHEET



## MasterMix Universal Putty

Version  
1.2

Revision Date:  
09.02.2024

SDS Number:  
MAT0PL400902  
ZA/EN

Date of last issue: 31.01.2024  
Date of first issue: 30.01.2024

Biodegradation: 90 %  
Exposure time: 25 d  
Method: OECD Test Guideline 301B

Stability in water : Hydrolyses readily.

Photodegradation :

### 12.3 Bioaccumulative potential

#### Components:

##### **styrene:**

Bioaccumulation : Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water : log Pow: 2,95

##### **toluene:**

Partition coefficient: n-octanol/water : log Pow: 2,65

##### **maleic anhydride:**

Bioaccumulation : Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water : log Pow: -2,61 (20 °C)

### 12.4 Mobility in soil

#### Components:

##### **styrene:**

Mobility : Medium: Air  
Content: 98,6 %

: Medium: Water  
Content: 1,21 %

: Medium: Sediment  
Content: 0,09 %

: Medium: Soil  
Content: 0,09 %

##### **maleic anhydride:**

Mobility : Medium: Water  
Content: 100 %

: Medium: Soil  
Content: 0 %

Distribution among environ- : Koc: 42, log Koc: 1,63



# SAFETY DATA SHEET



## MasterMix Universal Putty

Version	Revision Date:	SDS Number:	Date of last issue: 31.01.2024
1.2	09.02.2024	MAT0PL400902	Date of first issue: 30.01.2024
		ZA/EN	

mental compartments

### 12.5 Results of PBT and vPvB assessment

#### **Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Other adverse effects

#### **Product:**

Endocrine disrupting potential : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Additional ecological information : No data available

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

## SECTION 14: Transport information

### 14.1 UN number

UNRTDG	: UN 3269
IMDG	: UN 3269
IATA	: UN 3269
SANS 10228	: UN 3269

### 14.2 UN proper shipping name

UNRTDG	: POLYESTER RESIN KIT
IMDG	: POLYESTER RESIN KIT

# SAFETY DATA SHEET



## MasterMix Universal Putty

Version	Revision Date:	SDS Number:	Date of last issue: 31.01.2024
1.2	09.02.2024	MAT0PL400902 ZA/EN	Date of first issue: 30.01.2024

---

**IATA** : Polyester resin kit

**SANS 10228** : POLYESTER RESIN KIT

### 14.3 Transport hazard class(es)

	Class	Subsidiary risks
<b>UNRTDG</b>	: 3	
<b>IMDG</b>	: 3	
<b>IATA</b>	: 3	
<b>SANS 10228</b>	: 3	

### 14.4 Packing group

**UNRTDG**  
Packing group : III  
Labels : 3

**IMDG**  
Packing group : III  
Labels : 3  
EmS Code : F-E, S-D

**IATA (Cargo)**  
Packing instruction (cargo aircraft) : 370  
Packing instruction (LQ) : Y370  
Packing group : III  
Labels : Flammable Liquids

**IATA (Passenger)**  
Packing instruction (passenger aircraft) : 370  
Packing instruction (LQ) : Y370  
Packing group : III  
Labels : Flammable Liquids

**SANS 10228**  
Packing group : III  
Labels : 3

### 14.5 Environmental hazards

**UNRTDG**  
Environmentally hazardous : no

**IMDG**  
Marine pollutant : no

**SANS 10228**  
Environmentally hazardous : no

### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data

# SAFETY DATA SHEET



## MasterMix Universal Putty

Version	Revision Date:	SDS Number:	Date of last issue: 31.01.2024
1.2	09.02.2024	MAT0PL400902 ZA/EN	Date of first issue: 30.01.2024

Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Volatile organic compounds : Directive 2004/42/EC  
Volatile organic compounds (VOC) content: 250 g/l

### 15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

## SECTION 16: Other information

### Full text of H-Statements

H225	: Highly flammable liquid and vapour.
H226	: Flammable liquid and vapour.
H302	: Harmful if swallowed.
H304	: May be fatal if swallowed and enters airways.
H314	: Causes severe skin burns and eye damage.
H315	: Causes skin irritation.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H334	: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H361d	: Suspected of damaging the unborn child.
H372	: Causes damage to organs through prolonged or repeated exposure.
H373	: May cause damage to organs through prolonged or repeated exposure.
H412	: Harmful to aquatic life with long lasting effects.

### Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Eye Dam.	: Serious eye damage
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids

# SAFETY DATA SHEET



## MasterMix Universal Putty

Version	Revision Date:	SDS Number:	Date of last issue: 31.01.2024
1.2	09.02.2024	MAT0PL400902	Date of first issue: 30.01.2024
		ZA/EN	

Repr.	: Reproductive toxicity
Resp. Sens.	: Respiratory sensitisation
Skin Corr.	: Skin corrosion
Skin Irrit.	: Skin irritation
STOT RE	: Specific target organ toxicity - repeated exposure
STOT SE	: Specific target organ toxicity - single exposure
2004/37/EC	: Europe. Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens or mutagens at work
2006/15/EC	: Europe. Indicative occupational exposure limit values
ZA BEI	: South Africa. The Regulations for Hazardous Chemical Agents, Biological Exposure Indices
ZA OEL	: South Africa. The Regulations for Hazardous Chemical Agents, Occupational Exposure Limits
2004/37/EC / TWA	: Long term exposure limit
2006/15/EC / TWA	: Limit Value - eight hours
2006/15/EC / STEL	: Short term exposure limit
ZA OEL / TWA OEL-CL	: Long term occupational exposure limits - control limit
ZA OEL / STEL OEL-CL	: Short term occupational exposure limits - control limit
ZA OEL / TWA OEL-RL	: Long term occupational exposure limits - recommended limit

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

# SAFETY DATA SHEET



## MasterMix Universal Putty

Version  
1.2

Revision Date:  
09.02.2024

SDS Number:  
MAT0PL400902  
ZA/EN

Date of last issue: 31.01.2024  
Date of first issue: 30.01.2024

---

### Further information

#### Classification of the mixture:

Flam. Liq. 3	H226
Skin Irrit. 2	H315
Eye Irrit. 2	H319
Skin Sens. 1	H317
Repr. 2	H361d
STOT RE 1	H372

#### Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.