according to Regulation (EC) No. 1907/2006



# **TESSAROL** metal Express RAL----

Version Revision Date: SDS Number: Date of last issue: -

1.0 20.10.2023 MAT0GA00\_107 Date of first issue: 20.10.2023

IE/EN

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : TESSAROL metal Express RAL----

Product code : Please see section 16 for detailed data

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : SU19Building and construction work

stance/Mixture PROC10, PROC11 Roller application or brushing, Non indus-

trial spraying

PC9a Coatings and paints, thinners, paint removers

Recommended restrictions

on use

Professional and consumer use of coatings

1.3 Details of the supplier of the safety data sheet

Company : Helios TBLUS d.o.o.

Količevo 65 1230 Domžale Slovenia

Telephone Company : 386 (1) 722 4383

Telefax Company : 386 (1) 722 4310

Responsible/issuing person : 386 (1) 722 4383

productsafety@helios.si

1.4 Emergency telephone number

01 809 2166 National Poisons Information Centre 01 809 2166

01 809 2566 Healtcare Professionals 01 809 2566

01 809 2566 Healtcare Professionals 01 809 2566

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

## Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 H226: Flammable liquid and vapour.

Skin irritation, Category 2 H315: Causes skin irritation.

Eye irritation, Category 2 H319: Causes serious eye irritation. Specific target organ toxicity - single ex- H335: May cause respiratory irritation.

posure, Category 3, Respiratory system

according to Regulation (EC) No. 1907/2006



# TESSAROL metal Express RAL----

Version Revision Date: SDS Number: Date of last issue: -

1.0 20.10.2023 MAT0GA00\_107 Date of first issue: 20.10.2023

IE/EN

Specific target organ toxicity - single exposure, Category 3, Central nervous

system

Specific target organ toxicity - repeated

exposure, Category 1

Long-term (chronic) aquatic hazard, Cat-

egory 3

H336: May cause drowsiness or dizziness.

H372: Causes damage to organs through pro-

longed or repeated exposure.

H412: Harmful to aquatic life with long lasting ef-

fects.

#### 2.2 Label elements

## Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms







Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.

H372 Causes damage to organs through prolonged or re-

peated exposure.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : P101

P101 If medical advice is needed, have product container or

label at hand.

P102 Keep out of reach of children.

#### Prevention:

P210 Keep away from heat, hot surfaces, sparks, open

flames and other ignition sources. No smoking.

P260 Do not breathe mist or vapours.

P271 Use only outdoors or in a well-ventilated area.

#### Response:

P370 + P378 In case of fire: Use dry sand, dry chemical or

alcohol-resistant foam to extinguish.

## Storage:

P405 Store locked up.

#### Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

#### Hazardous components which must be listed on the label:

hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclic, aromatic content (2-25%) reaction mixture of ethylbenzene, m-xylene and p-xylene n-butyl acetate

#### **Additional Labelling**

according to Regulation (EC) No. 1907/2006



# **TESSAROL** metal Express RAL----

Version Revision Date: SDS Number: Date of last issue: -

1.0 20.10.2023 MAT0GA00\_107 Date of first issue: 20.10.2023

IE/EN

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not

breathe spray or mist.

EUH208 Contains maleic anhydride, derivative of propanoic acid (ECHA 948-776-8).

May produce an allergic reaction.

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclic, aromatic content (2-25%)	919-446-0 649-330-00-2 01-2119458049-33	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) STOT RE 1; H372 Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>= 20 - < 25
reaction mixture of ethylbenzene, m-xylene and p-xylene	- 905-562-9 01-2119555267-33	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 Asp. Tox. 1; H304	>= 20 - < 30
n-butyl acetate	123-86-4 204-658-1 607-025-00-1 01-2119485493-29	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) EUH066	>= 1 - < 10

according to Regulation (EC) No. 1907/2006



# **TESSAROL** metal Express RAL----

Version Revision Date: SDS Number: Date of last issue: -

1.0 20.10.2023 MAT0GA00\_107 Date of first issue: 20.10.2023

IE/EN

2-Propenoic acid, 2-methyl-, 2- (dimethylamino)ethyl ester, poly- mer with butyl 2-propenoate, compds. with polyethylene glycol hydrogen maleate C9-11-alkyl ethers	948-776-8	Skin Sens. 1; H317	>= 0.1 - < 1
strontium bis(2-ethylhexanoate)	2457-02-5 219-536-3	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 Repr. 1B; H360D	>= 0.1 - < 0.3
maleic anhydride	108-31-6 203-571-6 607-096-00-9 01-2119472428-31	Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 Resp. Sens. 1; H334 STOT RE 1; H372 (Respiratory system) EUH071	< 0.001

#### **SECTION 4: First aid measures**

## 4.1 Description of first aid measures

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : Consult a physician after significant exposure.

If unconscious, place in recovery position and seek medical

advice.

In case of skin contact : If skin irritation persists, call a physician.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

according to Regulation (EC) No. 1907/2006



# TESSAROL metal Express RAL----

Version Revision Date: SDS Number: Date of last issue: -

1.0 20.10.2023 MAT0GA00\_107 Date of first issue: 20.10.2023

IE/EN

Take victim immediately to hospital.

#### 4.2 Most important symptoms and effects, both acute and delayed

Risks Causes skin irritation.

> Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness.

Causes damage to organs through prolonged or repeated

exposure.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

## **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

High volume water jet

#### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

ucts

Hazardous combustion prod- : No hazardous combustion products are known

#### 5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

For safety reasons in case of fire, cans should be stored sepa-

rately in closed containments.

Use a water spray to cool fully closed containers.

## **SECTION 6: Accidental release measures**

# 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment.

Remove all sources of ignition.

according to Regulation (EC) No. 1907/2006



# **TESSAROL** metal Express RAL----

Version Revision Date: SDS Number: Date of last issue: -

1.0 20.10.2023 MAT0GA00\_107 Date of first issue: 20.10.2023

IE/EN

Evacuate personnel to safe areas.

Beware of vapours accumulating to form explosive concentra-

tions. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible ab-

sorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local

/ national regulations (see section 13).

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

**SECTION 7: Handling and storage** 

7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol.

Do not breathe vapours/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Take precautionary measures against static discharges.

Provide sufficient air exchange and/or exhaust in work rooms.

Open drum carefully as content may be under pressure.

Dispose of rinse water in accordance with local and national

regulations.

Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Advice on protection against

fire and explosion

Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge

(which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

No smoking. Keep container tightly closed in a dry and wellventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe

according to Regulation (EC) No. 1907/2006



# **TESSAROL** metal Express RAL----

Version Revision Date: SDS Number: Date of last issue: -

1.0 20.10.2023 MAT0GA00\_107 Date of first issue: 20.10.2023

IE/EN

label precautions. Electrical installations / working materials

must comply with the technological safety standards.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : For further information, refer to the product technical data

sheet.

Consult the technical guidelines for the use of this sub-

stance/mixture.

# **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

#### **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
reaction mixture of ethylbenzene, m- xylene and p- xylene	1330-20-7	OELV - 8 hrs (TWA)	50 ppm 221 mg/m3	IE OEL
			which have the capacity to point it, and be absorbed into t	
		OELV - 15 min (STEL)	100 ppm 442 mg/m3	IE OEL
			which have the capacity to po ith it, and be absorbed into t	
		TWA	50 ppm 221 mg/m3	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	100 ppm 442 mg/m3	2000/39/EC
	Further inform skin, Indicativ		possibility of significant upta	ke through the
titanium dioxide	13463-67-7	OELV - 8 hrs (TWA) (Respira- ble dust)	4 mg/m3	IE OEL
		OELV - 8 hrs (TWA) (inhalable dust)	10 mg/m3	IE OEL
n-butyl acetate	123-86-4	OELV - 8 hrs (TWA)	50 ppm 241 mg/m3	IE OEL
		OELV - 15 min (STEL)	150 ppm 723 mg/m3	IE OEL
		STEL	150 ppm 723 mg/m3	2019/1831/E U
	Further inform	nation: Indicative		

according to Regulation (EC) No. 1907/2006



# **TESSAROL** metal Express RAL----

Version Revision Date: SDS Number: Date of last issue: -

IE/EN

1.0 20.10.2023 MAT0GA00\_107 Date of first issue: 20.10.2023

		TWA	50 ppm 241 mg/m3	2019/1831/E U
	Further information: Indicative			
maleic anhydride	108-31-6	OELV - 8 hrs (TWA) (Inhalable fraction and va- pour)	0.01 ppm	IE OEL
	Further information: Chemical agents which following exposure may cause sensitisation of the respiratory tract and lead to asthma, rhinitis or extrinsic allergic alveolitis			

# Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
hydrocarbons, C9- C12, n-alkanes, isoal- kanes, cyclic, aro- matic content (2-25%)	Workers	Inhalation	Long-term systemic effects	330 mg/m3
	Consumers	Inhalation	Long-term systemic effects	71 mg/m3
	Workers	Dermal	Long-term systemic effects	44 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	26 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	26 mg/kg bw/day
reaction mixture of ethylbenzene, m-xylene and p-xylene	Workers	Inhalation	Long-term systemic effects	77 mg/m3
	Consumers	Inhalation	Long-term local ef- fects	65.3 mg/m3
	Workers	Inhalation	Acute systemic effects	442 mg/m3
	Workers	Inhalation	Acute local effects	289 mg/m3
	Consumers	Inhalation	Acute systemic effects	260 mg/m3
	Workers	Inhalation	Long-term local ef- fects	221 mg/m3
	Consumers	Inhalation	Long-term systemic effects	14.8 mg/m3
	Consumers	Inhalation	Acute local effects	260 mg/m3
	Consumers	Dermal	Long-term systemic effects	108 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	16 mg/kg bw/day
_	Workers	Dermal	Long-term systemic effects	180 mg/kg bw/day
titanium dioxide	Workers	Inhalation	Long-term local ef- fects	10 mg/m3
	Consumers	Oral	Long-term systemic effects	700 mg/kg bw/day
n-butyl acetate	Workers	Inhalation	Acute systemic ef-	600 mg/m3

according to Regulation (EC) No. 1907/2006



# **TESSAROL** metal Express RAL----

Version Revision Date: SDS Number: Date of last issue: -

IE/EN

1.0 20.10.2023 MAT0GA00\_107 Date of first issue: 20.10.2023

1			fects	
	Workers	Inhalation	Acute local effects	600 mg/m3
	Workers	Inhalation	Long-term systemic effects	48 mg/m3
	Workers	Inhalation	Long-term local effects	300 mg/m3
	Consumers	Inhalation	Acute systemic effects	300 mg/m3
	Consumers	Inhalation	Acute local effects	300 mg/m3
	Consumers	Inhalation	Long-term systemic effects	12 mg/m3
	Consumers	Inhalation	Long-term local effects	35.7 mg/m3
	Consumers	Dermal	Long-term systemic effects	3.4 mg/kg bw/day
	Consumers	Dermal	Acute systemic effects	6 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	2 mg/kg bw/day
	Consumers	Oral	Acute systemic effects	2 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	7 mg/kg bw/day
	Workers	Dermal	Acute systemic effects	11 mg/kg bw/day
strontium bis(2- ethylhexanoate)	Workers	Inhalation	Long-term systemic effects	0.730 mg/m3
	Workers	Dermal	Long-term systemic effects	0.410 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	0.180 mg/m3
	Consumers	Dermal	Long-term systemic effects	0.210 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	0.210 mg/kg bw/day

# Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
reaction mixture of ethylbenzene, m-xylene and p-xylene	Soil	2.31 mg/kg dry weight (d.w.)
	Marine water	0.327 mg/l
	Fresh water	0.327 mg/l
	Marine sediment	12.46 mg/kg dry weight (d.w.)
	Fresh water sediment	12.46 mg/kg dry weight (d.w.)
	Sewage treatment plant	6.58 mg/l
	Intermittent use/release	0.327 mg/l
titanium dioxide	Soil	100 mg/kg dry weight (d.w.)
	Marine water	0.0184 mg/l
	Fresh water	0.184 mg/l

according to Regulation (EC) No. 1907/2006



# **TESSAROL** metal Express RAL----

Version Revision Date: SDS Number: Date of last issue: -

1.0 20.10.2023 MAT0GA00\_107 Date of first issue: 20.10.2023

IE/EN

1	i.	1
	Marine sediment	100 mg/kg dry
		weight (d.w.)
	Fresh water sediment	1000 mg/kg dry
		weight (d.w.)
	Sewage treatment plant	100 mg/l
	Intermittent use/release	0.193 mg/l
n-butyl acetate	Soil	0.0903 mg/kg dry
		weight (d.w.)
	Marine water	0.018 mg/l
	Fresh water	0.18 mg/l
	Marine sediment	0.0981 mg/kg dry
		weight (d.w.)
	Fresh water sediment	0.981 mg/kg dry
		weight (d.w.)
	Sewage treatment plant	35.6 mg/l
	Intermittent use/release	0.36 mg/l
strontium bis(2-ethylhexanoate)	Fresh water	0.360 - 0.440
,		mg/l
	Intermittent use/release	0.493 - 0.610
		mg/l
	Marine water	0.036 - 0.040
		mg/l
	Sewage treatment plant	71.7 - 88.52 mg/l
	Fresh water sediment	6.37 - 7.86 mg/kg
		dry weight (d.w.)
	Marine sediment	0.637 - 0.790
		mg/kg dry weight
		(d.w.)
	Soil	1.06 - 1.31 mg/kg
		dry weight (d.w.)

#### 8.2 Exposure controls

Personal protective equipment

Eye/face protection : Equipment should conform to EN 166

Eye wash bottle with pure water Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Hand protection

Gloves : | Viton® (> 0,6 mm; < 240 min); DIN EN374 |

PE laminate (> 0,1 mm; < 240 min); DIN EN374

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of

cuts, abrasion, and the contact time.

Skin and body protection : Impervious clothing

according to Regulation (EC) No. 1907/2006



# TESSAROL metal Express RAL----

Version Revision Date: SDS Number: Date of last issue: -

1.0 20.10.2023 MAT0GA00\_107 Date of first issue: 20.10.2023

IE/EN

Choose body protection according to the amount and con-

centration of the dangerous substance at the work place.

Respiratory protection : Use respiratory protection unless adequate local exhaust ven-

tilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Equipment should conform to EN 14387

Filter type : Combined particulates and organic vapour type (A-P)

Protective measures : Wash thoroughly after handling.

Avoid contact with skin, eyes and clothing.

Keep away from food, drink and animal feedingstuffs.

#### **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Physical state : liquid

Colour : in accordance with the product description

Odour : solvent-like
Odour Threshold : No data available

Melting point/freezing point : -47.9 - 13.3 °C (calculation method (principal components,

lowest value))

Boiling point/boiling range : 138 - 141.4 °C (calculation method (principal components,

lowest value))

Flammability : Static-accumulating flammable liquid., Combustible Solids

Upper explosion limit / Upper

flammability limit

6.6 %(V) (calculation method (principal components, highest

value))

Lower explosion limit / Lower

flammability limit

1.1 %(V) (calculation method (principal components, highest

value))

Flash point : 25 °C (calculation method (principal components, lowest val-

ue))

Ignition temperature : 465 - 525 °C (calculation method (principal components, high-

est value))

Decomposition temperature : No decomposition if stored and applied as directed.

Hazardous decomposition products formed under fire condi-

tions.

pH : No data available

Viscosity

according to Regulation (EC) No. 1907/2006



# TESSAROL metal Express RAL----

Version Revision Date: SDS Number: Date of last issue: -

1.0 20.10.2023 MAT0GA00\_107 Date of first issue: 20.10.2023

IE/EN

Viscosity, kinematic : > 20.5 mm2/s (40 °C)

Flow time : 110 - 150 s

Method: DIN 53211 (CF4)

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : Description: miscible with most organic solvents

Partition coefficient: n-

octanol/water

log Pow: 2.77 - 3.15 (calculation method (principal compo-

nents, highest value))

Vapour pressure : 8.21 hPa (calculation method (principal components, highest

value)) (20 °C)

Relative density : No data available

Density : 0.95 - 1.2 g/cm3

Relative vapour density : No data available

9.2 Other information

Explosives : Not applicable

Oxidizing properties : Sustains combustion

VOC : (Directive 2004/42/EC)

500 g/l

## **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

No decomposition if stored and applied as directed.

## 10.2 Chemical stability

No decomposition if stored and applied as directed.

# 10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Incompatible with strong acids and bases.

according to Regulation (EC) No. 1907/2006



# TESSAROL metal Express RAL----

Version Revision Date: SDS Number: Date of last issue: -

1.0 20.10.2023 MAT0GA00\_107 Date of first issue: 20.10.2023

IE/EN

## 10.6 Hazardous decomposition products

Adequate ventilation is required.

Heating can release vapours which can be ignited.

Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

## **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### **Acute toxicity**

Not classified based on available information.

**Product:** 

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l

Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg

Method: Calculation method

#### **Components:**

## reaction mixture of ethylbenzene, m-xylene and p-xylene:

Acute oral toxicity : LD50 Oral (Rat): >= 8,700 mg/kg

Acute inhalation toxicity : LC50 (Rat): 27.14 mg/l

Test atmosphere: vapour

Acute dermal toxicity : Assessment: The component/mixture is moderately toxic after

single contact withskin.

n-butyl acetate:

Acute oral toxicity : LD50 Oral (Rat): >= 10,760 mg/kg

Acute dermal toxicity : LD50 (Rabbit): >= 5,000 mg/kg

## strontium bis(2-ethylhexanoate):

Acute oral toxicity : Assessment: The component/mixture is moderately toxic after

single ingestion.

maleic anhydride:

Acute oral toxicity : Assessment: The component/mixture is moderately toxic after

single ingestion.

#### Skin corrosion/irritation

Causes skin irritation.

according to Regulation (EC) No. 1907/2006



# **TESSAROL** metal Express RAL----

Version Revision Date: SDS Number: Date of last issue: -

1.0 20.10.2023 MAT0GA00\_107 Date of first issue: 20.10.2023

IE/EN

**Product:** 

Remarks : May cause skin irritation and/or dermatitis.

**Components:** 

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Result : irritating

strontium bis(2-ethylhexanoate):

Result : irritating

maleic anhydride:

Result : Corrosive after 3 minutes to 1 hour of exposure

Serious eye damage/eye irritation

Causes serious eye irritation.

**Product:** 

Remarks : May cause irreversible eye damage.

**Components:** 

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Result : Eye irritation

strontium bis(2-ethylhexanoate):

Result : Corrosive

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Product:

Remarks : Causes sensitisation.

**Components:** 

derivative of propanoic acid (ECHA 948-776-8):

Result : Probability or evidence of skin sensitisation in humans

maleic anhydride:

Result : Probability of respiratory sensitisation in humans based on

animaltesting

according to Regulation (EC) No. 1907/2006



# **TESSAROL** metal Express RAL----

Version Revision Date: SDS Number: Date of last issue: -

1.0 20.10.2023 MAT0GA00\_107 Date of first issue: 20.10.2023

IE/EN

Result : Probability or evidence of skin sensitisation in humans

## Germ cell mutagenicity

Not classified based on available information.

#### Carcinogenicity

Not classified based on available information.

## Reproductive toxicity

Not classified based on available information.

#### STOT - single exposure

May cause respiratory irritation.

May cause drowsiness or dizziness.

#### **Components:**

#### hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclic, aromatic content (2-25%):

Assessment : May cause drowsiness or dizziness.

#### reaction mixture of ethylbenzene, m-xylene and p-xylene:

Assessment : May cause respiratory irritation.

n-butyl acetate:

Assessment : May cause drowsiness or dizziness.

#### STOT - repeated exposure

Causes damage to organs through prolonged or repeated exposure.

## **Components:**

#### hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclic, aromatic content (2-25%):

Assessment : Causes damage to organs through prolonged or repeated

exposure.

# reaction mixture of ethylbenzene, m-xylene and p-xylene:

Assessment : May cause damage to organs through prolonged or repeated

exposure.

maleic anhydride:

Assessment : May cause damage to organs through prolonged or repeated

exposure.

#### **Aspiration toxicity**

Not classified based on available information.

according to Regulation (EC) No. 1907/2006



# TESSAROL metal Express RAL----

Version Revision Date: SDS Number: Date of last issue: -

1.0 20.10.2023 MAT0GA00\_107 Date of first issue: 20.10.2023

IE/EN

#### Components:

hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclic, aromatic content (2-25%):

May be fatal if swallowed and enters airways.

reaction mixture of ethylbenzene, m-xylene and p-xylene:

May be fatal if swallowed and enters airways.

#### 11.2 Information on other hazards

#### **Endocrine disrupting properties**

**Product:** 

Assessment : The substance/mixture does not contain components consid-

> ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

**Further information** 

**Product:** 

Remarks Symptoms of overexposure may be headache, dizziness,

tiredness, nausea and vomiting.

Concentrations substantially above the TLV value may cause

narcotic effects.

Solvents may degrease the skin.

## **SECTION 12: Ecological information**

#### 12.1 Toxicity

## Components:

hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclic, aromatic content (2-25%):

**Ecotoxicology Assessment** 

Chronic aquatic toxicity Toxic to aquatic life with long lasting effects.

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Toxicity to fish : LC50 (Fish): >= 1 - 10 mg/l

aquatic invertebrates

Toxicity to daphnia and other : LC50 (Daphnia (water flea)): >= 1 - 10 mg/l

Toxicity to microorganisms : EC50 (Bacteria): >= 1 - 100 mg/l

n-butyl acetate:

Toxicity to algae/aquatic

plants

NOEC (Desmodesmus subspicatus (green algae)): > 200 mg/l

16 / 24

according to Regulation (EC) No. 1907/2006



# TESSAROL metal Express RAL----

Version Revision Date: SDS Number: Date of last issue: -

1.0 20.10.2023 MAT0GA00\_107 Date of first issue: 20.10.2023

IE/EN

EC50 (Desmodesmus subspicatus (green algae)): >= 647.7

mg/l

Exposure time: 72 h

Toxicity to microorganisms : IC50 (Tetrahymena pyriformis): 356 mg/l

Exposure time: 40 h

maleic anhydride:

Toxicity to fish : LC50 : 75 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

NOEC: 10 mg/l Exposure time: 21 d

ic toxicity)

Species: Daphnia magna (Water flea)

## 12.2 Persistence and degradability

#### **Components:**

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Biodegradability : Readily biodegradable.

Photodegradation : Decomposes rapidly in contact with light.

n-butyl acetate:

Biodegradability : Result: Biodegradable

Biodegradation: 83 % Exposure time: 28 d

Method: OECD Test Guideline 301D

Stability in water : Degradation half life: 78 d

pH: 8

Hydrolyses slowly.

Photodegradation : Decomposes rapidly in contact with light.

maleic anhydride:

Biodegradability : Result: Biodegradable

Biodegradation: 90 % Exposure time: 25 d

Method: OECD Test Guideline 301B

Stability in water : Hydrolyses readily.

Photodegradation :

## 12.3 Bioaccumulative potential

#### **Components:**

reaction mixture of ethylbenzene, m-xylene and p-xylene:

according to Regulation (EC) No. 1907/2006



# TESSAROL metal Express RAL----

Version Revision Date: SDS Number: Date of last issue: -

1.0 20.10.2023 MAT0GA00\_107 Date of first issue: 20.10.2023

IE/EN

Bioaccumulation : Bioconcentration factor (BCF): 25.9

Bioaccumulation is unlikely.

Partition coefficient: n-

octanol/water

log Pow: 2.77 - 3.15

n-butyl acetate:

Bioaccumulation : Bioconcentration factor (BCF): 15

Bioaccumulation is unlikely.

Partition coefficient: n-

octanol/water

log Pow: 1.81

maleic anhydride:

Bioaccumulation : Bioaccumulation is unlikely.

Partition coefficient: n-

octanol/water

log Pow: -2.61 (20 °C)

#### 12.4 Mobility in soil

#### **Components:**

## reaction mixture of ethylbenzene, m-xylene and p-xylene:

Distribution among environ-

mental compartments

Koc: 537, log Koc: 2.73 Moderately mobile in soils

The product evaporates from soil.

Stability in soil : Dissipation time: 23 d

Percentage dissipation: 50 % (DT50)

maleic anhydride:

Mobility : Medium: Water

Content: 100 %

Medium: Soil Content: 0 %

Distribution among environ-

mental compartments

: Koc: 42, log Koc: 1.63

#### 12.5 Results of PBT and vPvB assessment

#### **Product:**

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

#### 12.6 Endocrine disrupting properties

**Product:** 

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to

according to Regulation (EC) No. 1907/2006



# TESSAROL metal Express RAL----

Version Revision Date: SDS Number: Date of last issue: -

1.0 20.10.2023 MAT0GA00\_107 Date of first issue: 20.10.2023

IE/EN

REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

#### 12.7 Other adverse effects

**Product:** 

Additional ecological infor: : An

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Harmful to aquatic life with long lasting effects.

## **SECTION 13: Disposal considerations**

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

Waste Code : 08 00 00, WASTES FROM THE MANUFACTURE,

FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS

(PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS

08 01 00, wastes from MFSU and removal of paint and var-

nish

08 01 11, waste paint and varnish containing organic solvents

or other hazardoussubstances

15 00 00, WASTE PACKAGING; ABSORBENTS, WIPING

CLOTHS, FILTER MATERIALS AND PROTECTIVE

**CLOTHING NOT OTHERWISE SPECIFIED** 

15 01 00, packaging (including separately collected municipal

packaging waste)

15 01 10, packaging containing residues of or contaminated

by hazardoussubstances

HP3, Flammable

HP4, Irritant - skin irritation and eye damage

HP5, Specific Target Organ Toxicity (STOT)/Aspiration Toxici-

ty

HP13, Sensitising HP14, Ecotoxic

according to Regulation (EC) No. 1907/2006



# **TESSAROL** metal Express RAL----

Version Revision Date: SDS Number: Date of last issue: -

1.0 20.10.2023 MAT0GA00\_107 Date of first issue: 20.10.2023

IE/EN

## **SECTION 14: Transport information**

#### 14.1 UN number or ID number

ADN : UN 1263
ADR : UN 1263
RID : UN 1263
IMDG : UN 1263
IATA : UN 1263

#### 14.2 UN proper shipping name

ADN : PAINT
ADR : PAINT
RID : PAINT
IMDG : PAINT
IATA : Paint

## 14.3 Transport hazard class(es)

Class Subsidiary risks

ADN : 3
ADR : 3
RID : 3
IMDG : 3
IATA : 3

#### 14.4 Packing group

#### ADN

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

# ADR

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3
Tunnel restriction code : (D/E)

#### **RID**

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

## **IMDG**

according to Regulation (EC) No. 1907/2006



# TESSAROL metal Express RAL----

Version Revision Date: SDS Number: Date of last issue: -

1.0 20.10.2023 MAT0GA00\_107 Date of first issue: 20.10.2023

IE/EN

Packing group : III Labels : 3

EmS Code : F-E, <u>S-E</u>

IATA (Cargo)

Packing instruction (cargo : 366

aircraft)

Packing instruction (LQ) : Y344
Packing group : III

Labels : Flammable Liquids

IATA (Passenger)

Packing instruction (passen: 355

ger aircraft)

Packing instruction (LQ) : Y344
Packing group : III

Labels : Flammable Liquids

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

**IMDG** 

Marine pollutant : no

#### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

## **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) Conditions of restriction for the following entries should be considered: Number on list 75, 3

If you intend to use this product as tattoo ink, please contact your vendor.

dibutyltin oxide (Number on list 75, 20)

according to Regulation (EC) No. 1907/2006



# TESSAROL metal Express RAL----

Version Revision Date: SDS Number: Date of last issue: -

1.0 20.10.2023 MAT0GA00\_107 Date of first issue: 20.10.2023

IE/EN

REACH - Candidate List of Substances of Very High : Not applicable

Concern for Authorisation (Article 59).

Regulation (EC) No 1005/2009 on substances that de- : Not applicable

plete the ozone layer

Regulation (EU) 2019/1021 on persistent organic pollu- : Not applicable

tants (recast)

Regulation (EC) No 649/2012 of the European Parlia: Not applicable

ment and the Council concerning the export and import

of dangerous chemicals

REACH - List of substances subject to authorisation : Not applicable

(Annex XIV)

Seveso III: Directive 2012/18/EU of the Euro- P5c FLAMMABLE LIQUIDS

pean Parliament and of the Council on the control of major-accident hazards involving

dangerous substances.

Volatile organic compounds : Directive 2004/42/EC

Volatile organic compounds (VOC) content: 500 g/l

## Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

#### 15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

## **SECTION 16: Other information**

#### **Full text of H-Statements**

H226 : Flammable liquid and vapour.

H302 : Harmful if swallowed.

H304 : May be fatal if swallowed and enters airways.

H312 : Harmful in contact with skin.

H314 : Causes severe skin burns and eye damage.

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.

H332 : Harmful if inhaled.

H334 : May cause allergy or asthma symptoms or breathing difficul-

ties if inhaled.

H335 : May cause respiratory irritation.
H336 : May cause drowsiness or dizziness.
H360D : May damage the unborn child.

H372 : Causes damage to organs through prolonged or repeated

exposure.

H372 : Causes damage to organs through prolonged or repeated

according to Regulation (EC) No. 1907/2006



# TESSAROL metal Express RAL----

Version Revision Date: SDS Number: Date of last issue: -

1.0 20.10.2023 MAT0GA00\_107 Date of first issue: 20.10.2023

IE/EN

exposure if inhaled.

H373 : May cause damage to organs through prolonged or repeated

exposure.

H411 : Toxic to aquatic life with long lasting effects.

EUH066 : Repeated exposure may cause skin dryness or cracking.

EUH071 : Corrosive to the respiratory tract.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Chronic : Long-term (chronic) aquatic hazard

Asp. Tox. : Aspiration hazard Eye Dam. : Serious eye damage

Eye Irrit. : Eye irritation
Flam. Liq. : Flammable liquids
Repr. : Reproductive toxicity
Resp. Sens. : Respiratory sensitisation

Skin Corr. : Skin corrosion
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation

STOT RE : Specific target organ toxicity - repeated exposure STOT SE : Specific target organ toxicity - single exposure

2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first

list of indicative occupational exposure limit values

2019/1831/EU : Europe. Commission Directive 2019/1831/EU establishing a

fifth list of indicative occupational exposure limit values

IE OEL : Ireland. List of Chemical Agents and Occupational Exposure

Limit Values - Schedule 1 Limit Value - eight hours

2000/39/EC / TWA: Limit Value - eight hours2000/39/EC / STEL: Short term exposure limit2019/1831/EU / TWA: Limit Value - eight hours2019/1831/EU / STEL: Short term exposure limit

IE OEL / OELV - 8 hrs (TWA) : Occupational exposure limit value (8-hour reference period)
IE OEL / OELV - 15 min : Occupational exposure limit value (15-minute reference peri-

(STEL) od

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA -European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - Interna-

according to Regulation (EC) No. 1907/2006



# **TESSAROL** metal Express RAL----

Version Revision Date: SDS Number: Date of last issue: -

1.0 20.10.2023 MAT0GA00\_107 Date of first issue: 20.10.2023

IE/EN

tional Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

#### **Further information**

# Classification of the mixture: Classification procedure:

Flam. Liq. 3	H226	Based on product data or assessment
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
STOT SE 3	H335	Calculation method
STOT SE 3	H336	Calculation method
STOT RE 1	H372	Calculation method
Aquatic Chronic 3	H412	Calculation method

Material codes (bulk) for 401652, 401653, 401654, 401655, 401656, 401657, 401658, which the SDS is valid 401659, 401660, 401661, 401750, 480868, 480869

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.