

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



IDEAL hardener for 2K polyurethane parquet lacquer DS semi-matt (B)

Version	Revision Date:	SDS Number:	Date of last issue: 21.09.2022
1.2	22.09.2022	MAT000473539	Date of first issue: 08.03.2021
		GB / EN	

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name	:	IDEAL hardener for 2K polyurethane parquet lacquer DS semi-matt (B)
Product code	:	47353905
Unique Formula Identifier (UFI)	:	ACSK-R09E-K008-QAHU

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture	:	Building and construction work Roller application or brushing, Non industrial spraying Coatings and paints, thinners, paint removers
Recommended restrictions on use	:	Professional and consumer use of coatings

1.3 Details of the supplier of the safety data sheet

Company	:	KANSAI HELIOS Slovenija d.o.o. Količevo 65 1230 Domžale Slovenia
Telephone Company	:	386 (1) 722 4383
Telefax Company	:	386 (1) 722 4310
Responsible/issuing person	:	386 (1) 722 4383 productsafety@kansai-helios.si

1.4 Emergency telephone number

Call 999 (or 112) for emergency medical attention
professionals only: National Poison Information Service (NPIS) 24h national number 0844 892 0111
consumer: National Health Service (NHS) 24h national number, England & Scotland 111

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



IDEAL hardener for 2K polyurethane parquet lacquer DS semi-matt (B)

Version	Revision Date:	SDS Number:	Date of last issue: 21.09.2022
1.2	22.09.2022	MAT000473539	Date of first issue: 08.03.2021
		GB / EN	

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Flammable liquids, Category 2	H225: Highly flammable liquid and vapour.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Hazard pictograms :



Signal word : Danger

Hazard statements :
H225 Highly flammable liquid and vapour.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Supplemental Hazard Statements : EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements :
P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



IDEAL hardener for 2K polyurethane parquet lacquer DS semi-matt (B)

Version
1.2

Revision Date:
22.09.2022

SDS Number:
MAT000473539
GB / EN

Date of last issue: 21.09.2022
Date of first issue: 08.03.2021

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label:

n-butyl acetate

Toluene diisocyanate, oligomeric reaction products with 2,2'-oxydiethanol and propy-
lidenetrimethanol

Benzene, 1,3-diisocyanatomethyl-, homopolymer

m-tolylidene diisocyanate

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumula-
tive and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or
higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
n-butyl acetate	123-86-4 204-658-1 607-025-00-1 01-2119485493-29	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) EUH066	>= 30 - < 50
aromatic polyisocyanate	53317-61-6 500-120-8	Eye Irrit. 2; H319 Skin Sens. 1; H317	>= 20 - < 30
aromatic polyisocyanate	9017-01-0	Eye Irrit. 2; H319 Skin Sens. 1; H317	>= 10 - < 20
ethylacetate	141-78-6 205-500-4 607-022-00-5 01-2119475103-46	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system) EUH066	>= 1 - < 10

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



IDEAL hardener for 2K polyurethane parquet lacquer DS semi-matt (B)

Version	Revision Date:	SDS Number:	Date of last issue: 21.09.2022
1.2	22.09.2022	MAT000473539	Date of first issue: 08.03.2021
GB / EN			

m-tolylidene diisocyanate	26471-62-5 247-722-4 615-006-00-4 01-2119454791-34	Acute Tox. 2; H330 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 (Respiratory sys- tem) Aquatic Chronic 3; H412 specific concentra- tion limit Resp. Sens. 1; H334 >= 0,1 %	>= 0,025 - < 0,1
---------------------------	---	---	---------------------

SECTION 4: First aid measures

4.1 Description of first aid measures

- | | |
|-------------------------|---|
| General advice | : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended. |
| If inhaled | : Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice. |
| In case of skin contact | : If on skin, rinse well with water.
If on clothes, remove clothes. |
| In case of eye contact | : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist. |
| If swallowed | : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician. |

4.2 Most important symptoms and effects, both acute and delayed

- | | |
|-------|--|
| Risks | : May cause an allergic skin reaction.
Causes serious eye irritation. |
|-------|--|

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



IDEAL hardener for 2K polyurethane parquet lacquer DS semi-matt (B)

Version	Revision Date:	SDS Number:	Date of last issue: 21.09.2022
1.2	22.09.2022	MAT000473539	Date of first issue: 08.03.2021
		GB / EN	

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause drowsiness or dizziness.

Repeated exposure may cause skin dryness or cracking.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : No hazardous combustion products are known.

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentra-

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



IDEAL hardener for 2K polyurethane parquet lacquer DS semi-matt (B)

Version	Revision Date:	SDS Number:	Date of last issue: 21.09.2022
1.2	22.09.2022	MAT000473539	Date of first issue: 08.03.2021
		GB / EN	

tions. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform
respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible ab-
sorbent material, (e.g. sand, earth, diatomaceous earth, ver-
miculite) and place in container for disposal according to local
/ national regulations (see section 13).

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the ap-
plication area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national
regulations.
Persons susceptible to skin sensitisation problems or asthma,
allergies, chronic or recurrent respiratory disease should not
be employed in any process in which this mixture is being
used.

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.
Take necessary action to avoid static electricity discharge
(which might cause ignition of organic vapours). Use only
explosion-proof equipment. Keep away from open flames, hot
surfaces and sources of ignition.

Hygiene measures : When using do not eat or drink. When using do not smoke.
Wash hands before breaks and at the end of workday.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



IDEAL hardener for 2K polyurethane parquet lacquer DS semi-matt (B)

Version	Revision Date:	SDS Number:	Date of last issue: 21.09.2022
1.2	22.09.2022	MAT000473539	Date of first issue: 08.03.2021
		GB / EN	

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : For further information, refer to the product technical data sheet.

Consult the technical guidelines for the use of this substance/mixture.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Derived No Effect Level (DNEL):

Substance name	End Use	Exposure routes	Potential health effects	Value
n-butyl acetate	Workers	Inhalation	Acute systemic effects	600 mg/m3
	Workers	Inhalation	Acute local effects	600 mg/m3
	Workers	Inhalation	Long-term systemic effects	48 mg/m3
	Workers	Inhalation	Long-term local effects	300 mg/m3
	Consumers	Inhalation	Acute systemic effects	300 mg/m3
	Consumers	Inhalation	Acute local effects	300 mg/m3
	Consumers	Inhalation	Long-term systemic effects	12 mg/m3
	Consumers	Inhalation	Long-term local effects	35,7 mg/m3
	Consumers	Dermal	Long-term systemic effects	3,4 mg/kg bw/day
	Consumers	Dermal	Acute systemic effects	6 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	2 mg/kg bw/day
	Consumers	Oral	Acute systemic effects	2 mg/kg bw/day
	Workers	Dermal	Long-term systemic	7 mg/kg

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



IDEAL hardener for 2K polyurethane parquet lacquer DS semi-matt (B)

Version
1.2

Revision Date:
22.09.2022

SDS Number:
MAT000473539
GB / EN

Date of last issue: 21.09.2022

Date of first issue: 08.03.2021

			effects	bw/day
	Workers	Dermal	Acute systemic effects	11 mg/kg bw/day
ethyl acetate	Workers	Inhalation	Acute systemic effects	1468 mg/m3
	Workers	Inhalation	Long-term local effects	1468 mg/m3
	Workers	Inhalation	Long-term systemic effects	734 mg/m3
	Workers	Inhalation	Long-term local effects	734 mg/m3
	Consumers	Inhalation	Acute systemic effects	734 mg/m3
	Consumers	Inhalation	Acute local effects	734 mg/m3
	Consumers	Inhalation	Long-term systemic effects	367 mg/m3
	Consumers	Inhalation	Long-term local effects	367 mg/m3
	Workers	Dermal	Long-term systemic effects	63 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	37 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	4,5 mg/kg bw/day
m-tolylidene diisocyanate	Workers	Inhalation	Long-term systemic effects	0,035 mg/m3
	Workers	Inhalation	Acute systemic effects	0,14 mg/m3
	Workers	Inhalation	Long-term local effects	0,035 mg/m3
	Workers	Inhalation	Acute systemic effects	0,14 mg/m3

Predicted No Effect Concentration (PNEC):

Substance name	Environmental Compartment	Value
n-butyl acetate	Soil	0,0903 mg/kg dry weight (d.w.)
	Marine water	0,018 mg/l
	Fresh water	0,18 mg/l
	Marine sediment	0,0981 mg/kg dry weight (d.w.)
	Fresh water sediment	0,981 mg/kg dry weight (d.w.)
	Sewage treatment plant	35,6 mg/l
	Intermittent use/release	0,36 mg/l
ethyl acetate	Soil	0,24 mg/kg dry weight (d.w.)
	Marine water	0,026 mg/l
	Fresh water	0,26 mg/l
	Marine sediment	0,125 mg/kg dry

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



IDEAL hardener for 2K polyurethane parquet lacquer DS semi-matt (B)

Version	Revision Date:	SDS Number:	Date of last issue: 21.09.2022
1.2	22.09.2022	MAT000473539	Date of first issue: 08.03.2021
GB / EN			

		weight (d.w.)
	Fresh water sediment	1,25 mg/kg dry weight (d.w.)
	Sewage treatment plant	650 mg/l
	Intermittent use/release	1,65 mg/l
m-tolylidene diisocyanate	Soil	1 mg/kg dry weight (d.w.)
	Marine water	0,00125 mg/l
	Fresh water	0,0125 mg/l
	Sewage treatment plant	1 mg/l
	Intermittent use/release	0,125 mg/l

8.2 Exposure controls

Personal protective equipment

Eye protection : Equipment should conform to EN 166
Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Hand protection

Gloves : Nitrile rubber (> 0,1 mm; < 60 min); DIN EN374 |
butyl-rubber (> 0,6 mm; < 240 min); DIN EN374 |
Viton® (> 0,6 mm; < 240 min); DIN EN374 |
PE laminate (> 0,1 mm; < 240 min); DIN EN374 |

Remarks : Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
Equipment should conform to EN 14387

Filter type : Organic vapour type (A)

Protective measures : Wash thoroughly after handling.
Avoid contact with skin, eyes and clothing.
Keep away from food, drink and animal feedingstuffs.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



IDEAL hardener for 2K polyurethane parquet lacquer DS semi-matt (B)

Version	Revision Date:	SDS Number:	Date of last issue: 21.09.2022
1.2	22.09.2022	MAT000473539	Date of first issue: 08.03.2021
		GB / EN	

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	: liquid
Colour	: in accordance with the product description
Odour	: characteristic
Odour Threshold	: No data available
pH	: Not applicable
Melting point/freezing point	: -83,6 °C (calculation method (principal components, lowest value))
Boiling point/boiling range	: 77 °C (calculation method (principal components, lowest value))
Flash point	: -1 °C (calculation method (principal components, lowest value))
Flammability (solid, gas)	: Static-accumulating flammable liquid., Combustible Solids
Upper explosion limit / Upper flammability limit	: 11 %(V) (calculation method (principal components, highest value))
Lower explosion limit / Lower flammability limit	: 1,2 %(V) (calculation method (principal components, highest value))
Vapour pressure	: < 1.100 hPa (calculation method (principal components, highest value)) (50 °C)
Relative vapour density	: 4 (calculation method (principal components, highest value))
Relative density	: 0,93 (calculation method (principal components, highest value))
Density	: 1,015 - 1,050 g/cm ³ (23 °C)
Solubility(ies)	
Water solubility	: insoluble
Solubility in other solvents	: Description: miscible with most organic solvents

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



IDEAL hardener for 2K polyurethane parquet lacquer DS semi-matt (B)

Version	Revision Date:	SDS Number:	Date of last issue: 21.09.2022
1.2	22.09.2022	MAT000473539 GB / EN	Date of first issue: 08.03.2021

Partition coefficient: n-octanol/water	:	log Pow: 1,81 (calculation method (principal components, highest value))
Auto-ignition temperature	:	425 °C (calculation method (principal components, highest value))
Decomposition temperature	:	No decomposition if stored and applied as directed. Hazardous decomposition products formed under fire conditions.
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	> 20,5 mm ² /s (40 °C)
Flow time	:	14 - 17 s at 23 °C Method: DIN 53211 (CF4)
Explosive properties	:	Not applicable
Oxidizing properties	:	Sustains combustion

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Incompatible with strong acids and bases.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



IDEAL hardener for 2K polyurethane parquet lacquer DS semi-matt (B)

Version	Revision Date:	SDS Number:	Date of last issue: 21.09.2022
1.2	22.09.2022	MAT000473539	Date of first issue: 08.03.2021
		GB / EN	

10.6 Hazardous decomposition products

Adequate ventilation is required.
Heating can release vapours which can be ignited.
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

Components:

n-butyl acetate:

Acute oral toxicity : LD50 Oral (Rat): ≥ 10.760 mg/kg

Acute dermal toxicity : LD50 (Rabbit): ≥ 5.000 mg/kg

ethyl acetate:

Acute oral toxicity : LD50 Oral (Rat): ≥ 5.620 mg/kg

Acute inhalation toxicity : LC50 (Rat): 1600 ppm
Exposure time: 8 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): ≥ 20.000 mg/kg

m-tolylidene diisocyanate:

Acute inhalation toxicity : Test atmosphere: dust/mist
Assessment: The component/mixture is highly toxic after short
term inhalation.

Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

Product:

Remarks : May cause skin irritation and/or dermatitis.

Components:

m-tolylidene diisocyanate:

Result : irritating

Serious eye damage/eye irritation

Causes serious eye irritation.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



IDEAL hardener for 2K polyurethane parquet lacquer DS semi-matt (B)

Version	Revision Date:	SDS Number:	Date of last issue: 21.09.2022
1.2	22.09.2022	MAT000473539	Date of first issue: 08.03.2021
		GB / EN	

Product:

Remarks : May cause irreversible eye damage.

Components:

**Toluene diisocyanate, oligomeric reaction products with 2,2'-oxydiethanol and propy-
lidenetrimethanol:**

Result : Eye irritation

Benzene, 1,3-diisocyanatomethyl-, homopolymer:

Result : Eye irritation

ethyl acetate:

Result : Eye irritation

m-tolylidene diisocyanate:

Result : Eye irritation

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Product:

Remarks : Causes sensitisation.

Components:

**Toluene diisocyanate, oligomeric reaction products with 2,2'-oxydiethanol and propy-
lidenetrimethanol:**

Result : Probability or evidence of skin sensitisation in humans

Benzene, 1,3-diisocyanatomethyl-, homopolymer:

Result : Probability or evidence of skin sensitisation in humans

m-tolylidene diisocyanate:

Result : Probability of respiratory sensitisation in humans based on
animal testing

Result : Probability or evidence of skin sensitisation in humans

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



IDEAL hardener for 2K polyurethane parquet lacquer DS semi-matt (B)

Version	Revision Date:	SDS Number:	Date of last issue: 21.09.2022
1.2	22.09.2022	MAT000473539	Date of first issue: 08.03.2021
		GB / EN	

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Components:

m-tolylidene diisocyanate:

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in animal studies

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause drowsiness or dizziness.

Components:

n-butyl acetate:

Assessment : May cause drowsiness or dizziness.

ethyl acetate:

Assessment : May cause drowsiness or dizziness.

m-tolylidene diisocyanate:

Assessment : May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.
Concentrations substantially above the TLV value may cause narcotic effects.
Solvents may degrease the skin.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



IDEAL hardener for 2K polyurethane parquet lacquer DS semi-matt (B)

Version	Revision Date:	SDS Number:	Date of last issue: 21.09.2022
1.2	22.09.2022	MAT000473539	Date of first issue: 08.03.2021
		GB / EN	

SECTION 12: Ecological information

12.1 Toxicity

Components:

n-butyl acetate:

Toxicity to algae/aquatic plants : NOEC (Desmodesmus subspicatus (green algae)): > 200 mg/l

EC50 (Desmodesmus subspicatus (green algae)): >= 647,7 mg/l
Exposure time: 72 h

Toxicity to microorganisms : IC50 (Tetrahymena pyriformis): 356 mg/l
Exposure time: 40 h

m-tolylidene diisocyanate:

Ecotoxicology Assessment

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

12.2 Persistence and degradability

Components:

n-butyl acetate:

Biodegradability : Result: Biodegradable
Biodegradation: 83 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

Stability in water : Degradation half life: 78 d
pH: 8
Remarks: Hydrolyses slowly.

Photodegradation : Remarks: Decomposes rapidly in contact with light.

12.3 Bioaccumulative potential

Components:

n-butyl acetate:

Bioaccumulation : Bioconcentration factor (BCF): 15
Remarks: Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water : log Pow: 1,81

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



IDEAL hardener for 2K polyurethane parquet lacquer DS semi-matt (B)

Version	Revision Date:	SDS Number:	Date of last issue: 21.09.2022
1.2	22.09.2022	MAT000473539	Date of first issue: 08.03.2021
		GB / EN	

ethyl acetate:

Partition coefficient: n-
octanol/water : log Pow: 0,6

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Product:

Endocrine disrupting potential : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Additional ecological information : No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	: Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.
Contaminated packaging	: Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.
Waste Code	: 08 00 00, WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS 08 01 00, wastes from MFSU and removal of paint and varnish 08 01 11*, waste paint and varnish containing organic sol-

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



IDEAL hardener for 2K polyurethane parquet lacquer DS semi-matt (B)

Version	Revision Date:	SDS Number:	Date of last issue: 21.09.2022
1.2	22.09.2022	MAT000473539	Date of first issue: 08.03.2021
GB / EN			

vents or other hazardous substances
15 00 00, WASTE PACKAGING; ABSORBENTS, WIPING
CLOTHS, FILTER MATERIALS AND PROTECTIVE
CLOTHING NOT OTHERWISE SPECIFIED
15 01 00, packaging (including separately collected municipal
packaging waste)
15 01 10*, packaging containing residues of or contaminated
by hazardous substances
HP3, Flammable
HP4, Irritant - skin irritation and eye damage
HP13, Sensitising

SECTION 14: Transport information

14.1 UN number

ADN	:	UN 1263
ADR	:	UN 1263
RID	:	UN 1263
IMDG	:	UN 1263
IATA	:	UN 1263

14.2 UN proper shipping name

ADN	:	PAINT
ADR	:	PAINT
RID	:	PAINT
IMDG	:	PAINT
IATA	:	Paint

14.3 Transport hazard class(es)

ADN	:	3
ADR	:	3
RID	:	3
IMDG	:	3
IATA	:	3

14.4 Packing group

ADN	:	
Packing group	:	II
Classification Code	:	F1
Hazard Identification Number	:	33
Labels	:	3

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



IDEAL hardener for 2K polyurethane parquet lacquer DS semi-matt (B)

Version	Revision Date:	SDS Number:	Date of last issue: 21.09.2022
1.2	22.09.2022	MAT000473539	Date of first issue: 08.03.2021
		GB / EN	

ADR

Packing group : II
Classification Code : F1
Hazard Identification Number : 33
Labels : 3
Tunnel restriction code : (D/E)

RID

Packing group : II
Classification Code : F1
Hazard Identification Number : 33
Labels : 3

IMDG

Packing group : II
Labels : 3
EmS Code : F-E, S-E

IATA (Cargo)

Packing instruction (cargo aircraft) : 364
Packing instruction (LQ) : Y341
Packing group : II
Labels : Flammable Liquids

IATA (Passenger)

Packing instruction (passenger aircraft) : 353
Packing instruction (LQ) : Y341
Packing group : II
Labels : Flammable Liquids

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



IDEAL hardener for 2K polyurethane parquet lacquer DS semi-matt (B)

Version	Revision Date:	SDS Number:	Date of last issue: 21.09.2022
1.2	22.09.2022	MAT000473539	Date of first issue: 08.03.2021
		GB / EN	

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII)	:	Conditions of restriction for the following entries should be considered: Number on list 3 hexamethylene-di-isocyanate (Number on list 74) 4-methyl-m-phenylene diisocyanate (Number on list 74)
REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII)	:	Conditions of restriction for the following entries should be considered: Number on list 3 hexamethylene-di-isocyanate (Number on list 74) 4-methyl-m-phenylene diisocyanate (Number on list 74)
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	:	Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	:	Not applicable
Regulation (EU) 2019/1021 on persistent organic pollutants (recast)	:	Not applicable
UK REACH List of substances subject to authorisation (Annex XIV)	:	Not applicable

P5c

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.	P5c	FLAMMABLE LIQUIDS
---	-----	-------------------

Seveso III Directive (2012/18/EU) implemented by Control of Major Accident Hazards Regulations 2015 (COMAH)	P5c
---	-----

P5c	FLAMMABLE LIQUIDS
-----	-------------------

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



IDEAL hardener for 2K polyurethane parquet lacquer DS semi-matt (B)

Version	Revision Date:	SDS Number:	Date of last issue: 21.09.2022
1.2	22.09.2022	MAT000473539	Date of first issue: 08.03.2021
		GB / EN	

Other regulations:

15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

SECTION 16: Other information

Full text of H-Statements

H225	: Highly flammable liquid and vapour.
H226	: Flammable liquid and vapour.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H319	: Causes serious eye irritation.
H330	: Fatal if inhaled.
H334	: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H351	: Suspected of causing cancer.
H412	: Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Carc.	: Carcinogenicity
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Resp. Sens.	: Respiratory sensitisation
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitisation
STOT SE	: Specific target organ toxicity - single exposure

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified;

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



IDEAL hardener for 2K polyurethane parquet lacquer DS semi-matt (B)

Version	Revision Date:	SDS Number:	Date of last issue: 21.09.2022
1.2	22.09.2022	MAT000473539	Date of first issue: 08.03.2021
		GB / EN	

NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECl - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Classification of the mixture:

Flam. Liq. 2	H225
Eye Irrit. 2	H319
Skin Sens. 1	H317
STOT SE 3	H336

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN