

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MOBIHEL QDry THINNER

Version	Revision Date:	SDS Number:	Date of last issue: 13.07.2021
2.0	21.06.2024	MAT000480788	Date of first issue: 13.07.2021
		GB/EN	

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : MOBIHEL QDry THINNER

Product code : 48078802

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-
stance/Mixture : Coatings and paints, thinners, paint removers

Recommended restrictions
on use : Reserved for industrial and professional use.

1.3 Details of the supplier of the safety data sheet

Company : KANSAI HELIOS Slovenija d.o.o.
Količevo 65
1230 Domžale
Slovenia

Telephone Company : 386 (1) 722 4383

Telefax Company : 386 (1) 722 4310

Responsible/issuing person : 386 (1) 722 4383
productsafety@kansai-helios.si

1.4 Emergency telephone number

Call 999 (or 112) for emergency medical attention

professionals only: National Poison Information Service (NPIS) 24h national number 0844 892
0111

consumer: National Health Service (NHS) 24h national number, England & Scotland 111

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK
SI 2019/720, and UK SI 2020/1567)

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758







MOBIHEL QDry THINNER

Version	Revision Date:	SDS Number:	Date of last issue: 13.07.2021
2.0	21.06.2024	MAT000480788	Date of first issue: 13.07.2021
		GB/EN	

Flammable liquids, Category 2	H225: Highly flammable liquid and vapour.
Skin irritation, Category 2	H315: Causes skin irritation.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Reproductive toxicity, Category 2	H361d: Suspected of damaging the unborn child.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Specific target organ toxicity - repeated exposure, Category 2	H373: May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard, Category 1	H304: May be fatal if swallowed and enters airways.
Long-term (chronic) aquatic hazard, Category 3	H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Hazard pictograms	:				
Signal word	:	Danger			
Hazard statements	:	H225	Highly flammable liquid and vapour.		
		H304	May be fatal if swallowed and enters airways.		
		H315	Causes skin irritation.		
		H318	Causes serious eye damage.		
		H336	May cause drowsiness or dizziness.		
		H361d	Suspected of damaging the unborn child.		
		H373	May cause damage to organs through prolonged or repeated exposure.		
		H412	Harmful to aquatic life with long lasting effects.		
Precautionary statements	:	Prevention:			
		P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.		
		P260	Do not breathe mist or vapours.		
		P280	Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.		
		Response:			
		P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.		
		P305 + P351 + P338 + P310	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.		
		P331	Do NOT induce vomiting.		

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MOBIHEL QDry THINNER

Version
2.0

Revision Date:
21.06.2024

SDS Number:
MAT000480788
GB/EN

Date of last issue: 13.07.2021
Date of first issue: 13.07.2021

P370 + P378 In case of fire: Use dry sand, dry chemical or
alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

acetone
toluene
hydrocarbons, C6-C7, isoalkanes, cyclic, <5% n-hexane
butan-1-ol

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
acetone	67-64-1 200-662-2 606-001-00-8 01-2119471330-49	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system)	>= 30 - < 50
toluene	108-88-3 203-625-9 601-021-00-3 01-2119471310-51	Flam. Liq. 2; H225 Skin Irrit. 2; H315 Repr. 2; H361d STOT SE 3; H336 (Central nervous system) STOT RE 2; H373 Asp. Tox. 1; H304 Aquatic Chronic 3; H412	>= 30 - < 50
hydrocarbons, C6-C7, isoalkanes, cyclic, <5% n-hexane	64742-49-0 01-2119486291-36	Flam. Liq. 2; H225 STOT SE 3; H336 (Central nervous system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>= 10 - < 20
n-butyl acetate	123-86-4 204-658-1 607-025-00-1	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous	>= 1 - < 10

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MOBIHEL QDry THINNER

Version
2.0

Revision Date:
21.06.2024

SDS Number:
MAT000480788
GB/EN

Date of last issue: 13.07.2021
Date of first issue: 13.07.2021

	01-2119485493-29	system)	
1-butanol	71-36-3 200-751-6 603-004-00-6 01-2119484630-38	Flam. Liq. 3; H226 Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system)	$\geq 3 - < 10$
hexane	110-54-3 203-777-6 601-037-00-0 01-2119480412-44	Flam. Liq. 2; H225 Skin Irrit. 2; H315 Repr. 2; H361f STOT SE 3; H336 (Central nervous system) STOT RE 2; H373 Asp. Tox. 1; H304 Aquatic Chronic 2; H411 specific concentration limit STOT RE 2; H373 $\geq 5 \%$	$\geq 0,25 - < 1$

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
Symptoms of poisoning may appear several hours later.
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tis-

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MOBIHEL QDry THINNER

Version	Revision Date:	SDS Number:	Date of last issue: 13.07.2021
2.0	21.06.2024	MAT000480788	Date of first issue: 13.07.2021
		GB/EN	

sue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty
of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

Risks : May be fatal if swallowed and enters airways.
Causes skin irritation.
Causes serious eye damage.
May cause drowsiness or dizziness.
Suspected of damaging the unborn child.
May cause damage to organs through prolonged or repeated
exposure.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water
courses.

Hazardous combustion products : No hazardous combustion products are known

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MOBIHEL QDry THINNER

Version	Revision Date:	SDS Number:	Date of last issue: 13.07.2021
2.0	21.06.2024	MAT000480788	Date of first issue: 13.07.2021
		GB/EN	

5.3 Advice for firefighters

- Special protective equipment : In the event of fire, wear self-contained breathing apparatus. for firefighters
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- Personal precautions : Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

- Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MOBIHEL QDry THINNER

Version
2.0

Revision Date:
21.06.2024

SDS Number:
MAT000480788
GB/EN

Date of last issue: 13.07.2021
Date of first issue: 13.07.2021

- Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
To avoid spills during handling keep bottle on a metal tray.
Dispose of rinse water in accordance with local and national regulations.
- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.
- Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

- Specific use(s) : For further information, refer to the product technical data sheet.
- Consult the technical guidelines for the use of this substance/mixture.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
acetone	67-64-1	TWA	500 ppm 1.210 mg/m ³	GB EH40
		STEL	1.500 ppm 3.620 mg/m ³	GB EH40
		TWA	500 ppm 1.210 mg/m ³	2000/39/EC
Further information: Indicative				
toluene	108-88-3	TWA	50 ppm	GB EH40

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MOBIHEL QDry THINNER

Version
2.0

Revision Date:
21.06.2024

SDS Number:
MAT000480788
GB/EN

Date of last issue: 13.07.2021
Date of first issue: 13.07.2021

			191 mg/m3	
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	100 ppm 384 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		TWA	50 ppm 192 mg/m3	2006/15/EC
	Further information: Indicative, Identifies the possibility of significant uptake through the skin			
		STEL	100 ppm 384 mg/m3	2006/15/EC
	Further information: Indicative, Identifies the possibility of significant uptake through the skin			
n-butyl acetate	123-86-4	TWA	150 ppm 724 mg/m3	GB EH40
		STEL	200 ppm 966 mg/m3	GB EH40
		STEL	150 ppm 723 mg/m3	2019/1831/E U
	Further information: Indicative			
		TWA	50 ppm 241 mg/m3	2019/1831/E U
	Further information: Indicative			
butan-1-ol	71-36-3	STEL	50 ppm 154 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
n-hexane	110-54-3	TWA	20 ppm 72 mg/m3	GB EH40
		TWA	20 ppm 72 mg/m3	2006/15/EC
	Further information: Indicative			

Derived No Effect Level (DNEL):

according to Regulation (EC) No. 1907/2006

Substance name	End Use	Exposure routes	Potential health effects	Value
acetone	Consumers	Inhalation	Long-term systemic effects	200 mg/m3
	Workers	Inhalation	Acute local effects	2420 mg/m3
	Workers	Inhalation	Long-term systemic effects	1210 mg/m3
	Consumers	Oral	Long-term systemic effects	62 mg/kg

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MOBIHEL QDry THINNER

Version
2.0

Revision Date:
21.06.2024

SDS Number:
MAT000480788
GB/EN

Date of last issue: 13.07.2021
Date of first issue: 13.07.2021

	Consumers	Dermal	Long-term systemic effects	62 mg/kg
	Workers	Dermal	Long-term systemic effects	186 mg/kg
toluene	Workers	Inhalation	Long-term systemic effects	192 mg/m3
	Workers	Inhalation	Long-term local effects	192 mg/m3
	Consumers	Inhalation	Acute systemic effects	226 mg/m3
	Consumers	Inhalation	Acute local effects	226 mg/m3
hydrocarbons, C6-C7, isoalkanes, cyclic, <5% n-hexane	Workers	Inhalation	Long-term systemic effects	5306 mg/m3
	Consumers	Inhalation	Long-term systemic effects	1131 mg/m3
	Consumers	Oral	Long-term systemic effects	1301 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	13964 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	1377 mg/kg bw/day
n-butyl acetate	Workers	Inhalation	Acute systemic effects	600 mg/m3
	Workers	Inhalation	Acute local effects	600 mg/m3
	Workers	Inhalation	Long-term systemic effects	48 mg/m3
	Workers	Inhalation	Long-term local effects	300 mg/m3
	Consumers	Inhalation	Acute systemic effects	300 mg/m3
	Consumers	Inhalation	Acute local effects	300 mg/m3
	Consumers	Inhalation	Long-term systemic effects	12 mg/m3
	Consumers	Inhalation	Long-term local effects	35,7 mg/m3
	Consumers	Dermal	Long-term systemic effects	3,4 mg/kg bw/day
	Consumers	Dermal	Acute systemic effects	6 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	2 mg/kg bw/day
	Consumers	Oral	Acute systemic effects	2 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	7 mg/kg bw/day
	Workers	Dermal	Acute systemic effects	11 mg/kg bw/day
butan-1-ol	Workers	Inhalation	Long-term local effects	310 mg/m3

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MOBIHEL QDry THINNER

Version
2.0

Revision Date:
21.06.2024

SDS Number:
MAT000480788
GB/EN

Date of last issue: 13.07.2021
Date of first issue: 13.07.2021

			fects	
	Consumers	Inhalation	Long-term systemic effects	55,357 mg/m3
	Consumers	Inhalation	Long-term local effects	155 mg/m3
	Consumers	Dermal	Long-term systemic effects	3,125 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	1,562 mg/kg bw/day

Predicted No Effect Concentration (PNEC):

according to Regulation (EC) No. 1907/2006

Substance name	Environmental Compartment	Value
acetone	Soil	29,5 mg/kg
	Marine water	1,06 mg/l
	Fresh water	10,6 mg/l
	Marine sediment	3,04 mg/l
	Fresh water sediment	30,4 mg/l
toluene	Sewage treatment plant	100 mg/l
	Soil	2,89 mg/kg dry weight (d.w.)
	Marine water	0,68 mg/l
	Fresh water	0,68 mg/l
	Marine sediment	16,39 mg/kg dry weight (d.w.)
	Fresh water sediment	16,39 mg/kg dry weight (d.w.)
n-butyl acetate	Sewage treatment plant	13,61 mg/l
	Intermittent use/release	0,68 mg/l
	Soil	0,0903 mg/kg dry weight (d.w.)
	Marine water	0,018 mg/l
	Fresh water	0,18 mg/l
	Marine sediment	0,0981 mg/kg dry weight (d.w.)
	Fresh water sediment	0,981 mg/kg dry weight (d.w.)
	Sewage treatment plant	35,6 mg/l
	Intermittent use/release	0,36 mg/l
butan-1-ol	Soil	0,0166 mg/kg dry weight (d.w.)
	Marine water	0,0082 mg/l
	Fresh water	0,082 mg/l
	Marine sediment	0,0324 mg/kg dry weight (d.w.)
	Fresh water sediment	0,324 mg/kg dry weight (d.w.)
	Sewage treatment plant	2476 mg/l
	Intermittent use/release	2,25 mg/l

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MOBIHEL QDry THINNER

Version	Revision Date:	SDS Number:	Date of last issue: 13.07.2021
2.0	21.06.2024	MAT000480788	Date of first issue: 13.07.2021
		GB/EN	

8.2 Exposure controls

Personal protective equipment

Eye/face protection	:	Equipment should conform to EN 166 Eye wash bottle with pure water Tightly fitting safety goggles Wear face-shield and protective suit for abnormal processing problems.
Hand protection	:	
Gloves	:	PE laminate (> 0,1 mm; < 240 min); ISO EN374
Remarks	:	The suitability for a specific workplace should be discussed with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.
Skin and body protection	:	Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Respiratory protection	:	Wear a full face respirator conforming to EN136 with Type A/P2 filter or better. Self-contained closed-circuit breathing apparatus compressed (EN 145) In the case of aerosol and mist formation use an approved respirator filter (EN 141).

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	:	liquid
Colour	:	colourless
Odour	:	solvent-like
Odour Threshold	:	No data available
pH	:	Not applicable
Melting point/freezing point	:	-95,0 °C (calculation method (principal components, lowest value))
Boiling point/boiling range	:	56 °C (calculation method (principal components, lowest value))
Flash point	:	-18 °C (calculation method (principal components, lowest value)) Method: ISO 3679, closed cup
Evaporation rate	:	No data available

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MOBIHEL QDry THINNER

Version	Revision Date:	SDS Number:	Date of last issue: 13.07.2021
2.0	21.06.2024	MAT000480788	Date of first issue: 13.07.2021
		GB/EN	

Flammability (solid, gas)	:	Static-accumulating flammable liquid., Combustible Solids
Upper explosion limit / Upper flammability limit	:	13 %(V) (calculation method (principal components, highest value))
Lower explosion limit / Lower flammability limit	:	1,2 %(V) (calculation method (principal components, highest value))
Vapour pressure	:	< 1.100 hPa (calculation method (principal components, highest value)) (50 °C)
Relative vapour density	:	4 (calculation method (principal components, highest value))
Relative density	:	0,79 (calculation method (principal components, highest value))
Density	:	0,804 g/cm ³
Solubility(ies)	:	
Water solubility	:	immiscible, partly soluble
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	log Pow: 2,65 (calculation method (principal components, highest value))
Ignition temperature	:	425 °C (calculation method (principal components, highest value))
Decomposition temperature	:	No decomposition if used as directed. Hazardous decomposition products formed under fire conditions.
Viscosity	:	
Viscosity, kinematic	:	< 20,5 mm ² /s (40 °C)
Explosive properties	:	Not applicable

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MOBIHEL QDry THINNER

Version	Revision Date:	SDS Number:	Date of last issue: 13.07.2021
2.0	21.06.2024	MAT000480788	Date of first issue: 13.07.2021
		GB/EN	

Oxidizing properties : Sustains combustion

9.2 Other information

No data available
VOC : (Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control))
98 %

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Incompatible with strong acids and bases.

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.
Not classified due to lack of data.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MOBIHEL QDry THINNER

Version
2.0

Revision Date:
21.06.2024

SDS Number:
MAT000480788
GB/EN

Date of last issue: 13.07.2021
Date of first issue: 13.07.2021

Components:

acetone:

Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg
Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg

toluene:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg
Acute inhalation toxicity : LC50 (Rat): > 28 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

n-butyl acetate:

Acute oral toxicity : LD50 Oral (Rat): >= 10.760 mg/kg
Acute dermal toxicity : LD50 (Rabbit): >= 5.000 mg/kg

butan-1-ol:

Acute oral toxicity : Assessment: The component/mixture is moderately toxic after single ingestion.
LD50 Oral (Rat): > 2.000 mg/kg
Acute inhalation toxicity : LC50 (Rat): > 5 mg/l
Test atmosphere: vapour
Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg

Skin corrosion/irritation

Causes skin irritation.
Causes skin irritation.

Product:

Remarks : Extremely corrosive and destructive to tissue.

Components:

toluene:

Result : irritating

butan-1-ol:

Result : irritating

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MOBIHEL QDry THINNER

Version
2.0

Revision Date:
21.06.2024

SDS Number:
MAT000480788
GB/EN

Date of last issue: 13.07.2021
Date of first issue: 13.07.2021

n-hexane:

Result : irritating

Serious eye damage/eye irritation

Causes serious eye damage.
Causes serious eye damage.

Product:

Remarks : May cause irreversible eye damage.

Components:

acetone:

Result : Eye irritation

butan-1-ol:

Result : Corrosive

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Skin sensitisation

Not classified due to lack of data.

Respiratory sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified due to lack of data.

Germ cell mutagenicity

Not classified based on available information.
Not classified due to lack of data.

Carcinogenicity

Not classified based on available information.
Not classified due to lack of data.

Reproductive toxicity

Suspected of damaging the unborn child.
Suspected of damaging the unborn child.

Components:

toluene:

Reproductive toxicity - As- : Some evidence of adverse effects on sexual function and

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MOBIHEL QDry THINNER

Version	Revision Date:	SDS Number:	Date of last issue: 13.07.2021
2.0	21.06.2024	MAT000480788	Date of first issue: 13.07.2021
		GB/EN	

assessment fertility ,and/or on development, based on animal experiments.

n-hexane:

Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility ,and/or on development, based on animal experiments.

STOT - single exposure

May cause drowsiness or dizziness.
May cause drowsiness or dizziness.

Components:

acetone:

Assessment : May cause drowsiness or dizziness.

toluene:

Assessment : May cause drowsiness or dizziness.

hydrocarbons, C6-C7, isoalkanes, cyclic, <5% n-hexane:

Assessment : May cause drowsiness or dizziness.

n-butyl acetate:

Assessment : May cause drowsiness or dizziness.

butan-1-ol:

Assessment : May cause drowsiness or dizziness.

Assessment : May cause respiratory irritation.

n-hexane:

Assessment : May cause drowsiness or dizziness.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure.
May cause damage to organs through prolonged or repeated exposure.

Components:

toluene:

Assessment : May cause damage to organs through prolonged or repeated exposure.

n-hexane:

Assessment : May cause damage to organs through prolonged or repeated

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MOBIHEL QDry THINNER

Version
2.0

Revision Date:
21.06.2024

SDS Number:
MAT000480788
GB/EN

Date of last issue: 13.07.2021
Date of first issue: 13.07.2021

exposure.

Aspiration toxicity

May be fatal if swallowed and enters airways.
May be fatal if swallowed and enters airways.

Components:

toluene:

May be fatal if swallowed and enters airways.

hydrocarbons, C6-C7, isoalkanes, cyclic, <5% n-hexane:

May be fatal if swallowed and enters airways.

n-hexane:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.
Concentrations substantially above the TLV value may cause narcotic effects.
Solvents may degrease the skin.

SECTION 12: Ecological information

12.1 Toxicity

Components:

acetone:

Toxicity to fish : LC50 (Fish): > 1.000 mg/l

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)): > 1.000 mg/l

Toxicity to microorganisms : EC50 (Bacteria): > 1.000 mg/l

toluene:

Ecotoxicology Assessment

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MOBIHEL QDry THINNER

Version	Revision Date:	SDS Number:	Date of last issue: 13.07.2021
2.0	21.06.2024	MAT000480788	Date of first issue: 13.07.2021
		GB/EN	

hydrocarbons, C6-C7, isoalkanes, cyclic, <5% n-hexane:

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

n-butyl acetate:

Toxicity to algae/aquatic plants : NOEC (Desmodesmus subspicatus (green algae)): > 200 mg/l
EC50 (Desmodesmus subspicatus (green algae)): >= 647,7 mg/l
Exposure time: 72 h

Toxicity to microorganisms : IC50 (Tetrahymena pyriformis): 356 mg/l
Exposure time: 40 h

butan-1-ol:

Toxicity to fish : LC50 (Fish): > 1.000 mg/l
Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)): > 1.000 mg/l
Toxicity to microorganisms : EC50 (Bacteria): > 1.000 mg/l

n-hexane:

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

Components:

n-butyl acetate:

Biodegradability : Result: Biodegradable
Biodegradation: 83 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

Stability in water : Degradation half life: 78 d
pH: 8
Hydrolyses slowly.

Photodegradation : Decomposes rapidly in contact with light.

12.3 Bioaccumulative potential

Components:

acetone:

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MOBIHEL QDry THINNER

Version	Revision Date:	SDS Number:	Date of last issue: 13.07.2021
2.0	21.06.2024	MAT000480788	Date of first issue: 13.07.2021
		GB/EN	

Partition coefficient: n-octanol/water : log Pow: -0,24

toluene:

Partition coefficient: n-octanol/water : log Pow: 2,65

n-butyl acetate:

Bioaccumulation : Bioconcentration factor (BCF): 15
Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water : log Pow: 1,81

butan-1-ol:

Partition coefficient: n-octanol/water : log Pow: 0,785

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Product:

Endocrine disrupting potential : This substance/mixture does not contain components considered to have endocrine disrupting properties for environment according to UK REACH Article 57(f).
Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MOBIHEL QDry THINNER

Version	Revision Date:	SDS Number:	Date of last issue: 13.07.2021
2.0	21.06.2024	MAT000480788	Date of first issue: 13.07.2021
		GB/EN	

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

14.1 UN number

ADN	: UN 1263
ADR	: UN 1263
RID	: UN 1263
IMDG	: UN 1263
IATA	: UN 1263

14.2 UN proper shipping name

ADN	: PAINT RELATED MATERIAL
ADR	: PAINT RELATED MATERIAL
RID	: PAINT RELATED MATERIAL
IMDG	: PAINT RELATED MATERIAL
IATA	: Paint related material

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADN	: 3	
ADR	: 3	
RID	: 3	
IMDG	: 3	
IATA	: 3	

14.4 Packing group

ADN	
Packing group	: II
Classification Code	: F1
Hazard Identification Number	: 33
Labels	: 3
Remarks	: Special Provision 640D
ADR	
Packing group	: II
Classification Code	: F1
Hazard Identification Number	: 33

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MOBIHEL QDry THINNER

Version	Revision Date:	SDS Number:	Date of last issue: 13.07.2021
2.0	21.06.2024	MAT000480788	Date of first issue: 13.07.2021
		GB/EN	

Labels : 3
Tunnel restriction code : (D/E)
Remarks : Special Provision 640D

RID

Packing group : II
Classification Code : F1
Hazard Identification Number : 33
Labels : 3
Remarks : Special Provision 640D

IMDG

Packing group : II
Labels : 3
EmS Code : F-E, S-E

IATA (Cargo)

Packing instruction (cargo aircraft) : 364
Packing instruction (LQ) : Y341
Packing group : II
Labels : Flammable Liquids

IATA (Passenger)

Packing instruction (passenger aircraft) : 353
Packing instruction (LQ) : Y341
Packing group : II
Labels : Flammable Liquids

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MOBIHEL QDry THINNER

Version	Revision Date:	SDS Number:	Date of last issue: 13.07.2021
2.0	21.06.2024	MAT000480788	Date of first issue: 13.07.2021
		GB/EN	

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17)	:	Conditions of restriction for the following entries should be considered: Number on list 3 toluene (Number on list 48)
UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation	:	Not applicable
The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain)	:	Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	:	Not applicable
Regulation (EU) 2019/1148 on the marketing and use of explosives precursors	:	acetone
UK REACH List of substances subject to authorisation (Annex XIV)	:	Not applicable
GB Export and import of hazardous chemicals - Prior Informed Consent (PIC) Regulation	:	Not applicable
Control of Major Accident Hazards Regulations 2015 (COMAH)	P5c	FLAMMABLE LIQUIDS
Volatile organic compounds	:	Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 98 %

Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

SECTION 16: Other information

Full text of H-Statements

H225	:	Highly flammable liquid and vapour.
H226	:	Flammable liquid and vapour.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MOBIHEL QDry THINNER

Version	Revision Date:	SDS Number:	Date of last issue: 13.07.2021
2.0	21.06.2024	MAT000480788	Date of first issue: 13.07.2021
		GB/EN	

H302	: Harmful if swallowed.
H304	: May be fatal if swallowed and enters airways.
H315	: Causes skin irritation.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H361d	: Suspected of damaging the unborn child.
H361f	: Suspected of damaging fertility.
H373	: May cause damage to organs through prolonged or repeated exposure.
H411	: Toxic to aquatic life with long lasting effects.
H412	: Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Eye Dam.	: Serious eye damage
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Repr.	: Reproductive toxicity
Skin Irrit.	: Skin irritation
STOT RE	: Specific target organ toxicity - repeated exposure
STOT SE	: Specific target organ toxicity - single exposure
2000/39/EC	: Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2006/15/EC	: Europe. Indicative occupational exposure limit values
2019/1831/EU	: Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values
GB EH40	: UK. EH40 WEL - Workplace Exposure Limits
2000/39/EC / TWA	: Limit Value - eight hours
2006/15/EC / TWA	: Limit Value - eight hours
2006/15/EC / STEL	: Short term exposure limit
2019/1831/EU / TWA	: Limit Value - eight hours
2019/1831/EU / STEL	: Short term exposure limit
GB EH40 / TWA	: Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	: Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships car-

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MOBIHEL QDry THINNER

Version	Revision Date:	SDS Number:	Date of last issue: 13.07.2021
2.0	21.06.2024	MAT000480788	Date of first issue: 13.07.2021
		GB/EN	

rying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Classification procedure:

Flam. Liq. 2	H225	Based on product data or assessment
Skin Irrit. 2	H315	Calculation method
Eye Dam. 1	H318	Calculation method
Repr. 2	H361d	Calculation method
STOT SE 3	H336	Calculation method
STOT RE 2	H373	Calculation method
Asp. Tox. 1	H304	Calculation method
Aquatic Chronic 3	H412	Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.