

MOBIHEL THINNER FOR BASE 3100

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	28.11.2023	MAT000418259 IL/EN	Date of first issue: 28.11.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier**

Trade name : MOBIHEL THINNER FOR BASE 3100
Product code : 41825906

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Coatings and paints, thinners, paint removers
Recommended restrictions on use : Reserved for industrial and professional use.

1.3 Details of the supplier of the safety data sheet

Company : KANSAI HELIOS Slovenija d.o.o.
Količevo 65
1230 Domžale
Slovenia
Telephone Company : 386 (1) 722 4383
Telefax Company : 386 (1) 722 4310
Responsible/issuing person : 386 (1) 722 4383
productsafety@kansai-helios.si

1.4 Emergency telephone number

Ambulance (972) 101
Israel Poison Information Center +972 4 854 19 00

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****Classification (REGULATION (EC) No 1272/2008)**

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Skin irritation, Category 2	H315: Causes skin irritation.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Reproductive toxicity, Category 2	H361: Suspected of damaging fertility or the unborn child.
Specific target organ toxicity - single ex-	H336: May cause drowsiness or dizziness.

MOBIHEL THINNER FOR BASE 3100

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	28.11.2023	MAT000418259	Date of first issue: 28.11.2023
		IL/EN	

posure, Category 3, Central nervous system

Specific target organ toxicity - repeated exposure, Category 2

H373: May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard, Category 1

H304: May be fatal if swallowed and enters airways.

Long-term (chronic) aquatic hazard, Category 3

H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements :

- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H336 May cause drowsiness or dizziness.
- H361 Suspected of damaging fertility or the unborn child.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H412 Harmful to aquatic life with long lasting effects.

Precautionary statements :

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P260 Do not breathe mist or vapours.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
 P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.
 P331 Do NOT induce vomiting.
 P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

n-butyl acetate

MOBIHEL THINNER FOR BASE 3100

Version 1.0 Revision Date: 28.11.2023 SDS Number: MAT000418259 IL/EN Date of last issue: - Date of first issue: 28.11.2023

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclic, <2% aromatics
 reaction mixture of ethylbenzene, m-xylene and p-xylene
 butyl glycollate

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients**3.2 Mixtures****Components**

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
n-butyl acetate	123-86-4 204-658-1 607-025-00-1 01-2119485493-29	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system)	>= 30 - < 50
hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclic, <2% aromatics	- 01-2119471843-32	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) Asp. Tox. 1; H304 Aquatic Chronic 3; H412	>= 30 - < 50
reaction mixture of ethylbenzene, m-xylene and p-xylene	- 905-562-9 01-2119555267-33	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 Asp. Tox. 1; H304	>= 10 - < 20
butyl glycollate	7397-62-8 230-991-7 01-2119514685-36	Eye Dam. 1; H318 Repr. 2; H361	>= 3 - < 10

SECTION 4: First aid measures**4.1 Description of first aid measures**

General advice : Move out of dangerous area.
 Consult a physician.

MOBIHEL THINNER FOR BASE 3100

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	28.11.2023	MAT000418259 IL/EN	Date of first issue: 28.11.2023

Show this safety data sheet to the doctor in attendance.
Symptoms of poisoning may appear several hours later.
Do not leave the victim unattended.

- If inhaled : Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

- Risks : May be fatal if swallowed and enters airways.
Causes skin irritation.
Causes serious eye damage.
May cause drowsiness or dizziness.
Suspected of damaging fertility or the unborn child.
May cause damage to organs through prolonged or repeated exposure.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.

SECTION 5: Firefighting measures**5.1 Extinguishing media**

- Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet

MOBIHEL THINNER FOR BASE 3100

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	28.11.2023	MAT000418259 IL/EN	Date of first issue: 28.11.2023

5.2 Special hazards arising from the substance or mixture

- Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : No hazardous combustion products are known

5.3 Advice for firefighters

- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

- Personal precautions : Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

- Environmental precautions : Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

- Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

- Advice on safe handling : Avoid formation of aerosol.

MOBIHEL THINNER FOR BASE 3100

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	28.11.2023	MAT000418259 IL/EN	Date of first issue: 28.11.2023

Do not breathe vapours/dust.
 Avoid exposure - obtain special instructions before use.
 Avoid contact with skin and eyes.
 For personal protection see section 8.
 Smoking, eating and drinking should be prohibited in the application area.
 Take precautionary measures against static discharges.
 Provide sufficient air exchange and/or exhaust in work rooms.
 Open drum carefully as content may be under pressure.
 To avoid spills during handling keep bottle on a metal tray.
 Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : For further information, refer to the product technical data sheet.

Consult the technical guidelines for the use of this substance/mixture.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
n-butyl acetate	123-86-4	STEL	150 ppm 723 mg/m ³	2019/1831/E U
Further information: Indicative				
		TWA	50 ppm 241 mg/m ³	2019/1831/E U
Further information: Indicative				

MOBIHEL THINNER FOR BASE 3100

Version
1.0Revision Date:
28.11.2023SDS Number:
MAT000418259
IL/ENDate of last issue: -
Date of first issue: 28.11.2023

		TWA	50 ppm	ACGIH
		STEL	150 ppm	ACGIH
reaction mixture of ethylbenzene, m-xylene and p-xylene	1330-20-7	TLV-TWA	100 ppm	IL OEL
		TLV-C	150 mg/m ³	IL OEL
		TWA	50 ppm 221 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	100 ppm 442 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	20 ppm	ACGIH

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
reaction mixture of ethylbenzene, m-xylene and p-xylene	1330-20-7	methyl hippuric acid: 1.5 g/g creatinine (Urine)		IL BEI
		Methylhippuric acids: 1.5 g/g creatinine (Urine)	End of shift (As soon as possible after exposure ceases)	ACGIH BEI

Derived No Effect Level (DNEL)

according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
n-butyl acetate	Workers	Inhalation	Acute systemic effects	600 mg/m ³
	Workers	Inhalation	Acute local effects	600 mg/m ³
	Workers	Inhalation	Long-term systemic effects	48 mg/m ³
	Workers	Inhalation	Long-term local effects	300 mg/m ³
	Consumers	Inhalation	Acute systemic effects	300 mg/m ³
	Consumers	Inhalation	Acute local effects	300 mg/m ³
	Consumers	Inhalation	Long-term systemic effects	12 mg/m ³
	Consumers	Inhalation	Long-term local effects	35.7 mg/m ³
	Consumers	Dermal	Long-term systemic effects	3.4 mg/kg bw/day
	Consumers	Dermal	Acute systemic effects	6 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	2 mg/kg bw/day

MOBIHEL THINNER FOR BASE 3100

Version
1.0Revision Date:
28.11.2023SDS Number:
MAT000418259
IL/ENDate of last issue: -
Date of first issue: 28.11.2023

	Consumers	Oral	Acute systemic effects	2 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	7 mg/kg bw/day
	Workers	Dermal	Acute systemic effects	11 mg/kg bw/day
hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclic, <2% aromatics	Workers	Inhalation	Long-term systemic effects	871 mg/m ³
	Consumers	Inhalation	Long-term systemic effects	185 mg/m ³
	Workers	Dermal	Long-term systemic effects	208 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	125 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	125 mg/kg bw/day
reaction mixture of ethylbenzene, m-xylene and p-xylene	Workers	Inhalation	Long-term systemic effects	77 mg/m ³
	Consumers	Inhalation	Long-term local effects	65.3 mg/m ³
	Workers	Inhalation	Acute systemic effects	442 mg/m ³
	Workers	Inhalation	Acute local effects	289 mg/m ³
	Consumers	Inhalation	Acute systemic effects	260 mg/m ³
	Workers	Inhalation	Long-term local effects	221 mg/m ³
	Consumers	Inhalation	Long-term systemic effects	14.8 mg/m ³
	Consumers	Inhalation	Acute local effects	260 mg/m ³
	Consumers	Dermal	Long-term systemic effects	108 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	16 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	180 mg/kg bw/day
butyl glycollate	Workers	Inhalation	Long-term systemic effects	58.8 mg/m ³
	Consumers	Inhalation	Long-term systemic effects	17.4 mg/m ³
	Consumers	Inhalation	Long-term local effects	17.4 mg/m ³
	Consumers	Dermal	Long-term local effects	0.11 mg/cm ²
	Consumers	Oral	Long-term systemic effects	4.2 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	41.7 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	25 mg/kg bw/day

MOBIHEL THINNER FOR BASE 3100

Version 1.0 Revision Date: 28.11.2023 SDS Number: MAT000418259 IL/EN Date of last issue: - Date of first issue: 28.11.2023

Predicted No Effect Concentration (PNEC)

according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
n-butyl acetate	Soil	0.0903 mg/kg dry weight (d.w.)
	Marine water	0.018 mg/l
	Fresh water	0.18 mg/l
	Marine sediment	0.0981 mg/kg dry weight (d.w.)
	Fresh water sediment	0.981 mg/kg dry weight (d.w.)
	Sewage treatment plant	35.6 mg/l
	Intermittent use/release	0.36 mg/l
reaction mixture of ethylbenzene, m-xylene and p-xylene	Soil	2.31 mg/kg dry weight (d.w.)
	Marine water	0.327 mg/l
	Fresh water	0.327 mg/l
	Marine sediment	12.46 mg/kg dry weight (d.w.)
	Fresh water sediment	12.46 mg/kg dry weight (d.w.)
	Sewage treatment plant	6.58 mg/l
	Intermittent use/release	0.327 mg/l
butyl glycollate	Soil	0.0112 mg/kg dry weight (d.w.)
	Marine water	0.005 mg/l
	Fresh water	0.05 mg/l
	Marine sediment	0.0203 mg/kg dry weight (d.w.)
	Fresh water sediment	0.203 mg/kg dry weight (d.w.)
	Sewage treatment plant	232 mg/l
	Intermittent use/release	0.5 mg/l

8.2 Exposure controls**Personal protective equipment**

Eye/face protection : Equipment should conform to EN 166
 Eye wash bottle with pure water
 Tightly fitting safety goggles
 Wear face-shield and protective suit for abnormal processing problems.

Hand protection

Gloves : | Nitrile rubber (> 0,1 mm; < 60 min); DIN EN374 |
 | Viton® (> 0,6 mm; < 240 min); DIN EN374 |
 | PE laminate (> 0,1 mm; < 240 min); DIN EN374 |

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
 Please observe the instructions regarding permeability and

MOBIHEL THINNER FOR BASE 3100

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	28.11.2023	MAT000418259 IL/EN	Date of first issue: 28.11.2023

breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

- Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
- Filter type : Organic vapour type (A)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- Appearance : liquid
- Colour : colourless
- Odour : solvent-like
- Odour Threshold : No data available
- pH : Not applicable
- Melting point/freezing point : -78.0 °C
(calculation method (principal components, lowest value))
- Boiling point/boiling range : 80 - 110 °C (calculation method (principal components, lowest value))
- Flash point : 25 °C
- Evaporation rate : No data available
- Flammability (solid, gas) : Static-accumulating flammable liquid., Combustible Solids
- Upper explosion limit / Upper flammability limit : 7.5 %(V) (calculation method (principal components, highest value))
- Lower explosion limit / Lower flammability limit : 1.1 %(V) (calculation method (principal components, highest value))
- Vapour pressure : < 1,100 hPa (calculation method (principal components, highest value))
(50 °C)
- Relative vapour density : 4 (calculation method (principal components, highest value))

MOBIHEL THINNER FOR BASE 3100

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	28.11.2023	MAT000418259 IL/EN	Date of first issue: 28.11.2023

Relative density : 0.93 (calculation method (principal components, highest value))

Density : 0.836 g/cm³

Solubility(ies)
Water solubility : immiscible, partly soluble

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : log Pow: 2.77 - 3.15 (calculation method (principal components, highest value))

Auto-ignition temperature : 405 °C (calculation method (principal components, highest value))

Decomposition temperature : No decomposition if used as directed.
Hazardous decomposition products formed under fire conditions.

Viscosity
Viscosity, kinematic : < 20.5 mm²/s (40 °C)

Explosive properties : Not applicable

Oxidizing properties : Sustains combustion

9.2 Other information

No data available

SECTION 10: Stability and reactivity**10.1 Reactivity**

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

MOBIHEL THINNER FOR BASE 3100

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	28.11.2023	MAT000418259 IL/EN	Date of first issue: 28.11.2023

Materials to avoid : Incompatible with strong acids and bases.

10.6 Hazardous decomposition products

Adequate ventilation is required.
Heating can release vapours which can be ignited.
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

SECTION 11: Toxicological information**11.1 Information on toxicological effects****Acute toxicity**

Not classified based on available information.

Product:

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Components:**n-butyl acetate:**

Acute oral toxicity : LD50 Oral (Rat): \geq 10,760 mg/kg

Acute dermal toxicity : LD50 (Rabbit): \geq 5,000 mg/kg

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Acute oral toxicity : LD50 Oral (Rat): \geq 8,700 mg/kg

Acute inhalation toxicity : LC50 (Rat): 27.14 mg/l
Test atmosphere: vapour

Acute dermal toxicity : Assessment: The component/mixture is moderately toxic after single contact with skin.

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks : Extremely corrosive and destructive to tissue.

Components:**reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Result : irritating

MOBIHEL THINNER FOR BASE 3100

Version
1.0Revision Date:
28.11.2023SDS Number:
MAT000418259
IL/ENDate of last issue: -
Date of first issue: 28.11.2023**Serious eye damage/eye irritation**

Causes serious eye damage.

Product:

Remarks : May cause irreversible eye damage.

Components:**reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Result : Eye irritation

butyl glycollate:

Result : Corrosive

Respiratory or skin sensitisation**Skin sensitisation**

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

Components:**butyl glycollate:**

Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments.

STOT - single exposure

May cause drowsiness or dizziness.

Components:**n-butyl acetate:**

Assessment : May cause drowsiness or dizziness.

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclic, <2% aromatics:

Assessment : May cause drowsiness or dizziness.

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Assessment : May cause respiratory irritation.

MOBIHEL THINNER FOR BASE 3100

Version
1.0Revision Date:
28.11.2023SDS Number:
MAT000418259
IL/ENDate of last issue: -
Date of first issue: 28.11.2023**STOT - repeated exposure**

May cause damage to organs through prolonged or repeated exposure.

Components:**reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Assessment : May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

May be fatal if swallowed and enters airways.

Components:**hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclic, <2% aromatics:**

May be fatal if swallowed and enters airways.

reaction mixture of ethylbenzene, m-xylene and p-xylene:

May be fatal if swallowed and enters airways.

Further information**Product:**Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.
Concentrations substantially above the TLV value may cause narcotic effects.
Solvents may degrease the skin.**SECTION 12: Ecological information****12.1 Toxicity****Components:****n-butyl acetate:**

Toxicity to algae/aquatic plants : NOEC (Desmodesmus subspicatus (green algae)): > 200 mg/l

EC50 (Desmodesmus subspicatus (green algae)): >= 647.7 mg/l

Exposure time: 72 h

Toxicity to microorganisms : IC50 (Tetrahymena pyriformis): 356 mg/l
Exposure time: 40 h**hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclic, <2% aromatics:****Ecotoxicology Assessment**

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

MOBIHEL THINNER FOR BASE 3100

Version 1.0 Revision Date: 28.11.2023 SDS Number: MAT000418259 IL/EN Date of last issue: -
Date of first issue: 28.11.2023

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Toxicity to fish : LC50 (Fish): $\geq 1 - 10$ mg/l
Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)): $\geq 1 - 10$ mg/l
Toxicity to microorganisms : EC50 (Bacteria): $\geq 1 - 100$ mg/l

12.2 Persistence and degradability**Components:****n-butyl acetate:**

Biodegradability : Result: Biodegradable
Biodegradation: 83 %
Exposure time: 28 d
Method: OECD Test Guideline 301D
Stability in water : Degradation half life: 78 d
pH: 8
Remarks: Hydrolyses slowly.
Photodegradation : Remarks: Decomposes rapidly in contact with light.

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Biodegradability : Remarks: Readily biodegradable.
Photodegradation : Remarks: Decomposes rapidly in contact with light.

12.3 Bioaccumulative potential**Components:****n-butyl acetate:**

Bioaccumulation : Bioconcentration factor (BCF): 15
Remarks: Bioaccumulation is unlikely.
Partition coefficient: n-octanol/water : log Pow: 1.81

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Bioaccumulation : Bioconcentration factor (BCF): 25.9
Remarks: Bioaccumulation is unlikely.
Partition coefficient: n-octanol/water : log Pow: 2.77 - 3.15

12.4 Mobility in soil**Components:**

reaction mixture of ethylbenzene, m-xylene and p-xylene:

MOBIHEL THINNER FOR BASE 3100

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	28.11.2023	MAT000418259 IL/EN	Date of first issue: 28.11.2023

Distribution among environmental compartments : Koc: 537, log Koc: 2.73
Remarks: Moderately mobile in soils
The product evaporates from soil.

Stability in soil : Dissipation time: 23 d
Percentage dissipation: 50 % (DT50)

12.5 Results of PBT and vPvB assessment**Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects**Product:**

Endocrine disrupting potential : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

Product : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information**14.1 UN number**

ADN : UN 1263
ADR : UN 1263

MOBIHEL THINNER FOR BASE 3100

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	28.11.2023	MAT000418259 IL/EN	Date of first issue: 28.11.2023

RID : UN 1263
IMDG : UN 1263
IATA : UN 1263

14.2 UN proper shipping name

ADN : PAINT RELATED MATERIAL
ADR : PAINT RELATED MATERIAL
RID : PAINT RELATED MATERIAL
IMDG : PAINT RELATED MATERIAL
IATA : Paint related material

14.3 Transport hazard class(es)

ADN : 3
ADR : 3
RID : 3
IMDG : 3
IATA : 3

14.4 Packing group

ADN
 Packing group : III
 Classification Code : F1
 Hazard Identification Number : 30
 Labels : 3

ADR
 Packing group : III
 Classification Code : F1
 Hazard Identification Number : 30
 Labels : 3
 Tunnel restriction code : (D/E)

RID
 Packing group : III
 Classification Code : F1
 Hazard Identification Number : 30
 Labels : 3

IMDG
 Packing group : III
 Labels : 3
 EmS Code : F-E, S-E

IATA (Cargo)
 Packing instruction (cargo aircraft) : 366
 Packing instruction (LQ) : Y344
 Packing group : III
 Labels : Flammable Liquids

MOBIHEL THINNER FOR BASE 3100

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	28.11.2023	MAT000418259 IL/EN	Date of first issue: 28.11.2023

IATA (Passenger)

Packing instruction (passenger aircraft)	:	355
Packing instruction (LQ)	:	Y344
Packing group	:	III
Labels	:	Flammable Liquids

14.5 Environmental hazards**ADN**

Environmentally hazardous	:	no
---------------------------	---	----

ADR

Environmentally hazardous	:	no
---------------------------	---	----

RID

Environmentally hazardous	:	no
---------------------------	---	----

IMDG

Marine pollutant	:	no
------------------	---	----

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****15.2 Chemical safety assessment**

A Chemical Safety Assessment is not required for this substance.

SECTION 16: Other information**Full text of H-Statements**

H226	:	Flammable liquid and vapour.
H304	:	May be fatal if swallowed and enters airways.
H312	:	Harmful in contact with skin.
H315	:	Causes skin irritation.
H318	:	Causes serious eye damage.
H319	:	Causes serious eye irritation.
H332	:	Harmful if inhaled.
H335	:	May cause respiratory irritation.
H336	:	May cause drowsiness or dizziness.
H361	:	Suspected of damaging fertility or the unborn child.
H373	:	May cause damage to organs through prolonged or repeated exposure.

MOBIHEL THINNER FOR BASE 3100

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	28.11.2023	MAT000418259	Date of first issue: 28.11.2023
		IL/EN	

H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Eye Dam.	: Serious eye damage
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Repr.	: Reproductive toxicity
Skin Irrit.	: Skin irritation
STOT RE	: Specific target organ toxicity - repeated exposure
STOT SE	: Specific target organ toxicity - single exposure
2000/39/EC	: Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2019/1831/EU	: Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values
ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	: ACGIH - Biological Exposure Indices (BEI)
IL BEI	: Israel. Safety at Work Regulations - Annex III Biological Exposure Indices
IL OEL	: Israel. Safety at Work Regulations (Environmental monitoring and biological monitoring of workers)
2000/39/EC / TWA	: Limit Value - eight hours
2000/39/EC / STEL	: Short term exposure limit
2019/1831/EU / TWA	: Limit Value - eight hours
2019/1831/EU / STEL	: Short term exposure limit
ACGIH / TWA	: 8-hour, time-weighted average
ACGIH / STEL	: Short-term exposure limit
IL OEL / TLV-TWA	: Threshold Limit Value - Time Weighted (TLV-TWA)
IL OEL / TLV-C	: Threshold Limit Value - Ceiling (TLV-C)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic sub-

MOBIHEL THINNER FOR BASE 3100

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	28.11.2023	MAT000418259 IL/EN	Date of first issue: 28.11.2023

stance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information**Classification of the mixture:**

Flam. Liq. 3	H226
Skin Irrit. 2	H315
Eye Dam. 1	H318
Repr. 2	H361
STOT SE 3	H336
STOT RE 2	H373
Asp. Tox. 1	H304
Aquatic Chronic 3	H412

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

IL / EN