

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL HYDRO CLEAR BASE

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	23.08.2021	MAT000419597	Date of first issue: 23.08.2021
		GB / EN	

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Product code : 41959721

Trade name : MOBIHEL HYDRO CLEAR BASE

Unique Formula Identifier (UFI) : J0N0-J0A7-D00S-Y9P8

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : PC9a Coatings and paints, thinners, paint removers

Recommended restrictions on use : Reserved for industrial and professional use.

#### 1.3 Details of the supplier of the safety data sheet

Company : KANSAI HELIOS Slovenija d.o.o.  
Količevo 65  
1230 Domžale  
Slovenia

Telephone Company : 386 (1) 722 4383

Telefax Company : 386 (1) 722 4310

Responsible/issuing person : 386 (1) 722 4383  
productsafety@kansai-helios.si

#### 1.4 Emergency telephone number

Call 999 (or 112) for emergency medical attention

professionals only: National Poison Information Service (NPIS) 24h national number 0844 892 0111

consumer: National Health Service (NHS) 24h national number, England & Scotland 111

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Eye irritation, Category 2 H319: Causes serious eye irritation.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL HYDRO CLEAR BASE

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	23.08.2021	MAT000419597	Date of first issue: 23.08.2021
		GB / EN	

Skin sensitisation, Category 1

H317: May cause an allergic skin reaction.

Reproductive toxicity, Category 1B

H360D: May damage the unborn child.

### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements : H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H360D May damage the unborn child.

Precautionary statements : **Prevention:**  
P201 Obtain special instructions before use.  
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.  
**Response:**  
P308 + P313 IF exposed or concerned: Get medical advice/ attention.  
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.  
P337 + P313 If eye irritation persists: Get medical advice/ attention.

#### Hazardous components which must be listed on the label:

N-methyl-2-pyrrolidone  
2-methylisothiazol-3(2H)-one

#### Additional Labelling

Restricted to professional users.

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL HYDRO CLEAR BASE

Version  
1.0

Revision Date:  
23.08.2021

SDS Number:  
MAT000419597  
GB / EN

Date of last issue: -  
Date of first issue: 23.08.2021

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

##### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
2-butoxyethanol	111-76-2 203-905-0 603-014-00-0 01-2119475108-36	Acute Tox. 4; H302 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319	$\geq 1 - < 10$
butan-1-ol	71-36-3 200-751-6 603-004-00-6 01-2119484630-38	Flam. Liq. 3; H226 Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system)	$\geq 1 - < 3$
N-methyl-2-pyrrolidone	872-50-4 212-828-1 606-021-00-7 01-2119472430-46	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Repr. 1B; H360D STOT SE 3; H335 (Respiratory system)  specific concentration limit STOT SE 3; H335 $\geq 10\%$	$\geq 0,3 - < 1$
2-dimethylaminoethanol	108-01-0 203-542-8 603-047-00-0 01-2119492298-24	Flam. Liq. 3; H226 Acute Tox. 4; H302 Acute Tox. 3; H331 Acute Tox. 4; H312 Skin Corr. 1B; H314 Eye Dam. 1; H318 STOT SE 3; H335 (Respiratory system)  specific concentration limit STOT SE 3; H335 $\geq 5\%$	$\geq 0,1 - < 1$

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL HYDRO CLEAR BASE

Version 1.0      Revision Date: 23.08.2021      SDS Number: MAT000419597      Date of last issue: -  
Date of first issue: 23.08.2021  
GB / EN

2-methylisothiazol-3(2H)-one	2682-20-4 220-239-6 613-326-00-9 01-2120764690-50	Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 3; H311 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071  M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 1  specific concentration limit Skin Sens. 1A; H317 >= 0,0015 %	>= 0,0025 - < 0,025
------------------------------	--	--	------------------------

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of skin contact : If skin irritation persists, call a physician.  
If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Induce vomiting immediately and call a physician.  
Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL HYDRO CLEAR BASE

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	23.08.2021	MAT000419597	Date of first issue: 23.08.2021
		GB / EN	

Take victim immediately to hospital.

### 4.2 Most important symptoms and effects, both acute and delayed

Risks : May cause an allergic skin reaction.  
Causes serious eye irritation.  
May damage the unborn child.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Carbon dioxide (CO<sub>2</sub>)

Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : No hazardous combustion products are known.

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL HYDRO CLEAR BASE

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	23.08.2021	MAT000419597	Date of first issue: 23.08.2021
		GB / EN	

respective authorities.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).  
Keep in suitable, closed containers for disposal.

### 6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol.  
Do not breathe vapours/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.  
Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : When using do not eat or drink. When using do not smoke.  
Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : No smoking. Keep in a well-ventilated place. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage stability : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

Specific use(s) : For further information, refer to the product technical data sheet.

Consult the technical guidelines for the use of this substance/mixture.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL HYDRO CLEAR BASE

Version  
1.0

Revision Date:  
23.08.2021

SDS Number:  
MAT000419597  
GB / EN

Date of last issue: -  
Date of first issue: 23.08.2021

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

##### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
2-butoxyethanol	111-76-2	TWA	20 ppm 98 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	50 ppm 246 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	25 ppm 123 mg/m <sup>3</sup>	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	50 ppm 246 mg/m <sup>3</sup>	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
butan-1-ol	71-36-3	STEL	50 ppm 154 mg/m <sup>3</sup>	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
N-methyl-2-pyrrolidone	872-50-4	TWA	10 ppm 40 mg/m <sup>3</sup>	2009/161/EU
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	20 ppm 80 mg/m <sup>3</sup>	2009/161/EU
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	10 ppm 40 mg/m <sup>3</sup>	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	20 ppm 80 mg/m <sup>3</sup>	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
2-dimethylaminoethanol	108-01-0	TWA	2 ppm 7,4 mg/m <sup>3</sup>	GB EH40

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL HYDRO CLEAR BASE

Version  
1.0

Revision Date:  
23.08.2021

SDS Number:  
MAT000419597  
GB / EN

Date of last issue: -  
Date of first issue: 23.08.2021

		STEL	6 ppm 22 mg/m <sup>3</sup>	GB EH40
--	--	------	-------------------------------	---------

### Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
2-butoxyethanol	111-76-2	butoxyacetic acid: 240 Millimoles per mole Creatinine (Urine)	After shift	GB EH40 BAT

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
2-butoxyethanol	Workers	Inhalation	Long-term systemic effects	98 mg/m <sup>3</sup>
	Workers	Inhalation	Acute systemic effects	1091 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	246 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term systemic effects	59 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute systemic effects	426 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute local effects	147 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	125 mg/kg bw/day
	Workers	Dermal	Acute systemic effects	89 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	75 mg/kg bw/day
	Consumers	Dermal	Acute systemic effects	89 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	6,3 mg/kg bw/day
	Consumers	Oral	Acute systemic effects	26,7 mg/kg bw/day
butan-1-ol	Workers	Inhalation	Long-term local effects	310 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term systemic effects	55,357 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local effects	155 mg/m <sup>3</sup>
	Consumers	Dermal	Long-term systemic effects	3,125 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	1,562 mg/kg bw/day
N-methyl-2-pyrrolidone	Workers	Inhalation	Long-term local effects	40 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term systemic effects	14,4 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term systemic effects	3,6 mg/m <sup>3</sup>



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL HYDRO CLEAR BASE

Version  
1.0

Revision Date:  
23.08.2021

SDS Number:  
MAT000419597  
GB / EN

Date of last issue: -  
Date of first issue: 23.08.2021

	Workers	Dermal	Long-term systemic effects	4,8 mg/kg bw/day
	Consumers	Inhalation	Long-term local effects	4,5 mg/m3
	Consumers	Dermal	Long-term systemic effects	2,4 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	0,85 mg/kg bw/day
2-dimethylaminoethanol	Workers	Inhalation	Long-term systemic effects	7,4 mg/m3
	Workers	Inhalation	Acute local effects	22 mg/m3
	Workers	Dermal	Acute local effects	0,08 mg/cm2
	Workers	Dermal	Long-term systemic effects	1,04 mg/kg bw/day
	Workers	Dermal	Acute systemic effects	5 mg/kg bw/day

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
2-butoxyethanol	Soil	2,33 mg/kg dry weight (d.w.)
	Marine water	0,88 mg/l
	Fresh water	8,8 mg/l
	Fresh water sediment	34,6 mg/kg dry weight (d.w.)
	Sewage treatment plant	463 mg/l
	Intermittent use/release	9,1 mg/l
butan-1-ol	Soil	0,0166 mg/kg dry weight (d.w.)
	Marine water	0,0082 mg/l
	Fresh water	0,082 mg/l
	Marine sediment	0,0324 mg/kg dry weight (d.w.)
	Fresh water sediment	0,324 mg/kg dry weight (d.w.)
	Sewage treatment plant	2476 mg/l
N-methyl-2-pyrrolidone	Intermittent use/release	2,25 mg/l
	Soil	0,07 mg/kg dry weight (d.w.)
	Marine water	0,025 mg/l
	Fresh water	0,25 mg/l
	Fresh water sediment	1,09 mg/kg dry weight (d.w.)
	Sewage treatment plant	10 mg/l
2-dimethylaminoethanol	Intermittent use/release	5 mg/l
	Marine sediment	0,109 mg/kg dry weight (d.w.)
	Soil	0,0177 mg/kg dry weight (d.w.)
	Marine water	0,00661 mg/l
	Fresh water	0,0661 mg/l
	Fresh water sediment	0,0529 mg/kg dry

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL HYDRO CLEAR BASE

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	23.08.2021	MAT000419597	Date of first issue: 23.08.2021
		GB / EN	

		weight (d.w.)
	Sewage treatment plant	10 mg/l
	Intermittent use/release	0,0661 mg/l

### 8.2 Exposure controls

#### Personal protective equipment

Eye protection : Equipment should conform to EN 166  
Eye wash bottle with pure water  
Tightly fitting safety goggles  
Wear face-shield and protective suit for abnormal processing problems.

#### Hand protection

Gloves : | Nitrile rubber (> 0,1 mm; < 60 min); DIN EN374 | | butyl-rubber (> 0,6 mm; < 240 min); DIN EN374 | | Viton® (> 0,6 mm; < 240 min); DIN EN374 | | PE laminate (> 0,1 mm; < 240 min); DIN EN374 |

Remarks : Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

Skin and body protection : Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Equipment should conform to EN 14387

Filter type : Organic vapour type (A)

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state	: liquid
Colour	: colourless
Odour	: solvent-like
Odour Threshold	: No data available
Melting point/freezing point	: 0,0 °C (calculation method (principal components, lowest value))
Boiling point/boiling range	: 100 °C (calculation method (principal components, lowest value))

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL HYDRO CLEAR BASE

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	23.08.2021	MAT000419597	Date of first issue: 23.08.2021
		GB / EN	

---

	value))
Flammability	: Static-accumulating flammable liquid., Combustible Solids
Flash point	: 66 °C
Decomposition temperature	
Decomposition temperature	: No decomposition if used as directed. Hazardous decomposition products formed under fire conditions.
pH	: Not applicable
Viscosity	
Viscosity, kinematic	: < 20,5 mm <sup>2</sup> /s (40 °C)
Solubility(ies)	
Water solubility	: immiscible, partly soluble
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Vapour pressure	: 23 hPa (calculation method (principal components, highest value)) (20 °C)
Relative density	: 0,99 (calculation method (principal components, highest value))
Density	: 1,031 g/cm <sup>3</sup>

### 9.2 Other information

Explosives	: Not applicable
Oxidizing properties	: Sustains combustion
Evaporation rate	: No data available
VOC	: (Directive 2004/42/EC) 410 g/l

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL HYDRO CLEAR BASE

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	23.08.2021	MAT000419597	Date of first issue: 23.08.2021
GB / EN			

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

### 10.5 Incompatible materials

Materials to avoid : Incompatible with strong acids and bases.

### 10.6 Hazardous decomposition products

Adequate ventilation is required.

Heating can release vapours which can be ignited.

Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Not classified based on available information.

#### Product:

Acute oral toxicity : Acute toxicity estimate: > 2.000 mg/kg  
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg  
Method: Calculation method

#### Components:

##### 2-butoxyethanol:

Acute oral toxicity : Assessment: The component/mixture is moderately toxic after single ingestion.

LD50 Oral (Rat): >= 1.480 mg/kg

Acute inhalation toxicity : Test atmosphere: vapour  
Assessment: The component/mixture is moderately toxic after short term inhalation.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL HYDRO CLEAR BASE

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	23.08.2021	MAT000419597	Date of first issue: 23.08.2021
		GB / EN	

LC50 (Rat): 450 ppm  
Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity : Assessment: The component/mixture is moderately toxic after single contact with skin.

LD50 (Rabbit):  $\geq 1.500$  mg/kg

### butan-1-ol:

Acute oral toxicity : Assessment: The component/mixture is moderately toxic after single ingestion.

LD50 Oral (Rat):  $> 2.000$  mg/kg

Acute inhalation toxicity : LC50 (Rat):  $> 5$  mg/l  
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit):  $> 2.000$  mg/kg

### N-methyl-2-pyrrolidone:

Acute oral toxicity : LD50 Oral (Rat):  $\geq 4.150$  mg/kg

Acute inhalation toxicity : LC50 (Rat):  $\geq 5,1$  mg/l  
Exposure time: 4 h

Acute dermal toxicity : LD50 Dermal (Rat):  $\geq 5.000$  mg/kg

### 2-dimethylaminoethanol:

Acute inhalation toxicity : Assessment: The component/mixture is toxic after short term inhalation.

### 2-methylisothiazol-3(2H)-one:

Acute oral toxicity : Assessment: The component/mixture is toxic after single ingestion.

Acute inhalation toxicity : Test atmosphere: vapour  
Assessment: The component/mixture is highly toxic after short term inhalation.

Acute dermal toxicity : Assessment: The component/mixture is toxic after single contact with skin.

### Skin corrosion/irritation

Not classified based on available information.

### Product:

Remarks : May cause skin irritation and/or dermatitis.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL HYDRO CLEAR BASE

Version 1.0      Revision Date: 23.08.2021      SDS Number: MAT000419597  
GB / EN

Date of last issue: -  
Date of first issue: 23.08.2021

### Components:

#### **2-butoxyethanol:**

Result : irritating

#### **butan-1-ol:**

Result : irritating

#### **N-methyl-2-pyrrolidone:**

Result : irritating

#### **2-methylisothiazol-3(2H)-one:**

Result : Corrosive after 3 minutes to 1 hour of exposure

#### **Serious eye damage/eye irritation**

Causes serious eye irritation.

### Product:

Remarks : May cause irreversible eye damage.

### Components:

#### **2-butoxyethanol:**

Result : Eye irritation

#### **butan-1-ol:**

Result : Corrosive

#### **N-methyl-2-pyrrolidone:**

Result : Eye irritation

#### **Respiratory or skin sensitisation**

##### **Skin sensitisation**

May cause an allergic skin reaction.

##### **Respiratory sensitisation**

Not classified based on available information.

### Components:

#### **2-methylisothiazol-3(2H)-one:**

Result : Probability or evidence of skin sensitisation in humans

#### **Germ cell mutagenicity**

Not classified based on available information.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL HYDRO CLEAR BASE

Version  
1.0

Revision Date:  
23.08.2021

SDS Number:  
MAT000419597  
GB / EN

Date of last issue: -  
Date of first issue: 23.08.2021

### **Carcinogenicity**

Not classified based on available information.

### **Reproductive toxicity**

May damage the unborn child.

### **Components:**

#### **N-methyl-2-pyrrolidone:**

Reproductive toxicity - Assessment : Clear evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments

### **STOT - single exposure**

Not classified based on available information.

### **Components:**

#### **butan-1-ol:**

Assessment : May cause drowsiness or dizziness.

Assessment : May cause respiratory irritation.

#### **N-methyl-2-pyrrolidone:**

Assessment : May cause respiratory irritation.

#### **2-dimethylaminoethanol:**

Assessment : May cause respiratory irritation.

### **STOT - repeated exposure**

Not classified based on available information.

### **Aspiration toxicity**

Not classified based on available information.

## **11.2 Information on other hazards**

### **Endocrine disrupting properties**

#### **Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### **Further information**

#### **Product:**

Remarks : No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL HYDRO CLEAR BASE

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	23.08.2021	MAT000419597	Date of first issue: 23.08.2021
		GB / EN	

### SECTION 12: Ecological information

#### 12.1 Toxicity

##### Components:

##### **2-butoxyethanol:**

Toxicity to fish	: LC50 (Fish): $\geq 1.700$ mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	: LC50 (Daphnia (water flea)): $> 1.000$ mg/l Exposure time: 48 h
Toxicity to microorganisms	: EC50 (Bacteria): $> 5.000$ mg/l

##### **butan-1-ol:**

Toxicity to fish	: LC50 (Fish): $> 1.000$ mg/l
Toxicity to daphnia and other aquatic invertebrates	: LC50 (Daphnia (water flea)): $> 1.000$ mg/l
Toxicity to microorganisms	: EC50 (Bacteria): $> 1.000$ mg/l

##### **2-methylisothiazol-3(2H)-one:**

M-Factor (Acute aquatic toxicity)	: 10
M-Factor (Chronic aquatic toxicity)	: 1

##### **Ecotoxicology Assessment**

Acute aquatic toxicity	: Very toxic to aquatic life.
------------------------	-------------------------------

#### 12.2 Persistence and degradability

##### Components:

##### **2-butoxyethanol:**

Biodegradability	: Result: Biodegradable
Stability in water	: Hydrolyses slowly.
Photodegradation	: Decomposes slowly in contact with light.

##### **2-methylisothiazol-3(2H)-one:**

Biodegradability	: Result: Biodegradable
------------------	-------------------------



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL HYDRO CLEAR BASE

Version  
1.0

Revision Date:  
23.08.2021

SDS Number:  
MAT000419597  
GB / EN

Date of last issue: -  
Date of first issue: 23.08.2021

### 12.3 Bioaccumulative potential

#### Components:

##### **2-butoxyethanol:**

Partition coefficient: n-octanol/water : log Pow: 0,81 (20 °C)

##### **butan-1-ol:**

Partition coefficient: n-octanol/water : log Pow: 0,785

##### **N-methyl-2-pyrrolidone:**

Partition coefficient: n-octanol/water : log Pow: -0,46

##### **2-dimethylaminoethanol:**

Partition coefficient: n-octanol/water : log Pow: -0,55

### 12.4 Mobility in soil

#### Components:

##### **2-butoxyethanol:**

Mobility : Medium: Air  
Content: 1 %  
: Medium: Water  
Content: 47 %  
: Medium: Soil  
Content: 52 %

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

#### Components:

##### **2-butoxyethanol:**

Assessment : This substance is not considered to be persistent, bioaccumulating and toxic (PBT)..

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL HYDRO CLEAR BASE

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	23.08.2021	MAT000419597	Date of first issue: 23.08.2021
		GB / EN	

### 12.6 Endocrine disrupting properties

#### **Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

#### **Product:**

Additional ecological information : No data available

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product	: Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.
Contaminated packaging	: Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.
Waste Code	: 08 00 00, WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS 08 01 00, wastes from MFSU and removal of paint and varnish 08 01 11*, waste paint and varnish containing organic solvents or other hazardous substances 15 00 00, WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED 15 01 00, packaging (including separately collected municipal packaging waste) 15 01 10*, packaging containing residues of or contaminated by hazardous substances HP4, Irritant - skin irritation and eye damage HP10, Toxic for reproduction HP13, Sensitising

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL HYDRO CLEAR BASE

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	23.08.2021	MAT000419597	Date of first issue: 23.08.2021
		GB / EN	

### SECTION 14: Transport information

#### 14.1 UN number or ID number

Not regulated as a dangerous good

#### 14.2 UN proper shipping name

Not regulated as a dangerous good

#### 14.3 Transport hazard class(es)

Not regulated as a dangerous good

#### 14.4 Packing group

Not regulated as a dangerous good

#### 14.5 Environmental hazards

Not regulated as a dangerous good

#### 14.6 Special precautions for user

Not applicable

#### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 3

N-methyl-2-pyrrolidone (Number on list 72, 71, 30)

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : N-methyl-2-pyrrolidone

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

Seveso III: Directive 2012/18/EU of the Euro- : Not applicable

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL HYDRO CLEAR BASE

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	23.08.2021	MAT000419597	Date of first issue: 23.08.2021
		GB / EN	

European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Volatile organic compounds : Directive 2004/42/EC  
Volatile organic compounds (VOC) content: 410 g/l

### Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

### 15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

## SECTION 16: Other information

### Full text of H-Statements

H226	: Flammable liquid and vapour.
H301	: Toxic if swallowed.
H302	: Harmful if swallowed.
H311	: Toxic in contact with skin.
H312	: Harmful in contact with skin.
H314	: Causes severe skin burns and eye damage.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H330	: Fatal if inhaled.
H331	: Toxic if inhaled.
H332	: Harmful if inhaled.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H360D	: May damage the unborn child.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.
EUH071	: Corrosive to the respiratory tract.

### Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Acute	: Short-term (acute) aquatic hazard
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Eye Dam.	: Serious eye damage
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Repr.	: Reproductive toxicity
Skin Corr.	: Skin corrosion
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitisation

according to Regulation (EC) No. 1907/2006



Version 1.0	Revision Date: 23.08.2021	SDS Number: MAT000419597 GB / EN	Date of last issue: - Date of first issue: 23.08.2021
----------------	------------------------------	--	--

STOT SE	: Specific target organ toxicity - single exposure
2000/39/EC	: Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2009/161/EU	: Europe. COMMISSION DIRECTIVE 2009/161/EU establishing a third list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC and amending Commission Directive 2000/39/EC
GB EH40	: UK. EH40 WEL - Workplace Exposure Limits
GB EH40 BAT	: UK. Biological monitoring guidance values
2000/39/EC / TWA	: Limit Value - eight hours
2000/39/EC / STEL	: Short term exposure limit
2009/161/EU / TWA	: Limit Value - eight hours
2009/161/EU / STEL	: Short term exposure limit
GB EH40 / TWA	: Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	: Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

**Classification of the mixture:**

Eye Irrit. 2

H319

**Classification procedure:**

## Calculation method

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## MOBIHEL HYDRO CLEAR BASE

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	23.08.2021	MAT000419597	Date of first issue: 23.08.2021
		GB / EN	

---

Skin Sens. 1	H317	Calculation method
Repr. 1B	H360D	Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.