

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL 2K HS HARDENER 4500

| | | | |
|---------|----------------|-----------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 27.11.2023 |
| 2.0 | 19.12.2023 | MAT000470888 ES/EN | Date of first issue: 27.11.2023 |

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : MOBIHEL 2K HS HARDENER 4500
Product code : 47088821

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : PC9a Coatings and paints, thinners, paint removers
Recommended restrictions on use : Reserved for industrial and professional use.

1.3 Details of the supplier of the safety data sheet

Company : KANSAI HELIOS Slovenija d.o.o.
Količevo 65
1230 Domžale
Slovenia
Telephone Company : 386 (1) 722 4383
Telefax Company : 386 (1) 722 4310
Responsible/issuing person : 386 (1) 722 4383
productsafety@kansai-helios.si

1.4 Emergency telephone number

Instituto Nacional de Toxicología y Ciencias Forenses Servicio de Información Toxicológica + 34
91 562 04 20

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

| | |
|--------------------------------|--|
| Flammable liquids, Category 3 | H226: Flammable liquid and vapour. |
| Skin irritation, Category 2 | H315: Causes skin irritation. |
| Eye irritation, Category 2 | H319: Causes serious eye irritation. |
| Skin sensitisation, Category 1 | H317: May cause an allergic skin reaction. |




MOBIHEL 2K HS HARDENER 4500

| | | | |
|---------|----------------|-----------------------|---|
| Version | Revision Date: | SDS Number: | Date of last issue: |
| 2.0 | 19.12.2023 | MAT000470888 ES/EN | 27.11.2023 Date of first issue: 27.11.2023 |

| | |
|--|--|
| Reproductive toxicity, Category 2 | H361d: Suspected of damaging the unborn child. |
| Specific target organ toxicity - single exposure, Category 3, Respiratory system | H335: May cause respiratory irritation. |
| Specific target organ toxicity - single exposure, Category 3, Central nervous system | H336: May cause drowsiness or dizziness. |
| Specific target organ toxicity - repeated exposure, Category 2 | H373: May cause damage to organs through prolonged or repeated exposure. |
| Long-term (chronic) aquatic hazard, Category 3 | H412: Harmful to aquatic life with long lasting effects. |

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

| | | |
|--------------------------|---|--|
| Hazard pictograms | : |    |
| Signal word | : | Warning |
| Hazard statements | : | H226 Flammable liquid and vapour. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H361d Suspected of damaging the unborn child. H373 May cause damage to organs through prolonged or repeated exposure. H412 Harmful to aquatic life with long lasting effects. |
| Precautionary statements | : | Prevention: P201 Obtain special instructions before use. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P260 Do not breathe mist or vapours. P264 Wash skin thoroughly after handling. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection. Response: P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish. |

Hazardous components which must be listed on the label:

Hexamethylene-di-isocyanate, polymer

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL 2K HS HARDENER 4500

Version
2.0

Revision Date:
19.12.2023

SDS Number:
MAT000470888
ES/EN

Date of last issue: 27.11.2023
Date of first issue: 27.11.2023

n-butyl acetate
reaction mixture of ethylbenzene, m-xylene and p-xylene
toluene
dibutyltin dilaurate
hexamethylene-di-isocyanate

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

| Chemical name | CAS-No. EC-No. Index-No. Registration number | Classification | Concentration (% w/w) |
|---|---|--|--------------------------|
| Hexamethylene-di-isocyanate, polymer | 28182-81-2 500-060-2 01-2119485796-17 | Acute Tox. 4; H332 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system) | >= 50 - < 70 |
| n-butyl acetate | 123-86-4 204-658-1 607-025-00-1 01-2119485493-29 | Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) EUH066 | >= 20 - < 30 |
| reaction mixture of ethylbenzene, m-xylene and p-xylene | - 905-562-9 01-2119555267-33 | Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 Asp. Tox. 1; H304 | >= 10 - < 20 |
| toluene | 108-88-3 203-625-9 601-021-00-3 01-2119471310-51 | Flam. Liq. 2; H225 Skin Irrit. 2; H315 Repr. 2; H361d STOT SE 3; H336 (Central nervous system) | >= 3 - < 10 |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL 2K HS HARDENER 4500

Version
2.0

Revision Date:
19.12.2023

SDS Number:
MAT000470888
ES/EN

Date of last issue: 27.11.2023
Date of first issue: 27.11.2023

| | | | |
|---|---|---|---------------------|
| | | system) STOT RE 2; H373 Asp. Tox. 1; H304 Aquatic Chronic 3; H412 | |
| Solvent naphtha (petroleum), light arom.; Low boiling point naphtha - unspecified | 64742-95-6 265-199-0 649-356-00-4 01-2119455851-35 | Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411 | $\geq 2,5 - < 10$ |
| dibutyltin dilaurate | 77-58-7 201-039-8 050-030-00-3 01-2119496068-27 | Eye Irrit. 2; H319 Skin Sens. 1; H317 Muta. 2; H341 Repr. 1B; H360FD STOT SE 1; H370 STOT RE 1; H372 (Immune system) Aquatic Acute 1; H400 Aquatic Chronic 1; H410 | $\geq 0,1 - < 0,25$ |
| hexamethylene-di-isocyanate | 822-06-0 212-485-8 615-011-00-1 01-2119457571-37 | Acute Tox. 4; H302 Acute Tox. 2; H330 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system) <hr/> specific concentration limit Resp. Sens. 1; H334 $\geq 0,5 \%$ Skin Sens. 1; H317 $\geq 0,5 \%$ | $< 0,1$ |

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL 2K HS HARDENER 4500

Version
2.0

Revision Date:
19.12.2023

SDS Number:
MAT000470888
ES/EN

Date of last issue: 27.11.2023
Date of first issue: 27.11.2023

advice.

- In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

- Risks : Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
May cause respiratory irritation.
May cause drowsiness or dizziness.
Suspected of damaging the unborn child.
May cause damage to organs through prolonged or repeated exposure.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

- Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

- Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : No hazardous combustion products are known

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL 2K HS HARDENER 4500

Version
2.0

Revision Date:
19.12.2023

SDS Number:
MAT000470888
ES/EN

Date of last issue: 27.11.2023
Date of first issue: 27.11.2023

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.

MOBIHEL 2K HS HARDENER 4500

| | | | |
|---------|----------------|-----------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 27.11.2023 |
| 2.0 | 19.12.2023 | MAT000470888 ES/EN | Date of first issue: 27.11.2023 |

Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations. Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions : Protect from moisture.

Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : For further information, refer to the product technical data sheet.

Consult the technical guidelines for the use of this substance/mixture.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

| Components | CAS-No. | Value type (Form of exposure) | Control parameters | Basis |
|---------------------------------|----------|-------------------------------|----------------------------------|------------------|
| n-butyl acetate | 123-86-4 | VLA-ED | 50 ppm 241 mg/m ³ | ES VLA |
| | | VLA-EC | 150 ppm 723 mg/m ³ | ES VLA |
| | | STEL | 150 ppm 723 mg/m ³ | 2019/1831/E U |
| Further information: Indicative | | | | |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL 2K HS HARDENER 4500

Version
2.0

Revision Date:
19.12.2023

SDS Number:
MAT000470888
ES/EN

Date of last issue: 27.11.2023
Date of first issue: 27.11.2023

| | | | | |
|---|--|--------|--------------------------------------|------------------|
| | | TWA | 50 ppm 241 mg/m ³ | 2019/1831/E U |
| | Further information: Indicative | | | |
| reaction mixture of ethylbenzene, m-xylene and p-xylene | 1330-20-7 | VLA-ED | 50 ppm 221 mg/m ³ | ES VLA |
| | Further information: Skin | | | |
| | | VLA-EC | 100 ppm 442 mg/m ³ | ES VLA |
| | Further information: Skin | | | |
| | | TWA | 50 ppm 221 mg/m ³ | 2000/39/EC |
| | Further information: Identifies the possibility of significant uptake through the skin, Indicative | | | |
| | | STEL | 100 ppm 442 mg/m ³ | 2000/39/EC |
| | Further information: Identifies the possibility of significant uptake through the skin, Indicative | | | |
| toluene | 108-88-3 | TWA | 50 ppm 192 mg/m ³ | 2006/15/EC |
| | Further information: Indicative, Identifies the possibility of significant uptake through the skin | | | |
| | | STEL | 100 ppm 384 mg/m ³ | 2006/15/EC |
| | Further information: Indicative, Identifies the possibility of significant uptake through the skin | | | |
| | | VLA-ED | 50 ppm 192 mg/m ³ | ES VLA |
| | Further information: Skin | | | |
| | | VLA-EC | 100 ppm 384 mg/m ³ | ES VLA |
| | Further information: Skin | | | |
| dibutyltin dilaurate | 77-58-7 | VLA-ED | 0,1 mg/m ³ (Tin) | ES VLA |
| | Further information: Skin | | | |
| | | VLA-EC | 0,2 mg/m ³ (Tin) | ES VLA |
| | Further information: Skin | | | |
| hexamethylene-diisocyanate | 822-06-0 | VLA-ED | 0,005 ppm 0,035 mg/m ³ | ES VLA |
| | Further information: Sensitizer agent | | | |

Biological occupational exposure limits

| Substance name | CAS-No. | Control parameters | Sampling time | Basis |
|---|-----------|--|----------------|--------|
| reaction mixture of ethylbenzene, m-xylene and p-xylene | 1330-20-7 | methylhippuric acids: 1 g/g creatinine (Urine) | End of workday | ES VLB |
| toluene | 108-88-3 | toluene: 0,08 mg/l (Urine) | End of workday | ES VLB |
| | | o-cresol: 0.6 mg/g | End of workday | ES VLB |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL 2K HS HARDENER 4500

Version
2.0

Revision Date:
19.12.2023

SDS Number:
MAT000470888
ES/EN

Date of last issue: 27.11.2023
Date of first issue: 27.11.2023

| | | | | |
|--|--|----------------------------|---------------------------------|--------|
| | | Creatinine (Urine) | | |
| | | toluene: 0,05 mg/l (Blood) | prior to last shift of workweek | ES VLB |

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

| Substance name | End Use | Exposure routes | Potential health effects | Value |
|---|-----------|-----------------|----------------------------|------------------------|
| Hexamethylene-diisocyanate, polymer | Workers | Inhalation | Long-term local effects | 0,5 mg/m ³ |
| | Workers | Inhalation | Long-term systemic effects | 1 mg/m ³ |
| n-butyl acetate | Workers | Inhalation | Acute systemic effects | 600 mg/m ³ |
| | Workers | Inhalation | Acute local effects | 600 mg/m ³ |
| | Workers | Inhalation | Long-term systemic effects | 48 mg/m ³ |
| | Workers | Inhalation | Long-term local effects | 300 mg/m ³ |
| | Consumers | Inhalation | Acute systemic effects | 300 mg/m ³ |
| | Consumers | Inhalation | Acute local effects | 300 mg/m ³ |
| | Consumers | Inhalation | Long-term systemic effects | 12 mg/m ³ |
| | Consumers | Inhalation | Long-term local effects | 35,7 mg/m ³ |
| | Consumers | Dermal | Long-term systemic effects | 3,4 mg/kg bw/day |
| | Consumers | Dermal | Acute systemic effects | 6 mg/kg bw/day |
| | Consumers | Oral | Long-term systemic effects | 2 mg/kg bw/day |
| | Consumers | Oral | Acute systemic effects | 2 mg/kg bw/day |
| | Workers | Dermal | Long-term systemic effects | 7 mg/kg bw/day |
| | Workers | Dermal | Acute systemic effects | 11 mg/kg bw/day |
| reaction mixture of ethylbenzene, m-xylene and p-xylene | Workers | Inhalation | Long-term systemic effects | 77 mg/m ³ |
| | Consumers | Inhalation | Long-term local effects | 65,3 mg/m ³ |
| | Workers | Inhalation | Acute systemic effects | 442 mg/m ³ |
| | Workers | Inhalation | Acute local effects | 289 mg/m ³ |
| | Consumers | Inhalation | Acute systemic effects | 260 mg/m ³ |
| | Workers | Inhalation | Long-term local effects | 221 mg/m ³ |
| | Consumers | Inhalation | Long-term systemic effects | 14,8 mg/m ³ |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL 2K HS HARDENER 4500

Version
2.0

Revision Date:
19.12.2023

SDS Number:
MAT000470888
ES/EN

Date of last issue: 27.11.2023
Date of first issue: 27.11.2023

| | | | | |
|--|-----------|------------|----------------------------|--------------------------|
| | Consumers | Inhalation | Acute local effects | 260 mg/m ³ |
| | Consumers | Dermal | Long-term systemic effects | 108 mg/kg bw/day |
| | Consumers | Oral | Long-term systemic effects | 16 mg/kg bw/day |
| | Workers | Dermal | Long-term systemic effects | 180 mg/kg bw/day |
| toluene | Workers | Inhalation | Long-term systemic effects | 192 mg/m ³ |
| | Workers | Inhalation | Long-term local effects | 192 mg/m ³ |
| | Consumers | Inhalation | Acute systemic effects | 226 mg/m ³ |
| | Consumers | Inhalation | Acute local effects | 226 mg/m ³ |
| Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified | Workers | Inhalation | Long-term systemic effects | 150 mg/m ³ |
| | Consumers | Inhalation | Long-term systemic effects | 32 mg/m ³ |
| | Consumers | Dermal | Long-term systemic effects | 11 mg/kg bw/day |
| | Workers | Dermal | Long-term systemic effects | 25 mg/kg bw/day |
| | Consumers | Oral | Long-term systemic effects | 11 mg/kg bw/day |
| dibutyltin dilaurate | Workers | Inhalation | Long-term systemic effects | 0,02 mg/m ³ |
| | Consumers | Inhalation | Long-term systemic effects | 0,0046 mg/m ³ |
| | Consumers | Inhalation | Acute systemic effects | 0,04 mg/m ³ |
| | Workers | Dermal | Long-term systemic effects | 0,43 mg/kg bw/day |
| | Workers | Dermal | Acute systemic effects | 2,08 mg/kg bw/day |
| | Consumers | Dermal | Long-term systemic effects | 0,16 mg/kg bw/day |
| | Consumers | Dermal | Acute systemic effects | 0,5 mg/kg bw/day |
| | Consumers | Oral | Long-term systemic effects | 0,0031 mg/kg bw/day |
| | Consumers | Oral | Acute systemic effects | 0,02 mg/kg bw/day |
| hexamethylene-diisocyanate | Workers | Inhalation | Long-term systemic effects | 0,035 mg/m ³ |
| | Workers | Inhalation | Acute systemic effects | 0,07 mg/m ³ |
| | Workers | Inhalation | Long-term local effects | 0,035 mg/m ³ |
| | Workers | Inhalation | Acute local effects | 0,07 mg/m ³ |

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL 2K HS HARDENER 4500

Version
2.0

Revision Date:
19.12.2023

SDS Number:
MAT000470888
ES/EN

Date of last issue: 27.11.2023
Date of first issue: 27.11.2023

| Substance name | Environmental Compartment | Value |
|---|---------------------------|----------------------------------|
| Hexamethylene-di-isocyanate, polymer | Soil | 505 mg/kg dry weight (d.w.) |
| | Marine water | 0,01 mg/l |
| | Fresh water | 0,1 mg/l |
| | Marine sediment | 253 mg/kg dry weight (d.w.) |
| | Fresh water sediment | 2530 mg/kg dry weight (d.w.) |
| | Sewage treatment plant | 100 mg/l |
| n-butyl acetate | Intermittent use/release | 1 mg/l |
| | Soil | 0,0903 mg/kg dry weight (d.w.) |
| | Marine water | 0,018 mg/l |
| | Fresh water | 0,18 mg/l |
| | Marine sediment | 0,0981 mg/kg dry weight (d.w.) |
| | Fresh water sediment | 0,981 mg/kg dry weight (d.w.) |
| reaction mixture of ethylbenzene, m-xylene and p-xylene | Sewage treatment plant | 35,6 mg/l |
| | Intermittent use/release | 0,36 mg/l |
| | Soil | 2,31 mg/kg dry weight (d.w.) |
| | Marine water | 0,327 mg/l |
| | Fresh water | 0,327 mg/l |
| | Marine sediment | 12,46 mg/kg dry weight (d.w.) |
| toluene | Fresh water sediment | 12,46 mg/kg dry weight (d.w.) |
| | Sewage treatment plant | 6,58 mg/l |
| | Intermittent use/release | 0,327 mg/l |
| | Soil | 2,89 mg/kg dry weight (d.w.) |
| | Marine water | 0,68 mg/l |
| | Fresh water | 0,68 mg/l |
| dibutyltin dilaurate | Marine sediment | 16,39 mg/kg dry weight (d.w.) |
| | Fresh water sediment | 16,39 mg/kg dry weight (d.w.) |
| | Sewage treatment plant | 13,61 mg/l |
| | Intermittent use/release | 0,68 mg/l |
| | Fresh water | 0,000463 mg/l |
| | Sewage treatment plant | 100 mg/l |
| hexamethylene-di-isocyanate | Intermittent use/release | 0,00463 mg/l |
| | Soil | 0,0026 mg/kg dry weight (d.w.) |
| | Marine water | 0,00774 mg/l |
| | Fresh water | 0,0774 mg/l |
| | Marine sediment | 0,001344 mg/kg dry weight (d.w.) |
| Fresh water sediment | 0,01334 mg/kg | |

MOBIHEL 2K HS HARDENER 4500

| | | | |
|---------|----------------|-----------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 27.11.2023 |
| 2.0 | 19.12.2023 | MAT000470888 ES/EN | Date of first issue: 27.11.2023 |

| | | |
|--|--------------------------|-------------------|
| | | dry weight (d.w.) |
| | Sewage treatment plant | 8,42 mg/l |
| | Intermittent use/release | 0,774 mg/l |

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Equipment should conform to EN 166
Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Hand protection

Gloves : Viton® (> 0,6 mm; < 240 min); DIN EN374 |
PE laminate (> 0,1 mm; < 240 min); DIN EN374 |

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
Equipment should conform to EN 14387

Filter type : Organic vapour type (A)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid

Colour : colourless

Odour : solvent-like

Odour Threshold : No data available

Melting point/freezing point : -78,0 °C (calculation method (principal components, lowest value))

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL 2K HS HARDENER 4500

Version
2.0

Revision Date:
19.12.2023

SDS Number:
MAT000470888
ES/EN

Date of last issue: 27.11.2023
Date of first issue: 27.11.2023

| | | |
|--|---|---|
| Boiling point/boiling range | : | 126 °C (calculation method (principal components, lowest value)) |
| Flammability | : | Static-accumulating flammable liquid., Combustible Solids |
| Upper explosion limit / Upper flammability limit | : | 7,5 %(V) (calculation method (principal components, highest value)) |
| Lower explosion limit / Lower flammability limit | : | 1,1 %(V) (calculation method (principal components, highest value)) |
| Flash point | : | 31 °C |
| Ignition temperature | : | 425 °C (calculation method (principal components, highest value)) |
| Decomposition temperature | : | No decomposition if stored and applied as directed. Hazardous decomposition products formed under fire conditions. |
| pH | : | Not applicable |
| Viscosity Viscosity, kinematic | : | > 20,5 mm ² /s (40 °C) |
| Flow time | : | 13 s at 20 °C Cross section: 4 mm Method: DIN 53211 |
| Solubility(ies) Water solubility | : | partly miscible |
| Solubility in other solvents | : | Description: miscible with most organic solvents |
| Partition coefficient: n-octanol/water | : | log Pow: 2,77 - 3,15 (calculation method (principal components, highest value)) |
| Vapour pressure | : | < 1.100 hPa (calculation method (principal components, highest value)) (50 °C) |
| Relative density | : | No data available |
| Density | : | 1,02 g/cm ³ |
| Relative vapour density | : | 4 (calculation method (principal components, lowest value)) |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL 2K HS HARDENER 4500

Version
2.0

Revision Date:
19.12.2023

SDS Number:
MAT000470888
ES/EN

Date of last issue: 27.11.2023
Date of first issue: 27.11.2023

9.2 Other information

Explosives : Not applicable
Oxidizing properties : Sustains combustion

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.
Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Incompatible with strong acids and bases.

10.6 Hazardous decomposition products

Adequate ventilation is required.
Heating can release vapours which can be ignited.
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Product:

Acute inhalation toxicity : Assessment: The substance or mixture has no acute inhalation toxicity
Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

Components:

Hexamethylene-di-isocyanate, polymer:

Acute inhalation toxicity : Assessment: The component/mixture is moderately toxic after

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL 2K HS HARDENER 4500

Version
2.0

Revision Date:
19.12.2023

SDS Number:
MAT000470888
ES/EN

Date of last issue: 27.11.2023
Date of first issue: 27.11.2023

short term inhalation.

n-butyl acetate:

Acute oral toxicity : LD50 Oral (Rat): \geq 10.760 mg/kg

Acute dermal toxicity : LD50 (Rabbit): \geq 5.000 mg/kg

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Acute oral toxicity : LD50 Oral (Rat): \geq 8.700 mg/kg

Acute inhalation toxicity : LC50 (Rat): 27,14 mg/l
Test atmosphere: vapour

Acute dermal toxicity : Assessment: The component/mixture is moderately toxic after single contact with skin.

toluene:

Acute oral toxicity : LD50 Oral (Rat): $>$ 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): $>$ 28 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): $>$ 5.000 mg/kg

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:

Acute oral toxicity : LD50 Oral (Rat): $>$ 2.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): $>$ 5 mg/l
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): $>$ 2.000 mg/kg

hexamethylene-di-isocyanate:

Acute oral toxicity : Assessment: The component/mixture is moderately toxic after single ingestion.

Acute inhalation toxicity : Assessment: The component/mixture is highly toxic after short term inhalation.

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks : May cause skin irritation and/or dermatitis.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL 2K HS HARDENER 4500

Version
2.0

Revision Date:
19.12.2023

SDS Number:
MAT000470888
ES/EN

Date of last issue: 27.11.2023
Date of first issue: 27.11.2023

Components:

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Result : irritating

toluene:

Result : irritating

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks : May cause irreversible eye damage.

Components:

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Result : Eye irritation

dibutyltin dilaurate:

Result : Eye irritation

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Product:

Remarks : Causes sensitisation.

Components:

Hexamethylene-di-isocyanate, polymer:

Result : Probability or evidence of skin sensitisation in humans

dibutyltin dilaurate:

Result : Probability or evidence of skin sensitisation in humans

Germ cell mutagenicity

Not classified based on available information.

Components:

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:

Germ cell mutagenicity- Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL 2K HS HARDENER 4500

Version
2.0

Revision Date:
19.12.2023

SDS Number:
MAT000470888
ES/EN

Date of last issue: 27.11.2023
Date of first issue: 27.11.2023

dibutyltin dilaurate:

Germ cell mutagenicity- Assessment : In vitro tests showed mutagenic effects

Carcinogenicity

Not classified based on available information.

Components:

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:

Carcinogenicity - Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

Reproductive toxicity

Suspected of damaging the unborn child.

Components:

toluene:

Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments.

dibutyltin dilaurate:

Reproductive toxicity - Assessment : Clear evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments

STOT - single exposure

May cause respiratory irritation.
May cause drowsiness or dizziness.

Components:

Hexamethylene-di-isocyanate, polymer:

Assessment : May cause respiratory irritation.

n-butyl acetate:

Assessment : May cause drowsiness or dizziness.

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Assessment : May cause respiratory irritation.

toluene:

Assessment : May cause drowsiness or dizziness.

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:

Assessment : May cause drowsiness or dizziness.

MOBIHEL 2K HS HARDENER 4500

| | | | |
|---------|----------------|-----------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 27.11.2023 |
| 2.0 | 19.12.2023 | MAT000470888 ES/EN | Date of first issue: 27.11.2023 |

Assessment : May cause respiratory irritation.

dibutyltin dilaurate:

Assessment : Causes damage to organs.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Components:

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Assessment : May cause damage to organs through prolonged or repeated exposure.

toluene:

Assessment : May cause damage to organs through prolonged or repeated exposure.

dibutyltin dilaurate:

Assessment : Causes damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

Components:

reaction mixture of ethylbenzene, m-xylene and p-xylene:

May be fatal if swallowed and enters airways.

toluene:

May be fatal if swallowed and enters airways.

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:

May be fatal if swallowed and enters airways.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL 2K HS HARDENER 4500

Version
2.0

Revision Date:
19.12.2023

SDS Number:
MAT000470888
ES/EN

Date of last issue: 27.11.2023
Date of first issue: 27.11.2023

Further information

Product:

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.
Concentrations substantially above the TLV value may cause narcotic effects.
Solvents may degrease the skin.

SECTION 12: Ecological information

12.1 Toxicity

Components:

n-butyl acetate:

Toxicity to algae/aquatic plants : NOEC (Desmodesmus subspicatus (green algae)): > 200 mg/l
EC50 (Desmodesmus subspicatus (green algae)): >= 647,7 mg/l
Exposure time: 72 h

Toxicity to microorganisms : IC50 (Tetrahymena pyriformis): 356 mg/l
Exposure time: 40 h

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Toxicity to fish : LC50 (Fish): >= 1 - 10 mg/l
Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)): >= 1 - 10 mg/l
Toxicity to microorganisms : EC50 (Bacteria): >= 1 - 100 mg/l

toluene:

Ecotoxicology Assessment

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:

Toxicity to fish : LC50 (Fish): > 1 - 10 mg/l
Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)): > 1 - 10 mg/l
Toxicity to microorganisms : EC50 (Bacteria): > 1 - 10 mg/l

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL 2K HS HARDENER 4500

Version
2.0

Revision Date:
19.12.2023

SDS Number:
MAT000470888
ES/EN

Date of last issue: 27.11.2023
Date of first issue: 27.11.2023

dibutyltin dilaurate:

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

Components:

n-butyl acetate:

Biodegradability : Result: Biodegradable
Biodegradation: 83 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

Stability in water : Degradation half life: 78 d
pH: 8
Hydrolyses slowly.

Photodegradation : Decomposes rapidly in contact with light.

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Biodegradability : Readily biodegradable.

Photodegradation : Decomposes rapidly in contact with light.

12.3 Bioaccumulative potential

Components:

n-butyl acetate:

Bioaccumulation : Bioconcentration factor (BCF): 15
Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water : log Pow: 1,81

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Bioaccumulation : Bioconcentration factor (BCF): 25,9
Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water : log Pow: 2,77 - 3,15

toluene:

Partition coefficient: n-octanol/water : log Pow: 2,65

MOBIHEL 2K HS HARDENER 4500

| | | | |
|---------|----------------|-----------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 27.11.2023 |
| 2.0 | 19.12.2023 | MAT000470888 ES/EN | Date of first issue: 27.11.2023 |

12.4 Mobility in soil

Components:

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Distribution among environmental compartments : Koc: 537, log Koc: 2,73
Moderately mobile in soils
The product evaporates from soil.

Stability in soil : Dissipation time: 23 d
Percentage dissipation: 50 % (DT50)

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL 2K HS HARDENER 4500

Version
2.0

Revision Date:
19.12.2023

SDS Number:
MAT000470888
ES/EN

Date of last issue: 27.11.2023
Date of first issue: 27.11.2023

Do not burn, or use a cutting torch on, the empty drum.

Waste Code : 08 00 00, WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01 00, wastes from MFSU and removal of paint and varnish
08 01 11, waste paint and varnish containing organic solvents or other hazardous substances
15 00 00, WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED
15 01 00, packaging (including separately collected municipal packaging waste)
15 01 10, packaging containing residues of or contaminated by hazardous substances
HP3, Flammable
HP4, Irritant - skin irritation and eye damage
HP5, Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP10, Toxic for reproduction
HP13, Sensitising

SECTION 14: Transport information

14.1 UN number or ID number

ADN : UN 1263
ADR : UN 1263
RID : UN 1263
IMDG : UN 1263
IATA : UN 1263

14.2 UN proper shipping name

ADN : PAINT
ADR : PAINT
RID : PAINT
IMDG : PAINT
IATA : Paint

14.3 Transport hazard class(es)

| | Class | Subsidiary risks |
|-----|-------|------------------|
| ADN | : 3 | |
| ADR | : 3 | |
| RID | : 3 | |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL 2K HS HARDENER 4500

Version 2.0 Revision Date: 19.12.2023 SDS Number: MAT000470888
ES/EN

Date of last issue: 27.11.2023
Date of first issue: 27.11.2023

IMDG : 3

IATA : 3

14.4 Packing group

ADN

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

ADR

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3
Tunnel restriction code : (D/E)

RID

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

IMDG

Packing group : III
Labels : 3
EmS Code : F-E, S-E

IATA (Cargo)

Packing instruction (cargo aircraft) : 366
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids

IATA (Passenger)

Packing instruction (passenger aircraft) : 355
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL 2K HS HARDENER 4500

| | | | |
|---------|----------------|-----------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 27.11.2023 |
| 2.0 | 19.12.2023 | MAT000470888 ES/EN | Date of first issue: 27.11.2023 |

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 75, 3

If you intend to use this product as tattoo ink, please contact your vendor.

toluene (Number on list 48)

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : dibutyltin dilaurate

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P5c FLAMMABLE LIQUIDS

34 Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL 2K HS HARDENER 4500

Version
2.0

Revision Date:
19.12.2023

SDS Number:
MAT000470888
ES/EN

Date of last issue: 27.11.2023
Date of first issue: 27.11.2023

streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)

Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

SECTION 16: Other information

Full text of H-Statements

| | |
|--------|--|
| H225 | : Highly flammable liquid and vapour. |
| H226 | : Flammable liquid and vapour. |
| H302 | : Harmful if swallowed. |
| H304 | : May be fatal if swallowed and enters airways. |
| H312 | : Harmful in contact with skin. |
| H315 | : Causes skin irritation. |
| H317 | : May cause an allergic skin reaction. |
| H319 | : Causes serious eye irritation. |
| H330 | : Fatal if inhaled. |
| H332 | : Harmful if inhaled. |
| H334 | : May cause allergy or asthma symptoms or breathing difficulties if inhaled. |
| H335 | : May cause respiratory irritation. |
| H336 | : May cause drowsiness or dizziness. |
| H341 | : Suspected of causing genetic defects. |
| H360FD | : May damage fertility. May damage the unborn child. |
| H361d | : Suspected of damaging the unborn child. |
| H370 | : Causes damage to organs. |
| H372 | : Causes damage to organs through prolonged or repeated exposure. |
| H373 | : May cause damage to organs through prolonged or repeated exposure. |
| H400 | : Very toxic to aquatic life. |
| H410 | : Very toxic to aquatic life with long lasting effects. |
| H411 | : Toxic to aquatic life with long lasting effects. |
| H412 | : Harmful to aquatic life with long lasting effects. |
| EUH066 | : Repeated exposure may cause skin dryness or cracking. |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL 2K HS HARDENER 4500

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 27.11.2023 |
| 2.0 | 19.12.2023 | MAT000470888 | Date of first issue: 27.11.2023 |
| | | ES/EN | |

Full text of other abbreviations

| | | |
|---------------------|---|--|
| Acute Tox. | : | Acute toxicity |
| Aquatic Acute | : | Short-term (acute) aquatic hazard |
| Aquatic Chronic | : | Long-term (chronic) aquatic hazard |
| Asp. Tox. | : | Aspiration hazard |
| Eye Irrit. | : | Eye irritation |
| Flam. Liq. | : | Flammable liquids |
| Muta. | : | Germ cell mutagenicity |
| Repr. | : | Reproductive toxicity |
| Resp. Sens. | : | Respiratory sensitisation |
| Skin Irrit. | : | Skin irritation |
| Skin Sens. | : | Skin sensitisation |
| STOT RE | : | Specific target organ toxicity - repeated exposure |
| STOT SE | : | Specific target organ toxicity - single exposure |
| 2000/39/EC | : | Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values |
| 2006/15/EC | : | Europe. Indicative occupational exposure limit values |
| 2019/1831/EU | : | Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values |
| ES VLA | : | Spain. Environmental Limits for exposure to Chemical agents - Table 1: Occupational Exposure Values |
| ES VLB | : | Occupational Exposure Limits for Chemical Agents in Spain - Biological Exposure Values |
| 2000/39/EC / TWA | : | Limit Value - eight hours |
| 2000/39/EC / STEL | : | Short term exposure limit |
| 2006/15/EC / TWA | : | Limit Value - eight hours |
| 2006/15/EC / STEL | : | Short term exposure limit |
| 2019/1831/EU / TWA | : | Limit Value - eight hours |
| 2019/1831/EU / STEL | : | Short term exposure limit |
| ES VLA / VLA-ED | : | Environmental Daily Limit Value |
| ES VLA / VLA-EC | : | Environmental Short Term Value |

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Ef-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL 2K HS HARDENER 4500

Version
2.0

Revision Date:
19.12.2023

SDS Number:
MAT000470888
ES/EN

Date of last issue: 27.11.2023
Date of first issue: 27.11.2023

fect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

| | |
|-------------------|-------|
| Flam. Liq. 3 | H226 |
| Skin Irrit. 2 | H315 |
| Eye Irrit. 2 | H319 |
| Skin Sens. 1 | H317 |
| Repr. 2 | H361d |
| STOT SE 3 | H335 |
| STOT SE 3 | H336 |
| STOT RE 2 | H373 |
| Aquatic Chronic 3 | H412 |

Classification procedure:

| |
|-------------------------------------|
| Based on product data or assessment |
| Calculation method |
| Calculation method |
| Calculation method |
| Calculation method |
| Calculation method |
| Calculation method |
| Calculation method |
| Calculation method |

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.