according to Regulation (EC) No. 1907/2006



MOBIHEL HYDRO Base MIX

Version Revision Date: SDS Number: Date of last issue: -

1.0 06.09.2023 MAT0GA05_010 Date of first issue: 06.09.2023

IE/EN

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : MOBIHEL HYDRO Base MIX

Product code : Please see section 16 for detailed data

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : PC9a Coatings and paints, thinners, paint removers

stance/Mixture

Recommended restrictions

on use

: Reserved for industrial and professional use.

1.3 Details of the supplier of the safety data sheet

Company : KANSAI HELIOS Slovenija d.o.o.

Količevo 65 1230 Domžale Slovenia

Telephone Company : 386 (1) 722 4383

Telefax Company : 386 (1) 722 4310

Responsible/issuing person : 386 (1) 722 4383

productsafety@kansai-helios.si

1.4 Emergency telephone number

01 809 2166 National Poisons Information Centre 01 809 2166

01 809 2566 Healtcare Professionals 01 809 2566

01 809 2566 Healtcare Professionals 01 809 2566

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Serious eye damage, Category 1 H318: Causes serious eye damage. Reproductive toxicity, Category 1B H360D: May damage the unborn child.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

according to Regulation (EC) No. 1907/2006



MOBIHEL HYDRO Base MIX

Version Revision Date: SDS Number: Date of last issue: -

1.0 06.09.2023 MAT0GA05_010 Date of first issue: 06.09.2023

IE/EN

Hazard pictograms :



Signal word : Danger

Hazard statements : H318 Causes serious eye damage.

H360D May damage the unborn child.

Precautionary statements : Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been

read and understood.

P280 Wear protective gloves/ protective clothing/ eye protec-

tion/ face protection/ hearing protection.

Response:

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a

POISON CENTER/ doctor.

P308 + P313 IF exposed or concerned: Get medical advice/

attention.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

Hazardous components which must be listed on the label:

butan-1-ol

N-methyl-2-pyrrolidone

Additional Labelling

EUH208 Contains 1,2-benzisothiazol-3(2H)-one, 2-methylisothiazol-3(2H)-one, reaction

mass of: 5-chloro-2- methyl-4-isothiazolin-3-one and 2-methyl-2H -isothiazol-3-

one (3:1). May produce an allergic reaction.

Restricted to professional users.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not

breathe spray or mist.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006



MOBIHEL HYDRO Base MIX

Version Revision Date: SDS Number: Date of last issue: -

1.0 06.09.2023 MAT0GA05_010 Date of first issue: 06.09.2023

IE/EN

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
2-butoxyethanol	111-76-2 203-905-0 603-014-00-0 01-2119475108-36	Acute Tox. 4; H302 Acute Tox. 3; H331 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Acute toxicity estimate Acute oral toxicity: 1,200 mg/kg	>= 1 - < 10
butan-1-ol	71-36-3 200-751-6 603-004-00-6 01-2119484630-38	Flam. Liq. 3; H226 Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system)	>= 3 - < 10
N-methyl-2-pyrrolidone	872-50-4 212-828-1 606-021-00-7 01-2119472430-46	Acute Tox. 3; H331 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Repr. 1B; H360D STOT SE 3; H335 (Respiratory system) specific concentration limit STOT SE 3; H335 >= 10 % Acute toxicity estimate	>= 1 - < 10
2-dimethylaminoethanol	108-01-0	Acute inhalation toxicity (vapour): 5.1 mg/l Flam. Liq. 3; H226	>= 0.1 - < 1

according to Regulation (EC) No. 1907/2006



MOBIHEL HYDRO Base MIX

Version Revision Date: SDS Number: Date of last issue: -

1.0 06.09.2023 MAT0GA05_010 Date of first issue: 06.09.2023

IE/EN

	203-542-8 603-047-00-0 01-2119492298-24	Acute Tox. 4; H302 Acute Tox. 3; H331 Acute Tox. 4; H312 Skin Corr. 1B; H314 Eye Dam. 1; H318 STOT SE 3; H335 (Respiratory system) specific concentration limit STOT SE 3; H335 >= 5 %	
1,2-benzisothiazol-3(2H)-one	2634-33-5 220-120-9 613-088-00-6 01-2120761540-60	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 2; H411 ——————————————————————————————————	>= 0.0025 - < 0.025
		Skin Sens. 1; H317 >= 0.05 %	
2-methylisothiazol-3(2H)-one	2682-20-4 220-239-6 613-326-00-9 01-2120764690-50	Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 3; H311 Skin Corr. 1B; H314 Eye Dam. 1; H318 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071	>= 0.0002 - < 0.0015
		M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 1	
		specific concentration limit Skin Sens. 1A; H317 >= 0.0015 %	
reaction mass of: 5-chloro-2- me- thyl-4-isothiazolin-3-one and 2- methyl-2H -isothiazol-3- one (3:1)	55965-84-9 613-167-00-5	Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 2; H310	>= 0.0002 - < 0.0015

according to Regulation (EC) No. 1907/2006



MOBIHEL HYDRO Base MIX

Version Revision Date: SDS Number: Date of last issue: -

1.0 06.09.2023 MAT0GA05_010 Date of first issue: 06.09.2023

IE/EN

Skin Corr. 1C; H314 01-2120764691-48 Eye Dam. 1; H318 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071 M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100 specific concentration limit Skin Corr. 1C; H314 >= 0.6 % Skin Irrit. 2; H315 0.06 - < 0.6 % Eve Irrit. 2; H319 0.06 - < 0.6 % Skin Sens. 1A; H317 >= 0.0015 % Eye Dam. 1; H318 >= 0.6 %

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : If skin irritation persists, call a physician.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tis-

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

according to Regulation (EC) No. 1907/2006



MOBIHEL HYDRO Base MIX

Version Revision Date: SDS Number: Date of last issue: -

1.0 06.09.2023 MAT0GA05_010 Date of first issue: 06.09.2023

IE/EN

Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed Keep respiratory tract clear.

Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

Risks Causes serious eye damage.

May damage the unborn child.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Carbon dioxide (CO2)

Unsuitable extinguishing

media

High volume water jet

5.2 Special hazards arising from the substance or mixture

fighting

Specific hazards during fire : Do not allow run-off from fire fighting to enter drains or water

courses.

ucts

Hazardous combustion prod- : No hazardous combustion products are known

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

For safety reasons in case of fire, cans should be stored sepa-

rately in closed containments.

Use a water spray to cool fully closed containers.

according to Regulation (EC) No. 1907/2006



MOBIHEL HYDRO Base MIX

Version Revision Date: SDS Number: Date of last issue: -

1.0 06.09.2023 MAT0GA05_010 Date of first issue: 06.09.2023

IE/EN

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible ab-

sorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local

/ national regulations (see section 13).

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol.

Do not breathe vapours/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Provide sufficient air exchange and/or exhaust in work rooms. To avoid spills during handling keep bottle on a metal tray. Dispose of rinse water in accordance with local and national

regulations.

Advice on protection against

fire and explosion

Do not spray on a naked flame or any incandescent material.

Keep away from open flames, hot surfaces and sources of

ignition.

Hygiene measures : When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

No smoking. Keep in a well-ventilated place. Observe label precautions. Electrical installations / working materials must

comply with the technological safety standards.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

according to Regulation (EC) No. 1907/2006



MOBIHEL HYDRO Base MIX

Version Revision Date: SDS Number: Date of last issue: -

1.0 06.09.2023 MAT0GA05_010 Date of first issue: 06.09.2023

IE/EN

7.3 Specific end use(s)

Specific use(s) : For further information, refer to the product technical data

sheet.

Consult the technical guidelines for the use of this sub-

stance/mixture.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
2-butoxyethanol	111-76-2	TWA	20 ppm 98 mg/m3	2000/39/EC
	Further inforn skin, Indicativ		possibility of significant uptal	ke through the
		STEL	50 ppm 246 mg/m3	2000/39/EC
	Further inforn skin, Indicativ	е	possibility of significant uptak	ke through the
		OELV - 8 hrs (TWA)	20 ppm 98 mg/m3	IE OEL
		ey come in contact wi	which have the capacity to pe ith it, and be absorbed into the	ne body
		OELV - 15 min (STEL)	50 ppm 246 mg/m3	IE OEL
			which have the capacity to pe ith it, and be absorbed into the	
butan-1-ol	71-36-3	OELV - 8 hrs (TWA)	20 ppm	IE OEL
aluminium	7429-90-5	OELV - 8 hrs (TWA) (Respira- ble dust)	1 mg/m3	IE OEL
N-methyl-2- pyrrolidone	872-50-4	TWA	10 ppm 40 mg/m3	2009/161/EU
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	20 ppm 80 mg/m3	2009/161/EU
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		OELV - 15 min (STEL)	20 ppm 80 mg/m3	IE OEL
	Further information: Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body			
		OELV - 8 hrs (TWA)	10 ppm 40 mg/m3	IE OEL
Further information: Substances which have the capacity to penetrate intact				

according to Regulation (EC) No. 1907/2006



MOBIHEL HYDRO Base MIX

Version Revision Date: SDS Number: Date of last issue: -

1.0 06.09.2023 MAT0GA05_010 Date of first issue: 06.09.2023

IE/EN

	skin when the	ey come in contact w	ith it, and be absorbed into tl	ne body	
		TWA	10 ppm	2004/37/EC	
			40 mg/m3		
	Further inforn	Further information: Skin, Carcinogens or mutagens			
		STEL	20 ppm	2004/37/EC	
			80 mg/m3		
	Further inforn	Further information: Skin, Carcinogens or mutagens			
titanium dioxide	13463-67-7	OELV - 8 hrs	4 mg/m3	IE OEL	
		(TWA) (Respira-			
		ble dust)			
		OELV - 8 hrs	10 mg/m3	IE OEL	
İ		(TWA) (inhalable			
		dust)			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
2-butoxyethanol	Workers	Inhalation	Long-term systemic effects	98 mg/m3
	Workers	Inhalation	Acute systemic effects	1091 mg/m3
	Workers	Inhalation	Acute local effects	246 mg/m3
	Consumers	Inhalation	Long-term systemic effects	59 mg/m3
	Consumers	Inhalation	Acute systemic effects	426 mg/m3
	Consumers	Inhalation	Acute local effects	147 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	125 mg/kg bw/day
	Workers	Dermal	Acute systemic ef- fects	89 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	75 mg/kg bw/day
	Consumers	Dermal	Acute systemic effects	89 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	6.3 mg/kg bw/day
	Consumers	Oral	Acute systemic effects	26.7 mg/kg bw/day
butan-1-ol	Workers	Inhalation	Long-term local ef- fects	310 mg/m3
	Consumers	Inhalation	Long-term systemic effects	55.357 mg/m3
	Consumers	Inhalation	Long-term local effects	155 mg/m3
	Consumers	Dermal	Long-term systemic effects	3.125 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	1.562 mg/kg bw/day
aluminium	Workers	Inhalation	Long-term systemic effects	3.72 mg/m3

according to Regulation (EC) No. 1907/2006



MOBIHEL HYDRO Base MIX

יטט inumber: MAT0GA05_010 JE/FN Version Revision Date: Date of last issue: -

1.0 06.09.2023 Date of first issue: 06.09.2023 IE/EN

	Workers	Inhalation	Long-term local effects	3.72 mg/m3
	Consumers	Oral	Long-term systemic effects	3.95 mg/kg bw/day
N-methyl-2- pyrrolidone	Workers	Inhalation	Long-term local ef- fects	40 mg/m3
	Workers	Inhalation	Long-term systemic effects	14.4 mg/m3
	Consumers	Inhalation	Long-term systemic effects	3.6 mg/m3
	Workers	Dermal	Long-term systemic effects	4.8 mg/kg bw/day
	Consumers	Inhalation	Long-term local ef- fects	4.5 mg/m3
	Consumers	Dermal	Long-term systemic effects	2.4 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	0.85 mg/kg bw/day
titanium dioxide	Workers	Inhalation	Long-term local ef- fects	10 mg/m3
	Consumers	Oral	Long-term systemic effects	700 mg/kg bw/day
2- dimethylaminoethanol	Workers	Inhalation	Long-term systemic effects	7.4 mg/m3
, , , , , , , , , , , , , , , , , , ,	Workers	Inhalation	Acute local effects	22 mg/m3
	Workers	Dermal	Acute local effects	0.08 mg/cm2
	Workers	Dermal	Long-term systemic effects	1.04 mg/kg bw/day
	Workers	Dermal	Acute systemic ef- fects	5 mg/kg bw/day
1,2-benzisothiazol- 3(2H)-one	Workers	Inhalation	Long-term systemic effects	6.81 mg/m3
	Workers	Dermal	Long-term systemic effects	0.966 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	1.2 mg/m3
	Consumers	Dermal	Long-term systemic effects	0.345 mg/kg bw/day
reaction mass of: 5- chloro-2- methyl-4- isothiazolin-3-one and 2-methyl-2H - isothiazol-3- one (3:1)	Consumers	Inhalation	Acute local effects	0.04 mg/m3
	Workers	Inhalation	Long-term local effects	0.02 mg/m3
	Workers	Inhalation	Acute local effects	0.04 mg/m3
	Consumers	Inhalation	Long-term local ef- fects	0.02 mg/m3
	Consumers	Oral	Long-term systemic effects	0.09 mg/kg bw/day
	Consumers	Oral	Acute systemic ef- fects	0.11 mg/kg bw/day

according to Regulation (EC) No. 1907/2006



MOBIHEL HYDRO Base MIX

Version Revision Date: SDS Number: Date of last issue: -

1.0 06.09.2023 MAT0GA05_010 Date of first issue: 06.09.2023

IE/EN

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
2-butoxyethanol	Soil	2.33 mg/kg dry
•		weight (d.w.)
	Marine water	0.88 mg/l
	Fresh water	8.8 mg/l
	Fresh water sediment	34.6 mg/kg dry
		weight (d.w.)
	Sewage treatment plant	463 mg/l
	Intermittent use/release	9.1 mg/l
butan-1-ol	Soil	0.0166 mg/kg dry
		weight (d.w.)
	Marine water	0.0082 mg/l
	Fresh water	0.082 mg/l
	Marine sediment	0.0324 mg/kg dry
		weight (d.w.)
	Fresh water sediment	0.324 mg/kg dry
		weight (d.w.)
	Sewage treatment plant	2476 mg/l
	Intermittent use/release	2.25 mg/l
aluminium	Sewage treatment plant	20 mg/l
N-methyl-2-pyrrolidone	Soil	0.07 mg/kg dry
, ,,		weight (d.w.)
	Marine water	0.025 mg/l
	Fresh water	0.25 mg/l
	Fresh water sediment	1.09 mg/kg dry
		weight (d.w.)
	Sewage treatment plant	10 mg/l
	Intermittent use/release	5 mg/l
	Marine sediment	0.109 mg/kg dry
		weight (d.w.)
titanium dioxide	Soil	100 mg/kg dry
		weight (d.w.)
	Marine water	0.0184 mg/l
	Fresh water	0.184 mg/l
	Marine sediment	100 mg/kg dry
		weight (d.w.)
	Fresh water sediment	1000 mg/kg dry
		weight (d.w.)
	Sewage treatment plant	100 mg/l
	Intermittent use/release	0.193 mg/l
2-dimethylaminoethanol	Soil	0.0177 mg/kg dry
•		weight (d.w.)
	Marine water	0.00661 mg/l
	Fresh water	0.0661 mg/l
	Fresh water sediment	0.0529 mg/kg dry
		weight (d.w.)
	Sewage treatment plant	10 mg/l
	Intermittent use/release	0.0661 mg/l
1,2-benzisothiazol-3(2H)-one	Fresh water	0.00403 mg/l
, ,	Intermittent use/release	0.0011 mg/l

according to Regulation (EC) No. 1907/2006



MOBIHEL HYDRO Base MIX

Version Revision Date: SDS Number: Date of last issue: -

1.0 06.09.2023 MAT0GA05_010 Date of first issue: 06.09.2023

IE/EN

	Marine water	0.000403 mg/l
	Sewage treatment plant	1.03 mg/l
	Fresh water sediment	0.0499 mg/kg dry weight (d.w.)
	Marine sediment	0.00499 mg/kg dry weight (d.w.)
	Soil	3 mg/kg dry weight (d.w.)
reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one and 2-methyl-2H -isothiazol-3- one (3:1)	Soil	0.01 mg/kg dry weight (d.w.)
	Marine water	0.00339 mg/l
	Fresh water	0.00339 mg/l
	Marine sediment	0.027 mg/kg dry weight (d.w.)
	Fresh water sediment	0.027 mg/kg dry weight (d.w.)
	Sewage treatment plant	0.23 mg/l
	Intermittent use/release	0.00339 mg/l

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Equipment should conform to EN 166

Eye wash bottle with pure water Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Hand protection

Gloves : Nitrile rubber (> 0,1 mm; < 60 min); DIN EN374

butyl-rubber (> 0,6 mm; < 240 min); DIN EN374 | Viton® (> 0,6 mm; < 240 min); DIN EN374 | PE laminate (> 0,1 mm; < 240 min); DIN EN374 |

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of

cuts, abrasion, and the contact time.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : Use respiratory protection unless adequate local exhaust ven-

tilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Equipment should conform to EN 14387

Filter type : Combined particulates and organic vapour type (A-P)

according to Regulation (EC) No. 1907/2006



MOBIHEL HYDRO Base MIX

Version SDS Number: Date of last issue: -Revision Date:

1.0 06.09.2023 MAT0GA05_010 Date of first issue: 06.09.2023

IE/EN

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state liquid

Colour in accordance with the product description

Odour solvent-like Odour Threshold No data available

Melting point/freezing point 0.0 °C (calculation method (principal components, lowest val-

ue))

Boiling point/boiling range 100 °C (calculation method (principal components, lowest

value))

Static-accumulating flammable liquid., Combustible Solids Flammability

Flash point 66 °C

No decomposition if stored and applied as directed. Decomposition temperature

Hazardous decomposition products formed under fire condi-

tions.

Not applicable рΗ

Viscosity

Viscosity, kinematic $> 20.5 \text{ mm}2/\text{s} (40 ^{\circ}\text{C})$

Flow time 35 - 45 s at 20 °C

Cross section: 4 mm

Method: DIN4

Solubility(ies)

Water solubility immiscible, partly soluble

Description: miscible with most organic solvents Solubility in other solvents

Partition coefficient: n-

octanol/water

No data available

Vapour pressure 23 hPa (calculation method (principal components, highest

> value)) (20 °C)

Relative density No data available

Density 0.99 - 1.213 g/cm3

No data available Relative vapour density

9.2 Other information

Explosives Not applicable

according to Regulation (EC) No. 1907/2006



MOBIHEL HYDRO Base MIX

Version Revision Date: SDS Number: Date of last issue: -

1.0 06.09.2023 MAT0GA05_010 Date of first issue: 06.09.2023

IE/EN

Oxidizing properties : Not applicable

VOC : (Directive 2004/42/EC)

410 g/l

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Incompatible with strong acids and bases.

10.6 Hazardous decomposition products

Adequate ventilation is required.

Heating can release vapours which can be ignited.

Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l

Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Components:

2-butoxyethanol:

according to Regulation (EC) No. 1907/2006



MOBIHEL HYDRO Base MIX

Version Revision Date: SDS Number: Date of last issue: -

1.0 06.09.2023 MAT0GA05_010 Date of first issue: 06.09.2023

IE/EN

Acute oral toxicity : Acute toxicity estimate: 1,200 mg/kg

Method: Acute toxicity estimate according to Regulation (EC)

No. 1272/2008

Acute inhalation toxicity : LC50 (Rat): 450 ppm

Exposure time: 4 h
Test atmosphere: vapour

Assessment: The component/mixture is toxic after short term

inhalation.

butan-1-ol:

Acute oral toxicity : Assessment: The component/mixture is moderately toxic after

single ingestion.

LD50 Oral (Rat): > 2,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l

Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

N-methyl-2-pyrrolidone:

Acute oral toxicity : LD50 Oral (Rat): >= 4,150 mg/kg

Acute inhalation toxicity : LC50 (Rat): >= 5.1 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 Dermal (Rat): >= 5,000 mg/kg

2-dimethylaminoethanol:

Acute inhalation toxicity : Assessment: The component/mixture is toxic after short term

inhalation.

1,2-benzisothiazol-3(2H)-one:

Acute oral toxicity : Assessment: The component/mixture is moderately toxic after

single ingestion.

2-methylisothiazol-3(2H)-one:

Acute oral toxicity : Assessment: The component/mixture is toxic after single in-

gestion.

Acute inhalation toxicity : Test atmosphere: vapour

Assessment: The component/mixture is highly toxic after short

term inhalation.

Acute dermal toxicity : Assessment: The component/mixture is toxic after single con-

tact with skin.

according to Regulation (EC) No. 1907/2006



MOBIHEL HYDRO Base MIX

Version Revision Date: SDS Number: Date of last issue: -

1.0 06.09.2023 MAT0GA05_010 Date of first issue: 06.09.2023

IE/EN

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks : Extremely corrosive and destructive to tissue.

Components:

2-butoxyethanol:

Result : irritating

butan-1-ol:

Result : irritating

N-methyl-2-pyrrolidone:

Result : irritating

1,2-benzisothiazol-3(2H)-one:

Result : irritating

2-methylisothiazol-3(2H)-one:

Result : Corrosive after 3 minutes to 1 hour of exposure

Serious eye damage/eye irritation

Causes serious eye damage.

Product:

Remarks : May cause irreversible eye damage.

Components:

2-butoxyethanol:

Result : Eye irritation

butan-1-ol:

Result : Corrosive

N-methyl-2-pyrrolidone:

Result : Eye irritation

1,2-benzisothiazol-3(2H)-one:

Result : Corrosive

according to Regulation (EC) No. 1907/2006



MOBIHEL HYDRO Base MIX

Version Revision Date: SDS Number: Date of last issue: -

1.0 06.09.2023 MAT0GA05_010 Date of first issue: 06.09.2023

IE/EN

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

1,2-benzisothiazol-3(2H)-one:

Result : Probability or evidence of skin sensitisation in humans

2-methylisothiazol-3(2H)-one:

Result : Probability or evidence of skin sensitisation in humans

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

May damage the unborn child.

Components:

N-methyl-2-pyrrolidone:

Reproductive toxicity - As- : Clear evidence of adverse effects on sexual function and fertil-

sessment ity,and/or on development, based on animal experiments

STOT - single exposure

Not classified based on available information.

Components:

butan-1-ol:

Assessment : May cause drowsiness or dizziness.

Assessment : May cause respiratory irritation.

N-methyl-2-pyrrolidone:

Assessment : May cause respiratory irritation.

2-dimethylaminoethanol:

Assessment : May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

according to Regulation (EC) No. 1907/2006



MOBIHEL HYDRO Base MIX

Version SDS Number: Date of last issue: -Revision Date:

1.0 06.09.2023 MAT0GA05_010 Date of first issue: 06.09.2023

IE/EN

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

The substance/mixture does not contain components consid-Assessment

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

Further information

Product:

Remarks No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

2-butoxyethanol:

Toxicity to fish LC50 (Fish): >= 1,700 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

LC50 (Daphnia (water flea)): > 1,000 mg/l

Exposure time: 48 h

Toxicity to microorganisms EC50 (Bacteria): > 5,000 mg/l

butan-1-ol:

Toxicity to fish LC50 (Fish): > 1,000 mg/l

aquatic invertebrates

Toxicity to daphnia and other : LC50 (Daphnia (water flea)): > 1,000 mg/l

Toxicity to microorganisms : EC50 (Bacteria): > 1,000 mg/l

1,2-benzisothiazol-3(2H)-one:

Ecotoxicology Assessment

Chronic aquatic toxicity Toxic to aquatic life with long lasting effects.

2-methylisothiazol-3(2H)-one:

M-Factor (Acute aquatic tox- : 10

icity)

18 / 25

according to Regulation (EC) No. 1907/2006



MOBIHEL HYDRO Base MIX

Version Revision Date: SDS Number: Date of last issue: -

1.0 06.09.2023 MAT0GA05_010 Date of first issue: 06.09.2023

IE/EN

M-Factor (Chronic aquatic

toxicity)

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one and 2-methyl-2H -isothiazol-3-

one (3:1):

Toxicity to fish : LC50 (Salvelinus namaycush (lake trout)): >= 10.85 mg/l

Exposure time: 96 h

Toxicity to algae/aquatic

plants

LC50 (algae): >= 0.82 mg/l

Exposure time: 48 h

LC50 (algae): 0.018 mg/l Exposure time: 72 h

M-Factor (Acute aquatic tox- :

icity)

100

M-Factor (Chronic aquatic

toxicity)

100

12.2 Persistence and degradability

Components:

2-butoxyethanol:

Biodegradability : Result: Biodegradable

Stability in water : Hydrolyses slowly.

Photodegradation : Decomposes slowly in contact with light.

2-methylisothiazol-3(2H)-one:

Biodegradability : Result: Biodegradable

12.3 Bioaccumulative potential

Components:

2-butoxyethanol:

Partition coefficient: n- : log Pow: 0.81 (20 °C)

octanol/water

butan-1-ol:

Partition coefficient: n- :

octanol/water

log Pow: 0.785

N-methyl-2-pyrrolidone:

Partition coefficient: n-

octanol/water

log Pow: -0.46

according to Regulation (EC) No. 1907/2006



MOBIHEL HYDRO Base MIX

Version Revision Date: SDS Number: Date of last issue: -

1.0 06.09.2023 MAT0GA05_010 Date of first issue: 06.09.2023

IE/EN

2-dimethylaminoethanol:

Partition coefficient: n-

octanol/water

log Pow: -0.55

1,2-benzisothiazol-3(2H)-one:

Partition coefficient: n-

octanol/water

: log Pow: 1.3

12.4 Mobility in soil

Components:

2-butoxyethanol:

Mobility : Medium: Air

Content: 1 %

Medium: Water Content: 47 %

Medium: Soil Content: 52 %

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

Components:

2-butoxyethanol:

Assessment : This substance is not considered to be persistent, bioaccumu-

lating and toxic (PBT).

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological infor-

mation

: No data available

according to Regulation (EC) No. 1907/2006



MOBIHEL HYDRO Base MIX

Version SDS Number: Date of last issue: -Revision Date:

1.0 06.09.2023 MAT0GA05_010 Date of first issue: 06.09.2023

IE/EN

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Send to a licensed waste management company.

Contaminated packaging Empty remaining contents.

> Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

Waste Code 08 00 00, WASTES FROM THE MANUFACTURE,

FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS

(PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS

08 01 00, wastes from MFSU and removal of paint and var-

08 01 11, waste paint and varnish containing organic solvents

or other hazardoussubstances

15 00 00, WASTE PACKAGING; ABSORBENTS, WIPING

CLOTHS, FILTER MATERIALS AND PROTECTIVE

CLOTHING NOT OTHERWISE SPECIFIED

15 01 00, packaging (including separately collected municipal

packaging waste)

15 01 10, packaging containing residues of or contaminated

by hazardoussubstances

HP4, Irritant - skin irritation and eye damage

HP10, Toxic for reproduction

SECTION 14: Transport information

14.1 UN number or ID number

ADN Not regulated as a dangerous good **ADR** Not regulated as a dangerous good

RID Not regulated as a dangerous good

Not regulated as a dangerous good **IATA** Not regulated as a dangerous good

14.2 UN proper shipping name

IMDG

ADN Not regulated as a dangerous good

ADR : Not regulated as a dangerous good

RID Not regulated as a dangerous good

IMDG Not regulated as a dangerous good

according to Regulation (EC) No. 1907/2006



MOBIHEL HYDRO Base MIX

Version Revision Date: SDS Number: Date of last issue: -

1.0 06.09.2023 MAT0GA05_010 Date of first issue: 06.09.2023

IE/EN

IATA : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.4 Packing group

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA (Cargo) : Not regulated as a dangerous good
IATA (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) Conditions of restriction for the following entries should be considered: Number on list 75, 3

If you intend to use this product as tattoo ink, please contact your vendor.

N-methyl-2-pyrrolidone (Number on list 72, 71, 30)

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

N-methyl-2-pyrrolidone

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Regulation (EU) 2019/1021 on persistent organic pollu-

: Not applicable

: Not applicable

according to Regulation (EC) No. 1907/2006



MOBIHEL HYDRO Base MIX

Version Date of last issue: -Revision Date: SDS Number:

1.0 06.09.2023 MAT0GA05_010 Date of first issue: 06.09.2023

IE/EN

tants (recast)

Regulation (EC) No 649/2012 of the European Parlia-Not applicable

ment and the Council concerning the export and import

of dangerous chemicals

REACH - List of substances subject to authorisation Not applicable

(Annex XIV)

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving

dangerous substances.

Not applicable

Directive 2004/42/EC Volatile organic compounds

Volatile organic compounds (VOC) content: 410 g/l

Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations. where applicable.

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

SECTION 16: Other information

Full text of H-Statements

Flammable liquid and vapour. H226

Toxic if swallowed. H301 H302 Harmful if swallowed. Fatal in contact with skin. H310 Toxic in contact with skin. H311 H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

Causes skin irritation. H315

H317 May cause an allergic skin reaction. Causes serious eye damage. H318 Causes serious eye irritation. H319

Fatal if inhaled. H330 H331 Toxic if inhaled.

H335 May cause respiratory irritation. May cause drowsiness or dizziness. H336 May damage the unborn child. H360D

Very toxic to aquatic life. H400

Very toxic to aquatic life with long lasting effects. H410 H411 Toxic to aquatic life with long lasting effects.

EUH071 Corrosive to the respiratory tract.

Full text of other abbreviations

Acute Tox. Acute toxicity

Short-term (acute) aquatic hazard **Aquatic Acute**

according to Regulation (EC) No. 1907/2006



MOBIHEL HYDRO Base MIX

Version Revision Date: SDS Number: Date of last issue: -

1.0 06.09.2023 MAT0GA05_010 Date of first issue: 06.09.2023

IE/EN

Aquatic Chronic : Long-term (chronic) aquatic hazard

Eye Dam. : Serious eye damage

Eye Irrit. : Eye irritation
Flam. Liq. : Flammable liquids
Repr. : Reproductive toxicity

Skin Corr. : Skin corrosion
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation

STOT SE : Specific target organ toxicity - single exposure

2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first

list of indicative occupational exposure limit values

2004/37/EC : Europe. Directive 2004/37/EC on the protection of workers

from the risks related to exposure to carcinogens or mutagens

at work

2009/161/EU : Europe. COMMISSION DIRECTIVE 2009/161/EU establishing

a third list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC and amending

Commission Directive 2000/39/EC

IE OEL : Ireland. List of Chemical Agents and Occupational Exposure

Limit Values - Schedule 1

2000/39/EC / TWA : Limit Value - eight hours 2000/39/EC / STEL : Short term exposure limit 2004/37/EC / TWA : Long term exposure limit 2009/161/EU / TWA : Limit Value - eight hours 2009/161/EU / STEL : Short term exposure limit : Short term exposure limit

IE OEL / OELV - 8 hrs (TWA) : Occupational exposure limit value (8-hour reference period)
IE OEL / OELV - 15 min : Occupational exposure limit value (15-minute reference peri-

(STEL) od)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA -European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic sub-

according to Regulation (EC) No. 1907/2006



MOBIHEL HYDRO Base MIX

Version Revision Date: SDS Number: Date of last issue: -

1.0 06.09.2023 MAT0GA05_010 Date of first issue: 06.09.2023

IE/EN

stance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture: Classification procedure:

Eye Dam. 1H318Calculation methodRepr. 1BH360DCalculation method

Material codes (bulk) for 400929, 400996, 401107, 401194, 401196, 470600, 470601, which the SDS is valid 470608, 470610, 470612, 470613, 470614, 470616, 470617,

470618, 470619, 470621, 470622, 470625, 470626, 470627,

470628, 470629, 470630, 470631, 470632, 470633, 470641,

470642, 470643, 470644, 470645, 470646, 470651, 470652,

 $470661,\,470662,\,470663,\,470665,\,470700,\,470701,\,470702,$

470703, 470704, 470705, 470706, 470708, 470715, 470720, 470721, 470722, 470730, 470740, 470750, 470751, 470752,

470753, 470760, 470770, 470771, 470772, 470780, 470781,

470795, 470796, 470800, 470801, 470802, 470803, 470804,

470805

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.