

**MOBIHEL GLASSFIBRE PUTTY**

|         |                     |                       |                                 |
|---------|---------------------|-----------------------|---------------------------------|
| Version | Revision            | SDS Number:           | Date of last issue: -           |
| 1.0     | Date:<br>16.11.2023 | MAT0GA05_065<br>AU/EN | Date of first issue: 16.11.2023 |

---

**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Product name : MOBIHEL GLASSFIBRE PUTTY

Product code : 40090301

**Manufacturer or supplier's details****Details of the supplier of the safety data sheet**Company : Helios Coatings Australia Pty Ltd  
50 Clapham Road  
SEFTON NSW 2162  
AustraliaTelephone : 61 2 9645 3188  
E-mail address Responsible/issuing person : 61 2 9645 3188  
info@helioscoatings.com.au**Emergency telephone number**

112 (mobile) Ambulance 000, Poisons Information Centre: 131 126

---

**SECTION 2. HAZARDS IDENTIFICATION****GHS Classification**

|  |               |
|--|---------------|
| Flammable liquids                                  | : Category 3  |
| Skin corrosion/irritation                          | : Category 2  |
| Serious eye damage/eye irritation                  | : Category 2A |
| Skin sensitisation                                 | : Category 1  |
| Reproductive toxicity                              | : Category 2  |
| Specific target organ toxicity - repeated exposure | : Category 1  |

**GHS label elements**Hazard pictograms : 

Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.

**MOBIHEL GLASSFIBRE PUTTY**

|         |                     |                       |                                 |
|---------|---------------------|-----------------------|---------------------------------|
| Version | Revision            | SDS Number:           | Date of last issue: -           |
| 1.0     | Date:<br>16.11.2023 | MAT0GA05_065<br>AU/EN | Date of first issue: 16.11.2023 |

---

H319 Causes serious eye irritation.  
H361 Suspected of damaging fertility or the unborn child.  
H372 Causes damage to organs through prolonged or repeated exposure.

## Precautionary statements

:

**Prevention:**

P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 Keep container tightly closed.  
P240 Ground and bond container and receiving equipment.  
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.  
P242 Use non-sparking tools.  
P243 Take action to prevent static discharges.  
P260 Do not breathe mist or vapours.  
P264 Wash skin thoroughly after handling.  
P270 Do not eat, drink or smoke when using this product.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

**Response:**

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308 + P313 IF exposed or concerned: Get medical advice/ attention.  
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.  
P337 + P313 If eye irritation persists: Get medical advice/ attention.  
P362 + P364 Take off contaminated clothing and wash it before reuse.  
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

**Storage:**

P403 + P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

**Other hazards which do not result in classification**

None known.

**MOBIHEL GLASSFIBRE PUTTY**

Version      Revision      SDS Number:  
1.0          Date:          MAT0GA05\_065  
              16.11.2023      AU/EN

Date of last issue: -  
Date of first issue: 16.11.2023

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS****Components**

| Chemical name            | CAS-No.    | Concentration (% w/w) |
|--------------------------|------------|-----------------------|
| talc                     | 14807-96-6 | >= 30 -< 60           |
| styrene                  | 100-42-5   | >= 10 -< 20           |
| Limestone                | 1317-65-3  | >= 10 -< 30           |
| barium sulphate, natural | 7727-43-7  | < 10                  |
| titanium dioxide         | 13463-67-7 | < 10                  |
| toluene                  | 108-88-3   | < 3                   |

**SECTION 4. FIRST AID MEASURES**

- General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of skin contact : If skin irritation persists, call a physician.  
If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.
- Most important symptoms and effects, both acute and delayed : None known.
- Notes to physician : Treat symptomatically.

**SECTION 5. FIREFIGHTING MEASURES**

- Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : High volume water jet

**MOBIHEL GLASSFIBRE PUTTY**

|         |                     |                       |                                 |
|---------|---------------------|-----------------------|---------------------------------|
| Version | Revision            | SDS Number:           | Date of last issue: -           |
| 1.0     | Date:<br>16.11.2023 | MAT0GA05_065<br>AU/EN | Date of first issue: 16.11.2023 |

---

|   |   |   |
|---|---|---|
| Specific hazards during fire-fighting         | : | Do not allow run-off from fire fighting to enter drains or water courses.   |
| Hazardous combustion products                 | : | No hazardous combustion products are known  |
| Specific extinguishing methods                | : | Collect contaminated fire extinguishing water separately. This must not be discharged into drains.<br>Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.<br>For safety reasons in case of fire, cans should be stored separately in closed containments.<br>Use a water spray to cool fully closed containers. |
| Special protective equipment for firefighters | : | Wear self-contained breathing apparatus for firefighting if necessary.  |
| Hazchem Code                                  | : | •2YE  |

---

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

|   |   |   |
|---|---|---|
| Personal precautions, protective equipment and emergency procedures | : | Use personal protective equipment.<br>Remove all sources of ignition.<br>Evacuate personnel to safe areas.<br>Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.             |
| Environmental precautions   | : | Prevent product from entering drains.<br>Prevent further leakage or spillage if safe to do so.<br>If the product contaminates rivers and lakes or drains inform respective authorities.   |
| Methods and materials for containment and cleaning up               | : | Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). |

---

**SECTION 7. HANDLING AND STORAGE**

|   |   |  |
|---|---|--|
| Advice on protection against fire and explosion | : | Do not spray on a naked flame or any incandescent material.<br>Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).<br>Keep away from open flames, hot surfaces and sources of ignition.                                     |
| Advice on safe handling                         | : | Avoid formation of aerosol.<br>Do not breathe vapours/dust.<br>Avoid exposure - obtain special instructions before use.<br>Avoid contact with skin and eyes.<br>For personal protection see section 8.<br>Smoking, eating and drinking should be prohibited in the application area. |

**MOBIHEL GLASSFIBRE PUTTY**

|         |            |              |                                 |
|---------|------------|--------------|---------------------------------|
| Version | Revision   | SDS Number:  | Date of last issue: -           |
| 1.0     | Date:      | MAT0GA05_065 | Date of first issue: 16.11.2023 |
|         | 16.11.2023 | AU/EN        |                                 |

Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Open drum carefully as content may be under pressure.  
Dispose of rinse water in accordance with local and national regulations.  
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

- Hygiene measures : When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.
- Conditions for safe storage : No smoking.  
Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage stability : No decomposition if stored and applied as directed.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION****Components with workplace control parameters**

| Components       | CAS-No.    | Value type<br>(Form of exposure)    | Control parameters / Permissible concentration | Basis  |
|------------------|------------|-------------------------------------|--|--------|
| Talc             | 14807-96-6 | TWA                                 | 2.5 mg/m <sup>3</sup>                          | AU OEL |
|                  |            | TWA (Respirable particulate matter) | 2 mg/m <sup>3</sup>                            | ACGIH  |
| styrene          | 100-42-5   | TWA                                 | 50 ppm<br>213 mg/m <sup>3</sup>                | AU OEL |
|                  |            | STEL                                | 100 ppm<br>426 mg/m <sup>3</sup>               | AU OEL |
|                  |            | TWA                                 | 10 ppm   | ACGIH  |
|                  |            | STEL                                | 20 ppm   | ACGIH  |
| Limestone        | 1317-65-3  | TWA                                 | 10 mg/m <sup>3</sup><br>(Calcium carbonate)    | AU OEL |
| barium sulfate   | 7727-43-7  | TWA                                 | 10 mg/m <sup>3</sup>                           | AU OEL |
|                  |            | TWA (Inhalable particulate matter)  | 5 mg/m <sup>3</sup>                            | ACGIH  |
| titanium dioxide | 13463-67-7 | TWA                                 | 10 mg/m <sup>3</sup>                           | AU OEL |
|                  |            | TWA (Res-                           | 0.2 mg/m <sup>3</sup>                          | ACGIH  |

## SAFETY DATA SHEET



## MOBIHEL GLASSFIBRE PUTTY

Version  
1.0Revision  
Date:  
16.11.2023SDS Number:  
MAT0GA05\_065  
AU/ENDate of last issue: -  
Date of first issue: 16.11.2023

|                                      |          |                                     |   |        |
|--------------------------------------|----------|-------------------------------------|---|--------|
|                                      |          | pirable particulate matter)         | (Titanium dioxide)                          |        |
|                                      |          | TWA (Respirable particulate matter) | 2.5 mg/m <sup>3</sup><br>(Titanium dioxide) | ACGIH  |
| toluene                              | 108-88-3 | TWA                                 | 50 ppm<br>191 mg/m <sup>3</sup>             | AU OEL |
| Further information: Skin absorption |          |                                     |   |        |
|                                      |          | STEL                                | 150 ppm<br>574 mg/m <sup>3</sup>            | AU OEL |
| Further information: Skin absorption |          |                                     |   |        |
|                                      |          | TWA                                 | 20 ppm                                      | ACGIH  |

## Biological occupational exposure limits

| Components | CAS-No.  | Control parameters                      | Biological specimen | Sampling time  | Permissible concentration | Basis     |
|------------|----------|---|---------------------|--|---------------------------|-----------|
| styrene    | 100-42-5 | Mandelic acid plus phenylglyoxylic acid | Urine               | End of shift (As soon as possible after exposure ceases) | 400 mg/g Creatinine       | ACGIH BEI |
|            |          | Styrene                                 | Urine               | End of shift (As soon as possible after exposure ceases) | 40 µg/l                   | ACGIH BEI |
| toluene    | 108-88-3 | Toluene                                 | In blood            | Prior to last shift of work-week                         | 0.02 mg/l                 | ACGIH BEI |
|            |          | Toluene                                 | Urine               | End of shift (As soon as possible after exposure ceases) | 0.03 mg/l                 | ACGIH BEI |
|            |          | o-Cresol                                | Urine               | End of shift (As soon as possible after exposure ceases) | 0.3 mg/g Creatinine       | ACGIH BEI |

## Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

**MOBIHEL GLASSFIBRE PUTTY**

|         |                     |                       |                                 |
|---------|---------------------|-----------------------|---------------------------------|
| Version | Revision            | SDS Number:           | Date of last issue: -           |
| 1.0     | Date:<br>16.11.2023 | MAT0GA05_065<br>AU/EN | Date of first issue: 16.11.2023 |

---

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Combined particulates and organic vapour type

**Hand protection**

Gloves : Nitrile rubber (> 0,1 mm; < 60 min); DIN EN374 |  
butyl-rubber (> 0,6 mm; < 240 min); DIN EN374 |  
Viton® (> 0,6 mm; < 240 min); DIN EN374 |  
PE laminate (> 0,1 mm; < 240 min); DIN EN374 |

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.  
Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

Eye protection : Equipment should conform to EN 166  
Eye wash bottle with pure water  
Tightly fitting safety goggles  
Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection : Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

---

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : viscous liquid

Colour : in accordance with the product description

Odour : solvent-like

Odour Threshold : No data available

pH : Not applicable

Melting point/freezing point : -31.0 °C  
(calculation method (principal components, lowest value))

Boiling point/boiling range : 145 °C  
(calculation method (principal components, lowest value))

Flash point : 31 °C

**MOBIHEL GLASSFIBRE PUTTY**

|         |                     |                       |                                 |
|---------|---------------------|-----------------------|---------------------------------|
| Version | Revision            | SDS Number:           | Date of last issue: -           |
| 1.0     | Date:<br>16.11.2023 | MAT0GA05_065<br>AU/EN | Date of first issue: 16.11.2023 |

(calculation method (principal components, lowest value))

|  |   |   |
|--|---|---|
| Evaporation rate                                 | : | No data available   |
| Flammability (solid, gas)                        | : | Static-accumulating flammable liquid., Combustible Solids   |
| Upper explosion limit / Upper flammability limit | : | 8 %(V)  |
| Lower explosion limit / Lower flammability limit | : | 1.1 %(V)  |
| Relative vapour density                          | : | 3.6<br>(Air = 1.0)  |
| Relative density                                 | : | 1.60  |
| Density  | : | 1.687 - 1.801 g/cm3   |
| Solubility(ies)                                  |   |   |
| Water solubility                                 | : | immiscible, partly soluble  |
| Solubility in other solvents                     | : | No data available   |
| Partition coefficient: n-octanol/water           | : | log Pow: 2.95   |
| Auto-ignition temperature                        | : | 490 °C  |
| Decomposition temperature                        | : | No decomposition if stored and applied as directed.<br>Hazardous decomposition products formed under fire conditions. |
| Viscosity  |   |   |
| Viscosity, kinematic                             | : | > 20.5 mm2/s ( 40 °C)   |
| Explosive properties                             | : | Not applicable  |
| Oxidizing properties                             | : | Sustains combustion   |
| VOC  | : | (Directive 2004/42/EC)<br>250 g/l   |

**SECTION 10. STABILITY AND REACTIVITY**

|                                    |   |   |
|------------------------------------|---|---|
| Reactivity                         | : | No decomposition if stored and applied as directed.   |
| Chemical stability                 | : | No decomposition if stored and applied as directed.   |
| Possibility of hazardous reactions | : | No decomposition if stored and applied as directed.<br>Vapours may form explosive mixture with air. |



**MOBIHEL GLASSFIBRE PUTTY**

|         |                     |                       |                                 |
|---------|---------------------|-----------------------|---------------------------------|
| Version | Revision            | SDS Number:           | Date of last issue: -           |
| 1.0     | Date:<br>16.11.2023 | MAT0GA05_065<br>AU/EN | Date of first issue: 16.11.2023 |

|                                  |  |
|----------------------------------|--|
| Conditions to avoid              | : Heat, flames and sparks.   |
| Incompatible materials           | : Incompatible with strong acids and bases.  |
| Hazardous decomposition products | : Adequate ventilation is required.<br>Heating can release vapours which can be ignited.<br>Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke). |

**SECTION 11. TOXICOLOGICAL INFORMATION****Acute toxicity****Components:****styrene:**

|                           |   |
|---------------------------|---|
| Acute oral toxicity       | : LD50 Oral (Rat): $\geq 5,000$ mg/kg   |
| Acute inhalation toxicity | : LC50 (Rat): $\geq 24$ mg/l<br>Exposure time: 4 h<br>Test atmosphere: vapour |
| Acute dermal toxicity     | : LD50 (Rabbit): $> 2,650$ mg/kg  |

**Limestone:**

|                           |   |
|---------------------------|---|
| Acute inhalation toxicity | : Assessment: The substance or mixture has no acute inhalation toxicity |
|---------------------------|---|

**toluene:**

|                           |  |
|---------------------------|--|
| Acute oral toxicity       | : LD50 Oral (Rat): $> 5,000$ mg/kg   |
| Acute inhalation toxicity | : LC50 (Rat): $> 28$ mg/l<br>Exposure time: 4 h<br>Test atmosphere: vapour |
| Acute dermal toxicity     | : LD50 (Rabbit): $> 5,000$ mg/kg   |

**Skin corrosion/irritation****Product:**

|         |  |
|---------|--|
| Remarks | : May cause skin irritation and/or dermatitis. |
|---------|--|

**Components:****styrene:**

|        |              |
|--------|--------------|
| Result | : irritating |
|--------|--------------|

**toluene:**

|        |              |
|--------|--------------|
| Result | : irritating |
|--------|--------------|

|         |                     |                       |                                 |
|---------|---------------------|-----------------------|---------------------------------|
| Version | Revision            | SDS Number:           | Date of last issue: -           |
| 1.0     | Date:<br>16.11.2023 | MAT0GA05_065<br>AU/EN | Date of first issue: 16.11.2023 |

Remarks : May cause irreversible eye damage.

### Components:

**styrene:**

Result : Eye irritation

## Respiratory or skin sensitisation

**Product:**

|         |                         |
|---------|-------------------------|
| Remarks | : Causes sensitisation. |
|---------|-------------------------|

## Chronic toxicity

## Reproductive toxicity

**Components:**

**styrene:**

|                                    |  |
|------------------------------------|--|
| Reproductive toxicity - Assessment | : Some evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments. |
|------------------------------------|--|

**toluene:**

|                                    |  |
|------------------------------------|--|
| Reproductive toxicity - Assessment | : Some evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments. |
|------------------------------------|--|

## STOT - single exposure

### Components:

**styrene:**

Assessment : May cause respiratory irritation.

**toluene:**

**Assessment** : May cause drowsiness or dizziness.

### STOT - repeated exposure

### Components:

**styrene:**

Assessment : Causes damage to organs through prolonged or repeated exposure.

**MOBIHEL GLASSFIBRE PUTTY**

|         |                     |                       |                                 |
|---------|---------------------|-----------------------|---------------------------------|
| Version | Revision            | SDS Number:           | Date of last issue: -           |
| 1.0     | Date:<br>16.11.2023 | MAT0GA05_065<br>AU/EN | Date of first issue: 16.11.2023 |

---

**toluene:**

Assessment : May cause damage to organs through prolonged or repeated exposure.

**Aspiration toxicity****Components:****styrene:**

May be fatal if swallowed and enters airways.

**toluene:**

May be fatal if swallowed and enters airways.

**Further information****Product:**

Remarks : Solvents may degrease the skin.

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Components:****styrene:**

Toxicity to fish : LC50 (Fish):  $\geq 10 - 12$  mg/l

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)):  $\geq 4.7$  mg/l

**Ecotoxicology Assessment**

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

**toluene:****Ecotoxicology Assessment**

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

**Persistence and degradability****Components:****styrene:**

Biodegradability : aerobic  
Remarks: Readily biodegradable.

anaerobic  
Remarks: According to the results of tests of biodegradability

**MOBIHEL GLASSFIBRE PUTTY**

|         |                     |                       |                                 |
|---------|---------------------|-----------------------|---------------------------------|
| Version | Revision            | SDS Number:           | Date of last issue: -           |
| 1.0     | Date:<br>16.11.2023 | MAT0GA05_065<br>AU/EN | Date of first issue: 16.11.2023 |

---

this product is not readily biodegradable.

Physico-chemical removability : Remarks: The product evaporates readily.  
Readily biodegradable.

Stability in water : Remarks: Hydrolyses slowly.

Photodegradation : Remarks: Decomposes rapidly in contact with light.

**Bioaccumulative potential****Components:****styrene:**

Bioaccumulation : Remarks: Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water : log Pow: 2.95

**toluene:**

Partition coefficient: n-octanol/water : log Pow: 2.65

**Mobility in soil****Components:****styrene:**

Mobility : Medium: Air  
Content: 98.6 %  
  
Medium: Water  
Content: 1.21 %  
  
Medium: Sediment  
Content: 0.09 %  
  
Medium: Soil  
Content: 0.09 %

**Other adverse effects****Product:**

Additional ecological information : No data available

---

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Waste from residues : Do not dispose of waste into sewer.

**MOBIHEL GLASSFIBRE PUTTY**

|         |                     |                       |                                 |
|---------|---------------------|-----------------------|---------------------------------|
| Version | Revision            | SDS Number:           | Date of last issue: -           |
| 1.0     | Date:<br>16.11.2023 | MAT0GA05_065<br>AU/EN | Date of first issue: 16.11.2023 |

---

Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

---

**SECTION 14. TRANSPORT INFORMATION****International Regulations****UNRTDG**

UN number : UN 3269  
Proper shipping name : POLYESTER RESIN KIT  
Class : 3  
Packing group : III  
Labels : 3

**IATA-DGR**

UN/ID No. : UN 3269  
Proper shipping name : Polyester resin kit  
Class : 3  
Packing group : III  
Labels : Flammable Liquids  
Packing instruction (cargo aircraft) : 370  
Packing instruction (passenger aircraft) : 370

**IMDG-Code**

UN number : UN 3269  
Proper shipping name : POLYESTER RESIN KIT  
  
Class : 3  
Packing group : III  
Labels : 3  
EmS Code : F-E, S-D  
Marine pollutant : no

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**National Regulations****ADG**

UN number : UN 3269  
Proper shipping name : POLYESTER RESIN KIT  
Class : 3  
Packing group : III  
Labels : 3  
Hazchem Code : •2YE

**MOBIHEL GLASSFIBRE PUTTY**

|         |            |              |                                 |
|---------|------------|--------------|---------------------------------|
| Version | Revision   | SDS Number:  | Date of last issue: -           |
| 1.0     | Date:      | MAT0GA05_065 | Date of first issue: 16.11.2023 |
|         | 16.11.2023 | AU/EN        |                                 |

**Special precautions for user**

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

**SECTION 15. REGULATORY INFORMATION****Safety, health and environmental regulations/legislation specific for the substance or mixture**

Standard for the Uniform : Schedule 6  
Scheduling of Medicines and  
Poisons

Prohibition/Licensing Requirements : There is no applicable prohibition, authorisation and restricted use requirements, including for carcinogens referred to in Schedule 10 of the model WHS Act and Regulations.

**SECTION 16. OTHER INFORMATION**

Revision Date : 16.11.2023  
Date format : dd.mm.yyyy

**Full text of other abbreviations**

ACGIH : USA. ACGIH Threshold Limit Values (TLV)  
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)  
AU OEL : Australia. Workplace Exposure Standards for Airborne Contaminants.

ACGIH / TWA : 8-hour, time-weighted average  
ACGIH / STEL : Short-term exposure limit  
AU OEL / TWA : Exposure standard - time weighted average  
AU OEL / STEL : Exposure standard - short term exposure limit

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International

**MOBIHEL GLASSFIBRE PUTTY**

|         |            |              |                                 |
|---------|------------|--------------|---------------------------------|
| Version | Revision   | SDS Number:  | Date of last issue: -           |
| 1.0     | Date:      | MAT0GA05_065 | Date of first issue: 16.11.2023 |
|         | 16.11.2023 | AU/EN        |                                 |

---

Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

AU / EN