

**MOBIHEL 2:1 HS CLEARCOAT FastDry**

Version	Revision	SDS Number:	Date of last issue: -
1.0	Date: 16.11.2023	MAT000400931 AU/EN	Date of first issue: 16.11.2023

---

**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**



Product name : MOBIHEL 2:1 HS CLEARCOAT FastDry

Product code : 40093104

**Manufacturer or supplier's details****Details of the supplier of the safety data sheet**Company : Helios Coatings Australia Pty Ltd  
50 Clapham Road  
SEFTON NSW 2162  
AustraliaTelephone : 61 2 9645 3188  
E-mail address Responsible/issuing person : 61 2 9645 3188  
info@helioscoatings.com.au**Emergency telephone number**

112 (mobile) Ambulance 000, Poisons Information Centre: 131 126

---

**SECTION 2. HAZARDS IDENTIFICATION****GHS Classification**Flammable liquids : Category 3  
Skin sensitisation : Category 1  
Specific target organ toxicity - single exposure : Category 3 (Central nervous system)**GHS label elements**Hazard pictograms :  The hazard pictograms consist of two red diamond-shaped symbols. The first symbol contains a black flame, representing a flammable liquid. The second symbol contains a black exclamation mark, representing a health hazard.

Signal word : Warning

Hazard statements : H226 Flammable liquid and vapour.  
H317 May cause an allergic skin reaction.  
H336 May cause drowsiness or dizziness.Precautionary statements : **Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 Keep container tightly closed.  
P240 Ground and bond container and receiving equipment.  
P241 Use explosion-proof electrical/ ventilating/ lighting equip-

## MOBIHEL 2:1 HS CLEARCOAT FastDry

Version	Revision	SDS Number:	Date of last issue: -
1.0	Date: 16.11.2023	MAT000400931 AU/EN	Date of first issue: 16.11.2023

ment.  
P242 Use non-sparking tools.  
P243 Take action to prevent static discharges.  
P261 Avoid breathing mist or vapours.  
P271 Use only outdoors or in a well-ventilated area.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

**Response:**

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.  
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.  
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.  
P362 + P364 Take off contaminated clothing and wash it before reuse.  
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

**Storage:**

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
P403 + P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

**Other hazards which do not result in classification**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

**Components**

Chemical name	CAS-No.	Concentration (% w/w)
n-butyl acetate	123-86-4	>= 20 -< 30
heptan-2-one	110-43-0	>= 10 -< 20
isobutyl acetate	110-19-0	< 10
mixture of benzotriazole	104810-48-2	< 1
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	1065336-91-5	< 1
glycol dimercaptopropionate	22504-50-3	>= 0.1 -< 10
dibutyltin dilaurate	77-58-7	< 0.3

**MOBIHEL 2:1 HS CLEARCOAT FastDry**

Version	Revision	SDS Number:	Date of last issue: -
1.0	Date: 16.11.2023	MAT000400931 AU/EN	Date of first issue: 16.11.2023

---

**SECTION 4. FIRST AID MEASURES**

- General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.  
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Flush eyes with water as a precaution.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.
- Most important symptoms and effects, both acute and delayed : May cause an allergic skin reaction.  
May cause drowsiness or dizziness.
- Notes to physician : Treat symptomatically.  
  
Treat symptomatically.
- 

**SECTION 5. FIREFIGHTING MEASURES**

- Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : No hazardous combustion products are known
- Specific extinguishing methods : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored sepa-
-

## MOBIHEL 2:1 HS CLEARCOAT FastDry

Version	Revision	SDS Number:	Date of last issue: -
1.0	Date: 16.11.2023	MAT000400931 AU/EN	Date of first issue: 16.11.2023

rately in closed containments.  
Use a water spray to cool fully closed containers.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Hazchem Code : •3Y

---

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

---

**SECTION 7. HANDLING AND STORAGE**

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).  
Keep away from open flames, hot surfaces and sources of ignition.

Advice on safe handling : Avoid formation of aerosol.  
Do not breathe vapours/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Open drum carefully as content may be under pressure.  
Dispose of rinse water in accordance with local and national regulations.  
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Hygiene measures : When using do not eat or drink.  
When using do not smoke.

## MOBIHEL 2:1 HS CLEARCOAT FastDry

Version	Revision	SDS Number:	Date of last issue: -
1.0	Date:	MAT000400931	Date of first issue: 16.11.2023
	16.11.2023	AU/EN	

Wash hands before breaks and at the end of workday.

Conditions for safe storage : No smoking.  
 Keep container tightly closed in a dry and well-ventilated place.  
 Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
 Observe label precautions.  
 Electrical installations / working materials must comply with the technological safety standards.

Further information on storage stability : No decomposition if stored and applied as directed.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis	
n-butyl acetate	123-86-4	STEL	200 ppm 950 mg/m <sup>3</sup>	AU OEL	
		TWA	150 ppm 713 mg/m <sup>3</sup>	AU OEL	
		TWA	50 ppm	ACGIH	
		STEL	150 ppm	ACGIH	
heptan-2-one	110-43-0	TWA	50 ppm 233 mg/m <sup>3</sup>	AU OEL	
		TWA	50 ppm	ACGIH	
isobutyl acetate	110-19-0	TWA	150 ppm 713 mg/m <sup>3</sup>	AU OEL	
		TWA	50 ppm	ACGIH	
		STEL	150 ppm	ACGIH	
dibutyltin dilaurate	77-58-7	TWA	0.1 mg/m <sup>3</sup> (Tin)	AU OEL	
		Further information: Skin absorption			
		STEL	0.2 mg/m <sup>3</sup> (Tin)	AU OEL	
		Further information: Skin absorption			
		TWA	0.1 mg/m <sup>3</sup> (Tin)	ACGIH	
		STEL	0.2 mg/m <sup>3</sup> (Tin)	ACGIH	

## Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Organic vapour type

Hand protection

## MOBIHEL 2:1 HS CLEARCOAT FastDry

Version	Revision	SDS Number:	Date of last issue: -
1.0	Date: 16.11.2023	MAT000400931 AU/EN	Date of first issue: 16.11.2023

---

Gloves	:	<table border="0"> <tr> <td> </td> <td>Nitrile rubber (&gt; 0,1 mm; &lt; 60 min); DIN EN374</td> <td> </td> </tr> <tr> <td> </td> <td>butyl-rubber (&gt; 0,6 mm; &lt; 240 min); DIN EN374</td> <td> </td> </tr> <tr> <td> </td> <td>Viton® (&gt; 0,6 mm; &lt; 240 min); DIN EN374</td> <td> </td> </tr> <tr> <td> </td> <td>PE laminate (&gt; 0,1 mm; &lt; 240 min); DIN EN374</td> <td> </td> </tr> </table>		Nitrile rubber (> 0,1 mm; < 60 min); DIN EN374			butyl-rubber (> 0,6 mm; < 240 min); DIN EN374			Viton® (> 0,6 mm; < 240 min); DIN EN374			PE laminate (> 0,1 mm; < 240 min); DIN EN374	
	Nitrile rubber (> 0,1 mm; < 60 min); DIN EN374													
	butyl-rubber (> 0,6 mm; < 240 min); DIN EN374													
	Viton® (> 0,6 mm; < 240 min); DIN EN374													
	PE laminate (> 0,1 mm; < 240 min); DIN EN374													
Remarks	:	<p>The suitability for a specific workplace should be discussed with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.</p>												
Eye protection	:	<p>Equipment should conform to EN 166 Eye wash bottle with pure water Tightly fitting safety goggles</p>												
Skin and body protection	:	<p>Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.</p>												

---

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance	:	liquid
Colour	:	colourless
Odour	:	solvent-like
Odour Threshold	:	No data available
pH	:	Not applicable
Melting point/freezing point	:	-98.8 °C (calculation method (principal components, lowest value))
Boiling point/boiling range	:	117 °C (calculation method (principal components, lowest value))
Flash point	:	25 °C  Method: ISO 3679, closed cup
Flammability (solid, gas)	:	Static-accumulating flammable liquid., Combustible Solids
Upper explosion limit / Upper flammability limit	:	10.5 %(V)

## MOBIHEL 2:1 HS CLEARCOAT FastDry

Version	Revision	SDS Number:	Date of last issue: -
1.0	Date: 16.11.2023	MAT000400931 AU/EN	Date of first issue: 16.11.2023

---

Lower explosion limit / Lower flammability limit	:	1.2 %(V)
Relative vapour density	:	No data available
Relative density	:	No data available
Density	:	0.979 g/cm <sup>3</sup>
Solubility(ies)	:	
Water solubility	:	partly miscible
Solubility in other solvents	:	Description: miscible with most organic solvents
Partition coefficient: n-octanol/water	:	log Pow: 1.98
Auto-ignition temperature	:	393 °C
Decomposition temperature	:	No decomposition if stored and applied as directed. Hazardous decomposition products formed under fire conditions.
Viscosity	:	
Viscosity, kinematic	:	> 20.5 mm <sup>2</sup> /s ( 40 °C)
Flow time	:	18 - 23 s (20 °C) Cross section: 4 mm Method: DIN 53211
Explosive properties	:	Not applicable
Oxidizing properties	:	Sustains combustion
VOC	:	(Directive 2004/42/EC) 420 g/l

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	No decomposition if stored and applied as directed. Vapours may form explosive mixture with air.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Incompatible with strong acids and bases.
Hazardous decomposition products	:	Adequate ventilation is required. Heating can release vapours which can be ignited. Carbon monoxide, carbon dioxide and unburned hydrocar-

## MOBIHEL 2:1 HS CLEARCOAT FastDry

Version	Revision	SDS Number:	Date of last issue: -
1.0	Date: 16.11.2023	MAT000400931 AU/EN	Date of first issue: 16.11.2023

bons (smoke).

**SECTION 11. TOXICOLOGICAL INFORMATION****Acute toxicity**

Not classified based on available information.

**Product:**

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg  
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method

**Components:****n-butyl acetate:**

Acute oral toxicity : LD50 Oral (Rat):  $\geq$  10,760 mg/kg

Acute dermal toxicity : LD50 (Rabbit):  $\geq$  5,000 mg/kg

**heptan-2-one:**

Acute oral toxicity : Assessment: The component/mixture is moderately toxic after single ingestion.

Acute inhalation toxicity : Test atmosphere: vapour  
Assessment: The component/mixture is moderately toxic after short term inhalation.

**ethylene bis(3-mercaptopropionate):**

Acute oral toxicity : LD50 Oral (Rat): 668 mg/kg

Acute dermal toxicity : LD50 Dermal (Rat): 2,000 mg/kg

**Skin corrosion/irritation**

Not classified based on available information.

**Product:**

Remarks : May cause skin irritation and/or dermatitis.

**Serious eye damage/eye irritation**

Not classified based on available information.

**Product:**

Remarks : Vapours may cause irritation to the eyes, respiratory system and the skin.



MOBIHEL 2:1 HS CLEARCOAT FastDry

Version	Revision	SDS Number:	Date of last issue: -
1.0	Date:	MAT000400931	Date of first issue: 16.11.2023
	16.11.2023	AU/EN	

---

**Components:**

**ethylene bis(3-mercaptopropionate):**

Result : Eye irritation

**dibutyltin dilaurate:**

Result : Eye irritation

**Respiratory or skin sensitisation**

**Skin sensitisation**

May cause an allergic skin reaction.

**Respiratory sensitisation**

Not classified based on available information.

**Product:**

Remarks : Causes sensitisation.

**Components:**

**mixture of benzotriazole:**

Result : Probability or evidence of skin sensitisation in humans

**mixture of sterically composed sebacates:**

Result : May cause sensitisation by skin contact.

**ethylene bis(3-mercaptopropionate):**

Result : The product is a skin sensitiser, sub-category 1A.

**dibutyltin dilaurate:**

Result : Probability or evidence of skin sensitisation in humans

**Chronic toxicity**

**Germ cell mutagenicity**

Not classified based on available information.

**Components:**

**dibutyltin dilaurate:**

Germ cell mutagenicity - Assessment : In vitro tests showed mutagenic effects

**Carcinogenicity**

Not classified based on available information.

**Reproductive toxicity**

Not classified based on available information.

## MOBIHEL 2:1 HS CLEARCOAT FastDry

Version	Revision	SDS Number:	Date of last issue: -
1.0	Date: 16.11.2023	MAT000400931 AU/EN	Date of first issue: 16.11.2023

---

**Components:****mixture of sterically composed sebacates:**

Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility, based on animal experiments.

**dibutyltin dilaurate:**

Reproductive toxicity - Assessment : Clear evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments

**STOT - single exposure**

May cause drowsiness or dizziness.

**Components:****n-butyl acetate:**

Assessment : May cause drowsiness or dizziness.

**heptan-2-one:**

Assessment : May cause drowsiness or dizziness.

**isobutyl acetate:**

Assessment : May cause drowsiness or dizziness.

**dibutyltin dilaurate:**

Assessment : Causes damage to organs.

**STOT - repeated exposure**

Not classified based on available information.

**Components:****dibutyltin dilaurate:**

Assessment : Causes damage to organs through prolonged or repeated exposure.

**Aspiration toxicity**

Not classified based on available information.

**Further information****Product:**

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.  
Concentrations substantially above the TLV value may cause narcotic effects.  
Solvents may degrease the skin.

## MOBIHEL 2:1 HS CLEARCOAT FastDry

Version	Revision	SDS Number:	Date of last issue: -
1.0	Date: 16.11.2023	MAT000400931 AU/EN	Date of first issue: 16.11.2023

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Components:****n-butyl acetate:**

Toxicity to algae/aquatic plants : NOEC (Desmodesmus subspicatus (green algae)): > 200 mg/l

EC50 (Desmodesmus subspicatus (green algae)): >= 647.7 mg/l  
Exposure time: 72 h

Toxicity to microorganisms : IC50 (Tetrahymena pyriformis): 356 mg/l  
Exposure time: 40 h

**mixture of benzotriazole:****Ecotoxicology Assessment**

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

**mixture of sterically composed sebacates:****Ecotoxicology Assessment**

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

**ethylene bis(3-mercaptopropionate):****Ecotoxicology Assessment**

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

**dibutyltin dilaurate:****Ecotoxicology Assessment**

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

**Persistence and degradability****Components:****n-butyl acetate:**

Biodegradability : Result: Biodegradable  
Biodegradation: 83 %  
Exposure time: 28 d

## MOBIHEL 2:1 HS CLEARCOAT FastDry

Version	Revision	SDS Number:	Date of last issue: -
1.0	Date: 16.11.2023	MAT000400931 AU/EN	Date of first issue: 16.11.2023

---

Method: OECD Test Guideline 301D

Stability in water : Degradation half life: 78 d pH: 8  
Remarks: Hydrolyses slowly.

Photodegradation : Remarks: Decomposes rapidly in contact with light.

**Bioaccumulative potential****Components:****n-butyl acetate:**Bioaccumulation : Bioconcentration factor (BCF): 15  
Remarks: Bioaccumulation is unlikely.Partition coefficient: n-  
octanol/water : log Pow: 1.81**heptan-2-one:**Partition coefficient: n-  
octanol/water : log Pow: 1.98**isobutyl acetate:**Partition coefficient: n-  
octanol/water : log Pow: 1.72**mixture of sterically composed sebacates:**Partition coefficient: n-  
octanol/water : log Pow: 2.37 - 2.77  
pH: 7**Mobility in soil**

No data available

**Other adverse effects****Product:**Additional ecological infor-  
mation : An environmental hazard cannot be excluded in the event of  
unprofessional handling or disposal.  
Harmful to aquatic life with long lasting effects.

---

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**Waste from residues : The product should not be allowed to enter drains, water  
courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemi-  
cal or used container.  
Send to a licensed waste management company.

## MOBIHEL 2:1 HS CLEARCOAT FastDry

Version	Revision	SDS Number:	Date of last issue: -
1.0	Date: 16.11.2023	MAT000400931 AU/EN	Date of first issue: 16.11.2023

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

**SECTION 14. TRANSPORT INFORMATION****International Regulations****UNRTDG**

UN number : UN 1263  
Proper shipping name : PAINT  
Class : 3  
Packing group : III  
Labels : 3

**IATA-DGR**

UN/ID No. : UN 1263  
Proper shipping name : Paint  
Class : 3  
Packing group : III  
Labels : Flammable Liquids  
Packing instruction (cargo aircraft) : 366  
Packing instruction (passenger aircraft) : 355

**IMDG-Code**

UN number : UN 1263  
Proper shipping name : PAINT  
  
Class : 3  
Packing group : III  
Labels : 3  
EmS Code : F-E, S-E  
Marine pollutant : no

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**National Regulations****ADG**

UN number : UN 1263  
Proper shipping name : PAINT  
Class : 3  
Packing group : III  
Labels : 3  
Hazchem Code : •3Y

**Special precautions for user**

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## MOBIHEL 2:1 HS CLEARCOAT FastDry

Version	Revision	SDS Number:	Date of last issue: -
1.0	Date:	MAT000400931	Date of first issue: 16.11.2023
	16.11.2023	AU/EN	

## SECTION 15. REGULATORY INFORMATION

**Safety, health and environmental regulations/legislation specific for the substance or mixture**

Standard for the Uniform : Schedule 7  
Scheduling of Medicines and  
Poisons

Prohibition/Licensing Requirements : dibutyltin dilaurate  
Refer to model WHS Act and Regulations for prohibition, authorisation and restricted use.

## SECTION 16. OTHER INFORMATION

Revision Date : 16.11.2023

Date format : dd.mm.yyyy

**Full text of other abbreviations**

ACGIH : USA. ACGIH Threshold Limit Values (TLV)  
AU OEL : Australia. Workplace Exposure Standards for Airborne Contaminants.

ACGIH / TWA : 8-hour, time-weighted average  
ACGIH / STEL : Short-term exposure limit  
AU OEL / TWA : Exposure standard - time weighted average  
AU OEL / STEL : Exposure standard - short term exposure limit

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECl - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Develop-

## MOBIHEL 2:1 HS CLEARCOAT FastDry

Version	Revision	SDS Number:	Date of last issue: -
1.0	Date:	MAT000400931	Date of first issue: 16.11.2023
	16.11.2023	AU/EN	

---

ment; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

AU / EN