

## MOBIHEL 3:1 HS FILLER W/W

Version	Revision Date:	SDS Number:	Date of last issue: 16.11.2023
1.1	22.05.2024	MAT000478435 AU/EN	Date of first issue: 16.11.2023

**SECTION 1: IDENTIFICATION**

Product name : MOBIHEL 3:1 HS FILLER W/W

Product code : 47843502

**Manufacturer or supplier's details****Details of the supplier of the safety data sheet**Company : Helios Coatings Australia Pty Ltd  
50 Clapham Road  
SEFTON NSW 2162  
AustraliaTelephone : 61 2 9645 3188  
E-mail address Responsible/issuing person : 61 2 9645 3188  
info@helioscoatings.com.au**Emergency telephone number**

112 (mobile) Ambulance 000, Poisons Information Centre: 131 126

**SECTION 2. HAZARDS IDENTIFICATION****GHS Classification**

Flammable liquids : Category 3

Skin corrosion/irritation : Category 2

Serious eye damage/eye irritation : Category 2A

Specific target organ toxicity - single exposure : Category 3 (Respiratory system, Central nervous system)

Specific target organ toxicity - repeated exposure : Category 2

**GHS label elements**Hazard pictograms : 

Signal word : Warning

Hazard statements : H226 Flammable liquid and vapour.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H373 May cause damage to organs through prolonged or re-

**MOBIHEL 3:1 HS FILLER W/W**Version  
1.1Revision Date:  
22.05.2024SDS Number:  
MAT000478435  
AU/ENDate of last issue: 16.11.2023  
Date of first issue: 16.11.2023

peated exposure.

## Precautionary statements

:

**Prevention:**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P260 Do not breathe mist or vapours.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

**Response:**

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P314 Get medical advice/ attention if you feel unwell.

P332 + P313 If skin irritation occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

**Storage:**

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

**Other hazards which do not result in classification**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture

: Mixture

**MOBIHEL 3:1 HS FILLER W/W**

Date of last issue: 16.11.2023  
Date of first issue: 16.11.2023

Chemical name	CAS-No.	Concentration (% w/w)
calcium carbonate	471-34-1	>= 10 -< 30
titanium dioxide	13463-67-7	>= 10 -< 30
reaction mixture of ethylbenzene, m-xylene and p-xylene	1330-20-7	>= 10 -< 20
Hydrocarbons, C9 aromatics	128601-23-0	>= 1 -< 10
n-butyl acetate	123-86-4	< 10
2-methoxy-1-methylethyl acetate	108-65-6	< 10
solvent naphtha (petroleum), light aromatic	64742-95-6	>= 1 -< 10
2-butanone	78-93-3	< 10
pentane-2,4-dione	123-54-6	< 10
dibutyltin dilaurate	77-58-7	< 0.3
Hexanoic acid, 2-ethyl-, zinc salt, basic	85203-81-2	< 3
hydrocarbons, terpene processing by-products	68956-56-9	< 1
2-diethylaminoethanol	100-37-8	< 1

General advice	: Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.
If inhaled	: Consult a physician after significant exposure. If unconscious, place in recovery position and seek medical advice.
In case of skin contact	: If skin irritation persists, call a physician. If on skin, rinse well with water. If on clothes, remove clothes.
In case of eye contact	: Immediately flush eye(s) with plenty of water. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	: Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.
Most important symptoms and effects, both acute and delayed	: None known.
Notes to physician	: Treat symptomatically.

Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO2)

**MOBIHEL 3:1 HS FILLER W/W**

Version	Revision Date:	SDS Number:	Date of last issue: 16.11.2023
1.1	22.05.2024	MAT000478435	Date of first issue: 16.11.2023
		AU/EN	

Dry chemical

- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : No hazardous combustion products are known
- Specific extinguishing methods : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
- Hazchem Code : •3Y

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

**SECTION 7. HANDLING AND STORAGE**

- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).  
Keep away from open flames, hot surfaces and sources of ignition.
- Advice on safe handling : Avoid formation of aerosol.  
Do not breathe vapours/dust.  
Avoid exposure - obtain special instructions before use.

**MOBIHEL 3:1 HS FILLER W/W**Version  
1.1Revision Date:  
22.05.2024SDS Number:  
MAT000478435  
AU/ENDate of last issue: 16.11.2023  
Date of first issue: 16.11.2023

Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Open drum carefully as content may be under pressure.  
Dispose of rinse water in accordance with local and national regulations.  
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

- Hygiene measures : When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.
- Conditions for safe storage : No smoking.  
Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage stability : No decomposition if stored and applied as directed.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION****Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Calcium carbonate	471-34-1	TWA	10 mg/m <sup>3</sup> (Calcium carbonate)	AU OEL
titanium dioxide	13463-67-7	TWA	10 mg/m <sup>3</sup>	AU OEL
		TWA (Respirable particulate matter)	0.2 mg/m <sup>3</sup> (Titanium dioxide)	ACGIH
		TWA (Respirable particulate matter)	2.5 mg/m <sup>3</sup> (Titanium dioxide)	ACGIH
reaction mixture of ethylbenzene, m-xylene and p-xylene	1330-20-7	STEL	150 ppm 655 mg/m <sup>3</sup>	AU OEL
		TWA	80 ppm 350 mg/m <sup>3</sup>	AU OEL

## SAFETY DATA SHEET



## MOBIHEL 3:1 HS FILLER W/W

Version  
1.1Revision Date:  
22.05.2024SDS Number:  
MAT000478435  
AU/ENDate of last issue: 16.11.2023  
Date of first issue: 16.11.2023

		TWA	20 ppm	ACGIH
n-butyl acetate	123-86-4	STEL	200 ppm 950 mg/m <sup>3</sup>	AU OEL
		TWA	150 ppm 713 mg/m <sup>3</sup>	AU OEL
		TWA	50 ppm	ACGIH
		STEL	150 ppm	ACGIH
2-methoxy-1-methylethyl acetate	108-65-6	TWA	50 ppm 274 mg/m <sup>3</sup>	AU OEL
Further information: Skin absorption				
		STEL	100 ppm 548 mg/m <sup>3</sup>	AU OEL
Further information: Skin absorption				
Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified	64742-95-6	TWA	900 mg/m <sup>3</sup>	AU OEL
butanone	78-93-3	STEL	300 ppm 890 mg/m <sup>3</sup>	AU OEL
		TWA	150 ppm 445 mg/m <sup>3</sup>	AU OEL
		TWA	200 ppm	ACGIH
		STEL	300 ppm	ACGIH
pentane-2,4-dione	123-54-6	TWA	25 ppm	ACGIH
dibutyltin dilaurate	77-58-7	TWA	0.1 mg/m <sup>3</sup> (Tin)	AU OEL
Further information: Skin absorption				
		STEL	0.2 mg/m <sup>3</sup> (Tin)	AU OEL
Further information: Skin absorption				
		TWA	0.1 mg/m <sup>3</sup> (Tin)	ACGIH
		STEL	0.2 mg/m <sup>3</sup> (Tin)	ACGIH
2-diethylaminoethanol	100-37-8	TWA	10 ppm 48 mg/m <sup>3</sup>	AU OEL
Further information: Skin absorption				
		TWA	2 ppm	ACGIH

## Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
reaction mixture of ethylbenzene, m-xylene and p-xylene	1330-20-7	Methylhippuric acids	Urine	End of shift (As soon as possible after exposure ceases)	1.5 g/g creatinine	ACGIH BEI
butanone	78-93-3	methyl ethyl ketone	Urine	End of shift (As soon as possible)	2 mg/l	ACGIH BEI

**MOBIHEL 3:1 HS FILLER W/W**Version  
1.1Revision Date:  
22.05.2024SDS Number:  
MAT000478435  
AU/ENDate of last issue: 16.11.2023  
Date of first issue: 16.11.2023

				after exposure ceases)		
--	--	--	--	------------------------------	--	--

**Personal protective equipment**

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Combined particulates and organic vapour type

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.  
Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

Eye protection : Equipment should conform to EN 166  
Eye wash bottle with pure water  
Tightly fitting safety goggles  
Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection : Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid

Colour : grey

Odour : solvent-like

Odour Threshold : No data available

pH : Not applicable

Melting point/freezing point : -78.0 °C  
(calculation method (principal components, lowest value))

Boiling point/boiling range : 126 °C  
(calculation method (principal components, lowest value))

**MOBIHEL 3:1 HS FILLER W/W**

Version	Revision Date:	SDS Number:	Date of last issue: 16.11.2023
1.1	22.05.2024	MAT000478435 AU/EN	Date of first issue: 16.11.2023

---

Flash point	:	29 °C
		Method: ISO 3679, closed cup
Flammability (solid, gas)	:	Static-accumulating flammable liquid., Combustible Solids
Upper explosion limit / Upper flammability limit	:	7.5 %(V)
Lower explosion limit / Lower flammability limit	:	1.0 %(V)
Relative vapour density	:	No data available
Relative density	:	No data available
Density	:	1.398 g/cm3
Solubility(ies)	:	
Water solubility	:	immiscible, partly soluble
Solubility in other solvents	:	Description: miscible with most organic solvents
Partition coefficient: n-octanol/water	:	log Pow: < 4
Auto-ignition temperature	:	425 °C
Decomposition temperature	:	No decomposition if stored and applied as directed. Hazardous decomposition products formed under fire conditions.
Viscosity	:	
Viscosity, kinematic	:	> 20.5 mm2/s ( 40 °C)
Explosive properties	:	Not applicable
Oxidizing properties	:	Sustains combustion
VOC	:	(Directive 2004/42/EC) 540 g/l

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	No decomposition if stored and applied as directed. Vapours may form explosive mixture with air.
Conditions to avoid	:	Heat, flames and sparks.



**MOBIHEL 3:1 HS FILLER W/W**

Version	Revision Date:	SDS Number:	Date of last issue: 16.11.2023
1.1	22.05.2024	MAT000478435 AU/EN	Date of first issue: 16.11.2023

Incompatible materials	:	Incompatible with strong acids and bases.
Hazardous decomposition products	:	No hazardous decomposition products are known.

**SECTION 11. TOXICOLOGICAL INFORMATION****Acute toxicity****Product:**

Acute oral toxicity	:	Acute toxicity estimate: > 2,000 mg/kg Method: Calculation method
Acute inhalation toxicity	:	Acute toxicity estimate: > 20 mg/l Exposure time: 4 h Test atmosphere: vapour Method: Calculation method
Acute dermal toxicity	:	Acute toxicity estimate: > 2,000 mg/kg Method: Calculation method

**Components:****reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Acute oral toxicity	:	LD50 Oral (Rat): $\geq$ 8,700 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): 27.14 mg/l Test atmosphere: vapour
Acute dermal toxicity	:	Assessment: The component/mixture is moderately toxic after single contact with skin.

**Hydrocarbons, C9 aromatics:**

Acute dermal toxicity	:	LD50 (Rabbit): > 3,160 mg/kg
-----------------------	---	------------------------------

**n-butyl acetate:**

Acute oral toxicity	:	LD50 Oral (Rat): $\geq$ 10,760 mg/kg
Acute dermal toxicity	:	LD50 (Rabbit): $\geq$ 5,000 mg/kg

**2-methoxy-1-methylethyl acetate:**

Acute oral toxicity	:	LD50 Oral (Rat): > > 2,000 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): > 5 mg/l Test atmosphere: vapour  LC0 (Rat): 2000 ppm Exposure time: 3 h
Acute dermal toxicity	:	LD50 (Rabbit): > > 2,000 mg/kg

**MOBIHEL 3:1 HS FILLER W/W**Version  
1.1Revision Date:  
22.05.2024SDS Number:  
MAT000478435  
AU/ENDate of last issue: 16.11.2023  
Date of first issue: 16.11.2023**Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Acute oral toxicity : LD50 Oral (Rat): &gt; 2,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l  
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): &gt; 2,000 mg/kg

**butanone:**

Acute oral toxicity : LD50 Oral (Rat): &gt; &gt; 2,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l  
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): &gt; &gt; 2,000 mg/kg

**pentane-2,4-dione:**

Acute oral toxicity : Assessment: The component/mixture is moderately toxic after single ingestion.

Acute inhalation toxicity : Test atmosphere: vapour  
Assessment: The component/mixture is toxic after short term inhalation.

Acute dermal toxicity : Assessment: The component/mixture is toxic after single contact with skin.

**2-diethylaminoethanol:**

Acute oral toxicity : Assessment: The component/mixture is moderately toxic after single ingestion.

Acute inhalation toxicity : Test atmosphere: vapour  
Assessment: The component/mixture is toxic after short term inhalation.

Acute dermal toxicity : Assessment: The component/mixture is toxic after single contact with skin.

**Skin corrosion/irritation****Product:**

Remarks : May cause skin irritation and/or dermatitis.

**Components:****reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Result : irritating

**Hydrocarbons, terpene processing by-products:**

Result : irritating

**MOBIHEL 3:1 HS FILLER W/W**Version  
1.1Revision Date:  
22.05.2024SDS Number:  
MAT000478435  
AU/ENDate of last issue: 16.11.2023  
Date of first issue: 16.11.2023

---

**2-diethylaminoethanol:**

Result : Corrosive after 3 minutes to 1 hour of exposure

**Serious eye damage/eye irritation****Product:**

Remarks : May cause irreversible eye damage.

**Components:****reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Result : Eye irritation

**butanone:**

Result : Eye irritation

**dibutyltin dilaurate:**

Result : Eye irritation

**Hexanoic acid, 2-ethyl-, zinc salt, basic:**

Result : Eye irritation

**Hydrocarbons, terpene processing by-products:**

Result : Eye irritation

**Respiratory or skin sensitisation****Product:**

Remarks : Causes sensitisation.

**Components:****dibutyltin dilaurate:**

Result : Probability or evidence of skin sensitisation in humans

**Hydrocarbons, terpene processing by-products:**

Result : Probability or evidence of skin sensitisation in humans

**Chronic toxicity****Germ cell mutagenicity****Components:****Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Germ cell mutagenicity - : Classified based on benzene content &lt; 0.1% (Regulation (EC))

**MOBIHEL 3:1 HS FILLER W/W**

Version	Revision Date:	SDS Number:	Date of last issue: 16.11.2023
1.1	22.05.2024	MAT000478435 AU/EN	Date of first issue: 16.11.2023

Assessment 1272/2008, Annex VI, Part 3, Note P)

**dibutyltin dilaurate:**

Germ cell mutagenicity - Assessment : In vitro tests showed mutagenic effects

**Carcinogenicity****Components:****Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Carcinogenicity - Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

**Reproductive toxicity****Components:****dibutyltin dilaurate:**

Reproductive toxicity - Assessment : Clear evidence of adverse effects on sexual function and fertility ,and/or on development, based on animal experiments

**Hexanoic acid, 2-ethyl-, zinc salt, basic:**

Reproductive toxicity - Assessment : Some evidence of adverse effects on development, based on animal experiments.

**STOT - single exposure****Components:****reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Assessment : May cause respiratory irritation.

**Hydrocarbons, C9 aromatics:**

Assessment : May cause drowsiness or dizziness.

Assessment : May cause respiratory irritation.

**n-butyl acetate:**

Assessment : May cause drowsiness or dizziness.

**2-methoxy-1-methylethyl acetate:**

Assessment : May cause drowsiness or dizziness.

**Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Assessment : May cause drowsiness or dizziness.

Assessment : May cause respiratory irritation.

**MOBIHEL 3:1 HS FILLER W/W**Version  
1.1Revision Date:  
22.05.2024SDS Number:  
MAT000478435  
AU/ENDate of last issue: 16.11.2023  
Date of first issue: 16.11.2023**butanone:**

Assessment : May cause drowsiness or dizziness.

**dibutyltin dilaurate:**

Assessment : Causes damage to organs.

**STOT - repeated exposure****Components:****reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Assessment : May cause damage to organs through prolonged or repeated exposure.

**dibutyltin dilaurate:**

Assessment : Causes damage to organs through prolonged or repeated exposure.

**Aspiration toxicity****Components:****reaction mixture of ethylbenzene, m-xylene and p-xylene:**

May be fatal if swallowed and enters airways.

**Hydrocarbons, C9 aromatics:**

May be fatal if swallowed and enters airways.

**Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

May be fatal if swallowed and enters airways.

**Hydrocarbons, terpene processing by-products:**

May be fatal if swallowed and enters airways.

**Further information****Product:**

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.  
Concentrations substantially above the TLV value may cause narcotic effects.  
Solvents may degrease the skin.

**MOBIHEL 3:1 HS FILLER W/W**

Version	Revision Date:	SDS Number:	Date of last issue: 16.11.2023
1.1	22.05.2024	MAT000478435 AU/EN	Date of first issue: 16.11.2023

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Components:****reaction mixture of ethylbenzene, m-xylene and p-xylene:**Toxicity to fish : LC50 (Fish):  $\geq 1 - 10$  mg/lToxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)):  $\geq 1 - 10$  mg/lToxicity to microorganisms : EC50 (Bacteria):  $\geq 1 - 100$  mg/l**Hydrocarbons, C9 aromatics:**Toxicity to fish : LC50 (Fish):  $\geq 9.2$  mg/l  
Exposure time: 96 hToxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)):  $\geq 3.2$  mg/l  
Exposure time: 48 h**Ecotoxicology Assessment**

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

**n-butyl acetate:**Toxicity to algae/aquatic plants : NOEC (Desmodesmus subspicatus (green algae)):  $> 200$  mg/lEC50 (Desmodesmus subspicatus (green algae)):  $\geq 647.7$  mg/l  
Exposure time: 72 hToxicity to microorganisms : IC50 (Tetrahymena pyriformis): 356 mg/l  
Exposure time: 40 h**2-methoxy-1-methylethyl acetate:**Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 130 mg/l  
Exposure time: 96 hNOEC : 100 mg/l  
Exposure time: 96 hToxicity to daphnia and other aquatic invertebrates : LC50: 408 mg/l  
Exposure time: 48 h

Toxicity to fish (Chronic toxicity) : EC10: 47.5 mg/l

**Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**Toxicity to fish : LC50 (Fish):  $> 1 - 10$  mg/l

**MOBIHEL 3:1 HS FILLER W/W**

Version	Revision Date:	SDS Number:	Date of last issue: 16.11.2023
1.1	22.05.2024	MAT000478435	Date of first issue: 16.11.2023
		AU/EN	

---

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)): > 1 - 10 mg/l

Toxicity to microorganisms : EC50 (Bacteria): > 1 - 10 mg/l

**Ecotoxicology Assessment**

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

**butanone:**

Toxicity to fish : LC50 (Fish): > 1,000 mg/l

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)): > 1,000 mg/l

Toxicity to microorganisms : EC50 (Bacteria): > 1,000 mg/l

**dibutyltin dilaurate:****Ecotoxicology Assessment**

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

**Hexanoic acid, 2-ethyl-, zinc salt, basic:****Ecotoxicology Assessment**

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

**Hydrocarbons, terpene processing by-products:****Ecotoxicology Assessment**

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

**2-diethylaminoethanol:**

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): 147 mg/l  
Exposure time: 96 h  
Method: DIN 38412

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 165 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Scenedesmus subspicatus): 62.3 mg/l  
Exposure time: 72 h  
Test Type: Growth inhibition

**Ecotoxicology Assessment**

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

**MOBIHEL 3:1 HS FILLER W/W**

Version            Revision Date:        SDS Number:  
1.1                22.05.2024            MAT000478435  
   AU/EN

Date of last issue: 16.11.2023  
Date of first issue: 16.11.2023

**Persistence and degradability****Components:****reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Biodegradability                                :    Remarks: Readily biodegradable.

Photodegradation                               :    Remarks: Decomposes rapidly in contact with light.

**n-butyl acetate:**

Biodegradability                               :    Result: Biodegradable  
   Biodegradation: 83 %  
   Exposure time: 28 d  
   Method: OECD Test Guideline 301D

Stability in water                               :    Degradation half life: 78 d pH: 8  
   Remarks: Hydrolyses slowly.

Photodegradation                               :    Remarks: Decomposes rapidly in contact with light.

**2-methoxy-1-methylethyl acetate:**

Biodegradability                               :    Remarks: Readily biodegradable.

**Bioaccumulative potential****Components:****reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Bioaccumulation                               :    Bioconcentration factor (BCF): 25.9  
   Remarks: Bioaccumulation is unlikely.

Partition coefficient: n-                        :    log Pow: 2.77 - 3.15  
octanol/water

**Hydrocarbons, C9 aromatics:**

Partition coefficient: n-                        :    log Pow: < 4  
octanol/water

**n-butyl acetate:**

Bioaccumulation                               :    Bioconcentration factor (BCF): 15  
   Remarks: Bioaccumulation is unlikely.

Partition coefficient: n-                        :    log Pow: 1.81  
octanol/water

**2-methoxy-1-methylethyl acetate:**

Partition coefficient: n-                        :    log Pow: 1.2 (20 °C)  
octanol/water     pH: 6.8

**butanone:**



**MOBIHEL 3:1 HS FILLER W/W**

Version	Revision Date:	SDS Number:	Date of last issue: 16.11.2023
1.1	22.05.2024	MAT000478435 AU/EN	Date of first issue: 16.11.2023

Partition coefficient: n-octanol/water : log Pow: 0.29

**pentane-2,4-dione:**

Partition coefficient: n-octanol/water : log Pow: 0.34

**2-diethylaminoethanol:**

Partition coefficient: n-octanol/water : log Pow: 0.21

**Mobility in soil****Components:****reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Distribution among environmental compartments : Koc: 537, log Koc: 2.73  
Remarks: Moderately mobile in soils  
The product evaporates from soil.

Stability in soil : Dissipation time: 23 d  
Percentage dissipation: 50 % (DT50)

**Hydrocarbons, C9 aromatics:**

Mobility : Medium: Air  
Content: 92.9 %

Medium: Water  
Content: 3.5 %

Medium: Soil  
Content: 1.9 %

Medium: Sediment  
Content: 1.8 %

Distribution among environmental compartments : Koc: 1.71 - 14.70  
Remarks: Mobile in soils

Remarks: The product is insoluble and floats on water.

**Other adverse effects****Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Toxic to aquatic life with long lasting effects.

**MOBIHEL 3:1 HS FILLER W/W**

Version	Revision Date:	SDS Number:	Date of last issue: 16.11.2023
1.1	22.05.2024	MAT000478435 AU/EN	Date of first issue: 16.11.2023

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

- Waste from residues : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.
- Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

**SECTION 14. TRANSPORT INFORMATION****International Regulations****UNRTDG**

- UN number : UN 1263  
Proper shipping name : PAINT  
Class : 3  
Packing group : III  
Labels : 3  
Environmentally hazardous : no

**IATA-DGR**

- UN/ID No. : UN 1263  
Proper shipping name : Paint  
Class : 3  
Packing group : III  
Labels : Flammable Liquids  
Packing instruction (cargo aircraft) : 366  
Packing instruction (passenger aircraft) : 355

**IMDG-Code**

- UN number : UN 1263  
Proper shipping name : PAINT  
(trizinc bis(orthophosphate), Hydrocarbons, C9 aromatics)  
Class : 3  
Packing group : III  
Labels : 3  
EmS Code : F-E, S-E  
Marine pollutant : yes

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**National Regulations****ADG**

- UN number : UN 1263

**MOBIHEL 3:1 HS FILLER W/W**

Version	Revision Date:	SDS Number:	Date of last issue: 16.11.2023
1.1	22.05.2024	MAT000478435 AU/EN	Date of first issue: 16.11.2023

Proper shipping name : PAINT  
Class : 3  
Packing group : III  
Labels : 3  
Hazchem Code : •3Y  
Environmentally hazardous : no

**Special precautions for user**

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

**SECTION 15. REGULATORY INFORMATION****Safety, health and environmental regulations/legislation specific for the substance or mixture**

Therapeutic Goods (Poisons : Schedule 7  
Standard) Instrument

Prohibition/Licensing Requirements : dibutyltin dilaurate  
Refer to model WHS Act and Regulations for prohibition, authorisation and restricted use.

**SECTION 16: ANY OTHER RELEVANT INFORMATION**

Revision Date : 22.05.2024

Date format : dd.mm.yyyy

**Full text of other abbreviations**

ACGIH : USA. ACGIH Threshold Limit Values (TLV)  
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)  
AU OEL : Australia. Workplace Exposure Standards for Airborne Contaminants.

ACGIH / TWA : 8-hour, time-weighted average  
ACGIH / STEL : Short-term exposure limit  
AU OEL / TWA : Exposure standard - time weighted average  
AU OEL / STEL : Exposure standard - short term exposure limit

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and

**MOBIHEL 3:1 HS FILLER W/W**

Version	Revision Date:	SDS Number:	Date of last issue: 16.11.2023
1.1	22.05.2024	MAT000478435	Date of first issue: 16.11.2023
		AU/EN	

Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.